

Lab - Smoothing

1. Filtering:
 - a. Read an image of your choice.
 - b. Apply salt & pepper noise with density =0.05
 - c. Implement median filtering algorithm using a mask of size 3*3. You can use the given pseudocode.
 - d. Compare your results with python function ***Skimage.filters.median***
 - e. Apply **Gaussian Filtering** to the noisy image with the following conditions:
 - i. Sigma(s) 8,3, 0.2 [Optional: use different lengths. Note: default skimage gaussian function doesn't accept length parameters]
 - ii. After understanding the effect of length and sigma. Choose the best combination that fits your image. Needs Justification.

```
edgex := (window width / 2) rounded down
edgey := (window height / 2) rounded down
for x from edgex to image width – edgex
{
    for y from edgey to image height – edgey
    {
        allocate colorArray[window width][window height]
        for fx from 0 to window width
            for fy from 0 to window height
                colorArray[fx][fy] := inputPixelValue[x + fx - edgex][y + fy - edgey]
        sort all entries in colorArray[][]
        outputPixelValue[x][y] := colorArray[window width / 2][window height / 2]
    }
}
```

Useful New Functions and Attributes

Name	Attribute or Function	Usage
round	Function	
np.zeros	Function	To generate matrix with a given shape all elements with zero values
range	Function	To generate range of indexes from low range to high range with an optional step
skimage.filters.gaussian	Function	To apply gaussian filter on an image.
np.median	Function	To get median value. <i>To get the median value for all the matrix (not for a certain axis), provide parameter axis=None</i>
skimage.filters.median	Function	To apply median filter on an image.

To make the range of a gray-scale image uint8 (from 0 – 255), use `astype(np.uint8)`.