

---

# Layerwise and Dimensionwise Locally Adaptive Method

---

Anonymous Author(s)

Affiliation

Address

email

## Abstract

In the emerging paradigm of Federated Learning (FL), large amount of clients, such as mobile devices, are used to train possibly high-dimensional models on their respective data. Due to the low bandwidth of mobile devices, decentralized optimization methods need to shift the computation burden from those clients to the computation server while preserving *privacy* and reasonable *communication cost*. In this paper, we focus on the training of deep, as in multilayered, neural networks, under the FL settings. We present, FED-LAMB, a novel Federated Learning method based on a *layerwise* and *dimensionwise* updates of the local models, alleviating the nonconvexity and the multilayeredness of the optimization task at hand. We provide a thorough finite-time convergence analysis for FED-LAMB characterizing how fast its gradient decreases. Finally, we provide experimental results under iid and non-iid settings to corroborate not only our theory, but also exhibit the faster convergence of our method, compared to the state-of-the-art.

## 1 Introduction

A growing and important task while learning models on observed data, is the ability to train the latter over a large number of clients which could either be devices or distinct entities. In the paradigm of Federated Learning (FL) [13; 21], the focus of our paper, a central server orchestrates the optimization over those clients under the constraint that the data can neither be centralized nor shared among the clients. Most modern machine learning tasks can be casted as a large finite-sum optimization problem written as:

$$\min_{\theta \in \Theta} \frac{1}{n} \sum_{i=1}^n f_i(\theta) \quad (1)$$

where  $n$  denotes the number of workers,  $f_i$  represents the average loss for worker  $i$  and  $\theta$  the global model parameter taking value in  $\Theta$ , a subset of  $\mathbb{R}^d$ . While this formulation recalls that of distributed optimization, the core principle of FL is different than standard distributed paradigm.

FL currently suffers from two bottlenecks: communication efficiency and privacy. We focus on the former in this paper. While local updates, updates during which each client learn their local models, can reduce drastically the number of communication rounds between the central server and devices, new techniques are still necessary to tackle the challenge of communication due to, e.g., wireless bandwidth. Some quantization [1; 30] or compression [20] methods allow to decrease the number of bits communicated at each round and are efficient methods in a distributed setting. The other approach one can take is to accelerate the local training on each device and thus sending a better local model to the server at each round, thus reducing the number of communication rounds needed to get a well-trained global model.

Under the important setting of heterogenous data, i.e. the data in each device can be distributed according to different distributions, current local optimization algorithms are perfectible. One of the most popular framework for FL is using multiple local Stochastic Gradient Descent (SGD) steps in

each device, sending those local models to the server that computes the average over those received local model parameters and broadcasts it back to the devices. This method is called FEDAVG [21].

In [2], the authors motivate the use of adaptive gradient optimization methods as a better alternative to the standard SGD inner loop in FEDAVG. They propose an adaptive gradient method, namely LOCAL AMSGRAD, with communication cost sublinear in  $T$  that is guaranteed to converge to stationary points in  $\mathcal{O}(\sqrt{d/Tn})$ , where  $T$  is the number of communication rounds,  $d$  is the overall dimension of the problem and  $n$  corresponds to the number of clients available.

Based on recent progress in adaptive methods for accelerating the training procedure, see [31], we propose a variant of LOCAL AMSGRAD integrating dimensionwise and layerwise adaptive learning rate in each device’s local update. Our contributions are as follows:

- We develop a novel optimization algorithm for federated learning, namely FED-LAMB, following a principled layerwise adaptation strategy to accelerate training of deep neural networks. Our method is provably and empirically communication-efficient for compositional structural models.
- We provide a rigorous theoretical understanding of the non asymptotic convergence rate of FED-LAMB. Based on the recent progress on nonconvex stochastic optimization, we derive for a any finite number of rounds performed by our method, a characterization of the rate at which the classical suboptimality condition, *i.e.*, the second order moment of the gradient of the objective function, decreases. Our bound in  $\mathcal{O}\left(\sqrt{\frac{p}{n}} \frac{1}{L\sqrt{R}}\right)$  matches state of the art methods in Federated Learning reaching a sublinear convergence in  $R$ , the total number of rounds.
- We exhibit the advantages of our method to reach similar, or better, test accuracy than baseline methods with less number of communication rounds, on several benchmarks supervised learning methods on both homogeneous and heterogeneous settings.

We establish a literature review of both realms of federated and adaptive learning.

**Adaptive gradient methods.** In recent study on stochastic nonconvex optimization, adaptive methods have proven to be the spearhead in many applications. Those gradient based optimization algorithms alleviate the possibly high nonconvexity of the objective function by adaptively updating each coordinate of their learning rate using past gradients. Most used examples include AMSGRAD [27], ADAM [12], RMSPROP [29], ADADELTA [33], and NADAM [3].

Their popularity and efficiency are due to their great performance at training deep neural networks. They generally combine the idea of adaptivity from ADAGRAD [4; 22], as explained above, and the idea of momentum from NESTEROV’S METHOD [23] or HEAVY BALL method [24] using past gradients. ADAGRAD displays a great edge when the gradient is sparse compared to other classical methods. Its update has a notable feature: it leverages an anisotropic learning rate depending on the magnitude of the gradient for each dimension which helps in exploiting the geometry of the data.

The anisotropic nature of this update represented a real breakthrough in the training of high dimensional and nonconvex loss functions. This adaptive learning rate helps accelerate the convergence when the gradient vector is sparse [4]. Yet, when applying ADAGRAD to train deep neural networks, it is observed that the learning rate might decay too fast, see [12] for more details. Consequently, Kingma and Ba [12] develops ADAM leveraging a moving average of the gradients divided by the square root of the second moment of this moving average (element-wise multiplication). A variant, called AMSGRAD described in [27] ought to fix ADAM failures using a max operator.

A natural extension of AMSGRAD has been developed in [31] specifically for multi layered neural network. A principled layerwise adaptation strategy to accelerate training of deep neural networks using large mini-batches is proposed using either a standard stochastic gradient update or a generalized adaptive method under the setting of a classical single server empirical risk minimization problem. In simple terms, the idea is based on the observation that in a large deep neural network, the magnitude of the gradient might be too small in comparison with the magnitude of the weight for some layers of the model, hence slowing down the overall convergence. As a consequence, layerwise adaptive learning rate is applied, such that in each iteration the model can move sufficiently far. This method empirically speeds up the convergence significantly in classical sequential models and can be provably faster than baseline methods.

**Federated learning.** An extension of the well known parameter server framework, where a model is being trained on several servers in a distributed manner, is called Federated Learning (FL), see [13]. Here, the central server only plays the role of computing power for aggregation and global update of the model. Compared with the distributed learning paradigm, in Federated Learning, the data stored in each worker must not be seen by the central server – preserving privacy is key – and the nature of those workers (e.g., mobile devices), combined with their usually large amount, makes communication between the devices and the central server less appealing – communication cost needs to be controlled. Thus, while traditional distributed gradient methods [25; 16; 34] do not respect those constraints, it has been proposed in [21], an algorithm called Federated Averaging – FED-AVG – extending parallel SGD with local updates performed on each device. In FED-AVG, each worker updates their own model parameters locally using SGD, and the local models are synchronized by periodic averaging on the central parameter server.

## 2 Layerwise and Dimensionwise Adaptive Method

Beforehand, it is important to provide useful and important notations used throughout our paper.

**Notations:** We denote by  $\theta$  the vector of parameters taking values in  $\mathbb{R}^d$ . For each layer  $\ell \in \llbracket L \rrbracket$ , where  $L$  is the total number of layers of the neural networks, and each coordinate  $j \in \llbracket p_\ell \rrbracket$  where  $p_\ell$  is the dimension per layer  $\ell$ , we note  $\theta_{r,i}^{\ell,t}$  its value at round  $r$ , local iteration  $t$  and for worker  $i$ . The gradient of  $f$  with respect to  $\theta^\ell$  is denoted by  $\nabla_\ell f(\theta)$ . The smoothness per layer is denoted by  $L_\ell$  for each layer  $\ell \in \llbracket L \rrbracket$ . We note for each communication  $r > 0$ , the set of randomly drawn devices  $D^r$  performing local updates.

### 2.1 AMSGrad, Local AMSGrad and Periodic Averaging

Under our Federated setting, we stress on the important of reducing the communication cost at each round between the central server, used mainly for aggregation purposes, and the many clients used for gradient computation and local updates. Using Periodic Averaging after few local epochs, updating local models on each device, as developed in [21] is the gold standard for achieving such communication cost reduction. Intuitively, one rather shift the computation burden from the many clients to the central server as much as possible. This allows for fewer local epochs and a better global model, from a loss minimization (or model fitting) perspective. The premises of that new paradigm are SGD updates performed locally on each device then averaged periodically, see [13; 35]. The heuristic efficiency of local updates using SGD and periodic averaging has been studied in [28; 32] and shown to reach a similar sublinear convergence rate as in the standard distributed optimization settings. Then, with the growing need of training far more complex models, such as deep neural networks, several efficient methods, built upon adaptive gradient algorithms, such as Local AMSGrad in [2], extended both empirically and theoretically, the benefits of performing local updates coupled with periodic averaging.

### 2.2 Layerwise and Dimensionwise Learning with Periodic Averaging

Recall that our original problem is the following optimization task  $\min_{\theta \in \Theta} \frac{1}{n} \sum_{i=1}^n f_i(\theta)$  where  $f_i(\theta)$  is the loss function associated to the client  $i \in \llbracket n \rrbracket$  and is parameterized, in our paper, by a deep neural network. The multilayer and nonconvex nature of the loss function imply having recourse to particular optimization methods in order to efficiently train our model. Besides, the distributed and clients low bandwidth constraints are strong motivations for improving existing methods for (1).

Based on the periodic averaging and local AMSGrad algorithms, presented prior, we propose a layerwise and dimensionwise local AMS algorithm detailed in Algorithm 1, which is a natural adaptation of the vanilla AMSGrad method, for *multilayer* neural networks under the *federated* setting. In particular, while Line 8 and Line 10 corresponds to the standard approximation of the first and second moments, via the smooth updates allowed by the tuning parameters  $\beta_1$  and  $\beta_2$  respectively and that both Line 9 and Line 11 are correct the biases of those estimates, the final local update in Line 13 is novel and corresponds to the specialization per layer of our federated method. Note that a scaling factor is applied to the learning rate  $\alpha_r$  at each round  $r > 0$  via the quantity  $\phi(\|\theta_{r,i}^{\ell,t-1}\|)$  depending on the dimensionwise and layerwise quantity computed in Line 12. This function is user designed and can be, for instance, set to the identity function. In other words, we normalize the gradient in each layer according to the magnitude of the layer’s weight.

141 The adaptivity of our federated learning method is thus manifold. There occurs a per dimension  
 142 normalization with respect to the square root of the second moment used in adaptive gradient methods  
 143 and a layerwise normalization obtained via the final local update (Line 13).

---

**Algorithm 1** FED-LAMB for Federated Learning

---

1: **Input:** parameter  $0 < \beta_1, \beta_2 < 1$ , and learning rate  $\alpha_t$ , weight decaying parameter  $\lambda \in ]0, 1[$ .  
 2: **Init:**  $\theta_0 \in \Theta \subseteq \mathbb{R}^d$ , as the global model and  $\hat{v}_0 = v_0 = \epsilon \mathbf{1} \in \mathbb{R}^d$  and  $\bar{\theta}_0 = \frac{1}{n} \sum_{i=1}^n \theta_0$ .  
 3: **for**  $r = 1$  to  $R$  **do**  
 4:   **for** parallel for device  $i \in D^r$  **do**  
 5:     Set  $\theta_{r,i}^0 = \bar{\theta}_{r-1}$ .  
 6:     Compute stochastic gradient  $g_{r,i}$  at  $\theta_{r,i}^0$ .  
 7:     **for**  $t = 1$  to  $T$  **do**  
 8:        $m_{r,i}^t = \beta_1 m_{r-1,i}^{t-1} + (1 - \beta_1) g_{r,i}$  and  $m_{r,i}^t = m_{r,i}^t / (1 - \beta_1^t)$ .  
 9:        $v_{r,i}^t = \beta_2 v_{r-1,i}^{t-1} + (1 - \beta_2) g_{r,i}^2$  and  $v_{r,i}^t = v_{r,i}^t / (1 - \beta_2^t)$ .  
 10:       Compute the ratio  $p_{r,i}^t = m_{r,i}^t / (\sqrt{v_{r,i}^t} + \epsilon)$ .  
 11:       Update local model for each layer  $\ell \in \llbracket L \rrbracket$ :  
       
$$\theta_{r,i}^{\ell,t} = \theta_{r,i}^{\ell,t-1} - \alpha_r \phi(\|\theta_{r,i}^{\ell,t-1}\|)(p_{r,i}^{\ell,t} + \lambda \theta_{r,i}^{\ell,t-1}) / \|p_{r,i}^{\ell,t} + \lambda \theta_{r,i}^{\ell,t-1}\|$$
  
 12:     **end for**  
 13:     Devices send  $\theta_{r,i}^T = [\theta_{r,i}^{\ell,T}]_{\ell=1}^L$  and  $v_{r,i}^T$  to server.  
 14:   **end for**  
 15:   Server computes averages of the local models  $\bar{\theta}_r = [\bar{\theta}_r^{\ell}]_{\ell=1}^L = [\frac{1}{n} \sum_{i=1}^n \theta_{r,i}^{\ell,T}]_{\ell=1}^L$  and  $\hat{v}_{r+1} = \max(\hat{v}_r, \frac{1}{n} \sum_{i=1}^n v_{r,i}^T)$  and send them back to the devices.  
 16: **end for**

---

### 144 3 On The Convergence of FED-LAMB

145 We develop in this section, the theoretical analysis of Algorithm 1. Based on classical result for  
 146 stochastic nonconvex optimization, we provide a collection of results that aims to providing a better  
 147 understanding of the convergence behavior of our distributed optimization method under the federated  
 148 learning framework. The main challenges we ought to overcome are manifold (i) The large amount of  
 149 decentralized workers working solely on their own data stored locally. (ii) A periodic averaging occurs  
 150 on the central server pushing each of those clients to send local models after some local iterations. (iii)  
 151 Each client computes a backpropagation of the main model, *i.e.*, the deep neural network, and then  
 152 updates its local version of the model via an adaptive gradient method: the distinctiveness being that  
 153 those updates are done *dimensionwise* and *layerwise*. Our analysis encompasses the consideration of  
 154 those challenges and leads to a informative convergence rates depending on the quantities of interest  
 155 in our problem: the number of layers of the DNN, the number of communications rounds and the  
 156 number of clients used under our federated settings.

#### 157 3.1 Finite Time Analysis of FED-LAMB

158 In the sequel, the analysis of our scheme we provide is *global*, in the sense that it does not depend on  
 159 the initialization of our algorithm, and *finite-time*, meaning that it is true for any arbitrary number of  
 160 communication rounds, in particular small ones. In the particular context of nonconvex stochastic  
 161 optimization for distributed clients, we assume the following:

162 **H1.** (*Smoothness per layer*) For  $i \in \llbracket n \rrbracket$  and  $\ell \in \llbracket L \rrbracket$ :  $\|\nabla f_i(\theta^\ell) - \nabla f_i(\vartheta^\ell)\| \leq L_\ell \|\theta^\ell - \vartheta^\ell\|$ .

163 We add some classical assumption in the unbiased stochastic optimization realm, on the gradient of  
 164 the objective function:

165 **H2.** (*Unbiased and Bounded gradient*) The stochastic gradient is unbiased for any iteration  $r > 0$ :  
 166  $\mathbb{E}[g_r] = \nabla f(\theta_r)$  and is bounded from above, *i.e.*,  $\|g_t\| \leq M$ .

167 **H3.** (*Bounded variance*) The variance of the stochastic gradient is bounded for any iteration  $r > 0$   
 168 and any dimension  $j \in \llbracket d \rrbracket$ :  $\mathbb{E}[(g_r^j - \nabla f(\theta_r)^j)^2] < \sigma^2$ .

169 **H4. (Bounded Scale)** For any value  $a \in \mathbb{R}_+^*$ , there exists strictly positive constants such that  
 170  $\phi_m \leq \phi(a) \leq \phi_M$ .

171 We now state our main result regarding the non asymptotic convergence analysis of our Algorithm 1:

172 **Theorem 1.** Assume **H1-H4**. Consider  $\{\bar{\theta}_r\}_{r>0}$ , the sequence of parameters obtained via Algo-  
 173 rithm 1 with a decreasing  $\text{lr } \alpha_r$ . Then, if  $T = 1$  and  $\lambda = 0$ :

$$\frac{1}{R} \sum_{r=1}^R \mathbb{E} \left[ \left\| \frac{\nabla f(\bar{\theta}_r)}{\sqrt{v_r^t}} \right\|^2 \right] \leq \sqrt{\frac{M^2 p}{n} \frac{\mathbb{E}[f(\bar{\theta}_1)] - f^*}{\mathbb{L} \alpha_r R}} + \frac{\phi_M}{R} \left[ \frac{(1 - \beta_2) \bar{L} \alpha_r^2 M^2 \phi_M p}{v_0} + \frac{\sigma^2}{n} \sqrt{\frac{1 - \beta_2}{M^2 p}} \right] \quad (2)$$

174 where  $\bar{L} = \sum_{\ell=1}^L L_\ell$  is the sum of all smoothness constants,  $\mathbb{L}$  is the total number of layers and  
 175  $f^* := \min_{\theta \in \Theta} f(\theta)$ .

### 176 3.2 Important Intermediary Lemmas

177 Two important Lemmas are required in the proof of the Theorem above. We also report the complete  
 178 proof of our bound in the Appendix of this paper.

179 The first result gives a characterization of the gap between the averaged model, that is computed by  
 180 the central server in a periodic manner, and each of the local models stored in each client  $i \in \llbracket n \rrbracket$ .

181 **Lemma 1.** Consider  $\{\bar{\theta}_r\}_{r>0}$ , the sequence of parameters obtained running Algorithm 1. Then for  
 182  $i \in \llbracket n \rrbracket$  and  $r > 0$ :

$$\|\bar{\theta}_r - \theta_{r,i}\|^2 \leq \alpha_r^2 M^2 \phi_M^2 \frac{(1 - \beta_2)p}{v_0} \quad (3)$$

183 where  $\phi_M$  is defined in H4 and  $p$  is the total number of dimensions  $p = \sum_{\ell=1}^L p_\ell$ .

184 The gap is provably bounded by some quantities of interest such as the total dimension of the  
 185 multilayered model  $p$ , the learning rate and the assumed upper bound of the gradient, see H2.

186 Then, the following Lemma allows us to convert the suboptimality condition  $\left\| \frac{\bar{\nabla} f(\bar{\theta}_r)}{\sqrt{v_r^t}} \right\|$  to the desired

187 one which is  $\left\| \frac{\nabla f(\bar{\theta}_r)}{\sqrt{v_r^t}} \right\|$ . Note that the end goal is to characterize how fast the gradient of the  
 188 averaged/global parameter  $\bar{\theta}_r$  goes to zero, and not the averaged gradient.

189 **Lemma 2.** Consider  $\{\bar{\theta}_r\}_{r>0}$ , the sequence of parameters obtained running Algorithm 1. Then for  
 190  $r > 0$ :

$$\left\| \frac{\bar{\nabla} f(\bar{\theta}_r)}{\sqrt{v_r^t}} \right\|^2 \geq \frac{1}{2} \left\| \frac{\nabla f(\bar{\theta}_r)}{\sqrt{v_r^t}} \right\|^2 - \bar{L} \alpha^2 M^2 \phi_M^2 \frac{(1 - \beta_2)p}{v_0} \quad (4)$$

191 where  $M$  is defined in H2,  $p = \sum_{\ell=1}^L p_\ell$  and  $\phi_M$  is defined in H4.

192 We focus in the next subsection on two particular papers of utmost interest for our contribution.

### 193 3.3 Comparison with LAMB and Local-AMS

194 We dedicate the following paragraph to a discussion on the bound derived above in comparison with  
 195 known results in the literature.

196 **LAMB bound in You et al. [31]:** We first start our discussion with the comparison of con-  
 197 vergence rate of FED-LAMB with that of LAMB, Theorem 3 in [31]. The convergence rates of  
 198 FED-LAMB and LAMB differ in two ways: (i) the suboptimality, or convergence criterion, used

199 here is  $\frac{1}{R} \sum_{r=1}^R \mathbb{E} \left[ \left\| \frac{\nabla f(\bar{\theta}_r)}{\sqrt{v_r^t}} \right\|^2 \right]$  for a total number of rounds  $R$  as opposed to  $\mathbb{E} [\|\nabla f(\theta_{\mathcal{R}})\|^2]$  for  
 200 some random termination round  $\mathcal{R}$  uniformly drawn from  $\llbracket R \rrbracket$ . First, note that the characterization

is given at the averaged parameters noted  $\overline{\theta_R}$  due to our distributed settings. It is thus natural to consider the evolution of our objective function, precisely its gradient, evaluated at some global model values –as opposed to the outcome of a single step drift in the central server paradigm. Besides, for ease of interpretation, the LHS of (2) is summed over all rounds instead of a fictive random termination point. A simple calculation would lead to such characterization, found in several nonconvex stochastic optimization paper such as [5]. (ii) Assuming that the convergence criterion in both Theorems is of similar order (which happens for a large enough number of rounds), convergence rate of FED-LAMB displays a similar  $\mathcal{O}(\frac{1}{R})$  behaviour for the initialization term, meaning that, despite the distributed (federated) settings, our dimensionwise and layerwise method benefits from the double adaptivity phenomenon explained above and exhibited in the LAMB method of [31], performed under a central server setting.

**Local-AMS bound in Chen et al. [2]:** We now discuss the similarities and differences between the distributed adaptive method developed in [2] and named local-AMS, and our *deep federated* method, namely FED-LAMB. We first recall their main result:

**Theorem 2** (Theorem 5.1 in [2]). *Under some regularity conditions on the local losses and similar arguments as ours, LOCAL-AMS reaches a stationary point with the following rate:*

$$\frac{1}{R} \sum_{r=1}^R \mathbb{E} \left[ \left\| \frac{\nabla f(\bar{\theta}_r)}{\sqrt{v_r^t}} \right\|^2 \right] \leq 8\sqrt{\frac{p}{Rn}} [f(\bar{\theta}_1) - \mathbb{E}[f(\bar{\theta}_{R+1})]] + 8L_s \sqrt{\frac{p}{Rn}} \frac{\sigma^2}{\epsilon} + cst. \quad (5)$$

where  $\epsilon$  corresponds to their initialization of the vector  $\hat{v}_0$  and  $L_s$  is the sum of the local smoothness constants.

The first two terms of their results and ours, standard in convergence analysis, displays a strong dependence of the convergence rate on the initialization, which tends to be forgotten, and the bounded variance assumption of the stochastic gradient, see H3. The acceleration of our layerwise scheme is exhibited in the dependence on  $\frac{1}{R}$  in those two terms, while results in [2] are of order  $\frac{1}{\sqrt{R}}$ . Note that the boundedness assumption is done on each dimension in H3 and leads to a manifestation of the term  $\sqrt{p}$  in both rates. This can be handled for simplicity and clarity of the results when H3 is assumed globally. It is important to note that their rate include an analysis with respect to the number of local updates, noted  $T$  in this paper. While our result is derived for a single local update  $T = 1$ , we acknowledge that exhibiting a dependency on  $T$  can be interesting, particularly in order to see the impact of several local updates which are, in practice, in different directions –as a byproduct of heterogeneous local training samples. We leave this investigation to future work.

In light of the prior remarks, we give a simple variant of Theorem 1 as Corollary 1 where we assume an upperbound on the norm of the second moment approximate  $\sqrt{v_r^t}$ :

**H5.** For  $t > 0$  and  $r > 0$ , there exists some constant such that  $\|\sqrt{v_r^t}\| \leq V^2$ .

**Corollary 1.** Assume H1-H4. Consider  $\{\bar{\theta}_r\}_{r>0}$ , the sequence of parameters obtained running Algorithm 1 and set  $\alpha_r = \mathcal{O}(\frac{1}{L\sqrt{R}})$ . Then, if the number of local epochs is set to  $T = 1$ ,  $\lambda = 0$  we have, under H5:

$$\frac{1}{R} \mathbb{E} \left[ \|\nabla f(\bar{\theta}_R)\|^2 \right] \leq \mathcal{O} \left( \sqrt{\frac{p}{n}} \frac{1}{L\sqrt{R}} \right) \quad (6)$$

We now discuss our bound regarding several aspects in order to gain understanding of the advantages of our method:

**Communication Complexity:** The (sublinear) dependence on the number of communication rounds of our bound matches that of most recent methods in Federated Learning, see [11] developing SCAFFOLD, a solution to the problem posed by heterogeneity of the data in each client, and of [26], adapting state of the art method in optimization, here ADAM, under the federated setting. Yet, contrary to SCAFFOLD, our method only sends bits once per communication round while SCAFFOLD needs to send two vectors, including an additional control variate term from the clients to the central server. Novelty in our bound occurs considering the sublinear dependence on the number of layer  $L$  and the dependence on the total number of dimension of our problem  $p$ . For the latter, the dependency can be simplified with stronger assumption on the control of the variance of the stochastic gradient. For the former,






Figure 1: **Top Row:** Test accuracy on MNIST+MLP, with non-iid data distribution. **Bottom Row:** Test accuracy on MNIST+CNN, with non-iid data distribution. **Left panel:** 1 local epoch. **Right panel:** 5 local epochs.

**Homogeneous and Heterogeneous Data:** A common assumption regarding the stochastic gradient, and its variance, considers an upper-bound of the global variance, in the sense that it applies to both the aggregated objective function (1) and each of its local component. An alternative theoretical approach is to set apart a local variance for each local loss, and global variance for their sum, see [2] for instance. Heterogeneity is of utmost importance in FL since client may store radically different data points in local devices. Existing methods can lead to poor convergence as detailed in [18; 19]. Improvements are proposed through the use of gradient tracking techniques performed locally as seen in [6; 9; 11].

**Dependence on the dimension  $p$ :** The  $\sqrt{p}$  term appearing in our bound is due to the assumption on coordinate-wise bounded variance. One may instead assume a bounded total variance to remove this term. In practice, the dependence on the overall size of the vectors being transmitted back and forth from the central to the devices can be improved in various ways. Indeed, recent efficient techniques aim at reducing the number of bits communicated at each round through sketches or compression techniques, see for instance [7; 10; 17] to name a few. This can be a great addition to FED-LAMB, and is naturally compatible, but is not the main focus of our contribution.

## 4 Numerical Experiments

In this section, we conduct numerical experiments on various datasets and network architectures to testify the effectiveness of our proposed method in practice. Our main objective is to validate the benefit of dimensionwise adaptive learning when integrated with adaptive Fed-AMS. We observe in the sequel that our method empirically confirms its edge in terms of convergence speed. Basically, our proposed method reduces the number of rounds and thus the communication cost required to achieve similar stationary points than baseline methods.

**Settings.** In our experiment, we will evaluate three federated learning algorithms: 1) Fed-SGD, 2) Fed-AMS and 3) our proposed Fed-LAMB (Algorithm 1), where the first two serve as the baseline methods. For adaptive methods 2) and 3), we set  $\beta_1 = 0.9$ ,  $\beta_2 = 0.999$  as default and recommended [27]. Regarding federated learning environment, we use 50 local workers with 0.5 participation rate. That means, we randomly pick half of the workers to be active for training in each round. To best accord with real scenarios where the local training batch size is usually limited, we set a relatively small local update batch size as 32. In each round, the training samples are allocated to the active devices, and one local epoch is finished after all the local devices run one epoch over their received samples by batch training. We test different number of local epochs in our experiments. For each dataset and number of local epochs, we tune the constant learning rate  $\alpha$  for each algorithm over a fine grid in logarithm scale. For Fed-LAMB, the parameter  $\lambda$  in Algorithm 1 controlling the overall scale of the layerwise gradients is tuned from  $\{0, 0.01, 0.1\}$ . For each experiment, we use the identity function for  $\phi(\cdot)$ . For each run, we take the model performance with the best  $\alpha$  and  $\lambda$ . The reported results are averaged over three independent runs, each with same initialization for every method.

**Models.** We test the performance of different federated learning algorithms on MNIST [15] and CIFAR10 [14] image classification datasets. For MNIST, we apply 1) a simple multilayer perceptron (MLP), which has one hidden layer containing 200 cells with dropout; 2) Convolutional Neural Network (CNN), which has two max-pooled convolutional layers followed by a dropout layer and two fully-connected layers with 320 and 50 cells respectively. For CIFAR10, we implement: 1) a CNN with three convolutional layers followed by two fully-connected layers, and 2) a ResNet-9 model proposed by [8].




Figure 2: Test accuracy on CIFAR+CNN and CIFAR+ResNet, with iid data distribution for 50 clients, 1 and 3 local epoch respectively. **Last two quadrants:** CIFAR+ResNet, with non-iid data distribution for 50 clients, 1 and 3 local epoch respectively.

**Results.** In Figure 1, we start by presenting the test accuracy on MNIST dataset trained by MLP. We compare each method under the heterogeneous (non-iid) data distribution settings, where each device only receives samples of one digit (out of ten). This is known to be the scenario where federated learning is harder to generalize well, see [21]. First of all, we observe that our proposed Fed-LAMB outperforms Fed-AMS and Fed-SGD with both 1 and 5 local epochs, illustrating its improvement over baseline federated methods. In addition, though it is not the main comparison of this paper, Fed-SGD slightly generalizes better than Fed-AMS, which means that SGD might be sufficient for this rather simple model. Yet, Fed-LAMB overachieves both methods on this task in terms of test accuracies. Similar comparison can be drawn with respect to the losses.

We also evaluate various algorithms on larger models. Since Fed-LAMB is specifically designed for multi-layer deep learning networks, we expect it to show more substantial advantage over Fed-AMS on larger network architectures, since we recall that in Corollary 1, the convergence bound decreases with larger number of layers  $L$ . In Figure 1, we present the results on MNIST with CNN, under non-iid data distribution. Firstly, we see that Fed-LAMB outperforms Fed-AMS in both cases. The advantage is in particular significant with 1 local epoch, where Fed-SGD generalizes poorly. Importantly, we would like to address the acceleration effect of Fed-LAMB, in the early stage of training. We observe that Fed-LAMB converges faster than the vanilla Fed-AMS at first few communication rounds, in both cases. As a side note, the poor performance of Fed-SGD is, to some extent, consistent with prior literature and practical numerical experiments showing that adaptive gradient methods usually perform better than simple SGD in training large deep learning models. We refer the readers to a collection of prior studies such as [2; 26].

In Figure 2, we report the test accuracies of a Convolutional Neural Network trained on CIFAR-10 dataset, where the data is iid allocated among clients. When we run 1 local epoch per device, we observe a clear advantage of Fed-LAMB over Fed-AMS on both test accuracy and convergence speed. Note that Fed-SGD again fails to achieve close performance as those two adaptive gradient methods. Increasing the number of local iterations in each device per communication round leads to similar observations: our newly introduced method, namely Fed-LAMB, converges the fastest, with similar generalization error as Fed-AMS.

Lastly, we test the algorithms on CIFAR-10 using a Residual Neural Network, the ResNet-9 model. We again observe in Figure 2 that Fed-LAMB improves the performance of vanilla local AMS method under various settings regarding the number clients and number local iterations, corroborating the solid improvement brought by our layerwise adaptive strategy. We see remarkable acceleration in the accuracy curve of Fed-LAMB, especially with 50 clients and 1 local epoch (left bottom). In



324 addition, Fed-AMS also compares favorably with Fed-SGD, though their performances are close on  
325 this specific task.

## 326 5 Conclusion

327 We study in this contribution a doubly adaptive method in the particular framework of federated  
328 learning. Built upon the success of periodic averaging, and of state-of-the-art adaptive gradient  
329 methods for single server nonconvex stochastic optimization, we derive FED-LAMB, a distributed  
330 AMSGrad method that performs local updates on each worker and periodically averages local models.  
331 Besides, when the trained model is a deep neural network, a core component of our method, namely  
332 FED-LAMB, is a *layerwise* update of each local model. The main contribution of our paper is  
333 thus a Federated Learning optimization algorithm that leverages a double level of adaptivity: the  
334 first one stemming from a *dimensionwise* adaptivity of adaptive gradient methods, extended to their  
335 distributed (and local) counterpart, the second one is due to a *layerwise* adaptivity making use of  
336 the particular compositionality of the considered model. Proved convergence guarantees of our  
337 scheme are provided in our contribution and exhibits a sublinear dependence on the total number of  
338 communications rounds, the number of clients and the number of layers of the model. The multiple  
339 benefits of periodic averaging, adaptive optimization methods and layerwise updates are displayed  
340 in our bounds. We empirically confirm the advantage of our algorithm over baselines methods on a  
341 panel of numerical experiments.

## References

- [1] Dan Alistarh, Demjan Grubic, Jerry Li, Ryota Tomioka, and Milan Vojnovic. Qsgd: Communication-efficient sgd via gradient quantization and encoding. In *Advances in Neural Information Processing Systems*, pages 1709–1720, 2017.
- [2] Xiangyi Chen, Xiaoyun Li, and Ping Li. Toward communication efficient adaptive gradient method. In *ACM-IMS Foundations of Data Science Conference (FODS)*, Seattle, WA, 2020.
- [3] Timothy Dozat. Incorporating nesterov momentum into adam. *ICLR (Workshop Track)*, 2016.
- [4] John Duchi, Elad Hazan, and Yoram Singer. Adaptive subgradient methods for online learning and stochastic optimization. *Journal of Machine Learning Research (JMLR)*, 2011.
- [5] Saeed Ghadimi and Guanghui Lan. Stochastic first-and zeroth-order methods for nonconvex stochastic programming. *SIAM Journal on Optimization*, 23(4):2341–2368, 2013.
- [6] Farzin Haddadpour, Mohammad Mahdi Kamani, Aryan Mokhtari, and Mehrdad Mahdavi. Federated learning with compression: Unified analysis and sharp guarantees. *arXiv preprint arXiv:2007.01154*, 2020.
- [7] Farzin Haddadpour, Belhal Karimi, Ping Li, and Xiaoyun Li. Fedsketch: Communication-efficient and private federated learning via sketching. *arXiv preprint arXiv:2008.04975*, 2020.
- [8] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *2016 IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2016, Las Vegas, NV, USA, June 27-30, 2016*, pages 770–778. IEEE Computer Society, 2016.
- [9] Samuel Horváth, Dmitry Kovalev, Konstantin Mishchenko, Sebastian Stich, and Peter Richtárik. Stochastic distributed learning with gradient quantization and variance reduction. *arXiv preprint arXiv:1904.05115*, 2019.
- [10] Nikita Ivkin, Daniel Rothchild, Enayat Ullah, Vladimir Braverman, Ion Stoica, and Raman Arora. Communication-efficient distributed SGD with sketching. In *Advances in Neural Information Processing Systems (NeurIPS)*, pages 13144–13154, Vancouver, Canada, 2019.
- [11] Sai Praneeth Karimireddy, Satyen Kale, Mehryar Mohri, Sashank J Reddi, Sebastian U Stich, and Ananda Theertha Suresh. Scaffold: Stochastic controlled averaging for on-device federated learning. *arXiv preprint arXiv:1910.06378*, 2019.
- [12] Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *ICLR*, 2015.
- [13] Jakub Konečný, H Brendan McMahan, Felix X Yu, Peter Richtárik, Ananda Theertha Suresh, and Dave Bacon. Federated learning: Strategies for improving communication efficiency. *arXiv preprint arXiv:1610.05492*, 2016.
- [14] A. Krizhevsky and G. Hinton. Learning multiple layers of features from tiny images. *Master’s thesis, Department of Computer Science, University of Toronto*, 2009.
- [15] Yann LeCun. The mnist database of handwritten digits. <http://yann.lecun.com/exdb/mnist/>, 1998.
- [16] Mu Li, David G Andersen, Jun Woo Park, Alexander J Smola, Amr Ahmed, Vanja Josifovski, James Long, Eugene J Shekita, and Bor-Yiing Su. Scaling distributed machine learning with the parameter server. In *11th {USENIX} Symposium on Operating Systems Design and Implementation ({OSDI} 14)*, pages 583–598, 2014.
- [17] Tian Li, Zaoxing Liu, Vyas Sekar, and Virginia Smith. Privacy for free: Communication-efficient learning with differential privacy using sketches. *arXiv preprint arXiv:1911.00972*, 2019.
- [18] Tian Li, Anit Kumar Sahu, Ameet Talwalkar, and Virginia Smith. Federated learning: Challenges, methods, and future directions. *IEEE Signal Process. Mag.*, 37(3):50–60, 2020.

- [19] Xianfeng Liang, Shuheng Shen, Jingchang Liu, Zhen Pan, Enhong Chen, and Yifei Cheng. Variance reduced local sgd with lower communication complexity. *arXiv preprint arXiv:1912.12844*, 2019.
- [20] Yujun Lin, Song Han, Huizi Mao, Yu Wang, and William J Dally. Deep gradient compression: Reducing the communication bandwidth for distributed training. *arXiv preprint arXiv:1712.01887*, 2017.
- [21] Brendan McMahan, Eider Moore, Daniel Ramage, Seth Hampson, and Blaise Aguera y Arcas. Communication-efficient learning of deep networks from decentralized data. In *Artificial Intelligence and Statistics*, pages 1273–1282. PMLR, 2017.
- [22] H. Brendan McMahan and Matthew J. Streeter. Adaptive bound optimization for online convex optimization. *COLT*, 2010.
- [23] Yurii Nesterov. Introductory lectures on convex optimization: A basic course. *Springer*, 2004.
- [24] B. T. Polyak. Some methods of speeding up the convergence of iteration methods. *Mathematics and Mathematical Physics*, 1964.
- [25] Benjamin Recht, Christopher Re, Stephen Wright, and Feng Niu. Hogwild!: A lock-free approach to parallelizing stochastic gradient descent. *Advances in neural information processing systems*, 24:693–701, 2011.
- [26] Sashank Reddi, Zachary Charles, Manzil Zaheer, Zachary Garrett, Keith Rush, Jakub Konečný, Sanjiv Kumar, and H Brendan McMahan. Adaptive federated optimization. *arXiv preprint arXiv:2003.00295*, 2020.
- [27] Sashank J. Reddi, Satyen Kale, and Sanjiv Kumar. On the convergence of adam and beyond. *ICLR*, 2018.
- [28] Sebastian U Stich. Local sgd converges fast and communicates little. *arXiv preprint arXiv:1805.09767*, 2018.
- [29] T. Tieleman and G. Hinton. Rmsprop: Divide the gradient by a running average of its recent magnitude. *COURSERA: Neural Networks for Machine Learning*, 2012.
- [30] Jianqiao Wangni, Jialei Wang, Ji Liu, and Tong Zhang. Gradient sparsification for communication-efficient distributed optimization. In *Advances in Neural Information Processing Systems*, pages 1299–1309, 2018.
- [31] Yang You, Jing Li, Sashank Reddi, Jonathan Hseu, Sanjiv Kumar, Srinadh Bhojanapalli, Xiaodan Song, James Demmel, Kurt Keutzer, and Cho-Jui Hsieh. Large batch optimization for deep learning: Training bert in 76 minutes. *arXiv preprint arXiv:1904.00962*, 2019.
- [32] Hao Yu, Rong Jin, and Sen Yang. On the linear speedup analysis of communication efficient momentum sgd for distributed non-convex optimization. *arXiv preprint arXiv:1905.03817*, 2019.
- [33] Matthew D. Zeiler. Adadelta: An adaptive learning rate method. *arXiv:1212.5701*, 2012.
- [34] Weijie Zhao, Deping Xie, Ronglai Jia, Yulei Qian, Ruiquan Ding, Mingming Sun, and Ping Li. Distributed hierarchical gpu parameter server for massive scale deep learning ads systems. *arXiv preprint arXiv:2003.05622*, 2020.
- [35] Fan Zhou and Guojing Cong. On the convergence properties of a  $k$ -step averaging stochastic gradient descent algorithm for nonconvex optimization. *arXiv preprint arXiv:1708.01012*, 2017.

## Checklist

### 1. For all authors...

- (a) Do the main claims made in the abstract and introduction accurately reflect the paper's contributions and scope? [Yes]
- (b) Did you describe the limitations of your work? [Yes]
- (c) Did you discuss any potential negative societal impacts of your work? [N/A]
- (d) Have you read the ethics review guidelines and ensured that your paper conforms to them? [Yes]

### 2. If you are including theoretical results...

- (a) Did you state the full set of assumptions of all theoretical results? [Yes] See Section 3
- (b) Did you include complete proofs of all theoretical results? [Yes] See Supplementary Material

### 3. If you ran experiments...

- (a) Did you include the code, data, and instructions needed to reproduce the main experimental results (either in the supplemental material or as a URL)? [Yes] Instructions and hyperparameters are given in Section 4
- (b) Did you specify all the training details (e.g., data splits, hyperparameters, how they were chosen)? [Yes] Settings for MNIST and CIFAR are standard
- (c) Did you report error bars (e.g., with respect to the random seed after running experiments multiple times)? [Yes] Results curves are averaged over 5 runs
- (d) Did you include the total amount of compute and the type of resources used (e.g., type of GPUs, internal cluster, or cloud provider)? [N/A]

### 4. If you are using existing assets (e.g., code, data, models) or curating/releasing new assets...

- (a) If your work uses existing assets, did you cite the creators? [Yes]
- (b) Did you mention the license of the assets? [No]
- (c) Did you include any new assets either in the supplemental material or as a URL? [No]
- (d) Did you discuss whether and how consent was obtained from people whose data you're using/curating? [N/A] Data is public
- (e) Did you discuss whether the data you are using/curating contains personally identifiable information or offensive content? [N/A]

### 5. If you used crowdsourcing or conducted research with human subjects...

- (a) Did you include the full text of instructions given to participants and screenshots, if applicable? [N/A]
- (b) Did you describe any potential participant risks, with links to Institutional Review Board (IRB) approvals, if applicable? [N/A]
- (c) Did you include the estimated hourly wage paid to participants and the total amount spent on participant compensation? [N/A]

465 We first recall in Table 1 some important notations that will be used in our following analysis.

$R, T$	$\triangleq$	Number of communications rounds and local iterations (resp.)
$n, D, i$	$\triangleq$	Total number of clients, portion sampled uniformly and client index
$L, \ell$	$\triangleq$	Total number of layers in the DNN and its index
$\phi(\cdot)$	$\triangleq$	Scaling factor in FED-LAMBUpdate
$\bar{\theta}$	$\triangleq$	Global model (after periodic averaging)
$p_{r,i}^t$	$\triangleq$	ratio computed at round $r$ , local iteration $t$ and for device $i$ . $p_{r,i}^{\ell,t}$ denotes its component at layer $\ell$

Table 1: Summary of notations used in the paper.

## 466 A Theoretical Analysis

467 We first provide the proofs for the theoretical results of the main paper, including the intermediary  
 468 Lemmas and the main convergence result, Theorem 1. Then, we provide the extension of this result  
 469 to the setting of multiple local updates in Section A.4.

### 470 A.1 Intermediary Lemmas

471 **Lemma.** Consider  $\{\bar{\theta}_r\}_{r>0}$ , the sequence of parameters obtained running Algorithm 1. Then for  
 472  $i \in \llbracket n \rrbracket$ :

$$\|\bar{\theta}_r - \theta_{r,i}\|^2 \leq \alpha^2 M^2 \phi_M^2 \frac{(1 - \beta_2)p}{v_0},$$

473 where  $\phi_M$  is defined in H4 and  $p$  is the total number of dimensions  $p = \sum_{\ell=1}^L p_\ell$ .

474 *Proof.* Assuming the simplest case when  $T = 1$ , i.e. one local iteration, then by construction of  
 475 Algorithm 1, we have for all  $\ell \in \llbracket L \rrbracket$ ,  $i \in \llbracket n \rrbracket$  and  $r > 0$ :

$$\theta_{r,i}^\ell = \bar{\theta}_r^\ell - \alpha \phi(\|\theta_{r,i}^{\ell,t-1}\|) p_{r,i}^j / \|p_{r,i}^\ell\| = \bar{\theta}_r^\ell - \alpha \phi(\|\theta_{r,i}^{\ell,t-1}\|) \frac{m_{r,i}^t}{\sqrt{v_r^t}} \frac{1}{\|p_{r,i}^\ell\|}$$

476 leading to

$$\begin{aligned} \|\bar{\theta}_r - \theta_{r,i}\|^2 &= \sum_{\ell=1}^L \left\langle \bar{\theta}_r^\ell - \theta_{r,i}^\ell \mid \bar{\theta}_r^\ell - \theta_{r,i}^\ell \right\rangle \\ &\leq \alpha^2 M^2 \phi_M^2 \frac{(1 - \beta_2)p}{v_0}, \end{aligned}$$

477 which concludes the proof. □

478 **Lemma.** Consider  $\{\bar{\theta}_r\}_{r>0}$ , the sequence of parameters obtained running Algorithm 1. Then for  
 479  $r > 0$ :

$$\left\| \frac{\bar{\nabla} f(\bar{\theta}_r)}{\sqrt{v_r^t}} \right\|^2 \geq \frac{1}{2} \left\| \frac{\nabla f(\bar{\theta}_r)}{\sqrt{v_r^t}} \right\|^2 - \bar{L} \alpha^2 M^2 \phi_M^2 \frac{(1 - \beta_2)p}{v_0}$$

480 where  $M$  is defined in H2,  $p$  is the total number of dimensions  $p = \sum_{\ell=1}^L p_\ell$  and  $\phi_M$  is defined in  
 481 H4.

482 *Proof.* Consider the following sequence:

$$\left\| \frac{\bar{\nabla} f(\theta_r)}{\sqrt{v_r^t}} \right\|^2 \geq \frac{1}{2} \left\| \frac{\nabla f(\bar{\theta}_r)}{\sqrt{v_r^t}} \right\|^2 - \left\| \frac{\bar{\nabla} f(\theta_r) - \nabla f(\bar{\theta}_r)}{\sqrt{v_r^t}} \right\|^2,$$

483 where the inequality is due to the Cauchy-Schwartz inequality.

484 Under the smoothness assumption H1 and using Lemma 1, we have

$$\begin{aligned} \left\| \frac{\bar{\nabla} f(\theta_r)}{\sqrt{v_r^t}} \right\|^2 &\geq \frac{1}{2} \left\| \frac{\nabla f(\bar{\theta}_r)}{\sqrt{v_r^t}} \right\|^2 - \left\| \frac{\bar{\nabla} f(\theta_r) - \nabla f(\bar{\theta}_r)}{\sqrt{v_r^t}} \right\|^2 \\ &\geq \frac{1}{2} \left\| \frac{\nabla f(\bar{\theta}_r)}{\sqrt{v_r^t}} \right\|^2 - \bar{L}\alpha^2 M^2 \phi_M^2 \frac{(1 - \beta_2)p}{v_0}, \end{aligned}$$

485 which concludes the proof.  $\square$

## 486 A.2 Proof of Theorem 1

487 **Theorem.** Assume H1-H4. Consider  $\{\bar{\theta}_r\}_{r>0}$ , the sequence of parameters obtained running Algo-  
 488 rithm 1 with a decreasing learning rate  $\alpha_r$ . Then, if the number of local epochs is set to  $T = 1$  and  
 489  $\lambda = 0$ , we have:

$$\begin{aligned} &\frac{1}{R} \sum_{r=1}^R \mathbb{E} \left[ \left\| \frac{\nabla f(\bar{\theta}_r)}{\sqrt{v_r^t}} \right\|^2 \right] \\ &\leq \sqrt{\frac{M^2 p}{n}} \frac{\mathbb{E}[f(\bar{\theta}_1)] - \min_{\theta \in \Theta} f(\theta)}{\bar{L}\alpha_r R} + \frac{\phi_M \sigma^2}{Rn} \sqrt{\frac{1 - \beta_2}{M^2 p}} \\ &\quad + \alpha_r \phi_M \sigma \bar{L} p \sqrt{n} + \frac{\bar{L}\beta_1^2 \bar{L}(1 - \beta_2) M^2 \phi_M^2 n}{2(1 - \beta_1)^2 v_0} \\ &\quad + \frac{\alpha_r \beta_1}{1 - \beta_1} \sqrt{(1 - \beta_2)p} \frac{\bar{L} M^2}{\sqrt{v_0}} + \bar{L}\alpha_r^2 M^2 \phi_M^2 \frac{(1 - \beta_2)p}{Rv_0} \end{aligned}$$

490 **Case with  $T = 1$ ,  $\epsilon = 0$  and  $\lambda = 0$ :** Using H1, we have:

$$\begin{aligned} f(\bar{\vartheta}_{r+1}) &\leq f(\bar{\vartheta}_r) + \langle \nabla f(\bar{\vartheta}_r) | \bar{\vartheta}_{r+1} - \bar{\vartheta}_r \rangle + \sum_{\ell=1}^L \frac{L_\ell}{2} \|\bar{\vartheta}_{r+1}^\ell - \bar{\vartheta}_r^\ell\|^2 \\ &\leq f(\bar{\vartheta}_r) + \sum_{\ell=1}^L \sum_{j=1}^{p_\ell} \nabla_\ell f(\bar{\vartheta}_r)^j (\bar{\vartheta}_{r+1}^{\ell,j} - \bar{\vartheta}_r^{\ell,j}) + \sum_{\ell=1}^L \frac{L_\ell}{2} \|\bar{\vartheta}_{r+1}^\ell - \bar{\vartheta}_r^\ell\|^2. \end{aligned}$$

491 Taking expectations on both sides leads to:

$$-\mathbb{E}[\langle \nabla f(\bar{\vartheta}_r) | \bar{\vartheta}_{r+1} - \bar{\vartheta}_r \rangle] \leq \mathbb{E}[f(\bar{\vartheta}_r) - f(\bar{\vartheta}_{r+1})] + \sum_{\ell=1}^L \frac{L_\ell}{2} \mathbb{E}[\|\bar{\vartheta}_{r+1}^\ell - \bar{\vartheta}_r^\ell\|^2]. \quad (7)$$

492 Yet, we observe that, using the classical intermediate quantity, used for proving convergence results  
 493 of adaptive optimization methods, see for instance [27], we have:

$$\bar{\vartheta}_r = \bar{\theta}_r + \frac{\beta_1}{1 - \beta_1} (\bar{\theta}_r - \bar{\theta}_{r-1}), \quad (8)$$



494 where  $\bar{\theta}_r$  denotes the average of the local models at round  $r$ . Then for each layer  $\ell$ ,

$$\bar{\vartheta}_{r+1}^\ell - \bar{\vartheta}_r^\ell = \frac{1}{1 - \beta_1} (\bar{\theta}_{r+1}^\ell - \bar{\theta}_r^\ell) - \frac{\beta_1}{1 - \beta_1} (\bar{\theta}_r^\ell - \bar{\theta}_{r-1}^\ell) \quad (9)$$

$$= \frac{\alpha_r}{1 - \beta_1} \frac{1}{n} \sum_{i=1}^n \frac{\phi(\|\theta_{r,i}^\ell\|)}{\|p_{r,i}^\ell\|} p_{r,i}^\ell - \frac{\alpha_{r-1}}{1 - \beta_1} \frac{1}{n} \sum_{i=1}^n \frac{\phi(\|\theta_{r-1,i}^\ell\|)}{\|p_{r-1,i}^\ell\|} p_{r-1,i}^\ell \quad (10)$$

$$= \frac{\alpha\beta_1}{1 - \beta_1} \frac{1}{n} \sum_{i=1}^n \left( \frac{\phi(\|\theta_{r,i}^\ell\|)}{\sqrt{v_r^t} \|p_{r,i}^\ell\|} - \frac{\phi(\|\theta_{r-1,i}^\ell\|)}{\sqrt{v_{r-1}^t} \|p_{r-1,i}^\ell\|} \right) m_{r-1}^t + \frac{\alpha}{n} \sum_{i=1}^n \frac{\phi(\|\theta_{r,i}^\ell\|)}{\sqrt{v_r^t} \|p_{r,i}^\ell\|} g_{r,i}^\ell, \quad (11)$$

495 where we have assumed a constant learning rate  $\alpha$ .

496 We note for all  $\theta \in \Theta$ , the majorant  $G > 0$  such that  $\phi(\|\theta\|) \leq G$ . Then, following (7), we obtain:

$$-\mathbb{E}[\langle \nabla f(\bar{\vartheta}_r) | \bar{\vartheta}_{r+1} - \bar{\vartheta}_r \rangle] \leq \mathbb{E}[f(\bar{\vartheta}_r) - f(\bar{\vartheta}_{r+1})] + \sum_{\ell=1}^L \frac{L_\ell}{2} \mathbb{E}[\|\bar{\vartheta}_{r+1} - \bar{\vartheta}_r\|^2]. \quad (12)$$

497 Developing the LHS of (12) using (9) leads to

$$\langle \nabla f(\bar{\vartheta}_r) | \bar{\vartheta}_{r+1} - \bar{\vartheta}_r \rangle = \sum_{\ell=1}^L \sum_{j=1}^{p_\ell} \nabla_\ell f(\bar{\vartheta}_r)^j (\bar{\vartheta}_{r+1}^{\ell,j} - \bar{\vartheta}_r^{\ell,j}) \quad (13)$$

$$= \frac{\alpha\beta_1}{1 - \beta_1} \frac{1}{n} \sum_{\ell=1}^L \sum_{j=1}^{p_\ell} \nabla_\ell f(\bar{\vartheta}_r)^j \left[ \sum_{i=1}^n \left( \frac{\phi(\|\theta_{r,i}^\ell\|)}{\sqrt{v_r^t} \|p_{r,i}^\ell\|} - \frac{\phi(\|\theta_{r-1,i}^\ell\|)}{\sqrt{v_{r-1}^t} \|p_{r-1,i}^\ell\|} \right) m_{r-1}^t \right] \quad (14)$$

$$- \underbrace{\frac{\alpha}{n} \sum_{\ell=1}^L \sum_{j=1}^{p_\ell} \nabla_\ell f(\bar{\vartheta}_r)^j \sum_{i=1}^n \frac{\phi(\|\theta_{r,i}^\ell\|)}{\sqrt{v_r^t} \|p_{r,i}^\ell\|} g_{r,i}^{\ell,j}}_{=A_1}. \quad (15)$$

498 **Term  $A_1$ :** Since we have that  $\|p_{r,i}^\ell\| \leq \sqrt{\frac{p_\ell}{1 - \beta_2}}$  and  $1/\sqrt{v_r^t} \leq 1/\sqrt{v_0}$ , using H2, we develop the  
499 term  $A_1$  as follows:

$$\begin{aligned} A_1 &\leq -\frac{\alpha}{n} \sum_{\ell=1}^L \sum_{j=1}^{p_\ell} \nabla_\ell f(\bar{\vartheta}_r)^j \sum_{i=1}^n \frac{\phi(\|\theta_{r,i}^\ell\|)}{\sqrt{v_r^t} \|p_{r,i}^\ell\|} g_{r,i}^{\ell,j} \\ &\leq -\frac{\alpha}{n} \sum_{\ell=1}^L \sqrt{\frac{1 - \beta_2}{M^2 p_\ell}} \sum_{i=1}^n \sum_{j=1}^{p_\ell} \phi(\|\theta_{r,i}^\ell\|) \nabla_\ell f(\bar{\vartheta}_r)^j g_{r,i}^{\ell,j} \\ &\quad - \frac{\alpha}{n} \sum_{\ell=1}^L \sum_{i=1}^n \sum_{j=1}^{p_\ell} \left( \phi(\|\theta_{r,i}^\ell\|) \nabla_\ell f(\bar{\vartheta}_r)^j \frac{p_{r,i}^\ell}{\|p_{r,i}^\ell\|} \right) \mathbf{1}(\text{sign}(\nabla_\ell f(\bar{\vartheta}_r)^j) \neq \text{sign}(g_{r,i}^{\ell,j})) \end{aligned}$$

500 Taking the expectations on both sides and using H4 yields:

$$\begin{aligned}
\mathbb{E}[A_1] &\leq -\alpha \sum_{\ell=1}^L \sqrt{\frac{1-\beta_2}{M^2 p_\ell}} \sum_{i=1}^n \sum_{j=1}^{p_\ell} \mathbb{E} \left[ \phi(\|\theta_{r,i}^\ell\|) \nabla_\ell f(\bar{\vartheta}_r)^j g_{r,i}^{\ell,j} \right] \\
&\quad - \frac{\alpha}{n} \sum_{\ell=1}^L \sum_{i=1}^n \sum_{j=1}^{p_\ell} \mathbb{E} \left[ \phi(\|\theta_{r,i}^\ell\|) \nabla_\ell f(\bar{\vartheta}_r)^j \frac{p_{r,i}^\ell}{\|p_{r,i}^\ell\|} \mathbf{1} \left( \text{sign}(\nabla_\ell f(\bar{\vartheta}_r)^j) \neq \text{sign}(g_{r,i}^{\ell,j}) \right) \right] \\
&\leq -\frac{\alpha}{n} \sum_{\ell=1}^L \phi_m \sqrt{\frac{1-\beta_2}{M^2 p_\ell}} \sum_{i=1}^n \sum_{j=1}^{p_\ell} (\nabla_\ell f(\bar{\vartheta}_r)^j)^2 \\
&\quad - \frac{\alpha}{n} \sum_{\ell=1}^L \sum_{i=1}^n \sum_{j=1}^{p_\ell} \phi_M \mathbb{E} \left[ \left| \nabla_\ell f(\bar{\vartheta}_r)^j \frac{p_{r,i}^\ell}{\|p_{r,i}^\ell\|} \right| \mathbf{1} \left( \text{sign}(\nabla_\ell f(\bar{\vartheta}_r)^j) \neq \text{sign}(g_{r,i}^{\ell,j}) \right) \right].
\end{aligned}$$

501 Since for any  $\ell, i, j$ , we have

$$\mathbb{E} \left[ \left| \nabla_\ell f(\bar{\vartheta}_r)^j \frac{p_{r,i}^\ell}{\|p_{r,i}^\ell\|} \right| \mathbf{1} \left( \text{sign}(\nabla_\ell f(\bar{\vartheta}_r)^j) \neq \text{sign}(g_{r,i}^{\ell,j}) \right) \right] \leq |\nabla_\ell f(\bar{\vartheta}_r)^j| \mathbb{P} \left( \text{sign}(\nabla_\ell f(\bar{\vartheta}_r)^j) \neq \text{sign}(g_{r,i}^{\ell,j}) \right)$$

502 Then, we obtain

$$\mathbb{E}[A_1] \leq -\alpha \phi_m \sqrt{\frac{L(1-\beta_2)}{M^2 p}} \mathbb{E}[\|\bar{\nabla} f(\bar{\vartheta}_r)\|^2] - \alpha \phi_M \sum_{\ell=1}^L \sum_{i=1}^n \sum_{j=1}^{p_\ell} \frac{\sigma_i^{\ell,j}}{\sqrt{n}}, \quad (16)$$

503 where for any  $\theta \in \Theta$  we define  $\bar{\nabla} f(\cdot) = \sum_{i=1}^n \nabla f_i(\cdot)$ .

504 We now need to bound the following remaining terms:

$$\begin{aligned}
A_r^2 &:= \mathbb{E}[\|\bar{\vartheta}_{r+1} - \bar{\vartheta}_r\|^2] \\
A_r^3 &:= \frac{\alpha \beta_1}{1 - \beta_1} \frac{1}{n} \sum_{\ell=1}^L \sum_{j=1}^{p_\ell} \nabla_\ell f(\bar{\vartheta}_r)^j \left[ \sum_{i=1}^n \left( \frac{\phi(\|\theta_{r,i}^\ell\|)}{\sqrt{v_r^t} \|p_{r,i}^\ell\|} - \frac{\phi(\|\theta_{r-1,i}^\ell\|)}{\sqrt{v_{r-1}^t} \|p_{r-1,i}^\ell\|} \right) m_{r-1}^t \right].
\end{aligned}$$

505 **Term  $A_r^2$ :** According to definition (8), for each layer  $\ell \in \llbracket L \rrbracket$ , we have, using the Cauchy-Schwartz  
506 inequality, that:

$$\begin{aligned}
\|\bar{\vartheta}_{r+1}^\ell - \bar{\vartheta}_r^\ell\|^2 &= \left\| \frac{\alpha \beta_1}{1 - \beta_1} \frac{1}{n} \sum_{i=1}^n \left( \frac{\phi(\|\theta_{r,i}^\ell\|)}{\sqrt{v_r^t} \|p_{r,i}^\ell\|} - \frac{\phi(\|\theta_{r-1,i}^\ell\|)}{\sqrt{v_{r-1}^t} \|p_{r-1,i}^\ell\|} \right) m_{r-1}^t + \frac{\alpha}{n} \sum_{i=1}^n \frac{\phi(\|\theta_{r,i}^\ell\|)}{\sqrt{v_r^t} \|p_{r,i}^\ell\|} g_{r,i} \right\|^2 \\
&\leq 2 \frac{\alpha^2}{n^2} \left\| \frac{\beta_1}{1 - \beta_1} \sum_{i=1}^n \left( \frac{\phi(\|\theta_{r,i}^\ell\|)}{\sqrt{v_r^t} \|p_{r,i}^\ell\|} - \frac{\phi(\|\theta_{r-1,i}^\ell\|)}{\sqrt{v_{r-1}^t} \|p_{r-1,i}^\ell\|} \right) m_{r-1}^t \right\|^2 + \frac{\alpha^2}{n^2} \left\| \sum_{i=1}^n \frac{\phi(\|\theta_{r,i}^\ell\|)}{\sqrt{v_r^t} \|p_{r,i}^\ell\|} g_{r,i} \right\|^2
\end{aligned}$$

507 Taking the expectation on both sides leads to:

$$\begin{aligned}
\mathbb{E}[\|\bar{\vartheta}_{r+1}^\ell - \bar{\vartheta}_r^\ell\|^2] &\leq 2\alpha^2 \mathbb{E} \left[ \left\| \frac{\beta_1}{1-\beta_1} \sum_{i=1}^n \left( \frac{\phi(\|\theta_{r,i}^\ell\|)}{\sqrt{v_r^t} \|p_{r,i}^\ell\|} - \frac{\phi(\|\theta_{r-1,i}^\ell\|)}{\sqrt{v_{r-1}^t} \|p_{r-1,i}^\ell\|} \right) m_{r-1}^t \right\|^2 \right] + \frac{\alpha^2}{n^2} \mathbb{E} \left[ \left\| \sum_{i=1}^n \frac{\phi(\|\theta_{r,i}^\ell\|)}{\sqrt{v_r^t} \|p_{r,i}^\ell\|} g_{r,i} \right\|^2 \right] \\
&\leq 2\frac{\alpha^2}{n^2} \mathbb{E} \left[ \left\| \frac{\beta_1}{1-\beta_1} \sum_{i=1}^n \left( \frac{\phi(\|\theta_{r,i}^\ell\|)}{\sqrt{v_r^t} \|p_{r,i}^\ell\|} - \frac{\phi(\|\theta_{r-1,i}^\ell\|)}{\sqrt{v_{r-1}^t} \|p_{r-1,i}^\ell\|} \right) m_{r-1}^t \right\|^2 \right] \\
&\quad + \frac{\alpha^2}{n^2} \mathbb{E} \left[ \sum_{i=1}^n \sum_{j=1}^p \left\langle \Gamma_{r,i}^j (\nabla f_i(\theta_r))^j + g_{r,i}^j - \nabla f_i(\theta_r)^j \mid \Gamma_{r,i}^j (\nabla f_i(\theta_r))^j + g_{r,i}^j - \nabla f_i(\theta_r)^j \right\rangle \right] \\
&\leq 2\frac{\alpha^2}{n^2} \mathbb{E} \left[ \left\| \frac{\beta_1}{1-\beta_1} \sum_{i=1}^n \left( \frac{\phi(\|\theta_{r,i}^\ell\|)}{\sqrt{v_r^t} \|p_{r,i}^\ell\|} - \frac{\phi(\|\theta_{r-1,i}^\ell\|)}{\sqrt{v_{r-1}^t} \|p_{r-1,i}^\ell\|} \right) m_{r-1}^t \right\|^2 \right] \\
&\quad + \frac{\alpha^2}{n^2} \mathbb{E} \left[ \left\| \sum_{i=1}^n \frac{\phi(\|\theta_{r,i}^\ell\|)}{\sqrt{v_r^t} \|p_{r,i}^\ell\|} \nabla f_i(\theta_r) \right\|^2 \right] + \frac{\alpha^2}{n^2} \sum_{i=1}^n \sigma_i^2 \mathbb{E} \left[ \left\| \frac{\phi(\|\theta_{r,i}^\ell\|)}{\sqrt{v_r^t} \|p_{r,i}^\ell\|} \right\|^2 \right]
\end{aligned} \tag{17}$$

508 where the last line uses assumptions H2 and H3 (unbiased gradient and bounded variance of the  
509 stochastic gradient) and  $\Gamma_{r,i}^\ell := \frac{\phi(\|\theta_{r,i}^\ell\|)}{\sqrt{v_r^t} \|p_{r,i}^\ell\|}$ .

510 On the other hand, using the bound on the gradient H2,

$$\begin{aligned}
&\sum_{r=1}^R \mathbb{E} \left[ \left\| \frac{\beta_1}{1-\beta_1} \sum_{i=1}^n \left( \frac{\phi(\|\theta_{r,i}^\ell\|)}{\sqrt{v_r^t} \|p_{r,i}^\ell\|} - \frac{\phi(\|\theta_{r-1,i}^\ell\|)}{\sqrt{v_{r-1}^t} \|p_{r-1,i}^\ell\|} \right) m_{r-1}^t \right\|^2 \right] \\
&\leq \frac{\beta_1^2}{(1-\beta_1)^2} M^2 \phi_M^2 \sum_{r=1}^R \mathbb{E} \left[ \left\| \sum_{i=1}^n \left( \frac{1}{\sqrt{v_r^t} \|p_{r,i}^\ell\|} - \frac{1}{\sqrt{v_{r-1}^t} \|p_{r-1,i}^\ell\|} \right) \right\|^2 \right] \\
&\leq \frac{\beta_1^2}{(1-\beta_1)^2} \frac{\mathsf{L}(1-\beta_2)}{p} M^2 \phi_M^2 \sum_{r=1}^R \mathbb{E} \left[ \left\| \sum_{i=1}^n \left( \frac{1}{\sqrt{v_r^t}} - \frac{1}{\sqrt{v_{r-1}^t}} \right) \right\|^2 \right] \\
&\leq \frac{\beta_1^2}{(1-\beta_1)^2} \frac{\mathsf{L}(1-\beta_2)}{p} M^2 \phi_M^2 \sum_{r=1}^R \mathbb{E} \left[ \sum_{i=1}^n \sum_{j=1}^p \left( \frac{1}{\sqrt{v_r^{t,j}}} - \frac{1}{\sqrt{v_{r-1}^{t,j}}} \right) \right] \\
&\leq \frac{\beta_1^2}{(1-\beta_1)^2} \frac{\mathsf{L}(1-\beta_2)}{p} M^2 \phi_M^2 \frac{np}{v_0}
\end{aligned} \tag{18}$$

511 where, in the telescopic sum, we have used the initial value  $v_0$  of the non decreasing sequence  
512  $\{v_r^t\}_{r>0}$  by construction (max operator).

513 Combining (18) into (17) and summing over the total number of rounds  $R$  yields

$$\begin{aligned}
\sum_{r=1}^R A_r^2 &:= \sum_{r=1}^R \mathbb{E}[\|\bar{\vartheta}_{r+1}^\ell - \bar{\vartheta}_r^\ell\|^2] \leq \frac{\beta_1^2}{(1-\beta_1)^2} \frac{\mathsf{L}(1-\beta_2)}{p} M^2 \phi_M^2 \frac{np}{v_0} \\
&\quad + \sum_{r=1}^R \left[ \frac{\alpha^2}{n^2} \mathbb{E} \left[ \left\| \sum_{i=1}^n \frac{\phi(\|\theta_{r,i}^\ell\|)}{\sqrt{v_r^t} \|p_{r,i}^\ell\|} \nabla f_i(\theta_r) \right\|^2 \right] + \frac{\alpha^2}{n^2} \sum_{i=1}^n \sigma_i^2 \mathbb{E} \left[ \left\| \frac{\phi(\|\theta_{r,i}^\ell\|)}{\sqrt{v_r^t} \|p_{r,i}^\ell\|} \right\|^2 \right] \right]
\end{aligned} \tag{19}$$

514 **Term  $A_r^3$ :** According to similar arguments on the non decreasing sequence involved in the algorithm  
 515 as in the previous series of calculations, observe that

$$\sum_{r=1}^R A_r^3 \leq \frac{\alpha\beta_1}{1-\beta_1} \sqrt{(1-\beta_2)p} \frac{\mathsf{L}M^2}{\sqrt{v_0}}. \quad (20)$$

516 Plugging (16) into (12) combined with (19) and (20) injected into the original smoothness definition  
 517 (7) summed over the total number of rounds:

$$-\sum_{r=1}^R \mathbb{E}[\langle \nabla f(\bar{\vartheta}_r) | \bar{\vartheta}_{r+1} - \bar{\vartheta}_r \rangle] \leq \sum_{r=1}^R \mathbb{E}[f(\bar{\vartheta}_r) - f(\bar{\vartheta}_{r+1})] + \sum_{r=1}^R \sum_{\ell=1}^L \frac{L_\ell}{2} \mathbb{E}[\|\bar{\vartheta}_{r+1}^\ell - \bar{\vartheta}_r^\ell\|^2]$$

518 leading to the following:

$$\begin{aligned} & \sum_{r=1}^R \alpha\phi_m \sqrt{\frac{\mathsf{L}(1-\beta_2)}{M^2p}} \mathbb{E}[\|\nabla f(\bar{\vartheta}_r)\|^2] - \alpha\phi_M \sum_{\ell=1}^L \sum_{i=1}^n \sum_{j=1}^{p_\ell} \frac{\sigma_i^{\ell,j}}{\sqrt{n}} + \frac{\alpha\beta_1}{1-\beta_1} \sqrt{(1-\beta_2)p} \frac{\mathsf{L}M^2}{\sqrt{v_0}} \\ & \leq \sum_{r=1}^R \mathbb{E}[f(\bar{\vartheta}_r) - f(\bar{\vartheta}_{r+1})] + \sum_{\ell=1}^L \frac{L_\ell}{2} \frac{\beta_1^2}{(1-\beta_1)^2} \frac{\mathsf{L}(1-\beta_2)}{p} M^2 \phi_M^2 \frac{np}{v_0} \\ & \quad - \sum_{r=1}^R \left[ \frac{\alpha^2}{n^2} \mathbb{E} \left[ \left\| \sum_{i=1}^n \frac{\phi(\|\theta_{r,i}^\ell\|)}{\sqrt{v_r^t} \|p_{r,i}^\ell\|} \nabla f_i(\theta_r) \right\|^2 \right] + \frac{\alpha^2}{n^2} \sum_{i=1}^n \sigma_i^2 \mathbb{E} \left[ \left\| \frac{\phi(\|\theta_{r,i}^\ell\|)}{\sqrt{v_r^t} \|p_{r,i}^\ell\|} \right\|^2 \right] \right] \end{aligned}$$

519 Noting that  $\sum_{r=1}^R \mathbb{E}[f(\bar{\vartheta}_r) - f(\bar{\vartheta}_{r+1})] = f(\bar{\vartheta}_1) - \mathbb{E}[f(\bar{\vartheta}_{R+1})]$ , we obtain

$$\begin{aligned} & \sum_{r=1}^R \alpha\phi_m \sqrt{\frac{\mathsf{L}(1-\beta_2)}{M^2p}} \mathbb{E}[\|\nabla f(\bar{\vartheta}_r)\|^2] + \frac{1}{n^2} \sum_{r=1}^R \mathbb{E} \left[ \left\| \sum_{i=1}^n \frac{\phi(\|\theta_{r,i}^\ell\|)}{\sqrt{v_r^t} \|p_{r,i}^\ell\|} \nabla f_i(\theta_r) \right\|^2 \right] \\ & \leq f(\bar{\vartheta}_1) - \mathbb{E}[f(\bar{\vartheta}_{R+1})] + \frac{1}{n^2} \sum_{i=1}^n \sigma_i^2 \mathbb{E} \left[ \left\| \frac{\phi(\|\theta_{r,i}^\ell\|)}{\sqrt{v_r^t} \|p_{r,i}^\ell\|} \right\|^2 \right] + \alpha\phi_M \sum_{\ell=1}^L \sum_{i=1}^n \sum_{j=1}^{p_\ell} \frac{\sigma_i^{\ell,j}}{\sqrt{n}} + \frac{\alpha\beta_1}{1-\beta_1} \sqrt{(1-\beta_2)p} \frac{\mathsf{L}M^2}{\sqrt{v_0}} \\ & + \sum_{\ell=1}^L \frac{L_\ell}{2} \frac{\beta_1^2}{(1-\beta_1)^2} \frac{\mathsf{L}(1-\beta_2)}{p} M^2 \phi_M^2 \frac{np}{v_0}, \end{aligned}$$

520 leading to

$$\begin{aligned} \sum_{r=1}^R \mathbb{E} \left[ \left\| \frac{1}{n} \sum_{i=1}^n \frac{\phi(\|\theta_{r,i}^\ell\|)}{\sqrt{v_r^t} \|p_{r,i}^\ell\|} \nabla f_i(\theta_r) \right\|^2 \right] & \leq \frac{1}{\alpha} [f(\bar{\vartheta}_1) - \mathbb{E}[f(\bar{\vartheta}_{R+1})]] + \sum_{r=1}^R \frac{\alpha}{n^2} \sum_{i=1}^n \sigma_i^2 \mathbb{E} \left[ \left\| \frac{\phi(\|\theta_{r,i}^\ell\|)}{\sqrt{v_r^t} \|p_{r,i}^\ell\|} \right\|^2 \right] \\ & \quad + \alpha\phi_M \sigma \mathsf{L} p \sqrt{n} + \frac{\bar{L}\beta_1^2 \mathsf{L}(1-\beta_2) M^2 \phi_M^2 n}{2(1-\beta_1)^2 v_0} + \frac{\alpha\beta_1}{1-\beta_1} \sqrt{(1-\beta_2)p} \frac{\mathsf{L}M^2}{\sqrt{v_0}}, \end{aligned} \quad (21)$$

521 where  $\bar{L} = \sum_{\ell=1}^L L_\ell$  is the sum of all smoothness constants.

522 Consider the following inequality:

$$\frac{1}{n} \sum_{i=1}^n \frac{\phi(\|\theta_{r,i}^\ell\|)}{\sqrt{v_r^t} \|p_{r,i}^\ell\|} \nabla f_i(\theta_r) \leq \phi_M (1-\beta_2) \frac{\bar{\nabla} f(\theta_r)}{\sqrt{v_r^t}}$$

523 where  $\bar{\nabla} f(\theta_r) := \frac{1}{n} \sum_{i=1}^n \nabla f_i(\theta_r)$ . And using the Cauchy-Schwartz inequality we have

$$\left\| \frac{\bar{\nabla} f(\theta_r)}{\sqrt{v_r^t}} \right\|^2 \geq \frac{1}{2} \left\| \frac{\nabla f(\bar{\theta}_r)}{\sqrt{v_r^t}} \right\|^2 - \left\| \frac{\bar{\nabla} f(\theta_r) - \nabla f(\bar{\theta}_r)}{\sqrt{v_r^t}} \right\|^2$$

524 Using Lemma 1 and the smoothness assumption H1, we have

$$\begin{aligned} \left\| \frac{\bar{\nabla} f(\theta_r)}{\sqrt{v_r^t}} \right\|^2 &\geq \frac{1}{2} \left\| \frac{\nabla f(\bar{\theta}_r)}{\sqrt{v_r^t}} \right\|^2 - \left\| \frac{\bar{\nabla} f(\theta_r) - \nabla f(\bar{\theta}_r)}{\sqrt{v_r^t}} \right\|^2 \\ &\geq \frac{1}{2} \left\| \frac{\nabla f(\bar{\theta}_r)}{\sqrt{v_r^t}} \right\|^2 - \bar{L} \alpha^2 M^2 \phi_M^2 \frac{(1 - \beta_2)p}{v_0}, \end{aligned}$$

525 which is due to Lemma 2. Plugging the above inequality into (21) and dividing both sides by  $R$   
526 yields:

$$\begin{aligned} \frac{1}{R} \sum_{r=1}^R \mathbb{E} \left[ \left\| \frac{\nabla f(\bar{\theta}_r)}{\sqrt{v_r^t}} \right\|^2 \right] &\leq \sqrt{\frac{M^2 p}{n}} \frac{f(\bar{\vartheta}_1) - \mathbb{E}[f(\bar{\vartheta}_{R+1})]}{\mathbb{L} \alpha R} + \frac{\alpha}{n^2} \sum_{r=1}^R \sum_{i=1}^n \sigma_i^2 \mathbb{E} \left[ \left\| \frac{\phi(\|\theta_{r,i}^\ell\|)}{\sqrt{v_r^t} \|p_{r,i}^\ell\|} \right\|^2 \right] \\ &\quad + \alpha \phi_M \sigma \mathbb{L} p \sqrt{n} + \frac{\bar{L} \beta_1^2 \mathbb{L} (1 - \beta_2) M^2 \phi_M^2 n}{2(1 - \beta_1)^2 v_0} + \frac{\alpha \beta_1}{1 - \beta_1} \sqrt{(1 - \beta_2)p} \frac{\mathbb{L} M^2}{\sqrt{v_0}} + \bar{L} \alpha^2 M^2 \phi_M^2 \frac{(1 - \beta_2)p}{R v_0} \end{aligned}$$

527 Then using the fact that  $\vartheta_1 = \theta_1$  and that for all  $\vartheta \in \Theta$ ,  $-f(\vartheta) \leq -\min_{\theta \in \Theta} f(\theta)$  concludes the proof  
528 of our main convergence result.

### 529 A.3 Proof Corollary 1

530 **Corollary.** Assume H1-H4. Consider  $\{\bar{\theta}_r\}_{r>0}$ , the sequence of parameters obtained running  
531 Algorithm 1. Then, if the number of local epochs is set to  $T = 1$ ,  $\epsilon = \lambda = 0$  we have, under H5:

$$\frac{1}{R} \mathbb{E} \left[ \|\nabla f(\bar{\theta}_R)\|^2 \right] \leq \mathcal{O} \left( \sqrt{\frac{p}{n}} \frac{1}{\mathbb{L} \sqrt{R}} \right)$$

532 *Proof.* From the bound in Theorem 1 and with assumption H5. □

### 533 A.4 Extension of Theorem 1 to multiple local updates

534 We now develop a proof for the two intermediary lemmas, Lemma 1 and Lemma 2, in the case when  
535 each local model is obtained after more than one local update. Then the two quantities, either the  
536 gap between the periodically averaged parameter and each local update, i.e.,  $\|\bar{\theta}_r - \theta_{r,i}\|^2$ , and the  
537 ratio of the average gradient, more particularly its relation to the gradient of the average global model  
538 (i.e.,  $\left\| \frac{\bar{\nabla} f(\theta_r)}{\sqrt{v_r^t}} \right\|$  and  $\left\| \frac{\nabla f(\bar{\theta}_r)}{\sqrt{v_r^t}} \right\|$ ), are impacted.

539 **Theorem 3.** Assume H1-H4. Consider  $\{\bar{\theta}_r\}_{r>0}$ , the sequence of parameters obtained running  
540 Algorithm 1 with a decreasing learning rate  $\alpha$ . Let the number of local epochs be  $T \geq 1$  and  $\lambda = 0$ .  
541 Then, at iteration  $\tau$ , we have:

$$\begin{aligned} \frac{1}{\tau} \sum_{t=1}^{\tau} \mathbb{E} \left[ \left\| \frac{\nabla f(\bar{\theta}_t)}{\hat{v}_t^{1/4}} \right\|^2 \right] &\leq \sqrt{\frac{M^2 p}{n}} \frac{\mathbb{E}[f(\bar{\theta}_1)] - \min_{\theta \in \Theta} f(\theta)}{\mathbb{L} \alpha_r \tau} + \frac{\phi_M \sigma^2}{\tau n} \sqrt{\frac{1 - \beta_2}{M^2 p}} \\ &\quad + 4\alpha \left[ \frac{\alpha^2 L_\ell}{\sqrt{v_0}} M^2 (T - 1)^2 \phi_M^2 (1 - \beta_2) p + \frac{M^2}{\sqrt{v_0}} + \phi_M^2 \sqrt{M^2 + p \sigma^2} + \phi_M \frac{\mathbb{L} \sigma^2}{\sqrt{n}} \right] + cst. \end{aligned} \tag{22}$$

542 If one considers a decreasing stepsize as  $\alpha_\tau = \mathcal{O}(\frac{1}{L\sqrt{\tau}})$ , then:

$$\frac{1}{\tau} \sum_{t=1}^{\tau} \mathbb{E} \left[ \left\| \frac{\nabla f(\bar{\theta}_t)}{\hat{v}_t^{1/4}} \right\|^2 \right] \leq \mathcal{O} \left( \sqrt{\frac{M^2 p}{n}} \frac{1}{\sqrt{\mathbb{L} \tau}} + \frac{\sigma^2}{\tau n \sqrt{p}} + \frac{(T - 1)^2 p}{\tau^{3/2} L^3} \right)$$

543 **Discussion on the bound:** Obviously, the last term containing the number of local updates  $T$  is small  
544 as long as  $T \leq \mathcal{O}(\frac{\tau^{1/2} L^{5/4}}{(np)^{1/4}})$ . Treating  $p^{1/4}/L = \mathcal{O}(1)$  which is usually small, the result implies that

we can get the same rate of convergence as the algorithm using one local update, with  $O(\tau^{1/2}/n^{1/4})$  rounds of communication. When the number of workers  $n$  increases, then a constraint on the number of local updates  $T$  is occurring, meaning that we would need more rounds of communication to achieve the same convergence rate, for a identical  $\epsilon$ -stationary point. We recall that a  $\epsilon$ -stationary point is defined by the number of communication rounds  $\mathcal{R}$  such that  $\frac{1}{\tau} \sum_{t=1}^{\mathcal{R}} \mathbb{E} \left[ \left\| \frac{\nabla f(\bar{\theta}_t)}{\hat{v}_t^{1/4}} \right\|^2 \right] \leq \epsilon$ .

We now provide the proof for Theorem 3.

*Proof.* The structure of proof generally follows previous analysis. We change all index  $r$  to iteration  $t$ . Suppose  $T$  is the number of local iterations. We can write (15) as

$$A_1 = -\alpha_t \langle \nabla f(\bar{\vartheta}_t), \frac{\bar{g}_t}{\sqrt{\hat{v}_t}} \rangle,$$

where  $\bar{g}_t = \frac{1}{n} \sum_{i=1}^n \bar{g}_{t,i}$ , with  $\bar{g}_{t,i} = \left[ \frac{\phi(\|\theta_{t,i}^1\|)}{\|p_{t,i}^1\|} g_{t,i}^1, \dots, \frac{\phi(\|\theta_{t,i}^L\|)}{\|p_{t,i}^L\|} g_{t,i}^L \right]$  representing the normalized gradient (concatenated by layers) of the  $i$ -th device. It holds that

$$\langle \nabla f(\bar{\vartheta}_t), \frac{\bar{g}_t}{\sqrt{\hat{v}_t}} \rangle = \frac{1}{2} \left\| \frac{\nabla f(\bar{\vartheta}_t)}{\hat{v}_t^{1/4}} \right\|^2 + \frac{1}{2} \left\| \frac{\bar{g}_t}{\hat{v}_t^{1/4}} \right\|^2 - \left\| \frac{\nabla f(\bar{\vartheta}_t) - \bar{g}_t}{\hat{v}_t^{1/4}} \right\|^2. \quad (23)$$

To bound the last term on the RHS, we have

$$\begin{aligned} \left\| \frac{\nabla f(\bar{\vartheta}_t) - \bar{g}_t}{\hat{v}_t^{1/4}} \right\|^2 &= \left\| \frac{\frac{1}{n} \sum_{i=1}^n (\nabla f(\bar{\vartheta}_t) - \bar{g}_{t,i})}{\hat{v}_t^{1/4}} \right\|^2 \\ &\leq \frac{1}{n} \sum_{i=1}^n \left\| \frac{\nabla f(\bar{\vartheta}_t) - \bar{g}_{t,i}}{\hat{v}_t^{1/4}} \right\|^2 \\ &\leq \frac{2}{n} \sum_{i=1}^n \left( \left\| \frac{\nabla f(\bar{\vartheta}_t) - \nabla f(\bar{\theta}_t)}{\hat{v}_t^{1/4}} \right\|^2 + \left\| \frac{\nabla f(\bar{\theta}_t) - \bar{g}_{t,i}}{\hat{v}_t^{1/4}} \right\|^2 \right). \end{aligned}$$

By Lipschitz smoothness of the loss function, the first term admits

$$\begin{aligned} \frac{2}{n} \sum_{i=1}^n \left\| \frac{\nabla f_i(\bar{\vartheta}_t) - \nabla f_i(\bar{\theta}_t)}{\hat{v}_t^{1/4}} \right\|^2 &\leq \frac{2}{n\sqrt{v_0}} \sum_{i=1}^n L_\ell \|\bar{\vartheta}_t - \bar{\theta}_t\|^2 \\ &= \frac{2L_\ell}{n\sqrt{v_0}} \frac{\beta_1^2}{(1-\beta_1)^2} \sum_{i=1}^n \|\bar{\theta}_t - \bar{\theta}_{t-1}\|^2 \\ &\leq \frac{2\alpha_r^2 L_\ell}{n\sqrt{v_0}} \frac{\beta_1^2}{(1-\beta_1)^2} \sum_{l=1}^L \sum_{i=1}^n \left\| \frac{\phi(\|\theta_{t,i}^l\|)}{\|p_{t,i}^l\|} p_{t,i}^l \right\|^2 \\ &\leq \frac{2\alpha_r^2 L_\ell p \phi_M^2}{\sqrt{v_0}} \frac{\beta_1^2}{(1-\beta_1)^2}. \end{aligned}$$

For the second term,

$$\frac{2}{n} \sum_{i=1}^n \left\| \frac{\nabla f(\bar{\theta}_t) - \bar{g}_{t,i}}{\hat{v}_t^{1/4}} \right\|^2 \leq \frac{4}{n} \underbrace{\left( \sum_{i=1}^n \left\| \frac{\nabla f(\bar{\theta}_t) - \nabla f(\theta_{t,i})}{\hat{v}_t^{1/4}} \right\|^2 \right)}_{B_1} + \underbrace{\left( \sum_{i=1}^n \left\| \frac{\nabla f(\theta_{t,i}) - \bar{g}_{t,i}}{\hat{v}_t^{1/4}} \right\|^2 \right)}_{B_2}. \quad (24)$$

Using the smoothness of  $f_i$  we can transform  $B_1$  into consensus error by

$$\begin{aligned} B_1 &\leq \frac{L}{\sqrt{v_0}} \sum_{i=1}^n \|\bar{\theta}_t - \theta_{t,i}\|^2 \\ &= \frac{\alpha_r^2 L}{\sqrt{v_0}} \sum_{i=1}^n \sum_{l=1}^L \left\| \sum_{j=\lfloor t \rfloor_{T+1}}^t \left( \frac{\phi(\|\theta_{j,i}^l\|)}{\|p_{j,i}^l\|} p_{j,i}^l - \frac{1}{n} \sum_{k=1}^n \frac{\phi(\|\theta_{j,k}^l\|)}{\|p_{j,k}^l\|} p_{j,k}^l \right) \right\|^2 \\ &\leq n \frac{\alpha_r^2 L}{\sqrt{v_0}} M^2 (T-1)^2 \phi_M^2 (1-\beta_2) p \end{aligned} \quad (25)$$



where the last inequality stems from Lemma 1 in the particular case where  $\theta_{t,i}$  are averaged every  $ct + 1$  local iterations for any integer  $c$ , since  $(t - 1) - (\lfloor t \rfloor_T + 1) + 1 \leq T - 1$ .

We now develop the expectation of  $B_2$  under the simplification that  $\beta_1 = 0$ :

$$\begin{aligned}
\mathbb{E}[B_2] &= \mathbb{E}\left[\sum_{i=1}^n \left\| \frac{\nabla f(\theta_{t,i}) - \bar{g}_{t,i}}{\hat{v}_t^{1/4}} \right\|^2\right] \\
&\leq \frac{nM^2}{\sqrt{v_0}} + n\phi_M^2 \sqrt{M^2 + p\sigma^2} - 2 \sum_{i=1}^n \mathbb{E}[\langle \nabla f(\theta_{t,i}), \bar{g}_{t,i} \rangle / \sqrt{\hat{v}_t}] \\
&= \frac{nM^2}{\sqrt{v_0}} + n\phi_M^2 \sqrt{M^2 + p\sigma^2} - 2 \sum_{i=1}^n \sum_{\ell=1}^L \mathbb{E}[\langle \nabla_\ell f(\theta_{t,i}), \frac{\phi(\|\theta_{t,i}^\ell\|)}{\|p_{t,i}^\ell\|} g_{t,i}^\ell \rangle / \sqrt{\hat{v}_t}] \\
&= \frac{nM^2}{\sqrt{v_0}} + n\phi_M^2 \sqrt{M^2 + p\sigma^2} - 2 \sum_{i=1}^n \sum_{\ell=1}^L \sum_{j=1}^{p_\ell} \mathbb{E}[\nabla_\ell f(\theta_{t,i})^j \frac{\phi(\|\theta_{t,i}^{\ell,j}\|)}{\sqrt{\hat{v}_t} \|p_{t,i}^{\ell,j}\|} g_{t,i}^{\ell,j}] \\
&\leq \frac{nM^2}{\sqrt{v_0}} + n\phi_M^2 \sqrt{M^2 + p\sigma^2} - 2 \sum_{i=1}^n \sum_{\ell=1}^L \sum_{j=1}^{p_\ell} \mathbb{E} \left[ \sqrt{\frac{1 - \beta_2}{M^2 p_\ell}} \phi(\|\theta_{r,i}^{\ell,j}\|) \nabla_\ell f(\theta_{t,i})^j g_{t,i}^{\ell,j} \right] \\
&\quad - 2 \sum_{i=1}^n \sum_{\ell=1}^L \sum_{j=1}^{p_\ell} \mathbb{E} \left[ \left( \phi(\|\theta_{r,i}^{\ell,j}\|) \nabla_\ell f(\theta_{t,i})^j \frac{g_{r,i}^{\ell,j}}{\|p_{r,i}^{\ell,j}\|} \right) \mathbf{1} \left( \text{sign}(\nabla_\ell f(\theta_{t,i})^j) \neq \text{sign}(g_{r,i}^{\ell,j}) \right) \right]
\end{aligned}$$

where we use assumption H2, H3 and H4. Yet,

$$-\mathbb{E} \left[ \left( \phi(\|\theta_{r,i}^{\ell,j}\|) \nabla_\ell f(\theta_{t,i})^j \frac{g_{r,i}^{\ell,j}}{\|p_{r,i}^{\ell,j}\|} \right) \mathbf{1} \left( \text{sign}(\nabla_\ell f(\theta_{t,i})^j) \neq \text{sign}(g_{r,i}^{\ell,j}) \right) \right] \leq \phi_M \nabla_\ell f(\theta_{t,i})^j \mathbb{P} \left[ \text{sign}(\nabla_\ell f(\theta_{t,i})^j) \neq \text{sign}(g_{r,i}^{\ell,j}) \right]$$

Then we have:

$$\mathbb{E}[B_2] \leq \frac{nM^2}{\sqrt{v_0}} + n\phi_M^2 \sqrt{M^2 + p\sigma^2} - 2\phi_m \sqrt{\frac{1 - \beta_2}{M^2 p}} \sum_{i=1}^n \mathbb{E}[\|\nabla f(\theta_{t,i})\|^2] + \phi_M \frac{L\sigma^2}{\sqrt{n}}$$

Thus, (24) becomes:

$$\frac{2}{n} \sum_{i=1}^n \left\| \frac{\nabla f_i(\bar{\theta}_t) - \bar{g}_{t,i}}{\hat{v}_t^{1/4}} \right\|^2 \leq 4 \left[ \frac{\alpha_t^2 L_\ell}{\sqrt{v_0}} \alpha_r^2 M^2 (T - 1)^2 \phi_M^2 (1 - \beta_2) p + \frac{M^2}{\sqrt{v_0}} + \phi_M^2 \sqrt{M^2 + p\sigma^2} + \phi_M \frac{L\sigma^2}{\sqrt{n}} \right]$$

Substituting all ingredients into (23), we obtain

$$\begin{aligned}
-\alpha_t \mathbb{E}[\langle \nabla f(\bar{\vartheta}_t), \frac{\bar{g}_t}{\sqrt{\hat{v}_t}} \rangle] &\leq -\frac{\alpha_t}{2} \mathbb{E}[\|\frac{\nabla f(\bar{\vartheta}_t)}{\hat{v}_t^{1/4}}\|^2] - \frac{\alpha_t}{2} \mathbb{E}[\|\frac{\bar{g}_t}{\hat{v}_t^{1/4}}\|^2] + \frac{2\alpha_t^3 L_\ell p \phi_M^2}{\sqrt{v_0}} \frac{\beta_1^2}{(1 - \beta_1)^2} \\
&\quad + 4 \left[ \frac{\alpha_t^2 L_\ell}{\sqrt{v_0}} M^2 (T - 1)^2 \phi_M^2 (1 - \beta_2) p + \frac{M^2}{\sqrt{v_0}} + \phi_M^2 \sqrt{M^2 + p\sigma^2} + \phi_M \frac{L\sigma^2}{\sqrt{n}} \right].
\end{aligned}$$

At the same time, we have

$$\begin{aligned}
\mathbb{E}[\|\frac{\bar{g}_t}{\hat{v}_t^{1/4}}\|^2] &= \frac{1}{n^2} \mathbb{E}[\|\sum_{i=1}^n \frac{\bar{g}_{t,i}}{\hat{v}_t^{1/4}}\|^2] \\
&= \frac{1}{n^2} \mathbb{E}[\sum_{\ell=1}^L \sum_{i=1}^n \|\frac{\phi(\|\theta_{t,i}^\ell\|)}{\hat{v}_t^{1/4} \|p_{t,i}^\ell\|} g_{t,i}^\ell\|^2] \\
&\geq \phi_m^2 (1 - \beta_2) \mathbb{E} \left[ \left\| \frac{1}{n} \sum_{i=1}^n \frac{\nabla f(\theta_{t,i})}{\hat{v}_t^{1/4}} \right\|^2 \right] \\
&= \phi_m^2 (1 - \beta_2) \mathbb{E} \left[ \left\| \frac{\bar{\nabla} f(\theta_t)}{\hat{v}_t^{1/4}} \right\|^2 \right]
\end{aligned}$$

Regarding (22), we have

$$\begin{aligned}
\left\| \frac{\nabla f(\theta_t)}{\hat{v}_t^{1/4}} \right\|^2 &\geq \frac{1}{2} \left\| \frac{\nabla f(\bar{\theta}_t)}{\hat{v}_t^{1/4}} \right\|^2 - \left\| \frac{\nabla f(\theta_t) - \nabla f(\bar{\theta}_t)}{\hat{v}_t^{1/4}} \right\|^2 \\
&\geq \frac{1}{2} \left\| \frac{\nabla f(\bar{\theta}_t)}{\hat{v}_t^{1/4}} \right\|^2 - \left\| \frac{\frac{1}{n} \sum_{i=1}^n (\nabla f(\theta_{t,i}) - \nabla f(\bar{\theta}_t))}{\hat{v}_t^{1/4}} \right\|^2 \\
&\geq \frac{1}{2} \left\| \frac{\nabla f(\bar{\theta}_t)}{\hat{v}_t^{1/4}} \right\|^2 - \frac{\alpha_t^2 L_\ell}{\sqrt{v_0}} M^2 (T-1)^2 \phi_M^2 (1-\beta_2) p,
\end{aligned}$$

where the last line is due to (25). Therefore, we have obtained

$$\begin{aligned}
A_1 \leq & -\frac{\phi_M^2 (1-\beta_2)}{2} \left\| \frac{\nabla f(\bar{\theta}_t)}{\hat{v}_t^{1/4}} \right\|^2 + \frac{\alpha_t^2 L_\ell}{\sqrt{v_0}} M^2 (T-1)^2 \phi_M^2 \phi_M^2 (1-\beta_2)^2 p + \frac{2\alpha^3 L_\ell p \phi_M^2}{\sqrt{v_0}} \frac{\beta_1^2}{(1-\beta_1)^2} \\
& + 4\alpha_t \left[ \frac{\alpha_t^2 L_\ell}{\sqrt{v_0}} M^2 (T-1)^2 \phi_M^2 (1-\beta_2) p + \frac{M^2}{\sqrt{v_0}} + \phi_M^2 \sqrt{M^2 + p\sigma^2} + \phi_M \frac{L\sigma^2}{\sqrt{n}} \right].
\end{aligned}$$

Substitute back into (15), and leave other derivations unchanged. Assuming  $M \leq 1$ , we have the following:

$$\begin{aligned}
\frac{1}{\tau} \sum_{t=1}^{\tau} \mathbb{E} \left[ \left\| \frac{\nabla f(\bar{\theta}_t)}{\hat{v}_t^{1/4}} \right\|^2 \right] &\lesssim \sqrt{\frac{M^2 p}{n}} \frac{f(\bar{\theta}_1) - \mathbb{E}[f(\bar{\theta}_{\tau+1})]}{L\alpha_t \tau} + \frac{\alpha_t}{n^2} \sum_{r=1}^{\tau} \sum_{i=1}^n \sigma_i^2 \mathbb{E} \left[ \left\| \frac{\phi(\|\theta_{r,i}^\ell\|)}{\sqrt{v_t} \|p_{r,i}^\ell\|} \right\|^2 \right] + \frac{2\alpha^3 L_\ell p \phi_M^2}{\sqrt{v_0}} \frac{\beta_1^2}{(1-\beta_1)^2} \\
&+ 4\alpha_t \left[ \frac{\alpha_t^2 L_\ell}{\sqrt{v_0}} M^2 (T-1)^2 \phi_M^2 (1-\beta_2) p + \frac{M^2}{\sqrt{v_0}} + \phi_M^2 \sqrt{M^2 + p\sigma^2} + \phi_M \frac{L\sigma^2}{\sqrt{n}} \right] + \frac{\bar{L}\beta_1^2 L(1-\beta_2)M}{2(1-\beta_1)^2 v_0} \\
&+ \frac{\alpha_t \beta_1}{1-\beta_1} \sqrt{(1-\beta_2)p} \frac{LM^2}{\sqrt{v_0}} + \bar{L}\alpha_t^2 M^2 \phi_M^2 \frac{(1-\beta_2)p}{Tv_0} \\
&\leq \sqrt{\frac{M^2 p}{n}} \frac{\mathbb{E}[f(\bar{\theta}_1)] - \min_{\theta \in \Theta} f(\theta)}{L\alpha_t \tau} + \frac{\phi_M \sigma^2}{\tau n} \sqrt{\frac{1-\beta_2}{M^2 p}} \\
&+ 4\alpha_t \left[ \frac{\alpha_t^2 L_\ell}{\sqrt{v_0}} M^2 (T-1)^2 \phi_M^2 (1-\beta_2) p + \frac{M^2}{\sqrt{v_0}} + \phi_M^2 \sqrt{M^2 + p\sigma^2} + \phi_M \frac{L\sigma^2}{\sqrt{n}} \right] \\
&+ \frac{\alpha_t \beta_1}{1-\beta_1} \sqrt{(1-\beta_2)p} \frac{LM^2}{\sqrt{v_0}} + \bar{L}\alpha_t^2 M^2 \phi_M^2 \frac{(1-\beta_2)p}{Tv_0} + \frac{\bar{L}\beta_1^2 L(1-\beta_2)M^2 \phi_M^2 n}{2(1-\beta_1)^2 v_0} + \frac{2\alpha^3 L_\ell p \phi_M^2}{\sqrt{v_0}} \frac{\beta_1^2}{(1-\beta_1)^2}
\end{aligned}$$

And if we set the learning rate to be of order  $\mathcal{O}(\frac{1}{L\sqrt{\tau}})$  then:

$$\frac{1}{\tau} \sum_{t=1}^{\tau} \mathbb{E} \left[ \left\| \frac{\nabla f(\bar{\theta}_t)}{\hat{v}_t^{1/4}} \right\|^2 \right] \leq \mathcal{O} \left( \sqrt{\frac{M^2 p}{n}} \frac{1}{\sqrt{L\tau}} + \frac{\sigma^2}{\tau n \sqrt{p}} + \frac{(T-1)^2 p}{\tau^{3/2} L^3} \right),$$

concluding our proof.  $\square$

## B Additional Numerical Experiments

### B.1 CIFAR-10 with Convolutional Neural Network and Residual Neural Network

In Figure 2, we report the test accuracies of a Convolutional Neural Network trained on CIFAR-10 dataset, where the data is iid allocated among clients. When we run 1 local epoch per device, we observe a clear advantage of FED-LAMBover Fed-AMS on both test accuracy and convergence speed. Note that Fed-SGD again fails to achieve close performance as those two adaptive gradient methods. Increasing the number of local iterations in each device per communication round leads to similar observations: our newly introduced method, namely FED-LAMB, converges the fastest, with similar generalization error as Fed-AMS.




Figure 3: **From Left to Right:** Test accuracy on CIFAR+ResNet, with iid data distribution. 10 clients and (Left) 1 local epoch, (Right) 3 local epoch