

# Introduction to **Information Retrieval**

Lecture 6: Scoring, Term Weighting and the  
Vector Space Model

# This lecture; IIR Sections 6.2-6.4.3

---

- Ranked retrieval
- Scoring documents
- Term frequency
- Collection statistics
- Weighting schemes
- Vector space scoring

# Ranked retrieval

---

- Thus far, our queries have all been Boolean.
  - Documents either match or don't.
- Good for expert users with precise understanding of their needs and the collection.
  - Also good for applications: Applications can easily consume 1000s of results.
- Not good for the majority of users.
  - Most users incapable of writing Boolean queries (or they are, but they think it's too much work).
  - Most users don't want to wade through 1000s of results.
    - This is particularly true of web search.

# Problem with Boolean search: feast or famine

---

- Boolean queries often result in either too few (=0) or too many (1000s) results.
- Query 1: “*standard user dlink 650*” → 200,000 hits
- Query 2: “*standard user dlink 650 no card found*”: 0 hits
- It takes a lot of skill to come up with a query that produces a manageable number of hits.
  - AND gives too few; OR gives too many

# Ranked retrieval models

---

- Rather than a set of documents satisfying a query expression, in **ranked retrieval models**, the system returns an ordering over the (top) documents in the collection with respect to a query
- **Free text queries**: Rather than a query language of operators and expressions, the user's query is just one or more words in a human language
- In principle, there are two separate choices here, but in practice, ranked retrieval models have normally been associated with free text queries and vice versa

# Feast or famine: not a problem in ranked retrieval

---

- When a system produces a ranked result set, large result sets are not an issue
  - Indeed, the size of the result set is not an issue
  - We just show the **top  $k$**  ( $\approx 10$ ) results
  - We don't overwhelm the user
- Premise: the ranking algorithm works

# Scoring as the basis of ranked retrieval

---

- We wish to return in order the documents most likely to be useful to the searcher
- How can we rank-order the documents in the collection with respect to a query?
- Assign a score – say in  $[0, 1]$  – to each document
- This score measures how well document and query “match”.

# Query-document matching scores

---

- We need a way of assigning a score to a query/document pair
- Let's start with a one-term query
- If the query term does not occur in the document: score should be 0
- The more frequent the query term in the document, the higher the score (should be)
- We will look at a number of alternatives for this.

# Take 1: Jaccard coefficient

---

- Recall from Lecture 3: A commonly used measure of overlap of two sets  $A$  and  $B$
- $\text{jaccard}(A,B) = |A \cap B| / |A \cup B|$
- $\text{jaccard}(A,A) = 1$
- $\text{jaccard}(A,B) = 0$  if  $A \cap B = 0$
- $A$  and  $B$  don't have to be the same size.
- Always assigns a number between 0 and 1.

# Jaccard coefficient: Scoring example

- What is the query-document match score that the Jaccard coefficient computes for each of the two documents below?
- Query: *ides of march*
- Document 1: *caesar died in march*
- Document 2: *the long march*

the term *Ides of March* is best known as the date that Julius Caesar was killed in 709 AUC or 44 B.C

# Issues with Jaccard for scoring

---

- 1 It doesn't consider *term frequency* (how many times a term occurs in a document)
- 2 Rare terms in a collection are more informative than frequent terms. Jaccard doesn't consider this information
  - We need a more sophisticated way of normalizing for length

# Recall (Lecture 1): Binary term-document incidence matrix

	Antony and Cleopatra	Julius Caesar	The Tempest	Hamlet	Othello	Macbeth
Antony	1	1	0	0	0	1
Brutus	1	1	0	1	0	0
Caesar	1	1	0	1	1	1
Calpurnia	0	1	0	0	0	0
Cleopatra	1	0	0	0	0	0
mercy	1	0	1	1	1	1
worser	1	0	1	1	1	0

Each document is represented by a binary vector  $\in \{0,1\}^{|V|}$

# Term-document count matrices

- Consider the number of occurrences of a term in a document:
  - Each document is a **count vector** in  $\mathbb{N}^v$ : a column below

	Antony and Cleopatra	Julius Caesar	The Tempest	Hamlet	Othello	Macbeth
Antony	157	73	0	0	0	0
Brutus	4	157	0	1	0	0
Caesar	232	227	0	2	1	1
Calpurnia	0	10	0	0	0	0
Cleopatra	57	0	0	0	0	0
mercy	2	0	3	5	5	1
worser	2	0	1	1	1	0

# Bag of words model

---

- Vector representation doesn't consider the ordering of words in a document
- *John is quicker than Mary and Mary is quicker than John have the same vectors*
- This is called the bag of words model.
- In a sense, this is a step back: The positional index was able to distinguish these two documents.
- We will look at “recovering” positional information later in this course.
- For now: bag of words model

# Term frequency tf

- The term frequency  $tf_{t,d}$  of term  $t$  in document  $d$  is defined as the number of times that  $t$  occurs in  $d$ .
- We want to use tf when computing query-document match scores. But how?
- Raw term frequency is not what we want:
  - A document with 10 occurrences of the term is more relevant than a document with 1 occurrence of the term.
  - But not 10 times more relevant.
- Relevance does not increase proportionally with term frequency.

NB: frequency = count in IR

# Log-frequency weighting

- The log frequency weight of term  $t$  in  $d$  is

$$w_{t,d} = \begin{cases} 1 + \log_{10} \text{tf}_{t,d}, & \text{if } \text{tf}_{t,d} > 0 \\ 0, & \text{otherwise} \end{cases}$$

- $0 \rightarrow 0, 1 \rightarrow 1, 2 \rightarrow 1.3, 10 \rightarrow 2, 1000 \rightarrow 4$ , etc.
- Score for a document-query pair: sum over terms  $t$  in both  $q$  and  $d$ :
- score  $= \sum_{t \in q \cap d} (1 + \log \text{tf}_{t,d})$
- The score is 0 if none of the query terms is present in the document.

# Document frequency

---

- Rare terms are more informative than frequent terms
  - Recall stop words
- Consider a term in the query that is rare in the collection (e.g., *arachnocentric*)
- A document containing this term is very likely to be relevant to the query *arachnocentric*
- → We want a high weight for rare terms like *arachnocentric*.

# Document frequency, continued

---

- Frequent terms are less informative than rare terms
- Consider a query term that is frequent in the collection (e.g., *high*, *increase*, *line*)
- A document containing such a term is more likely to be relevant than a document that doesn't
- But it's not a sure indicator of relevance.
- → For frequent terms, we want high positive weights for words like *high*, *increase*, and *line*
- But lower weights than for rare terms.
- We will use document frequency (df) to capture this.

# idf weight

- $\text{df}_t$  is the document frequency of  $t$ : the number of documents that contain  $t$ 
  - $\text{df}_t$  is an inverse measure of the informativeness of  $t$
  - $\text{df}_t \leq N$
- We define the idf (inverse document frequency) of  $t$  by

$$\text{idf}_t = \log_{10} (N/\text{df}_t)$$

- We use  $\log (N/\text{df}_t)$  instead of  $N/\text{df}_t$  to “dampen” the effect of idf.

Will turn out the base of the log is immaterial.

# idf example, suppose $N = 1$ million

term	$\text{df}_t$	$\text{idf}_t$
calpurnia	1	
animal	100	
sunday	1,000	
fly	10,000	
under	100,000	
the	1,000,000	

$$\text{idf}_t = \log_{10} (N/\text{df}_t)$$

There is one idf value for each term  $t$  in a collection.

# Effect of idf on ranking

---

- Does idf have an effect on ranking for one-term queries, like
  - iPhone
- idf has no effect on ranking one term queries
  - idf affects the ranking of documents for queries with at least two terms
  - For the query **capricious person**, idf weighting makes occurrences of **capricious** count for much more in the final document ranking than occurrences of **person**.

# Collection vs. Document frequency

- The collection frequency of  $t$  is the number of occurrences of  $t$  in the collection, counting multiple occurrences.
- Example:

Word	Collection frequency	Document frequency
<i>insurance</i>	10440	3997
<i>try</i>	10422	8760

- Which word is a better search term (and should get a higher weight)?

# tf-idf weighting

---

- The tf-idf weight of a term is the product of its tf weight and its idf weight.

$$w_{t,d} = (1 + \log_{10} tf_{t,d}) \times \log_{10}(N / df_t)$$

- Best known weighting scheme in information retrieval
  - Note: the “-” in tf-idf is a hyphen, not a minus sign!
  - Alternative names: tf.idf, tf x idf
- Increases with the number of occurrences within a document
- Increases with the rarity of the term in the collection

# Final ranking of documents for a query

---

$$\text{Score}(q, d) = \sum_{t \in q \cap d} \text{tf.idf}_{t,d}$$

# Binary → count → weight matrix

	Antony and Cleopatra	Julius Caesar	The Tempest	Hamlet	Othello	Macbeth
Antony	5.25	3.18	0	0	0	0.35
Brutus	1.21	6.1	0	1	0	0
Caesar	8.59	2.54	0	1.51	0.25	0
Calpurnia	0	1.54	0	0	0	0
Cleopatra	2.85	0	0	0	0	0
mercy	1.51	0	1.9	0.12	5.25	0.88
worser	1.37	0	0.11	4.15	0.25	1.95

Each document is now represented by a real-valued vector of tf-idf weights  $\in \mathbb{R}^{|V|}$

# Documents as vectors

---

- So we have a  $|V|$ -dimensional vector space
- Terms are axes of the space
- Documents are points or vectors in this space
- Very high-dimensional: tens of millions of dimensions when you apply this to a web search engine
- These are very sparse vectors - most entries are zero.

# Queries as vectors

---

- Key idea 1: Do the same for queries: represent them as vectors in the space
- Key idea 2: Rank documents according to their proximity to the query in this space
- proximity = similarity of vectors
- proximity  $\approx$  inverse of distance
- Recall: We do this because we want to get away from the you're-either-in-or-out Boolean model.
- Instead: rank more relevant documents higher than less relevant documents


# Formalizing vector space proximity

---

- First cut: distance between two points
  - ( = distance between the end points of the two vectors)
- Euclidean distance?
- Euclidean distance is a bad idea . . .
- . . . because Euclidean distance is large for vectors of different lengths.

# Why distance is a bad idea

The Euclidean distance between  $\vec{q}$  and  $\vec{d_2}$  is large even though the distribution of terms in the query  $\vec{q}$  and the distribution of terms in the document  $\vec{d_2}$  are very similar.



# Use angle instead of distance

---


- Thought experiment: take a document  $d$  and append it to itself. Call this document  $d'$ .
- “Semantically”  $d$  and  $d'$  have the same content
- The Euclidean distance between the two documents can be quite large
- The angle between the two documents is 0, corresponding to maximal similarity.
  
- Key idea: Rank documents according to angle with query.

# From angles to cosines

---

- The following two notions are equivalent.
  - Rank documents in decreasing order of the angle between query and document
  - Rank documents in increasing order of cosine(query,document)
- Cosine is a monotonically decreasing function for the interval  $[0^\circ, 180^\circ]$

# From angles to cosines



- But how – *and why* – should we be computing cosines?

# Length normalization

---

- A vector can be (length-) normalized by dividing each of its components by its length – for this we use the  $L_2$  norm:

$$\|\vec{x}\|_2 = \sqrt{\sum_i x_i^2}$$

- Dividing a vector by its  $L_2$  norm makes it a unit (length) vector (on surface of unit hypersphere)
- Effect on the two documents d and d' (d appended to itself) from earlier slide: they have identical vectors after length-normalization.
  - Long and short documents now have comparable weights

# cosine(query,document)

$$\cos(\vec{q}, \vec{d}) = \frac{\vec{q} \bullet \vec{d}}{\|\vec{q}\| \|\vec{d}\|} = \frac{\vec{q}}{\|\vec{q}\|} \bullet \frac{\vec{d}}{\|\vec{d}\|} = \frac{\sum_{i=1}^{|V|} q_i d_i}{\sqrt{\sum_{i=1}^{|V|} q_i^2} \sqrt{\sum_{i=1}^{|V|} d_i^2}}$$

Dot product      Unit vectors

$q_i$  is the tf-idf weight of term  $i$  in the query  
 $d_i$  is the tf-idf weight of term  $i$  in the document

$\cos(\vec{q}, \vec{d})$  is the cosine similarity of  $\vec{q}$  and  $\vec{d}$  ... or,  
equivalently, the cosine of the angle between  $\vec{q}$  and  $\vec{d}$ .

# Cosine for length-normalized vectors


---

- For length-normalized vectors, cosine similarity is simply the dot product (or scalar product):

$$\cos(\vec{q}, \vec{d}) = \vec{q} \bullet \vec{d} = \sum_{i=1}^{|V|} q_i d_i$$

for  $q$ ,  $d$  length-normalized.

# Cosine similarity illustrated



# Cosine similarity amongst 3 documents

How similar are

the novels

SaS: *Sense and*

*Sensibility*

PaP: *Pride and*

*Prejudice*, and

WH: *Wuthering*

*Heights*?

term	SaS	PaP	WH
affection	115	58	20
jealous	10	7	11
gossip	2	0	6
wuthering	0	0	38

Term frequencies (counts)

Note: To simplify this example, we don't do idf weighting in this example.

# 3 documents example contd.

---

## Log frequency weighting

term	SaS	PaP	WH
affection	3.06	2.76	2.30
jealous	2.00	1.85	2.04
gossip	1.30	0	1.78
wuthering	0	0	2.58

## After length normalization

term	SaS	PaP	WH
affection	0.789	0.832	0.524
jealous	0.515	0.555	0.465
gossip	0.335	0	0.405
wuthering	0	0	0.588

$$\cos(\text{SaS}, \text{PaP}) \approx$$

$$0.789 \times 0.832 + 0.515 \times 0.555 + 0.335 \times 0.0 + 0.0 \times 0.0$$

$$\approx 0.94$$

$$\cos(\text{SaS}, \text{WH}) \approx 0.79$$

$$\cos(\text{PaP}, \text{WH}) \approx 0.69$$

Why do we have  $\cos(\text{SaS}, \text{PaP}) > \cos(\text{SaS}, \text{WH})$ ?

# Computing cosine scores

---

COSINESCORE( $q$ )

- 1 *float Scores[N] = 0*
- 2 *float Length[N]*
- 3 **for each** query term  $t$
- 4 **do** calculate  $w_{t,q}$  and fetch postings list for  $t$
- 5     **for each** pair( $d, tf_{t,d}$ ) in postings list
- 6         **do**  $Scores[d] += w_{t,d} \times w_{t,q}$
- 7     Read the array  $Length$
- 8     **for each**  $d$
- 9         **do**  $Scores[d] = Scores[d]/Length[d]$
- 10     **return** Top  $K$  components of  $Scores[]$

# tf-idf weighting has many variants

Term frequency	Document frequency	Normalization
n (natural) $tf_{t,d}$	n (no)      1	n (none)      1
I (logarithm) $1 + \log(tf_{t,d})$	t (idf) $\log \frac{N}{df_t}$	c (cosine) $\frac{1}{\sqrt{w_1^2 + w_2^2 + \dots + w_M^2}}$
a (augmented) $0.5 + \frac{0.5 \times tf_{t,d}}{\max_t(tf_{t,d})}$	p (prob idf) $\max\{0, \log \frac{N - df_t}{df_t}\}$	u (pivoted unique) $1/u$
b (boolean) $\begin{cases} 1 & \text{if } tf_{t,d} > 0 \\ 0 & \text{otherwise} \end{cases}$		b (byte size) $1/CharLength^\alpha, \alpha < 1$
L (log ave) $\frac{1 + \log(tf_{t,d})}{1 + \log(\text{ave}_{t \in d}(tf_{t,d}))}$		

Columns headed ‘n’ are acronyms for weight schemes.

Why is the base of the log in idf immaterial?

# Weighting may differ in queries vs documents

---

- Many search engines allow for different weightings for queries vs. documents
- SMART Notation: denotes the combination in use in an engine, with the notation *ddd.ooo*, using the acronyms from the previous table
- A very standard weighting scheme is: **lnc.ltc**
  - Document: logarithmic tf (*l* as first character), no idf and cosine normalization
  - Query: logarithmic tf (*l* in leftmost column), idf (*t* in second column), cosine normalization ...

A bad idea?

# tf-idf example: Inc.ltc

Document: *car insurance auto insurance*

Query: *best car insurance*

Term	Query						Document				Prod
	tf-raw	tf-wt	df	idf	wt	n'liz e	tf-raw	tf-wt	wt	n'liz e	
auto	0	0	5000	2.3	0	0	1	1	1	0.52	0
best	1	1	50000	1.3	1.3	0.34	0	0	0	0	0
car	1	1	10000	2.0	2.0	0.52	1	1	1	0.52	0.27
insurance	1	1	1000	3.0	3.0	0.78	2	1.3	1.3	0.68	0.53

Exercise: what is  $N$ , the number of docs?

$$\text{Doc length} = \sqrt{1^2 + 0^2 + 1^2 + 1.3^2} \approx 1.92$$

$$\text{Score} = 0+0+0.27+0.53 = 0.8$$

# Representation/feature perspective

---

- Inc.ltc
  - doc vector:
    - tf-vector
    - normalized to unit length
  - query vector
    - tf-idf-vector
    - normalized to unit length
  - score = similarity = inner product between the two vectors

# Summary – vector space ranking

---

- Represent the query as a weighted tf-idf vector
- Represent each document as a weighted tf-idf vector
- Compute the cosine similarity score for the query vector and each document vector
- Rank documents with respect to the query by score
- Return the top  $K$  (e.g.,  $K = 10$ ) to the user

# Resources for today's lecture

---

- IIR 6.2 – 6.4.3
- <http://www.miislita.com/information-retrieval-tutorial/cosine-similarity-tutorial.html>
  - Term weighting and cosine similarity tutorial for SEO folk!