

Computer Networks and Applications

COMP 3331/COMP 9331

Week 5

P2P + Transport Layer Part 1

Reading Guide: Chapter 2, 2.5 + Chapter 3, Sections 3.1 – 3.4

2. Application Layer: outline

2.1 principles of network applications

- app architectures
- app requirements

2.2 Web and HTTP

2.3 electronic mail

- SMTP, POP3, IMAP

2.4 DNS

2.5 P2P applications

2.6 video streaming and content distribution networks (CDNs)


2.7 socket programming with UDP and TCP

P2P architecture

- ❖ no always-on server
- ❖ arbitrary end systems directly communicate
- ❖ peers are intermittently connected and change IP addresses

examples:


- file distribution (BitTorrent)
- Streaming (KanKan)
- VoIP (Skype)



File distribution: client-server vs P2P

Question: how much time to distribute file (size F) from one server to N peers?

- peer upload/download capacity is limited resource




File distribution time: client-server

❖ **server transmission:** must sequentially send (upload) N file copies:

- time to send one copy: F/u_s
- time to send N copies: NF/u_s

❖ **client:** each client must download file copy

- d_{\min} = min client download rate
- min client download time: F/d_{\min}




*time to distribute F
to N clients using
client-server approach*

$$D_{c-s} \geq \max\{NF/u_s, F/d_{\min}\}$$

increases linearly in N

File distribution time: P2P

- ❖ **server transmission:** must upload at least one copy
 - time to send one copy: F/u_s
- ❖ **client:** each client must download file copy
 - min client download time: F/d_{\min}



- ❖ **clients:** as aggregate must download NF bits
 - max upload rate (limiting max download rate) is $u_s + \sum u_i$

*time to distribute F
to N clients using
P2P approach*


$$D_{P2P} \geq \max\{F/u_s, F/d_{\min}, NF/(u_s + \sum u_i)\}$$

increases linearly in N ...

... but so does this, as each peer brings service capacity

Client-server vs. P2P: example

client upload rate = u , $F/u = 1$ hour, $u_s = 10u$, $d_{min} \geq u_s$




P2P file distribution: BitTorrent

- ❖ file divided into 256Kb chunks
- ❖ peers in torrent send/receive file chunks

tracker: tracks peers participating in torrent


torrent: group of peers exchanging chunks of a file



P2P file distribution: BitTorrent

- ❖ peer joining torrent:

- has no chunks, but will accumulate them over time from other peers
- registers with tracker to get list of peers, connects to subset of peers (“neighbours”)



- ❖ while downloading, peer uploads chunks to other peers
- ❖ peer may change peers with whom it exchanges chunks
 - ❖ *churn*: peers may come and go
- ❖ once peer has entire file, it may (selfishly) leave or (altruistically) remain in torrent

BitTorrent: requesting, sending file chunks

requesting chunks:


- ❖ at any given time, different peers have different subsets of file chunks
- ❖ periodically, Alice asks each peer for list of chunks that they have
- ❖ Alice requests missing chunks from peers, rarest first
- ❖ **Q:** Why rarest first?

sending chunks: tit-for-tat

- ❖ Alice sends chunks to those four peers currently sending her chunks *at highest rate*
 - other peers are choked by Alice (do not receive chunks from her)
 - re-evaluate top 4 every 10 secs
- ❖ every 30 secs: randomly select another peer, starts sending chunks
 - “optimistically unchoke” this peer
 - newly chosen peer may join top 4

BitTorrent: tit-for-tat

- (1) Alice “optimistically unchokes” Bob
- (2) Alice becomes one of Bob’s top-four providers; Bob reciprocates
- (3) Bob becomes one of Alice’s top-four providers



Quiz: Free-riding



- ❖ Suppose Todd joins a BitTorrent torrent, but he does not want to upload any data to any other peers. Todd claims that he can receive a complete copy of the file that is shared by the swarm. Is Todd's claim possible? Why or Why not?

Getting rid of the server/tracker

- ❖ Distribute the tracker information using a Distributed Hash Table (DHT)
- ❖ A DHT is a lookup structure
 - Maps keys to an arbitrary value
 - Works a lot like, well hash table

Hash table - review

- ❖ (key,value) pairs
- ❖ Centralised hash table – all (key,value) pairs on 1 node
- ❖ Distributed hash tables – each node has a “section” of (key,value) pairs




Figure src: http://en.wikipedia.org/wiki/Hash_table

Distributed Hash Table (DHT)

- ❖ DHT: a *distributed P2P database*
- ❖ database has (key, value) pairs; examples:
 - key: TFN number; value: human name
 - key: file name; value: BT tracker peer(s)
- ❖ Distribute the (key, value) pairs over the (millions of peers)
- ❖ a peer **queries** DHT with key
 - DHT returns values that match the key
- ❖ peers can also **insert** (key, value) pairs

Challenges

- ❖ How do we assign (key, value) pairs to nodes?
- ❖ How do we find them again quickly?
- ❖ What happens if nodes join/leave?

Q: how to assign keys to peers?

❖ basic idea:

- convert each key to an integer
- Assign integer to each peer
- put (key,value) pair in the peer that is **closest** to the key


DHT identifiers: Consistent Hashing

- ❖ assign integer identifier to each peer in range $[0, 2^n - 1]$ for some n -bit hash function
 - E.g., node ID is hash of its IP address
- ❖ require each key to be an integer in same range
- ❖ to get integer key, hash original key
 - e.g., key = **hash**("House of Cards Season 4")
 - this is why its is referred to as a *distributed "hash" table*

Assign keys to peers

- ❖ rule: assign key to the peer that has the *closest* ID.
- ❖ common convention: closest is the *immediate successor* of the key.
- ❖ e.g., $n=4$; peers: 1,3,4,5,8,10,12,14;
 - key = 13, then successor peer = 14
 - key = 15, then successor peer = 1


Circular DHT (I)



- ❖ each peer *only* aware of immediate successor and predecessor.
- ❖ “overlay network”

Circular DHT (2)

- Each peer maintains 2 neighbours
- 6 query messages are sent




Define closest
as closest
successor

Tradeoff: #of neighbours vs. #of messages


- The smaller the number of neighbours to maintain, the larger the number of messages have to be sent;
- Previous example: 2 neighbours, 6 messages
- Worst case: N messages
- Average: $N/2$ messages

Circular DHT with shortcuts



- ❖ each peer keeps track of IP addresses of predecessor, successor, short cuts
- ❖ reduced from 6 to 2 messages.
- ❖ possible to design shortcuts so $O(\log N)$ neighbours, $O(\log N)$ messages in query

Peer churn



handling peer churn:

- ❖ peers may come and go (churn)
- ❖ each peer knows address of its two successors
- ❖ each peer periodically pings its two successors to check aliveness
- ❖ if immediate successor leaves, choose next successor as new immediate successor

example: peer 5 abruptly leaves

- ❖ peer 4 detects peer 5 departure; makes 8 its immediate successor; asks 8 who its immediate successor is; makes 8's immediate successor its second successor.

More DHT info

- ❖ How do nodes join?
- ❖ How does cryptographic hashing work?
- ❖ How much state does each node store?

Research Articles (available from Moodle page):
Chord: A Scalable Peer-to-Peer Lookup Service for Internet Applications
Dynamo: Amazon's Highly Available Key-value Store

DHT: Applications

- ❖ File sharing and backup [CFS, Ivy, OceanStore, PAST, Pastiche ...]
- ❖ Web cache and replica [Squirrel, Croquet Media Player]
- ❖ Censor-resistant stores [Eternity]
- ❖ DB query and indexing [PIER, Place Lab, VPN Index]
- ❖ Event notification [Scribe]
- ❖ Naming systems [ChordDNS, Twine, INS, HIP]
- ❖ Distributed BitTorrent tracker [Kademlia, Vuze]
- ❖ Communication primitives [I3, ...]
- ❖ Host mobility [DTN Tetherless Architecture]

Transport Layer

our goals:

- ❖ understand principles behind transport layer services:
 - multiplexing, demultiplexing
 - reliable data transfer
 - flow control
 - congestion control
- ❖ learn about Internet transport layer protocols:
 - UDP: connectionless transport
 - TCP: connection-oriented reliable transport
 - TCP congestion control

Transport Layer Outline

3.1 transport-layer services

3.2 multiplexing and demultiplexing

3.3 connectionless transport: UDP

3.4 principles of reliable data transfer

3.5 connection-oriented transport: TCP


- segment structure
- reliable data transfer
- flow control
- connection management

3.6 principles of congestion control

3.7 TCP congestion control

Transport layer

- ❖ Moving “down” a layer
- ❖ Current perspective:
 - Application is the boss....
 - Usually executing within the OS Kernel
 - The network layer is ours to command !!




Network layer (context)

- ❖ What it does: finds paths through network
 - Routing from one end host to another
- ❖ What it doesn't:
 - Reliable transfer: “best effort delivery”
 - Guarantee paths
 - Arbitrate transfer rates
- ❖ For now, think of the network layer as giving us an “API” with one function:
sendtohost(data, host)
 - Promise: the data will go to that (usually!!)


Transport services and protocols

- ❖ provide *logical communication* between app processes running on different hosts
- ❖ transport protocols run in end systems
 - send side: breaks app messages into *segments*, passes to network layer
 - rcv side: reassembles segments into messages, passes to app layer
 - Exports services to application that network layer does not provide




Network layer provides logical communication between hosts

Why a transport layer?




Host A



Host B

Why a transport layer?



Transport Layer Outline

3.1 transport-layer services

3.2 multiplexing and demultiplexing

3.3 connectionless transport: UDP

3.4 principles of reliable data transfer

3.5 connection-oriented transport: TCP

- segment structure
- reliable data transfer
- flow control
- connection management


3.6 principles of congestion control

3.7 TCP congestion control

Multiplexing/demultiplexing

multiplexing at sender:
handle data from multiple sockets, add transport header (later used for demultiplexing)

demultiplexing at receiver:
use header info to deliver received segments to correct socket



Note: The network is a shared resource. It does not care about your applications, sockets, etc.

Connectionless demultiplexing

- ❖ *recall*: created socket has host-local port #:

```
DatagramSocket mySocket1  
= new DatagramSocket(12534) ;
```

- ❖ *recall*: when creating datagram to send into UDP socket, must specify
 - destination IP address
 - destination port #

- ❖ when host receives UDP segment:

- checks destination port # in segment
- directs UDP segment to socket with that port #




IP datagrams with *same dest. port #*, but different source IP addresses and/or source port numbers will be directed to *same socket* at dest

Connectionless demux: example

```
DatagramSocket  
mySocket2 = new  
DatagramSocket  
(9157);
```

```
DatagramSocket  
serverSocket = new  
DatagramSocket  
(6428);
```

```
DatagramSocket  
mySocket1 = new  
DatagramSocket  
(5775);
```




Connection-oriented demux


- ❖ TCP socket identified by 4-tuple:
 - source IP address
 - source port number
 - dest IP address
 - dest port number
- ❖ demux: receiver uses all four values to direct segment to appropriate socket
- ❖ server host may support many simultaneous TCP sockets:
 - each socket identified by its own 4-tuple
- ❖ web servers have different sockets for each connecting client
 - non-persistent HTTP will have different socket for each request

Revisiting TCP Sockets

Server process creates (spawns) two more sockets for two different TCP connections



Connection-oriented demux: example



three segments, all destined to IP address: B,
dest port: 80 are demultiplexed to *different* sockets

Take-away message

- ❖ UDP is identified by 2-tuple
 - Server maintains a single socket for all incoming UDP packets
- ❖ TCP is identified by 4-tuple
 - Server creates new sockets for each TCP connection

May I scan your ports?

<http://netsecurity.about.com/cs/hackertools/a/aa121303.htm>

- ❖ Servers wait at open ports for client requests
- ❖ Hackers often perform *port scans* to determine open, closed and unreachable ports on candidate victims
- ❖ Several ports are well-known
 - <1024 are reserved for well-known apps
 - Other apps also use known ports
 - MS SQL server uses port 1434 (udp)
 - Sun Network File System (NFS) 2049 (tcp/udp)
- ❖ Hackers can use exploit known flaws with these known apps
 - Example: Slammer worm exploited buffer overflow flaw in the SQL server
- ❖ How do you scan ports?
 - Nmap, Superscan, etc

<http://www.auditmypc.com/>

<https://www.grc.com/shieldsup>

Transport Layer Outline

3.1 transport-layer services

3.2 multiplexing and demultiplexing

3.3 connectionless transport: UDP

3.4 principles of reliable data transfer

3.5 connection-oriented transport: TCP

- segment structure
- reliable data transfer
- flow control
- connection management


3.6 principles of congestion control

3.7 TCP congestion control

UDP: User Datagram Protocol [RFC 768]

- ❖ “no frills,” “bare bones” Internet transport protocol
- ❖ “best effort” service, UDP segments may be:
 - lost
 - delivered out-of-order to app
- ❖ *connectionless*:
 - no handshaking between UDP sender, receiver
 - each UDP segment handled independently of others

UDP: segment header



UDP segment format

why is there a UDP?

- ❖ no connection establishment (which can add delay)
- ❖ simple: no connection state at sender, receiver
- ❖ small header size
- ❖ no congestion control: UDP can blast away as fast as desired

UDP checksum

- **Goal:** detect “errors” (e.g., flipped bits) in transmitted segment
 - Router memory errors
 - Driver bugs
 - Electromagnetic interference

sender:

- ❖ treat segment contents, including header fields, as sequence of 16-bit integers
- ❖ checksum: addition (one's complement sum) of segment contents
- ❖ sender puts checksum value into UDP checksum field

receiver:

- ❖ Add all the received together as 16-bit integers
- ❖ Add that to the checksum
- ❖ If the result is not 1111 1111 1111, there are errors !

Internet checksum: example

example: add two 16-bit integers

	1	1	1	0	0	1	1	0	0	1	1	0	0	1	1	0
	1	1	0	1	0	1	0	1	0	1	0	1	0	1	0	1
<hr/>																
wraparound	1	1	0	1	1	1	0	1	1	1	0	1	1	1	0	1
<hr/>																
sum	1	0	1	1	1	0	1	1	1	0	1	1	1	1	0	0
checksum	0	1	0	0	0	1	0	0	0	1	0	0	0	0	1	1

Note: when adding numbers, a carryout from the most significant bit needs to be added to the result

UDP Applications

- ❖ Latency sensitive/time critical
 - ❖ Quick request/response (DNS, DHCP)
 - ❖ Network management (SNMP)
 - ❖ Routing updates (RIP)
 - ❖ Voice/video chat
 - ❖ Gaming (especially FPS)
- ❖ Error correction unnecessary (periodic messages)

Transport Layer Outline

3.1 transport-layer services

3.2 multiplexing and demultiplexing

3.3 connectionless transport: UDP

3.4 principles of reliable data transfer

3.5 connection-oriented transport: TCP

- segment structure
- reliable data transfer
- flow control
- connection management


3.6 principles of congestion control

3.7 TCP congestion control

Reliable Transport


- In a perfect world, reliable transport is easy
- All the bad things best-effort can do
 - a packet is corrupted (bit errors)
 - a packet is lost
 - a packet is delayed (*why?*)
 - packets are reordered (*why?*)
 - a packet is duplicated (*why?*)

The Two Generals Problem



- ❖ Two army divisions (blue) surround enemy (red)
 - Each division led by a general
 - Both must agree when to simultaneously attack
 - If either side attacks alone, defeat
- ❖ Generals can only communicate via messengers
 - Messengers may get captured (unreliable channel)


The Two Generals Problem



❖ How to coordinate?


- Send messenger: “Attack at dawn”
- What if messenger doesn’t make it?

The Two Generals Problem



- ❖ How to be sure messenger made it?
 - Send acknowledgement: “We received message”

Engineering



❖ Concerns

- Message corruption
- Message duplication
- Message loss
- Message reordering
- Performance

❖ Our toolbox


- Checksums
- Timeouts
- Acks and Nacks
- Sequence numbering
- Pipelining

We will use these to build **Automatic Repeat Request (ARQ)** protocols

- Stop-and-wait
- Pipelining
 - Go-back-N
 - Selective Repeat

Principles of reliable data transfer

- ❖ important in application, transport, link layers
 - top-10 list of important networking topics!




(a) provided service

- ❖ characteristics of unreliable channel will determine complexity of reliable data transfer protocol (rdt)

Principles of reliable data transfer


- ❖ important in application, transport, link layers
 - top-10 list of important networking topics!



- ❖ characteristics of unreliable channel will determine complexity of reliable data transfer protocol (rdt)

Principles of reliable data transfer

- ❖ important in application, transport, link layers
 - top-10 list of important networking topics!



- ❖ characteristics of unreliable channel will determine complexity of reliable data transfer protocol (rdt)

rdt1.0: reliable transfer over a reliable channel

- ❖ underlying channel perfectly reliable
 - no bit errors
 - no loss of packets
- Transport layer does not have to do anything !!

rdt2.0: channel with bit errors


- ❖ underlying channel may flip bits in packet
 - checksum to detect bit errors
- ❖ *the question: how to recover from errors:*

*How do humans recover from “errors”
during conversation?*

rdt2.0: channel with bit errors

- ❖ underlying channel may flip bits in packet
 - checksum to detect bit errors
- ❖ *the question: how to recover from errors:*
 - *acknowledgements (ACKs)*: receiver explicitly tells sender that pkt received OK
 - *negative acknowledgements (NAKs)*: receiver explicitly tells sender that pkt had errors
 - sender retransmits pkt on receipt of NAK
- ❖ new mechanisms in `rdt2.0` (beyond `rdt1.0`):
 - error detection
 - feedback: control msgs (ACK,NAK) from receiver to sender

Global Picture of rdt2.0



rdt2.0 has a fatal flaw!

what happens if ACK/ NAK corrupted?

- ❖ sender doesn't know what happened at receiver!
- ❖ can't just retransmit: possible duplicate

handling duplicates:

- ❖ sender retransmits current pkt if ACK/NAK corrupted
- ❖ sender adds *sequence number* to each pkt
- ❖ receiver discards (doesn't deliver up) duplicate pkt

stop and wait

sender sends one packet,
then waits for receiver
response

rdt2.1: discussion

sender:


- ❖ seq # added to pkt
- ❖ two seq. #'s (0,1) will suffice. Why?
- ❖ must check if received ACK/NAK corrupted
- ❖ twice as many states
 - state must “remember” whether “expected” pkt should have seq # of 0 or 1

receiver:

- ❖ must check if received packet is duplicate
 - state indicates whether 0 or 1 is expected pkt seq #
- ❖ note: receiver can *not* know if its last ACK/NAK received OK at sender

Another Look at rdt2.1

Dotted line: erroneous transmission
Solid line: error-free transmission




rdt2.2: a NAK-free protocol

- ❖ same functionality as rdt2.1, using ACKs only
- ❖ instead of NAK, receiver sends ACK for last pkt received OK
 - receiver must *explicitly* include seq # of pkt being ACKed
- ❖ duplicate ACK at sender results in same action as NAK: *retransmit current pkt*

rdt2.2: Example

Dotted line: erroneous transmission
Solid line: error-free transmission



rdt3.0: channels with errors *and* loss

new assumption:


underlying channel can also lose packets (data, ACKs)

- checksum, seq. #, ACKs, retransmissions will be of help ... but not enough


approach: sender waits “reasonable” amount of time for ACK

- ❖ retransmits if no ACK received in this time
- ❖ if pkt (or ACK) just delayed (not lost):
 - retransmission will be duplicate, but seq. #'s already handles this
 - receiver must specify seq # of pkt being ACKed
- ❖ requires countdown timer

rdt3.0 in action




(a) no loss




(b) packet loss

rdt3.0 in action



(c) ACK loss



(d) premature timeout/ delayed ACK

Transport Part I: Summary

- ❖ principles behind transport layer services:
 - multiplexing, demultiplexing
 - reliable data transfer

- ❖ UDP

- ❖ **Next Week:**

- Pipelined Protocols for reliable data transfer
- TCP
 - TCP Flow Control
 - TCP Connection Management
 - TCP Congestion Control