			Frequencies			
Step	Mode number	Frequency (LSCF)	Frequency (CWT1)	Frequency (CWT2)	Number of transients	Std Dev (CWT1)
		$_{ m Hz}$	Hz	${ m Hz}$	(CWT1)	$_{ m Hz}$
	1	£.2f	£.2f	£.2f	£u	£.2f
P_0	2	£.2f	£.2f	£.2f	£u	$\pounds.2f$
	3	£.2f	£.2f	£.2f	£u	£.2f
	1	£.2f	£.2f	£.2f	£u	£.2f
P_6	2	£.2f	£.2f	£.2f	£u	$\pounds.2f$
	3	£.2f	£.2f	£.2f	£u	£.2f
	4	£.2f	£.2f	£.2f	£u	£.2f
P_7	1	£.2f	£.2f	£.2f	£u	£.2f
	2	£.2f	£.2f	£.2f	£u	£.2f
	3	£.2f	£.2f	£.2f	£u	£.2f

		D	amping rati			
Step	Mode number	Damping (LSCF) %	Damping (CWT1)	Damping (CWT2) %	Number of transients (CWT1)	Std Dev (CWT1)
	1	£.2f	£.2f	£.2f	£u	£.2f
P_0	2	£.2f	£.2f	£.2f	£u	£.2f
	3	£.2f	£.2f	£.2f	£u	£.2f
	1	£.2f	£.2f	£.2f	£u	£.2f
P_6	2	£.2f	£.2f	£.2f	£u	£.2f
	3	£.2f	£.2f	£.2f	£u	£.2f
	4	£.2f	£.2f	£.2f	£u	£.2f
P_7	1	£.2f	£.2f	£.2f	£u	£.2f
	2	£.2f	£.2f	£.2f	£u	£.2f
	3	£.2f	£.2f	£.2f	£u	£.2f

		Modal Assurance Criterion					
	Mode	MAC	MAC	MAC			
Step		$(CWT1 \times LSCF)$	$(CWT2 \times LSCF)$	$(CWT2\times CWT1)$			
	number	%	%	%			
	1	£.2f	£.2f	£.2f			
P_0	2 £.2f		£.2f	£.2f			
	3	£.2f	£.2f	£.2f			
	1	£.2f	£.2f	£.2f			
P_6	2	£.2f	$\pounds.2f$	£.2f			
	3	£.2f	£.2f	£.2f			
	4	£.2f	£.2f	£.2f			
P ₇	1	£.2f	£.2f	£.2f			
	2	£.2f	£.2f	£.2f			
	3	£.2f	£.2f	£.2f			

		Non-pr	oportionali			
Step	Mode number	$\begin{array}{c c} \tilde{I}_{np} \\ \text{(LSCF)} \\ \% \end{array}$	$\begin{array}{c} \tilde{I}_{np} \\ (\text{CWT1}) \\ \% \end{array}$	$\begin{array}{c} \tilde{I}_{np} \\ (\text{CWT2}) \\ \% \end{array}$	Number of transients (CWT1)	Std Dev (CWT1) %
	1	£.2f	£.2f	£.2f	£u	£.2f
P_0	2	£.2f	£.2f	£.2f	£u	£.2f
	3	£.2f	£.2f	£.2f	£u	£.2f
	1	£.2f	£.2f	£.2f	£u	£.2f
P_6	2	£.2f	£.2f	£.2f	£u	£.2f
	3	$\pounds.2f$	£.2f	£.2f	£u	£.2f
	4	£.2f	£.2f	£.2f	£u	£.2f
	1	£.2f	£.2f	£.2f	£u	£.2f
P_7	2	$\pounds.2f$	£.2f	£.2f	£u	£.2f
	3	£.2f	£.2f	£.2f	£u	£.2f

		Non-proportionality index				
Step	Mode number	$\parallel (LSCF) \mid (CW)$		$\begin{array}{c} \tilde{I}_{np} \\ (\text{CWT2}) \\ \% \end{array}$		
	1	£.2f	£.2f	£.2f		
P_0	2	£.2f	£.2f	£.2f		
	3	£.2f	£.2f	£.2f		
	1	£.2f	£.2f	£.2f		
P_6	2	£.2f	£.2f	£.2f		
	3	£.2f	£.2f	£.2f		
	4	£.2f	£.2f	£.2f		
	1	£.2f	£.2f	£.2f		
P_7	2	£.2f	£.2f	£.2f		
	3	£.2f	£.2f	£.2f		

			Modal Shapes							
Step	Mode number	Number of transients (CWT1)	MAC (CWT1 × LSCF)	MAC (CWT2 × LSCF)	$\begin{array}{c} \text{MAC} \\ \text{(CWT2} \\ \times \text{CWT1)} \\ \end{array}$	$\begin{array}{c} \tilde{I}_{np} \\ \text{(LSCF)} \\ \% \end{array}$	$\begin{array}{ c c } \tilde{I}_{np} \\ (\text{CWT1}) \\ \% \end{array}$	Std Dev (CWT1)	$\begin{array}{c} \tilde{I}_{np} \\ (\text{CWT2}) \\ \% \end{array}$	
	1	1	99.73	/	/	2.46	1.39	/	/	
P_0	2	3	99.98	99.94	99.88	7.10	7.90	0.81	7.21	
	3	2	98.91	99.11	99.52	5.50	3.93	3.50	4.31	
P_6	1	2	100.00	/	/	0.23	0.29	0.26	/	
	2	1	99.94	/	/	1.34	1.07	/	/	
	3	2	99.92	/	/	1.09	1.43	0.04	/	
	4	1	98.96	/	/	5.75	5.51	/	/	
P_7	1	3	99.99	/	/	0.46	0.61	0.39	/	
	2	5	99.96	97.65	97.59	0.65	1.56	1.78	3.21	
	3	8	91.08	84.49	97.30	31.32	3.86	2.89	2.83	