

### 31. Separate Keywords and Identifiers

```
#include <stdio.h>
```

```
#include <string.h>
```

```
#include <ctype.h>
```

```
int isKeyword(char word[])
```

```
{
```

```
    char keywords[32][15] = {
```

```
        "auto","break","case","char","const","continue",
```

```
        "default","do","double","else","enum","extern",
```

```
        "float","for","goto","if","int","long",
```

```
        "register","return","short","signed","sizeof",
```

```
        "static","struct","switch","typedef","union",
```

```
        "unsigned","void","volatile","while"
```

```
    };
```

```
    int i;
```

```
    for (i = 0; i < 32; i++)
```

```
    {
```

```
        if (strcmp(word, keywords[i]) == 0)
```

```
            return 1;
```

```
    }
```

```
    return 0;
```

```
}
```

```
int main()
```

```

{
    char program[] =
        "int main() { int number = 10; float value = 20.5; return 0; }";

    char word[50];
    int i = 0, j;

    printf("KEYWORDS AND IDENTIFIERS\n");
    printf("-----\n");

    while (program[i] != '\0')
    {
        if (isalpha(program[i]) || program[i] == '_')
        {
            j = 0;

            while (isalnum(program[i]) || program[i] == '_')
                word[j++] = program[i++];

            word[j] = '\0';

            if (isKeyword(word))
                printf("Keyword   : %s\n", word);
            else
                printf("Identifier : %s\n", word);
        }
        else
        {

```

```
        i++;  
    }  
}  
  
return 0;  
}
```

## OUTPUT

```
Enter C program statement:  
int  
  
KEYWORDS:  
int  
  
IDENTIFIERS:  
-----  
Process exited after 51.43 seconds with return value 0  
Press any key to continue . . . |
```