MATH5004 LAB 6

FEM for 1D problems (continue)

Consider the following boundary value problem:

$$-\frac{d}{dx}\left(a(x)\frac{du}{dx}\right) + c(x)u(x) = f(x), \quad 0 < x < 1,$$

$$u(0) = u(1) = 0.$$

In this LAB, we apply a MATLAB code based on finite element method with piecewise linear elements to above BVP, and compare the computed and exact solutions with the L2 and seminorm errors.

To compute a finite element approximation, a set of n equally spaced nodes is defined from 0.0 to 1.0, a set of piecewise linear basis functions is set up, with one basis function associated with each node, and then an integral form of the BVP is used, in which the differential equation is multiplied by each basis function, and integration by parts is used to simplify the integrand. A simple two point Gauss quadrature formula is used to estimate the resulting integrals over each interval.

```
function main()
% - uxx + u = x  for 0 < x < 1
% u(0) = u(1) = 0
% exact = x - sinh(x) / sinh(1)
% exact' = 1 - cosh(x) / sinh(1)
  timestamp ();
  fprintf ( 1, '\n' );
  n = 11;
 fprintf (1, '\n');
  fprintf ( 1, 'FEM1D_BVP_LINEAR_TEST00\n' );
  fprintf (1, 'Solve - (\mathbb{A}(x) \mathbb{U}''(x))'' + \mathbb{C}(x) \mathbb{U}(x) = \mathbb{F}(x) \setminus \mathbb{N}');
  fprintf (1, ' for 0 < x < 1, with U(0) = U(1) = 0.\n');
 fprintf ( 1, ' A(X) = 1.0 n');
 fprintf (1, 'C(X) = 1.0\n');
 fprintf (1, ' F(X) = X \setminus n');
 fprintf (1, 'U(X) = X - SINH(X) / SINH(1) \n');
 fprintf ( 1, '\n' );
 fprintf ( 1, ' Number of nodes = %d\n', n );
% Geometry definitions
 x first = 0.0;
 x last = 1.0;
 x = linspace (x first, x last, n);
 x = x(:);
  u = fem1d\_bvp\_linear(n, @a, @c, @f, x);
  uexact = exact(x);
  fprintf ( 1, '\n' );
  fprintf (1, '
                         X
                                   U Uexact Error\n');
  fprintf ( 1, '\n' );
  for i = 1 : n
    fprintf ( 1, ' %4d %8f %8f %8f %8e\n', ...
      i, x(i), u(i), uexact(i), abs(u(i) - uexact(i));
  end
  e1 = 11 error (n, x, u, @exact);
```

```
e2 = 12_error_linear ( n, x, u, @exact );
h1s = h1s_error_linear ( n, x, u, @exact_ux );
mx = max_error_linear ( n, x, u, @exact );
fprintf ( 1, '\n' );
fprintf ( 1, ' l1 norm of error = %g\n', e1 );
fprintf ( 1, ' L2 norm of error = %g\n', e2 );
fprintf ( 1, ' Seminorm of error = %g\n', h1s );
fprintf ( 1, ' Max norm of error = %g\n', mx );

fprintf ( 1, '\n' );
fprintf ( 1, '\n' );
fprintf ( 1, '\n' );
timestamp ( );
end
```

In main() function, **fem1d_bvp_linear** (n, @a, @c, @f, x) is called. This function has five arguments, i.e.

```
n is the number of equally spaced nodes. @ a is the function which evaluates a(x);
```

@c is the function which evaluates c(x);

@f is the function which evaluates f(x).

x is the input vector of n nodes.

and its return is the output vector \mathbf{u} of n values at the nodes, which can also be regarded as the finite element coefficients.

The functions a(x), c(x) and f(x) are defined in the following MATLAB functions.

```
function value = a( x )
% Parameters:
% Input, real X, the evaluation point.
% Output, real VALUE, the value of A(X).
%
  value = 1.0;
end
```

```
function value = c( x )
% Parameters:
% Input, real X, the evaluation point.
% Output, real VALUE, the value of C(X).
  value = 1.0;
end
```

```
function value = f( x )
% Parameters:
% Input, real X, the evaluation point.
% Output, real VALUE, the value of F(X).
%
  value = x;
end
```

We also compare the computed and exact solutions with the L2 and semi-norm errors. We then need the following functions.

```
function value = exact( x )
% Parameters:
% Input, real X, the evaluation point.
% Output, real VALUE, the value of U(X).
% exact = x - sinh(x) / sinh(1)
  value = x - sinh ( x ) / sinh ( 1.0 );
end
```

```
function value = exact_ux( x )
% Parameters:
% Input, real X, the evaluation point.
% Output, real VALUE, the value of dUdX(X).
%
  value = 1.0 - cosh ( x ) / sinh ( 1.0 );
end
```

```
function timestamp ()
%% TIMESTAMP prints the current YMDHMS date as a timestamp.

t = now;
c = datevec (t);
s = datestr (c, 0);
fprintf (1, '%s\n', s);
end
```

```
function h1s = h1s error linear ( n, x, u, exact ux )
% seminorm error of a finite element solution.
 Parameters:
    Input: integer N, the number of nodes.
           real X(N), the mesh points.
           real U(N), the finite element coefficients.
응
           function EQ = EXACT UX (X), returns the value of the exact
                                          derivative at the point X.
    Output: real H1S, the estimated seminorm of the error.
% h1s = 0.0;
% Quadrature definitions.
 quad num = 2;
  abscissa(1) = -0.577350269189625764509148780502;
  abscissa(2) = +0.577350269189625764509148780502;
 weight(1) = 1.0;
 weight(2) = 1.0;
% Integrate over each interval.
 for i = 1 : n - 1
   x1 = x(i);
   xr = x(i+1);
   ul = u(i);
   ur = u(i+1);
    for q = 1 : quad_num
      xq = ( (1.0 - abscissa(q)) * xl ...
           + ( 1.0 + abscissa(q) ) * xr ) ...
```

```
/ 2.0;
wq = weight(q) * ( xr - xl ) / 2.0;

% The piecewise linear derivative is a constant in the interval.

uxq = ( ur - ul ) / ( xr - xl );
exq = exact_ux ( xq );
h1s = h1s + wq * ( uxq - exq )^2;
end
end

h1s = sqrt ( h1s );
end
```

```
function e1 = 11_error ( n, x, u, exact )
% l1 error norm of a finite element solution.
응
  Parameters:
   Input, integer N, the number of nodes.
용
           real X(N), the mesh points.
응
응
           real U(N), the finite element coefficients.
응
           function EQ = EXACT ( X ), returns the value of the exact
응
                                       solution at the point X.
   Output, real E1, the little 11 norm of the error.
용
 u = u(:);
 x = x(:);
 e1 = sum (abs (u(1:n) - exact (x(1:n)));
 e1 = e1 / n;
end
```

```
function e2 = 12 error linear ( n, x, u, exact )
% L2 error norm of a finite element solution.
% Parameters:
응
   Input, integer N, the number of nodes.
응
           real X(N), the mesh points.
응
           real U(N), the finite element coefficients.
응
           function EQ = EXACT ( X ), returns the value of the exact
응
                                      solution at the point X.
    Output, real E2, the estimated L2 norm of the error.
 e2 = 0.0;
% Quadrature definitions.
 quad num = 2;
  abscissa(1) = -0.577350269189625764509148780502;
 abscissa(2) = +0.577350269189625764509148780502;
 weight(1) = 1.0;
 weight(2) = 1.0;
  Integrate over each interval.
 for i = 1 : n - 1
   xl = x(i);
   xr = x(i+1);
   ul = u(i);
   ur = u(i+1);
    for q = 1: quad num
      xq = ((1.0 - abscissa(q)) * xl
```

```
function value = max_error_linear ( n, x, u, exact, value )
% the max error norm of a finite element solution.
% This function estimates the max norm of the error:
% MAX NORM = Integral ( A <= X <= B ) max ( abs ( U(X) - EXACT(X) ) ) dX
% Parameters:
응
   Input, integer N, the number of nodes.
응
           real X(N), the mesh points.
           real U(N), the finite element coefficients.
9
응
           function EQ = EXACT ( X ), returns the value of the exact
응
           solution at the point X.
    Output, real VALUE, the estimated max norm of the error.
 quad num = 8;
 value = 0.0;
 e num = n - 1;
 for e = 1 : e_num
   1 = e;
   x1 = x(1);
   ul = u(1);
   r = e + 1;
   xr = x(r);
   ur = u(r);
   for q = 0: quad num - 1
      xq = ( (quad_num - q) * xl ...
                q ) * xr ) ...
         + (
        / (quad_num
% Use the fact that U is a linear combination of piecewise linears.
     uq = ((xr - xq)) * ul
          + ( xq - xl ) * ur ) ...
          / ( xr - xl );
     eq = exact (xq);
      value = max ( value, abs ( uq - eq ) );
    end
  end
% For completeness, check last node.
```

```
xq = x(n);
uq = u(n);
eq = exact ( xq );
value = max ( value, abs ( uq - eq ) );

% Integral approximation requires multiplication by interval length.

value = value * ( x(n) - x(1) );
end
```

MATLAB OUTPUT

```
12-Sep-2016 14:17:28
FEM1D BVP LINEAR TEST
 MATLAB version
 Test the FEM1D BVP LINEAR library.
FEM1D BVP LINEAR TEST01
  Solve -( A(x) U'(x))' + C(x) U(x) = F(x)
  for 0 < x < 1, with U(0) = U(1) = 0.
 A1(X) = 1.0
 C1(X) = 0.0
 F1(X) = X * (X + 3) * exp (X)
 U1(X) = X * (1 - X) * exp (X)
 Number of nodes = 11
    Ι
         Х
                 IJ
                            Uexact
                                     Error
    1 0.000000 0.000000 0.000000 2.220446e-16
    2 0.100000 0.099466 0.099465 1.334229e-07
    3 0.200000 0.195425 0.195424 2.475629e-07
    4 0.300000 0.283471 0.283470 3.394330e-07
    5 0.400000 0.358038 0.358038 4.056126e-07
    6 0.500000 0.412181 0.412180 4.421874e-07
    7 0.600000 0.437309 0.437309 4.446805e-07
    8 0.700000 0.422888 0.422888 4.079761e-07
    9 0.800000 0.356087 0.356087 3.262308e-07
   10 0.900000 0.221364 0.221364 1.927749e-07
   11 1.000000 0.000000 0.000000 0.000000e+00
  11 norm of error = 2.93988e-06
 L2 norm of error = 0.00400665
  Seminorm of error = 0.138667
```

Assignment II

Question 1 (LAB-Wk6). Given coefficient functions

$$A(X) = 1.0,$$

$$C(X) = 2.0 * X,$$

external load

$$F(X) = -X * (2 * X * X - 3 * X - 3) * exp(X),$$

and exact solution

$$U(X) = X * (1 - X) * exp(X)$$

of the BVP:

$$-(A(x) U'(x))' + C(x) U(x) = F(x)$$
 for $0 < x < 1$, with $U(0) = U(1) = 0$.

Implement MATLAB codes to obtain FE approximation, and determine L_1 , L_2 and seminorm errors.

Note: Assignments II (25%): Assignment Questions will be given weekly.

In this week, Questions 1 (LAB-WK6) is a part of Assignment II, please submit a document file with MATLAB code via Blackboard by the due date of Assignment I on Friday 23 October 2020