Dialight

607 Series
LED Panel Mount Indicators
for 7.2mm Mounting Hole
w/ Optional Watertight Capability

▲ Voltage requirements:
  2 VDC (current limiting resistor required)
  6, 12, 24 VDC (no resistor required)

▲ Electrical connection through solder terminals

▲ Mounting hole size: 0.283 inches (7.2 mm)

▲ Maximum panel thickness:
  (see reverse side)

▲ Mounts with lock washer and nut
  0.362 lbs/ft or 5 Kg/cm torque recommended

  0.217 lbs/ft or 3 Kg/cm torque recommended (Figure 5 only)

▲ Operating Temperature : -30ºC to +85ºC

▲ Storage Temperature: -40ºC to +85ºC

▲ Housing Material:
  Protruding & Recessed positions:
    Chrome plated brass or
  Internal Position:
    Polycarbonate to match emitting color -
    (Figure 5)

▲ Watertight Seal from front of panel meets
  NEMA 4X/IP66

FEATURES / BENEFITS

▲ RoHS compliant*
▲ Long Life - typically 100K hours
▲ Lower Power consumption - uses up to 90% less energy then an incandescent indicator
▲ No heat generated
▲ Colors include red, green and yellow
▲ Front panel mounting
▲ Available Watertight Version: NEMA 4X/ IP66
▲ Chrome or plastic housing:
  LED Positions: (See Figures below)
    Protruding (Fig 1,2)
    Recessed (Fig 3,4)
    Internal (Fig 5)

SPECIFICATIONS

FIG. 1
FIG. 2
FIG. 3
FIG. 4
FIG. 5

Dimensions in inches [mm] All measurements are typical

*Compliant with exemption 6c, lead used as an alloying element in brass (up to 4% by weight)

MDEL607X001_D

STANDARD VERSIONS

Part Number	Color	Voltage (VDC)	Intensity* TYP. (mcd)	LED Positions	Fig.	Panel Thickness
607-1112-110F	Red	2	22	Protuding	1	0.187" (4.75mm)
607-1212-110F	Green	2	50	Protuding	1	
607-1312-110F	Yellow	2	66	Protuding	1	
607-1112-120F	Red	6	22	Protuding	2	0.265" (6.75mm)
607-1212-120F	Green	6	50	Protuding	2	
607-1312-120F	Yellow	6	66	Protuding	2	
607-1112-130F	Red	12	22	Protuding	2	
607-1212-130F	Green	12	50	Protuding	2	
607-1312-130F	Yellow	12	66	Protuding	2	
607-2112-110F	Red	2	22	Recessed	3	0.136" (3.50mm)
607-2212-110F	Green	2	50	Recessed	3	
607-2312-110F	Yellow	2	66	Recessed	3	
607-2112-120F	Red	6	22	Recessed	4	0.336" (8.50mm)
607-2212-120F	Green	6	50	Recessed	4	
607-2312-120F	Yellow	6	66	Recessed	4	
607-2112-130F	Red	12	22	Recessed	4	
607-2212-130F	Green	12	50	Recessed	4	
607-2312-130F	Yellow	12	66	Recessed	4	
607-3132-120F	Red	6	20	Internal	5	0.187" (4.75mm)
607-3232-120F	Green	6	45	Internal	5	
607-3332-120F	Yellow	6	60	Internal	5	
607-3132-130F	Red	12	20	Internal	5	
607-3232-130F	Green	12	45	Internal	5	
607-3332-130F	Yellow	12	60	Internal	5	
607-3132-140F	Red	24	20	Internal	5	
607-3232-140F	Green	24	45	Internal	5	
607-3332-140F	Yellow	24	60	Internal	5	

WATERTIGHT VERSIONS

Part Number	Color	Voltage (VDC)	Intensity* TYP. (mcd)	LED Positions	Fig.	Panel Thickness
607-1112-310F	Red	2	22	Protuding	1	0.147" (3.75mm)
607-1212-310F	Green	2	50	Protuding	1	
607-1312-310F	Yellow	2	66	Protuding	1	
607-1112-320F	Red	6	22	Protuding	2	0.226" (5.75mm)
607-1212-320F	Green	6	50	Protuding	2	
607-1312-320F	Yellow	6	66	Postuding	2	
607-1112-330F	Red	12	22	Protuding	2	
607-1212-330F	Green	12	50	Protuding	2	
607-1312-330F	Yellow	12	66	Protuding	2	
607-2112-310F	Red	2	22	Recessed	3	0.096" (2.50mm)
607-2212-310F	Green	2	50	Recessed	3	
607-2312-310F	Yellow	2	66	Recessed	3	
607-2112-320F	Red	6	22	Recessed	4	0.296" (7.50mm)
607-2212-320F	Green	6	50	Recessed	4	
607-2312-320F	Yellow	6	66	Recessed	4	
607-2112-330F	Red	12	22	Recessed	4	
607-2212-330F	Green	12	50	Recessed	4	
607-2312-330F	Yellow	12	66	Recessed	4	
607-3132-320F	Red	6	20	Internal	5	0.147" (3.75mm)
607-3232-320F	Green	6	45	Internal	5	
607-3332-320F	Yellow	6	60	Internal	5	
607-3132-330F	Red	12	20	Internal	5	
607-3232-330F	Green	12	45	Internal	5	
607-3332-330F	Yellow	12	60	Internal	5	
607-3132-340F	Red	24	20	Internal	5	
607-3232-340F	Green	24	45	Internal	5	
607-3332-340F	Yellow	24	60	Internal	5	

*15 mA current