The AlphaFold 2 Master Screenplay & Mathematical Monograph

A First-Principles Mathematical Script and Stage Performance Protocol for Pair Presenting

Evita Bosch Pokunevich (ebosch@ethz.ch) & **Ben Bullinger** (bben@ethz.ch)

Machine Learning for Genomics (263-5351-00L), ETH Zürich • Prof. Dr. Valentina Boeva

Fall Semester 2026 • Target Duration: 25:00 min talk + 10:00 min Q&A

Abstract

This document constitutes the definitive mathematical foundation, pedagogical script, and stage screenplay for the pair presentation of Jumper et al., *Nature* 596 (2021) (*AlphaFold 2*). The presentation is designed as an architectural duality: the slide deck (`main.tex`) is the visual shadow, while this screenplay is the canonical mathematical source of truth. Every transition, spoken sentence, blackboard derivation, and physical gesture is choreographed to adhere strictly to the 25-minute talk limit (130 words per minute, 12.5 minutes per speaker) followed by a 10-minute moderated seminar discussion and examination defense.

Contents

1 Stage Architecture, Protocol, and Timing **1**
- 1.1 Physical Choreography and Equipment Setup . . . 1
- 1.2 Timing Budget Table . . . 2

2 Act I: The Biology, Benchmark, and Evoformer Trunk **3**

3 Act II: Geometry, Structure Module, Training, and Frontiers **8**

4 Act III: Seminar Defense, Moderated Discussion, and Backups **13**

5 Technical Defense Manual: Backup Slides (1/14 to 14/14) **15**
- 5.1 Backup (1/14): Why is IPA invariant to rigid motions? . . . 15
- 5.2 Backup (2/14): Why is the structure module equivariant? . . . 15
- 5.3 Backup (3/14): Origin of stereochemical chirality . . . 15
- 5.4 Backup (4/14): What does FAPE measure? . . . 15
- 5.5 Backup (5/14): Is AlphaFold 2 a graph neural network? . . . 16
- 5.6 Backup (6/14): What does each block compute? . . . 16
- 5.7 Backup (7/14): What exactly did each ablation remove? . . . 16
- 5.8 Backup (8/14): How is confidence predicted? . . . 16
- 5.9 Backup (9/14): How was it trained? . . . 16
- 5.10 Backup (10/14): AlphaFold 3: further changes . . . 16
- 5.11 Backup (11/14): MSA row attention with pair bias . . . 16
- 5.12 Backup (12/14): Evoformer: columns and outer product mean . . . 17
- 5.13 Backup (13/14): Prediction and experiment superposed . . . 17
- 5.14 Backup (14/14): The AlphaFold 3 architecture . . . 17

---

1 Stage Architecture, Protocol, and Timing

1.1 Physical Choreography and Equipment Setup

- **Stage Layout**: Evita stands at stage-left (near the projection podium); Ben stands at stage-right. Both maintain an open posture toward the audience and the seminar panel (Prof. Boeva and course instructors).

- **Clicker Protocol**: Evita holds the wireless presenter during Part I (Slides 1–10). At the end of Slide 10, Evita executes the physical handover, passing the clicker smoothly to Ben. Ben presents Part II (Slides 11–20). During Part III (Exam Question and Q&A), both speakers step forward together.
- **Pacing Benchmark**: Average comfortable speaking rate is 125–130 words per minute. Slides average 75 seconds (1m 15s) each. Pauses for visual absorption are explicitly noted with *[Pause 2s]*.
- **Laser Pointer Discipline**: Never circle frantically. Point steadily at the exact coordinate, axis tick, or mathematical term for 1.5 seconds, then turn the laser off.

1.2 Timing Budget Table

Slide	Title	Speaker	Key Concept / Focus	Slide Time	Cumulative
Act I: The Biology, Benchmark, and Evoformer Trunk (Evita Bosch Pokunevich)					
Title	Title Slide	Evita	Context, PDB 6Y4F rendering, paper citation	0:30	0:30
1	The problem: sequence to structure	Evita	Levinthal's paradox, heavy atoms, 50-yr challenge	1:15	1:45
2	The benchmark: CASP14	Evita	Blind test, 0.96 Å median error vs 1.4 Å bond length	1:15	3:00
3	The pipeline: MSA in, coordinates out	Evita	End-to-end macro-pipeline, recycling loop	1:15	4:15
4	Four facts, four design choices	Evita	The architectural leitmotif of the entire talk	1:30	5:45
5	The two representations	Evita	MSA tensor $\mathbf{m}_{si}$ and Pair matrix $\mathbf{z}_{ij}$	1:15	7:00
6	The input: MSA representation	Evita	Evolutionary covariance, co-mutations, epistasis	1:15	8:15
7	The input: Pair representation	Evita	Graph edges, spatial distance prior, relative pos	1:15	9:30
8	The Evoformer block	Evita	Dual-track architecture, 48 blocks, axial attention	1:15	10:45
9	MSA row attention with pair bias	Evita	Pair bias injection b_{ij}, gating mechanism	1:15	12:00
10	The pair representation: triangle updates	Evita	Triangle inequality, outer product mean, handover	1:30	13:30
Act II: Geometry, Structure Module, Training, and Frontiers (Ben Bullinger)					
11	Invariant Point Attention (IPA)	Ben	SE(3) invariance proof, local coordinate frames	1:30	15:00
12	Frame Aligned Point Error (FAPE)	Ben	Loss formulation, chirality sensitivity, metric proof	1:30	16:30
13	Recycling: four iterations	Ben	Dynamic refinement, convergence without backprop	1:00	17:30
14	Loss functions: seven terms	Ben	Multi-task supervision, auxiliary heads, violation loss	1:15	18:45
15	Trunk intermediate structures	Ben	Progressive folding, early exit dynamics (LmrP, ORF8)	1:15	20:00
16	Confidence: pLDDT against measured lDDT	Ben	Well-calibrated uncertainty, IDR identification	1:15	21:15
17	Limitations: MSA depth and complexes	Ben	$N_{\text{eff}} < 30$ cliff, multi-chain/conformational gap	1:15	22:30
18	After AlphaFold 2: 2021 to 2025	Ben	AFDB (214M), Multimer, ESMFold, Nobel Prize 2024	1:00	23:30
19	AlphaFold 3: which choices survived	Ben	The Bitter Lesson: graph survived, diffusion replaced IPA	1:15	24:45
20	Summary: four design choices, measured	Ben	Quantitative ablation scorecard, final synthesis	0:45	25:30
Act III: Moderated Discussion, Exam Question, and Defense (Shared)					
21	Exam question	Evita/Ben	Course assignment breakdown	2:00	27:30
22	Questions for the audience	Evita/Ben	Moderated interactive peer debate	4:30	32:00
23–24	References	Evita/Ben	Formal literature grounding	1:00	33:00
25	Resources: AlphaFold at ETH	Evita/Ben	Euler cluster, ColabFold, code repo, calling card	2:00	35:00

2 Act I: The Biology, Benchmark, and Evoformer Trunk

Slide Title: Highly Accurate Protein Structure Prediction with AlphaFold

Evita • 0:00–0:30

THE SLIDE (THE SHADOW): Minimalist title slide: paper citation (Jumper et al., *Nature* 2021), authors, ETH institutional affiliation, presenter names and contact links.

[Evita stands tall, makes direct eye contact with Prof. Boeva and the audience. Speaks with quiet confidence.]

EVITA: Good morning everyone, Prof. Boeva, and fellow researchers. Today, Ben and I have the pleasure of presenting one of the true milestones of contemporary computational biology: *"Highly accurate protein structure prediction with AlphaFold"*, published in Nature in 2021 by John Jumper and the team at DeepMind. When we say AlphaFold today, we mean AlphaFold 2. Our goal today is not merely to summarize what the network does, but to unpack the rigorous mathematical and physical inductive biases that enabled deep learning to solve a 50-year-old grand challenge in molecular biology.

Slide 1: The problem: sequence to structure

Evita • 0:30–1:45

THE SLIDE (THE SHADOW): Left: amino acid string 'SIFSYITESTGTPS…', arrows pointing right, bullet points on experimental timescale vs sequence database explosion. Right: CASP14 Target T1049 (PDB 6Y4F), blue prediction overlaid on green experiment.

[Evita points to the amino acid string on the left, then gestures toward the ribbon structure on the right.]

EVITA: Let us begin from first principles. A protein begins life as a one-dimensional polymer: an unbranched sequence of amino acids selected from an alphabet of 20 canonical residues. Every residue shares an identical chemical backbone—Nitrogen, Carbon-alpha, and Carbon—and is distinguished only by its sidechain.

In the thermodynamic hypothesis formulated by Christian Anfinsen in 1973, native protein structures reside at the global free energy minimum. Yet according to Levinthal's paradox, an unbiased random conformational search of a 100-residue chain across its torsional angles would require 10^{77} years—longer than the age of the universe. In nature, proteins fold spontaneously in milliseconds.

For structural biologists, determining one structure experimentally via X-ray crystallography or cryo-EM requires months to years of arduous wet-lab labor, costing tens of thousands of Swiss francs. As high-throughput sequencing exploded, the UniProt database grew past hundreds of millions of known sequences, while the Protein Data Bank (PDB) remained constrained to around 180,000 resolved structures. The challenge: can machine learning map directly from the 1D primary sequence to the 3D atomic coordinates of all heavy atoms?

MATHEMATICAL CORE & DEEP LEARNING PRINCIPLES:

Let $\mathcal{A}$ denote the alphabet of 20 amino acids. The primary sequence is $\boldsymbol{s} = (s_1, \ldots, s_N) \in \mathcal{A}^N$. The target output is the set of Cartesian coordinates for all M heavy (non-hydrogen) atoms:

$$\mathbf{X} = \{\boldsymbol{x}_a \in \mathbb{R}^3 \mid a \in \{1, \ldots, M\}\}. \tag{1}$$

Each residue $i \in \{1, \ldots, N\}$ has backbone atoms $(\mathrm{N}_i, \mathrm{C}\alpha_i, \mathrm{C}_i, \mathrm{O}_i)$ and up to four sidechain dihedral angles $\chi_{i,1}, \chi_{i,2}, \chi_{i,3}, \chi_{i,4}$.

Slide 2: The benchmark: CASP14

Evita • 1:45–3:00

THE SLIDE (THE SHADOW): CASP14 bar plot: AlphaFold in blue (0.96 Å), 14 next best groups in gray (2.8 Å). Dashed red line at 1.4 Å marked 'Atomic bond length ≈ 1.4 Å (C–C)'. Horizontal y-axis label atop ticks: 'Median backbone error (Å)'.

[Evita points laser pointer steadily at the blue bar, then sweeps across the dashed red line.]

EVITA: To evaluate whether computational models truly generalize rather than overfit to known structures, the community established CASP: the Critical Assessment of protein Structure Prediction. In CASP, targets are blind: experimental structures solved by crystallography or cryo-EM are withheld from the public until predictions are formally submitted.

Here are the official results from CASP14 in summer 2020. The metric is root-mean-square deviation of backbone $C\alpha$ atoms on the 95% best-fitting residues. The gray bars show the fourteen next-best computational teams in the world, hovering with median backbone errors around 2.8 Å.

The blue bar is AlphaFold: its median error is 0.96 Å. Notice the horizontal dashed line at 1.4 Å. That is the length of a single carbon-carbon covalent bond. AlphaFold did not merely edge out competitors by a standard incremental margin; it crossed the fundamental physical threshold of atomic resolution without human intervention.

SEMINAR DEFENSE & EXAM ANTICIPATION:

Possible Examiner Question: *Why is $C\alpha$-$RMSD_{95}$ used rather than standard all-atom RMSD?*
Mathematical Defense: All-atom global RMSD is notoriously brittle to a single flexible loop or unstructured terminal tail swinging in solvent. A 10 Å displacement of a 5-residue tail would inflate the global RMSD of an otherwise atomically flawless 500-residue core. $RMSD_{95}$ fits the rigid core by discarding the 5% worst outliers, reflecting the true structural accuracy of the catalytic domain.

Slide 3: The pipeline: MSA in, coordinates out

Evita • 3:00–4:15

THE SLIDE (THE SHADOW): Macro architecture schematic: MSA & Templates → 48 Evoformer blocks → 8 Structure Module iterations → All-atom relaxation. Recycling loop shown with dashed arrow cycling 4 times.

[Evita sweeps hand from the left inputs across the central trunk to the coordinate output.]

EVITA: How does AlphaFold accomplish this? Look at the overall macro-architecture. AlphaFold abandons legacy two-stage pipelines that first predicted 2D contact distance maps and then handed them off to separate physical simulation software like Rosetta.

AlphaFold is end-to-end differentiable. The network takes the query sequence, searches genomic databases to assemble a Multiple Sequence Alignment (MSA), retrieves structural templates, and constructs two fundamental data structures: an MSA representation and a Pair representation.

These two arrays pass through 48 blocks of the Evoformer trunk, which perform deep evolutionary and spatial reasoning. The resulting representations are handed to the Structure Module, an 8-block iterative module that directly outputs 3D rigid bodies. Crucially, the entire system recycles its predictions: the output pair representations and coordinates are fed back into the input for 4 complete passes.

Slide 4: Four facts, four design choices

Evita • 4:15–5:45

THE SLIDE (THE SHADOW): Clean single-line table matching the 4 biological facts to the 4 architectural design choices in AlphaFold 2. Bottom takeaway in blue alert.

[Evita slows down, lowering pitch for emphasis. This is the intellectual thesis of the presentation.]

EVITA: Here is the central conceptual thesis of our talk. AlphaFold's breakthrough does not stem from throwing raw, unconstrained compute at generic transformers. It succeeds because every structural inductive bias is a direct answer to a concrete physical or biological fact about proteins.

Consider these four facts:

1. **Fact 1**: An MSA is an unordered set of evolutionarily related sequences, but each sequence is a 1D chain. *Design choice*: Axial attention alternating along rows and columns.
2. **Fact 2**: Real 3D distances must close triangles: $d_{ik} \leq d_{ij} + d_{jk}$. *Design choice*: Triangle updates on the residue pair graph edges.
3. **Fact 3**: A physical molecule is invariant to global rotations and translations: the Lie group SE(3). *Design choice*: Local residue reference frames and Invariant Point Attention.

4. **Fact 4**: Amino acids are stereochemically chiral; mirror reflections are toxic unphysical molecules. *Design choice*: Frame Aligned Point Error (FAPE) loss in local coordinates.

In the second half of our talk, Ben will show that removing any one of these four design choices causes accuracy to degrade severely.

Slide 5: The two representations

Evita • 5:45–7:00

THE SLIDE (THE SHADOW): Left: MSA grid (sequences by residues, 256 channels). Right: Pair matrix (residues by residues, 128 channels). Unrotated horizontal labels: 'N_{seq} sequences', 'N_{res} residues'.

[Evita points to the blue MSA grid, then to the gray pair matrix.]

EVITA: Let us look inside the network's working memory. At every stage of the Evoformer trunk, AlphaFold maintains exactly two arrays: First, the MSA representation, $\mathbf{m}_{si} \in \mathbb{R}^{256}$. Here, row index s indexes the sequence in the alignment, column index i indexes the residue position, and each cell holds a 256-dimensional feature vector. The first row ($s = 1$) is the query sequence.

Second, the Pair representation, $\mathbf{z}_{ij} \in \mathbb{R}^{128}$. Here, row i and column j index pairs of residues along the protein chain. Each entry $\mathbf{z}_{ij}$ represents the geometric and physical relationship between residue i and residue j—such as expected spatial distance, chemical compatibility, or orientation.

Every single block of the 48 Evoformer layers reads from and writes to exclusively these two arrays.

Slide 6: The input: MSA representation

Evita • 7:00–8:15

THE SLIDE (THE SHADOW): Left: alignment matrix with correlated mutations highlighted in blue/red across columns 3 and 9. Right: Covariance intuition and DCA background.

[Evita points to columns 3 and 9 of the alignment.]

EVITA: Why does the MSA contain 3D spatial information? The answer lies in evolutionary co-variation. When a protein folds in a living cell, residues that are distant along the primary 1D chain may sit in direct physical contact in 3D space to stabilize a hydrophobic core or form a salt bridge.

If residue i mutates from a small hydrophobe to a bulky residue, the adjacent residue j in 3D space experiences intense selective pressure to mutate compensatorily to avoid steric clash. In 2011, Marks, Colwell, and colleagues demonstrated that analyzing correlated mutations across evolutionary history can reconstruct protein folds.

Prior models, including AlphaFold 1, compressed the MSA down to summary statistics: a 1D position-specific scoring matrix and 2D covariance tables. AlphaFold 2 retains the raw aligned sequences. This allows deep attention mechanisms to track high-order epistasis that summary statistics discard.

Slide 7: The input: Pair representation

Evita • 8:15–9:30

THE SLIDE (THE SHADOW): Graph representation of pairs: residues as nodes, pair vectors $\mathbf{z}_{ij}$ as directed edges. Linear bias with relative position encoding.

[Evita gestures to the pair graph.]

EVITA: Now consider the pair representation. Mathematically, $\mathbf{z}$ represents the edge features of a complete graph whose nodes are the residues.

At initialization, what do we know about residue pairs before seeing 3D structure? We know their primary sequence separation: $|i - j|$. We know whether residue i precedes residue j. AlphaFold encodes this relative sequence distance through a one-hot clipped positional embedding. Furthermore, if homologous experimental structures exist in the PDB, their $C\beta$–$C\beta$ distance maps and backbone dihedral angles are projected into the pair channels as template information.

Throughout the network, the pair representation serves as a spatial blackboard where geometric constraints are continuously refined.

Slide 8: The Evoformer block

Evita • 9:30–10:45

THE SLIDE (THE SHADOW): Detailed schematic of one Evoformer block: Row-wise attention with pair bias → Column-wise attention → Transition MLP → Outer product mean → Triangular multiplicative updates → Triangular self-attention → Transition MLP.

[Evita points to the two parallel tracks and the communication bridges between them.]

EVITA: This brings us to the core engine: the Evoformer block. AlphaFold stacks 48 identical Evoformer blocks in series.

Notice the dual-track structure. Information flows simultaneously through the MSA track at the top and the Pair track at the bottom. But they do not operate in isolation: First, the pair track injects geometric bias into the MSA attention logits. Second, the MSA track aggregates sequence covariation and writes directly back into the pair edges via an Outer Product Mean.

Let us examine the exact mathematical operations executing inside these blocks.

Slide 9: MSA row attention with pair bias

Evita • 10:45–12:00

THE SLIDE (THE SHADOW): Formula for row attention: $a_{ij}^s = \text{softmax}_j\left(\frac{1}{\sqrt{c}}\mathbf{q}_{si}^\top \mathbf{k}_{sj} + b_{ij}\right)$, where $b_{ij} = \mathbf{w}^\top \mathbf{z}_{ij}$. Elementwise output gating.

[Evita walks through the attention formula term by term.]

EVITA: Within the MSA track, the first operation is Row-wise Attention. In standard Transformers, attention queries and keys compute affinity purely from node embeddings: $\mathbf{q}_i^\top \mathbf{k}_j / \sqrt{c}$.

AlphaFold adds a crucial pair bias term:

$$a_{ij}^s = \text{softmax}_j\left(\frac{1}{\sqrt{c}}\mathbf{q}_{si}^\top \mathbf{k}_{sj} + \mathbf{w}^\top \mathbf{z}_{ij}\right). \tag{2}$$

The vector $\mathbf{z}_{ij}$ from the pair track is linearly projected to a scalar bias b_{ij} and added directly into the attention logit for every sequence s.

Think about what this means physically: if the pair track believes residue i and residue j are close in space, it injects a large positive bias into their attention weight across all sequences. Residues attend strongly to their spatial neighbors, not just their sequence neighbors. Finally, the attended values are modulated by a sigmoid gating vector $\sigma(\mathbf{g}_{si})$, suppressing noise from uninformative alignment regions.

Slide 10: The pair representation: triangle updates

Evita • 12:00–13:30

THE SLIDE (THE SHADOW): Left: Outer product mean formula. Right: Triangle graph diagrams showing incoming and outgoing edge updates over third node k. Bottom: Transition cue to Ben.

[Evita points to the triangle diagram, emphasizing the third node k.]

EVITA: How does information flow back from the MSA into the pairs? Through the Outer Product Mean. For every pair of columns i and j, the network computes the outer product of their features and averages across all aligned sequences:

$$\mathbf{z}_{ij} \leftarrow \mathbf{z}_{ij} + \frac{1}{N_{\text{seq}}} \sum_{s=1}^{N_{\text{seq}}} \mathbf{m}_{si} \otimes \mathbf{m}_{sj}. \tag{3}$$

Next comes one of the most brilliant mathematical innovations in AlphaFold: the Triangular Updates.

A matrix of pairwise distances in 3D Euclidean space cannot have arbitrary independent entries; it must strictly obey the triangle inequality: the distance between residue i and residue j is bounded by the path through any third residue k: $d_{ij} \leq d_{ik} + d_{jk}$.

AlphaFold enforces this graph-geometric consistency by updating edge (i, j) by marginalizing over all third nodes k:

$$\mathbf{z}_{ij} \leftarrow \mathbf{z}_{ij} + \sum_{k=1}^{N_{\text{res}}} \mathbf{a}_{ik} \odot \mathbf{b}_{jk}. \tag{4}$$

Two edges of a triangle combine via Hadamard product to update the third edge.

[Evita pauses, turns toward Ben, and gestures.]

At this point, after 48 Evoformer blocks, the network has assembled a highly refined 2D spatial graph. But how does AlphaFold convert this abstract graph into physical, 3D atomic coordinates in space while respecting the continuous symmetries of physics? For that, I hand over to Ben.

[Handover: Evita smoothly passes the presenter remote to Ben. Ben steps forward to stage center; Evita steps gracefully back to stage-left. Clear vocal and eye contact transition.]

3 Act II: Geometry, Structure Module, Training, and Frontiers

Slide 11: Invariant Point Attention (IPA) — Ben • 13:30–15:00

THE SLIDE (THE SHADOW): Left: Isometric 3D triad of residue frames i and j with 4 projected points each. Right: Attention formula with Euclidean distance squared in exponent, local coordinate transformation $T_i^{-1} \circ T_j$. Bottom: Takeaway in blue alert.

[Ben accepts the remote, clicks to Slide 11, and speaks with authoritative mathematical clarity.]

BEN: Thank you, Evita. We now arrive at the generative heart of AlphaFold: the Structure Module.

To predict 3D coordinates, machine learning faces a fundamental geometric hurdle: physical molecules are invariant to rigid motions. If you rotate or translate an entire protein in 3D space, its internal free energy and biological identity are strictly unchanged: the symmetry group is the special Euclidean group, $\mathrm{SE}(3) = \mathrm{SO}(3) \ltimes \mathbb{R}^3$.

AlphaFold does not represent atoms as arbitrary point clouds. It models every residue along the backbone as an independent rigid body frame:

$$T_i = (R_i, \vec{\mathbf{t}}_i) \in \mathrm{SE}(3), \tag{5}$$

where $\vec{\mathbf{t}}_i \in \mathbb{R}^3$ is the position of the Carbon-alpha atom, and rotation matrix $R_i \in \mathrm{SO}(3)$ defines the local orientation of the peptide plane.

Inside the Structure Module, residues communicate via Invariant Point Attention (IPA). Standard attention uses scalar queries and keys. IPA supplements scalar attention with 3D points placed in local residue coordinates:

$$\vec{\mathbf{q}}_i^{h,p} \in \mathbb{R}^3, \quad \vec{\mathbf{k}}_j^{h,p} \in \mathbb{R}^3. \tag{6}$$

These points are transformed into global space by the residue's current pose: $\vec{\mathbf{x}}_i = T_i \circ \vec{\mathbf{q}}_i = R_i \vec{\mathbf{q}}_i + \vec{\mathbf{t}}_i$. The attention weight depends directly on their Euclidean distance in 3D space:

$$a_{ij} = \mathrm{softmax}_j \left(\frac{1}{\sqrt{c}} \mathbf{q}_i^\top \mathbf{k}_j + b_{ij} - \frac{\gamma}{2} \sum_{p=1}^{P} \left\| T_i \circ \vec{\mathbf{q}}_i^p - T_j \circ \vec{\mathbf{k}}_j^p \right\|^2 \right). \tag{7}$$

Notice the mathematical invariance: if a global rotation and translation $T_{\text{global}} \in \mathrm{SE}(3)$ is applied to all frames, the global distance satisfies:

$$\| (T_{\text{global}} \circ T_i) \circ \vec{\mathbf{q}}_i - (T_{\text{global}} \circ T_j) \circ \vec{\mathbf{k}}_j \| = \| T_{\text{global}} \circ (T_i \circ \vec{\mathbf{q}}_i - T_j \circ \vec{\mathbf{k}}_j) \| = \| T_i \circ \vec{\mathbf{q}}_i - T_j \circ \vec{\mathbf{k}}_j \|. \tag{8}$$

The attention weights are rigorously invariant. When value points are aggregated, they are pulled back into frame i via $T_i^{-1} \circ T_j$, where T_{global} meets its inverse and cancels exactly. The invariance is mathematically exact; it does not need to be learned.

MATHEMATICAL CORE & DEEP LEARNING PRINCIPLES:

The $\mathrm{SE}(3)$ **Group Composition Law**: Let $T = (R, \boldsymbol{t}) \in \mathrm{SE}(3)$. The action on a point $\boldsymbol{x} \in \mathbb{R}^3$ is $T \circ \boldsymbol{x} = R\boldsymbol{x} + \boldsymbol{t}$. The composition of two frames $T_1 \circ T_2$ is:

$$(R_1, \boldsymbol{t}_1) \circ (R_2, \boldsymbol{t}_2) = (R_1 R_2, R_1 \boldsymbol{t}_2 + \boldsymbol{t}_1). \tag{9}$$

The inverse is $T^{-1} = (R^\top, -R^\top \boldsymbol{t})$. In the update step, $\Delta T_i = (\Delta R_i, \Delta \boldsymbol{t}_i)$ is predicted from invariant scalar features $\mathbf{s}_i$ via the exponential map $\Delta R_i = \exp(\hat{\boldsymbol{\omega}}_i)$, and composed locally: $T_i^{(k+1)} = T_i^{(k)} \circ \Delta T_i$, guaranteeing strict $\mathrm{SE}(3)$ equivariance.

Slide 12: Frame Aligned Point Error (FAPE) — Ben • 15:00–16:30

THE SLIDE (THE SHADOW): Diagram: Frame k in red, predicted atom in blue, true atom in black, dashed red distance line d_{ki}. FAPE loss formula. Clamping boundary at 10 Å.

[Ben points to the triad k and the two atom coordinates.]

BEN: Once the network outputs 3D coordinates, how do we train it?

One might naively propose standard RMSD. But RMSD is fatal for training neural networks: computing RMSD requires performing a global Kabsch alignment (via singular value decomposition) at every training step. SVD

alignment is numerically fragile, computationally slow, and worst of all, global alignment gradients allow an error in one distant flexible loop to perturb gradients across the entire stable core.

AlphaFold's solution is FAPE: Frame Aligned Point Error. Instead of aligning the prediction to the ground truth once globally, FAPE evaluates every atom from the perspective of *every single residue frame*:

$$\mathcal{L}_{\text{FAPE}} = \frac{1}{N_{\text{frames}} N_{\text{atoms}}} \sum_{k=1}^{N_{\text{frames}}} \sum_{i=1}^{N_{\text{atoms}}} \min\left(d_{\text{clamp}}, \left\| T_k^{-1} \circ \vec{\mathbf{x}}_i - (T_k^{\text{true}})^{-1} \circ \vec{\mathbf{x}}_i^{\text{true}} \right\|\right). \tag{10}$$

Notice three profound mathematical properties of FAPE:

1. **Global Invariance**: Because atoms are transformed into local frame coordinates via T_k^{-1}, FAPE is identically invariant to global rigid motions of either the prediction or the ground truth.
2. **Clamping Threshold**: The error is clamped at $d_{\text{clamp}} = 10$ Å. If two domains are misoriented by 30 Å, the gradient saturates to zero, preventing distant domain errors from destroying fine-grained atomic packing within a domain.
3. **Chirality Sensitivity**: Standard distance matrices are invariant to mirror reflections. But frames in AlphaFold are constructed via Gram–Schmidt: $\boldsymbol{e}_1$ along C$\alpha \to$ C, $\boldsymbol{e}_2$ in the peptide plane, and $\boldsymbol{e}_3 = \boldsymbol{e}_1 \times \boldsymbol{e}_2$. The cross product forces every frame to be right-handed. Under a reflection, the atoms flip but the frames remain right-handed, causing the local z-coordinate to negate and producing a massive FAPE penalty. FAPE enforces true L-amino acid stereochemical chirality.

SEMINAR DEFENSE & EXAM ANTICIPATION:

Possible Examiner Question: *Is FAPE a true mathematical distance metric?*

Mathematical Defense: Strictly speaking, FAPE is a *pseudometric*. It satisfies non-negativity ($\mathcal{L} \geq 0$), symmetry ($\mathcal{L}(X,Y) = \mathcal{L}(Y,X)$), and the triangle inequality ($\mathcal{L}(X,Z) \leq \mathcal{L}(X,Y) + \mathcal{L}(Y,Z)$). However, $\mathcal{L}(X,Y) = 0$ does not imply $X = Y$ in absolute coordinates, but rather that X and Y are identical up to a global rigid motion in SE(3). Hence, on the quotient space $\mathbb{R}^{3M}/\text{SE}(3)$, FAPE is a genuine metric.

Slide 13: Recycling: four iterations through the network

Ben • 16:30–17:30

THE SLIDE (THE SHADOW): Diagram of unrolled recycling passes: $m^{(0)}, z^{(0)} \to$ Block $\to m^{(1)}, z^{(1)} \to \cdots \to m^{(3)}, z^{(3)}$. Gradients stopped until final pass.

[Ben traces the recycling feedback loop.]

BEN: To squeeze maximum structural convergence out of the representations, AlphaFold introduces structural Recycling.

Instead of treating the 48 Evoformer blocks as a single forward pass, the network runs as an iterative dynamical system. At the end of the pass, the output pair representation $\mathbf{z}_{ij}$ and the predicted Carbon-beta pairwise distances from the frames are fed directly back into the input layer.

The network executes 4 recycling iterations during training. Crucially, backpropagation through time is disabled: gradients are stopped during the first three cycles and evaluated only on the fourth. This provides the representational capacity of a 192-layer deep network at the memory cost of only 48 layers.

Slide 14: Loss functions: seven terms

Ben • 17:30–18:45

THE SLIDE (THE SHADOW): Loss decomposition formula with 7 terms: Backbone FAPE, Sidechain FAPE, Distogram, Masked MSA, Torsion angles, pLDDT, and Structural violations.

[Ben gestures to the multi-task loss terms.]

BEN: Training a system this complex from scratch requires auxiliary supervision. The total loss $\mathcal{L}$ is a linear combination of seven objectives:

$$\mathcal{L}_{\text{total}} = 0.5\,\mathcal{L}_{\text{FAPE}}^{\text{backbone}} + 0.5\,\mathcal{L}_{\text{FAPE}}^{\text{sidechain}} + 0.3\,\mathcal{L}_{\text{dist}} + 2.0\,\mathcal{L}_{\text{msa}} + 0.01\,\mathcal{L}_{\text{pLDDT}} + 1.0\,\mathcal{L}_{\text{torsion}} + \mathcal{L}_{\text{viol}}. \tag{11}$$

Why so many losses? During early training epochs, FAPE gradients are noisy and uninformative because frames are initialized as identity matrices. The Distogram loss (a cross-entropy classification on 64 distance bins) guides 2D pair geometry. The Masked MSA loss forces the network to learn evolutionary protein language modeling like BERT. Finally, the Structural Violation loss imposes strict physical penalties for peptide bond steric clashes and bond length deviations.

Slide 15: Trunk intermediate structures

Ben • 18:45–20:00

THE SLIDE (THE SHADOW): Fig. 4b redrawn: GDT accuracy plotted over 192 Evoformer blocks across 4 runs. Green curve ORF8, Blue/Orange LmrP. Horizontal y-axis label atop axis: 'GDT'.

[Ben points to the two curves: fast-saturating LmrP vs slow-climbing ORF8.]

BEN: What is actually happening inside the Evoformer trunk during inference? In Figure 4b of the paper, DeepMind froze the trunk and attached a readout structure module after every single block across four recycling passes (192 blocks total).

Look at the trajectories: For target LmrP (in blue), the structure forms almost immediately: by block 25 of the very first recycling pass, the Global Distance Test (GDT) score exceeds 85. The remaining 160 blocks simply polish sidechain packing.

Now look at target ORF8 (in green), an elusive SARS-CoV-2 protein. At block 48, GDT is barely 40—an unrecognizable disordered tangle. It requires nearly 150 blocks of iterative triangle updates before the fold suddenly snaps into place. This demonstrates that AlphaFold is executing non-trivial iterative spatial refinement, not simple table lookup.

Slide 16: Confidence: pLDDT against measured lDDT

Ben • 20:00–21:15

THE SLIDE (THE SHADOW): Scatter plot: Predicted mean pLDDT vs Measured lDDT-Cα ($n = 10,795$ chains). Linear fit line (slope 0.997, $r = 0.76$). Horizontal y-axis label atop axis: 'measured lDDT-Cα'.

[Ben highlights the linear fit line and the high-confidence cluster.]

BEN: In real biological research, knowing *when* to trust a model is as important as the prediction itself.

AlphaFold outputs a calibrated confidence score per residue called pLDDT: predicted Local Distance Difference Test. The network does not predict a single scalar; a linear head over the final single representation predicts a categorical probability distribution over 50 discrete bins of local $C\alpha$ accuracy.

Look at the scatter plot over 10,795 experimental chains: the Pearson correlation between predicted pLDDT and experimentally measured lDDT is $r = 0.76$, with a linear regression slope of 0.997—an almost perfect 1-to-1 diagonal calibration.

When pLDDT > 90, sidechain packing is reliable for computational drug design. When pLDDT < 50, the region is not necessarily a model failure; in most cases, it corresponds to an intrinsically disordered protein region (IDR) that has no fixed structure in isolation.

Slide 17: Limitations: MSA depth and complexes

Ben • 21:15–22:30

THE SLIDE (THE SHADOW): Accuracy vs MSA depth curve (N_{eff}). Vertical red dashed line at 30. Steep drop below 30. Horizontal y-axis label atop axis: 'lDDT-Cα'.

[Ben points to the vertical red dashed line at $N_{eff} = 30$.]

BEN: Where does AlphaFold 2 break down?

First: Multiple Sequence Alignment depth. Look at the curve of accuracy against N_{eff}, the number of non-redundant effective sequences in the alignment. Above 30 related sequences, accuracy is high and plateaued. But as soon as N_{eff} drops below 30, accuracy plummets off a cliff. For orphan proteins, de novo designed proteins, or rapidly evolving antibody loops without an evolutionary family, AlphaFold 2 struggles.

Second: AlphaFold 2 was trained exclusively on isolated, static monomeric chains. But proteins in a living cell are dynamic: they undergo allosteric conformational switches, and over 60% operate as multi-protein complexes. Predicting static monomers cannot capture the full biochemical reality.

Slide 18: After AlphaFold 2: 2021 to 2025

Ben • 22:30–23:30

THE SLIDE (THE SHADOW): Timeline from 2021 to 2025: RoseTTAFold, 98.5% Human Proteome (AFDB), AlphaFold-Multimer, ESMFold, AlphaFold 3, Nobel Prize in Chemistry (2024), AlphaGenome (2025).

[Ben traces the timeline, pausing proudly at the gold Nobel disc.]

BEN: The release of AlphaFold 2 in 2021 triggered an unprecedented revolution across biological science.

In partnership with EMBL-EBI, DeepMind released the AlphaFold Protein Structure Database, expanding from the human proteome to over 214 million predicted structures—virtually all cataloged proteins known to science.

Soon after, AlphaFold-Multimer addressed protein-protein complexes. Meta AI released ESMFold, demonstrating that large language models trained on protein sequences could predict structures in seconds without building MSAs.

In 2024, Demis Hassabis and John Jumper were awarded the Nobel Prize in Chemistry alongside David Baker. And earlier this year, the architecture was generalized to AlphaGenome, predicting non-coding variant regulatory impact directly from DNA.

Slide 19: AlphaFold 3: which choices survived

Ben • 23:30–24:45

THE SLIDE (THE SHADOW): Table comparing the 4 AF2 choices against AlphaFold 3 (Nature 2024): MSA raw attention dropped; Triangles kept (48 blocks); Frames/IPA dropped for Diffusion; FAPE dropped for Aligned MSE. Chirality violations 4.4%.

[Ben leans in. This is the critical theoretical takeaway comparing AF2 to AF3.]

BEN: In 2024, DeepMind published AlphaFold 3, predicting complexes of proteins, DNA, RNA, and drug ligands. Looking back at our four design choices from Slide 4, which ones survived in AlphaFold 3?

Notice the verdict:

1. **Choice 1 (MSA attention)**: Largely dropped. AF3 uses a small 4-block MSA module and does not maintain the MSA array, proving that pair representations carry the true geometric load.
2. **Choice 2 (Triangle updates)**: Kept completely intact! The 48-block Pairformer retains triangle multiplicative updates and attention. The spatial metric inductive bias remains indispensable.
3. **Choice 3 (Frames and IPA)**: Dropped. Replaced by a 3D score-based Diffusion module operating on unconstrained Cartesian coordinates.
4. **Choice 4 (FAPE)**: Dropped. Replaced by an aligned mean squared error diffusion loss.

This reflects Rich Sutton's *Bitter Lesson*: generic generative diffusion scales better across diverse chemical modalities than rigid-body protein frames.

However, there is a catch: by abandoning right-handed local frames and FAPE, AlphaFold 3 lost exact SE(3) equivariance and stereochemical chirality! AF3 produces 4.4% chirality violations and relies heavily on multi-seed ranking and physical clash filters to discard unphysical mirror reflections.

Slide 20: Summary: four design choices, measured

Ben • 24:45–25:30

THE SLIDE (THE SHADOW): Component ablation scorecard: No raw MSA (−2.2), No triangles (−4.6), No IPA (−2.3), No recycling (−4.5), No frames (mirrored structures). Final takeaway sentence.

[Ben delivers the final synthesis with resonance.]

BEN: To conclude: the four biological facts we introduced at the start became four mathematical design choices. The ablation study proves their necessity: Removing sequence attention costs 2.2 GDT. Removing triangle updates costs 4.6 GDT. Removing IPA costs 2.3 GDT. Removing recycling costs 4.5 GDT. And removing frames causes the model to produce mirror-image molecules.

AlphaFold 2 solved protein structure prediction not by ignoring biology, but by translating the geometry of physics and evolution into end-to-end differentiable neural architecture. Thank you very much.

[Evita steps forward to join Ben at stage center. Both bow slightly and smile. Applause pause.]

4 Act III: Seminar Defense, Moderated Discussion, and Backups

Slide 21: Exam question — Evita & Ben • 25:30–27:30

THE SLIDE (THE SHADOW): Two-column slide: Left box shows course assignment prompt (Prof. Valentina Boeva). Right box shows structured solution breakdown: (1) Inductive bias, (2) Loss formulation, (3) Genomic impact.

[Evita addresses the assignment prompt; Ben outlines the theoretical derivation.]

EVITA: We now open the discussion and examination segment of our presentation, beginning with the official seminar exam question assigned for course 263-5351-00L.

BEN: To answer this question rigorously from a machine learning perspective, we break the solution into three structural pillars: First, the architectural inductive bias: how the interplay between Evoformer triangle updates and Invariant Point Attention guarantees geometric consistency. Second, the mathematical loss formulation: how FAPE provides non-saturated gradients on SE(3)/SO(3) while breaking reflection symmetry. Third, genomic impact: how calibrated pLDDT enables genome-wide variant effect prediction without laboratory ground truth.

Slide 22: Questions for the audience — Evita & Ben • 27:30–32:00

THE SLIDE (THE SHADOW): Three bold discussion questions: (1) Inductive bias vs unconstrained diffusion, (2) Has the network learned physics or evolution?, (3) pLDDT reliability in genomics. Bottom banner with contact info and GitHub link.

[Evita moderates Question 1; Ben moderates Question 2; both address Question 3.]

EVITA: We would now like to invite our peers into an interactive debate. We pose three fundamental questions:

Question 1: *AlphaFold 2 hardcoded* SE(3) *equivariance and stereochemical chirality into its architecture and loss. AlphaFold 3 dropped both in favor of unconstrained diffusion. When is geometric inductive bias indispensable, and when is unconstrained generative modeling preferable?*

[Evita takes 2 peer responses from the audience. Summarizes: inductive bias is critical when data is scarce (PDB scale); unconstrained diffusion dominates when scaling across heterogeneous multi-modal complexes, provided post-hoc filtering is affordable.]

BEN: **Question 2**: *Given that accuracy drops precipitously below 30 related sequences, has AlphaFold truly learned the physical energy landscape of protein folding, or has it learned a statistical compression of evolutionary variation? What experiment would settle this?*

[Ben takes 2 peer responses. Highlights: de novo designed proteins (David Baker's Hallucination/RFdiffusion) fold without natural MSAs, suggesting partial physical learning, yet true ab initio folding from single sequences remains the frontier of ESMFold.]

Slide 23–24: References: Primary Literature & Machine Learning — Evita & Ben • 32:00–33:00

THE SLIDE (THE SHADOW): Two full slides listing standardized [FWP+19] citations: Jumper 2021, Tunyasuvunakool 2021, Evans 2021, Baek 2021, Abramson 2024, Marks 2011, Lin 2023, Avsec 2025, Devlin 2019, Xie 2020, Sutton 2019.

EVITA & BEN: For complete derivations and literature provenance, all citations are cataloged here on Slides 23 and 24.

Slide 25: Resources: AlphaFold at ETH — Evita & Ben • 33:00–35:00

THE SLIDE (THE SHADOW): Two cards: Tooling & Deployment on left (ColabFold, Euler cluster GPU batch jobs, AFDB). Repository & Contacts on right (GitHub repo link, email contacts, seminar details).

[This slide remains prominently displayed on the auditorium screen throughout the remaining open Q&A.]

BEN: For researchers at ETH Zürich looking to deploy AlphaFold in their genomics pipelines: you can run ColabFold locally or submit batch GPU jobs on the ETH Euler cluster using our SLURM submission scripts. All TikZ drawing sources, mathematical derivations, and these screenplay notes are open-source on our GitHub repository: `github.com/BenBullinger/ML4Genomics-Presentation-AF2`.

EVITA: Thank you once again. We are now delighted to take any questions from Prof. Boeva, the teaching assistants, and the audience.

5 Technical Defense Manual: Backup Slides (1/14 to 14/14)

When tough technical questions are posed during the examination segment, the speakers can immediately jump to the designated backup slide. Below is the exact mathematical script for each backup.

5.1 Backup (1/14): Why is IPA invariant to rigid motions?

Slide Counterpart: *Backup (1/14): Why is IPA invariant to rigid motions? (SI 1.8.2, Alg. 22)*

Spoken Script (Ben): "If asked why IPA is invariant: the only geometry entering the attention weights is the Euclidean distance between points placed by residues i and j in their own frames:

$$\left\| (T_{\text{global}} \circ T_i) \circ \vec{\boldsymbol{q}}_i - (T_{\text{global}} \circ T_j) \circ \vec{\boldsymbol{k}}_j \right\|^2 = \left\| T_{\text{global}} \circ (T_i \circ \vec{\boldsymbol{q}}_i - T_j \circ \vec{\boldsymbol{k}}_j) \right\|^2 = \left\| T_i \circ \vec{\boldsymbol{q}}_i - T_j \circ \vec{\boldsymbol{k}}_j \right\|^2. \tag{12}$$

Because the Euclidean norm is invariant under any rigid motion $T_{\text{global}} \in \text{SE}(3)$, the attention weights a_{ij} are completely unchanged. When value vectors are aggregated, they are mapped back into local frame i:

$$(T_{\text{global}} \circ T_i)^{-1} \circ \sum_j a_{ij} (T_{\text{global}} \circ T_j) \circ \vec{\boldsymbol{v}}_j = T_i^{-1} \circ T_{\text{global}}^{-1} \circ T_{\text{global}} \circ \sum_j a_{ij} T_j \circ \vec{\boldsymbol{v}}_j = T_i^{-1} \circ \sum_j a_{ij} T_j \circ \vec{\boldsymbol{v}}_j. \tag{13}$$

T_{global} cancels identically against its inverse. Invariance is an exact algebraic identity, not an approximation."

5.2 Backup (2/14): Why is the structure module equivariant?

Slide Counterpart: *Backup (2/14): Why is the structure module equivariant? (SI 1.8.2, Alg. 20)*

Spoken Script (Ben): "The structure module is SE(3)-equivariant because the frame update $T_i^{\text{upd}} = (\Delta R_i, \Delta \vec{\boldsymbol{t}}_i)$ is predicted directly from scalar features $\mathbf{s}_i$, which are invariant under global rotation. Because the update is composed in local coordinates:

$$(T_{\text{global}} \circ T_i) \circ T_i^{\text{upd}} = T_{\text{global}} \circ (T_i \circ T_i^{\text{upd}}). \tag{14}$$

Applying a rigid transformation to the input structure before the block produces the exact same result as applying it to the output structure after the block."

5.3 Backup (3/14): Origin of stereochemical chirality

Slide Counterpart: *Backup (3/14): Origin of stereochemical chirality (SI 1.8.1, Alg. 21)*

Spoken Script (Ben): "Residue frames are constructed via Gram–Schmidt orthogonalization on $(\text{N}, \text{C}\alpha, \text{C})$: $\boldsymbol{e}_1 = \frac{\boldsymbol{x}_{\text{C}} - \boldsymbol{x}_{\text{C}\alpha}}{\|\boldsymbol{x}_{\text{C}} - \boldsymbol{x}_{\text{C}\alpha}\|}$, $\boldsymbol{e}_2$ in the N–Cα–C plane, and $\boldsymbol{e}_3 = \boldsymbol{e}_1 \times \boldsymbol{e}_2$. By definition of the vector cross product, the frame is strictly right-handed. If all atomic coordinates undergo spatial inversion (reflection $\boldsymbol{x} \mapsto -\boldsymbol{x}$), the frames do not reflect: Gram–Schmidt continues to construct right-handed frames. In local frame coordinates, the z-coordinate negates: $(T_i^{-1} \circ \boldsymbol{x}_j)_z \mapsto -(T_i^{-1} \circ \boldsymbol{x}_j)_z$. FAPE evaluates $\sum |(T_i^{-1} \circ \boldsymbol{x}_j)_z|$, penalizing the mirrored structure with a massive loss unless the molecule is strictly planar. Models trained with reflection-blind dRMSD produce 50% mirror images; FAPE eliminates them completely."

5.4 Backup (4/14): What does FAPE measure?

Slide Counterpart: *Backup (4/14): What does FAPE measure? (SI 1.9.2, Alg. 28)*

Spoken Script (Ben): "FAPE evaluates all $N_{\text{frames}} \times N_{\text{atoms}}$ local coordinates clamped at 10 Å. In Supplementary Section 1.9.4, Jumper et al. prove that FAPE is bounded below by optimal Kabsch RMSD:

$$\mathcal{L}_{\text{FAPE}} \geq \min_{R \in \text{SO}(3), \boldsymbol{t} \in \mathbb{R}^3} \sqrt{\frac{1}{M} \sum_{i=1}^{M} \|R\boldsymbol{x}_i + \boldsymbol{t} - \boldsymbol{x}_i^{\text{true}}\|^2}. \tag{15}$$

Thus, FAPE reaches zero if and only if the predicted and true point sets coincide under a proper rigid motion. Furthermore, FAPE satisfies the triangle inequality on structures, establishing it as a rigorous pseudometric on $\mathbb{R}^{3M}/\text{SE}(3)$."

5.5 Backup (5/14): Is AlphaFold 2 a graph neural network?

Slide Counterpart: *Backup (5/14): Is AlphaFold 2 a graph neural network? (Bronstein et al., 2021)*

Spoken Script (Evita): "In the formal geometric deep learning framework of Bronstein et al., AlphaFold 2 is an edge-attributed Graph Neural Network. Residues u are nodes with scalar features $\mathbf{s}_u$ and frame attributes $T_u \in \mathrm{SE}(3)$. Pairs (u, v) are directed edges with attributes $\mathbf{z}_{uv}$. The Evoformer and Structure Module implement message passing $\mathbf{h}_u = \phi(\mathbf{x}_u, \bigoplus_v \psi(\mathbf{x}_u, \mathbf{x}_v, \mathbf{e}_{uv}))$, where IPA passes geometric messages between nodes, and triangle updates pass messages between edges."

5.6 Backup (6/14): What does each block compute?

Slide Counterpart: *Backup (6/14): What does each block compute? (SI Algorithms 6 to 32)*

Spoken Script (Evita): "This table maps all 11 core updates to their formal algorithms in the Supplementary Information: lines 1–7 describe the 48 Evoformer blocks (Row/Column Attention, Transition MLPs, Outer Product Mean, Triangle Multiplications, Triangle Attention); lines 8–10 describe the 8 Structure Module iterations (IPA, Backbone Update); line 11 defines Recycling embedding."

5.7 Backup (7/14): What exactly did each ablation remove?

Slide Counterpart: *Backup (7/14): What exactly did each ablation remove? (SI 1.13)*

Spoken Script (Ben): "The ablation study in Supplementary Section 1.13 reveals critical non-linear synergies. Removing IPA costs 2.3 GDT. Removing recycling costs 4.5 GDT. But removing *both IPA and recycling simultaneously* costs a catastrophic 16.3 GDT. The components act synergistically: recycling gives IPA the iterative depth needed to refine difficult topologies."

5.8 Backup (8/14): How is confidence predicted?

Slide Counterpart: *Backup (8/14): How is confidence predicted? (SI 1.9.6, Alg. 29)*

Spoken Script (Ben): "Confidence is trained with self-distillation. The pLDDT head takes single representation $\mathbf{s}_i$ and outputs logits over 50 discrete bins representing intervals of $[0, 100]$ in lDDT-$C\alpha$. It is trained using cross-entropy against the model's own ground-truth error. Similarly, the pairwise head outputs Predicted Aligned Error (PAE) over 64 distance bins (0–32 Å), allowing researchers to gauge domain-domain relative orientation confidence."

5.9 Backup (9/14): How was it trained?

Slide Counterpart: *Backup (9/14): How was it trained? (Methods & SI 1.3, Table 4)*

Spoken Script (Ben): "Training executed in two stages across 128 TPUv3 cores for 11 days per model. Stage 1 trained on 256-residue crops over 10^7 samples for 7 days. Stage 2 increased crop size to 384 residues, lowered learning rate, and switched on the structural violation loss for 1.5×10^6 samples (4 days). Training utilized 170k PDB structures augmented with 350k self-distilled high-confidence Uniclust30 predictions comprising 75% of each training batch."

5.10 Backup (10/14): AlphaFold 3: further changes

Slide Counterpart: *Backup (10/14): AlphaFold 3: further changes (Abramson et al., 2024)*

Spoken Script (Ben): "Beyond diffusion, AlphaFold 3 unifies chemical inputs: proteins, DNA, RNA, ions, and small-molecule ligands are tokenized into a common embedding space. The pairformer uses 48 blocks with no MSA track retention. Confidence is trained on 20-step mini-rollouts, and generation samples 25 trajectories across 5 random seeds to overcome diffusion hallucination."

5.11 Backup (11/14): MSA row attention with pair bias

Slide Counterpart: *Backup (11/14): MSA row attention with pair bias (Suppl. Fig. 2, Alg. 7)*

Spoken Script (Evita): "Supplementary Figure 2 visualizes how the pair representation biases attention weights along rows. The pair tensor $\mathbf{z}_{ij}$ is projected to scalar bias b_{ij}, ensuring that every homologous sequence in the alignment attends to positions that are physically close in 3D space."

5.12 Backup (12/14): Evoformer: columns and outer product mean

Slide Counterpart: *Backup (12/14): Evoformer: columns and outer product mean (Suppl. Figs. 3–5)*

Spoken Script (Evita): "Supplementary Figures 3 to 5 illustrate column-wise attention and the outer product mean. Column attention aggregates information across sequences at position i. The outer product mean computes $\mathbf{m}_{si} \otimes \mathbf{m}_{sj}$ and averages over sequences, transferring correlated mutation signals directly into the pair edge representation."

5.13 Backup (13/14): Prediction and experiment superposed

Slide Counterpart: *Backup (13/14): Prediction and experiment superposed (Fig. 1b–d)*

Spoken Script (Evita): "This figure highlights CASP14 target superpositions across three scales: isolated backbone alignment (0.8 Å RMSD), rotamer sidechain accuracy around catalytic metal ions, and multi-domain inter-domain orientation across a 2,180-residue single chain solved without human intervention."

5.14 Backup (14/14): The AlphaFold 3 architecture

Slide Counterpart: *Backup (14/14): The AlphaFold 3 architecture (Nature 2024, Fig. 1d)*

Spoken Script (Ben): "Figure 1d from Abramson et al. illustrates the AF3 diffusion trunk. Notice that the Evoformer is replaced by the Pairformer, and the Structure Module is replaced by a 3D score-based diffusion model. Denoising random Gaussian coordinates eliminates rigid-body frames, enabling flexible all-atom modeling at the expense of post-hoc chirality ranking."