Presentable Debugging with LLVManim

Benjamin Houle
Dept. of Computer Science
University of Massachusetts Lowell
Lowell, Massachusetts, USA
Benjamin_Houle@student.uml.edu

Ebenezer Oloyede
Dept. of Computer Science
University of Massachusetts Lowell
Lowell, Massachusetts, USA
Ebenezer_Oloyede@student.uml.edu

Lily Grippo
Dept. of Computer Science
University of Massachusetts Lowell
Lowell, Massachusetts, USA
Lily_Grippo@student.uml.edu

Mohammad Ahmed
Dept. of Computer Science
University of Massachusetts Lowell
Lowell, Massachusetts, USA
ahmedzubair16dec@gmail.com

***Abstract*—LLVManim is a code visualization tool that generates aesthetically pleasing animations of control flow and memory operations from LLVM IR. Over the course of a single semester, we designed and implemented a three-layer pipeline—Ingestion, Transformation, and Rendering—that parses `.ll` files with `LLVMLite`, derives a typed intermediate scene graph, and renders animations through Manim Community Edition. The finished tool supports three animation modes (basic stack view, rich IR spotlight, and a three-column SSA panel), a CFG traversal animation driven by Graphviz layout, and machine-readable JSON and DOT export. The implementation comprises 26 Python modules validated by 302 automated tests at 84% line coverage, enforced by a four-stage quality gate (Ruff, Pyright, import-linter, pytest). LLVManim demonstrates that presentation-quality program visualization can be made accessible through a simple command-line interface, eliminating the need for manual Manim scripting or post-processing of LLVM's utilitarian graph output.**

CCS Concepts: **• Human-centered computing → Visualization → Visualization systems and tools → Visualization toolkits; • Software and its engineering → Software notations and tools → Compilers; • Applied computing → Education → Interactive learning environments**

***Index Terms*—program visualization, code animation, LLVM, static analysis, control flow graphs, memory visualization, educational tools, Manim, compiler infrastructure, presentation tools**

I. Introduction

Despite static analysis and data visualization being among the oldest concepts in computer science, disappointingly few graphic designers have been significantly interested in the former. While plenty of tools exist for creating control flow graphs or visualizing the stack, the majority of these favor a "function over form" paradigm that focuses on creating lightweight, readable output, assuming the user is more concerned with the information than its presentation. However, this assumption does not always hold: presenting in any context, such as at a conference or school, generally favors quickly digestible and visually appealing content over static, large blocks of text. In these cases, the presenter is forced to choose between using the unappealing generated visualization and the slog of creating something presentable for themselves.

We developed LLVManim to address this problem. By pairing LLVM's powerful static analysis infrastructure with the Manim animation library, the tool automatically generates professional-quality visualizations from LLVM Intermediate Representation (IR) and runtime traces. Through a simple command-line interface, users can produce animated stack walkthroughs, IR spotlight views with Static-Single-Assignment (SSA) value tracking, Control Flow Graph (CFG), which represents the execution paths between basic blocks in a program, traversal animations, and machine-readable scene graph exports—all without writing any Manim code or manually post-processing compiler output.

The remainder of this paper describes the tools and techniques that informed our design (Section II), the system architecture (Section III), the results of our implementation (Section V), lessons learned (Section VI), and conclusions (Section VII).

II. Related Work

Three prior projects directly shaped LLVManim's design: PythonTutor's step-by-step execution visualization, LLVM's existing analysis infrastructure and its output limitations, and the Manim animation library that serves as our rendering backend. Each is examined in turn.

A. PythonTutor

PythonTutor [1] is a widely used educational tool for visualizing program execution, originally developed to help novices build accurate mental models of how code runs. Its core contribution is a step-by-step execution trace—illustrated in Fig. 1—that exposes stack frames, heap objects, and control flow in a concrete, visual manner. As described by its creator, Philip J. Guo, PythonTutor aims to "help people overcome a fundamental barrier to learning programming: understanding what happens as the computer runs each line of code" [2].

PythonTutor has been shown to be effective in improving students' understanding of programming concepts; Guo's further studies demonstrated significant learning gains when



Fig. 1: Example PythonTutor.com output showing a step-by-step execution trace with stack frames and heap objects.

PythonTutor was used as a supplement to traditional instruction [3]. This demonstrates the educational value of connecting code execution to visual representations, as well as the benefits of an accessible, interactive tool.

However, the visualizations produced by PythonTutor are relatively basic and not suitable for presentation purposes. PythonTutor's primary focus is on clarity and educational value rather than aesthetics, resulting in output that may be difficult to read or visually unappealing when projected to an audience. This, along with the fact that the tool is web-based and not designed for offline use, makes it less than ideal for use in settings where visual impact is important, such as conference presentations. PythonTutor is additionally restricted by its limited customization options, minimal library of visualization methods, and support for only C, C++, Java, Javascript, and Python.

B. LLVM Analysis and Transform Passes

LLVM has emerged as the de-facto standard compiler infrastructure for modern software development, powering everything from the development environment for Apple operating systems to cutting-edge systems research efforts. Its adoption by the compiler community can be attributed to several key strengths—a modular architecture that separates language frontends from optimization backends, an extensive suite of analysis and transformation passes that expose deep insights into program behavior, and robust support for over 30 programming languages, including those supported by PythonTutor. LLVM even provides users with an API to define their own language [4].

At the core of LLVM's value proposition for code analysis is its Intermediate Representation, a low-level and platform-independent format that captures program semantics in a standardized way. This IR serves as the foundation for powerful built-in analysis passes that can generate control flow graphs, dominator trees, data flow analyses, and detailed memory access patterns. For compiler developers and researchers, these capabilities are invaluable—LLVM effectively solves the hard problem of extracting structured information from code, allowing them to focus on higher-level tasks like optimization or verification [5].

However, LLVM's visualization capabilities tell a different story. The standard approach for visualizing analysis results relies on generating DOT[1] files through passes like `-dot-cfg` or `-view-cfg`, which are then rendered using Graphviz [6]. While functionally correct, the resulting diagrams—an example of which is shown in Fig. 2—embody a strictly utilitarian aesthetic: monochrome nodes and edges, densely packed labels filled with LLVM IR instructions, and layouts optimized for completeness rather than clarity. This "function over form" philosophy serves well enough as a developer tool for debugging optimizer passes, but it fails as a solution for communication beyond that narrow domain.

The barrier extends beyond mere aesthetics. Interpreting these diagrams requires familiarity with LLVM IR syntax—understanding what "`%4 = load i32, i32* %3`"[2] means demands compiler knowledge that most audiences lack. The visualizations are fundamentally static images with no mechanism for progressive disclosure or animation, forcing presenters to mentally simulate execution flow while pointing at a frozen graph. Moreover, customization options are severely limited; changing colors, adjusting layouts, or highlighting specific execution paths requires manual post-

[1] A plain-text graph description language used by Graphviz to define nodes and edges for rendering graphs.

[2] This instruction loads a 32-bit integer from the memory address stored in `%3` into the register `%4`.



Fig. 2: Example Control-Flow Graph (CFG) using LLVM `-dot-cfg` pass. While technically accurate, the visualization prioritizes information density over visual clarity.

processing in external tools, completely defeating the purpose of automated generation.

In essence, LLVM provides extraordinarily powerful analysis capabilities but pairs them with visualization tools that assume their primary consumer is someone who already understands what they are looking at. This creates a frustrating gap: rich semantic information about program behavior can be automatically extracted, but it cannot be automatically presented in a way that serves educational or presentational contexts. LLVManim was built to bridge this gap by maintaining LLVM's analytical rigor while replacing its austere output with animations designed for human communication rather than machine precision.

C. Manim

The Manim library [7] was originally developed by Grant Sanderson [8] for his educational YouTube channel "3Blue1Brown" [9] to create animations of mathematical and computer-science concepts. Since its release, the channel has accumulated over 6 million subscribers, demonstrating the educational impact of smooth, precisely choreographed animations (Fig. 3) that build intuition about abstract concepts. Given this history, Manim represented an excellent candidate for creating high-quality educational visualizations of program behavior.

Manim's strength lies in its ability to programmatically generate animations with mathematical precision. Instead of tedious keyframe animation, users write Python code to determine how objects should appear, change, and interact. Manim can render 3D scenes, typeset LaTeX equations, and output crisp 60 fps animations suitable for anything from YouTube tutorials to academic conferences. For education, its capacity to make complicated ideas—like matrix transformations, function composition, or program flow—tangible and understandable by systematically unfolding them is particularly valuable.

Yet this power comes with a barrier to entry. A professor preparing a single lecture, or a researcher creating visualizations for a conference talk, may have a clear idea of what they want to show—perhaps how a recursive function builds up its stack—but writing Manim code for it requires a distinct



Fig. 3: Examples of 3Blue1Brown videos on Computer Science topics [10]. The thumbnails show a variety of animation styles, from 3D scenes to 2D diagrams, all rendered with Manim.

skill set. LLVManim addressed this challenge by automatically translating program semantics into Manim scenes, thereby eliminating the barrier of manual coding between LLVM's analytical power and Manim's visual sophistication.

III. LLVMANIM SYSTEM DESIGN

LLVManim bridges the gap between two observations:

1) Methods exist to quickly generate code visualizations, but they produce output that is unappealing for presentation purposes.
2) The Manim library can produce visually impressive animations, but using it requires significant manual effort.

By automating the translation from LLVM IR to Manim scenes, educators and tech leads alike can produce presentation-ready visualizations without needing to compromise between style and accessibility.

A. Design Goals

The following design requirements guided the implementation of LLVManim:

- **Simple CLI:** A command-line interface that accepts `.ll` files, selects visualization options via flags, and produces output with minimal configuration.
- **LLVM IR Parsing:** Extraction of control flow, memory operations, and SSA value information from LLVM IR using the `LLVMLite` [11] Python binding.
- **Multiple Animation Modes:** Several rendering modes offering different levels of detail—from a compact stack-only view to a full three-column layout showing IR source, SSA values, and the call stack simultaneously.
- **IR Instruction Coverage:** Support for the most common LLVM IR instructions (`alloca`, `load`, `store`, `call`, `ret`, `br`, binary operations, and comparisons), enabling visualization of a wide range of programs.
- **Machine-Readable Export:** JSON scene graph and Graphviz DOT output for integration with external tools and downstream analysis.
- **Testability and Quality:** A comprehensive automated test suite and multi-stage quality gate to maintain correctness throughout development.

Deliverables:

- A command-line tool that accepts LLVM IR as input and produces animations, DOT graphs, or JSON scene data as output.
- A library of reusable Manim scene components for visualizing control flow and stack operations.
- Sample visualizations demonstrating LLVManim on standard test programs.
- Documentation covering installation, usage, CLI flags, and supported IR constructs.
- A test suite of 302 automated tests with 84% line coverage.

B. Architecture

LLVManim is implemented as a three-layer pipeline—**Ingestion**, **Transformation**, and **Render**—orchestrated by a dedicated **CLI** entry point. The high-level structure is shown in Fig. 5. Layer boundaries are enforced at build time by `import-linter`, ensuring that no module imports from a downstream layer. The entire codebase is written in Python 3.12 and managed with `uv` [12].



Fig. 4: CLI dispatch flow. Each command flag (`--json`, `--draw`, `--animate`, `--cfg-animate`) shares the Ingest pipeline and branches to the appropriate Transform and Render stages.

1) CLI Entry Point: The `llvmanim.cli` module is the user-facing entry point. It accepts LLVM IR files and orchestrates the three pipeline layers via `argparse`; example usage is shown in Listing 1.

```
# Export JSON scene graph + Graphviz DOT/PNG
uv run llvmanim input.ll --json --draw --outdir
↪  out/
# Render basic stack animation
uv run llvmanim input.ll --animate --ir-mode
↪  basic --outdir out/
# Render rich IR spotlight with SSA panel
uv run llvmanim input.ll --animate --ir-mode
↪  rich-ssa --speed 1.5 --outdir out/
# CFG traversal animation
uv run llvmanim input.ll --cfg-animate --dot-cfg
↪  main.dot --import-trace trace.json --outdir
↪  out/
```

Listing 1: CLI usage

The CLI supports multiple modes of operation, including JSON export, static CFG drawing, stack animation with three IR detail levels, and CFG traversal animation with optional trace import. Each command flag routes through the shared Ingest pipeline to the appropriate Transform and Render stages, as detailed in Fig. 4. When the tool encounters unsupported IR constructs, missing debug metadata, or malformed input, it emits a descriptive error message and continues processing the remainder of the program where possible.

2) Ingestion Layer: The Ingestion layer extracts program structure from LLVM IR. It uses the `LLVMLite` Python binding to parse `.ll` files and also supports importing precomputed data from JSON.

- **`llvm_events.py`:** Parses an LLVM module and emits a `ProgramEventStream`—a typed sequence of `IREvent` records. Each event carries the function name, block name, opcode, full instruction text, a classified `EventKind` (one of `alloca`, `load`, `store`, `binop`, `compare`, `call`, `ret`, `br`, or `other`), its index within the function, debug line number, and operand list. Typed CFG edges are extracted directly from `LLVMLite` terminator operands (`br`, `switch`, `invoke`, `indirectbr`, `callbr`) with true/false labels on conditional branches.
- **`cfg_edge_io.py`:** Serializes and deserializes `CFGEdge` lists to JSON, enabling round-trip import/export of control-flow edges via dedicated CLI flags.
- **`analysis_metadata_io.py`:** Loads and saves dominator-tree and loop-analysis metadata as JSON, supporting round-trip import and export via CLI flags.
- **`trace_io.py`:** Reads and writes runtime path traces as JSON (`--import-trace` / `--export-trace`), used for overlay visualization in CFG traversal animations.
- **`dot_layout.py`:** Parses a Graphviz DOT file produced by `opt -passes=dot-cfg` and computes a `DotLayout` with node positions and edge routes for the CFG animation scene.



Fig. 5: Detailed module-level architecture. The Ingestion layer collects LLVM IR and metadata, the Transformation layer maps it to an intermediate scene graph, and the Rendering layer renders animations or exports artifacts.

- **`display_lines.py`:** Cleans raw IR text into per-function line lists used by the rich animation panels.

3) Transformation Layer: The Transformation layer converts the ingest output into an intermediate scene graph and execution traces suitable for rendering. The complete data model spanning all three layers is shown in Fig. 6.

- **`models.py`:** Defines the core data model—`SceneGraph`, `SceneNode`, `SceneEdge`, `CFGBlock`, `TraceOverlay`, and `BlockMetadata`. Also defines `AnimationCommand` and `ActionKind`, the typed animation primitives consumed by the Render layer. Nodes carry a `kind` string and an open `properties` dict, with an optional `animation_hint` string. `SceneGraph` embeds an ordered `commands` list alongside its nodes and edges.
- **`scene.py`:** The `build_scene_graph` function groups events by function and block, attaches typed CFG edges, assigns block roles, applies optional domtree/loop metadata, and populates `SceneGraph.commands` via the overlay builder. `build_stack_scene_graph` produces a call-tree-ordered `SceneGraph` with a fully populated `commands` list, translating the parsed `ProgramEventStream` directly into typed `AnimationCommand` records (carrying `ActionKind`, `target`, and `params`) ready for consumption by the Render layer.
- **`trace.py`:** The `build_execution_trace` function produces a list of `TraceStep` or `RichTraceStep` records capturing the execution order with optional SSA result values for `binop`, `compare`, and `load` instructions.

4) Render Layer: The Render layer renders the scene graph using Manim Community Edition [13] and provides export functionality. All scenes extend `CommandDrivenScene`, a base class that iterates over the `SceneGraph.commands` list and dispatches each `AnimationCommand` to a registered handler. The complete type hierarchy—from Ingest types through Transform intermediates to the Render dispatch classes—is shown in Fig. 6.

- **Animation Modes:** The tool supports three stack-rendering modes using `--ir-mode` flags, all driven by `StackRenderer`—a `CommandDrivenScene` subclass. Each mode consumes the same `AnimationCommand` records (detailed in Fig. 6) but presents progressively more detail. Specific information on the implemented modes is provided in the *Results* Section V-C.
- **CFG Traversal:** `--cfg-animate` renders an animated walk through the control-flow graph using `CFGRenderer` (another `CommandDrivenScene` subclass) with DOT-derived node positions (`--dot-cfg`) and a runtime trace (`--import-trace`). If no trace is provided, a static DFS trace is derived automatically.
- **Export:** Static artifacts complement the animated output.
  - `--json`: Writes a machine-readable scene graph (`scene_graph.json`).
  - `--draw`: Writes `cfg_main.dot` and, when Graphviz is available, a rendered `cfg_main.png`.
- **Rendering:** Manim CE renders MP4 or GIF output. GIF conversion uses an `ffmpeg` palette workflow to reduce peak memory usage. The `--preview` flag opens the rendered animation in a viewer.

IV. Risk Evaluation and Mitigation

Prior to implementation, we identified and categorized the primary risks to the project across two dimensions: technical risks arising from the complexity of the target technologies, and architectural risks stemming from design and scope decisions.

A. Technical Risks

- **LLVM IR Complexity:** LLVM IR supports a wide range of constructs, including vector operations, intrinsics, and optimization-introduced transformations. LLVManim targets a common subset of instructions for the initial implementation.
  - *Risk:* Unsupported constructs may cause parsing failures or incomplete visualizations.
  - *Mitigation:* Restrict the MVP to unoptimized `-O0` IR and provide clear diagnostic messages when encountering unsupported instructions.
- **Manim Performance:** Manim provides high-quality animations but can be computationally expensive, especially for scenes with many objects or transitions.
  - *Risk:* Long render times may slow development and limit iterative testing.
  - *Mitigation:* Use low-quality preview rendering during development and reserve high-quality output for final deliverables.
- **Cross-Platform Compatibility:** Achieving consistent LLVManim behavior across operating systems and development environments can be challenging.
  - *Risk:* Platform-specific issues may arise and cause inconsistent behavior or failures.
  - *Mitigation:* Use cross-platform libraries and conduct testing on multiple platforms to ensure compatibility.
- **Dependency Fragility:** LLVManim depends on Clang, LLVMlite, and Manim, each of which may introduce version incompatibilities or platform-specific issues.
  - *Risk:* Changes in LLVM or Manim APIs could break LLVManim's functionality.
  - *Mitigation:* Provide a reproducible environment via containerization or a standardized setup script.



Fig. 6: Unified data model. Ingest types (`ProgramEventStream`, `IREvent`, `CFGEdge`, `DotLayout`) feed into Transform types (`SceneGraph`, `SceneNode`, `SceneEdge`, `AnimationCommand`, `TraceOverlay`) which are consumed by Render types (`CommandDrivenScene`, `StackRenderer`, `CFGRenderer`).

B. Architectural Risks

- **User Expectations for Customization:** Educators and presenters often need fine-grained control over pacing, color schemes, and layout choices.
  - *Risk:* Limited customization may reduce adoption and may fail to meet expectations for presentation-quality output.
  - *Mitigation:* Provide a minimal but meaningful set of customization flags (e.g., palette, speed, verbosity) in the initial release.

V. Results

This section reports the implemented capabilities of LLVManim across its final release, covering feature completeness, the supported subset of LLVM IR instructions, available animation modes, test suite quality, and overall codebase size. Performance metrics and reproducibility details are also included to demonstrate the tool's practical usability and reliability.

A. Feature Coverage

Table I summarizes the proposed features from the original project goals alongside their implementation status. Of the originally proposed proof-of-concept targets, all were achieved except a GUI. Interactive stepping/pause was deemed redundant given the ability to manually control `mp4` playback in most modern media players.

TABLE I: Proposed vs. Implemented Features

Feature	Status
CLI accepting `.ll` files	✓
LLVM IR parsing via `LLVMLite`	✓
Typed CFG edge extraction	✓
Intermediate scene graph	✓
JSON scene graph export	✓
Graphviz DOT/PNG export	✓
Basic stack animation	✓
Rich IR spotlight animation	✓
Rich-SSA 3-column animation	✓
CFG traversal animation	✓
Runtime trace import/export	✓
Domtree/loop metadata import	✓
GIF output with palette workflow	✓
Adjustable animation speed	✓
Automatic C compilation	✓
YAML configuration files	✓
Color palette selection	✓
Interactive stepping/pause	∼
GUI	×

B. Supported IR Instructions

LLVManim classifies each LLVM IR instruction into one of nine `EventKind` categories:

- `alloca`: Stack memory allocation
- `load` / `store`: Memory read and write operations
- `binop`: Binary arithmetic operations (`add`, `sub`, `mul`, etc.)
- `compare`: Integer and floating-point comparisons (`icmp`, `fcmp`)
- `call`: Function invocations
- `ret`: Function returns
- `br`: Branch instructions (conditional and unconditional)
- `other`: Unsupported or unrecognized instructions (skipped with a diagnostic message)

CFG edge extraction supports five terminator types: `br`, `switch`, `invoke`, `indirectbr`, and `callbr`. Conditional branches are labeled with T/F direction annotations.

C. Animation Modes

LLVManim provides three stack-focused animation modes and one graph-based mode, each reproducible with a single CLI command. The stack-focused modes (basic, rich, rich-SSA) share a common layout and animation style, with increasing levels of IR detail. The graph-based mode renders an animated traversal of the control-flow graph using Graphviz layout and a runtime trace for the traversal order. Each mode is designed to target different presentation contexts and audience familiarity levels, allowing users to choose the appropriate level of detail for their needs. The following sections describe each mode in detail, along with example CLI commands for generating the animations. All animations were generated from the same `double.ll` test program, which contains a simple loop with arithmetic operations, memory accesses, and control flow. The full source code for `double.c` and `double.ll` is provided in appendix A.

Basic mode (`--ir-mode basic`) renders a minimal stack-only view. Each IR instruction triggers a per-cell badge flash on the corresponding stack slot, providing a clean visual pulse of execution without additional clutter. This mode is best suited for audiences who need only a high-level sense of execution flow, such as introductory lectures or quick demonstrations, since it strips away all source-level detail and focuses purely on the call stack. Listing 2 shows the CLI command used to generate the animation shown in Fig. 7.

```
uv run llvmanim double.ll --animate --ir-mode
↪  basic --outdir out/
```

Listing 2: CLI command to generate the basic mode animation shown in Fig. 7.

Rich mode (`--ir-mode rich`) extends the basic view with a two-column layout. An IR source panel on the left displays the current function's instructions while a spotlight cursor tracks the executing line, giving the audience both the



Fig. 7: Basic mode: stack-only view with per-cell badge flash during a `call` to `@init`.



Fig. 8: Rich mode: two-column layout with IR source spotlight alongside the stack.

"what" (the stack) and the "where" (the source). This mode is particularly valuable when the presenter wants to walk through specific IR constructs—for example, showing how a series of `alloca` and `store` instructions initialize local variables before a loop body executes. The spotlight cursor provides a natural focal point that guides the viewer's attention through the code. Listing 3 shows the CLI command used to generate the animation shown in Fig. 8.

```
uv run llvmanim double.ll --animate --ir-mode
↪  rich --outdir out/
```

Listing 3: CLI command to generate a rich mode animation shown in Fig. 8.

Rich-SSA mode (`--ir-mode rich-ssa`) takes the rich layout a step further with a dedicated third column for SSA values (IR Source | SSA Values | Stack). The center panel displays the symbolic result of each binary operation, comparison, or load as it executes, making it possible to follow data dependencies without mentally resolving `%`-names. This is the most detailed mode and targets audiences already familiar with SSA form—for instance, a compiler course where students need to see how `%4 = icmp slt i32 %2, %3` evaluates during a loop iteration. Listing 4 shows the CLI command used to generate the animation shown in Fig. 9.

```
uv run llvmanim double.ll --animate --ir-mode
↪  rich-ssa --outdir out/
```

Listing 4: CLI command to generate a rich-SSA mode animation shown in Fig. 9.

CFG traversal (`--cfg-animate`) renders an animated walk through the control-flow graph, using Graphviz DOT layout for node positions and a runtime trace for the traversal order:

```
uv run llvmanim double.ll --cfg-animate --dot-cfg
↪  main.dot --import-trace trace.json --outdir
↪  out/
```

Listing 5: CLI command to generate a CFG traversal animation.

D. Test Coverage and Quality

The LLVManim implementation is validated by 302 automated tests organized into four marker categories:

TABLE II: Test Distribution by Category

Category	Count
Unit (ingest, transform)	192
Integration (present, cli, pipeline)	96
Contract (export boundaries)	8
End-to-end (entrypoints)	6
Total	**302**

Line coverage stands at 84% across the entire `llvmanim` package. Fig. 11a (Appendix B) shows per-module coverage and Fig. 11b shows the test distribution across modules. A four-stage quality gate runs on every pull request:

1) **Ruff**: Linting and import sorting
2) **Pyright**: Static type checking (strict mode)
3) **import-linter**: Architectural boundary enforcement between layers
4) **pytest**: Full test suite execution with coverage reporting

E. Codebase Size

The LLVManim codebase comprises 3,189 lines of Python across 18 modules. Fig. 12 (Appendix B) shows the breakdown by layer and module. The Render layer accounts for 42% of the code, followed by Ingest (25%), Transform (19%), and CLI (14%).

F. Performance

All pipeline stages exhibit linear scaling behavior, confirming that LLVManim can handle realistically sized LLVM IR inputs. Benchmarks use synthetic IR programs with controlled instruction and block counts (median of 5 runs per data point).

Fig. 13 (Appendix B) shows the relative wall-clock cost of each pipeline stage for a 50-block CFG. The Ingest stage (`parse_module_to_events`) dominates at 11.6 ms, while all Transform stages complete in under 0.25 ms. Fig. 14 confirms that parse time scales linearly with instruction count—$\Theta(n)$ where n is the number of IR instructions.

The scene-graph construction stages also scale linearly: `build_scene_graph(mode='cfg')` is $\Theta(n_b)$ in block count (Fig. 15), `derive_cfg_trace` is $\Theta(n_b)$ for linear-chain CFGs and $O(n_b \cdot k)$ in the presence of loops (Fig. 16), and `build_scene_graph(mode='stack')` exhibits sub-linear growth empirically (Fig. 17).

Peak memory allocation also grows linearly with IR size for both pipelines (Fig. 18).

G. Reproducibility

All LLVManim results can be reproduced from the public repository [14]:

```
git clone
↪  https://github.com/BenHoule/LLVManim.git
cd LLVManim
uv sync --dev
# run all 4 quality gates
./scripts/quality-check.sh
# Create coverage and LoC figures.
./uv run python docs/metrics/generate_metrics.py
# Create pipeline latency and scaling figures.
./uv run python
↪  docs/metrics/generate_perf_metrics.py
```

Listing 6: Commands to reproduce all results.

System requirements: Python 3.12+, `uv`, Linux packages `libcairo2` and `libpango` (for Manim), and optionally `graphviz` for PNG graph export. See the repository's `README.md` for detailed setup instructions and troubleshooting tips.



Fig. 9: Rich-SSA mode: three-column layout showing computed SSA values for `load` and `icmp` instructions.



Fig. 10: CFG mode: Animated walk through the control-flow graph, highlighting blocks and edges as they are traversed.

VI. Discussion

This section reflects on the development process, examining the key architectural decisions made during implementation, where the final system diverged from the original proposal, the known limitations that remain unresolved, and lessons learned over the course of the project.

A. Architectural Decisions

Several architectural decisions shaped the final system—

- **Three-layer separation with import-linter:** Enforcing strict layer boundaries at build time prevented coupling between Ingestion, Transformation, and Rendering. This paid dividends during the IR display model refactor, where the Transformation layer's data structures were restructured without touching any Rendering layer code. The `import-linter` tool caught accidental cross-layer imports on multiple occasions during development.
- **Display model abstraction:** Rather than having Manim scenes query the scene graph directly, we introduced an explicit display model (the `TraceStep`/`RichTraceStep` and `AnimationCommand` types) that decouples rendering from data extraction. This made it straightforward to add the rich-SSA animation mode by extending the trace step type without modifying existing scene classes.
- **Pipeline approach:** The tool processes data in a linear pipeline: parse → build scene graph → render or export. This simplified testing because each stage could be exercised independently with deterministic fixtures. The 302 tests in the suite are predominantly unit tests that operate on a single layer.
- **LLVMLite for terminator parsing:** Early prototypes used regex-based parsing of LLVM IR text, which proved fragile for edge cases such as `switch` and `invoke` terminators. Switching to `LLVMLite`'s Python binding, which exposes the LLVM C API, made CFG edge extraction reliable across all five terminator types.

B. Deviations from Proposal

The following proposed features were not implemented—

- **Interactive stepping and pause:** Interactive playback was deprioritized in favor of richer static animation modes. Manim CE's rendering model produces video files rather than interactive sessions, making pause/step less natural.
- **YAML configuration and –palette:** Fine-grained customization via YAML files and named color palettes was deferred. The current CLI provides `--speed` and `--format` as the primary customization points.
- **GUI:** A graphical interface was listed as a stretch goal and was not pursued given the limited timeline.

Conversely, two capabilities were implemented that were *not* in the original proposal—

- **Rich-SSA three-column animation:** The `--ir-mode rich-ssa` mode displays symbolic SSA values alongside IR source and stack state, providing deeper instruction-level insight than originally planned.
- **CFG traversal animation:** The `--cfg-animate` mode renders an animated walk through the control-flow graph using Graphviz DOT layout, a feature that emerged from explorations in the sandbox environment.

C. Known Limitations

The current implementation has several known limitations—

- **Double-pop bug:** Under certain control-flow patterns involving consecutive returns, the basic animation mode may attempt to pop the stack twice for a single `ret` instruction. This is tracked as a known issue.
- **Symbolic-only SSA values:** The rich-SSA panel displays symbolic operand names (e.g., `%3 = add %1, %2`) rather than concrete runtime values. A single swap-point in `ssa_formatting.py` exists for when numeric runtime values are plumbed through in a future version.
- **No heap visualization:** The tool visualizes stack operations but does not yet render heap allocations or pointer-based data structures.
- **Manim render times:** Full-quality Manim renders can take significant time for programs with many instructions. The `--speed` flag and low-quality preview mode help during development, but render time remains a practical constraint for large programs.

D. Lessons Learned

- **TDD was essential for refactors:** The test suite caught regressions immediately when refactoring the IR display model and restructuring the scene graph. Without comprehensive tests, these refactors would have been significantly riskier.
- **Architectural enforcement catches violations early:** `import-linter` rejected several pull requests that would have introduced cross-layer dependencies, preventing technical debt before it accumulated.
- **Sandbox-driven exploration:** Experimental Manim scripts in the `sandbox/` directory allowed rapid prototyping of animation ideas (CFG traversal, register panels) without risking the main codebase.
- **Typed CFG edges via LLVMLite:** Moving from regex-based IR text parsing to `LLVMLite`'s terminator API eliminated an entire class of parsing bugs and made the Ingestion layer robust against IR formatting variations.

VII. Conclusion

We presented LLVManim, a tool that automatically generates presentation-quality animations from LLVM IR. The system's three-layer pipeline—Ingestion, Transformation, and Rendering—cleanly separates concerns and is enforced by architectural boundary checks at build time. Over a single semester, we delivered a fully functional CLI tool with

three animation modes, a CFG traversal visualizer, machine-readable export formats, and a comprehensive test suite of 302 tests at 84% line coverage.

LLVManim demonstrates that the gap between LLVM's powerful but utilitarian analysis output and the polished animations achievable with Manim can be bridged through thoughtful automation. By targeting LLVM IR as input, the tool inherits support for any language that compiles through the LLVM toolchain, making it broadly applicable to educational and presentational contexts.

Future Work

Several directions remain for future development:

- **Numeric SSA values:** Plumbing concrete runtime values through the trace overlay to replace symbolic operand names in the rich-SSA panel.
- **Heap visualization:** Extending the animation modes to render heap allocations, pointer dereferences, and linked data structures.
- **Double-pop fix:** Resolving the known bug in consecutive-return control-flow patterns.
- **Interactive playback:** Exploring Manim's OpenGL preview mode or alternative rendering backends for pause/step interactivity.

Acknowledgment

We would like to thank Dr. James Daly for his guidance, feedback, and support throughout the development of this work.

References

[1] P. J. Guo, "PythonTutor: Visualize code execution," https://pythontutor.com, 2010, accessed: Feb. 13, 2026.

[2] ——, "Online python tutor: embeddable web-based program visualization for cs education," in *Proceeding of the 44th ACM Technical Symposium on Computer Science Education*, ser. SIGCSE '13. New York, NY, USA: Association for Computing Machinery, 2013, pp. 579–584. [Online]. Available: https://doi.org/10.1145/2445196.2445368

[3] ——, "Codeopticon: Real-time, one-to-many human tutoring for computer programming," in *Proceedings of the 28th Annual ACM Symposium on User Interface Software & Technology*, ser. UIST '15. New York, NY, USA: Association for Computing Machinery, 2015, pp. 599–608. [Online]. Available: https://doi.org/10.1145/2807442.2807469

[4] C. Lattner and V. Adve, "LLVM: A compilation strategy for lifelong program analysis and transformation," in *Proceedings of the 2nd IEEE Annual CGO and ACM SIGPLAN Annual CC Symposium*, ser. CGO-CC '04. Palo Alto, CA, USA: IEEE Computer Society, 2004, pp. 60–72.

[5] LLVM Project, "LLVM language reference manual," https://llvm.org/docs/LangRef.html, 2024, accessed: 2026-02-25.

[6] J. Ellson, E. Gansner, E. Koutsofios, S. North, and G. Woodhull, "Graphviz – Open Graph Visualization Software," https://graphviz.org/, 2001, accessed: Apr. 17, 2026.

[7] G. Sanderson, "Manim – mathematical animation framework," https://github.com/3b1b/manim, 2015, accessed: Feb. 13, 2026.

[8] ——, "3blue1brown," Website, 2026, accessed: Feb. 13, 2026. [Online]. Available: https://www.3blue1brown.com/

[9] ——, "3blue1brown," Youtube Channel, March 2015, accessed: Apr. 27, 2026. [Online]. Available: https://www.youtube.com/@3blue1brown

[10] 3Blue1Brown, "Topics: Computer science," https://www.3blue1brown.com/?topic=computer-science, 2023, accessed: Apr. 27, 2026.

[11] Numba Development Team, "llvmlite: A lightweight llvm python binding for writing jit compilers," https://github.com/numba/llvmlite, 2024, accessed: 2026-02-25.

[12] Astral Software, *uv: An Extremely Fast Python Package and Project Manager*, Astral, 2026, accessed: 2026-04-21. [Online]. Available: https://astral.sh/uv

[13] Manim Community Developers, "Manim community edition," https://www.manim.community/, 2024, accessed: Apr. 17, 2026.

[14] B. Houle, E. Oloyede, L. Grippo, and M. Ahmed, "LLVManim: Presentable debugging with LLVM and Manim," https://github.com/BenHoule/LLVManim, 2026, accessed: Apr. 17, 2026.

Appendix A
Input Files: double.c and double.ll

double.c is a minimal C program used to generate the example LLVManim output. It defines three functions—init, double_1, and main—whose control flow, heap allocation, and loop structure exercise all four LLVManim animation modes.

```c
#include <stdlib.h>

void init(int *p) {
  *p=1;
}

int double_1(int *p){
  int tmp = *p;
  *p = 2*tmp;
  return (*p);
}

int main() {
  int r = 0;
  int *p = (int *) malloc(sizeof(int));
  init(p);
  while (*p < 100) {
    r = double_1(p);
  }
  return r;
}
```

Listing 7: Full C source (double.c) used for all sample animations.

double.ll is compiled at -O0 with full debug info (clang -O0 -g -S -emit-llvm double.c). It is the actual LLVM IR input used by LLVManim in the examples.

```llvm
; ModuleID = 'double.c'
source_filename = "double.c"
target datalayout = "e-m:e-p270:32:32-p271:32:32-p272:64:64-i64:64-i128:128-f80:128-n8:16:32:64-S128"
target triple = "x86_64-pc-linux-gnu"

; Function Attrs: noinline nounwind optnone uwtable
define dso_local void @init(ptr noundef %p) #0 !dbg !13 {
entry:
  %p.addr = alloca ptr, align 8
  store ptr %p, ptr %p.addr, align 8
  call void @llvm.dbg.declare(metadata ptr %p.addr, metadata !17, metadata !DIExpression()), !dbg !18
  %0 = load ptr, ptr %p.addr, align 8, !dbg !19
  store i32 1, ptr %0, align 4, !dbg !20
  ret void, !dbg !21
}

; Function Attrs: nocallback nofree nosync nounwind speculatable willreturn memory(none)
declare void @llvm.dbg.declare(metadata, metadata, metadata) #1

; Function Attrs: noinline nounwind optnone uwtable
define dso_local i32 @double_1(ptr noundef %p) #0 !dbg !22 {
entry:
  %p.addr = alloca ptr, align 8
  %tmp = alloca i32, align 4
  store ptr %p, ptr %p.addr, align 8
  call void @llvm.dbg.declare(metadata ptr %p.addr, metadata !25, metadata !DIExpression()), !dbg !26
  call void @llvm.dbg.declare(metadata ptr %tmp, metadata !27, metadata !DIExpression()), !dbg !28
  %0 = load ptr, ptr %p.addr, align 8, !dbg !29
  %1 = load i32, ptr %0, align 4, !dbg !30
  store i32 %1, ptr %tmp, align 4, !dbg !28
  %2 = load i32, ptr %tmp, align 4, !dbg !31
  %mul = mul nsw i32 2, %2, !dbg !32
```

```
  %3 = load ptr, ptr %p.addr, align 8, !dbg !33
  store i32 %mul, ptr %3, align 4, !dbg !34
  %4 = load ptr, ptr %p.addr, align 8, !dbg !35
  %5 = load i32, ptr %4, align 4, !dbg !36
  ret i32 %5, !dbg !37
}

; Function Attrs: noinline nounwind optnone uwtable
define dso_local i32 @main() #0 !dbg !38 {
entry:
  %retval = alloca i32, align 4
  %r = alloca i32, align 4
  %p = alloca ptr, align 8
  store i32 0, ptr %retval, align 4
  call void @llvm.dbg.declare(metadata ptr %r, metadata !41, metadata !DIExpression()), !dbg !42
  store i32 0, ptr %r, align 4, !dbg !42
  call void @llvm.dbg.declare(metadata ptr %p, metadata !43, metadata !DIExpression()), !dbg !44
  %call = call noalias ptr @malloc(i64 noundef 4) #3, !dbg !45
  store ptr %call, ptr %p, align 8, !dbg !44
  %0 = load ptr, ptr %p, align 8, !dbg !46
  call void @init(ptr noundef %0), !dbg !47
  br label %while.cond, !dbg !48

while.cond:                                       ; preds = %while.body, %entry
  %1 = load ptr, ptr %p, align 8, !dbg !49
  %2 = load i32, ptr %1, align 4, !dbg !50
  %cmp = icmp slt i32 %2, 100, !dbg !51
  br i1 %cmp, label %while.body, label %while.end, !dbg !48

while.body:                                       ; preds = %while.cond
  %3 = load ptr, ptr %p, align 8, !dbg !52
  %call1 = call i32 @double_1(ptr noundef %3), !dbg !54
  store i32 %call1, ptr %r, align 4, !dbg !55
  br label %while.cond, !dbg !48, !llvm.loop !56

while.end:                                        ; preds = %while.cond
  %4 = load i32, ptr %r, align 4, !dbg !59
  ret i32 %4, !dbg !60
}

; Function Attrs: nounwind allocsize(0)
declare noalias ptr @malloc(i64 noundef) #2

attributes #0 = { noinline nounwind optnone uwtable "frame-pointer"="all" "min-legal-vector-width"="0" "no-trapping-math"="true" "stack-protector-buffer-size"="8" "target-cpu"="x86-64" "target-features"="+cmov,+cx8,+fxsr,+mmx,+sse,+sse2,+x87" "tune-cpu"="generic" }
attributes #1 = { nocallback nofree nosync nounwind speculatable willreturn memory(none) }
attributes #2 = { nounwind allocsize(0) "frame-pointer"="all" "no-trapping-math"="true" "stack-protector-buffer-size"="8" "target-cpu"="x86-64" "target-features"="+cmov,+cx8,+fxsr,+mmx,+sse,+sse2,+x87" "tune-cpu"="generic" }
attributes #3 = { nounwind allocsize(0) }

!llvm.dbg.cu = !{!0}
!llvm.module.flags = !{!5, !6, !7, !8, !9, !10, !11}
!llvm.ident = !{!12}

!0 = distinct !DICompileUnit(language: DW_LANG_C11, file: !1, producer: "Ubuntu clang version 18.1.3 (1ubuntu1)", isOptimized: false, runtimeVersion: 0, emissionKind: FullDebug, retainedTypes: !2, splitDebugInlining: false, nameTableKind: None)
!1 = !DIFile(filename: "double.c", directory: "/home/benh/LLVManim", checksumkind: CSK_MD5, checksum: "0f941b637837176c30f52c4a0313c1b1")
!2 = !{!3}
!3 = !DIDerivedType(tag: DW_TAG_pointer_type, baseType: !4, size: 64)
!4 = !DIBasicType(name: "int", size: 32, encoding: DW_ATE_signed)
!5 = !{i32 7, !"Dwarf Version", i32 5}
!6 = !{i32 2, !"Debug Info Version", i32 3}
!7 = !{i32 1, !"wchar_size", i32 4}
!8 = !{i32 8, !"PIC Level", i32 2}
!9 = !{i32 7, !"PIE Level", i32 2}
!10 = !{i32 7, !"uwtable", i32 2}
!11 = !{i32 7, !"frame-pointer", i32 2}
!12 = !{!"Ubuntu clang version 18.1.3 (1ubuntu1)"}
```

```
!13 = distinct !DISubprogram(name: "init", scope: !1, file: !1, line: 5, type: !14, scopeLine: 5, flags: DIFlagPrototyped, spFlags: DISPFlagDefinition, unit: !0, retainedNodes: !16)
!14 = !DISubroutineType(types: !15)
!15 = !{null, !3}
!16 = !{}
!17 = !DILocalVariable(name: "p", arg: 1, scope: !13, file: !1, line: 5, type: !3)
!18 = !DILocation(line: 5, column: 16, scope: !13)
!19 = !DILocation(line: 6, column: 4, scope: !13)
!20 = !DILocation(line: 6, column: 5, scope: !13)
!21 = !DILocation(line: 7, column: 1, scope: !13)
!22 = distinct !DISubprogram(name: "double_1", scope: !1, file: !1, line: 9, type: !23, scopeLine: 9, flags: DIFlagPrototyped, spFlags: DISPFlagDefinition, unit: !0, retainedNodes: !16)
!23 = !DISubroutineType(types: !24)
!24 = !{!4, !3}
!25 = !DILocalVariable(name: "p", arg: 1, scope: !22, file: !1, line: 9, type: !3)
!26 = !DILocation(line: 9, column: 19, scope: !22)
!27 = !DILocalVariable(name: "tmp", scope: !22, file: !1, line: 10, type: !4)
!28 = !DILocation(line: 10, column: 7, scope: !22)
!29 = !DILocation(line: 10, column: 14, scope: !22)
!30 = !DILocation(line: 10, column: 13, scope: !22)
!31 = !DILocation(line: 11, column: 10, scope: !22)
!32 = !DILocation(line: 11, column: 9, scope: !22)
!33 = !DILocation(line: 11, column: 4, scope: !22)
!34 = !DILocation(line: 11, column: 6, scope: !22)
!35 = !DILocation(line: 12, column: 12, scope: !22)
!36 = !DILocation(line: 12, column: 11, scope: !22)
!37 = !DILocation(line: 12, column: 3, scope: !22)
!38 = distinct !DISubprogram(name: "main", scope: !1, file: !1, line: 15, type: !39, scopeLine: 15, spFlags: DISPFlagDefinition, unit: !0, retainedNodes: !16)
!39 = !DISubroutineType(types: !40)
!40 = !{!4}
!41 = !DILocalVariable(name: "r", scope: !38, file: !1, line: 16, type: !4)
!42 = !DILocation(line: 16, column: 7, scope: !38)
!43 = !DILocalVariable(name: "p", scope: !38, file: !1, line: 17, type: !3)
!44 = !DILocation(line: 17, column: 8, scope: !38)
!45 = !DILocation(line: 17, column: 20, scope: !38)
!46 = !DILocation(line: 18, column: 8, scope: !38)
!47 = !DILocation(line: 18, column: 3, scope: !38)
!48 = !DILocation(line: 19, column: 3, scope: !38)
!49 = !DILocation(line: 19, column: 11, scope: !38)
!50 = !DILocation(line: 19, column: 10, scope: !38)
!51 = !DILocation(line: 19, column: 13, scope: !38)
!52 = !DILocation(line: 20, column: 18, scope: !53)
!53 = distinct !DILexicalBlock(scope: !38, file: !1, line: 19, column: 20)
!54 = !DILocation(line: 20, column: 9, scope: !53)
!55 = !DILocation(line: 20, column: 7, scope: !53)
!56 = distinct !{!56, !48, !57, !58}
!57 = !DILocation(line: 21, column: 3, scope: !38)
!58 = !{!"llvm.loop.mustprogress"}
!59 = !DILocation(line: 22, column: 10, scope: !38)
!60 = !DILocation(line: 22, column: 3, scope: !38)
```

Listing 8: Full LLVM IR source (`double.ll`) used for all sample animations.

Appendix B
Figures for Metrics



(a) Test coverage by module. Most modules exceed the 80% threshold; `render/stack_renderer` (48%) and `render/cfg_renderer` (62%) are the primary gaps due to Manim rendering dependencies.



(b) Test count per module (298 total). CLI, transform, and ingest modules carry the largest test loads.

Fig. 11: Test coverage and test count by module.



Fig. 12: Lines of code by layer (left) and per module (right). The Render layer is the largest due to the Manim animation logic in `stack_renderer` and `cfg_animation`.



Fig. 13: Pipeline stage latency for a 50-block CFG (median of 5 runs). Parsing dominates; Transform stages are two orders of magnitude faster.



Fig. 14: `parse_module_to_events` scaling. Linear in instruction count—$\Theta(n)$.



Fig. 15: CFG scene-graph build time vs. block count—$\Theta(n)$.



Fig. 16: CFG trace derivation scaling—$\Theta(n)$ for linear chains, $O(n \cdot k)$ with loops.



Fig. 17: Stack scene-graph build time vs. call depth—$O(d)$ worst case, sub-linear empirically.



Fig. 18: Peak memory allocation vs. CFG block count. Both pipelines scale linearly—$\Theta(n)$.

Appendix C
Feedback

Pitch – 01/29/2026

[1]—*"The figures are helpful for showing how the existing tools work, but for the proposal make sure you show how you want the visualized code to work. This could be through making a mockup or setting up input for Manim to generate something that looks like what you want. You should also think about the pipeline for what data you are planning on getting from LLVM, how you are going to get it, and how you will feed it into Manim."*

[2]—*"You have figures for some existing tools. Make sure you talk about them in the proposal and what their limitations are."*

Proposal – 02/13/2026

[3]—*"This [PythonTutor] figure is unreadable."*

[4]—*"[PythonTutor] Spelling."*

[5]—*"Which languages [are supported by PythonTutor]?"*

[6]—*"You should have a citation for where to access the [PythonTutor] tool itself and not just the paper describing its efficacy."*

[7]—*"The text in the [control-flow graph] figure is too small."*

[8]—*"[Graphviz] Linky please."*

[9]—*"Linky to Manim."*

[10]—*"citation needed [for 3Blue1Brown's winning a Streamy award]"*

[11]—*"The order of the [model] diagram is in the opposite order that they are presented in [implementation plan] text."*

[12]—*"The items in the timeline are incredibly brief and need more detail or support."*

---

[13]—*"The figures are quite shrunk down especially figure 1 and figure 2 making it extremely difficult to read the content within it, if those were made larger it would greatly improve the readability."*

[14]—*"The abstract could briefly mention the intended users explicitly, such as educators, students, or software engineers. Additionally, the abstract could briefly summarize how LLVManim achieves this goal rather than only stating the objective."*

$Response_{[14]}$— The intended users of LLVManim are a broad spectrum, including educators, students, and software engineers. We believe the abstract already addresses the context in which LLVManim is useful, and to specify the users that exist within those contexts would be redundant.

[15]—*"The introduction could more explicitly define the scope of the LLVManim system itself earlier in the section. Currently, LLVManim is only briefly mentioned at the end. Introducing LLVManim sooner would improve clarity and help frame the remainder of the document."*

[16]—*"[The PythonTutor] section could be slightly condensed. Some explanations regarding educational benefits are repeated, and the limitations relevant specifically to LLVManim's goals like their lack of customization, presentation-quality output, etc., should be emphasized more clearly. Additionally, explicitly comparing PythonTutor directly to LLVManim in one or two sentences would make the relevance stronger."*

$Response_{[16]}$— We believe the current level of detail in the PythonTutor section is appropriate for providing necessary context and motivation for LLVManim. We may provide a more explicit comparison to LLVManim in the future, but we feel the current description sufficiently highlights the limitations of PythonTutor that LLVManim aims to address.

[17]—*"[The LLVM Analysis and Transform Passes] section could be improved by separating the strengths and weaknesses into clearly defined subsections or paragraphs. Currently, strengths and limitations are interwoven, which makes it slightly harder to skim. Additionally, some technical explanations like the IR syntax examples could be shortened slightly, as the focus of the proposal is visualization rather than compiler internals."*

$Response_{[17]}$— We believe the current structure of the LLVM Analysis and Transform Passes section effectively conveys the necessary information without overcomplicating the overall document structure. It follows the same format as the other sections describing existing tools, and we feel it is consistent with the overall style of the proposal.

[18]—*"[The Manim] section could more explicitly explain how Manim integrates into the LLVManim system pipeline. Additionally, some historical background about 3Blue1Brown could be slightly condensed to maintain focus on the project itself."*

$Response_{[18]}$— We reduced the historical background about 3Blue1Brown. However, these sections are focused on providing context for the tools we are using, and we feel that the current level of detail is appropriate.

[19]—*"Some proof-of-concept metrics (such as $\geq 95\%$ trace mapping and $\geq 80\%$ usability success rate) could briefly explain how these metrics will be measured or evaluated. This would strengthen the feasibility and evaluation clarity. Additionally, the distinction between core features and major features could be clarified slightly, as both appear required for the full system."*

[20]—*"The architecture diagram should be explicitly referenced and described more clearly in the text. Explaining what each arrow and component represents would improve clarity. Additionally, some implementation details (such as exact timing offsets and layout algorithms) may be overly detailed for a proposal and could be slightly condensed."*

[21]—*"The output format could be explained more clearly, particularly how it connects to the Transformation layer."*

[22]—*"The scene graph structure could benefit from a brief visual example or mock representation to clarify*

how data flows through the system. Additionally, the modified Sugiyama layout algorithm is mentioned but not briefly explained, which may confuse readers unfamiliar with graph layout techniques."

[23]—*"The relationship between scene graph generation and Manim output could be explained more clearly in terms of data flow. Additionally, it could briefly explain expected output formats and user workflows."*

[24]—*"[The User Interface] section could briefly explain error handling and limitations more clearly, such as unsupported language features or missing debug metadata. Additionally, this section could clarify whether the CLI is intended for developers, educators, or both."*

[25]—*"Testing and validation phases could be more clearly defined, particularly usability testing and feature validation. Additionally, stretch feature implementation is only briefly mentioned and could be explicitly identified in the timeline."*

$Response_{[25]}$— We have included testing and validation as part of the overall implementation plan, but we have not explicitly defined separate phases for these activities. We will be continuously testing and validating our implementation throughout the development process, and we will prioritize core features before stretch features to ensure we have a MVP by the end of the semester.

[26]—*"The feedback section [...] could be improved by explicitly explaining how each feedback item will be addressed moving forward rather than only stating that it remains unaddressed. Additionally, creating mockups or example animation output would significantly strengthen the proposal and demonstrate feasibility."*

$Response_{[26]}$— We have addressed feedback in the manner prescribed by the project guidelines, which is to either address it or explain why it remains unaddressed.

[27]—*"Ensure consistent formatting across all references and verify citation formatting matches IEEE or required course format exactly."*

$Response_{[27]}$— We have reviewed our references and believe they are formatted correctly according to the IEEE style. If there are any specific formatting issues, we would appreciate further clarification so we can address them appropriately.

---

[28]—*"It's unnecessary to explain how Julia works. It distracts from the main focus of the paper."*

$Response_{[28]}$— We do not explain how Julia works in the proposal. We have reworded the relevant section for clarity.

[29]—*"You don't have to include all these accomplishments. We already get the idea that [3Blue1Brown] is popular and well respected from earlier."*

[30]—*"Including pictures of Manim diagrams here would illustrate your point better."*

[31]—*"Your goals seem overly ambitious for just a one semester student project."*

$Response_{[31]}$— We acknowledge that our goals are ambitious, but we believe they are achievable with careful planning and prioritization. We also believe that our approach to the project is more relevant to the goals of the class than the final output, and we are committed to making significant progress towards our objectives regardless of the final scope of the project.

[32]—*"It's unrealistic to expect work to be done over spring break."*

$Response_{[32]}$— We appreciate the concern, but our teammembers are aware of the timeline and have planned accordingly.

[33]—*"You should talk more about the potential risks. It's not really mentioned at all."*

[34]—*"The motivation section could be strengthened. While the proposal explains that existing tools are either too technical or not presentation-friendly, it does not fully explain why this problem is important at a broader level. It would help to more clearly identify who specifically benefits from this tool and why current alternatives are insufficient. The proposal currently reads as though the improvement is mostly aesthetic, so emphasizing the educational or practical impact would make the motivation more compelling."*

$Response_{[34]}$— We believe the motivation section sufficiently explains the importance of the problem and the intended beneficiaries of LLVManim. We feel that the educational and practical impact of LLVManim is clear from the context provided, and, frankly, the improvement is primarily aesthetic.

[35]—*"[some objectives] could be more measurable. For example, the proposal mentions performance and trace mapping goals, but it would be helpful to specify what constitutes success more concretely. Adding clearer success criteria would make it easier to evaluate whether the project meets its goals."*

[36]—*"The [architecture] scope could be clarified further. It would be helpful to specify what subset of LLVM IR will be fully supported and how unsupported constructs will be handled. Addressing potential edge cases would make the approach feel more complete and realistic."*

[37]—*"The proposal would benefit from a clearer description of final deliverables. While features are described, it is not entirely clear what concrete artifacts will be submitted at the end of the project. Explicitly listing tangible deliverables would strengthen this section."*

[38]—*"The timeline is present but somewhat broad in places. Some weekly goals are described generally, which makes it difficult to determine what measurable progress will be achieved each week. Making each milestone more concrete and demonstrable would better align with the rubric's expectations."*

[39]—*"The proposal mentions evaluation goals such as trace mapping percentages and usability testing, which is good. However, the evaluation methodology could be described in more detail. For example, specifying the number of participants in the pilot study, the types of tasks they will perform, and how results will be measured would make the evaluation plan stronger and more rigorous."*

[40]—*"A clearly labeled risks section would improve the proposal. While potential challenges are implied, explicitly identifying technical and timeline risks and describing mitigation strategies would demonstrate thoughtful project planning."*

---

[41]—*"I feel [the PythonTutor section] should include the supported languages of PythonTutor, since the usefulness of the tool depends heavily on what languages are supported. It is more useful if it supports languages that are commonly used for education vs if it supports languages that are more obscure."*

[42]—*"What are DOT files? does this mean unix dot files, or does this stand for something?"*

[43]—*"What does verbosity mean in this application and how is it different from animation speed. Does the creator of the animation include an audio track, or is it the speed that words appear? If the latter, how and why are words appearing?"*

$Response_{[43]}$— Verbosity in this context refers to the amount of information displayed in the animation, such as whether variable values are shown or only control flow is visualized. It is different from animation speed, which controls how quickly the animation plays. This is a common feature in debugging tools, and we feel it is reasonable to expect readers to understand this distinction.

[44]—*"Go more in depth about what the study entails. Will you be comparing against other similar tools, or just compared to only reading the code? Will it be between subjects or within subjects? Are you only going to collect data about accuracy or will you also collect data about subjective user preference? Also this study does not seem like it connects well to the stated goal of this project. You are discussing making a tool that will help educational scenarios, but are only evaluating it for use in debugging. I would add a component focusing on user experience generating the images, or evaluating which ones help people to better understand the purpose of code. There are also no sample graphs or tables for the data that is to be collected."*

[45]—*"Why separate core features from MVP features when core features are defined as 'required to have a usable product at all', which is essentially the MVP?"*

[46]—*"How are animations utilized. Is it moving arrows to demonstrate code flow? Will sections of the code be moved on screen only when relevant, and removed afterward. For someone unfamiliar with Manim this is unclear."*

$Response_{[46]}$— A major portion of this project will be dedicated to exploring precisely this question. While we have some initial mockups and ideas for how the animations will work, these likely will not be finalized until towards the end of the project.

[47]—*"While I understand that this document is written with the assumption that the reader has a computer science bachelors degree, I think it would help to use the long form of this abbreviation at least once, as was done with LLVM IR."*

[48]—*"Why make your own 'JSON-like' format instead of just using standard JSON. If it is for data streaming purposes, perhaps consider JSON Lines."*

[49]—*"No discussion of risks or costs."*

[50]—*"Timeline does not say when the experiment will be performed."*

[51]—*"Missing time spent on project."*

[52]—*"The lack of Manim examples or proposed examples for this project makes it difficult for someone unfamiliar with that tool to understand what this tool will produce."*

ARCHITECTURE – 02/25/2026

[53]—*"Is [PythonTutor] the only such tool that you were able to find?"*

[54]—*"using"*

[55]—*"This figure is borderline unreadable."*

[56]—*"I'm not sure how valuable this [3Blue1Brown] paragraph is. It feels like it should be trimmed down and come before the previous one."*

[57]—*"How is this different than the IR Instruction Coverage core feature?"*

[58]—*"None of the stuff in the caption is represented in the [architecture] figure."*

[59]—*"The [architecture] figure doesn't really match the text in section IV-b either."*

[60]—*"This [mock output] figure is not readable."*

[61]—*"You also need the input (both the source file to be parsed and the command that produces the output)"*

[62]—*"[LLVMLite is] also not in your diagram."*

---

[63]—*"This [PythonTutor] figure is hard to read because of how small it is."*

[64]—*"Some programming languages come with their own quirks which will require language specific support. Doing 30 languages seems like too much for such a short project."*

$Response_{[64]}$— We are not planning to implement language-specific support for 30 languages. We will be targeting LLVM IR as input, which means that any language that compiles through the LLVM toolchain will be supported by default. This includes a wide range of languages, but we do not need to implement specific support for each one.

[65]—*"This [list] should be in the same order as your graph: presentation -> transformation -> ingestion."*

[66]—*"Are these the only instructions that will have animation primitives?"*

$Response_{[66]}$— They are the instructions targeted by our MVP, support for more instructions would be considered stretch futures. We prioritize instructions based on their frequency in real-world code and their relevance to control flow and memory visualization.

---

[67]—*"The relationships between components could be explained slightly more clearly. For example, while the diagram shows how data moves between layers, the text could more explicitly describe how the scene graph is passed from the transformation layer into the Manim rendering process. Adding a brief explanation of how the arrows in the architecture diagram correspond to specific data transformations would make the architecture easier to follow."*

[68]—*"One area that could be improved is clarifying the expected workflow for users. For example, it could help to describe a short step-by-step scenario showing how a typical user would run LLVManim from start to finish. This would make the interface section feel more concrete and easier to understand for someone unfamiliar with the system."*

[69]—*"In some sections the explanation becomes quite technical, particularly when describing LLVM internals. While this shows strong knowledge of the system, some of these details could be shortened slightly so that the focus remains on how the technologies support the architecture rather than on compiler internals themselves."*

$Response_{[69]}$— We believe the current level of technical detail is appropriate for the intended audience, which is expected to have a computer science background. We will continue to monitor the balance between technical depth and overall clarity as we develop the project further.

[70]—*"Some figures appear quite small and may be difficult to read, especially those showing outputs from other tools. Enlarging these figures or simplifying them could improve readability. In addition, including another visual example of the expected LLVManim output could further strengthen the proposal and help readers understand what the final animations will look like."*

[71]—*"In a few cases the responses focus more on explaining why the feedback was not implemented rather than demonstrating how the proposal was improved. In some situations, incorporating at least part of the suggested feedback might strengthen the document even further."*

$Response_{[71]}$— We have addressed feedback in the manner prescribed by the project guidelines, which is to either address it or explain why it remains unaddressed. We believe that our explanations for unaddressed feedback are sufficient and that we have made appropriate improvements to the proposal based on the feedback we received.

[72]—*"One possible improvement would be slightly condensing some of the background sections about existing tools. While they provide useful context, they are quite long compared to the sections describing the system architecture itself."*

[73]—*"In a few areas the sentences are quite long and contain multiple ideas at once. Breaking these into shorter sentences could improve readability and make the key points stand out more clearly."*

$Response_{[73]}$— Without specific examples, this feedback is rather difficult to address effectively.

---

[74]—*"How are the most common IR instructions being determined? There should probably be a citation if this data came from an outside source."*

$Response_{[74]}$— We do not use any specific analysis or references for determining the most common IR instructions. The "most common" instructions are somewhat self-evident based on the nature of LLVM IR and programs in general. Arithmetic/logic operations, branch instructions, and function calls are fundamental operations that appear frequently in most programs, while more complex instructions like vector operations or atomic instructions are less common and often specific to certain domains.

[75]—*"I would specify where the output of this tool will go, either to a file or to stdout. If it is a file, I would suggest a flag to specify a file name."*

[76]—*"I would add a flag to override the YAML config file with a provided one."*

$Response_{[76]}$— While we have not gotten to the point of implementing this feature, the intention was always that the path to the YAML file would be provided as a command-line argument, so the user can easily specify a custom configuration file if they choose to do so.

[77]—*"These options are shown as single dash long options, but Listing 1 shows long options with two dashes. This should be consistent."*

[78]—*"How does the user specify what format they want from your interface?"*

[79]—*"If you are using LLVMlite to handle .ll files generated by clang, how do you intend to handle user provided .ll files?"*

$Response_{[79]}$— User provided .ll files are supported by default, as long as they conform to the standard LLVM IR syntax.

[80]—*"Having this project also compile the code to LLVM IR, seems to violate the UNIX philosophy of 'Make each program do one thing well."*

$Response_{[80]}$— We are not planning to implement a full compiler that compiles source code to LLVM IR. Instead, we will be leveraging existing tools in the LLVM ecosystem to handle the compilation process. Our tool will focus on taking LLVM IR as input and generating visualizations from it, which is well within the scope of a single program doing one thing well.

[81]—*"Consider requiring the user to add a –force flag to generate animations for code with unsupported instructions, so they must take a positive step to use data that may produce inaccurate or malformed results."*

$Response_{[81]}$— This is a reasonable suggestion for future work, but we do not currently have plans to implement this feature. The current IR instruction coverage would require this flag to be used for any non-trivial program, which would create a poor user experience.

[82]—*"You do not discuss what platforms you intend to support with this project."*

[83]—*"I would also consider the fact that you provide the intermediate Manim code, so a user could perform manual theming, but still have the animations generated by this tool."*

$Response_{[83]}$— If users want to customize the intermediate Manim code, they are free to do so. However, we do not plan to officially support this as a standard workflow. Our primary focus is on providing a streamlined experience for users who want to generate animations directly from LLVM IR without needing to interact with the intermediate Manim code.

[84]—*"When nesting quotes, should alternate between single and double quotation marks."*

---

[85]—*"The document is now integrated well especially with the addition of the three-layer architecture, risks section, and expanded timeline. However, a few new sections feel appended rather than fully integrated, particularly the order of layers and the placement of diagrams. Reordering to match the architecture narrative would improve coherence."*

[86]—*"The architecture diagram is helpful and matches the intended three-layer pipeline. However, the diagram order conflicts with the text. This makes the pipeline harder to follow. The layers should be presented in the same order in both the diagram and the Implementation Plan, and the diagram should be explicitly referenced in the text with a short 'what the arrows mean, what data flows between layers' explanation."*

[87]—*"The CLI examples are strong and clearly show how a user interacts with the system. However, the interface requirements also ask how the tool interacts with the larger system it lives within. You could clarify the expected workflow and clearly state what artifacts the user receives."*

[88]—*"Since the current MVP is CLI-based, the document is fine without a GUI mockup. However, because a GUI is listed as a stretch feature, including a small mockup or a brief UI description (even one figure) would strengthen the Interfaces requirement and make the stretch goal more concrete."*

$Response_{[88]}$— We feel that including a GUI mockup at this stage would be premature, as we have not yet fully defined the features and layout of the GUI. We plan to focus on developing the core functionality of the CLI-based tool first, and then we can consider adding a GUI in the future once we have a better understanding of the user needs and how best to present the information visually.

[89]—*"You mention a 'Customization API' via flags/YAML and an intermediate 'scene graph.' If the scene graph or Manim component library is meant to be reusable, consider documenting it as a small API: what inputs it takes, what it outputs, and how another developer would extend it."*

[90]—*"The listed technologies make sense. The document should clarify which LLVM tools are required at runtime versus only during development. A brief dependency list would make setup expectations clearer."*

[91]—*"The risks section is a strong addition and aligns well with the assignment. A small improvement would be adding one or two project-management risks (scope creep, integration risk between layers, testing burden) and explicitly tying mitigations to your MVP priorities."*

[92]—*"The timeline is significantly improved and now has concrete deliverables and team assignments. However, it still needs explicit scheduling for evaluation/testing. There is also a quick consistency fix for LLVMlite in this section as lowercase needs to be made uppercase to be made consistent."*

$Response_{[92]}$— At this point in the project, it is a bit late to update the timeline with specific evaluation/testing milestones, as we have already completed a significant portion of the development work. However, we will ensure that testing and evaluation are integrated into our ongoing development process, and we will consider adding more explicit milestones for these activities in future iterations of the project plan. Additionally, we have updated the timeline to consistently refer to "LLVMLite" with the correct capitalization.

[93]—*"Figures 1 and 2 remain difficult to read due to scaling. If they are only for motivation, you could replace them with cropped 'key region' zoom-ins to show the point without unreadably dense text."*

INITIAL RESULTS – 04/01/2026

[94]—*"Make sure that you explain what DOT and CFG are."*

[95]—*"Are these [.ll files] the LLVM intermediate files?"*

[96]—*"[Sequence diagram] figure text is a little small."*

[97]—*"These [«literal» blocks] are enumerations?"*

[98]—*"Coloring to make the checkmarks and crosses more distinct would be helpful."*

[99]—*"Most of the text in the [LLVManim output] figures is unreadable. I think larger single-column images would be better since you don't have page constraints. Also, if you can output into light-mode, it would be better for print."*

---

[100]—*"What is this [sentence in section 1] referring to? It's better to clarify the subject."*

[101]—*"You are using acronyms without defining them first."*

[102]—*"Why are these [lines in figure 5] in a different color? The light gray makes it harder to read on a white background."*

[103]—*"This [Table 1] could be a little more clear. Does this mean that the feature has already been implemented or that it's being worked on."*

$Response_{[103]}$— A checkmark means the feature has been implemented and a cross means it has not been implemented (and is theoretically being worked on).

[104]—*"It's hard to make out the [LLVManim output] code because it's too small."*

---

[105]—*"This is a strong paper that clearly shows significant progress and a working system. The project demonstrates a fully functional pipeline, multiple visualization modes, and solid testing infrastructure, which aligns well with the assignment's goal of showing that your methodology and tools are operational."*

[106]—*"One area to improve is how the results are framed. The section reads more like a final report rather than "initial results," so it would help to explicitly connect what has been implemented to your original project goals and what you intended to achieve at this stage."*

$Response_{[106]}$— It is worded this way because the report is meant to be a precursor to the final report, and the results are meant to be a demonstration of the progress made so far. We include a table of the project goals and how they have been met in the results section, and provide a dedicated *Deviations from Proposal* subsection in the discussion section.

[107]—*"Since the goal of the project is to improve presentation and understanding, it would strengthen the report to include some discussion of how effective the visualizations are for users, even if only informally."*

$Response_{[107]}$— We have not yet conducted any user testing, so we do not have any data on the effectiveness of the visualizations for users. We do not think speculation on this topic would be helpful at this stage.

[108]—*"The figures showing the animation outputs are clear and helpful, but improving readability and consistency across all figures would make the document stronger overall."*

[109]—*"The reproducibility and testing aspects are very well done and clearly demonstrate strong development practices."*

---

[110]—*"How are the most common instructions determined?"*

$Response_{[110]}$— See $\text{Response}_{[74]}$.

[111]—*"Why inlude uv run in CLI example, when that will only work from the project source?"*

$Response_{[111]}$— Because the current implementation only supports running from the project source, and we wanted to show the actual command that would be used. We will update related instructions for the globally installed tool when such a feature is implemented.

[112]—*"These packages will be different by distro, so I would either specify the distro that these packages are for, or just the names of the libraries and let the user determine the package name."*

[113]—*"Consider including double.c to help the understanding of those who are less familiar with LLVM."*

[114]—*"Line numbering breaks page margins."*

[115]—*"In Grey-scale it is almost imposible to tell the difference between the purple and blue. I would consider using a symbol to distinguish the layers instead of colour."*

$Response_{[115]}$— The colors are primarily meant to help differentiate the layers quickly. While it is unfortunate that grayscale viewers lose out on this added benefit, it is not required for understanding the figures. However, we will consider adding symbols or patterns to further differentiate the layers in future iterations of the figures.

[116]—*"It is also difficult to tell the difference between the green and orange in grey-scale."*

$Response_{[116]}$— See $\text{Response}_{[115]}$.

[117]—*"Does not address feedback from Proofreading - Architecture"*

---

[118]—*"In addition to ordering issues, the document occasionally shifts between proposal-style language and results-style language, which makes it feel slightly inconsistent in tone. Some sections describe planned behavior, while others describe completed implementation. Keeping the tense consistent would improve overall readability and make the integration feel more polished."*

$Response_{[118]}$— This is a direct result of the fact that the project is ongoing and began as a proposal. Some behavior is still being planned and some behavior has already been implemented, so the tense shifts accordingly.

[119]—*"Another improvement would be to briefly summarize the full workflow in one paragraph near the end of the introduction. While each section explains its role well, a single high-level "start-to-finish" explanation would help make it easier to understand how all parts connect."*

$Response_{[119]}$— We have provided a high level summary in introduction.

[120]—*"Beyond alignment and ordering, the architecture section could benefit from explicit labeling of data types moving between layers. While the diagram shows components clearly, the specific forms of data are not always emphasized in the narrative explanation."*

$Response_{[120]}$— We would need a more specific example of where this is an issue in order to address it, as the data types are mentioned throughout the architecture section and we are not sure which ones are not emphasized enough.

[121]—*"Also, some terminology used in diagrams (such as SceneGraph, AnimationCommand, and TraceOverlay) appears in technical detail later but could be briefly defined earlier in the architecture section to improve readability."*

$Response_{[121]}$— Unforunately, page space is limited and we can only fit so many figures into the pages we have, resulting in some figures being pushed a page back due to how LaTeXdetermines figure placement. However, we believe that the current placement does not significantly hinder

understanding. We will consider adding brief definitions in the architecture section if we find that readers are having trouble understanding the diagrams without them.

> [122]—*"It would help to include one short example of a full user session, from command execution to generated output files. The current examples demonstrate commands clearly, but showing the result (such as filenames created or output directory structure) would make expected behavior easier to understand. It may also help to briefly describe expected failure behavior, such as what happens when invalid IR is supplied. While error handling is mentioned, an example error scenario would improve clarity."*

$Response_{[122]}$— We have provided a usage example in the results section, and we will consider adding an example error scenario in future iterations of the report.

> [123]—*"Another improvement would be to include one short usage example showing how a developer might extend the scene graph or animation behavior. This could be pseudocode demonstrating how a new animation command or visualization component would be added."*

$Response_{[123]}$— This is a good idea, but we feel that it is outside the scope of this report, as it would require a significant amount of additional content to explain how to extend the scene graph or animation behavior. Such information would be better suited for the project's technical documentation (which we hope to include with the final report).

> [124]—*"Also, it would be useful to specify whether the scene graph format is stable or experimental, since this affects how safely other developers could rely on it."*

$Response_{[124]}$— The scene graph format is currently experimental, as we are still iterating on the design and may make changes based on user feedback and implementation experience. We will make sure to clearly indicate this in the documentation so that developers understand that they should not rely on the current format for long-term use until it is stabilized.

> [125]—*"Beyond runtime vs development dependencies, it would be helpful to describe version sensitivity as for example, whether specific versions of Python, LLVM, or Manim are required. The document mentions Python 3.12, but similar version notes for other tools would reduce setup uncertainty. Additionally, identifying optional dependencies (such as Graphviz for visualization export) separately from required ones would make installation expectations clearer."*

$Response_{[125]}$— Version sensitivity is handled by the UV environment, which specifies exact versions of all dependencies.

> [126]—*"While responsibilities are assigned in the timeline, it may also help to include a brief summary table listing each team member and their primary responsibility area. This would make roles easier to reference without scanning the full timeline. Another possible addition would be a short note describing collaboration expectations, such as shared ownership of integration or testing tasks."*

$Response_{[126]}$— Unfortunately, our group was not quite organized enough to warrant such a table. The existing timeline is already somewhat arbitrary in how it divides responsibilities, any additional division would be even more so.

> [127]—*"In addition to adding project-management risks, another useful addition would be identifying technical dependency risks, such as reliance on external libraries (Manim or LLVM tooling). Explaining what fallback plan exists if these tools behave unexpectedly would strengthen the risk discussion."*

$Response_{[127]}$— read carefully. tools dependency risks are discussed.

> [128]—*"It would also be helpful to rank risks by relative severity or likelihood, rather than listing them equally. This would make mitigation planning appear more deliberate."*

$Response_{[128]}$— The risks for this project are not easily quantifiable, so we chose to list them without ranking.

> [129]—*"In addition to adding testing schedules, the timeline could benefit from explicit integration milestones, where components from different layers are combined and validated together. This is especially important in multi-layer architectures."*

$Response_{[129]}$— At this point in the project, it is a bit late to update the timeline with specific integration milestones, as we have already completed a significant portion of the development work. However, we will ensure that integration testing is integrated into our ongoing development process, and we will consider adding more explicit milestones for these activities in future iterations of the project plan.

> [130]—*"Another useful addition would be identifying checkpoint deliverables, such as demo-ready versions at specific weeks, to make progress easier to measure."*

$Response_{[130]}$— We have already completed a significant portion of the development work, so it is a bit late to update the timeline with specific checkpoint deliverables.

> [131]—*"Beyond scaling concerns, figure captions could be improved by including short explanations of why each figure matters, not just what it shows. Some captions describe the content but do not explain its significance to the system design."*

$Response_{[131]}$— Explanations for why each figure matters can be found in the body text of the document.

> [132]—*"Additionally, several figures contain dense technical details that might benefit from progressive disclosure, such as introducing a simplified diagram first and then a more detailed version later."*

$Response_{[132]}$— The paper is already crowded with figures, and we do not have the page space to include multiple versions of the same figure. We will consider adding

simplified diagrams in future iterations of the report if we find that readers are having trouble understanding the current diagrams.

DRAFT FINAL REPORT – 04/15/2026

[133]—*"Passive voice [in start of second paragraph of introduction]. It is ok to use "we"."*

[134]—*"For completeness, I'd give the meaning [of the example IR line] as a footnote."*

[135]—*"Is this figure [Listing 1] related to the text directly above it?"*

[136]—*"The space between the caption and the figure [Listing 1] should be smaller than between the caption and the following text."*

[137]—*"The table also says that you are missing YAML configuration, color selection, and a GUI."*

[138]—*"I don't see references to figures 7-9 anywhere."*

[139]—*"You should continue to use captions with numbers and reference them in the blocks above."*

[140]—*"The timeline can be cut from the final version."*

[141]—*"Feedback can be dropped from the final version."*

---

[142]—*"['slog'] is slightly too informal for a paper."*

$Response_{[142]}$— It is a common term and the paper is already quite formal, so we don't think this word is a problem.

[143]—*"You already said this [final paragraph of intro.] in the abstract so it's a little redundant to say it again."*

[144]—*"[LLVMLite] wasn't capitalized earlier in the report. It needs to be consistent."*

[145]—*"Taking data from potential users of your tool would be a good way to show it's effectiveness."*

$Response_{[145]}$— It would be, but we don't have the time.

[146]—*"Should be "are a broad spectrum" since users is plural."*

---

[147]—*"One area that could still be improved is the motivation and impact framing. While the introduction explains the gap between LLVM's functionality and presentation quality, the paper could more explicitly emphasize why this matters for users. Strengthening the connection to real-world use cases (such as teaching effectiveness or presentation clarity) would make the project feel more impactful rather than primarily technical."*

[148]—*"The results section is thorough, with strong coverage of features, performance, and testing. However, similar to earlier feedback, it focuses mostly on implementation metrics (coverage, performance, features completed). Including even a small amount of discussion about how effective the visualizations are for users would strengthen the evaluation and better tie results back to the original goals."*

[149]—*"some earlier figures and diagrams are dense, and slightly improving readability or consistency across all visuals would enhance the overall presentation."*

[150]—*"The discussion section is well done, particularly the reflection on architectural decisions and deviations from the proposal. This shows a strong understanding of the development process. The inclusion of limitations is also valuable, though briefly connecting those limitations back to future improvements or user impact could strengthen this section further."*

---

[151]—*"The radius of the corners of the layers seem to depend on the size of the rectangle. I would recommend making them all have the same radius"*

$Response_{[151]}$— This seems like an exceptionally minor detail.

[152]—*"[CI quality check output] cannot be reproduced"*

[153]—*"Additionally there is no 'uv' folder in the root of the repository so './uv run python docs/metrics/generate_metrics.py' & './uv run python docs/metrics/generate_perf_metrics.py' cannot be run"*

$Response_{[153]}$— `uv` is a Python task runner used to manage our development environment (mentioned in Section III-B). The `uv` configuration file specifies dependencies and commands for our project, but does not create a `uv` folder. To run the commands, you need to have `uv` installed; instructions for installing it can be found in the README.

[154]—*"Don't use dark mode for figures."*

$Response_{[154]}$— Working on it.

[155]—*"As far as I can tell, this feedback was not acted on, but no explanation was provided as to the reasoning. It seems to me that this is also the case with a few other pieces of feedback."*

$Response_{[155]}$— Not all feedback was able to be addressed in the time we were given, especially since peer reviews for this segment were only provided a couple days before it was due. Any unaddressed feedback without a provided explanation can be assumed as something we would have liked to address but were not able to. We will continue to work on addressing as much feedback as possible in future iterations of the report, and we will make sure to provide explanations for any feedback that we are not able to address.

[156]—*"I think it would be good to have one section where utilized technologies are discussed, as it is they are spread out and can be hard to find amongst all the other things that use typewriter text."*

HOURS SPENT: ~200 Hours