

In the Lecture Series Introduction to Database Systems




Conceptual Modeling



Presented by Stéphane Bressan

Introduction to Database Systems

Entity-relationship Diagram from the Tutorial




Entity Relationship

- The Entity-relationship model is a graphical model for representing the conceptual model for the data centric design of an application

Entities and Entity Sets

- Entities are identifiable “things”
- The named box represents a set of entities or entity set




Attributes, Values and Value Sets

- The E-R model is value-oriented
- Values can be integer, strings, or atoms



Attributes of Entities

- Entities can have attributes
- All entities in one entity set have the same attributes
- However the attributes take different values for each entities




Relationships and Relationship Sets

- Relationships
- A lozenge represents a set of relationships or a relationship set




Relationships and Relationship Sets

- A relationship associates 2 or more entities
- A relationship set is a set of relationships associating entities from the same entity sets




Relationships and Relationship Sets

- A relationship associates 2 or more entities
- A relationship set is a set of relationships associating entities from the same entity sets




Relationships and Relationship Sets

- Relationships can associate entities from the same entity set
- In this case and in general, participation, or role, in the relationship can be named




Relationships and Relationship Sets

- Relationships can associate entities from the same entity set
- In this case and in general, participation, or role, in the relationship can be named



Relationships and Relationship Sets


- A relationship can associate more than 2 entities



- We call them n-ary relationships


Relationships and Relationship Sets

- A relationship can associate more than 2 entities
- We call them n-ary relationships




Attributes of Relationships

- Relationship can have attributes
- All relationships in one relationship set have the same attributes




Attributes of Relationships

- Relationships are distinguished not by their attributes but by their participating entities




Entity or Relationship?




Hierarchies: Subset/Supersets

- It is possible to require that an entity set be a subset of another entity set (its superset)




Hierarchies: Inheritance

- Entities in the subsets inherit the attributes of their supersets




Hierarchies: Inheritance

- Entities in the subsets can participate in the relationships of their supersets



Hierarchies: Generalization/Specialization

- This construction can help design specialization hierarchies




Conceptual Modelling

Integrity


Entities' Identity

- One attribute can identify the entity
- This is a property of all entities in an entity set
- *Notice: at least all attributes identify the entity*




Entities' Identity

- A combination of attributes can identify the entity




Entities' Identity

- There might be several possible combination of attributes to identify an entity




Entities' Identity

- *Notice: at least all attributes identify the entity*
- *But we might prefer a minimum set of attributes*



Weak Entities




Weak Entities

- Some entities can only be identified within the scope of a relationship with another entity set
- Notice that the relationship must exist and be unique for each entity in the set

Relationships's Cardinality

- The cardinality of the participation in a relationship can be constrained by a minimum and maximum value:
(1,1)
(0, n)
(2, 5)




Relationships's Cardinality

- The cardinality of the participation in a relationship can be constrained by a minimum and maximum value:

(1,1)


(0, n)

(2, 5)



Relationships's Cardinality

- Another example



Relationships's Cardinality


- (1, x) mandatory participation
- (0, x) optional participation

Relationships's Cardinality

- $(x, 1)$ for all entities involved characterizes a one-to-one relationship
- $(x, 1)$ for one entity involved and (x, N) or (x, y) $y > 1$ for the others characterizes a one-to-many relationship
- (x, N) or (x, y) $y > 1$ for all entities involved characterizes a many-to-many relationship


Relationships's Cardinality

- Example of a one-to-one relationship




Relationships's Cardinality

- By default we have many-to-many relationships



Weak Entities

- Weak entities can only be defined for a participation constrained by (1,1) cardinalities
- Also called mandatory one-to-many relationships




Conceptual to Logical Design

From E-R to Relational
Textbook Section 3.5

Value Sets


- Value sets are mapped to domains
- *In practice this is a first step towards the physical design*
- E-R attributes are mapped to attributes of relations



Entity Sets

- Entity sets are mapped to relations
- The entity set attributes are mapped to attributes of the relation
- The keys are mapped to primary key

Entity Sets



Entity Sets

```
CREATE TABLE company  
(  
  name VARCHAR(64) PRIMARY KEY,  
  address VARCHAR(128),  
)
```


Entity Sets




Entity Sets

```
CREATE TABLE person
(
  first_name VARCHAR(32),
  last_name VARCHAR(32),
  address VARCHAR(128),
  PRIMARY KEY (first_name, last_name))
```

Relationship Sets

- Relationship sets are mapped to relations
- The attributes of the relation consist of the attributes of the relationship set
- As well as of the keys of the participating entities


Relationship Sets



Relationship Sets

```
CREATE TABLE contract
(
  start DATE,
  end DATE,
  object VARCHAR(128),
  pfirst_name VARCHAR(32),
  plast_name VARCHAR(32),
  cname VARCHAR(64),
  PRIMARY KEY (pfirst_name, plast_name, cname),
  FOREIGN KEY (pfirst_name , plast_name ) REFERENCES
  person(first_name, last_name),
  FOREIGN KEY (cname ) REFERENCES company(name)
)
```

Key Constraints (one-to-many relationships)




Key Constraints (one-to-many relationships)

```
CREATE TABLE work_for
(
  start DATE,
  end DATE,
  enumber CHAR(8),
  cname VARCHAR(32),
  PRIMARY KEY (enumber, cname),
  FOREIGN KEY (enumber) REFERENCES
  employee(number),
  FOREIGN KEY (cname) REFERENCES
  company(name)
)
```

Key Constraints (one-to-many relationships)

```
CREATE TABLE work_for
(
  start DATE,
  end DATE,
  enumber CHAR(8) PRIMARY KEY,
  cname VARCHAR(32),
  FOREIGN KEY (enumber) REFERENCES
  employee(number),
  FOREIGN KEY (cname) REFERENCES
  company(name)
)
```



Participation Constraints



Participation Constraints

```
CREATE TABLE work_for
(
  start DATE,
  end DATE,
  enumber CHAR(8),
  cname VARCHAR(32),
  PRIMARY KEY (enumber, cname),
  FOREIGN KEY (enumber) REFERENCES
  employee(number),
  FOREIGN KEY (cname) REFERENCES
  company(name)
)
```


Key and Participation Constraints



Key and Participation Constraints


```
CREATE TABLE employee_work_for
(
  start DATE,
  end DATE,
  enumber CHAR(8) PRIMARY KEY,
  ename CHAR(32),
  cname VARCHAR(32),
  FOREIGN KEY (cname) REFERENCES
  company(name)
)
```

Weak Entity Sets



Weak Entity Sets


```
CREATE TABLE employee_work_for  
(  
  start DATE,  
  end DATE,  
  enumber CHAR(8) PRIMARY KEY,  
  ename CHAR(32),  
  cname VARCHAR(32),  
  FOREIGN KEY (cname) REFERENCES  
  company(name)  
)
```



Weak Entity Sets

```
CREATE TABLE employee_work_for
(
  start DATE,
  end DATE,
  enumber CHAR(8),
  ename CHAR(32),
  cname VARCHAR(32),
  PRIMARY KEY (enumber, cname),
  FOREIGN KEY (cname) REFERENCES
  company(name)
)
```


Entity-relationship Diagram from the Tutorial



Hierarchies

- Hierarchies can be mapped to relations in different ways, e.g.:
 - Horizontal mapping
 - Vertical mapping


Hierarchies



Hierarchies: Horizontal Mapping

```
CREATE TABLE person
(
  first_name VARCHAR(32),
  last_name VARCHAR(32),
  address VARCHAR(128),
  PRIMARY KEY (first_name, last_name)
)


CREATE TABLE employee
(
  first_name VARCHAR(32),
  last_name VARCHAR(32),
  address VARCHAR(128),
  employee_number INTEGER PRIMARY KEY
)
```



Hierarchies: Vertical Mapping

```
CREATE TABLE person
(
  first_name VARCHAR(32),
  last_name VARCHAR(32),
  address VARCHAR(128),
  PRIMARY KEY (first_name, last_name)
)
```

```
CREATE TABLE employee
(
  first_name VARCHAR(32),
  last_name VARCHAR(32),
  employee_integer PRIMARY KEY,
  FOREIGN KEY (first_name, last_name) REFERENCES
  person(first_name, last_name) ON DELETE CASCADE
)
```



Credits

The content of this lecture is based
on chapter 7 of the book
“Introduction to database
Systems”

By
S. Bressan and B. Catania,
McGraw Hill publisher

Animated characters are animated
using VocaliseTTS under
license from Digital Curiosity

Clipart and media are licensed from
Microsoft Office Online Clipart
and Media

Copyright © 2012 by Stéphane Bressan

