

In the Lecture Series Introduction to Database Systems



# Normalization



*Presented by Stéphane Bressan*

*Introduction to Database Systems*

## Learning Objectives

- Understand the rationale (anomalies) and definition of the main normal forms based on functional dependencies (2NF, 3NF and BCNF)
- Be able to decompose (or synthesize) a schema into a dependency preserving BCNF or 3NF.

# Anomalies

- Redundant storage
- Update anomalies
- Insertion anomalies
- Deletion anomalies

# Anomalies: Example

Assume that the position determines the salary:

company                      position → salary

eNumber	firstName	lastName	address	depart ment	Position	salary
1XU3	Dewi	Srijaya	12a Jln Lempeng	Toys	Clerk	2000
4W3E	Izabel	Leong	10 Outram Park	Sports	Trainee	1200
3XXE	John	Smith	107 Clementi Rd	Toys	Clerk	2000
5SD2	Axel	Bayer	55 Cuscaden Rd	Sports	Trainee	1200
6RG5	Winnie	Lee	10 West Coast Rd	Sports	Manager	2500
755Y	Sylvia	Tok	22 East Coast Lane	Toys	Manager	2600
2SD3	Eric	Wei	100 Jurong drive	Toys	Assistant manager	2200
?	?	?	?	?	Security guard	1500

Redundant storage

Update anomaly

Potential deletion anomaly

key

Insertion anomaly

# Decomposition

- The decomposition of a relation scheme  $R$  is a set of relation schemes  $R_i$  such that:

$$\bigcup_i R_i = R$$

# Normalization: Example

## employee

eNumber	firstName	lastName	address	department	Position
1XU3	Dewi	Srijaya	12a Jln Lempeng	Toys	Clerk
4W3E	Izabel	Leong	10 Outram Park	Sports	Trainee
3XXE	John	Smith	107 Clementi Rd	Toys	Clerk
5SD2	Axel	Bayer	55 Cuscaden Rd	Sports	Trainee
6RG5	Winnie	Lee	10 West Coast Rd	Sports	Manager
755Y	Sylvia	Tok	22 East Coast Lane	Toys	Manager
2SD3	Eric	Wei	100 Jurong drive	Toys	Assistant manager



key

❑ Redundant storage?

❑ NO

❑ Update anomaly?

❑ NO

❑ Deletion anomaly?

❑ NO

❑ Insertion anomaly?

❑ NO

## salary

Position	salary
Clerk	2000
Trainee	1200
Manager	2500
Assistant manager	2200
Security guard	1500



key

## Lossless Decomposition: Example

- The decomposition is **lossless** if we can recover the initial table:

```
SELECT first_name, last_name, address,  
       department, T2.position, salary  
FROM T2, T3  
WHERE T2.position = T3.position
```

# Lossless Decomposition: Counter Example

Flight Number	Departure time	Arrival time	Origin	Destination
SG12	12h00	13h00+	SIN	CDG
TG414	15h50	16h30	SIN	JKT
TG415	12h00	14h20	BKK	SIN

□ **Flight Number** is the key



# Lossless Decomposition: Counter Example

Flight Number	Departure time	Arrival time	Origin	Destination
SG12	12h00	13h00+	SIN	CDG
TG414	15h50	16h30	SIN	JKT
TG415	12h00	14h20	BKK	SIN

Flight Number	Departure time	Origin
SG12	12h00	SIN
TG414	15h50	SIN
TG415	12h00	BKK

?

Departure time	Arrival time	Destination
12h00	13h00+	CDG
15h50	16h30	JKT
12h00	14h20	SIN

## Lossless, Dependency Preserving

- The decomposition is lossy
- And we lost functional dependencies:

**{Flight Number} → {Arrival time, Destination}**

## Decomposition: Example

- Consider the relation scheme  
 $\{C, S, J, D, P, Q, V\}$
- with FDs  
 $\{C\} \rightarrow \{S, J, D, P, Q, V\}$   
 $\{J, P\} \rightarrow \{C\}$   
 $\{S, D\} \rightarrow \{P\}$

## Decomposition: Example

- Consider the decomposition into  $\{C, S, J, D, Q, V\}$ ,  $\{S, D, P\}$
- The decomposition is lossless
  - We can recover the initial relation thanks to S,D
- However the functional dependency  $\{J, P\} \rightarrow \{C\}$  is **lost** across the two relations...
- This decomposition is **not dependency preserving**

## Dependency Preserving Decomposition

- The decomposition of a relation scheme
  - $R$  with FDs  $F$
  - Is a set of relation schemes  $R_i$  with FDs  $F_i$
- The decomposition is dependency preserving if and only if

$$(\cup_i F_i)^+ = F^+$$

## Too Much Decomposition

- It might be tempting to decompose to the extreme
- Evaluation of queries may be **inefficient** since it will involve combining several relations

# Too Much Decomposition: Example

Flight Number	Departure time	Origin
SG12	12h00	SIN
TG414	15h50	SIN
TG415	12h00	BKK

Flight Number	Arrival time	Destination
SG12	13h00+	CDG
TG414	16h30	JKT
TG415	14h20	SIN

## Looking for a “Good” Design

- The designer needs guidelines:
  - **Normalization theory**
    - Minimal redundancy and no anomalies
    - Lossless decompositions
    - Dependency preserving decompositions
- But ultimately the designer needs to look at the **workload** (the queries and their efficiency requirement)



## Second Normal Form (2NF)

- R is a relation schema, with the set F of FDs
- R is in 2NF if and only if
  - For all X:  $X \subset R$
  - and, for all  $A \in R$
  - such that there exists a FD:  $X \rightarrow \{A\}$  in  $F^+$
- Then
  - $A \in X$  (*the FD is trivial*), or
  - X is not a proper subset of a candidate key for R, or
  - A is part of some candidate key for R  
(*A is called a prime attribute*)

## Second Normal Form (2NF)

- Consider the relation scheme  $\{A,B,C,D\}$  with the FDs:
  - $\{A,B\} \rightarrow \{C,D\}$  and
  - $\{A\} \rightarrow \{D\}$
- $\{A,B\}$  is a primary key (it is not a proper subset)
- $\{A\}$  is a proper subset of a primary key
- $\{D\}$  is not part of some candidate key
- This scheme is **not** in 2NF

## Second Normal Form (2NF)

- E.g., Relation scheme  $\{A,D\}$  with FDs
  - $\{A\} \rightarrow \{D\}$
  - $\{A\}$  is the primary key (i.e., **not** proper subset)
  - The scheme **is** in 2NF
- E.g., Relation scheme  $\{A,B,C\}$  with FDs
  - $\{A,B\} \rightarrow \{C\}$
  - $\{A,B\}$  **is** the primary key
  - The scheme **is** in 2NF

## Third Normal Form (3NF)

- R is a relation schema, with the set F of FDs
- R is in 3NF if and only if
  - For all X:  $X \subset R$
  - And, for all  $A \in R$
  - such that there exists a FD:  $X \rightarrow \{A\}$  in  $F^+$
- Then
  - $A \in X$  (trivial FD), or
  - X is a **superkey** for R, or
  - A is **part of some candidate key** for R

## Third Normal Form (3NF)

- Rationale:
  - If  $X$  is not a superkey for  $R$  then this dependency is partial and may cause redundancy
  - If  $A$  is not part of some candidate key for  $R$  then there is a transitive dependency:  
candidate key  $\rightarrow X \rightarrow A$
  - Insertion/deletion/update anomalies

## Boyce-Codd Normal Form (BCNF)

- R is a relation schema, with the set F of FDs
- R is in BCNF if and only if
  - For all X:  $X \subset R$
  - And, for all  $A \in R$
  - such that there exists a FD:  $X \rightarrow \{A\}$  in  $F^+$
- Then
  - $A \in X$ , or
  - X is a superkey for R

# BCNF $\subset$ 3NF $\subset$ 2NF $\subset$ 1NF

- 2NF:
  - $A \in X$ , or
  - $X$  is not a proper subset of a candidate key for  $R$ , or
  - $A$  is part of some candidate key for  $R$
- 3NF:
  - $A \in X$ , or
  - $X$  is a superkey for  $R$ , or
  - $A$  is part of some candidate key for  $R$
- BCNF:
  - $A \in X$ , or
  - $X$  is a superkey for  $R$

## Decomposition into BCNF

Let S be the initial set of schemes with FDs F  
**Until** all relation schemes in S are in BCNF  
  **for** each R in S  
    **if** FD  $X \rightarrow Y$  in  $F^+$  violates BCNF for R  
      *( $X \rightarrow R$  not hold, not superkey  
       $X \cap Y = \emptyset$ , not trivial)*  
    **then**  
      use  $X \rightarrow X^+$   
      let S be  $(S - \{R\}) \cup \{(R - X^+) \cup X, X^+\}$   
  **endfor**  
**enduntil**



# Decomposition into BCNF

$X \rightarrow Y$

$X = \{c, d\}$

$X^+ = \{c, d, e, f\}$

a	b	c	d	e	f

a	b	c	d

c	d	e	f

## Decomposition into BCNF

- The different possible orders\* in which we may consider the dependencies violating BCNF in the algorithm application may lead to different decompositions

*\*orders in which we consider the constraints violating the BCNF condition*

## Remark: Projecting FDs

- If  $S$  is a fragment after decomposition of a relation  $R$  with FDs  $F$
- The set of projected FDs on  $S$  is the set  $G$  of FDs
  - If  $X \rightarrow Y$  is in  $G$ 
    - Then  $X$  and  $Y$  are subsets of  $S$
    - $X \rightarrow Y$  is in  $F^+$
  - If  $X \rightarrow Y$  is in  $F^+$  and  $X$  and  $Y$  are subsets of  $S$ 
    - Then  $X \rightarrow Y$  is in  $G^+$

## Decomposition into BCNF

- Let us consider the relation scheme  $R=\{A,B,C,D,E\}$  and the FDs:  
     $\{A\} \rightarrow \{B\}$   
     $\{A\} \rightarrow \{E\}$   
     $\{C\} \rightarrow \{D\}$
- Candidate key:  $\{A, C\}$

## Decomposition into BCNF

- R is not in BCNF
- Because (for instance):
  - $\{A\} \rightarrow \{B\}$  holds
  - It is **not** trivial
  - $\{A\}$  is **not** a superkey

## Decomposition into BCNF

- Pick  $\{A\} \rightarrow \{B\}$  for decomposition
- Expand into  $\{A\} \rightarrow \{B, E\}$
- $\{A, B, C, D, E\}$  becomes
  - $\{A, C, D\}$  and  $\{A, B, E\}$
- With FDs: (we need projected FDs)
  - $\{A\} \rightarrow \{B\}$ , on  $\{A, B, E\}$
  - $\{A\} \rightarrow \{E\}$ , on  $\{A, B, E\}$
  - $\{C\} \rightarrow \{D\}$ , on  $\{A, C, D\}$

## Decomposition into BCNF

- Pick  $\{C\} \rightarrow \{D\}$  for decomposition
- Expand into  $\{C\} \rightarrow \{D\}$
- $\{A,C,D\}$  and  $\{A,B,E\}$  becomes
  - $\{A,C\}$ ,  $\{C,D\}$  and  $\{A,B,E\}$
- With FDs: (*we need projected FDs*)
  - $\{A\} \rightarrow \{B\}$ , *on*  $\{A,B,E\}$
  - $\{A\} \rightarrow \{E\}$ , *on*  $\{A,B,E\}$
  - $\{C\} \rightarrow \{D\}$ , *on*  $\{C,D\}$

## Decomposition into BCNF

- Finally the BCNF decomposition of  $R=\{A,B,C,D,E\}$  with the FDs:  
     $\{A\} \rightarrow \{B\},$   
     $\{A\} \rightarrow \{E\},$   
     $\{C\} \rightarrow \{D\}$
- is:  $\{A,C\}, \{C,D\}$  and  $\{A,B,E\}$



## Decomposition into BCNF

- BCNF decomposition **may not** be **dependency preserving**
- Example:  $\{A,B,C\}$  with FDs
$$\{A,B\} \rightarrow \{C\}$$
$$\{C\} \rightarrow \{A\}$$
- The first FD is **not** preserved.

## Decomposition into 3NF

Let  $S$  be the initial set of relation scheme  $R$  with FDs  $F$

```
for each  $X \subset R$  such that  $X \rightarrow \{A_i\}$  is in the minimal cover of  
     $F$   
    if no scheme contains  $X \cup_i \{A_i\}$   
    then create relation with scheme  $X \cup_i \{A_i\}$   
endfor
```

```
if no scheme contains a key for  $R$   
then create a relation with scheme with key for  $R$ 
```

## Dependency preserving

- The 3NF synthesis algorithm always finds a lossless dependency preserving decomposition

## Credits

The content of this lecture is based  
on chapter 8 of the book  
“Introduction to database  
Systems”

By  
S. Bressan and B. Catania,  
McGraw Hill publisher

Animated characters are animated  
using VocaliseTTS under  
license from Digital Curiosity

Clipart and media are licensed from  
Microsoft Office Online Clipart  
and Media

Copyright © 2012 by Stéphane Bressan

