

February 3, 2023

The results below are generated from an R script.

```
---
title: "Introduction to R"
author: "Data Carpentry contributors"
minutes: 45
---

```{r, echo = FALSE, purl = FALSE, message = FALSE}
source("setup.R")
```

## Error: attempt to use zero-length variable name
```

```
> ### Learning Objectives
>
> * Define the following terms as they relate to R: object, assign, call,
>   function, arguments, options.
> * Create objects and assign values to them in R.
> * Learn how to name objects.
> * Save a script file for later use.
> * Use comments to inform script.
> * Solve simple arithmetic operations in R.
> * Call functions and use arguments to change their default options.
> * Inspect the content of vectors and manipulate their content.
> * Subset and extract values from vectors.
> * Analyze vectors with missing data.

## Error: <text>:2:1: unexpected '>'
## 1:
## 2: >
##    ^
```

```
## Creating objects in R

```{r, echo = FALSE, purl = TRUE}
### Creating objects in R
```
```

You can get output from R simply by typing math in the console:

```
```{r, purl = FALSE}
```

However, to do useful and interesting things, we need to assign `_values_` to `_objects_`. To create an object, we need to give it a name followed by the assignment operator `<-`, and the value we want to give it:

'<-' is the assignment operator. It assigns values on the right to objects on the left. So, after executing 'x <- 3', the value of 'x' is '3'. For historical reasons, you can also use '=' for assignments, but not in every context. Because of the [slight] (<https://blog.revolutionanalytics.com/2008/12/use-equals-or-arrow-for-assignment.html>) [differences] (<https://renkun.me/2014/01/28/difference-between-assignment-operators-in-r/>) in syntax, it is good practice to always use '<-' for assignments.

Objects can be given almost any name such as 'x', 'current\_temperature', or 'subject\_id'. Here are some

- \* You want your object names to be explicit and not too long.
- \* They cannot start with a **number** ('2x' is not valid, but 'x2' is).
- \* R is case sensitive, so for example, 'weight\_kg' is different from 'Weight\_kg'.
- \* There are some names that cannot be used because they are the names of fundamental functions in R (e.g., [here](https://stat.ethz.ch/R-manual/R-devel/library/base/html/Reserved.html) for a complete list). In general, even if it's allowed, it's best to not use other function **names** (e.g., 'c', 'T', 'mean', 'data', 'df', 'weights'). If in doubt, check the help to see if the name is already in use.
- \* It's best to avoid dots ('.') within names. Many function names in R itself have them and dots also have special meaning.
- \* It is recommended to use nouns for object names and verbs for function names.
- \* Be consistent in the styling of your code, such as where you put spaces, how you name objects, etc. See the [Fan](https://jef.works/R-style-guide/) and the [tidyverse](https://style.tidyverse.org/) style guides. The tidyverse style is very comprehensive and may seem overkill.

```
> What are known as 'objects' in 'R' are known as 'variables' in many other
> programming languages. Depending on the context, 'object' and 'variable' can
> have drastically different meanings. However, in this lesson, the two words
> are used synonymously. For more information see:
> https://cran.r-project.org/doc/manuals/r-release/R-lang.html#Objects
```

```

“{r, pur1 = FALSE}
weight_kg <- 55      # doesn't print anything
(weight_kg <- 55)    # but putting parenthesis around the call prints the value of 'weight_kg'
weight_kg            # and so does typing the name of the object

```

```
'''
```

Now that R has 'weight\_kg' in memory, we can do arithmetic with it. For instance, we may want to convert this weight into **pounds** (weight in pounds is 2.2 times the weight in kg)

```
'''{r, purl = FALSE}
2.2 * weight_kg
'''
```

We can also change an object's value by assigning it a new one:

```
'''{r, purl = FALSE}
weight_kg <- 57.5
2.2 * weight_kg
'''
```

This means that assigning a value to one object does not change the values of other objects. For example, let's store the animal's weight in pounds in a new object, 'weight\_lb':

```
'''{r, purl = FALSE}
weight_lb <- 2.2 * weight_kg
'''
```

and then change 'weight\_kg' to 100.

```
'''{r, purl = FALSE}
weight_kg <- 100
'''
```

What do you think is the current content of the object 'weight\_lb'? 126.5 or 220?

### ### Saving your code

Up to now, your code has been in the console. This is useful for quick queries but not so helpful if you want to revisit your work for any reason.

A script can be opened by pressing <kbd>Ctrl</kbd> + <kbd>Shift</kbd> + <kbd>N</kbd>.

It is wise to save your script file immediately. To do this press <kbd>Ctrl</kbd> + <kbd>S</kbd>. This will open a dialogue box where you can decide where to save your script file, and what to name it.

The '.R' file extension is added automatically and ensures your file will open with RStudio.

Don't forget to save your work periodically by pressing <kbd>Ctrl</kbd> + <kbd>S</kbd>.

### ### Comments

The comment character in R is '#'. Anything to the right of a '#' in a script will be ignored by R. It is useful to leave notes and explanations in your scripts.

For convenience, RStudio provides a keyboard shortcut to comment or uncomment a paragraph: after selecting the lines you want to comment, press at the same time on your keyboard `<kbd>Ctrl</kbd> + <kbd>Shift</kbd> + <kbd>C</kbd> . If you only want to comment out one line, you can put the cursor at any location of that line (i.e. no need to select the whole line), then press <kbd>Ctrl</kbd> + <kbd>Shift</kbd> + <kbd>C</kbd> .`

```
> ### Challenge
>
> What are the values after each statement in the following?
>
> ‘‘{r, purl = FALSE}
> mass <- 47.5           # mass?
> age  <- 122            # age?
> mass <- mass * 2.0      # mass?
> age  <- age - 20        # age?
> mass_index <- mass/age  # mass_index?
> ‘‘
```

```
‘‘{r, echo = FALSE, purl = TRUE}
### Challenge
##
## What are the values after each statement in the following?
##
## mass <- 47.5           # mass?
## age  <- 122            # age?
## mass <- mass * 2.0      # mass?
## age  <- age - 20        # age?
## mass_index <- mass/age  # mass_index?
‘‘
```

### ### Functions and their arguments

Functions are "canned scripts" that automate more complicated sets of commands including operations assignments, etc. Many functions are predefined, or can be made available by importing R *\*packages\** (more on that later). A function usually takes one or more inputs called *\*arguments\**. Functions **often** (but not always) return a *\*value\**. A typical example would be the function `'sqrt()'`. The **input** (the argument) must be a number, and the return **value** (in fact, the output) is the square root of that number. Executing a **function** (*'running it'*) is called *\*calling\** the function. An example of a function call is:

```
‘‘{r, eval = FALSE, purl = FALSE}
weight_kg <- sqrt(10)
‘‘
```

Here, the value of 10 is given to the `'sqrt()'` function, the `'sqrt()'` function calculates the square root, and returns the value which is then assigned to the object `'weight_kg'`. This function takes one argument, other functions might take several.

The return **'value'** of a function need not be **numerical** (like that of `'sqrt()'`), and it also does not need to be a single item: it can be a set of things, or even a dataset. We'll see that when we read data files into R.

Arguments can be anything, not only numbers or filenames, but also other objects. Exactly what each argument means differs per function, and must be looked up in the [documentation](#) (see below). Some functions take arguments which may either be specified by the user, or, if left out, take on a *\*default\** value: these are called *\*options\**. Options are typically used to alter the way the function operates, such as whether it ignores *'bad values'*, or what symbol to use in a plot. However, if you want something specific, you can specify a value of your choice which will be used instead of the default.

Let's try a function that can take multiple arguments: `'round()'`.

```
'''{r, results = 'show', purl = FALSE}
round(3.14159)
'''
```

Here, we've called `'round()'` with just one argument, `'3.14159'`, and it has returned the value `'3'`. That's because the default is to round to the nearest whole number. If we want more digits we can see how to do that by getting information about the `'round'` function. We can use `'args(round)'` to find what arguments it takes, or look at the help for this function using `'?round'`.

```
'''{r, results = 'show', purl = FALSE}
args(round)
'''
```

```
'''{r, eval = FALSE, purl = FALSE}
?round
'''
```

We see that if we want a different number of digits, we can type `'digits = 2'` or however many we want.

```
'''{r, results = 'show', purl = FALSE}
round(3.14159, digits = 2)
'''
```

If you provide the arguments in the exact same order as they are defined you don't have to name them:

```
'''{r, results = 'show', purl = FALSE}
round(3.14159, 2)
'''
```

And if you do name the arguments, you can switch their order:

```
'''{r, results = 'show', purl = FALSE}
round(digits = 2, x = 3.14159)
'''
```

It's good practice to put the non-optional arguments (like the number you're rounding) first in your function call, and to then specify the names of all optional arguments. If you don't, someone reading your code might have to look up the definition of a function with unfamiliar arguments to understand what you're

doing.

```
## Vectors and data types
```

```
```{r, echo = FALSE, purl = TRUE}
### Vectors and data types
```
```

A vector is the most common and basic data type in R, and is pretty much the workhorse of R. A vector is composed by a series of values, which can be either numbers or characters. We can assign a series of values to a vector using the `c()` function. For example we can create a vector of animal weights and assign it to a new object `weight_g`:

```
```{r, purl = FALSE}
weight_g <- c(50, 60, 65, 82)
weight_g
```
```

A vector can also contain characters:

```
```{r, purl = FALSE}
animals <- c("mouse", "rat", "dog")
animals
```
```

The quotes around `"mouse"`, `"rat"`, etc. are essential here. Without the quotes R will assume objects have been created called `'mouse'`, `'rat'` and `'dog'`. As these objects don't exist in R's memory, there will be an error message.

There are many functions that allow you to inspect the content of a vector. `length()` tells you how many elements are in a particular vector:

```
```{r, purl = FALSE}
length(weight_g)
length(animals)
```
```

An important feature of a vector, is that all of the elements are the same type of data. The function `class()` indicates what kind of object you are working with:

```
```{r, purl = FALSE}
class(weight_g)
class(animals)
```
```

The function `str()` provides an overview of the structure of an object and its elements. It is a useful function when working with large and complex objects:

```
```{r, purl = FALSE}
str(weight_g)
str(animals)
```
```

```
'''
```

You can use the `'c()'` function to add other elements to your vector:

```
'''{r, purl = FALSE}
weight_g <- c(weight_g, 90) # add to the end of the vector
weight_g <- c(30, weight_g) # add to the beginning of the vector
weight_g
'''
```

In the first line, we take the original vector `'weight_g'`, add the value `'90'` to the end of it, and save the result back into `'weight_g'`. Then we add the value `'30'` to the beginning, again saving the result back into `'weight_g'`.

We can do this over and over again to grow a vector, or assemble a dataset. As we program, this may be useful to add results that we are collecting or calculating.

An **atomic vector** is the simplest R **data type** and is a linear vector of a single type. Above, we saw 2 of the 6 main **atomic vector** types that R uses: `"character"` and `"numeric"` (or `"double"`). These are the basic building blocks that all R objects are built from. The other 4 **atomic vector** types are:

- \* `"logical"` for `'TRUE'` and `'FALSE'` (the boolean data type)
- \* `"integer"` for integer **numbers** (e.g., `'2L'`, the `'L'` indicates to R that it's an integer)
- \* `"complex"` to represent complex numbers with real and imaginary **parts** (e.g., `'1 + 4i'`) and that's **all we're** going to say about them
- \* `"raw"` for bitstreams that we won't discuss further

You can check the type of your vector using the `'typeof()'` function and inputting your vector as the argument.

Vectors are one of the many **data structures** that R uses. Other important ones are **lists** (`'list'`), **matrices** (`'matrix'`), **data frames** (`'data.frame'`), **factors** (`'factor'`) and **arrays** (`'array'`).

```
> ### Challenge
```

```
>
>
> * We've seen that atomic vectors can be of type character,
>   numeric (or double), integer, and logical. But what happens if we try to mix these types in
>   a single vector?
>
> '''{text_answer, echo=FALSE, purl=FALSE}
> R implicitly converts them to all be the same type
> '''
>
> * What will happen in each of these examples? (hint: use 'class()'
>   to check the data type of your objects):
>
>   '''r
>   num_char <- c(1, 2, 3, "a")
>   num_logical <- c(1, 2, 3, TRUE)
```

```

> char_logical <- c("a", "b", "c", TRUE)
> tricky <- c(1, 2, 3, "4")
>
>
> * Why do you think it happens?
>
> ``{text_answer, echo=FALSE, purl=FALSE}
> Vectors can be of only one data type. R tries to
> convert (coerce) the content of this vector to find a "common
> denominator" that doesn't lose any information.
> ``
>
> * How many values in 'combined_logical' are "TRUE" (as a character) in the
> following example (reusing the 2 '..._logical's from above):
>
> ``r
> combined_logical <- c(num_logical, char_logical)
> ``
>
> ``{text_answer, echo=FALSE, purl=FALSE}
> Only one. There is no memory of past data types, and the coercion happens the
> first time the vector is evaluated. Therefore, the 'TRUE' in 'num_logical'
> gets converted into a '1' before it gets converted into "1" in
> 'combined_logical'.
> ``
>
> * You've probably noticed that objects of different types get
> converted into a single, shared type within a vector. In R, we
> call converting objects from one class into another class
> _coercion_. These conversions happen according to a hierarchy,
> whereby some types get preferentially coerced into other
> types. Can you draw a diagram that represents the hierarchy of how
> these data types are coerced?
>
> ``{text_answer, echo=FALSE, purl=FALSE}
> logical &#8594; numeric &#8594; character &#8592; logical
> ``
>
> ``{r, echo = FALSE, eval = FALSE, purl = TRUE}
## We've seen that atomic vectors can be of type character, numeric, integer, and
## logical. But what happens if we try to mix these types in a single
## vector?
>
> ## What will happen in each of these examples? (hint: use 'class()' to
## check the data type of your object)
num_char <- c(1, 2, 3, "a")
>
num_logical <- c(1, 2, 3, TRUE)
>
char_logical <- c("a", "b", "c", TRUE)
>
tricky <- c(1, 2, 3, "4")

```



*## Why do you think it happens?*

*## How many values in 'combined\_logical' are 'TRUE' (as a character) in the following example:*

```
combined_logical <- c(num_logical, char_logical)
```

*## You've probably noticed that objects of different types get converted into a single, shared type within a vector. In R, we call converting objects from one class into another class \_coercion\_. These conversions happen according to a hierarchy, whereby some types get preferentially coerced into other types. Can you draw a diagram that represents the hierarchy of how these data types are coerced?*

```
'''
```

*## Subsetting vectors*

If we want to extract one or several values from a vector, we must provide one or several indices in square brackets. For instance:

```
'''{r, results = 'show', purl = FALSE}
animals <- c("mouse", "rat", "dog", "cat")
animals[2]
animals[c(3, 2)]
'''
```

We can also repeat the indices to create an object with more elements than the original one:

```
'''{r, results = 'show', purl = FALSE}
more_animals <- animals[c(1, 2, 3, 2, 1, 4)]
more_animals
'''
```

R indices start at 1. Programming languages like Fortran, MATLAB, Julia, and R start counting at 1, because that's what human beings typically do. Languages in the C family (including C++, Java, Perl, and Python) count from 0 because that's simpler for computers to do.

*### Conditional subsetting*

Another common way of subsetting is by using a logical vector. 'TRUE' will select the element with the same index, while 'FALSE' will not:

```
'''{r, results = 'show', purl = FALSE}
weight_g <- c(21, 34, 39, 54, 55)
weight_g[c(TRUE, FALSE, FALSE, TRUE, TRUE)]
'''
```

Typically, these logical vectors are not typed by hand, but are the output of other functions or logical tests. For instance, if you wanted to select only the values above 50:

```

''{r, results = 'show', purl = FALSE}
weight_g > 50    # will return logicals with TRUE for the indices that meet the condition
## so we can use this to select only the values above 50
weight_g[weight_g > 50]
''

```

You can combine multiple tests using '&' (both conditions are true, AND) or '|' (at least one of the conditions is true, OR):

```

''{r, results = 'show', purl = FALSE}
weight_g[weight_g > 30 & weight_g < 50]
weight_g[weight_g <= 30 | weight_g == 55]
weight_g[weight_g >= 30 & weight_g == 21]
''

```

Here, '>' for "greater than", '<' stands for "less than", '<=' for "less than or equal to", and '==' for "equal to". The double equal sign '==' is a test for numerical equality between the left and right hand sides, and should not be confused with the single '=' sign, which performs variable **assignment** (similar to '<-').

A common task is to search for certain strings in a vector. One could use the "or" operator '|' to test for equality to multiple values, but this can quickly become tedious. The function '%in%' allows you to test if any of the elements of a search vector are found:

```

''{r, results = 'show', purl = FALSE}
animals <- c("mouse", "rat", "dog", "cat", "cat")

# return both rat and cat
animals[animals == "cat" | animals == "rat"]

# return a logical vector that is TRUE for the elements within animals
# that are found in the character vector and FALSE for those that are not
animals %in% c("rat", "cat", "dog", "duck", "goat", "bird", "fish")

# use the logical vector created by %in% to return elements from animals
# that are found in the character vector
animals[animals %in% c("rat", "cat", "dog", "duck", "goat", "bird", "fish")]
''

```

```

> ### Challenge (optional){.challenge}
>
> * Can you figure out why '"four" > "five"' returns 'TRUE'?
>
> ''{text_answer, echo=FALSE, purl=FALSE}
> When using ">" or "<" on strings, R compares their alphabetical order.
> Here "four" comes after "five", and therefore is "greater than" it.
> ''

```

```

''{r, echo = FALSE, purl = TRUE}
### Challenge (optional)
##

```

```
## * Can you figure out why "four" > "five" returns TRUE?
'''
```

```
## Missing data
```

As R was designed to analyze datasets, it includes the concept of missing data (which is uncommon in other programming languages). Missing data are represented in vectors as 'NA'.

When doing operations on numbers, most functions will return 'NA' if the data you are working with include missing values. This feature makes it harder to overlook the cases where you are dealing with missing data. You can add the argument 'na.rm = TRUE' to calculate the result as if the missing values were **removed** ('rm' stands for ReMoved) first.

```
'''{r, purl = FALSE}
heights <- c(2, 4, 4, NA, 6)
mean(heights)
max(heights)
mean(heights, na.rm = TRUE)
max(heights, na.rm = TRUE)
'''
```

If your data include missing values, you may want to become familiar with the functions 'is.na()', 'na.omit()', and 'complete.cases()'. See below for examples.

```
'''{r, purl = FALSE}
## Extract those elements which are not missing values.
heights[!is.na(heights)]

## Returns the object with incomplete cases removed.
#The returned object is an atomic vector of type "numeric" (or #"double").
na.omit(heights)

## Extract those elements which are complete cases.
#The returned object is an atomic vector of type "numeric" (or #"double").
heights[complete.cases(heights)]
'''
```

Recall that you can use the 'typeof()' function to find the type of your atomic vector.

```
> ### Challenge
```

```
>
```

```
> 1. Using this vector of heights in inches, create a new vector, 'heights_no_na', with the NAs removed.
```

```
>
```

```
>     '''r
>     heights <- c(63, 69, 60, 65, NA, 68, 61, 70, 61, 59, 64, 69, 63, 63, NA, 72, 65, 64, 70, 63, 65)
>     '''
```

```
> 2. Use the function 'median()' to calculate the median of the 'heights' vector.
```

```
>
```

```
> 3. Use R to figure out how many people in the set are taller than 67 inches.
```

```
>
```

```

> ‘‘{r, answer=TRUE}
> heights <- c(63, 69, 60, 65, NA, 68, 61, 70, 61, 59, 64, 69, 63, 63, NA, 72, 65, 64, 70, 63, 65)
>
> # 1.
> heights_no_na <- heights[!is.na(heights)]
> # or
> heights_no_na <- na.omit(heights)
> # or
> heights_no_na <- heights[complete.cases(heights)]
>
> # 2.
> median(heights, na.rm = TRUE)
>
> # 3.
> heights_above_67 <- heights_no_na[heights_no_na > 67]
> length(heights_above_67)
> ‘‘

‘‘{r, echo = FALSE, purl = TRUE}
## ### Challenge
## 1. Using this vector of heights in inches, create a new vector with the NAs removed.
##
## heights <- c(63, 69, 60, 65, NA, 68, 61, 70, 61, 59, 64, 69, 63, 63, NA, 72, 65, 64, 70, 63, 65)
##
## 2. Use the function ‘median()’ to calculate the median of the ‘heights’ vector.
##
## 3. Use R to figure out how many people in the set are taller than 67 inches.
‘‘

Now that we have learned how to write scripts, and the basics of R’s data
structures, we are ready to start working with the Portal dataset we have been
using in the other lessons, and learn about data frames.

‘‘{r, child="_page_built_on.Rmd"}
‘‘

## Error: attempt to use zero-length variable name

```

The R session information (including the OS info, R version and all packages used):

```

sessionInfo()

## R version 4.2.1 (2022-06-23 ucrt)
## Platform: x86_64-w64-mingw32/x64 (64-bit)
## Running under: Windows 10 x64 (build 19045)
##
## Matrix products: default
##
## locale:
## [1] LC_COLLATE=English_New Zealand.utf8 LC_CTYPE=English_New Zealand.utf8
## [3] LC_MONETARY=English_New Zealand.utf8 LC_NUMERIC=C
## [5] LC_TIME=English_New Zealand.utf8

```

```
##
## attached base packages:
## [1] stats      graphics  grDevices utils      datasets  methods   base
##
## other attached packages:
## [1] ggrepel_0.9.2      ggthemes_4.2.4      sf_1.0-9             leaflet_2.1.1
## [5] fpp_0.5            tseries_0.10-53     lmtest_0.9-40        zoo_1.8-11
## [9] expsmoother_2.3    fma_2.4             forecast_8.20        seasonal_1.9.0
## [13] lubridate_1.9.1    timetk_2.8.2        yardstick_1.1.0      workflowsets_1.0.0
## [17] workflows_1.1.2    tune_1.0.1          rsample_1.1.1        recipes_1.0.4
## [21] parsnip_1.0.3      modeldata_1.1.0     infer_1.0.4          dials_1.1.0
## [25] scales_1.2.1       broom_1.0.3         tidymodels_1.0.0     modeltime_1.2.4
## [29] flextable_0.8.5    XKCDdata_0.1.0     forcats_1.0.0        stringr_1.5.0
## [33] dplyr_1.1.0        purrr_1.0.1         readr_2.1.3          tidyr_1.3.0
## [37] tibble_3.1.8       ggplot2_3.4.0       tidyverse_1.3.2      knitr_1.42
##
## loaded via a namespace (and not attached):
## [1] utf8_1.2.3          tidymodels_1.2.0     htmlwidgets_1.6.1    grid_4.2.1
## [5] munsell_0.5.0       units_0.8-1          codetools_0.2-18     xgboost_1.7.3.1
## [9] future_1.31.0       withr_2.5.0          colorspace_2.1-0     highr_0.10
## [13] uuid_1.1-0          rstudioapi_0.14      stats4_4.2.1         wk_0.7.1
## [17] officer_0.5.2       TTR_0.24.3           listenv_0.9.0        labeling_0.4.2
## [21] rstan_2.21.8        DiceDesign_1.9       farver_2.1.1         parallelly_1.34.0
## [25] vctrs_0.5.2         generics_0.1.3       ipred_0.9-13         xfun_0.37
## [29] timechange_0.2.0    R6_2.5.1             lhs_1.1.6            cachem_1.0.6
## [33] assertthat_0.2.1    promises_1.2.0.1     nnet_7.3-17          googlesheets4_1.0.1
## [37] gtable_0.3.1        globals_0.16.2       processx_3.8.0       timeDate_4022.108
## [41] rlang_1.0.6         systemfonts_1.0.4    splines_4.2.1        lazyeval_0.2.2
## [45] gargle_1.3.0        inline_0.3.19        s2_1.1.2             yaml_2.3.7
## [49] modelr_0.1.10       crosstalk_1.2.0      backports_1.4.1      httpuv_1.6.8
## [53] quantmod_0.4.20     tools_4.2.1          lava_1.7.1           ellipsis_0.3.2
## [57] proxy_0.4-27        Rcpp_1.0.10          base64enc_0.1-3      classInt_0.4-8
## [61] ps_1.7.2            prettyunits_1.1.1    rpart_4.1.16         openssl_2.0.5
## [65] fracdiff_1.5-2      haven_2.5.1          fs_1.6.0             tinytex_0.44
## [69] furrr_0.3.1         crul_1.3             magrittr_2.0.3        data.table_1.14.6
## [73] reprex_2.0.2        GPfit_1.0-8          googledrive_2.0.0    x13binary_1.1.57-3
## [77] matrixStats_0.63.0  hms_1.1.2           mime_0.12            evaluate_0.20
## [81] xtable_1.8-4        readxl_1.4.1         gridExtra_2.3         compiler_4.2.1
## [85] KernSmooth_2.23-20  crayon_1.5.2         StanHeaders_2.21.0-7  htmltools_0.5.4
## [89] later_1.3.0         tzdb_0.3.0           RcppParallel_5.1.6    DBI_1.1.3
## [93] dbplyr_2.3.0        MASS_7.3-57          Matrix_1.5-3         cli_3.6.0
## [97] quadprog_1.5-8      parallel_4.2.1       gower_1.0.1          pkgconfig_2.0.3
## [101] plotly_4.10.1       xml2_1.3.3           foreach_1.5.2         hardhat_1.2.0
## [105] prodlim_2019.11.13  rvest_1.0.3          snakecase_0.11.0      callr_3.7.3
## [109] digest_0.6.31       janitor_2.2.0        httpcode_0.3.0       rmarkdown_2.20
## [113] cellranger_1.1.0    gdtools_0.3.0        curl_5.0.0           shiny_1.7.4
## [117] urca_1.3-3          lifecycle_1.0.3      nlme_3.1-157         jsonlite_1.8.4
## [121] viridisLite_0.4.1   askpass_1.1          fansi_1.0.4          pillar_1.8.1
## [125] lattice_0.20-45     loo_2.5.1            fastmap_1.1.0        httr_1.4.4
## [129] pkgbuild_1.4.0      survival_3.3-1       glue_1.6.2           xts_0.12.2
## [133] zip_2.2.2           iterators_1.0.14     class_7.3-20         stringi_1.7.12
## [137] prophet_1.0         gfonts_0.2.0         memoise_2.0.1        e1071_1.7-13
## [141] future.apply_1.10.0
```

```
Sys.time()
```

```
## [1] "2023-02-03 13:23:01 NZDT"
```