
slug Documentation

Release 2.0

Mark Krumholz, Michele Fumagalli, et al.

January 03, 2015

1	License	3
2	Introduction to SLUG	5
2.1	What Does SLUG Do?	5
2.2	Cluster Simulations and Galaxy Simulations	5
2.3	Probability Distribution Functions: the IMF, SFH, CMF, CLF, A_V distribution	5
2.4	Spectra and Photometry	6
2.5	Monte Carlo Simulation	7
2.6	Nebular Processing	7
2.7	Extinction	8
3	Compiling and Installing SLUG	11
3.1	Dependencies	11
3.2	Compiling	11
4	Running a SLUG simulation	13
5	Parameter Specification	15
5.1	File Format	15
5.2	Basic Keywords	15
5.3	Simulation Control Keywords	15
5.4	Output Control Keywords	16
5.5	Physical Model Keywords	17
5.6	Photometric Filter Keywords	18
6	Probability Distribution Functions	21
6.1	Basic Mode	21
6.2	Advanced Mode	23
6.3	Sampling Methods	24
7	Output Files and Format	27
7.1	The integrated_prop File	27
7.2	The integrated_spec File	28
7.3	The integrated_phot File	29
7.4	The cluster_prop File	31
7.5	The cluster_spec File	32
7.6	The cluster_phot File	33
8	Filters and Filter Data	35
9	slugpy – The Python Helper Library	37
9.1	Basic Usage	37

9.2	Full Documentation of slugpy	39
10	cloudy_slug: An Automated Interface to cloudy	53
10.1	cloudy_slug Basics	53
10.2	The cloudy_slug Physical Model: Integrated Mode Versus Cluster Mode	54
10.3	The cloudy_slug Input Template	55
10.4	The cloudy_slug Interface Script	56
10.5	Full Description of cloudy_slug Output	57
10.6	Full Documentation of slugpy.cloudy	62
11	bayesphot: Bayesian Inference for Stochastic Stellar Populations	71
11.1	Full Documentation of slugpy.bayesphot	71
12	cluster_slug: Bayesian Inference of Star Cluster Properties	75
12.1	Full Documentation of slugpy.cluster_slug	75
13	sfr_slug: Bayesian Inference of Star Formation Rates	79
13.1	Full Documentation of slugpy.sfr_slug	79
14	Test Problems	83
14.1	Problem example_galaxy: basic galaxy simulation	83
14.2	Problem example_cluster: basic cluster simulation	83
14.3	Problem constsampl: importance of constrained sampling	84
14.4	Problem sampling: different sampling techniques	84
14.5	Problem imfchoice: different IMF implementations	85
14.6	Problem clfraction: cluster fraction at work	85
14.7	Problem cmfchoice: different CMF implementations	86
14.8	Problem sfhsampling: realizations of SFH	86
14.9	Problem cldisrupt: cluster disruption at work	87
14.10	Problem spectra: full spectra	88
15	Contributors and Acknowledgements	89
16	Indices and tables	91
	Python Module Index	93

Contents:

LICENSE

SLUG is distributed under the terms of the [GNU General Public License version 3.0](#). The text of the license is included in the main directory of the repository as `GPL-3.0.txt`.

INTRODUCTION TO SLUG

This is a guide for users of the SLUG software package. SLUG is distributed under the terms of the [GNU General Public License v. 3.0](#). A copy of the license notification is included in the main SLUG directory. If you use SLUG in any published work, please cite the SLUG method paper, da Silva, R. L., Fumagalli, M., & Krumholz, M. R., 2012, *The Astrophysical Journal*, 745, 145. A second method paper, describing the upgraded version 2 code and a set of ancillary tools, is in preparation at this time.

2.1 What Does SLUG Do?

SLUG is a stellar population synthesis (SPS) code, meaning that, for a specified stellar initial mass function (IMF), star formation history (SFH), cluster mass function (CMF), cluster lifetime function (CLF), and (optionally) distribution of extinctions (A_V), it predicts the spectra and photometry of both individual star clusters and the galaxies (or sub-regions of galaxies) that contain them. In this regard, SLUG operates much like any other SPS code. The main difference is that SLUG regards the functions describing the stellar population as probability distributions, and the resulting stellar population as being the result of a draw from them. SLUG performs a Monte Carlo simulation to determine the PDF of the light produced by the stellar populations that are drawn from these distributions. The remainder of this section briefly describes the major conceptual pieces of a SLUG simulation. For a more detailed description, readers are referred to da Silva, Fumagalli, & Krumholz (2012).

2.2 Cluster Simulations and Galaxy Simulations

SLUG can simulate either a simple stellar population (i.e., a group of stars all born at one time) or a composite stellar population, consisting of stars born at a distribution of times. We refer to the former case as a “cluster” simulation, and the latter as a “galaxy” simulation, since one can be thought of as approximating the behavior of a single star cluster, and the other as approximating a whole galaxy.

2.3 Probability Distribution Functions: the IMF, SFH, CMF, CLF, A_V distribution

As mentioned above, SLUG regards the IMF, SFH, CMF, CLF, and extinction A_V as probability distribution functions. These PDFs can be described by a very wide range of possible functional forms; see *Probability Distribution Functions* for details on the exact functional forms allowed, and on how they can be specified in the code. When SLUG runs a cluster simulation, it draws stars from the specified IMF in an attempt to produce a cluster of a user-specified total mass. There are a number of possible methods for performing such mass-limited sampling, and SLUG gives the user a wide menu of options; see *Probability Distribution Functions*. SLUG will also, upon user request, randomly draw a visual extinction A_V to be applied to the light.

For a galaxy simulation, the procedure involves one extra step. In this case, SLUG assumes that some fraction f_c of the stars in the galaxy are born in star clusters, which, for the purposes of SLUG, means that they all share the same birth time. The remaining fraction $1 - f_c$ of stars are field stars. When a galaxy simulation is run, SLUG determines the total mass of stars M_* that should have formed since the start of the simulation (or since the last output, if more than one output is requested) from the star formation history, and then draws field stars and star clusters in an attempt to produce masses $(1 - f_c)M_*$ and $f_c M_*$. For the field stars, the stellar masses are drawn from the IMF, in a process completely analogous to the cluster case, and each star is given its own randomly-generated extinction. For star clusters, the masses of the clusters are drawn from the CMF, and each cluster is then populated from the IMF as in the cluster case. Again, each cluster gets its own extinction. For both the field stars and the star clusters, the time of their birth is drawn from the PDF describing the SFH.

Finally, star clusters can be disrupted independent of the fate of their parent stars. When each cluster is formed, it is assigned a lifetime drawn from the CLF. Once that time has passed, the cluster ceases to be entered in the lists of individual cluster spectra and photometry (see next section), although the individual stars continue to contribute to the integrated light of the galaxy.

2.4 Spectra and Photometry

Once SLUG has drawn a population of stars, its final step is to compute the light they produce. SLUG does this in several steps. First, it computes the physical properties of all the stars present user-specified times using a set of stellar evolutionary tracks. Second, it uses these physical properties to compute the composite spectra produced by the stars, using a user-specified set of stellar atmosphere models. Formally, the quantity computed is the specific luminosity per unit wavelength L_λ . Third, if nebular emission is enabled, the code calculates the spectrum $L_{\lambda,\text{neb}}$ that emerges after the starlight passes through the HII region around the star – see [Nebular Processing](#). Fourth, if extinction is enabled, SLUG computes the extincted stellar and nebula-processed spectra $L_{\lambda,\text{ex}}$ and $L_{\lambda,\text{neb,ex}}$ – see [Extinction](#). Fifth and finally, SLUG computes photometry for the stellar population by integrating all computed spectra over a set of specified photometric filters. Depending on the options specified by the user and the filter under consideration, the photometric value output will be one of the following:

- The frequency-averaged luminosity across the filter, defined as

$$\langle L_\nu \rangle_R = \frac{\int L_\nu d \ln \nu}{\int R_\nu (\nu/\nu_c)^\beta d \ln \nu},$$

where L_ν is the specific luminosity per unit frequency, R_ν is the filter response function per photon at frequency ν , ν_c is the central wavelength of the filter, and β is a constant that is defined by convention for each filter, and is either 0, 1, or 2; usually it is 0 for optical and UV filters.

- The wavelength-averaged luminosity across the filter, defined as

where L_λ is the specific luminosity per unit wavelength, R_λ is the filter response function per photon at wavelength λ , and λ_c is the central wavelength of the filter.

- The AB magnitude, defined by

$$M_{\text{AB}} = -2.5 \log_{10} \left[\frac{\langle L_\nu \rangle_R}{4\pi (10 \text{ pc})^2} \right] - 48.6,$$

where $\langle L_\nu \rangle_R$ is in units of $\text{erg s}^{-1} \text{ Hz}^{-1}$.

- The ST magnitude, defined by

$$M_{\text{ST}} = -2.5 \log_{10} \left[\frac{\langle L_\lambda \rangle_R}{4\pi (10 \text{ pc})^2} \right] - 21.1,$$

where $\langle L_\lambda \rangle_R$ is in units of $\text{erg s}^{-1} \text{ Angstrom}^{-1}$.

- The Vega magnitude, defined by

$$M_{\text{Vega}} = M_{\text{AB}} - M_{\text{AB}}(\text{Vega}),$$

where $M_{\text{AB}}(\text{Vega})$ is the AB magnitude of Vega. The latter quantity is computed on the fly, using a stored Kurucz model spectrum for Vega.

- The photon flux above some threshold ν_0 , defined as

$$Q(\nu_0) = \int_{\nu_0}^{\infty} \frac{L_{\nu}}{h\nu} d\nu.$$

- The bolometric luminosity,

$$L_{\text{bol}} = \int_0^{\infty} L_{\nu} d\nu.$$

If nebular processing and/or extinction are enabled, photometric quantities are computed separately for each available version of the spectrum, L_{λ} , $L_{\lambda,\text{neb}}$, $L_{\lambda,\text{ex}}$, and $L_{\lambda,\text{neb,ex}}$.

For a cluster simulation, this procedure is applied to the star cluster being simulated at a user-specified set of output times. For a galaxy simulation, the procedure is much the same, but it can be done both for all the stars in the galaxy taken as a whole, and individually for each star cluster that is still present (i.e., that has not been disrupted).

2.5 Monte Carlo Simulation

The steps described in the previous two section are those required for a single realization of the stellar population. However, the entire point of SLUG is to repeat this procedure many times in order to build up the statistics of the population light output. Thus the entire procedure can be repeated as many times as the user desires.

2.6 Nebular Processing

SLUG includes methods for post-processing the output starlight to compute the light that will emerge from the HII region around star clusters, and to further apply extinction to that light.

Nebular emission is computed by assuming that all the ionizing photons are absorbed in a uniform-density, uniform-temperature HII region around each star cluster / star, and then computing the resulting emission at non-ionizing energies. The calculation assumes that the HII region is in photoionization equilibrium, and consists of hydrogen that is fully ionized and helium that is singly ionized. Under these assumptions the volume V , electron density n_e , and hydrogen density n_H are related to the hydrogen ionizing luminosity $Q(\text{H}^0)$ via

$$\phi_{\text{dust}} Q(\text{H}^0) = \alpha_B(T) n_e n_H V$$

Here ϕ_{dust} is the fraction of ionizing photons that are absorbed by hydrogen rather than dust grains, and $\alpha_B(T)$ is the temperature-dependent case B recombination rate coefficient. SLUG approximates $\alpha_B(T)$ using the analytic approximation given by equation 14.6 of [Draine \(2011, Physics of the Interstellar and Intergalactic Medium, Princeton University Press\)](#), while ϕ_{dust} and T are user-chosen parameters.

The relation above determines $n_e n_H V$, and from this SLUG computes the nebular emission including the following processes:

- Hydrogen free-free and H I bound-free emission
- Hydrogen 2-photon emission

- Hydrogen recombination lines from all lines with upper levels $n_u \leq 25$
- He II free-free and He I bound-free emission
- The brightest 33 brightest He I recombination and collisionally-excited lines

Formally, the luminosity per unit wavelength is computed as

$$L_{\lambda, \text{neb}} = \left[\gamma_{\text{ff}}^{(\text{H})} + \gamma_{\text{bf}}^{(\text{H})} + \gamma_{2\text{p}}^{(\text{H})} + \sum_{n, n' \leq 25, n < n'} \alpha_{nn'}^{\text{eff}, \text{B}, (\text{H})} E_{nn'}^{(\text{H})} + x_{\text{He}} \gamma_{\text{ff}}^{(\text{He})} + x_{\text{He}} \gamma_{\text{bf}}^{(\text{He})} + x_{\text{He}} \sum_{i=1}^{33} \gamma_{i, \text{line}}^{(\text{He})} \right] n_e n_{\text{H}} V$$

Here $n_e n_{\text{H}} V = \phi_{\text{dust}} Q(\text{H}^0) / \alpha_{\text{B}}(T)$ from photoionization equilibrium, $E_{nn'}$ is the energy difference between hydrogen levels n and n' , and the remaining terms and their sources appearing in this equation are:

- $\gamma_{\text{ff}}^{(\text{H})}$ and $\gamma_{\text{bf}}^{(\text{H})}$: hydrogen free-free and bound-free emissivity, from the tabulation of [Ferland \(1980, PASP, 92, 596\)](#) for wavelengths up to 13.1 μm , and from the analytic approximation of [Draine \(2011, eqn. 10.8\)](#) at longer wavelengths
- $\gamma_{2\text{p}}^{(\text{H})}$: hydrogen two-photon emissivity, computed as $\gamma_{2\text{p}}^{(\text{H})} = [hc/\lambda^3] I(\text{H}^0) P_{\nu} \alpha_{2s}^{\text{eff}, (\text{H})} / [1 + (n_{\text{H}} q_{2s-2p, p} + (1 + x_{\text{He}}) n_{\text{H}} q_{2s-2p, e}) / A_{2s-1s}]$. The quantities appearing in this expression are:
 - $I(\text{H}^0)$ is the hydrogen ionization potential
 - P_{ν} is the frequency distribution for two-photon emission, computed from the analytic approximation of [Nussbaumer & Schmutz \(1984, A&A, 138, 495\)](#)
 - $\alpha_{2s}^{\text{eff}, (\text{H})}$ is the effective recombination rate to the 2s state, taken from the tabulation of [Storey & Hummer \(1995, MNRAS, 272, 41\)](#)
 - $q_{2s-2p, p}$ and $q_{2s-2p, e}$ are the collisional rate coefficients for transitions from the 2s to the 2p state induced by collisions with protons and electrons, respectively, taken from [Osterbrock \(1989, University Science Books, table 4.10\)](#)
 - A_{2s-1s} is the Einstein coefficient for the hydrogen 2s-1s two-photon emission process, taken from [Draine \(2011, section 14.2.4\)](#)
- $\alpha_{nn'}^{\text{eff}, \text{B}, (\text{H})}$ is the effective emission rate coefficient for the n to n' H recombination line, taken from the tabulation of [Storey & Hummer \(1995, MNRAS, 272, 41\)](#)
- $\gamma_{i, \text{line}}^{(\text{He})}$ is the emissivity for the brightest recombination and collisionally-excited lines of He^+ , taken from the tabulation of [Benjamin et al. \(1999, ApJ, 514, 307\)](#)

2.7 Extinction

If extinction is enabled, SLUG applies extinction to the stellar spectra and, if nebular processing is enabled as well, to the spectrum that emerges from the nebula. Note that the nebular plus extincted spectrum computation is not fully self-consistent, in that the dust absorption factor ϕ_{dust} used in the nebular emission calculation (see [Nebular Processing](#)) is not affected by the value of A_V used in the calculation.

SLUG computes the extincted spectrum as

$$L_{\lambda, \text{ex}} = L_{\lambda} e^{-\tau_{\lambda}}$$

where the optical depth $\tau_{\lambda} = (\kappa_{\lambda} / \kappa_V) (A_V / 1.086)$, A_V is the visual extinction in mag, the factor 1.086 is the conversion between magnitudes and the true dimensionless optical depth, κ_{λ} is a user-specified input extinction at wavelength λ , and the V-band mean opacity is defined by

$$\kappa_V = \frac{\int \kappa_{\nu} R_{\nu}(V) d\nu}{\int R_{\nu}(V) d\nu}$$

where $R_\nu(V)$ is the filter response function as frequency ν for the Johnson V filter. The extinction curve κ_λ can be specified via a user-provided file, or the user may select from a set of pre-defined extinction curves; see [Physical Model Keywords](#) for details.

The computation for $L_{\lambda,\text{neb,ex}}$ is analogous.

COMPILING AND INSTALLING SLUG

3.1 Dependencies

The core SLUG program requires

- The [Boost C++ libraries](#)
- The [GNU scientific library](#)
- The [cfitsio library](#) (optional, only required for FITS capabilities)

Compilation will be easiest if you install these libraries such that the header files are included in your `CXX_INCLUDE_PATH` and the compiled object files are in your `LD_LIBRARY_PATH`. Alternately, you can manually specify the locations of these files by editing the Makefiles – see below. The `cfitsio` library is optional, and is only required if you want the ability to write FITS output. To compile without it, use the flag `FITS=DISABLE_FITS` when calling `make` (see below). Note that SLUG uses some Boost libraries that must be built separately (see the Boost documentation on how to build and install Boost libraries).

In addition to the core dependencies, `slugpy`, the python helper library requires:

- [numpy](#)
- [scipy](#)
- [astropy](#) (optional, only required for FITS capabilities)

Finally, the cloudy coupling capability requires:

- [cloudy](#)

This is only required performing cloudy runs, and is not required for any other part of SLUG.

3.2 Compiling

If you have `boost`, `GSL`, and (if you're using it) `cfitsio` included in your `CXX_INCLUDE_PATH` and `LD_LIBRARY_PATH` environment variables, and your system is running either MacOSX or Linux, you should be able to compile simply by doing:

```
make
```

from the main `slug` directory. To compile in debug mode, do:

```
make debug
```

instead. To compile without `cfitsio`, do:

```
make FITS=DISABLE_FITS
```

Alternately, you can manually specify the compiler flags to be used by creating a file named `Make.mach.MACHINE_NAME` in the `src` directory, and then doing:

```
make MACHINE=MACHINE_NAME
```

An example machine-specific file, `src/Make.mach.ucsc-hyades` is included in the repository. You can also override or reset any compilation flag you want by editing the file `src/Make.config.override`.

Finally, note that SLUG is written in C++11, and requires some C++11 features, so it may not work with older C++ compilers. The following compiler versions are known to work: gcc \geq 4.8 (4.7 works on most but not all platforms), clang/llvm \geq 3.3, icc \geq 14.0. Earlier versions may work as well, but no guarantees.

RUNNING A SLUG SIMULATION

Once SLUG is compiled, running a simulation is extremely simple. The first step, which is not required but makes life a lot simpler, is to set the environment variable `SLUG_DIR` to the directory where you have installed SLUG. If you are using a `bash`-like shell, the syntax for this is:

```
export SLUG_DIR = /path/to/slug
```

while for a `csh`-like shell, it is:

```
setenv SLUG_DIR /path/to/slug
```

This is helpful because SLUG needs a lot of input data, and if you don't set this variable, you will have to manually specify where to find it.

Next, to run on a single processor, just do:

```
./bin/slug param/filename.param
```

where `filename.param` is the name of a parameter file, formatted as specified in *Parameter Specification*. The code will write a series of output files as described in *Output Files and Format*.

If you have more than one core at your disposal, you can also run SLUG in parallel, using the command line:

```
python ./bin/slug.py param/filename.param
```

This called a python script that automatically divides up the Monte Carlo trials you have requested between the available processors, then consolidates the output so that it looks the same as if you had run a single-processor job. The python script allows fairly fine-grained control of the parallelism. It accepts the following command line arguments:

- `-n NPROC, --nproc NPROC`: this parameter specifies the number of simultaneous SLUG processes to run. It defaults to the number of cores present on the machine where the code is running
- `-b BATCHSIZE, --batchsize BATCHSIZE`: this specifies how to many trials to do per SLUG process. It defaults to the total number of trials requested divided by the total number of processes, rounded up, so that only one SLUG process is run per processor. *Rationale*: The default behavior is optimal from the standpoint of minimizing the overhead associated with reading data from disk, etc. However, if you are doing a very large number of runs that are going to require hours, days, or weeks to complete, and you probably want the code to checkpoint along the way. In that case it is probably wise to set this to a value smaller than the default in order to force output to be dumped periodically.
- `-nc, --noconsolidate`: by default the `slug.py` script will take all the outputs produced by the parallel runs and consolidate them into single output files, matching what would have been produced had the code been run in serial mode. If set, this flag suppresses that behavior, and instead leaves the output as a series of files whose root names match the model name given in the parameter file, plus the extension `_pppppp_nnnnnn`, where the digits `ppppp` give the number of the processor that produces that file, and the digits `nnnnn` give the run number on that processor. *Rationale*: normally consolidation is convenient. However, if the output is very large, this may produce undesirably bulky files. Furthermore, if one is doing a very large number of simulations

over an extended period, and the `slug.py` script is going to be run multiple times (e.g. due to wall clock limits on a cluster), it may be preferable to leave the files unconsolidated until all runs have been completed.

PARAMETER SPECIFICATION

5.1 File Format

An example parameter file is included as `param/example.param` in the source tree. Parameter files for SLUG are generically formatted as a series of entries of the form:

```
keyword    value
```

Any line starting with `#` is considered to be a comment and is ignored, and anything on a line after a `#` is similarly treated as a comment and ignored. Some general rules on keywords are:

- Keywords may appear in any order.
- Some keywords have default values, indicated in parenthesis in the list below. These keywords are optional and need not appear in the parameter file. All others are required.
- Keywords and values are case-insensitive.
- Unless explicitly stated otherwise, units for mass are always M_{\odot} , units for time are always yr.
- Any time a file or directory is specified, if it is given as a relative rather than absolute path, it is assumed to be relative to the environment variable `$SLUG_DIR`. If this environment variable is not set, it is assumed to be relative to the current working directory.

The keywords recognized by SLUG can be categorized as described in the remainder of this section.

5.2 Basic Keywords

These specify basic data for the run.

- `model_name` (default: `SLUG_DEF`): name of the model. This will become the base filename for the output files.
- `out_dir` (default: `output`): name of the directory into which output should be written.
- `verbosity` (default: 1): level of verbosity when running, with 0 indicating no output, 1 indicating some output, and 2 indicating a great deal of output.

5.3 Simulation Control Keywords

These control the operation of the simulation.

- `sim_type` (default: `galaxy`): set to `galaxy` to run a galaxy simulation (a composite stellar population), or to `cluster` to run a cluster simulation (a simple stellar population)
- `n_trials` (default: 1): number of trials to run
- `log_time` (default: 0): set to 1 for logarithmic time step, 0 for linear time steps
- `time_step`: size of the time step. If `log_time` is set to 0, this is in yr. If `log_time` is set to 1, this is in dex (i.e., a value of 0.2 indicates that every 5 time steps correspond to a factor of 10 increase in time).
- `start_time`: first output time. This may be omitted if `log_time` is set to 0, in which case it defaults to a value equal to `time_step`.
- `end_time`: last output time, in yr. Note that not all the tracks include entries going out to times >1 Gyr, and the results will become inaccurate if the final time is larger than the tracks allow.
- `sfr`: star formation rate. Only used if `sim_type` is `galaxy`; for `cluster`, it will be ignored, and can be omitted. If, instead of specifying a numerical value for this parameter, you specify the string `sfh`, the code will interpret this as a flag that a star formation history should be read from the file specified by the `sfh` keyword.
- `sfh`: name of star formation history file. This file is a PDF file, formatted as described in [Probability Distribution Functions](#). This is ignored, and can be omitted, if `sim_type` is `cluster`, or if `sfr` is not set to `sfh`.
- `cluster_mass`: mass of the star cluster for simulations with `sim_type` set to `cluster`. This can be omitted, and will be ignored, if `sim_type` is `galaxy`. This parameter can be set to either a positive number or to the string `cmf`. If it is set to a numerical value, that value will be used as the cluster mass, in M_{\odot} for each trial. If it is set to `cmf`, then a new cluster mass will be drawn from the CMF for each trial.
- `redshift` (default: 0): place the system at the specified redshift. The computed spectra and photometry will then be computed in the observed rather than the rest frame of the system.

5.4 Output Control Keywords

These control what quantities are computed and written to disk. Full a full description of the output files and how they are formatted, see [Output Files and Format](#).

- `out_cluster` (default: 1): write out the physical properties of star clusters? Set to 1 for yes, 0 for no.
- `out_cluster_phot` (default: 1): write out the photometry of star clusters? Set to 1 for yes, 0 for no.
- `out_cluster_spec` (default: 1): write out the spectra of star clusters? Set to 1 for yes, 0 for no.
- `out_integrated` (default: 1): write out the integrated physical properties of the whole galaxy? Set to 1 for yes, 0 for no. This keyword is ignored if `sim_type` is `cluster`.
- `out_integrated_phot` (default: 1): write out the integrated photometry of the entire galaxy? Set to 1 for yes, 0 for no. This keyword is ignored if `sim_type` is `cluster`.
- `out_integrated_spec` (default: 1): write out the integrated spectra of the entire galaxy? Set to 1 for yes, 0 for no. This keyword is ignored if `sim_type` is `cluster`.
- `output_mode` (default: `ascii`): set to `ascii`, `binary`, or `fits`. Selecting `ascii` causes the output to be written in ASCII text, which is human-readable, but produces much larger files. Selecting `binary` causes the output to be written in raw binary. Selecting `fits` causes the output to be written FITS format. This will be somewhat larger than raw binary output, but the resulting files will be portable between machines, which the raw binary files are not guaranteed to be. All three output modes can be read by the python library, though with varying speed – ASCII output is slowest, FITS is intermediate, and binary is fastest.

5.5 Physical Model Keywords

These specify the physical models to be used for stellar evolution, atmospheres, the IMF, extinction, etc.

- **imf** (default: `lib/imf/chabrier.imf`): name of the IMF descriptor file; this is a PDF file, formatted as described in [Probability Distribution Functions](#).
 - `chabrier.imf` (single-star IMF from Chabrier, 2005, in “The Initial Mass Function 50 Years Later”, eds. E. Corbelli, F. Palla, & H. Zinnecker, Springer: Dordrecht, p. 41)
 - `chabrier03.imf` (single-star IMF from Chabrier, 2003, PASP, 115, 763-795)
 - `kroupa.imf` (IMF from Kroupa, 2002, Science, 295, 82-91)
 - `kroupa_sb99.imf` (simplified version of the Kroupa, 2002 IMF used by default by `starburst99`)
 - `salpeter.imf` (single-component power law IMF from Salpeter, 1955, ApJ, 121, 161)
- **cmf** (default: `lib/cmf/slug_default.cmf`): name of the CMF descriptor file; this is a PDF file, formatted as described in [Probability Distribution Functions](#). The default selection is a power law $dN/dM \propto M^{-2}$ from $M = 10^2 - 10^7 M_{\odot}$. This is ignored, and may be omitted, if `sim_type` is set to `cluster` and `cluster_mass` is set to a numerical value.
- **clf** (default: `lib/clf/slug_default.clf`): name of the CLF descriptor file; this is a PDF file, formatted as described in [Probability Distribution Functions](#). The default gives a power law distribution of lifetimes t with $dN/dt \propto t^{-1.9}$ from 1 Myr to 1 Gyr. Note that this corresponds to a cluster age distribution of slope -0.9. The SLUG source also ships with an alternative CLF file, `lib/clf/nodisrupt.clf`, which disables cluster disruption entirely (by setting the lifetime distribution to a δ function at 10^{300} yr).
- **tracks** (default: `lib/tracks/Z0140v00.txt`): stellar evolution tracks to use. The following tracks ship with SLUG
 - `ZXXXXvYY.txt`: Geneva (2013) tracks; metallicities are Solar (`XXXX = 0140`) and 1/7 Solar (`XXXX = 0020`), and rotation rates are 0 (`YY = 00`) and 40% of breakup (`YY = 40`).
 - `modcXXX.dat`: Geneva tracks with standard mass loss, for metallicities of $2\times$ Solar (`040`), Solar (`020`), $0.4\times$ Solar (`008`), $0.2\times$ Solar (`004`), and $0.05\times$ Solar (`001`).
 - `modeXXX.dat`: same as `modcXXX.dat`, but with higher mass loss rates.
 - `modpXXX.dat`: Padova tracks with thermally pulsing AGB stars; metallicities use the same scale as `modcXXX.dat` files (i.e., `020` is Solar).
 - `modsXXX.dat`: same as `modpXXX.dat`, but without thermally pulsing AGB stars
- **atmospheres** (default: `lib/atmospheres`): directory where the stellar atmosphere library is located. Note that file names are hard-coded, so if you want to use different atmosphere models with a different format, you will have to write new source code to do so.
- **specsyn_mode** (default: `sb99`): spectral synthesis mode. Allowed values are:
 - `planck`: treat all stars as black bodies
 - `Kurucz`: use Kurucz atmospheres, as compiled by Lejeune et al. (1997, A&AS, 125, 229), for all stars
 - `Kurucz+Hillier`: use Kurucz atmospheres for all stars except Wolf-Rayet stars; WR stars use Hillier model atmospheres (Hillier & Miller, 1998, ApJ, 496, 407)
 - `Kurucz+Pauldrach`: use Kurucz atmospheres for all stars except OB stars; OB stars use Pauldrach model atmospheres (Pauldrach et al., 2001, A&A, 375, 161)
 - `SB99`: emulate the behavior of `starburst99`: use Pauldrach for OB stars, Hillier for WR stars, and Kurucz for all other stars

- `clust_frac` (default: 1.0): fraction of stars formed in clusters
- `min_stoch_mass` (default: 0.0): minimum stellar mass to be treated stochastically. All stars with masses below this value are assumed to be sampled continuously from the IMF.
- `metallicity`: metallicity of the stellar population, relative to solar. This may be omitted if `tracks` is set to one of the default sets of tracks that ships with SLUG, as the metallicities for these tracks are hardwired in. This keyword is provided to allow users to supply their own tracks.
- `WR_mass`: minimum starting mass that stars must have in order to pass through a Wolf-Rayet phase. This can be omitted if `tracks` is set to one of the default sets of tracks that ships with SLUG, as the WR cutoff masses for these tracks are hardwired in. This keyword is provided to allow users to supply their own tracks.
- `A_V` (default: no extinction): extinction distribution. This parameter has three possible behaviors. If the parameter `A_V` is omitted entirely, then the code will not compute extinction-corrected spectra or photometry at all; only unextincted values will be reported. If this parameter is specified as a real number, it will be interpreted as specifying a uniform extinction value A_V , in mag, and this extinction will be applied to all predicted light output. Finally, if this parameter is a string that cannot be converted to a real number, it will be interpreted as the name of a PDF file, formatted as described in *Probability Distribution Functions*, specifying the probability distribution of A_V values, in mag.
- **extinction_curve** (default: `lib/extinct/SB_ATT_SLUG.dat`) file specifying the extinction curve; the file format
 - `LMC_EXT_SLUG.dat` : LMC extinction curve; optical-UV from Fitzpatrick, E. L., 1999, PASP, 111, 63, IR from Landini, M., et al., 1984, A&A, 134, 284; parts combined by D. Calzetti
 - `MW_EXT_SLUG.dat` : MW extinction curve; optical-UV from Fitzpatrick, E. L., 1999 PASP, 111, 63, IR from Landini, M., et al., 1984, A&A, 134, 284; parts combined by D. Calzetti
 - `SB_ATT_SLUG.dat` : “starburst” extinction curve from Calzetti, D., et al., 2000, ApJ, 533, 682
 - `SMC_EXT_SLUG.dat` : SMC extinction curve from Bouchet, P., et al., 1985, A&A, 149, 330
- `compute_nebular` (default: 1): compute the spectrum that results after starlight is processed through the nebula surrounding each cluster or star? Set to 1 for yes, 0 for no.
- `atomic_dir` (default: `lib/atomic/`): directory where the atomic data used for nebular emission calculations is located
- `nebular_den` (default: 1e3): hydrogen number density in cm^{-3} to use in nebular emission computations
- `nebular_temp` (default: 1e4): gas kinetic temperature in K to use in nebular emission computations
- `nebular_phidust` (default: 0.73): fraction of ionizing photons absorbed by H atoms rather than by dust grains inside the HII region; the default value of 0.73, taken from McKee & Williams (1997, ApJ, 476, 144) means that 73% of ionizing photons are absorbed by H and 27% by dust

5.6 Photometric Filter Keywords

These describe the photometry to be computed. Note that none of these keywords have any effect unless `out_integrated_phot` or `out_cluster_phot` is set to 1.

- **phot_bands**: photometric bands for which photometry is to be computed. The values listed here can be comma- or white-space separated
 - `QH0`: the H^0 ionizing luminosity, in photons/sec
 - `QHe0`: the He^0 ionizing luminosity, in photons/sec
 - `QHe1`: the He^+ ionizing luminosity, in photons/sec

- Lbol: the bolometric luminosity, in L_{\odot}
- filters (default: lib/filters): directory containing photometric filter data
- phot_mode (default: L_nu): photometric system to be used when writing photometric outputs. Full definitions of the qu
 - L_nu: report frequency-averaged luminosity in the band, in units of erg/s/Hz
 - L_lambda: report wavelength-averaged luminosity in the band, in units of erg/s/Angstrom
 - AB: report AB magnitude
 - STMAG: report ST magnitude
 - VEGA: report Vega magnitude

PROBABILITY DISTRIBUTION FUNCTIONS

The SLUG code regards the IMF, the CMF, the CLF, the SFH, and the extinction A_V as probability distribution functions – see *Probability Distribution Functions: the IMF, SFH, CMF, CLF, A_V distribution*. The code provides a generic file format through which PDFs can be specified. Examples can be found in the `lib/imf`, `lib/cmf`, `lib/clf`, and `lib/sfh` directories of the SLUG distribution.

PDFs in SLUG are generically written as functions

$$\frac{dp}{dx} = n_1 f_1(x; x_{1,a}, x_{1,b}) + n_2 f_2(x; x_{2,a}, x_{2,b}) + n_3 f_3(x; x_{3,a}, x_{3,b}) + \dots,$$

where $f_i(x; x_{i,a}, x_{i,b})$ is non-zero only for $x \in [x_{i,a}, x_{i,b}]$. The functions f_i are simple continuous functional forms, which we refer to as *segments*. Functions in this form can be specified in SLUG in two ways.

6.1 Basic Mode

The most common way of specifying a PDF is in basic mode. Basic mode describes a PDF that has the properties that

1. the segments are contiguous with one another, i.e., $x_{i,b} = x_{i+1,a}$
2. $n_i f_i(x_{i,b}; x_{i,a}, x_{i,b}) = n_{i+1} f_{i+1}(x_{i+1,a}; x_{i+1,a}, x_{i+1,b})$
3. the overall PDF is normalized such that $\int (dp/dx) dx = 1$

Given these constraints, the PDF can be specified fully simply by giving the x values that define the edges of the segments and the functional forms f of each segment; the normalizations can be computed from the constraint equations. Note that SFH PDFs cannot be described using basic mode, because they are not normalized to unity. Specifying a non-constant SFH requires advanced mode.

An example of a basic mode PDF file is as follows:

```
#####
# This is an IMF definition file for SLUG v2.
# This file defines the Chabrier (2005) IMF
#####

# Breakpoints: mass values where the functional form changes
# The first and last breakpoint will define the minimum and
# maximum mass
breakpoints 0.08 1 120

# Definitions of segments between the breakpoints

# This segment is a lognormal with a mean of log_10 (0.2 Msun)
# and dispersion 0.55; the dispersion is in log base 10, not
```

```
# log base e
segment
type lognormal
mean 0.2
disp 0.55

# This segment is a powerlaw of slope -2.35
segment
type powerlaw
slope -2.35
```

This example represents a [Chabrier \(2005\)](#) IMF from $0.08 - 120 M_{\odot}$, which is of the functional form

$$\frac{dp}{dm} \propto \begin{cases} \exp[-\log(m/m_0)^2/(2\sigma^2)](m/m_b)^{-1}, & m < m_b \\ \exp[-\log(m_b/m_0)^2/(2\sigma^2)](m/m_b)^{-2.35}, & m \geq m_b \end{cases},$$

where $m_0 = 0.2 M_{\odot}$, $\sigma = 0.55$, and $m_b = 1 M_{\odot}$.

Formally, the format of a basic mode file is as follows. Any line beginning with # is a comment and is ignored. The first non-empty, non-comment line in a basic mode PDF file must be of the form:

```
breakpoints x1 x2 x3 ...
```

where x_1, x_2, x_3, \dots are a non-decreasing series of real numbers. These represent the breakpoints that define the edges of the segment, in units of M_{\odot} . In the example given above, the breakpoints are 0.08, 1, and 120, indicating that the first segment goes from $0.08 - 1 M_{\odot}$, and the second from $1 - 120 M_{\odot}$.

After the `breakpoints` line, there must be a series of entries of the form:

```
segment
type TYPE
key1 VAL1
key2 VAL2
...
```

where `TYPE` specifies what functional form describes the segment, and `key1 VAL1`, `key2 VAL2`, etc. are a series of (key, value) pairs that define the free parameters for that segment. In the example above, the first segment is described as having a `lognormal` functional form, and the keywords `mean` and `disp` specify that the lognormal has a mean of $0.2 M_{\odot}$ and a dispersion of 0.55 in \log_{10} . The second segment is of type `powerlaw`, and it has a slope of -2.35 . The full list of allowed segment types and the keywords that must be specified with them are listed in the [Segment Types](#) Table. Keywords and segment types are case-insensitive. Where more than one keyword is required, the order is arbitrary.

The total number of segments must be equal to one less than the number of breakpoints, so that each segment is described. Note that it is not necessary to specify a normalization for each segment, as the segments will be normalized relative to one another automatically so as to guarantee that the overall function is continuous.

Table 6.1: Segment Types

Name	Functional form	Key-word	Meaning	Key-word	Meaning
delta	$\delta(x - x_a)$				
exponential	$\exp(-x/x_*)$	scale	Scale length, x_*		
lognormal	$x^{-1} \exp\{-[\log_{10}(x/x_0)]^2/2\sigma^2\}$	mean	Mean, x_0	disp	Dispersion in \log_{10} , σ
normal	$\exp[-(x - x_0)^2/2\sigma^2]$	mean	Mean, x_0	disp	Dispersion, σ
powerlaw	x^p	slope	Slope, p		
schechter	$x^p \exp(-x/x_*)$	slope	Slope, p	xstar	Cutoff, x_*

6.2 Advanced Mode

In advanced mode, one has complete freedom to set all the parameters describing the PDF: the endpoints of each segment $x_{i,a}$ and $x_{i,b}$, the normalization of each segment n_i , and the functional forms of each segment f_i . This can be used to defined PDFs that are non-continuous, or that are overlapping; the latter option can be used to construct segments with nearly arbitrary functional forms, by constructing a Taylor series approximation to the desired functional form and then using a series of overlapping powerlaw segments to implement that series.

An example of an advanced mode PDF file is as follows:

```
#####
# This is a SFH definition file for SLUG v2.
# This defines a SF history consisting of a series of
# exponentially-decaying bursts with a period of 100 Myr and
# a decay timescale of 10 Myr, with an amplitude chosen to
# give a mean SFR of 10^-3 Msun/yr.
#####

# Declare that this is an advanced mode file
advanced

# First exponential burst
segment
type exponential
min      0.0
max      1.0e8          # Go to 100 Myr
weight   1.0e5          # Form 10^5 Msun of stars over 100 Myr
scale    1.0e7          # Decay time 10 Myr

# Next 4 bursts
segment
type exponential
min      1.0e8
max      2.0e8
weight   1.0e5
scale    1.0e7

segment
type exponential
min      2.0e8
max      3.0e8
weight   1.0e5
scale    1.0e7

segment
type exponential
min      3.0e8
max      4.0e8
weight   1.0e5
scale    1.0e7

segment
type exponential
min      4.0e8
max      5.0e8
weight   1.0e5
scale    1.0e7
```

This represents a star formation history that is a series of exponential bursts, separated by 100 Myr, with decay times of 10 Myr. Formally, this SFH follows the functional form

$$\dot{M}_* = n e^{-(t \bmod P)/t_{\text{dec}}},$$

where $P = 100$ Myr is the period and $t_{\text{dec}} = 10$ Myr is the decay time, from times 0 – 500 Myr. The normalization constant n is set by the condition that $(1/P) \int_0^P \dot{M}_* dt = 0.001 M_\odot \text{ yr}^{-1}$, i.e., that the mean SFR averaged over a single burst period is $0.001 M_\odot \text{ yr}^{-1}$.

Formally, the format of an advanced mode file is as follows. First, all advanced mode files must start with the line:

```
advanced
```

to declare that the file is in advanced mode. After that, there must be a series of entries of the form:

```
segment
type TYPE
min MIN
max MAX
weight WEIGHT
key1 VAL1
key2 VAL2
...
```

The `type` keyword is exactly the same as in basic mode, as are the segment-specific parameter keywords `key1`, `key2`, ... The same functional forms, listed in the *Segment Types* Table, are available as in basic mode. The additional keywords that must be supplied in advanced mode are `min`, `max`, and `weight`. The `min` and `max` keywords give the upper and lower limits $x_{i,a}$ and $x_{i,b}$ for the segment; the probability is zero outside these limits. The keyword `weight` specifies the integral under the segment, i.e., the weight w_i given for segment i is used to set the normalization n_i via the equation

$$w_i = n_i \int_{x_{i,a}}^{x_{i,b}} f_i(x) dx.$$

In the case of a star formation history, as in the example above, the weight w_i of a segment is simply the total mass of stars formed in that segment. In the example given above, the first segment declaration sets up a PDF that with a minimum at 0 Myr, a maximum at 100 Myr, following an exponential functional form with a decay time of 10^7 yr. During this time, a total mass of $10^5 M_\odot$ of stars is formed.

Note that, for the IMF, CMF, and CLF, the absolute values of the weights do not matter, only their relative values. On the other hand, for the SFH, the absolute weight does matter.

6.3 Sampling Methods

A final option allowed in both basic and advanced mode is a specification of the sampling method. The sampling method is a description of how to draw a population of objects from the PDF, when the population is specified as having a total sum M_{target} (usually but not necessarily a total mass) rather than a total number of members N ; there are a number of ways to do this, which do not necessarily yield identical distributions, even for the same underlying PDF. To specify a sampling method, simply add the line:

```
method METHOD
```

to the PDF file. This line can appear anywhere except inside a `segment` specification, or before the `breakpoints` or `advanced` line that begins the file. The following values are allowed for `METHOD` (case-insensitive, as always):

- `stop_nearest`: this is the default option: draw until the total mass of the population exceeds M_{target} . Either keep or exclude the final star drawn depending on which choice brings the total mass closer to the target value.

- `stop_before`: same as `stop_nearest`, but the final object drawn is always excluded.
- `stop_after`: same as `stop_nearest`, but the final object drawn is always kept.
- `stop_50`: same as `stop_nearest`, but keep or exclude the final object with 50% probability regardless of which choice gets closer to the target.
- `number`: draw exactly $N = M_{\text{target}} / \langle M \rangle$ object, where $\langle M \rangle$ is the expectation value for a single draw.
- `poisson`: draw exactly N objects, where the value of N is chosen from a Poisson distribution with expectation value $\langle N \rangle = M_{\text{target}} / \langle M \rangle$
- `sorted_sampling`: this method was introduced by [Weidner & Kroupa \(2006, MNRAS. 365, 1333\)](#), and proceeds in steps. One first draws exactly $N = M_{\text{target}} / \langle M \rangle$ as in the `number` method. If the resulting total mass M_{pop} is less than M_{target} , the procedure is repeated recursively using a target mass $M_{\text{target}} - M_{\text{pop}}$ until $M_{\text{pop}} > M_{\text{target}}$. Finally, one sorts the resulting stellar list from least to most massive, and then keeps or removes the final, most massive star using a `stop_nearest` policy.

See the file `lib/imf/wk06.imf` for an example of a PDF file with a method specification.

OUTPUT FILES AND FORMAT

SLUG can produce 7 output files, though the actual number produced depends on the setting for the `out_*` keywords in the parameter file. (Additional output files can be produced by *cloudy_slug: An Automated Interface to cloudy*, and are documented in that section rather than here.)

The only file that is always produced is the summary file, which is named `MODEL_NAME_summary.txt`, where `MODEL_NAME` is the value given by the `model_name` keyword in the parameter file. This file contains some basic summary information for the run, and is always formatted as ASCII text regardless of the output format requested.

The other six output files all have names of the form `MODEL_NAME_xxx.ext`, where the extension `.ext` is one of `.txt`, `.bin`, or `.fits` depending on the `output_mode` specified in the parameter file, and `xxx` is `integrated_prop`, `integrated_spec`, `integrated_phot`, `cluster_prop`, `cluster_spec`, or `cluster_phot`. The production of these output files is controlled by the parameters `out_integrated`, `out_integrated_spec`, `out_integrated_phot`, `out_cluster`, `out_cluster_spec`, and `out_cluster_phot` in the parameter file. The files are formatted as described below.

The following conventions are used throughout, unless noted otherwise:

- Masses are in M_{\odot}
- Times in year
- Wavelengths are in Angstrom
- Specific luminosities are in erg/s/Angstrom
- For binary outputs, variable types refer to C++ types

7.1 The `integrated_prop` File

This file contains data on the bulk physical properties of the galaxy as a whole. It consists of a series of entries containing the following fields:

- `Time`: evolution time at which the output is produced
- `TargetMass`: target mass of stars in the galaxy up to that time, if the IMF and SFH were perfectly sampled
- `ActualMass`: actual mass of stars produced in the galaxy up to that time; generally not exactly equal to `TargetMass` due to finite sampling of the IMF and SFH
- `LiveMass`: actual mass of stars produced in the galaxy up to that time, and which have not yet reached the end of their lives (as marked by the final entry in the stellar evolution tracks)
- `ClusterMass`: actual mass of stars produced in the galaxy up to that time that are still members of non-disrupted clusters
- `NumClusters`: number of non-disrupted clusters present in the galaxy at this time

- NumDisClust: number of disrupted clusters present in the galaxy at this time
- NumFldStars: number of field stars present in the galaxy at this time; this count only includes those stars being treated stochastically (see the parameter `min_stoch_mass` in *Physical Model Keywords*)

If `output_mode` is `ascii`, these data are output in a series of columns, with different trials separated by lines of dashes. If `output_mode` is `fits`, the data are stored as a FITS binary table extension, with one column for each of the variables above, plus an additional column giving the trial number for that entry. Both the ASCII- and FITS-formatted output should be fairly self-documenting.

For binary output, the file consists of a series of records containing the following variables

- Time (double)
- TargetMass (double)
- ActualMass (double)
- LiveMass (double)
- ClusterMass (double)
- NumClusters (`std::vector<double>::size_type`, usually unsigned long long)
- NumDisClust (`std::vector<double>::size_type`, usually unsigned long long)
- NumFldStars (`std::vector<double>::size_type`, usually unsigned long long)

There is one record of this form for each output time, with different trials ordered sequentially, so that all the times for one trial are output before the first time for the next trial.

7.2 The integrated_spec File

This file contains data on the spectra of the entire galaxy, and consists of a series of entries containing the following fields:

- Time: evolution time at which the output is produced
- Wavelength: observed frame wavelength at which the spectrum is evaluated
- L_lambda: specific luminosity at the specified wavelength, before extinction or nebular effects are applied
- L_lambda_neb: specific luminosity at the specified wavelength, after the light has been processed through the nebula (only present if SLUG was run with nebular emission enabled)
- L_lambda_ex: specific luminosity at the specified wavelength after extinction is applied, but without the effects of the nebula (only present if SLUG was run with extinction enabled)
- L_lambda_neb_ex: specific luminosity at the specified wavelength, after the light is first processed by the nebular and then subjected to dust extinction (only present if SLUG was run with both extinction and nebular emission enabled)

If `output_mode` is `ascii`, these data are output in a series of columns, with different trials separated by lines of dashes. Note that some entries for `L_lambda_ex` and `L_lambda_neb_ex` may be blank. This indicates wavelengths for which a stellar atmosphere model was available, but outside the wavelength range included in the user-specified extinction curve file. Extincted luminosities are unavailable at these wavelengths due to the lack of an extinction curve.

If `output_mode` is `fits`, the output FITS file has two binary table extensions. The first table contains a field listing the wavelengths at which the spectra are given; if extinction was enabled in the SLUG calculation, it also contains a field `Wavelength_ex` listing the wavelengths at which the extincted spectrum is computed. The second table has three fields if SLUG was run without extinction, or four fields if it was run with extinction. The first three fields, always present, give the trial number, the time,

and the spectrum `L_lambda` at that time. The remaining fields `L_lambda_neb`, `L_lambda_ex`, and `L_lambda_neb_ex`, give the spectra including nebular processing, extinction, and both. Both the ASCII- and FITS-formatted output should be fairly self-documenting.

For binary output, the file is formatted as follows. The file starts with

- `Nebular` (byte): a single byte, with a value of 0 indicating that nebular processing was not enabled for this run, and a value of 1 indicating that it was enabled
- `Extinct` (byte): a single byte, with a value of 0 indicating that extinction was not enabled for this run, and a value of 1 indicating that it was enabled
- `NWavelength` (`std::vector<double>::size_type`, usually unsigned long long): the number of wavelength entries in the spectra
- `Wavelength` (`NWavelength` entries of type double)
- `NWavelength_ex` (`std::vector<double>::size_type`, usually unsigned long long): the number of wavelength entries in the extinct spectra; only present if `Extinct` is 1
- `Wavelength_ex` (`NWavelength_ex` entries of type double); only present if `Extinct` is 1

and then contains a series of records in the format

- `Time` (double)
- `L_lambda` (`NWavelength` entries of type double)
- `L_lambda_neb` (`NWavelength` entries of type double); only present if `Nebular` is 1
- `L_lambda_ex` (`NWavelength_ex` entries of type double); only present if `Extinct` is 1
- `L_lambda_neb_ex` (`NWavelength_ex` entries of type double); only present if `Nebular` and `Extinct` are both 1

There is one such record for each output time, with different trials ordered sequentially, so that all the times for one trial are output before the first time for the next trial.

7.3 The integrated_phot File

This file contains data on the photometric properties of the entire galaxy, and consists of a series of entries containing the following fields:

- `Time`: evolution time at which the output is produced
- `PhotFilter1`: photometric value through filter 1, where filters follow the order in which they are specified by the `phot_bands` keyword; units depend on the value of `phot_mode` (see *Photometric Filter Keywords*)
- `PhotFilter2`
- `PhotFilter3`
- ...
- `PhotFilter1_neb`: photometric value through filter 1 for the spectrum after nebular processing, in the same units as `PhotFilter1`; only present if SLUG was run with nebular processing enabled
- `PhotFilter2_neb`
- `PhotFilter3_neb`
- ...

- `PhotFilter1_ex`: photometric value through filter 1 for the extincted spectrum, in the same units as `PhotFilter1`; only present if SLUG was run with extinction enabled
- `PhotFilter2_ex`
- `PhotFilter3_ex`
- ...
- `PhotFilter1_neb_ex`: photometric value through filter 1 for the spectrum after nebular processing and extinction, in the same units as `PhotFilter1`; only present if SLUG was run with both nebular processing and extinction enabled
- `PhotFilter2_neb_ex`
- `PhotFilter3_neb_ex`
- ...

If `output_mode` is `ascii`, these data are output in a series of columns, with different trials separated by lines of dashes. The columns for photometry of the extincted spectrum are present only if extinction was enabled when SLUG was run. Entries for some filters may be left blank. If so, this indicates that the photon response function provided for that filter extends beyond the wavelength range covered by the provided extinction curve. Since the extincted spectrum cannot be computed over the full range of the filter in this case, photometry for that filter cannot be computed either.

If `output_mode` is `fits`, the data are stored as a series of columns in a binary table extension to the FITS file; the filter names and units are included in the header information for the columns. If SLUG was run with nebular emission enabled, for each filter `FILTERNAME` there is a corresponding column `FILTERNAME_neb` giving the photometric value for the nebular-processed spectrum. Similarly, the columns `FILTERNAME_ex` and `FILTERNAME_neb_ex` give the photometric values for the extincted stellar and stellar + nebular spectra, respectively. Some of the extincted values may be NaN; this indicates that the photon response function provided for that filter extends beyond the wavelength range covered by the provided extinction curve. In addition to the time and photometric filter values, the FITS file contains a column specifying the trial number for that entry. Both the ASCII- and FITS-formatted output should be fairly self-documenting.

For binary output, the file is formatted as follows. The file starts with

- `NFilter` (stored as ASCII text): number of filters used
- `FilterName FilterUnit` (`NFilter` entries stored as ASCII text): the name and units for each filter are listed in ASCII, one filter-unit pair per line
- `Nebular` (byte): a single byte, with a value of 0 indicating that nebular processing was not enabled for this run, and a value of 1 indicating that it was enabled
- `Extinct` (byte): a single byte, with a value of 0 indicating that extinction was not enabled for this run, and a value of 1 indicating that it was enabled

This is followed by a series of entries of the form

- `Time` (double)
- `PhotFilter` (`NFilter` entries of type double)
- `PhotFilter_neb` (`NFilter` entries of type double); only present if `Nebular` is 1.
- `PhotFilter_ex` (`NFilter` entries of type double); only present if `Extinct` is 1. Note that some values may be NaN if photometry could not be computed for that filter (see above).
- `PhotFilter_neb_ex` (`NFilter` entries of type double); only present if `Nebular` and `Extinct` are both 1. Note that some values may be NaN if photometry could not be computed for that filter (see above).

There is one such record for each output time, with different trials ordered sequentially, so that all the times for one trial are output before the first time for the next trial.

7.4 The `cluster_prop` File

This file contains data on the bulk physical properties of the non-disrupted star clusters in the galaxy, with one entry per cluster per time at which that cluster exists. Each entry contains the following fields

- `UniqueID`: a unique identifier number for each cluster that is preserved across times and output files
- `Time`: evolution time at which the output is produced
- `FormTime`: time at which that cluster formed
- `Lifetime`: amount of time from birth to when the cluster will disrupt
- `TargetMass`: target mass of stars in the cluster, if the IMF were perfectly sampled
- `BirthMass`: actual mass of stars present in the cluster at formation
- `LiveMass`: actual mass of stars produced in the cluster at this output time that have not yet reached the end of their lives (as marked by the final entry in the stellar evolution tracks)
- `NumStar`: number of living stars in the cluster at this time; this count only includes those stars being treated stochastically (see the parameter `min_stoch_mass` in *Physical Model Keywords*)
- `MaxStarMass`: mass of most massive star still living in the cluster; this only includes those stars being treated stochastically (see the parameter `min_stoch_mass` in *Physical Model Keywords*)
- `A_V`: visual extinction for that cluster, in mag; present only if SLUG was run with extinction enabled

If `output_mode` is `ascii`, these data are output in a series of columns, with different trials separated by lines of dashes. If `output_mode` is `fits`, the data are stored as a FITS binary table extension, with one column for each of the variables above, plus an additional column giving the trial number for that entry. Both the ASCII- and FITS-formatted output should be fairly self-documenting.

For binary output, the first entry in the file is a header containing

- `Extinct (byte)`: a single byte, with a value of 0 indicating that extinction was not enabled for this run, and a value of 1 indicating that it was enabled

Thereafter, the file consists of a series of records, one for each output time, with different trials ordered sequentially, so that all the times for one trial are output before the first time for the next trial. Each record consists of a header containing

- `Time (double)`
- `NCluster (std::vector<double>::size_type, usually unsigned long long)`: number of non-disrupted clusters present at this time

This is followed by `NCluster` entries of the following form:

- `UniqueID (unsigned long)`
- `FormationTime (double)`
- `Lifetime (double)`
- `TargetMass (double)`
- `BirthMass (double)`
- `LiveMass (double)`
- `NumStar (std::vector<double>::size_type, usually unsigned long long)`
- `MaxStarMass (double)`
- `A_V (double)`; present only if `Extinct` is 1

7.5 The `cluster_spec` File

This file contains the spectra of the individual clusters, and each entry contains the following fields:

- `UniqueID`: a unique identifier number for each cluster that is preserved across times and output files
- `Time`: evolution time at which the output is produced
- `Wavelength`: observed frame wavelength at which the spectrum is evaluated
- `L_lambda`: specific luminosity at the specified wavelength
- `L_lambda_neb`: specific luminosity at the specified wavelength after nebular processing is applied (only present if SLUG was run with nebular processing enabled)
- `L_lambda_ex`: specific luminosity at the specified wavelength after extinction is applied (only present if SLUG was run with extinction enabled)
- `L_lambda_neb_ex`: specific luminosity at the specified wavelength after nebular processing and extinction are applied (only present if SLUG was run with both nebular processing and extinction enabled)

If `output_mode` is `ascii`, these data are output in a series of columns, with different trials separated by lines of dashes. The column `L_lambda_ex` is present only if SLUG was run with extinction enabled. Some entries for `L_lambda_ex` may be empty; see [The `integrated_spec` File](#).

If `output_mode` is `fits`, the output FITS file has two binary table extensions. The first table contains a field listing the wavelengths at which the spectra are given; if extinction was enabled in the SLUG calculation, it also contains a field `Wavelength_ex` listing the wavelengths at which the extincted spectrum is computed. The second table has always contains the fields `UniqueID`, `Time`, `Trial`, and `L_lambda` giving the cluster unique ID, time, trial number, and stellar spectrum. Depending on whether nebular processing and/or extinction were enabled when SLUG was run, it may also contain the fields `L_lambda_neb`, `L_lambda_ex`, and `L_lambda_neb_ex` giving the nebular-processed, extincted, and nebular-processed plus extincted spectra. Both the ASCII- and FITS-formatted output should be fairly self-documenting.

Output in binary mode is formatted as follows. The file starts with

- `Nebular` (byte): a single byte, with a value of 0 indicating that nebular processing was not enabled for this run, and a value of 1 indicating that it was enabled
- `Extinct` (byte): a single byte, with a value of 0 indicating that extinction was not enabled for this run, and a value of 1 indicating that it was enabled
- `NWavelength` (`std::vector<double>::size_type`, usually unsigned long long): the number of wavelength entries in the spectra
- `Wavelength` (`NWavelength` entries of type `double`)
- `NWavelength_ex` (`std::vector<double>::size_type`, usually unsigned long long): the number of wavelength entries in the extincted spectra; only present if `Extinct` is 1
- `Wavelength_ex` (`NWavelength_ex` entries of type `double`); only present if `Extinct` is 1

and then contains a series of records, one for each output time, with different trials ordered sequentially, so that all the times for one trial are output before the first time for the next trial. Each record consists of a header containing

- `Time` (`double`)
- `NCluster` (`std::vector<double>::size_type`, usually unsigned long long): number of non-disrupted clusters present at this time

This is followed by `NCluster` entries of the following form:

- `UniqueID` (unsigned long)

- `L_lambda` (NWavelength entries of type double)
- `L_lambda_neb` (NWavelength entries of type double); only present if Nebular is 1
- `L_lambda_ex` (NWavelength_ex entries of type double); only present if Extinct is 1
- `L_lambda_neb_ex` (NWavelength_ex entries of type double); only present if Nebular and Extinct are both 1

7.6 The `cluster_phot` File

This file contains the photometric values for the individual clusters. Each entry contains the following fields:

- `UniqueID`: a unique identifier number for each cluster that is preserved across times and output files
- `Time`: evolution time at which the output is produced
- `PhotFilter1`: photometric value through filter 1, where filters follow the order in which they are specified by the `phot_bands` keyword; units depend on the value of `phot_mode` (see [Photometric Filter Keywords](#))
- `PhotFilter2`
- `PhotFilter3`
- ...
- `PhotFilter1_neb`: photometric value through filter 1 for the spectrum after nebular processing, in the same units as `PhotFilter1`; only present if SLUG was run with nebular processing enabled
- `PhotFilter2_neb`
- `PhotFilter3_neb`
- ...
- `PhotFilter1_ex`: photometric value through filter 1 for the extincted spectrum, in the same units as `PhotFilter1`; only present if SLUG was run with extinction enabled
- `PhotFilter2_ex`
- `PhotFilter3_ex`
- ...
- `PhotFilter1_neb_ex`: photometric value through filter 1 for the spectrum after nebular processing and extinction, in the same units as `PhotFilter1`; only present if SLUG was run with both nebular processing and extinction enabled
- `PhotFilter2_neb_ex`
- `PhotFilter3_neb_ex`
- ...

If `output_mode` is `ascii`, these data are output in a series of columns, with different trials separated by lines of dashes. Some of the extincted photometry columns may be blank; see [The integrated_phot File](#).

If `output_mode` is `fits`, the data are stored as a series of columns in a binary table extension to the FITS file; the filter names and units are included in the header information for the columns. If SLUG was run with nebular emission enabled, for each filter `FILTERNAME` there is a corresponding column `FILTERNAME_neb` giving the photometric value for the nebular-processed spectrum. Similarly, the columns `FILTERNAME_ex` and `FILTERNAME_neb_ex` give the photometric values for the extincted stellar and stellar + nebular spectra, respectively. Some of the extincted values may be NaN; this indicates that the photon response function provided for that filter extends beyond the wavelength range covered by the provided extinction curve. In addition to the time and photometric filter values, the FITS

file contains a column specifying the trial number for that entry. Both the ASCII- and FITS-formatted output should be fairly self-documenting.

In binary output mode, the binary data file starts with

- `NFilter` (stored as ASCII text): number of filters used
- `FilterName FilterUnit` (`NFilter` entries stored as ASCII text): the name and units for each filter are listed in ASCII, one filter-unit pair per line
- `Nebular` (byte): a single byte, with a value of 0 indicating that nebular processing was not enabled for this run, and a value of 1 indicating that it was enabled
- `Extinct` (byte): a single byte, with a value of 0 indicating that extinction was not enabled for this run, and a value of 1 indicating that it was enabled

and then contains a series of records, one for each output time, with different trials ordered sequentially, so that all the times for one trial are output before the first time for the next trial. Each record consists of a header containing

- `Time` (double)
- `NCluster` (`std::vector<double>::size_type`, usually unsigned long long): number of non-disrupted clusters present at this time

This is followed by `NCluster` entries of the following form:

- `UniqueID` (unsigned long)
- `PhotFilter` (`NFilter` entries of type double)
- `PhotFilter_neb` (`NFilter` entries of type double); only present if `Nebular` is 1.
- `PhotFilter_ex` (`NFilter` entries of type double); only present if `Extinct` is 1. Note that some values may be NaN if photometry could not be computed for that filter (see above).
- `PhotFilter_neb_ex` (`NFilter` entries of type double); only present if `Nebular` and `Extinct` are both 1. Note that some values may be NaN if photometry could not be computed for that filter (see above).

FILTERS AND FILTER DATA

SLUG comes with a fairly extensive list of filters, adapted from the list maintained by Charlie Conroy as part of [fsps](#). However, users may wish to add additional filters, and so the format of the filter list is documented here for convenience.

Filter data is stored in two ASCII text files, `FILTER_LIST` and `allfilters.dat`, which are stored in the `lib/filters` directory. The `FILTER_LIST` file is an index listing the available filters. It consists of five whitespace-separated columns. The first column is just a numerical index. The second is the name of the filter; this is the name that should be entered in the `phot_bands` keyword (see [Photometric Filter Keywords](#)) to request photometry in that filter. The third and fourth columns are the value of β and λ_c (the central wavelength) for that filter – see [Spectra and Photometry](#) for definitions. Anything after the fourth column is regarded as a comment, and can be used freely for a description of that filter.

The `allfilters.dat` file contains the filter responses. The file contains a series of entries for different filters, each delineated by a header line that begins with `#`. The order in which filters appear in this file matches that in which they appear in the `FILTER_LIST`. After the header line, there are a series of lines each containing two numbers. The first is the wavelength in Angstrom, and the second is the filter response function at that wavelength.

SLUGPY – THE PYTHON HELPER LIBRARY

9.1 Basic Usage

SLUG comes with the python module `slugpy`, which contains an extensive set of routines for reading, writing, and manipulating SLUG outputs. The most common task is to read a set of SLUG outputs into memory so that they can be processed. To read the data from a SLUG run using `slugpy`, one can simply do the following:

```
from slugpy import *
idata = read_integrated('SLUG_MODEL_NAME')
cdata = read_cluster('SLUG_MODEL_NAME')
```

The `read_integrated` function reads all the integrated-light data (i.e., the data stored in the `_integrated_*` files – see [Output Files and Format](#)) for a SLUG output whose name is given as the argument. This is the base name specified by the `model_name` keyword (see [Basic Keywords](#)), without any extensions; the `slugpy` library will automatically determine which outputs are available and in what format, and read the appropriate files. It returns a `namedtuple` containing all the output data available for that simulation. Note that some of these fields will only be present if the `cloudy-slug` interface (see [cloudy-slug: An Automated Interface to cloudy](#)) was used to process the SLUG output through `cloudy` to predict nebular emission, and some will be present only if extinction was enabled when SLUG was run. The fields returned are as follows:

- `time`: output times
- `target_mass`: target stellar mass at each time
- `actual_mass`: actual stellar mass at each time
- `live_mass`: mass of currently-alive stars
- `cluster_mass`: mass of living stars in non-disrupted clusters
- `num_clusters`: number of non-disrupted clusters
- `num_dis_clusters`: number of disrupted clusters
- `num fld_stars`: number of still-living stars that formed in the field
- `wl`: wavelengths of output stellar spectra (in Angstrom)
- `spec`: integrated spectrum of all stars, expressed as a specific luminosity (erg/s/Angstrom)
- `filter_names`: list of photometric filter names
- `filter_units`: list of units for photometric outputs
- `filter_wl_eff`: effective wavelength for each photometric filter
- `filter_wl`: list of wavelengths for each filter at which the response function is given (in Angstrom)
- `filter_response`: photon response function for each filter at each wavelength (dimensionless)

- `filter_beta`: index β used to set the normalization for each filter – see [Spectra and Photometry](#)
- `filter_wl_c`: pivot wavelength used to set the normalization for each filter for which $\beta \neq 0$ – see [Spectra and Photometry](#)
- `phot`: photometry of the stars in each filter

The following fields are present only if SLUG was run with nebular processing enabled:

- `spec_neb`: same as `spec`, but for the spectrum that emerges after the starlight has passed through the nebulae around the emitting clusters and field stars
- `phot_neb`: same as `phot`, but for the nebular-processed spectrum

The following fields are present only if SLUG was run with extinction enabled:

- `wl_ex`: wavelengths of output stellar spectra after extinction has been applied(in Angstrom). Note that `wl_ex` may contain fewer elements than `wl`, because the extinction curve used may not cover the full wavelength range of the stellar spectra. Extincted spectra are computed only over the range covered by the extinction curve.
- `spec_ex`: same as `spec`, but for the extincted spectrum. May contain fewer entries than `spec` because the extinction curve does not cover the full wavelength range of the computed stellar spectra.
- `phot_ex`: same as `phot`, but for the extincted spectrum. Note that some values may be NaN. This indicates that photometry of the extincted spectrum could not be computed for that filter, because the filter response curve extends to wavelengths outside the range covered by the extinction curve.

The following fields are present only if SLUG was run with both nebular processing and extinction enabled:

- `spec_neb_ex`: same as `spec_neb`, but with extinction applied. May contain fewer entries than `spec` because the extinction curve does not cover the full wavelength range of the computed stellar spectra.
- `phot_neb_ex`: same as `phot_neb`, but with extinction applied. Note that some values may be NaN. This indicates that photometry of the extincted spectrum could not be computed for that filter, because the filter response curve extends to wavelengths outside the range covered by the extinction curve.

The following fields are present only for runs that have been processed through the `cloudy_slug` interface (see [cloudy_slug: An Automated Interface to cloudy](#)):

- `cloudy_wl`: wavelengths of the output nebular spectra (in Angstrom)
- `cloudy_inc`: incident stellar radiation field, expressed as a specific luminosity (erg/s/Angstrom) – should be the same as `spec`, but binned onto cloudy’s wavelength grid; provided mainly as a bug-checking diagnostic
- `cloudy_trans`: the transmitted stellar radiation field computed by cloudy, expressed as a specific luminosity (erg/s/Angstrom) – this is the radiation field of the stars after it has passed through the HII region, and is what one would see in an observational aperture centered on the stars with negligible contribution from the nebula
- `cloudy_emit`: the emitted nebular radiation field computed by cloudy, expressed as a specific luminosity (erg/s/Angstrom) – this is the radiation emitted by the nebula excluding the stars, and is what one would see in an observational aperture that included the nebula but masked out the stars
- `cloudy_trans_emit`: the sum of the transmitted stellar and emitted nebular radiation, expressed as a specific luminosity (erg/s/Angstrom) – this is what one would see in an observational aperture covering the both the stars and the nebula
- `cloudy_linelabel`: list of emitting species for the line luminosities computed by cloudy, following cloudy’s 4-letter notation
- `cloudy_linewl`: wavelengths of all the lines computed by cloudy (in Angstrom)
- `cloudy_linelum`: luminosities of the lines computed by cloudy (in erg/s)

- `cloudy_filter_names`, `cloudy_filter_units`, `cloudy_filter_wl_eff`, `cloudy_filter_wl`, `cloudy_filter_response`, `cloudy_filter_beta`, `cloudy_filter_wl_c`: exactly the same as the corresponding fields without the `cloudy` prefix, but for the photometric filters applied to the cloudy output
- `cloudy_phot_trans`, `cloudy_phot_emit`, and `cloudy_phot_trans_emit`: photometry of the transmitted, emitted, and transmitted+emitted radiation field provided by `cloudy_trans`, `cloudy_emit`, and `cloudy_trans_emit`

For the above fields, quantities that are different for each trial and each time are stored as numpy arrays with a shape (N_times, N_trials) for scalar quantities (e.g., `actual_mass`), or a shape (N, N_times, N_trials) for quantities that are vectors of length N (e.g., the spectrum).

The `read_cluster` function is analogous, except that instead of reading the whole-galaxy data, it reads data on the individual star clusters, as stored in the `_cluster_*` output files. It returns the following fields:

- `id`: a unique identifier number for each cluster; this is guaranteed to be unique across both times and trials, so that if two clusters in the list have the same id number, that means that the data given are for the same cluster at two different times in its evolution
- `trial`: the trial number in which that cluster appeared
- `time`: the time at which the data for that cluster are computed
- `form_time`: the time at which that cluster formed
- `lifetime`: the between when the cluster formed and when it will disrupt
- `target_mass`: the target stellar mass of the cluster
- `actual_mass`: the actual stellar mass of the cluster
- `live_mass`: the mass of all still-living stars in the cluster
- `num_star`: the number of stars in the cluster
- `max_star_mass`: the mass of the single most massive still-living star in the cluster
- `A_V`: the visual extinction for this cluster, in mag; present only if SLUG was run with extinction enabled
- All the remaining fields are identical to those listed above for integrated quantities, starting with `wl`

For all these fields, scalar quantities that are different for each cluster (e.g., `actual_mass`) will be stored as arrays of shape (N_cluster); vector quantities that are different for each cluster (e.g., `spec`) will be stored as arrays of shape (N_cluster, N).

9.2 Full Documentation of slugpy

`slugpy.combine_cluster(data)`

Function to combine cluster data from multiple SLUG2 runs, treating each input run as a separate set of trials. Trial and cluster unique ID numbers are altered as necessary to avoid duplication between the merged data sets.

Parameters:

data [list_like] A list containing the cluster data for each run, as returned by `read_cluster`

Returns:

combined_data [namedtuple] The combined data, in the same format as each object in `data`

`slugpy.combine_integrated(data)`

Function to combine integrated data from multiple SLUG2 runs, treating each input run as a separate set of trials.

Parameters

data [list_like] A list containing the integrated data for each run, as returned by `read_integrated`

Returns

combined_data [namedtuple] The combined data, in the same format as each object in `data`

`slugpy.compute_photometry(wl, spec, filtername, photsystem='L_nu', filter_wl=None, filter_response=None, filter_beta=None, filter_wl_c=None, filter_dir=None)`

This function takes an input spectrum and a set of response functions for photometric filters, and returns the photometry through those filters.

Parameters

wl [array] Wavelength of input spectrum in Angstrom

spec [array] Specific luminosity per unit wavelength for input spectrum, in erg/s/A

filtername [string or iterable of strings] Name or list of names of the filters to be used. Filter names can also include the special filters Lbol, QH0, QHe0, and QHe1; the values returned for these will be the bolometric luminosity (in erg/s) and the photon luminosities (in photons/s) in the H, He, and He+ ionizing-continua, respectively.

photsystem [string] The photometric system to use for the output. Allowable values are 'L_nu', 'L_lambda', 'AB', 'STMAG', and 'Vega', corresponding to the options defined in the SLUG code.

filter_wl [array or iterable of arrays] Array giving the wavelengths in Angstrom at which the filter is response function is given. If this object is an iterable of arrays rather than a single array, it is assumed to represent the wavelengths for a set of filters. If this is set, no data is read from disk. Default behavior is to read the filter information from disk.

filter_response [array or iterable of arrays] Array giving the filter response function at each wavelength and for each filter in `filter_wl`. Must be set if `filter_wl` is set, ignored otherwise.

filter_beta [iterable] Array-like object containing the index beta for each filter. Must be set if `filter_wl` is set, ignored otherwise.

filter_wl_c [iterable] Array-like object containing the pivot wavelength for each filter. Must be set if `filter_wl` is set, ignored otherwise.

filter_dir [string] Directory where the filter data files can be found. If left as None, filters will be looked for in the \$SLUG_DIR/lib/filters directory. This parameter is used only if `filtername` is not None.

Returns

phot [array] Photometric values in the requested filters. Units depend on the choice of photometric system: L_nu -> erg/s/Hz; L_lambda -> erg/s/A; AB -> absolute AB magnitude; STMAG -> absolute ST magnitude; Vega -> absolute Vega magnitude;

`slugpy.photometry_convert(photsystem, phot, units, wl_cen=None, filter_last=False, filter_names=None, filter_dir=None)`

Function to convert photometric data between photometric systems.

Parameters

photsystem [string] The photometric system to which to convert. Allowable values are 'L_nu', 'L_lambda', 'AB', 'STMAG', and 'Vega', corresponding to the options defined in the SLUG code. If this is set and the conversion requested involves a conversion from a wavelength-based system to a frequency-based one, `wl_cen` must not be None.

phot [array] array of photometric data; if the array has more than one dimension, the first dimension is assumed to represent the different photometric filters (unless `filter_last` is True, in which case the last dimension is represents the array of filters)

units [iterable of strings] iterable listing the units of the input photometric data. On return, strings will be changed to the units of the new system.

wl_cen [array] central wavelengths of the filters, in Angstrom; can be left as None if the requested conversion doesn't require going between wavelength- and frequency-based systems.

filter_last [bool] If the input data have more than one dimension, by default it is assumed that the first dimension contains values for the different photometric filters. If this keyword is set to True, it will instead be assumed that the last dimension contains the values for the different filters.

filter_names [iterable of strings] Names of all filters, used to read the filter response functions from disk; only needed for conversions to and from Vega magnitudes, and ignored otherwise

filter_dir [string] Directory where the filter data files can be found. If left as None, filters will be looked for in the \$SLUG_DIR/lib/filters directory. This parameter is used only for conversions to and from Vega magnitudes.

Returns Nothing

Raises ValueError, if `wl_cen` is None but the requested conversion requires going between wavelength- and frequency-based systems

`slugpy.read_cluster(model_name, output_dir=None, fmt=None, nofilterdata=False, photsys=
tem=None, verbose=False, read_info=None)`

Function to read all cluster data for a SLUG2 run.

Parameters

model_name [string] The name of the model to be read

output_dir [string] The directory where the SLUG2 output is located; if set to None, the current directory is searched, followed by the SLUG_DIR directory if that environment variable is set

fmt [string] Format for the file to be read. Allowed values are 'ascii', 'bin' or 'binary', and 'fits'. If one of these is set, the code will only attempt to open ASCII-, binary-, or FITS-formatted output, ending in .txt., .bin, or .fits, respectively. If set to None, the code will try to open ASCII files first, then if it fails try binary files, and if it fails again try FITS files.

nofilterdata [bool] If True, the routine does not attempt to read the filter response data from the standard location

photsystem [None or string] If photsystem is None, the data will be returned in the same photometric system in which they were read. Alternately, if it is a string, the data will be converted to the specified photometric system. Allowable values are 'L_nu', 'L_lambda', 'AB', 'STMAG', and 'Vega', corresponding to the options defined in the SLUG code. If this is set and the conversion requested involves a conversion from a wavelength-based system to a frequency-based one, nofilterdata must be False so that the central wavelength of the photometric filters is available.

verbose [bool] If True, verbose output is printed as code runs

read_info [dict] On return, this dict will contain the keys 'prop_name', 'phot_name', 'spec_name', 'cloudyspec_name', 'cloudyline_name' and 'format', giving the names of the files read and the format they were in; 'format' will be one of 'ascii', 'binary', or 'fits'. If one of the files is not present, the corresponding _name key will be omitted from the dict.

Returns A namedtuple containing the following fields:

(Always present)

id [array, dtype uint] unique ID of cluster

trial: array, dtype uint which trial was this cluster part of

time [array] time at which cluster's properties are being evaluated

(Present if the run being read contains a cluster_prop file)

form_time [array] time when cluster formed

lifetime [array] time at which cluster will disrupt

target_mass [array] target cluster mass

actual_mass [array] actual mass at formation

live_mass [array] mass of currently living stars

num_star [array, dtype ulonglong] number of living stars in cluster being treated stochastically

max_star_mass [array] mass of most massive living star in cluster

(Present if the run being read contains a cluster_spec file)

wl [array] wavelength, in Angstrom

spec [array, shape (N_cluster, N_wavelength)] specific luminosity of each cluster at each wavelength, in erg/s/A

If extinction is enabled, wl_ex and spec_ex will contain the spectra after extinction has been applied.

(Present if the run being read contains a cluster_phot file)

filter_names [list of string] a list giving the name for each filter

filter_units [list of string] a list giving the units for each filter

filter_wl_cen [list] central wavelength of each filter; this is set to None for the filters Lbol, QH0, QHe0, and QHe1; omitted if nofilterdata is True

filter_wl [list of arrays] a list giving the wavelength table for each filter; this is None for the filters Lbol, QH0, QHe0, and QHe1; omitted if nofilterdata is True

filter_response [list of arrays] a list giving the photon response function for each filter; this is None for the filters Lbol, QH0, QHe0, and QHe1; omitted if nofilterdata is True

phot [array, shape (N_cluster, N_filter)] photometric value in each filter for each cluster; units are as indicated in the units field

If extinction is enabled, phot_ex will contain photometry after extinction has been applied.

(Present if the run being read contains a cluster_cloudyspec file)

cloudy_wl [array] wavelength, in Angstrom

cloudy_inc [array, shape (N_cluster, N_wavelength)] specific luminosity of the cluster's stellar radiation field at each wavelength, in erg/s/A

cloudy_trans [array, shape (N_cluster, N_wavelength)] specific luminosity of the stellar radiation field after it has passed through the HII region, at each wavelength, in erg/s/A

cloudy_emit [array, shape (N_cluster, N_wavelength)] specific luminosity of the radiation field emitted by the HII region, at each wavelength, in erg/s/A

cloudy_trans_emit [array, shape (N_cluster, N_wavelength)] the sum of the emitted and transmitted fields; this is what would be seen by an observer looking at both the star cluster and its nebula

(Present if the run being read contains a cluster_cloudyline file)

cloudy_linelabel [array, dtype='S4', shape (N_lines)] labels for the lines, following cloudy's 4 character line label notation

cloudy_linewl [array, shape (N_lines)] rest wavelength for each line, in Angstrom

cloudy_linelum [array, shape (N_cluster, N_lines)] luminosity of each line at each time for each trial, in erg/s

(Present if the run being read contains a cluster_cloudyphot file)

cloudy_filter_names [list of string] a list giving the name for each filter

cloudy_filter_units [list of string] a list giving the units for each filter

cloudy_filter_wl_eff [list] effective wavelength of each filter; this is set to None for the filters Lbol, QH0, QHe0, and QHe1; omitted if nofilterdata is True

cloudy_filter_wl [list of arrays] a list giving the wavelength table for each filter; this is None for the filters Lbol, QH0, QHe0, and QHe1; omitted if nofilterdata is True

cloudy_filter_response [list of arrays] a list giving the photon response function for each filter; this is None for the filters Lbol, QH0, QHe0, and QHe1; omitted if nofilterdata is True

cloudy_filter_beta [list] powerlaw index beta for each filter; used to normalize the photometry

cloudy_filter_wl_c [list] pivot wavelength for each filter; used to normalize the photometry

cloudy_phot_trans [array, shape (N_cluster, N_filter)] photometric value for each cluster in each filter for the transmitted light (i.e., the starlight remaining after it has passed through the HII region); units are as indicated in the units field

cloudy_phot_emit [array, shape (N_cluster, N_filter)] photometric value for each cluster in each filter for the emitted light (i.e., the diffuse light emitted by the HII region); units are as indicated in the units field

cloudy_phot_trans_emit [array, shape (N_cluster, N_filter)] photometric value in each filter for each cluster for the transmitted plus emitted light (i.e., the light coming directly from the stars after absorption by the HII region, plus the diffuse light emitted by the HII region); units are as indicated in the units field

Raises IOError, if no photometry file can be opened ValueError, if photsystem is set to an unknown values

`slugpy.read_cluster_phot(model_name, output_dir=None, fmt=None, nofilterdata=False, photsystem=None, verbose=False, read_info=None)`

Function to read a SLUG2 cluster_phot file.

Parameters

model_name [string] The name of the model to be read

output_dir [string] The directory where the SLUG2 output is located; if set to None, the current directory is searched, followed by the SLUG_DIR directory if that environment variable is set

fmt [string] Format for the file to be read. Allowed values are 'ascii', 'bin' or 'binary', and 'fits'. If one of these is set, the code will only attempt to open ASCII-, binary-, or FITS-formatted output, ending in .txt., .bin, or .fits, respectively. If set to None, the code will try to open ASCII files first, then if it fails try binary files, and if it fails again try FITS files.

nofilterdata [bool] If True, the routine does not attempt to read the filter response data from the standard location

photosystem [None or string] If photosystem is None, the data will be returned in the same photometric system in which they were read. Alternately, if it is a string, the data will be converted to the specified photometric system. Allowable values are 'L_nu', 'L_lambda', 'AB', 'STMAG', and 'Vega', corresponding to the options defined in the SLUG code. If this is set and the conversion requested involves a conversion from a wavelength-based system to a frequency-based one, nofilterdata must be False so that the central wavelength of the photometric filters is available.

verbose [bool] If True, verbose output is printed as code runs

read_info [dict] On return, this dict will contain the keys ‘fname’ and ‘format’, giving the name of the file read and the format it was in; ‘format’ will be one of ‘ascii’, ‘binary’, or ‘fits’

Returns A namedtuple containing the following fields:

id [array, dtype uint] unique ID of cluster

trial: array, dtype uint which trial was this cluster part of

time [array] times at which cluster spectra are output, in yr

filter_names [list of string] a list giving the name for each filter

filter_units [list of string] a list giving the units for each filter

filter_wl_eff [list] effective wavelength of each filter; this is set to None for the filters Lbol, QH0, QHe0, and QHe1; omitted if nofilterdata is True

filter_wl [list of arrays] a list giving the wavelength table for each filter; this is None for the filters Lbol, QH0, QHe0, and QHe1; omitted if nofilterdata is True

filter_response [list of arrays] a list giving the photon response function for each filter; this is None for the filters Lbol, QH0, QHe0, and QHe1; omitted if nofilterdata is True

filter_beta [list] powerlaw index beta for each filter; used to normalize the photometry

filter_wl_c [list] pivot wavelength for each filter; used to normalize the photometry

phot [array, shape (N_cluster, N_filter)] photometric value in each filter for each cluster; units are as indicated in the units field

phot_neb [array, shape (N_filter, N_times, N_trials)] same as phot, but for the light after it has passed through the HII region (present only if SLUG was run with nebular emission enabled)

phot_ex [array, shape (N_filter, N_times, N_trials)] same as phot, but after extinction has been applied (present only if SLUG was run with extinction enabled)

phot_neb_ex [array, shape (N_filter, N_times, N_trials)] same as phot, but for the light after it has passed through the HII region and then had extinction applied (present only if SLUG was run with both nebular emission and extinction enabled)

Raises IOError, if no photometry file can be opened ValueError, if photosystem is set to an unknown values

```
slugpy.read_cluster_prop(model_name, output_dir=None, fmt=None, verbose=False,
                        read_info=None)
```

Function to read a SLUG2 cluster_prop file.

Parameters

model_name [string] The name of the model to be read

output_dir [string] The directory where the output is located; if set to None, the current directory is searched, followed by the SLUG_DIR directory if that environment variable is set

fmt [string] Format for the file to be read. Allowed values are ‘ascii’, ‘bin’ or ‘binary’, and ‘fits’. If one of these is set, the code will only attempt to open ASCII-, binary-, or FITS-formatted output, ending in .txt., .bin, or .fits, respectively. If set to None, the code will try to open ASCII files first, then if it fails try binary files, and if it fails again try FITS files.

verbose [bool] If True, verbose output is printed as code runs

read_info [dict] On return, this dict will contain the keys ‘fname’ and ‘format’, giving the name of the file read and the format it was in; ‘format’ will be one of ‘ascii’, ‘binary’, or ‘fits’

Returns A namedtuple containing the following fields:

id [array, dtype uint] unique ID of cluster

trial: array, dtype uint which trial was this cluster part of

time [array] time at which cluster's properties are being evaluated

form_time [array] time when cluster formed

lifetime [array] time at which cluster will disrupt

target_mass [array] target cluster mass

actual_mass [array] actual mass at formation

live_mass [array] mass of currently living stars

num_star [array, dtype ulonglong] number of living stars in cluster being treated stochastically

max_star_mass [array] mass of most massive living star in cluster

A_V [array] A_V value for each cluster, in mag (present only if SLUG was run with extinction enabled)

`slugpy.read_cluster_spec(model_name, output_dir=None, fmt=None, verbose=False, read_info=None)`

Function to read a SLUG2 cluster_spec file.

Parameters

model_name [string] The name of the model to be read

output_dir [string] The directory where the SLUG2 output is located; if set to None, the current directory is searched, followed by the SLUG_DIR directory if that environment variable is set

fmt [string] Format for the file to be read. Allowed values are 'ascii', 'bin' or 'binary', and 'fits'. If one of these is set, the code will only attempt to open ASCII-, binary-, or FITS-formatted output, ending in .txt., .bin, or .fits, respectively. If set to None, the code will try to open ASCII files first, then if it fails try binary files, and if it fails again try FITS files.

verbose [bool] If True, verbose output is printed as code runs

read_info [dict] On return, this dict will contain the keys 'fname' and 'format', giving the name of the file read and the format it was in; 'format' will be one of 'ascii', 'binary', or 'fits'

Returns A namedtuple containing the following fields:

id [array, dtype uint] unique ID of cluster

trial: array, dtype uint which trial was this cluster part of

time [array] times at which cluster spectra are output, in yr

wl [array] wavelength, in Angstrom

spec [array, shape (N_cluster, N_wavelength)] specific luminosity of each cluster at each wavelength, in erg/s/A

spec_neb [array, shape (N_wavelength, N_times, N_trials)] specific luminosity at each wavelength and each time for each trial, including emission and absorption by the HII region, in erg/s/A (present only if SLUG was run with nebular emission enabled)

wl_ex [array] wavelength for the extincted spectrum, in Angstrom (present only if SLUG was run with extinction enabled)

spec_ex [array, shape (N_cluster, N_wavelength)] specific luminosity at each wavelength in wl_ex and each time for each trial after extinction has been applied, in erg/s/A (present only if SLUG was run with extinction enabled)

spec_neb_ex [array, shape (N_wavelength, N_times, N_trials)] specific luminosity at each wavelength in `wl_ex` and each time for each trial including emission and absorption by the HII region, after extinction has been applied, in erg/s/A (present only if SLUG was run with nebular emission and extinction both enabled)

Raises IOError, if no spectrum file can be opened

`slugpy.read_filter(filtername, filter_dir=None)`

Function to read a filter or set of filters for SLUG2. By default this function searches the SLUG_DIR/lib/filter directory, followed by the current working directory. This can be overridden by the `filter_dir` keyword.

Parameters

filtername [string or iterable containing strings] Name or names of filters to be read; for the special filters Lbol, QH0, QHe0, and QHe1, the return value will be None

filter_dir [string] Directory where the filter data files can be found

Returns A namedtuple containing the following fields:

wl_eff [float or array] Central wavelength of the filter, defined by $wl_eff = \exp(\int R \ln \lambda d\ln \lambda / \int R d\ln \lambda)$

wl [array or list of arrays] Wavelength table for each filter, in Ang

response [array or list of arrays] Response function per photon for each filter

beta [float or array] Index beta for the filter

wl_c [float or array] Pivot wavelength for the filter; used when $\beta \neq 0$ to normalize the photometry

Raises IOError, if the filter data files cannot be opened, or if the requested filter cannot be found

`slugpy.read_integrated(model_name, output_dir=None, fmt=None, nofilterdata=False, photsystem=None, verbose=False, read_info=None)`

Function to read all integrated light data for a SLUG2 run.

Parameters

model_name [string] The name of the model to be read

output_dir [string] The directory where the SLUG2 output is located; if set to None, the current directory is searched, followed by the SLUG_DIR directory if that environment variable is set

fmt [string] Format for the file to be read. Allowed values are 'ascii', 'bin' or 'binary', and 'fits'. If one of these is set, the code will only attempt to open ASCII-, binary-, or FITS-formatted output, ending in .txt., .bin, or .fits, respectively. If set to None, the code will try to open ASCII files first, then if it fails try binary files, and if it fails again try FITS files.

nofilterdata [bool] If True, the routine does not attempt to read the filter response data from the standard location

photsystem [None or string] If photsystem is None, the data will be returned in the same photometric system in which they were read. Alternately, if it is a string, the data will be converted to the specified photometric system. Allowable values are 'L_nu', 'L_lambda', 'AB', 'STMAG', and 'Vega', corresponding to the options defined in the SLUG code. If this is set and the conversion requested involves a conversion from a wavelength-based system to a frequency-based one, nofilterdata must be False so that the central wavelength of the photometric filters is available.

verbose [bool] If True, verbose output is printed as code runs

read_info [dict] On return, this dict will contain the keys 'prop_name', 'phot_name', 'spec_name', 'cloudyspec_name', 'cloudyline_name' and 'format', giving the names of the files read and the format they were in; 'format' will be one of 'ascii', 'binary', or 'fits'. If one of the files is not present, the corresponding _name key will be omitted from the dict.

Returns A namedtuple containing the following fields:

(Always present)

time: array Times at which data are output

(Only present if an integrated_prop file is found)

target_mass [array, shape (N_times, N_trials)] Target stellar mass at each time in each trial

actual_mass [array, shape (N_times, N_trials)] Actual mass of stars created up to each time in each trial

live_mass [array, shape (N_times, N_trials)] Mass of currently-alive stars at each time in each trial

cluster_mass [array, shape (N_times, N_trials)] Mass of living stars in non-disrupted clusters at each time in each trial

num_clusters [array, shape (N_times, N_trials), dtype ulonglong] Number of non-disrupted clusters present at each time in each trial

num_dis_clusters [array, shape (N_times, N_trials), dtype ulonglong] Number of disrupted clusters present at each time in each trial

num fld_stars [array, shape (N_times, N_trials), dtype ulonglong] Number of living field stars (excluding those in disrupted clusters and those being treated non-stochastically) present at each time in each trial

(Only present if an integrated_spec file is found)

wl [array] wavelengths, in Angstrom

spec [array, shape (N_wavelength, N_times, N_trials)] specific luminosity at each wavelength and each time for each trial, in erg/s/A

If extinction is enabled, **wl_ex** and **spec_ex** will contain the spectra after extinction has been applied.

(Only present if an integrated_phot file is found)

filter_names [list of string] a list giving the name for each filter

filter_units [list of string] a list giving the units for each filter

filter_wl_cen [list] central wavelength of each filter; this is set to None for the filters Lbol, QH0, QHe0, and QHe1; omitted if nofilterdata is True

filter_wl [list of arrays] a list giving the wavelength table for each filter; this is None for the filters Lbol, QH0, QHe0, and QHe1; omitted if nofilterdata is True

filter_response [list of arrays] a list giving the photon response function for each filter; this is None for the filters Lbol, QH0, QHe0, and QHe1; omitted if nofilterdata is True

phot [array, shape (N_filter, N_times, N_trials)] photometric value in each filter at each time in each trial; units are as indicated in the units field

If extinction is enabled, **phot_ex** will contain photometry after extinction has been applied.

(Only present if an integrated_cloudyspec file is found)

cloudy_wl [array] wavelength, in Angstrom

cloudy_inc [array, shape (N_wavelength, N_times, N_trials)] specific luminosity of the stellar radiation field at each wavelength and each time for each trial, in erg/s/A

cloudy_trans [array, shape (N_wavelength, N_times, N_trials)] specific luminosity of the stellar radiation field after it has passed through the HII region, at each wavelength and each time for each trial, in erg/s/A

cloudy_emit [array, shape (N_wavelength, N_times, N_trials)] specific luminosity of the radiation field emitted by the HII region, at each wavelength and each time for each trial, in erg/s/Å

cloudy_trans_emit [array, shape (N_wavelength, N_times, N_trials)] the sum of emitted and transmitted; this is what would be seen by an observer looking at both the star cluster and its nebula

(Only present if an integrated_cloudyline file is found)

cloudy_linelabel [array, dtype='S4', shape (N_lines)] labels for the lines, following cloudy's 4 character line label notation

cloudy_linewl [array, shape (N_lines)] rest wavelength for each line, in Angstrom

cloudy_linelum [array, shape (N_lines, N_times, N_trials)] luminosity of each line at each time for each trial, in erg/s

(Only present if an integrated_cloudyphot file is found)

cloudy_filter_names [list of string] a list giving the name for each filter

cloudy_filter_units [list of string] a list giving the units for each filter

cloudy_filter_wl_eff [list] effective wavelength of each filter; this is set to None for the filters Lbol, QH0, QHe0, and QHe1; omitted if nofilterdata is True

cloudy_filter_wl [list of arrays] a list giving the wavelength table for each filter; this is None for the filters Lbol, QH0, QHe0, and QHe1; omitted if nofilterdata is True

cloudy_filter_response [list of arrays] a list giving the photon response function for each filter; this is None for the filters Lbol, QH0, QHe0, and QHe1; omitted if nofilterdata is True

cloudy_filter_beta [list] powerlaw index beta for each filter; used to normalize the photometry

cloudy_filter_wl_c [list] pivot wavelength for each filter; used to normalize the photometry

cloudy_phot_trans [array, shape (N_filter, N_times, N_trials)] photometric value in each filter at each time in each trial for the transmitted light (i.e., the starlight remaining after it has passed through the HII region); units are as indicated in the units field

cloudy_phot_emit [array, shape (N_filter, N_times, N_trials)] photometric value in each filter at each time in each trial for the emitted light (i.e., the diffuse light emitted by the HII region); units are as indicated in the units field

cloudy_phot_trans_emit [array, shape (N_filter, N_times, N_trials)] photometric value in each filter at each time in each trial for the transmitted plus emitted light (i.e., the light coming directly from the stars after absorption by the HII region, plus the diffuse light emitted by the HII region); units are as indicated in the units field

`slugpy.read_integrated_phot` (*model_name*, *output_dir=None*, *fmt=None*, *nofilterdata=False*, *phot-system=None*, *verbose=False*, *read_info=None*)

Function to read a SLUG2 integrated_phot file.

Parameters

model_name [string] The name of the model to be read

output_dir [string] The directory where the SLUG2 output is located; if set to None, the current directory is searched, followed by the SLUG_DIR directory if that environment variable is set

fmt [string] Format for the file to be read. Allowed values are 'ascii', 'bin' or 'binary', and 'fits'. If one of these is set, the code will only attempt to open ASCII-, binary-, or FITS-formatted output, ending in .txt., .bin, or .fits, respectively. If set to None, the code will try to open ASCII files first, then if it fails try binary files, and if it fails again try FITS files.

nofilterdata [bool] If True, the routine does not attempt to read the filter response data from the standard location

photosystem [None or string] If photosystem is None, the data will be returned in the same photometric system in which they were read. Alternately, if it is a string, the data will be converted to the specified photometric system. Allowable values are 'L_nu', 'L_lambda', 'AB', 'STMAG', and 'Vega', corresponding to the options defined in the SLUG code. If this is set and the conversion requested involves a conversion from a wavelength-based system to a frequency-based one, nofilterdata must be False so that the central wavelength of the photometric filters is available.

verbose [bool] If True, verbose output is printed as code runs

read_info [dict] On return, this dict will contain the keys 'fname' and 'format', giving the name of the file read and the format it was in; 'format' will be one of 'ascii', 'binary', or 'fits'

Returns A namedtuple containing the following fields:

time [array, shape (N_times) or shape (N_trials)] Times at which data are output; shape is either N_times (if the run was done with fixed output times) or N_trials (if the run was done with random output times)

filter_names [list of string] a list giving the name for each filter

filter_units [list of string] a list giving the units for each filter

filter_wl_eff [list] effective wavelength of each filter; this is set to None for the filters Lbol, QH0, QHe0, and QHe1; omitted if nofilterdata is True

filter_wl [list of arrays] a list giving the wavelength table for each filter; this is None for the filters Lbol, QH0, QHe0, and QHe1; omitted if nofilterdata is True

filter_response [list of arrays] a list giving the photon response function for each filter; this is None for the filters Lbol, QH0, QHe0, and QHe1; omitted if nofilterdata is True

filter_beta [list] powerlaw index beta for each filter; used to normalize the photometry

filter_wl_c [list] pivot wavelength for each filter; used to normalize the photometry

phot [array, shape (N_filter, N_times, N_trials)] photometric value in each filter at each time in each trial; units are as indicated in the units field

phot_neb [array, shape (N_filter, N_times, N_trials)] same as phot, but for the light after it has passed through the HII region (present only if SLUG was run with nebular emission enabled)

phot_ex [array, shape (N_filter, N_times, N_trials)] same as phot, but after extinction has been applied (present only if SLUG was run with extinction enabled)

phot_neb_ex [array, shape (N_filter, N_times, N_trials)] same as phot, but for the light after it has passed through the HII region and then had extinction applied (present only if SLUG was run with both nebular emission and extinction enabled)

Raises IOError, if no photometry file can be opened ValueError, if photosystem is set to an unknown value

`slugpy.read_integrated_prop(model_name, output_dir=None, fmt=None, verbose=False, read_info=None)`

Function to read a SLUG2 integrated_prop file.

Parameters

model_name [string] The name of the model to be read

output_dir [string] The directory where the SLUG2 output is located; if set to None, the current directory is searched, followed by the SLUG_DIR directory if that environment variable is set

fmt [string] Format for the file to be read. Allowed values are ‘ascii’, ‘bin’ or ‘binary’, and ‘fits’. If one of these is set, the code will only attempt to open ASCII-, binary-, or FITS-formatted output, ending in .txt., .bin, or .fits, respectively. If set to None, the code will try to open ASCII files first, then if it fails try binary files, and if it fails again try FITS files.

verbose [bool] If True, verbose output is printed as code runs

read_info [dict] On return, this dict will contain the keys ‘fname’ and ‘format’, giving the name of the file read and the format it was in; ‘format’ will be one of ‘ascii’, ‘binary’, or ‘fits’

Returns A namedtuple containing the following fields:

time [array, shape (N_times) or shape (N_trials)] Times at which data are output; shape is either N_times (if the run was done with fixed output times) or N_trials (if the run was done with random output times)

target_mass [array, shape (N_times, N_trials)] Target stellar mass at each time

actual_mass [array, shape (N_times, N_trials)] Actual mass of stars created up to each time in each trial

live_mass [array, shape (N_times, N_trials)] Mass of currently-alive stars at each time in each trial

cluster_mass [array, shape (N_times, N_trials)] Mass of living stars in non-disrupted clusters at each time in each trial

num_clusters [array, shape (N_times, N_trials), dtype ulonglong] Number of non-disrupted clusters present at each time in each trial

num_dis_clusters [array, shape (N_times, N_trials), dtype ulonglong] Number of disrupted clusters present at each time in each trial

num_fld_stars [array, shape (N_times, N_trials), dtype ulonglong] Number of living field stars (excluding those in disrupted clusters and those being treated non-stochastically) present at each time in each trial

`slugpy.read_integrated_spec(model_name, output_dir=None, fmt=None, verbose=False, read_info=None)`

Function to read a SLUG2 integrated_spec file.

Parameters

model_name [string] The name of the model to be read

output_dir [string] The directory where the SLUG2 output is located; if set to None, the current directory is searched, followed by the SLUG_DIR directory if that environment variable is set

fmt [string] Format for the file to be read. Allowed values are ‘ascii’, ‘bin’ or ‘binary’, and ‘fits’. If one of these is set, the code will only attempt to open ASCII-, binary-, or FITS-formatted output, ending in .txt., .bin, or .fits, respectively. If set to None, the code will try to open ASCII files first, then if it fails try binary files, and if it fails again try FITS files.

verbose [bool] If True, verbose output is printed as code runs

read_info [dict] On return, this dict will contain the keys ‘fname’ and ‘format’, giving the name of the file read and the format it was in; ‘format’ will be one of ‘ascii’, ‘binary’, or ‘fits’

Returns A namedtuple containing the following fields:

time [array, shape (N_times) or shape (N_trials)] Times at which data are output; shape is either N_times (if the run was done with fixed output times) or N_trials (if the run was done with random output times)

wl [array] wavelength, in Angstrom

spec [array, shape (N_wavelength, N_times, N_trials)] specific luminosity at each wavelength and each time for each trial, in erg/s/Å

spec_neb [array, shape (N_wavelength, N_times, N_trials)] specific luminosity at each wavelength and each time for each trial, including emission and absorption by the HII region, in erg/s/A (present only if SLUG was run with nebular emission enabled)

wl_ex [array] wavelength for the extincted spectrum, in Angstrom (present only if SLUG was run with extinction enabled)

spec_ex [array, shape (N_wavelength, N_times, N_trials)] specific luminosity at each wavelength in wl_ex and each time for each trial after extinction has been applied, in erg/s/A (present only if SLUG was run with extinction enabled)

spec_neb_ex [array, shape (N_wavelength, N_times, N_trials)] specific luminosity at each wavelength in wl_ex and each time for each trial including emission and absorption by the HII region, after extinction has been applied, in erg/s/A (present only if SLUG was run with nebular emission and extinction both enabled)

`slugpy.read_summary(model_name, output_dir=None)`

Function to open a SLUG output summary file.

Parameters

model_name [string] The name of the model to be read

output_dir [string] The directory where the SLUG2 output is located; if set to None, the current directory is searched, followed by the SLUG_DIR directory if that environment variable is set

Returns

summary [dict] A dict containing all the keywords stored in the output file

Raises IOError, if a summary file for the specified model cannot be found

`slugpy.slug_open(filename, output_dir=None, fmt=None)`

Function to open a SLUG2 output file.

Parameters

filename [string] Name of the file to open, without any extension. The following extensions are tried, in order: .txt, .bin, .fits

output_dir [string] The directory where the SLUG2 output is located; if set to None, the current directory is searched, followed by the SLUG_DIR/output directory if the SLUG_DIR environment variable is set

fmt [string] Format for the file to be read. Allowed values are 'ascii', 'bin' or 'binary', and 'fits'. If one of these is set, the code will only attempt to open ASCII-, binary-, or FITS-formatted output, ending in .txt., .bin, or .fits, respectively. If set to None, the code will try to open ASCII files first, then if it fails try binary files, and if it fails again try FITS files.

Returns

fp [file or astropy.io.fits.hdu.hdu.HDUList] A file object pointing the file that has been opened

fname [string] Name of the file that was opened

Raises IOError, if a file of the specified name cannot be found

`slugpy.write_cluster(data, model_name, fmt)`

Function to write a set of output cluster files in SLUG2 format, starting from a cluster data set as returned by read_cluster.

Parameters

data [namedtuple] Cluster data to be written, in the namedtuple format returned by read_cluster

model_name [string] Base file name to give the model to be written. Can include a directory specification if desired.

fmt [string] Format for the output file. Allowed values are 'ascii', 'bin' or 'binary', and 'fits'.

Returns Nothing

`slugpy.write_integrated(data, model_name, fmt)`

Function to write a set of output integrated files in SLUG2 format, starting from an integrated data set as returned by `read_integrated`.

Parameters

data [namedtuple] Integrated data to be written, in the namedtuple format returned by `read_integrated`

model_name [string] Base file name to give the model to be written. Can include a directory specification if desired.

fmt [string] Format for the output file. Allowed values are 'ascii', 'bin' or 'binary', and 'fits'.

Returns Nothing

CLOUDY_SLUG: AN AUTOMATED INTERFACE TO CLOUDY

SLUG stochastically generates stellar spectra, but it does not compute the nebular lines produced when those photons interact with the interstellar medium. To perform such calculations, SLUG includes an automated interface to [cloudy](#) (Ferland et al., 2013, *RMxAA*, 49, 137). This can be used to post-process the output of a SLUG run in order to compute nebular emission.

10.1 cloudy_slug Basics

The basic steps (described in greater detail below) are as follows:

1. Get cloudy installed and compiled, following the directions on the [cloudy website](#).
2. Set the environment variable `$CLOUDY_DIR` to the directory where the cloudy executable `cloudy.exe` is located. If you are using a bash-like shell, the syntax for this is:

```
export CLOUDY_DIR = /path/to/cloudy
```

while for a csh-like shell, it is:

```
setenv CLOUDY_DIR /path/to/cloudy
```

3. If you desire, edit the cloudy input template `cloudy_slug/cloudy.in_template` and the line list `cloudy_slug/LineList_HII.dat`. There are the template input files that will be used for all the cloudy runs, and their syntax follows the standard cloudy syntax. They control things like the density and element abundances in the nebula – see *The cloudy_slug Input Template* for more details.
4. Perform the desired SLUG simulation. The SLUG simulation outputs must include spectra and photometry, and one of the photometric bands output must be QH0 (see *Photometric Filter Keywords*). If running in integrated mode (the default – see *The cloudy_slug Physical Model: Integrated Mode Versus Cluster Mode*), integrated spectra and photometry are required, and if running in cluster mode, cluster spectra and photometry are required.
5. Invoke the `cloudy_slug` interface script via:

```
python cloudy_slug/cloudy_slug.py SLUG_MODEL_NAME
```

where `SLUG_MODEL_NAME` is the name of the SLUG run to be processed. See *The cloudy_slug Physical Model: Integrated Mode Versus Cluster Mode* for more information on the underlying physical model assumed in the calculation, and *The cloudy_slug Interface Script* for more details on the python script and its options.

6. The output will be stored as a series of additional output files of with names of the form `SLUG_MODEL_NAME_*cloudy*.ext`, where the extension is `.txt`, `.bin`, or `.fits`, depending on the format in which the original SLUG output was stored. These files can be processed automatically by the `slugpy` helper routines (see *slugpy – The Python Helper Library*). See *Full Description of cloudy_slug Output* for a description of the outputs.

10.2 The `cloudy_slug` Physical Model: Integrated Mode Versus Cluster Mode

Associating nebular emission with the stellar populations produced by SLUG requires some assumptions about geometry, and some choices about what quantities one is interested in computed. SLUG outputs both integrated spectra for all the stars in a galaxy, and spectra for individual clusters. One on hand, one could make the extreme assumption that all the star clusters are spatially close enough to one another that one can think of the entire galaxy as a single giant HII region, and compute the nebular emission for the galaxy as a whole. This may be a reasonable assumption for galaxies where the star formation is highly spatially-concentrated. At the other extreme, one may assume that there is no overlap whatsoever between the HII regions surrounding different star clusters, so that nebular emission should be computed for each one independently. This may be a reasonable assumption for extended, slowly star-forming systems like the outer disk of the Milky Way. Each of these assumptions entails somewhat different choices about how to set the inner radius and inner density the HII region, as required by `cloudy`. The `cloudy_slug` interface can compute nebular emission under either of these scenarios; we refer to the former as integrated mode, and to the latter as cluster mode. Note that, in either mode, the spectrum that is used to compute the nebular emission will be the *unextincted*, *non-redshifted* spectrum computed by SLUG.

10.2.1 Integrated Mode

In integrated mode, `cloudy_slug` will read all the spectra contained in the SLUG `integrated_spec` output file, and for each stellar spectrum it will perform a `cloudy` run to produce a calculation of the nebular emission produced by that stellar spectrum interacting with a surrounding HII region. The density in the first zone of the HII region will be as specified by the standard `hden` keyword in the `cloudy` input template (see [The `cloudy_slug` Input Template](#)). The inner radius of the HII region will be computed automatically, and will be set to 10^{-3} of the Stromgren radius for that density, where

$$r_{\text{St}} = \left(\frac{3.0Q(\text{H}^0)}{4\pi\alpha_B n_{\text{H}}^2} \right)^{1/3}$$

where $Q(\text{H}^0)$ is the ionizing luminosity computed by SLUG, n_{H} is the hydrogen number density stored in the `cloudy` input template, and α_B is the case B recombination coefficient, which is taken to have a value of $2.59 \times 10^{-13} \text{ cm}^3 \text{ s}^{-1}$.

10.2.2 Cluster Mode

In cluster mode, `cloudy_slug` will read all the individual cluster spectra contained in the SLUG `cluster_spec` file, and for each one it will perform a `cloudy` calculation to determine the corresponding nebular emission. The density and radius are handled somewhat differently in this case, since, for a mono-age stellar population, it is possible to compute the time evolution of the HII region radius and density.

In cluster mode, the hydrogen number density n_{H} stored in the `cloudy` input template (see [The `cloudy_slug` Input Template](#)) is taken to specify the density of the *neutral* gas around the HII region, not the density of the gas inside the HII region. The outer radius of the HII region is then computed using the approximate analytic solution for the expansion of an HII region into a uniform medium, including the effects of radiation pressure and stellar wind momentum deposition, given by Krumholz & Matzner (2009, *ApJ*, 703, 1352). The radius is computed from the

ionizing luminosity $Q(\text{H}^0)$, hydrogen number density n_{H} , and star cluster age t as

$$\begin{aligned} r_{\text{II}} &= r_{\text{ch}} \left(x_{\text{II,rad}}^{7/2} + x_{\text{II,gas}}^{7/2} \right)^{2/7} \\ x_{\text{II,rad}} &= (2\tau^2)^{1/4} \\ x_{\text{II,gas}} &= (49\tau^2/36)^{2/7} \\ \tau &= t/t_{\text{ch}} \\ r_{\text{ch}} &= \frac{\alpha_B}{12\pi\phi} \left(\frac{\epsilon_0}{2.2k_B T_{\text{II}}} \right)^2 f_{\text{trap}}^2 \frac{\psi^2 Q(\text{H}^0)}{c^2} \\ t_{\text{ch}} &= \left(\frac{4\pi\mu m_{\text{H}} n_{\text{H}} c r_{\text{ch}}^4}{3f_{\text{trap}} Q(\text{H}^0) \psi \epsilon_0} \right)^{1/2} \end{aligned}$$

where $\alpha_B = 2.59 \times 10^{-13} \text{ cm}^3 \text{ s}^{-1}$ is the case B recombination coefficient, $\phi = 0.73$ is the fraction of ionizing photons absorbed by hydrogen atoms rather than dust, $\epsilon_0 = 13.6 \text{ eV}$ is the hydrogen ionization potential, $T_{\text{II}} = 10^4 \text{ K}$ is the temperature inside the HII region, $f_{\text{trap}} = 2$ is the trapping factor that accounts for stellar wind and trapped infrared radiation pressure, $\psi = 3.2$ is the mean photon energy in Rydberg for a fully sampled IMF at zero age, and $\mu = 1.33$ is the mean mass per hydrogen nucleus for gas of the standard cosmic composition. See [Krumholz & Matzner \(2009\)](#) for a discussion of the fiducial choices of these factors.

Once the outer radius is known, `cloudy_slug` sets the starting radius for the cloudy calculation to $10^{-3} r_{\text{II}}$, and sets the starting density to the value expected for photoionization equilibrium in a uniform HII region,

$$n_{\text{II}} = \left(\frac{3Q(\text{H}^0)}{4.4\pi\alpha_B r_{\text{II}}^3} \right)^{1/2}$$

Note that this approximation will be highly inaccurate if $r_{\text{II}} \ll r_{\text{ch}}$, but no better analytic approximation is available, and this phase should be very short-lived for most clusters.

10.3 The cloudy_slug Input Template

The `cloudy_slug` interface operates by reading SLUG output spectra and using them as inputs to a cloudy calculation. However, cloudy obviously requires many input parameters beyond simply the spectrum of the input radiation field. These parameters are normally provided by an input file whose format is as described in the [cloudy documentation](#). The `cloudy_slug` interface works by reading a *template* input file that specifies all these parameter, and which will be used as a basis for the final cloudy input files that will contain the SLUG spectra.

In general the template input file looks just like an ordinary cloudy input file, subject to the following restrictions:

1. The input file *must not* contain any commands that specify the luminosity, intensity, or the spectral shape. These will be inserted automatically by the `cloudy_slug` script.
2. The input file *must not* contain a radius command. This too will be computed automatically by the `cloudy_slug` script.
3. The input file *must* contain an entry `hden N` where `N` is the log base 10 of the hydrogen density. This will be interpreted differently depending on whether `cloudy_slug` is being run in cluster mode or integrated mode – see [The cloudy_slug Physical Model: Integrated Mode Versus Cluster Mode](#).
4. Any outputs to be written (specified using the `save` or `punch` keywords) must give file names containing the string `OUTPUT_FILENAME`. This string will be replaced by the `cloudy_slug` script to generate a unique file name for each cloudy run, and to read back these outputs for post-processing.
5. The `cloudy_slug` output will contain output spectra only if the cloudy input file contains a `save last continuum` command. See [Full Description of cloudy_slug Output](#).

6. The `cloudy_slug` output will contain output line luminosities only if the cloudy input file contains a `save last line list emergent absolute column` command. See [Full Description of cloudy_slug Output](#).
7. If any other outputs are produced by the input file, they will neither be processed nor moved, deleted, or otherwise changed by the `cloudy_slug` script.
8. Running cloudy in grid mode is not currently supported.

An example cloudy input file with reasonable parameter choices is provided as `cloudy_slug/cloudy_in.template` in the main directory of the SLUG repository.

In addition to the input file, the default template makes use of a cloudy line list file to specify which line luminosities should be output (see the [cloudy documentation](#) for details). The template points to the file `cloudy_slug/LineList_HII.data` (which is identical to cloudy’s default line list for HII regions), but any other valid cloudy line list file would work as well.

10.4 The cloudy_slug Interface Script

The `cloudy_slug.py` script provides the interface between SLUG and cloudy. Usage for this script is as follows:

```
cloudy_slug.py [-h] [-a AGEMAX] [--cloudypath CLOUDYPATH]
               [--cloudytemplate CLOUDYTEMPLATE] [-cm] [-nl NICELEVEL]
               [-n NPROC] [-s] [--slugpath SLUGPATH] [-v]
               slug_model_name [start_spec] [end_spec]
```

The positional arguments are as follows:

- `slug_model_name`: this is the name of the SLUG output to be used as a basis for the cloudy calculation. This should be the same as the `model_name` parameter used in the SLUG simulation, with the optional addition of a path specification in front.
- `start_spec`: default behavior is to run cloudy on all the integrated spectra (in [Integrated Mode](#)) or cluster spectra (in [Cluster Mode](#)). If this argument is set, cloudy will only be run in spectra starting with the specified trial number (in [Integrated Mode](#)) or cluster number (in [Cluster Mode](#)); numbers are 0-offset, to the first trial/cluster is 0, the next is 1, etc.
- `end_spec`: default behavior is to run cloudy on all the integrated spectra (in [Integrated Mode](#)) or cluster spectra (in [Cluster Mode](#)). If this argument is set, cloudy will only be run on spectra up to the specified trial number (in [Integrated Mode](#)) or cluster number (in [Cluster Mode](#)); numbers are 0-offset, to the first trial/cluster is 0, the next is 1, etc.

The optional arguments are as follows:

- `-h`, `--help`: prints a help message and then exits
- `-a AGEMAX`, `--agemax AGEMAX`: maximum cluster age in Myr for cloudy computation. Cloudy will not be run on clusters older than this value, and the predicted nebular emission for such clusters will be recorded as zero. Default value is 4 Myr. This argument only has an effect if running in [Cluster Mode](#); otherwise it is ignored.
- `--cloudypath CLOUDYPATH`: path to the cloudy executable; default is `$CLOUDY_DIR/cloudy.exe`
- `--cloudytemplate CLOUDYTEMPLATE`: cloudy input file template (see [The cloudy_slug Input Template](#)); default is `$SLUG_DIR/cloudy_slug/cloudy_in.template`
- `-cm`, `--clustermode`: if this argument is set, then `cloudy_slug` will run in [Cluster Mode](#); default behavior is to run in [Integrated Mode](#)

- `-nl NICELEVEL, --nicelevel NICELEVEL`: if this is set, then the cloudy processes launched by the script will be run at this nice level. If it is not set, they will not be nice'd. Note that this option will only work correctly on platforms that support nice.
- `-n NPROC, --nproc NPROC`: number of simultaneous cloudy processes to run; default is the number of cores available on the system
- `-s, --save`: by default, `cloudy_slug` will extract line and spectral data from the cloudy outputs and store them as described in [Full Description of cloudy_slug Output](#), then delete the cloudy output files. If this option is set, the cloudy output files will NOT be deleted, and will be left in place. WARNING: cloudy's outputs are written in ASCII and are quite voluminous, so only choose this option if you are only running cloudy on a small number of SLUG spectra and/or you are prepared to store hundreds of GB more more.
- `--slugpath SLUGPATH`: path to the SLUG output data. If not set, `cloudy_slug` searches for an appropriately-named set of output files first in the current working directory, and next in `$SLUG_DIR/output`
- `-v, --verbose`: if this option is set, `cloudy_slug` produces verbose output as it runs

10.5 Full Description of cloudy_slug Output

The `cloudy_slug` script will automatically process the cloudy output and produce a series of new output files, which will be written to the same directory where the input SLUG files are located, and using the same output mode (ASCII text, raw binary, or FITS – see [Output Files and Format](#)). If `cloudy_slug` is run in *Integrated Mode*, the three output files will be `MODEL_NAME_integrated_cloudyline.ext`, `MODEL_NAME_integrated_cloudyphot.ext`, and `MODEL_NAME_integrated_cloudyspec.ext`, where the extension `.ext` is one of `.txt`, `.bin`, or `.fits`, depending on the `output_mode`. If `cloudy_slug` is run in *Cluster Mode*, the three output files will be `MODEL_NAME_cluster_cloudyline.ext`, `MODEL_NAME_cluster_cloudyphot.ext`, and `MODEL_NAME_cluster_cloudyspec.ext`. All of these output files will be read and processed automatically if the outputs are read using `read_integrated` or `read_cluster` in the *slugpy – The Python Helper Library* library.

The format of those files is described below.

10.5.1 The integrated_cloudyline File

This file contains data on the nebular line emission produced by the interaction of the stellar radiation field with the ISM. It consists of a series of entries containing the following fields:

- **Time**: evolution time at which the output is produced
- **LineLabel**: four letter code labeling each line. These codes are the codes used by cloudy (see the [cloudy documentation](#))
- **“Wavelength”**: wavelength of the line, in Angstrom. Note that default cloudy behavior is to round wavelengths to the nearest Angstrom.
- **Luminosity**: line luminosity, in erg/s

If the SLUG data input to `cloudy_slug` were written in `ascii` mode, these data are output as a text file containing a series of columns, with different trials separated by lines of dashes.

If the SLUG data input to `cloudy_slug` were written in `fits` mode, the data are written in a FITS file containing two binary table extensions. The first extension contains two fields, `Line_label` and `Wavelength`, giving the four-letter cloudy line codes and central wavelengths. The second extension contains three columns, giving the trial number, time, and line luminosity for each line at each time in each trial.

If the SLUG data input to `cloudy_slug` were written in `binary` mode, the data are written in a raw binary file. The file starts with a header consisting of

- `NLine` (python `int`, equivalent to C `long`): number of lines
- `LineLabel` (`NLine` entries stored as ASCII `text`): line labels listed in ASCII, one label per line

This is followed by a series of entries of the form

- `Time` (double)
- `LineLum` (`NLine` entries of type `numpy float64`)

There is one such record for each output time, with different trials ordered sequentially, so that all the times for one trial are output before the first time for the next trial.

10.5.2 The `integrated_cloudyspec` File

This file contains data on the spectrum produced by interaction between the stellar radiation field and the nebula. Each entry in the output file contains the following fields:

- `Time`: evolution time at which the output is produced
- `Wavelength`: the wavelength at which the spectrum is evaluated, in Angstrom
- `Incident`: specific luminosity in `erg/s/Angstrom` at the specified wavelength. In `cloudy`'s terminology, this is the *incident* spectrum, i.e., the stellar radiation field entering the nebula. It should be the same as the spectrum contained in the SLUG `integrated_spec` file for the corresponding time and trial, except interpolated onto the wavelength grid used by `cloudy`.
- `Transmitted`: specific luminosity in `erg/s/Angstrom` at the specified wavelength. In `cloudy`'s terminology, this is the *transmitted* spectrum, i.e., the stellar spectrum exiting the HII region, not including any emission produced within the nebula. This is what would be detected by an observing aperture that included only the stars, and none of the nebula.
- `Emitted`: specific luminosity in `erg/s/Angstrom` at the specified wavelength. In `cloudy`'s terminology, this is the *emitted* spectrum, i.e., the spectrum emitted by the diffuse gas in the HII region, excluding any light from the stars themselves. This is what would be seen by an observer whose aperture covered the nebula, but masked the stars.
- `Transmitted_plus_emitted`: this is just the sum of `Transmitted` and `Emitted`. It represents what would be observed in an aperture including both the stars and the HII region.

If the SLUG data input to `cloudy_slug` were written in `ascii` mode, these data are output as a text file containing a series of columns, with different trials separated by lines of dashes.

If the SLUG data input to `cloudy_slug` were written in `fits` mode, these data are written in a FITS file containing two binary table extensions. The first extension contains one field, `Wavelength`, which gives the wavelengths of the spectra in Angstrom. The second extension contains six fields: `Trial`, `Time`, `Incident_spectrum`, `Transmitted_spectrum`, `Emitted_spectrum`, and `Transmitted_plus_emitted_spectrum`. The first two of these give the trial number and time, and the remaining four give the incident, transmitted, emitted, and transmitted plus emitted spectra for the corresponding time and trial.

If the SLUG data input to `cloudy_slug` were written in `binary` mode, these data are written in a raw binary file that is formatted as follows. The file begins with a header consisting of

- `NWavelength` (`numpy int64`): number of wavelengths
- `Wavelength` (`NWavelength` entries of `numpy float64`)

and then contains a series of records of the form

- `Time` (`numpy float64`)

- Incident (NWavelength entries of numpy float64)
- Transmitted (NWavelength entries of numpy float64)
- Emitted (NWavelength entries of numpy float64)
- Transmitted_plus_emitted (NWavelength entries of numpy float64)

There is one such record for each output time, with different trials ordered sequentially, so that all the times for one trial are output before the first time for the next trial.

10.5.3 The `integrated_cloudyphot` File

This file contains photometric data computed for the spectra produced by the interaction between the stellar radiation field and the HII region. The file consists of a series of entries containing the following fields:

- Time: evolution time at which the output is computed
- PhotFilter1_trans: photometric value for the *Transmitted* radiation field through filter 1, where filter 1 here is the same as filter 1 in *The integrated_phot File*; units are also the same as in that file.
- PhotFilter1_emit: photometric value for the *Emitted* radiation field through filter 1
- PhotFilter1_trans_emit: photometric value for the *Transmitted_plus_emitted* radiation field through filter 1
- PhotFilter2_trans
- PhotFilter2_emit
- PhotFilter2_trans_emit
- ...

For distinctions between the *Transmitted*, *Emitted*, and *Transmitted_plus_emitted* radiation fields, see *The integrated_cloudyspec File*, or the [cloudy documentaiton](#). Note that we do not record photometry for the incident spectrum, since that would be, up to the accuracy of the numerical integration, identical to the photometry already recorded in the *The integrated_phot File*.

If the SLUG data input to `cloudy_slug` were written in `ascii` mode, these data are output as a text file containing a series of columns, with different trials separated by lines of dashes.

If the SLUG data input to `cloudy_slug` were written in `fits` mode, these data are written in a FITS file containing one binary table extension, consisting of a series of columns. The columns are `Trial`, `Time`, `Filter1_Transmitted`, `Filter1_Emitted`, `Filter1_Transmitted_plus_emitted`, ... The first two columns give the trial number and the time, and the remainder give the photometric values for the transmitted, emitted, and transmitted plus emitted spectra in each filter.

If the SLUG data input to `cloudy_slug` were written in `binary` mode, these data are written to a raw binary file that is formatted as follows. The file starts with an ASCII header consisting of the following, each on a separate line:

- NFilter (stored as ASCII text): number of filters used
- FilterName FilterUnit (NFilter entries stored as ASCII text): the name and units for each filter are listed in ASCII, one filter-unit pair per line

This is followed by a series of entries of the form:

- PhotFilter_Transmitted (NFilter entries of numpy float64), giving the transmitted photometry in each filter
- PhotFilter_Emitted (NFilter entries of numpy float64), giving the emitted photometry in each filter

- `PhotFilter_Transmitted_plus_emitted` (`NFilter` entries of `numpy float64`), giving the transmitted plus emitted photometry in each filter

There is one such record for each output time, with different trials ordered sequentially, so that all the times for one trial are output before the first time for the next trial.

10.5.4 The `cluster_cloudy` File

This file contains data on the nebular line emission produced by the interaction of the stellar radiation field with the ISM around each cluster. It consists of a series of entries containing the following fields:

- `UniqueID`: a unique identifier number for each cluster that is preserved across times and output files
- `Time`: evolution time at which the output is produced
- `LineLabel`: four letter code labeling each line. These codes are the codes used by `cloudy` (see the [cloudy documentation](#))
- `Wavelength`: wavelength of the line, in Angstrom. Note that default `cloudy` behavior is to round wavelengths to the nearest Angstrom.
- `Luminosity`: line luminosity, in erg/s

If the SLUG data input to `cloudy_slug` were written in `ascii` mode, these data are output as a text file containing a series of columns, with different trials separated by lines of dashes.

If the SLUG data input to `cloudy_slug` were written in `fits` mode, the data are written in a FITS file containing two binary table extensions. The first extension contains two fields, `Line_label` and `Wavelength`, giving the four-letter `cloudy` line codes and central wavelengths. The second extension contains four columns, giving the unique ID, trial number, time, and line luminosity for each line at each time in each trial.

If the SLUG data input to `cloudy_slug` were written in `binary` mode, the data are written in a raw binary file. The file starts with a header consisting of

- `NLine` (python `int`, equivalent to C `long`): number of lines
- `LineLabel` (`NLine` entries stored as ASCII `text`): line labels listed in ASCII, one label per line

This is followed by a series of records, one for each output time, with different trials ordered sequentially, so that all the times for one trial are output before the first time for the next trial. Each record consists of a header containing

- `Time` (double)
- `NCluster` (`std::vector<double>::size_type`, usually unsigned long long): number of non-disrupted clusters present at this time

This is followed by `NCluster` entries of the following form:

- `UniqueID` (numpy `uint64`)
- `LineLum` (`NLine` entries of numpy `float64`)

10.5.5 The `cluster_cloudy` File

This file contains data on the spectra produced by the interaction of the stellar radiation field with the ISM around each cluster. It consists of a series of entries containing the following fields:

- `UniqueID`: a unique identifier number for each cluster that is preserved across times and output files
- `Time`: evolution time at which the output is produced
- `Wavelength`: observed frame wavelength at which the spectrum is evaluated

- Incident: specific luminosity in erg/s/Angstrom at the specified wavelength for the *incident* radiation field
- Transmitted: specific luminosity in erg/s/Angstrom at the specified wavelength for the *transmitted* radiation field
- Emitted: specific luminosity in erg/s/Angstrom at the specified wavelength for the *emitted* radiation field
- Transmitted_plus_emitted: specific luminosity in erg/s/Angstrom at the specified wavelength for the *transmitted plus emitted* radiation field

For explanations of the distinction between the incident, transmitted, emitted, and transmitted plus emitted radiation fields, see [The *integrated_cloudyspec* File](#).

If the SLUG data input to `cloudy_slug` were written in `ascii` mode, these data are output as a text file containing a series of columns, with different trials separated by lines of dashes.

If the SLUG data input to `cloudy_slug` were written in `fits` mode, these data are written in a FITS file containing two binary table extensions. The first table contains a column `Wavelength` listing the wavelengths at which the spectra are given. The second table consists of seven columns: `Trial`, `UniqueID`, `Time`, `Incident_spectrum`, `Transmitted_spectrum`, `Emitted_spectrum`, and `Transmitted_plus_emitted_spectrum`. The first three of these give the trial number, unique ID of the cluster, and the time. The remaining four give the incident, transmitted, emitted, and transmitted plus emitted spectra for the corresponding cluster.

If the SLUG data input to `cloudy_slug` were written in `binary` mode, these data are written to a raw binary file formatted as follows. The file starts with

- `NWavelength` (numpy int64): the number of wavelength entries in the spectra
- `Wavelength` (NWavelength entries of type double)

and then contains a series of records, one for each output time, with different trials ordered sequentially, so that all the times for one trial are output before the first time for the next trial. Each record consists of a header containing

- `Time` (double)
- `NCluster` (python int): number of non-disrupted clusters present at this time

This is followed by `NCluster` entries of the following form:

- `UniqueID` (unsigned long)
- `Incident` (NWavelength entries of numpy float64)
- `Transmitted` (NWavelength entries of numpy float64)
- `Emitted` (NWavelength entries of numpy float64)
- `Transmitted_plus_emitted` (NWavelength entries of numpy float64)

10.5.6 The `cluster_cloudyphot` File

This file contains data on the photometry of the spectra produced by the interaction of the stellar radiation field with the ISM around each cluster. It consists of a series of entries containing the following fields:

- `UniqueID`: a unique identifier number for each cluster that is preserved across times and output files
- `Time`: evolution time at which the output is produced
- `PhotFilter1_trans`: photometric value for the *Transmitted* radiation field through filter 1, where filter 1 here is the same as filter 1 in [The *integrated_phot* File](#); units are also the same as in that file.
- `PhotFilter1_emit`: photometric value for the *Emitted* radiation field through filter 1
- `PhotFilter1_trans_emit`: photometric value for the *Transmitted_plus_emitted* radiation field through filter 1

- PhotFilter2_trans
- PhotFilter2_emit
- PhotFilter2_trans_emit
- ...

For distinctions between the *Transmitted*, *Emitted*, and *Transmitted_plus_emitted* radiation fields, see [The integrated_cloudyspec File](#), or the [cloudy documentaiton](#). Note that we do not record photometry for the incident spectrum, since that would be, up to the accuracy of the numerical integration, identical to the photometry already recorded in the [The cluster_phot File](#).

If the SLUG data input to `cloudy_slug` were written in `ascii` mode, these data are output as a text file containing a series of columns, with different trials separated by lines of dashes.

If the SLUG data input to `cloudy_slug` were written in `fits` mode, these data are written in a FITS file containing one binary table extension. The columns in this FITS file are `Trial`, `UniqueID`, `Time`, `Filter1_Transmitted`, `Filter1_Emitted`, `Filter1_Transmitted_plus_emitted`, ... The first three columns give the trial number, cluster unique ID, and the time, and the remainder give the photometric values for the transmitted, emitted, and transmitted plus emitted spectra in each filter.

If the SLUG data input to `cloudy_slug` were written in `binary` mode, these data are written in a raw binary file that is formatted as follows. The file starts with an ASCII text header consisting of the following, each on a separate line:

- `NFilter` (stored as `ASCII text`): number of filters used
- `FilterName FilterUnit` (`NFilter` entries stored as `ASCII text`): the name and units for each filter are listed in `ASCII`, one filter-unit pair per line

This is followed by a series of entries of that each begin with a header

- `Time` (`double`)
- `NCluster` (`std::vector<double>::size_type`, usually `unsigned long long`): number of non-disrupted clusters present at this time

This is followed by `NCluster` entries of the following form:

- `UniqueID` (`unsigned long`)
- `PhotFilter_Transmitted` (`NFilter` entries of `numpy float64`), giving the transmitted photometry in each filter
- `PhotFilter_Emitted` (`NFilter` entries of `numpy float64`), giving the emitted photometry in each filter
- `PhotFilter_Transmitted_plus_emitted` (`NFilter` entries of `numpy float64`), giving the transmitted plus emitted photometry in each filter

10.6 Full Documentation of `slugpy.cloudy`

`slugpy.cloudy.read_cloudy_continuum(filename, r0=None)`

Reads a cloudy continuum output, produced by `save last continuum`

Parameters

filename [string] name of the file to be read

r0 [float] inner radius, in cm; if included, the quantities returned will be total energies instead of energy emission rates instead of rates per unit area

Returns A `namedtuple` containing the following fields:

wl [array] wavelengths in Angstrom

incident [array] incident radiation field intensity

`slugpy.cloudy.read_cloudy_linelist(filename)`

Reads a cloudy line list output, produced by save last line list

Parameters

filename [string] name of the file to be read

Returns A namedtuple containing the following fields:

labels [array, dtype 'S4'] list of line labels

wl [array] array of line wavelengths, in Angstrom

lum [array] array of line luminosities; this will be in whatever units the cloudy output is in

`slugpy.cloudy.read_cluster_cloudyphot(model_name, output_dir=None, fmt=None, nofilterdata=False, photsystem=None, verbose=False, read_info=None)`

Function to read a SLUG2 cluster_cloudyphot file.

Parameters

model_name [string] The name of the model to be read

output_dir [string] The directory where the SLUG2 output is located; if set to None, the current directory is searched, followed by the SLUG_DIR directory if that environment variable is set

fmt [string] Format for the file to be read. Allowed values are 'ascii', 'bin' or 'binary', and 'fits'. If one of these is set, the code will only attempt to open ASCII-, binary-, or FITS-formatted output, ending in .txt., .bin, or .fits, respectively. If set to None, the code will try to open ASCII files first, then if it fails try binary files, and if it fails again try FITS files.

nofilterdata [bool] If True, the routine does not attempt to read the filter response data from the standard location

photsystem [None or string] If photsystem is None, the data will be returned in the same photometric system in which they were read. Alternately, if it is a string, the data will be converted to the specified photometric system. Allowable values are 'L_nu', 'L_lambda', 'AB', 'STMAG', and 'Vega', corresponding to the options defined in the SLUG code. If this is set and the conversion requested involves a conversion from a wavelength-based system to a frequency-based one, nofilterdata must be False so that the central wavelength of the photometric filters is available.

verbose [bool] If True, verbose output is printed as code runs

read_info [dict] On return, this dict will contain the keys 'fname' and 'format', giving the name of the file read and the format it was in; 'format' will be one of 'ascii', 'binary', or 'fits'

Returns A namedtuple containing the following fields:

id [array, dtype uint] unique ID of cluster

trial: array, dtype uint which trial was this cluster part of

time [array] times at which cluster spectra are output, in yr

cloudy_filter_names [list of string] a list giving the name for each filter

cloudy_filter_units [list of string] a list giving the units for each filter

cloudy_filter_wl_eff [list] effective wavelength of each filter; this is set to None for the filters Lbol, QH0, QHe0, and QHe1; omitted if nofilterdata is True

cloudy_filter_wl [list of arrays] a list giving the wavelength table for each filter; this is None for the filters Lbol, QH0, QHe0, and QHe1; omitted if nofilterdata is True

cloudy_filter_response [list of arrays] a list giving the photon response function for each filter; this is None for the filters Lbol, QH0, QHe0, and QHe1; omitted if nofilterdata is True

cloudy_filter_beta [list] powerlaw index beta for each filter; used to normalize the photometry

cloudy_filter_wl_c [list] pivot wavelength for each filter; used to normalize the photometry

cloudy_phot_trans [array, shape (N_cluster, N_filter)] photometric value for each cluster in each filter for the transmitted light (i.e., the starlight remaining after it has passed through the HII region); units are as indicated in the units field

cloudy_phot_emit [array, shape (N_cluster, N_filter)] photometric value for each cluster in each filter for the emitted light (i.e., the diffuse light emitted by the HII region); units are as indicated in the units field

cloudy_phot_trans_emit [array, shape (N_cluster, N_filter)] photometric value in each filter for each cluster for the transmitted plus emitted light (i.e., the light coming directly from the stars after absorption by the HII region, plus the diffuse light emitted by the HII region); units are as indicated in the units field

Raises IOError, if no photometry file can be opened; ValueError, if photosystem is set to an unknown value

`slugpy.cloudy.read_cluster_cloudyline`(*model_name*, *output_dir=None*, *fnt=None*, *verbose=False*, *read_info=None*)

Function to read a SLUG2 cluster_cloudyline file.

Parameters

model_name [string] The name of the model to be read

output_dir [string] The directory where the SLUG2 output is located; if set to None, the current directory is searched, followed by the SLUG_DIR directory if that environment variable is set

fnt [string] Format for the file to be read. Allowed values are 'ascii', 'bin' or 'binary', and 'fits'. If one of these is set, the code will only attempt to open ASCII-, binary-, or FITS-formatted output, ending in .txt., .bin, or .fits, respectively. If set to None, the code will try to open ASCII files first, then if it fails try binary files, and if it fails again try FITS files.

verbose [bool] If True, verbose output is printed as code runs

read_info [dict] On return, this dict will contain the keys 'fname' and 'format', giving the name of the file read and the format it was in; 'format' will be one of 'ascii', 'binary', or 'fits'

Returns A namedtuple containing the following fields:

id [array, dtype uint] unique ID of cluster

trial: array, dtype uint which trial was this cluster part of

time [array] times at which cluster spectra are output, in yr

cloudy_linelabel [array, dtype='S4', shape (N_lines)] labels for the lines, following cloudy's 4 character line label notation

cloudy_linewl [array, shape (N_lines)] rest wavelength for each line, in Angstrom

cloudy_linelum [array, shape (N_cluster, N_lines)] luminosity of each line at each time for each trial, in erg/s

`slugpy.cloudy.read_cluster_cloudyspec`(*model_name*, *output_dir=None*, *fnt=None*, *verbose=False*, *read_info=None*)

Function to read a SLUG2 cluster_cloudyspec file.

Parameters

- model_name** [string] The name of the model to be read
- output_dir** [string] The directory where the SLUG2 output is located; if set to None, the current directory is searched, followed by the SLUG_DIR directory if that environment variable is set
- fmt** [string] Format for the file to be read. Allowed values are 'ascii', 'bin' or 'binary', and 'fits'. If one of these is set, the code will only attempt to open ASCII-, binary-, or FITS-formatted output, ending in .txt., .bin, or .fits, respectively. If set to None, the code will try to open ASCII files first, then if it fails try binary files, and if it fails again try FITS files.
- verbose** [bool] If True, verbose output is printed as code runs
- read_info** [dict] On return, this dict will contain the keys 'fname' and 'format', giving the name of the file read and the format it was in; 'format' will be one of 'ascii', 'binary', or 'fits'

Returns A namedtuple containing the following fields:

- id** [array, dtype uint] unique ID of cluster
- trial: array, dtype uint** which trial was this cluster part of
- time** [array] times at which cluster spectra are output, in yr
- cloudy_wl** [array] wavelength, in Angstrom
- cloudy_inc** [array, shape (N_cluster, N_wavelength)] specific luminosity of the cluster's stellar radiation field at each wavelength, in erg/s/A
- cloudy_trans** [array, shape (N_cluster, N_wavelength)] specific luminosity of the stellar radiation field after it has passed through the HII region, at each wavelength, in erg/s/A
- cloudy_emit** [array, shape (N_cluster, N_wavelength)] specific luminosity of the radiation field emitted by the HII region, at each wavelength, in erg/s/A
- cloudy_trans_emit** [array, shape (N_cluster, N_wavelength)] the sum of the emitted and transmitted fields; this is what would be seen by an observer looking at both the star cluster and its nebula

Raises IOError, if no spectrum file can be opened

`slugpy.cloudy.read_integrated_cloudyline` (*model_name, output_dir=None, fmt=None, verbose=False, read_info=None*)

Function to read a SLUG2 integrated_cloudyline file.

Parameters

- model_name** [string] The name of the model to be read
- output_dir** [string] The directory where the SLUG2 output is located; if set to None, the current directory is searched, followed by the SLUG_DIR directory if that environment variable is set
- fmt** [string] Format for the file to be read. Allowed values are 'ascii', 'bin' or 'binary', and 'fits'. If one of these is set, the code will only attempt to open ASCII-, binary-, or FITS-formatted output, ending in .txt., .bin, or .fits, respectively. If set to None, the code will try to open ASCII files first, then if it fails try binary files, and if it fails again try FITS files.
- verbose** [bool] If True, verbose output is printed as code runs
- read_info** [dict] On return, this dict will contain the keys 'fname' and 'format', giving the name of the file read and the format it was in; 'format' will be one of 'ascii', 'binary', or 'fits'

Returns A namedtuple containing the following fields:

time [array, shape (N_times) or shape (N_trials)] Times at which data are output; shape is either N_times (if the run was done with fixed output times) or N_trials (if the run was done with random output times)

cloudy_linelabel [array, dtype='S4', shape (N_lines)] labels for the lines, following cloudy's 4 character line label notation

cloudy_linewl [array, shape (N_lines)] rest wavelength for each line, in Angstrom

cloudy_linelum [array, shape (N_lines, N_times, N_trials)] luminosity of each line at each time for each trial, in erg/s

`slugpy.cloudy.read_integrated_cloudyphot` (*model_name*, *output_dir=None*, *fmt=None*,
nofilterdata=False, *photosystem=None*, *verbose=False*, *read_info=None*)

Function to read a SLUG2 integrated_cloudyphot file.

Parameters

model_name [string] The name of the model to be read

output_dir [string] The directory where the SLUG2 output is located; if set to None, the current directory is searched, followed by the SLUG_DIR directory if that environment variable is set

fmt [string] Format for the file to be read. Allowed values are 'ascii', 'bin' or 'binary', and 'fits'. If one of these is set, the code will only attempt to open ASCII-, binary-, or FITS-formatted output, ending in .txt., .bin, or .fits, respectively. If set to None, the code will try to open ASCII files first, then if it fails try binary files, and if it fails again try FITS files.

nofilterdata [bool] If True, the routine does not attempt to read the filter response data from the standard location

photosystem [None or string] If photosystem is None, the data will be returned in the same photometric system in which they were read. Alternately, if it is a string, the data will be converted to the specified photometric system. Allowable values are 'L_nu', 'L_lambda', 'AB', 'STMAG', and 'Vega', corresponding to the options defined in the SLUG code. If this is set and the conversion requested involves a conversion from a wavelength-based system to a frequency-based one, nofilterdata must be False so that the central wavelength of the photometric filters is available.

verbose [bool] If True, verbose output is printed as code runs

read_info [dict] On return, this dict will contain the keys 'fname' and 'format', giving the name of the file read and the format it was in; 'format' will be one of 'ascii', 'binary', or 'fits'

Returns A namedtuple containing the following fields:

time [array, shape (N_times) or shape (N_trials)] Times at which data are output; shape is either N_times (if the run was done with fixed output times) or N_trials (if the run was done with random output times)

cloudy_filter_names [list of string] a list giving the name for each filter

cloudy_filter_units [list of string] a list giving the units for each filter

cloudy_filter_wl_eff [list] effective wavelength of each filter; this is set to None for the filters Lbol, QH0, QHe0, and QHe1; omitted if nofilterdata is True

cloudy_filter_wl [list of arrays] a list giving the wavelength table for each filter; this is None for the filters Lbol, QH0, QHe0, and QHe1; omitted if nofilterdata is True

cloudy_filter_response [list of arrays] a list giving the photon response function for each filter; this is None for the filters Lbol, QH0, QHe0, and QHe1; omitted if nofilterdata is True

cloudy_filter_beta [list] powerlaw index beta for each filter; used to normalize the photometry

cloudy_filter_wl_c [list] pivot wavelength for each filter; used to normalize the photometry

cloudy_phot_trans [array, shape (N_filter, N_times, N_trials)] photometric value in each filter at each time in each trial for the transmitted light (i.e., the starlight remaining after it has passed through the HII region); units are as indicated in the units field

cloudy_phot_emit [array, shape (N_filter, N_times, N_trials)] photometric value in each filter at each time in each trial for the emitted light (i.e., the diffuse light emitted by the HII region); units are as indicated in the units field

cloudy_phot_trans_emit [array, shape (N_filter, N_times, N_trials)] photometric value in each filter at each time in each trial for the transmitted plus emitted light (i.e., the light coming directly from the stars after absorption by the HII region, plus the diffuse light emitted by the HII region); units are as indicated in the units field

Raises IOError, if no photometry file can be opened; ValueError, if photosystem is set to an unknown value

`slugpy.cloudy.read_integrated_cloudyspec(model_name, output_dir=None, fmt=None, verbose=False, read_info=None)`

Function to read a SLUG2 integrated_cloudyspec file.

Parameters

model_name [string] The name of the model to be read

output_dir [string] The directory where the SLUG2 output is located; if set to None, the current directory is searched, followed by the SLUG_DIR directory if that environment variable is set

fmt [string] Format for the file to be read. Allowed values are 'ascii', 'bin' or 'binary', and 'fits'. If one of these is set, the code will only attempt to open ASCII-, binary-, or FITS-formatted output, ending in .txt., .bin, or .fits, respectively. If set to None, the code will try to open ASCII files first, then if it fails try binary files, and if it fails again try FITS files.

verbose [bool] If True, verbose output is printed as code runs

read_info [dict] On return, this dict will contain the keys 'fname' and 'format', giving the name of the file read and the format it was in; 'format' will be one of 'ascii', 'binary', or 'fits'

Returns A namedtuple containing the following fields:

time [array, shape (N_times) or shape (N_trials)] Times at which data are output; shape is either N_times (if the run was done with fixed output times) or N_trials (if the run was done with random output times)

cloudy_wl [array] wavelength, in Angstrom

cloudy_inc [array, shape (N_wavelength, N_times, N_trials)] specific luminosity of the stellar radiation field at each wavelength and each time for each trial, in erg/s/A

cloudy_trans [array, shape (N_wavelength, N_times, N_trials)] specific luminosity of the stellar radiation field after it has passed through the HII region, at each wavelength and each time for each trial, in erg/s/A

cloudy_emit [array, shape (N_wavelength, N_times, N_trials)] specific luminosity of the radiation field emitted by the HII region, at each wavelength and each time for each trial, in erg/s/A

cloudy_trans_emit [array, shape (N_wavelength, N_times, N_trials)] the sum of emitted and transmitted; this is what would be seen by an observer looking at both the star cluster and its nebula

`slugpy.cloudy.write_cluster_cloudyphot(data, model_name, fmt)`

Write out photometry for nebular emission computed by cloudy on a slug spectrum for a series of clusters

Parameters

data [namedtuple] Cluster cloudy photometry data to be written; a namedtuple containing the fields `id`, `time`, `cloudy_filter_names`, `cloudy_filter_units`, `cloudy_phot_trans`, `cloudy_phot_emit`, and `cloudy_phot_trans_emit`

model_name [string] Base file name to give the model to be written. Can include a directory specification if desired.

fmt [string] Format for the output file. Allowed values are 'ascii', 'bin' or 'binary', and 'fits'.

Returns Nothing

`slugpy.cloudy.write_cluster_cloudyline`s(*data, model_name, fmt*)

Write out data computed by cloudy on a slug spectrum

Parameters

data [namedtuple] Cloudy spectral data for clusters to be written; a namedtuple containing the fields `time`, `cloudy_linelist`, `cloudy_linewl`, `cloudy_linelum`

model_name [string] Base file name to give the model to be written. Can include a directory specification if desired.

fmt [string] Format for the output file. Allowed values are 'ascii', 'bin' or 'binary', and 'fits'.

Returns Nothing

`slugpy.cloudy.write_cluster_cloudyspec`(*data, model_name, fmt*)

Write out data computed by cloudy on a slug spectrum

Parameters

data [namedtuple] Cloudy spectral data for clusters to be written; a namedtuple containing the fields `id`, `time`, `cloudy_wl`, `cloudy_inc`, `cloudy_trans`, `cloudy_emit`, and `cloudy_trans_emit`

model_name [string] Base file name to give the model to be written. Can include a directory specification if desired.

fmt [string] Format for the output file. Allowed values are 'ascii', 'bin' or 'binary', and 'fits'.

Returns Nothing

`slugpy.cloudy.write_integrated_cloudyline`s(*data, model_name, fmt*)

Write out line luminosities computed by cloudy on a slug spectrum

Parameters

data [namedtuple] Integrated cloudy line data to be written; a namedtuple containing the fields `time`, `cloudy_linelist`, `cloudy_linewl`, `cloudy_linelum`

model_name [string] Base file name to give the model to be written. Can include a directory specification if desired.

fmt [string] Format for the output file. Allowed values are 'ascii', 'bin' or 'binary', and 'fits'.

Returns Nothing

`slugpy.cloudy.write_integrated_cloudyphot`(*data, model_name, fmt*)

Write out photometry for nebular emission computed by cloudy on a slug spectrum

Parameters

data [namedtuple] Integrated cloudy photometry data to be written; a namedtuple containing the fields `time`, `cloudy_filter_names`, `cloudy_filter_units`, `cloudy_phot_trans`, `cloudy_phot_emit`, and `cloudy_phot_trans_emit`

model_name [string] Base file name to give the model to be written. Can include a directory specification if desired.

fmt [string] Format for the output file. Allowed values are 'ascii', 'bin' or 'binary, and 'fits'.

Returns Nothing

`slugpy.cloudy.write_integrated_cloudyspec(data, model_name, fmt)`

Write out data computed by cloudy on a slug spectrum

Parameters

data [namedtuple] Integrated cloudy spectral data to be written; a namedtuple containing the field time, cloudy_wl, cloudy_inc, cloudy_trans, cloudy_emit, and cloudy_trans_emit

model_name [string] Base file name to give the model to be written. Can include a directory specification if desired.

fmt [string] Format for the output file. Allowed values are 'ascii', 'bin' or 'binary, and 'fits'.

Returns Nothing

BAYESPHOT: BAYESIAN INFERENCE FOR STOCHASTIC STELLAR POPULATIONS

11.1 Full Documentation of `slugpy.bayesphot`

This defines a class that can be used to estimate the PDF of physical quantities from a set of input photometry in various bands, together with a training data set.

```
class slugpy.bayesphot.bp.bp(dataset, nphys, filters=None, bandwidth='auto', ktype='gaussian', pri-  
                             ors=None, sample_density=None, reltol=0.001, abstol=1e-10, leaf-  
                             size=16)
```

A class that can be used to estimate the PDF of the physical properties of stellar population from a training set plus a set of measured photometric values.

Properties

priors [array, shape (N) | callable | None] prior probability on each data point; interpretation depends on the type passed; array, shape (N): values are interpreted as the prior probability of each data point; callable: the callable must take as an argument an array of shape (N, nphys), and return an array of shape (N) giving the prior probability at each data point; None: all data points have equal prior probability

bandwidth ['auto' | array, shape (M)] bandwidth for kernel density estimation; if set to 'auto', the bandwidth will be estimated automatically

```
__init__(dataset, nphys, filters=None, bandwidth='auto', ktype='gaussian', priors=None, sam-  
         ple_density=None, reltol=0.001, abstol=1e-10, leafsize=16)
```

Initialize a bp object.

Parameters

dataset [array, shape (N, M)] training data set; this is a set of N sample stellar populations, having M properties each; the first npys represent physical properties (e.g., log mass, log age), while the next M - nphys represent photometric properties

nphys [int] number of physical properties in dataset

filters [listlike of strings, nphys elements] names of photometric filters; if left as None, the filters can be referred to by index, but not by name

bandwidth ['auto' | array, shape (M)] bandwidth for kernel density estimation; if set to 'auto', the bandwidth will be estimated automatically

ktype [string] type of kernel to be used in density estimation; allowed values are 'gaussian' (default), 'epanechnikov', and 'tophat'; only Gaussian can be used with error bars

priors [array, shape (N) | callable | None] prior probability on each data point; interpretation depends on the type passed; array, shape (N): values are interpreted as the prior probability of each data

point; callable: the callable must take as an argument an array of shape (N, nphys), and return an array of shape (N) giving the prior probability at each data point; None: all data points have equal prior probability

sample_density [array, shape (N) | callable | 'auto' | None] the density of the data samples at each data point; this need not match the prior density; interpretation depends on the type passed; array, shape (N): values are interpreted as the density of data sampling at each sample point; callable: the callable must take as an argument an array of shape (N, nphys), and return an array of shape (N) giving the sampling density at each point; 'auto': the sample density will be computed directly from the data set; note that this can be quite slow for large data sets, so it is preferable to specify this analytically if it is known; None: data are assumed to be uniformly sampled

reitol [float] relative error tolerance; errors on all returned probabilities p will satisfy either $\text{abs}(p_{\text{est}} - p_{\text{true}}) \leq \text{reitol} * p_{\text{est}}$ OR $\text{abs}(p_{\text{est}} - p_{\text{true}}) \leq \text{abstol}$, where p_{est} is the returned estimate and p_{true} is the true value

abstol [float] absolute error tolerance; see above

leafsize [int] number of data points in each leaf of the KD tree

Returns Nothing

Raises IOError, if the bayesphot c library cannot be found

__weakref__

list of weak references to the object (if defined)

logL (*physprop*, *photprop*, *photerr=None*)

This function returns the natural log of the likelihood function evaluated at a particular log mass, log age, extinction, and set of log luminosities

Parameters

physprop [arraylike, shape (nphys) or (... , nphys)] array giving values of the physical properties; for a multidimensional array, the operation is vectorized over the leading dimensions

photprop [arraylike, shape (nfilter) or (... , nfilter)] array giving the photometric values; for a multi-dimensional array, the operation is vectorized over the leading dimensions

photerr [arraylike, shape (nfilter) or (... , nfilter)] array giving photometric errors; for a multidimensional array, the operation is vectorized over the leading dimensions

Returns

logL [float or arraylike] natural log of the likelihood function

mcmc (*photprop*, *photerr=None*, *mc_walkers=100*, *mc_steps=500*, *mc_burn_in=50*)

This function returns a sample of MCMC walkers sampling the physical parameters at a specified set of photometric values.

Parameters:

photprop [arraylike, shape (nfilter) or (... , nfilter)] array giving the photometric values; for a multi-dimensional array, the operation is vectorized over the leading dimensions

photerr [arraylike, shape (nfilter) or (... , nfilter)] array giving photometric errors; for a multidimensional array, the operation is vectorized over the leading dimensions

mc_walkers [int] number of walkers to use in the MCMC

mc_steps [int] number of steps in the MCMC

mc_burn_in [int] number of steps to consider “burn-in” and discard

Returns

samples [array] array of sample points returned by the MCMC

mpdf (*idx*, *photprop*, *photerr*=None, *ngrid*=128, *qmin*=None, *qmax*=None, *grid*=None, *norm*=True)

Returns the marginal probability for one or more physical quantities for one or more input sets of photometric properties. Output quantities are computed on a grid of values, in the same style as meshgrid

Parameters:

idx [int or listlike containing ints] index of the physical quantity whose PDF is to be computed; if this is an iterable, the joint distribution of the indicated quantities is returned

photprop [arraylike, shape (nfilter) or (... , nfilter)] array giving the photometric values; for a multi-dimensional array, the operation is vectorized over the leading dimensions

photerr [arraylike, shape (nfilter) or (... , nfilter)] array giving photometric errors; for a multidimensional array, the operation is vectorized over the leading dimensions

ngrid [int or listlike containing ints] number of points in each dimension of the output grid; if this is an iterable, it must have the same number of elements as *idx*

qmin [float or listlike] minimum value in the output grid in each quantity; if left as None, defaults to the minimum value in the library; if this is an iterable, it must contain the same number of elements as *idx*

qmax [float or listlike] maximum value in the output grid in each quantity; if left as None, defaults to the maximum value in the library; if this is an iterable, it must contain the same number of elements as *idx*

grid [listlike of arrays] set of values defining the grid on which the PDF is to be evaluated, in the same format used by meshgrid

norm [bool] if True, returned pdf's will be normalized to integrate to 1

Returns:

grid_out [array] array of values at which the PDF is evaluated; contents are the same as returned by meshgrid

pdf [array] array of marginal posterior probabilities at each point of the output grid, for each input cluster; the leading dimensions match the leading dimensions produced by broadcasting the leading dimensions of *photprop* and *photerr* together, while the trailing dimensions match the dimensions of the output grid

CLUSTER_SLUG: BAYESIAN INFERENCE OF STAR CLUSTER PROPERTIES

12.1 Full Documentation of `slugpy.cluster_slug`

```
class slugpy.cluster_slug.cluster_slug (libname=None, filters=None, bandwidth='auto',  
                                         ktype='gaussian', priors=None, sample_density=None,  
                                         retol=0.001, abstol=1e-10, leafsize=16)
```

A class that can be used to estimate the PDF of star cluster properties (mass, age, extinction) from a set of input photometry in various bands.

Properties

priors [array, shape (N) | callable | None] prior probability on each data point; interpretation depends on the type passed; array, shape (N): values are interpreted as the prior probability of each data point; callable: the callable must take as an argument an array of shape (N, nphys), and return an array of shape (N) giving the prior probability at each data point; None: all data points have equal prior probability

bandwidth ['auto' | array, shape (M)] bandwidth for kernel density estimation; if set to 'auto', the bandwidth will be estimated automatically

```
__init__ (libname=None, filters=None, bandwidth='auto', ktype='gaussian', priors=None, sam-  
         ple_density=None, retol=0.001, abstol=1e-10, leafsize=16)  
Initialize a cluster_slug object.
```

Parameters

libname [string] name of the SLUG model to load; if left as None, the default is \$SLUG_DIR/cluster_slug/CLUSTER_SLUG

filters [iterable of stringlike] list of filter names to be used for inference

bandwidth ['auto' | array, shape (M)] bandwidth for kernel density estimation; if set to 'auto', the bandwidth will be estimated automatically

ktype [string] type of kernel to be used in density estimation; allowed values are 'gaussian' (default), 'epanechnikov', and 'tophat'; only Gaussian can be used with error bars

priors [array, shape (N) | callable | None] prior probability on each data point; interpretation depends on the type passed; array, shape (N): values are interpreted as the prior probability of each data point; callable: the callable must take as an argument an array of shape (N, nphys), and return an array of shape (N) giving the prior probability at each data point; None: all data points have equal prior probability

sample_density [array, shape (N) | callable | 'auto' | None] the density of the data samples at each data point; this need not match the prior density; interpretation depends on the type passed; array,

shape (N): values are interpreted as the density of data sampling at each sample point; callable: the callable must take as an argument an array of shape (N, nphys), and return an array of shape (N) giving the sampling density at each point; 'auto': the sample density will be computed directly from the data set; note that this can be quite slow for large data sets, so it is preferable to specify this analytically if it is known; None: data are assumed to be uniformly sampled

reltol [float] relative error tolerance; errors on all returned probabilities p will satisfy either $\text{abs}(p_{\text{est}} - p_{\text{true}}) \leq \text{reltol} * p_{\text{est}}$ OR $\text{abs}(p_{\text{est}} - p_{\text{true}}) \leq \text{abstol}$, where p_{est} is the returned estimate and p_{true} is the true value

abstol [float] absolute error tolerance; see above

leafsize [int] number of data points in each leaf of the KD tree

Returns Nothing

Raises IOError, if the library cannot be found

__weakref__

list of weak references to the object (if defined)

add_filters (*filters*)

Add a set of filters to use for cluster property estimation

Parameters

filters [iterable of stringlike] list of filter names to be used for inference

Returns nothing

filters ()

Returns list of all available filters

Parameters: None

Returns:

filters [list of strings] list of available filter names

logL (*physprop*, *photprop*, *photerr*=None, *filters*=None)

This function returns the natural log of the likelihood function evaluated at a particular log mass, log age, extinction, and set of log luminosities

Parameters:

physprop [arraylike, shape (3) or (... , 3)] array giving values of the log M, log T, and A_V; for a multidimensional array, the operation is vectorized over the leading dimensions

photprop [arraylike, shape (nfilter) or (... , nfilter)] array giving the photometric values; for a multidimensional array, the operation is vectorized over the leading dimensions

photerr [arraylike, shape (nfilter) or (... , nfilter)] array giving photometric errors; for a multidimensional array, the operation is vectorized over the leading dimensions

filters [listlike of strings] list of photometric filters to use; if left as None, and only 1 set of photometric filters has been defined for the cluster_slug object, that set will be used by default

Returns:

logL [float or arraylike] natural log of the likelihood function

mcmc (*photprop*, *photerr*=None, *mc_walkers*=100, *mc_steps*=500, *mc_burn_in*=50, *filters*=None)

This function returns a sample of MCMC walkers for cluster mass, age, and extinction

Parameters:

photprop [arraylike, shape (nfilter) or (... , nfilter)] array giving the photometric values; for a multi-dimensional array, the operation is vectorized over the leading dimensions

photerr [arraylike, shape (nfilter) or (... , nfilter)] array giving photometric errors; for a multidimensional array, the operation is vectorized over the leading dimensions

mc_walkers [int] number of walkers to use in the MCMC

mc_steps [int] number of steps in the MCMC

mc_burn_in [int] number of steps to consider “burn-in” and discard

filters [listlike of strings] list of photometric filters to use; if left as None, and only 1 set of photometric filters has been defined for the cluster_slug object, that set will be used by default

Returns

samples [array] array of sample points returned by the MCMC

mpdf (*idx, photprop, photerr=None, ngrid=128, qmin=None, qmax=None, grid=None, norm=True, filters=None*)

Returns the marginal probability for one or more physical quantities for one or more input sets of photometric properties. Output quantities are computed on a grid of values, in the same style as meshgrid

Parameters:

idx [int or listlike containing ints] index of the physical quantity whose PDF is to be computed; 0 = log M, 1 = log T, 2 = A_V; if this is an iterable, the joint distribution of the indicated quantities is returned

photprop [arraylike, shape (nfilter) or (... , nfilter)] array giving the photometric values; for a multi-dimensional array, the operation is vectorized over the leading dimensions

photerr [arraylike, shape (nfilter) or (... , nfilter)] array giving photometric errors; for a multidimensional array, the operation is vectorized over the leading dimensions

ngrid [int or listlike containing ints] number of points in each dimension of the output grid; if this is an iterable, it must have the same number of elements as idx

qmin [float or listlike] minimum value in the output grid in each quantity; if left as None, defaults to the minimum value in the library; if this is an iterable, it must contain the same number of elements as idx

qmax [float or listlike] maximum value in the output grid in each quantity; if left as None, defaults to the maximum value in the library; if this is an iterable, it must contain the same number of elements as idx

grid [listlike of arrays] set of values defining the grid on which the PDF is to be evaluated, in the same format used by meshgrid

norm [bool] if True, returned pdf's will be normalized to integrate to 1

filters [listlike of strings] list of photometric filters to use; if left as None, and only 1 set of photometric filters has been defined for the cluster_slug object, that set will be used by default

Returns:

grid_out [array] array of values at which the PDF is evaluated; contents are the same as returned by meshgrid

pdf [array] array of marginal posterior probabilities at each point of the output grid, for each input cluster; the leading dimensions match the leading dimensions produced by broadcasting the leading dimensions of photprop and photerr together, while the trailing dimensions match the dimensions of the output grid

SFR_SLUG: BAYESIAN INFERENCE OF STAR FORMATION RATES

13.1 Full Documentation of `slugpy.sfr_slug`

```
class slugpy.sfr_slug.sfr_slug (libname=None, detname=None, filters=None, bandwidth='auto',  
                                ktype='gaussian', priors=None, sample_density='default', rel-  
                                tol=0.001, abstol=1e-10, leafsize=16)
```

A class that can be used to estimate the PDF of true star formation rate from a set of input point mass estimates of the star formation rate.

Properties

priors [array, shape (N) | callable | None] prior probability on each data point; interpretation depends on the type passed; array, shape (N): values are interpreted as the prior probability of each data point; callable: the callable must take as an argument an array of shape (N, nphys), and return an array of shape (N) giving the prior probability at each data point; None: all data points have equal prior probability

bandwidth ['auto' | array, shape (M)] bandwidth for kernel density estimation; if set to 'auto', the bandwidth will be estimated automatically

```
__init__ (libname=None, detname=None, filters=None, bandwidth='auto', ktype='gaussian', pri-  
            ors=None, sample_density='default', reltol=0.001, abstol=1e-10, leafsize=16)
```

Initialize an `sfr_slug` object.

Parameters

libname [string] name of the SLUG model to load; if left as None, the default is `$SLUG_DIR/sfr_slug/SFR_SLUG`

detname [string] name of a SLUG model run with the same parameters but no stochasticity; used to establish the non-stochastic photometry to SFR conversions; if left as None, the default is `libname_DET`

filters [iterable of stringlike] list of filter names to be used for inference

bandwidth ['auto' | array, shape (M)] bandwidth for kernel density estimation; if set to 'auto', the bandwidth will be estimated automatically

ktype [string] type of kernel to be used in density estimation; allowed values are 'gaussian' (default), 'epanechnikov', and 'tophat'; only Gaussian can be used with error bars

priors [array, shape (N) | callable | None] prior probability on each data point; interpretation depends on the type passed; array, shape (N): values are interpreted as the prior probability of each data point; callable: the callable must take as an argument an array of shape (N, nphys), and return an array of shape (N) giving the prior probability at each data point; None: all data points have equal prior probability

sample_density [array, shape (N) | callable | 'auto' | 'default' | None] the density of the data samples at each data point; this need not match the prior density; interpretation depends on the type passed; array, shape (N): values are interpreted as the density of data sampling at each sample point; callable: the callable must take as an argument an array of shape (N, nphys), and return an array of shape (N) giving the sampling density at each point; 'auto': the sample density will be computed directly from the data set; note that this can be quite slow for large data sets, so it is preferable to specify this analytically if it is known; 'default': the sample density is assumed to be that of the default library that ships with SLUG; None: data are assumed to be uniformly sampled

reltol [float] relative error tolerance; errors on all returned probabilities p will satisfy either $\text{abs}(p_{\text{est}} - p_{\text{true}}) \leq \text{reltol} * p_{\text{est}}$ OR $\text{abs}(p_{\text{est}} - p_{\text{true}}) \leq \text{abstol}$, where p_{est} is the returned estimate and p_{true} is the true value

abstol [float] absolute error tolerance; see above

leafsize [int] number of data points in each leaf of the KD tree

Returns Nothing

Raises IOError, if the library cannot be found

__weakref__

list of weak references to the object (if defined)

add_filters (*filters*)

Add a set of filters to use for cluster property estimation

Parameters

filters [iterable of stringlike] list of filter names to be used for inference

Returns nothing

filters ()

Returns list of all available filters

Parameters: None

Returns:

filters [list of strings] list of available filter names

logL (*logSFR, logSFRphot, logSFRphoterr=None, filters=None*)

This function returns the natural log of the likelihood function evaluated at a particular log SFR and set of log luminosities

Parameters:

logSFR [float or arraylike] float or array giving values of the log SFR; for an array, the operation is vectorized

logSFRphot [float or arraylike, shape (nfilter) or (... , nfilter)] float or array giving the SFR inferred from photometry using a deterministic conversion; for an array, the operation is vectorized over the leading dimensions

logSFRphoterr [float arraylike, shape (nfilter) or (... , nfilter)] float or array giving photometric SFR errors; for a multidimensional array, the operation is vectorized over the leading dimensions

filters [listlike of strings] list of photometric filters used for the SFR estimation; if left as None, and only 1 set of photometric filters has been defined for the `sfr_slug` object, that set will be used by default

Returns:

logL [float or arraylike] natural log of the likelihood function

mcmc (*photprop*, *photerr*=None, *mc_walkers*=100, *mc_steps*=500, *mc_burn_in*=50, *filters*=None)

This function returns a sample of MCMC walkers for cluster mass, age, and extinction

Parameters:

photprop [arraylike, shape (nfilter) or (... , nfilter)] array giving the photometric values; for a multi-dimensional array, the operation is vectorized over the leading dimensions

photerr [arraylike, shape (nfilter) or (... , nfilter)] array giving photometric errors; for a multidimensional array, the operation is vectorized over the leading dimensions

mc_walkers [int] number of walkers to use in the MCMC

mc_steps [int] number of steps in the MCMC

mc_burn_in [int] number of steps to consider “burn-in” and discard

filters [listlike of strings] list of photometric filters to use; if left as None, and only 1 set of photometric filters has been defined for the cluster_slug object, that set will be used by default

Returns

samples [array] array of sample points returned by the MCMC

mpdf (*logSFRpho*, *logSFRphoterr*=None, *ngrid*=128, *qmin*=None, *qmax*=None, *grid*=None, *norm*=True, *filters*=None)

Returns the marginal probability of logSFR for one or more input sets of photometric properties. Output quantities are computed on a grid of values, in the same style as meshgrid

Parameters:

logSFRphot [float or arraylike] float or array giving the log SFR inferred from photometry using a deterministic conversion; if the argument is an array, the operation is vectorized over it

logSFRphoterr [arraylike, shape (nfilter) or (... , nfilter)] array giving photometric errors; for a multidimensional array, the operation is vectorized over the leading dimensions

ngrid [int or listlike containing ints] number of points in each dimension of the output grid; if this is an iterable, it must have the same number of elements as idx

qmin [float or listlike] minimum value in the output grid in each quantity; if left as None, defaults to the minimum value in the library; if this is an iterable, it must contain the same number of elements as idx

qmax [float or listlike] maximum value in the output grid in each quantity; if left as None, defaults to the maximum value in the library; if this is an iterable, it must contain the same number of elements as idx

grid [listlike of arrays] set of values defining the grid on which the PDF is to be evaluated, in the same format used by meshgrid

norm [bool] if True, returned pdf's will be normalized to integrate to 1

filters [listlike of strings] list of photometric filters to use; if left as None, and only 1 set of photometric filters has been defined for the cluster_slug object, that set will be used by default

Returns:

grid_out [array] array of values at which the PDF is evaluated; contents are the same as returned by meshgrid

pdf [array] array of marginal posterior probabilities at each point of the output grid, for each input cluster; the leading dimensions match the leading dimensions produced by broadcasting the leading dimensions of photprop and photerr together, while the trailing dimensions match the dimensions of the output grid

TEST PROBLEMS

This section describes a set of problems that can be used to test and explore the different capabilities of SLUG. SLUG ships a set of problems `problemname` that are specified by a parameter file `param/problemname.param`. Problems that require multiple simulations are described instead by multiple parameter files, each with unique ID `XX`: `param/problemnameXX.param`. Users can reproduce the output of the test problems with the provided executable scripts `test/run_problemname.sh`. For each problem, a script for analysis is distributed in `test/problemname.py`. Details for each test problem are given below. Throughout this section, it is assumed that the `SLUG_DIR` has been properly set. These test problems are designed to work with outputs in FITS format, but that can be easily changed in the `.param` files. To run all the problems and the analysis scripts in one go, the user can simply run `test/run_alltest.sh`. It will take around 15 minutes for the script to complete on a standard laptop. About 700MB of data are generated. If SLUG is correctly installed and working, the first part of the script (i.e. the SLUG simulations) should run flawlessly. The second part of the script relies instead on external python procedures, including `sluggy`, `numpy`, and `matplotlib`. While these packages are fairly standard, the user needs to ensure that they are properly installed and visible to the script. This script has been written for and tested with Python 2.7.

14.1 Problem `example_galaxy`: basic galaxy simulation

This problem illustrates the basic usage of `slugin galaxy` mode by running 48 realizations of a galaxy with constant $\text{SFR} = 0.001 M_{\odot} \text{ yr}^{-1}$, up to a maximum time of $2 \times 10^8 \text{ yr}$. By issuing the command `test/run_example_galaxy.sh` the output files `SLUG_GALAXY_EXAMPLE*` are generated. Once the models are ready, `python test/plot_example_galaxy.py` produces a multi-panel figure `test/SLUG_GALAXY_EXAMPLE_f1.pdf`.

The top-left panel shows the actual mass produced by SLUG for each of the 48 models at different time steps as a function of the targeted mass. One can see that SLUG realizations only approximate the desired mass, which is a consequence of SLUG core algorithm. The 1:1 relation is shown by a red dashed line. The remaining panels show examples of integrated photometry (as labeled) of all simulated galaxies at different time steps, as a function of the actual mass. Due to its stochastic nature, SLUG produces distributions rather than single values for each time step. The expected rate of ionizing photon and the bolometric luminosities for a deterministic model with a continuous star formation rate of $\text{SFR} = 0.001 M_{\odot} \text{ yr}^{-1}$ are shown by red dashed lines in the relevant panels.

14.2 Problem `example_cluster`: basic cluster simulation

This problem illustrates the basic usage of SLUG in `cluster` mode by running 1000 realizations of a cluster with mass $500 M_{\odot}$, up to a maximum time of 10 Myr. By issuing the command `test/run_example_cluster.sh` the output files `SLUG_CLUSTER_EXAMPLE*` are generated. Once the models are ready, `python test/plot_example_cluster.py` produces a multi-panel figure `test/SLUG_CLUSTER_EXAMPLE_f1.pdf`.

This figure is divided in two columns: the left one shows outputs at the first time step, 1 Myr, while the second one shows outputs at the last time step, 10 Myr. The top row shows the actual cluster mass for an input mass of $500 M_{\odot}$. In `cluster` mode, all clusters are generated at the first time step and they evolve passively after that. Thus, the mass does not change. As a consequence of the random drawing from the IMF, masses are distributed around the input mass. As the wanted mass is large enough to allow for many stars to be drawn, the actual mass distribution is narrow.

The second row shows instead the distribution of the maximum mass of all stars that are still alive at a given time step. At 1 Myr, this distribution is a good approximation of the input distribution, which is the result of random draws from the IMF. At 10 Myr, which is the typical lifetime of a $15\text{--}20 M_{\odot}$ star, the most massive stars have died, and SLUG stops following them. The distribution of luminosities, and particularly those most sensitive to the presence of massive stars, change accordingly (third and fourth row for Q_{H_0} and FUV).

14.3 Problem `constsampl`: importance of constrained sampling

This problem illustrates in more detail the effects of constrained sampling on SLUG simulations. This is the first key ingredient in the core algorithm of SLUG. With the command `test/run_constsampl.sh`, three different `cluster` simulations are run, each with 1000 trials, but with masses of $50 M_{\odot}$, $250 M_{\odot}$, and $500 M_{\odot}$. A single timestep of 10^6 yr is generated. The analysis script `python test/plot_constsampl.py` produces a multi-panel figure `test/SLUG_CONSTSAMPL_f1.pdf`.

This figure shows the maximum mass of the stars in these realizations (top row), the rate of ionizing photons Q_{H_0} (central row), and the FUV luminosity (bottom row). Histograms refer, from left to right, to clusters with $50 M_{\odot}$, $250 M_{\odot}$, and $500 M_{\odot}$.

Due to the small timestep, the distributions of stellar masses shown in the top panels reflect to good approximation the distribution of the maximum stellar masses that are drawn from the IMF by SLUG in each realization. For a cluster of $50 M_{\odot}$, the vast majority of the stars are drawn below $20\text{--}50 M_{\odot}$. This is an obvious consequence of the fact that a cluster cannot contain stars much more massive than its own mass. However, stars more massive than the targeted mass are not impossible realizations for the default sampling algorithm (see below). For instance, if the first star to be drawn has mass $60 M_{\odot}$, then SLUG would add it to the cluster and stop. Leaving this star out would indeed be a worse approximation than overshooting the targeted cluster mass by only $10 M_{\odot}$. From left to right, one can see that, as the targeted cluster mass increases, the histogram shifts to progressively higher masses. In the limit of an infinite cluster, all stellar masses would be represented, and the histogram would peak at $120 M_{\odot}$. Essentially, this constrained sampling introduces a stochastic (and not deterministic) variation in the IMF. An IMF truncated above $60 M_{\odot}$ would roughly approximate the results of the left column; however, a deterministic cut-off would not correctly reproduce the non-zero tail at higher masses, thus artificially reducing the scatter introduced by random sampling.

The second and third row simply reflect what said above: for large clusters that can host stars at all masses, the luminosity peaks around what is expected according to a deterministic stellar population synthesis codes. At lower cluster masses, ionizing and UV fluxes are instead suppressed, due to the lack of massive stars. However, tails to high values exist in all cases.

14.4 Problem `sampling`: different sampling techniques

As highlighted in the previous section, the method with which stars are sampled from the IMF has a great influence on the final output. Starting from v2, SLUG has the capability of specifying the desired sampling algorithm for a given PDF. The command `test/run_sampling.sh` runs four `cluster` simulations, each with 1000 trials of masses of $50 M_{\odot}$, and a Kroupa (2002) IMF. The following four sampling methods are chosen for each simulation: 1) `stop_nearest`, which is the default in SLUG; 2) `stop_before`; 3) `stop_after`; 4) `sorted_sampling`. A description of each method is provided in Section [Sampling Methods](#). The analysis script `python test/plot_sampling.py` produces a multi-panel figure `test/SLUG_SAMPLING_f1.pdf`.

By comparing the panels in each column, one can understand the fundamental differences induced by the sampling technique. The top row shows the maximum stellar mass drawn from the IMF in each realization. The targeted cluster mass is also shown with red vertical lines. In the default mode, SLUG is allowed to overshoot the targeted mass if that constitutes a good approximation for the total cluster mass. Thus, a tail at stellar masses above the targeted cluster mass is visible. This tail is accentuated when the stop after method is selected (third column). In this case, SLUG always overshoots the cluster mass, and thus extreme realizations above $100 M_{\odot}$ are possible. Conversely, in the stop after method (second column), SLUG always under-fills the clusters, and (in this case) the cluster mass becomes a limit to the maximum stellar mass that can be drawn. A similar effect is seen when sorted sampling is enable (fourth column). However, the correspondence between the cluster mass and the maximum stellar mass is not trivially established, as it depends on the shape of the IMF. The second and third row show how the sampling techniques affect the output photometry.

14.5 Problem `imfchoice`: different IMF implementations

This problem highlights how SLUG can handle different IMF implementations by running three simulations with a Kroupa, a Salpeter, and a Chabrier IMF. However, SLUG is not restricted to these choices, as the user can in fact easily input an arbitrary IMF. The command `test/run_imfchoice.sh` runs three `cluster` simulations, each with 1000 trials of masses of $500 M_{\odot}$ and different IMF. The analysis script `python test/plot_imfchoice.py` produces a multi-panel figure `test/SLUG_IMFCHOICE_f1.pdf`. Each column shows different statistics for the three IMF. From top to bottom, these are: the maximum stellar mass in a cluster, the number of stars that SLUG treats stochastically, and the distributions of Q_{H0} and bolometric luminosities. As expected for a steep lower-end of the IMF, in the Salpeter case SLUG prefers to fill the clusters with a higher number of low mass stars.

14.6 Problem `clfraction`: cluster fraction at work

With the exception of the first example, these test problems have focused on how SLUG handles cluster simulations, and how these clusters are filled with stars drawn from the IMF. This new problem highlights instead the presence of additional stochasticity induced by a second level in the hierarchy of `galaxy` simulations: how clusters are drawn from the CMF to satisfy the targeted galaxy mass. Although it may not appear obvious at first, the fraction of stars that are formed in clusters, f_c , is a very important parameter that regulates the stochastic behavior of SLUG. This can be understood by considering two limiting cases. In the limit $f_c \rightarrow 0$, SLUG fills a galaxy by drawing stars from the IMF. Thus, because the mass of a galaxy is typically much larger than the mass of the upper end of the IMF, the effects of mass-constrained sampling highlighted in *Problem constsample: importance of constrained sampling* are simply not relevant anymore. In this case, stochasticity is minimal. Conversely, in the limit $f_c \rightarrow 1$, not only the IMF sampling contributes to the stochastic behavior of SLUG, but also clusters themselves contribute to additional stochasticity, as clusters are now drawn from the CMF to fill the targeted galaxy mass following the similar rules to those specified for the IMF draws. Thus, in this case, constrained mass sampling applies to both stars in clusters and clusters in galaxies, and stochasticity is amplified.

The command `test/run_clfraction.sh` runs three `galaxy` simulations, each with 500 trials of continuous SFR = $0.001 M_{\odot} \text{ yr}^{-1}$ which are evolved for a single timestep of $2 \times 10^6 \text{ yr}$. A Chabrier IMF and a cluster mass function $\propto M^{-2}$ are adopted. Cluster disruption is disabled. The three simulations differ only for the fraction of stars formed in clusters, respectively $f_c = 1, 0.5, 0.01$. The analysis script `python test/plot_clfraction.py` produces a multi-panel figure `test/SLUG_CLFRACTION_f1.pdf`. Each column shows properties of simulations for different fractions of stars formed in clusters.

The top row shows the maximum stellar mass in clusters. Clearly, f_c has no effect on the way clusters are filled up with stars, but the normalization changes. Thus, the least probable realizations in the tail of the distribution simply do not appear for $f_c \rightarrow 0$. The second row shows the number of stars in clusters. Obviously, this scales directly with f_c , as it does the number of field stars in the third row. This is expected as, by definition, f_c regulates the number of stars in clusters versus the field. However, as discussed, f_c also affects the stochastic behavior of the simulation. The fourth row shows histograms of the actual galaxy mass versus the targeted mass (red line). As f_c increases, one can

see that the spread around the targeted mass increase. This is again a consequence of the mass-constrained sampling and the stop-nearest condition. For $f_c \rightarrow 0$, the code tries to fill a galaxy of mass $0.001 \text{ M}_\odot \text{ yr}^{-1} \times 2 \times 10^6 \text{ yr}$ with stars. Thus, since the targeted mass is at least a factor of 10 larger than the mass of the building block, SLUG can approximate the desired mass very well (to better than 120 M_\odot , in fact). Conversely, for $f_c \rightarrow 1$, SLUG is using clusters as building blocks. As the typical mass of the building blocks is now more comparable to the targeted galaxy mass, the problem of the mass constrained sampling becomes a relevant one. Not only f_c affects the precision with which SLUG builds galaxies, but, as shown in the bottom row, it also affects photometry. One can see that Q_{H_0} increases as f_c decreases (the red lines indicate medians). The reason for this behavior should now be clear: in the case of clustered star formation ($f_c \rightarrow 1$), the mass of the most massive stars is subject to the mass constrained sampling of the IMF at the cluster level, reducing the occurrence of very massive stars and thus suppressing the flux of ionizing radiation. Conversely, for non clustered star formation ($f_c \rightarrow 0$), the sampling of the IMF is constrained only at the galaxy mass level, and since this is typically much greater than the mass of the most massive stars, one recovers higher fluxes on average.

14.7 Problem `cmfchoice`: different CMF implementations

Given the ability of SLUG v2 to handle generic PDFs, the user can specify arbitrary CMF, similarly to what shown in [Problem `imfchoice`: different IMF implementations](#). The command `test/run_cmfchoice.sh` runs three galaxy simulations, each with 500 trials of continuous $\text{SFR} = 0.001 \text{ M}_\odot \text{ yr}^{-1}$ which are evolved for a single timestep of $2 \times 10^6 \text{ yr}$. A Chabrier IMF and $f_c = 1$ are adopted. Cluster disruption is disabled. The three simulations differ only for the cluster mass function, which are: 1) the default powerlaw M^{-2} between $20 - 10^7 \text{ M}_\odot$; 2) a truncated powerlaw M^{-2} between $20 - 100 \text{ M}_\odot$; 3) a mass-independent CMF M^0 between $20 - 10^3 \text{ M}_\odot$. The analysis script `python test/plot_cmfchoice.py` produces a multi-panel figure `test/SLUG_CMFCHOICE_f1.pdf`. Each column shows properties of simulations for the different cluster mass functions.

The top row shows the maximum stellar mass in clusters. Compared to the default case, the histogram of the truncated CMF is steeper towards low masses. Given that the upper end of the CMF is comparable to the maximum stellar mass of the chosen IMF, low stellar masses are typically preferred as a result of the stop-nearest condition. A flat CMF prefers instead more massive clusters on average, which in turn results in higher probabilities of drawing massive stars. In this case, the residual slope of the distribution towards low stellar masses is a result of the shape of the IMF. A reflection of the effects induced by the shape of the CMF are also apparent in the bottom row, which shows the distribution of ionizing photons from these simulations. The second row shows instead the difference between the targeted galaxy mass (red line), and the distribution of actual masses. The spread is minimal for the truncated CMF because, as discussed above, SLUG is using small building blocks, and it can approximate the targeted galaxy mass very well. Larger spread is visible in the case of the flat CMF, as this choice allows for clusters with masses up to 10^3 M_\odot , without imposing an excess of probability at the low mass end. The largest scatter is visible for the default case, as this CMF is virtually a pure powerlaw without cutoff at the high mass end, and thus clusters as massive as the entire galaxy are accessible to SLUG.

14.8 Problem `sfhsampling`: realizations of SFH

The algorithm at the heart of SLUG is quite simple: for a given star formation history $\dot{\psi}(t)$ a stellar population with mass $\dot{\psi}(t) \times \Delta t$ is generated at each timestep, according to the constraints set by IMF, CMF and other controlling parameters. As discussed in the previous examples, SLUG builds a best approximation for the targeted mass $\dot{\psi}(t) \times \Delta t$. This means that the input SFH and the output SFHs are not identical. SLUG receives an input SFH which is used to constrain the rate with which clusters and stars are drawn to achieve the desired targeted mass in each timestep. However, the output SFHs are only realizations and not exact copies of the input SFH. This problem is designed to illustrate this behavior.

The command `test/run_sfhsampling.sh` runs two galaxy simulations, each with 100 trials of continuous

$\text{SFR} = 0.0001 \text{ M}_\odot \text{ yr}^{-1}$ which are evolved for a 10 timesteps of $5 \times 10^6 \text{ yr}$. A Chabrier IMF and a M^{-2} CMF are adopted. Cluster disruption is disabled. The two simulations differ only for the fraction of stars in clusters, $f_c = 1$ and $f_c = 0$ respectively. The analysis script `python test/plot_sfhsampling.py` produces a two-panel figure `test/SLUG_SFHSAMPLING_f1.pdf`, showing the box plot for the output SFH of the two simulations ($f_c = 1$ top, and $f_c = 0$ bottom).

In each panel, the median SFH over 100 trials is represented by the red lines, while the red squares show the mean. The box sizes represent instead the first and third quartile, with the ends of the whiskers representing the 5th and 95th percentiles. One can see that the input SFH at $\dot{\psi}(t) = 10^{-4} \text{ M}_\odot \text{ yr}^{-1}$ is recovered on average, albeit with significant variation in each realization. The reason for this variation lies in the fact that, at low SFRs, SLUG samples the input SFH with coarse sampling points, which are clusters and stars. One can also notice a widely different scatter between the $f_c = 1$ and $f_c = 0$ case. In the former case, the basic elements used by SLUG to sample the targeted mass in a given interval are clusters. In the latter case, they are stars. Given that the typical mass of a cluster is of the same order of the targeted mass in each interval, the output SFH for the $f_c = 1$ case are more sensitive to the history of drawings from the CMF. Conversely, for $f_c = 0$, the sampling elements are less massive than the targeted mass in a given interval, resulting in an output SFH distribution which is better converged towards the input value. Clearly, a comparable amplitude in the scatter will be present in the output photometry, especially for the traces that are more sensitive to variations in the SFHs on short timescales.

14.9 Problem `cldisrupt`: cluster disruption at work

One additional ingredient in SLUG is the lifetime distribution for clusters. Since v2, SLUG is flexible in controlling the rate with which clusters are disrupted. This problem shows a comparison between two simulations with and without cluster disruption.

The command `test/run_cldisrup.sh` runs two galaxy simulations, each with 100 trials which are evolved in timesteps of $5 \times 10^5 \text{ yr}$ up to a maximum age of $1 \times 10^7 \text{ yr}$. Both simulations are characterized by a burst of star formation $= 0.001 \text{ M}_\odot \text{ yr}^{-1}$ within the first Myr. A Chabrier IMF and a M^{-2} CMF are adopted, and $f_c = 1$. For the first simulation, cluster disruption is disabled. In the second simulation, cluster disruption operates at times $> 1 \text{ Myr}$, with a cluster lifetime function which is a powerlaw of index -1.9. The analysis script `python test/plot_cldisrup.py` produces the figure `test/SLUG_CLDISRUP_f1.pdf`. The two columns show results with (right) and without (left) cluster disruption.

The first row shows the median stellar mass of the 100 trials as a function of time. The blue dashed lines show the mass inside the galaxy, while the black solid lines show the median mass in clusters. The red band shows the first and fourth quartile of the distribution. One can see that in both cases the galaxy mass rises in the first Myr up to the desired targeted mass of $= 1000 \text{ M}_\odot$ given the input SFH. After 1 Myr, star formation stops and the galaxy mass does not evolve with time. Conversely, the cluster mass (black line, red regions) evolves differently. In the case without cluster disruption, because $f_c = 1$, the cluster mass tracks the galaxy mass at all time. When cluster disruption is enabled (right), one can see that the mass in clusters rise following the galaxy mass in the first Myr. Past that time, clusters start being disrupted and the mass in clusters declines. The same behavior is visible in the second row, which shows the median number of alive (black) and disrupted (black) clusters. To the left, without cluster disruption, the number of clusters alive tracks the galaxy mass. Conversely, this distribution declines with time to the right when cluster disruption is enabled. The complementary quantity (number of disrupted clusters) rises accordingly. The last two rows show instead the integrated fluxes in FUV and bolometric luminosity. Again, medians are in black and the first and third quartiles in red. One can see a nearly identical distribution in the left and right panels. In these simulations, the controlling factors of the integrated photometry are the SFH and the sampling techniques, which do not depend on the cluster disruption rate. Clearly, the photometry of stars in cluster would exhibit instead a similar dependence to what shown in the top panels.

14.10 Problem spectra: full spectra

Since v2, SLUG is able to generate spectra for star clusters and for galaxies, which can also be computed for arbitrary redshifts. This problem highlights the new features. It also demonstrates how SLUG can handle dust extinction, both in a deterministic and stochastic way.

The command `test/run_spectra.sh` runs four galaxy simulations, each with 500 trials of continuous SFR $= 0.001 \text{ M}_{\odot} \text{ yr}^{-1}$ which are evolved for a single timestep of $2 \times 10^6 \text{ yr}$. A Chabrier IMF and a M^{-2} CMF are adopted, cluster disruption is disabled, and $f_c = 1$. The simulations differ in the following way: 1) the reference model, computed without extinction and at $z = 0$; 2) same as the reference model, but at $z = 3$; 3) same as the reference model at $z = 0$, but with a deterministic extinction of $A_V = 0.5$ and a Calzetti+2000 starburst attenuation curve; 4) same as model number 3, but with stochastic extinction. The analysis script `python test/plot_spectra.py` produces the figure `test/SLUG_SPECTRA_f1.pdf`, which shows a gallery of galaxy SEDs for each model. The median SED is shown in black, the blue region corresponds to the first and third quartile of the distribution, and the red shaded region marks the 5 and 95 percentiles.

The top panel shows the default model, where stochasticity occurs as detailed in the previous examples. The second panel from the top shows instead a model with deterministic extinction. This is simply a scaled-down version of the reference model, according to the input dust law and normalization coefficient A_V . As the dust law extends only to 915 Angstrom the output SED is truncated. The third panel shows that, once SLUG handles dust in a stochastic way, the intrinsic scatter is amplified. This is a simple consequence of applying dust extinction with varying normalizations, which enhances the final scatter about the median. Finally, the bottom panel shows the trivial case in which the spectrum is shifted in wavelength by a constant factor $(1 + z)$. Obviously, redshift enhances the stochasticity in the optical due to a simple shift of wavelengths.

CONTRIBUTORS AND ACKNOWLEDGEMENTS

The following people contributed to slug2:

- Mark Krumholz: primary author of slug2
- Michele Fumagalli: primary author of the slug2 test suite, co-author of version 1 of slug
- Robert da Silva: primary author of version 1 of slug and of sfr_slug, wrote the first prototype version of slug2 and sfr_slug
- Jonathan Parra: contributed code that become part of the slug_PDF module
- Teddy Rendahl: wrote the first version of cloudy_slug
- Michelle Myers: contributed to the development of cluster_slug

In addition to these direct contributors, we gratefully acknowledge the following people who provided some of the data on which slug relies:

- The library of stellar evolutionary tracks and stellar atmospheres is taken from Claus Leitherer's [starburst99](#) package.
- Much of the library of photometric filters is taken from Charlie Conroy's [FSPS](#) package.
- Daniela Calzetti provided the extinction curves

INDICES AND TABLES

- *genindex*
- *modindex*
- *search*

S

slugpy, [39](#)
slugpy.bayesphot.bp, [71](#)
slugpy.cloudy, [62](#)