

Name: Bencito, Sonny Jay	Date Performed: 9/17/2022
Course/Section: CPE31S24	Date Submitted: 9/17/2022
Instructor: Dr. Jonathan Taylar	Semester and SY: 1st sem 2022-2023
Activity 5: Consolidating Playbook plays	
1. Objectives: 1.1 Use when command in playbook for different OS distributions 1.2 Apply refactoring techniques in cleaning up the playbook codes	
2. Discussion: <p>We are going to look at a way that we can differentiate a playbook by a host in terms of which distribution the host is running. It's very common in most Linux shops to run multiple distributions, for example, Ubuntu shop or Debian shop and you need a different distribution for a one off-case or perhaps you want to run plays only on certain distributions.</p> <p>It is a best practice in ansible when you are working in a collaborative environment to use the command git pull. git pull is a Git command used to update the local version of a repository from a remote. By default, git pull does two things. Updates the current local working branch (currently checked out branch) and updates the remote-tracking branches for all other branches. git pull essentially pulls down any changes that may have happened since the last time you worked on the repository.</p> <p>Requirement: In this activity, you will need to create a CentOS VM. Likewise, you need to activate the second adapter to a host-only adapter after the installations. Take note of the IP address of the CentOS VM. Make sure to use the command ssh-copy-id to copy the public key to CentOS. Verify if you can successfully SSH to CentOS VM.</p>	
Task 1: Use when command for different distributions	
<ol style="list-style-type: none"> In the local machine, make sure you are in the local repository directory (CPE232_yourname). Issue the command git pull. When prompted, enter the correct passphrase or password. Describe what happened when you issue this command. Did something happen? Why? <u>only in your repository run the ansible command.</u> Edit the inventory file and add the IP address of the Centos VM. Issue the command we used to execute the playbook (the one we used in the last 	

activity): *ansible-playbook --ask-become-pass install_apache.yml*. After executing this command, you may notice that it did not become successful in the Centos VM. You can see that the Centos VM has failed=1. Only the two remote servers have been changed. The reason is that Centos VM does not support "apt" as the package manager. The default package manager for Centos is "yum."

3. Edit the *install_apache.yml* file and insert the lines shown below.


```
---
- hosts: all
  become: true
  tasks:

    - name: update repository index
      apt:
        update_cache: yes
        when: ansible_distribution == "Ubuntu"

    - name: install apache2 package
      apt:
        name: apache2
        when: ansible_distribution == "Ubuntu"

    - name: add PHP support for apache
      apt:
        name: libapache2-mod-php
        when: ansible_distribution == "Ubuntu"
```

Make sure to save the file and exit.



```
bencito@bencito-VirtualBox: ~/CPE232_Bencito
GNU nano 6.2      install_apache.yml *
---
- hosts: all
  become: true
  tasks:

    - name: update repository index
      apt:
        update_cache: yes
        when: ansible_distribution == "Ubuntu"

    - name: install apache2 package
      apt:
        name: apache2
        state: latest

    - name: add PHP support for apache
      apt:
        name: libapache2-mod-php
        state: latest
        when: ansible_distribution == "Ubuntu"

Save modified buffer? [Y] Yes
N No      AC Cancel
```

Run *ansible-playbook --ask-become-pass install_apache.yml* and describe the result.

```
bencito@bencito-VirtualBox:~/CPE232_Bencito$ ansible-playbook --ask-become-pass
install_apache.yml
BECOME password:

PLAY [all] *****
*

TASK [Gathering Facts] *****
*
fatal: [192.168.56.103]: UNREACHABLE! => {"changed": false, "msg": "Failed to c
onnect to the host via ssh: no such identity: /home/bencito/.ssh/ansible: No su
ch file or directory\r\nbencito@192.168.56.103: Permission denied (publickey,pa
ssword).", "unreachable": true}
ok: [192.168.56.102]
ok: [192.168.56.104]

TASK [update repository index] *****
*
skipping: [192.168.56.102]
changed: [192.168.56.104]

TASK [install apache2 package] *****
*
skipping: [192.168.56.102]
changed: [192.168.56.104]

TASK [add PHP support for apache] *****
*
skipping: [192.168.56.102]
```

```
TASK [update repository index] *****
*
skipping: [192.168.56.102]
changed: [192.168.56.104]

TASK [install apache2 package] *****
*
skipping: [192.168.56.102]
changed: [192.168.56.104]

TASK [add PHP support for apache] *****
*
skipping: [192.168.56.102]
changed: [192.168.56.104]
```

```
PLAY RECAP *****
*
192.168.56.102      : ok=1    changed=0    unreachable=0    failed=0
skipped=3    rescued=0    ignored=0
192.168.56.103      : ok=0    changed=0    unreachable=1    failed=0
skipped=0    rescued=0    ignored=0
192.168.56.104      : ok=4    changed=3    unreachable=0    failed=0
skipped=0    rescued=0    ignored=0
```

```
bencito@bencito-VirtualBox:~/CPE232_Bencito$
```

If you have a mix of Debian and Ubuntu servers, you can change the configuration of your playbook like this.

The cent os was skip because it is not called in the repository you need to edit it and called the cent os.

- name: update repository index
apt:
 update_cache: yes
 when: ansible_distribution in ["Debian", "Ubuntu"]

Note: This will work also if you try. Notice the changes are highlighted.

4. Edit the *install_apache.yml* file and insert the lines shown below.

```
---  
- hosts: all  
  become: true  
  tasks:  
  
    - name: update repository index  
      apt:  
        update_cache: yes  
        when: ansible_distribution == "Ubuntu"  
  
    - name: install apache2 package  
      apt:  
        name: apache2  
        state: latest  
        when: ansible_distribution == "Ubuntu"  
  
    - name: add PHP support for apache  
      apt:  
        name: libapache2-mod-php  
        state: latest  
        when: ansible_distribution == "Ubuntu"  
  
    - name: update repository index  
      dnf:  
        update_cache: yes  
        when: ansible_distribution == "CentOS"  
  
    - name: install apache2 package  
      dnf:  
        name: httpd  
        state: latest  
        when: ansible_distribution == "CentOS"  
  
    - name: add PHP support for apache  
      dnf:  
        name: php  
        state: latest  
        when: ansible_distribution == "CentOS"
```

Make sure to save and exit.

```
bencito@bencito-VirtualBox: ~/CPE232_Bencito
GNU nano 6.2      install_apache.yml *
```

```
---
- hosts: all
  become: true
  tasks:

    - name: update repository index
      apt:
        update_cache: yes
      when: ansible_distribution == "Ubuntu"

    - name: install apache2 package
      apt:
        name: apache2
        state: latest
      when: ansible_distribution == "Ubuntu"

    - name: add php support for apache
      apt:
        name: libapache2-mod-php
        state: latest
      when: ansible_distribution == "Ubuntu"

    - name: update repository index
```

^G Help ^O Write Out ^W Where Is ^K Cut ^T Execute
^X Exit ^R Read File ^\ Replace ^U Paste ^J Justify

```
GNU nano 6.2      install_apache.yml *
```

```
- name: add php support for apache
  apt:
    name: libapache2-mod-php
    state: latest
  when: ansible_distribution == "Ubuntu"

- name: update repository index
  dnf:
    update_cache: yes
  when: ansible_distribution == "CentOS"

- name: install httpd package
  dnf:
    name: httpd
    state: latest
  when: ansible_distribution == "CentOS"

- name: add php support for apache
  dnf:
    name: php
    state: latest
  when: ansible_distribution == "CentOS"
```

^G Help ^O Write Out ^W Where Is ^K Cut ^T Execute
^X Exit ^R Read File ^\ Replace ^U Paste ^J Justify

Run *ansible-playbook --ask-become-pass install_apache.yml* and describe the result.

Now, the cent os was read because I added it on my nano script and into my repository.

```
bencito@bencito-VirtualBox:~/CPE232_Bencito$ ansible-playbook --ask-become-pass
install_apache.yml
BECOME password:

PLAY [all] *****
*

TASK [Gathering Facts] *****
*
fatal: [192.168.56.103]: UNREACHABLE! => {"changed": false, "msg": "Failed to c
onnect to the host via ssh: no such identity: /home/bencito/.ssh/ansible: No su
ch file or directory\r\nbencito@192.168.56.103: Permission denied (publickey,pa
ssword).", "unreachable": true}
ok: [192.168.56.102]
ok: [192.168.56.104]

TASK [update repository index] *****
*
skipping: [192.168.56.102]
changed: [192.168.56.104]

TASK [install apache2 package] *****
*
skipping: [192.168.56.102]
ok: [192.168.56.104]
```

```
bencito@bencito-VirtualBox: ~/CPE232_Bencito
*
skipping: [192.168.56.102]
ok: [192.168.56.104]

TASK [update repository index] *****
*
skipping: [192.168.56.104]
ok: [192.168.56.102]

TASK [install httpd package] *****
*
skipping: [192.168.56.104]
changed: [192.168.56.102]

TASK [add php support for apache] *****
*
skipping: [192.168.56.104]
changed: [192.168.56.102]

PLAY RECAP *****
*
192.168.56.102      : ok=4    changed=2    unreachable=0    failed=0
skipped=3    rescued=0    ignored=0
192.168.56.103      : ok=0    changed=0    unreachable=1    failed=0
skipped=0    rescued=0    ignored=0
192.168.56.104      : ok=4    changed=1    unreachable=0    failed=0
skipped=3    rescued=0    ignored=0
bencito@bencito-VirtualBox:~/CPE232_Bencito$
```

5. To verify the installations, go to CentOS VM and type its IP address on the browser. Was it successful? The answer is no. It's because the httpd service or the Apache HTTP server in CentOS is not yet active. Thus, you need to activate it first.

5.1 To activate, go to the CentOS VM terminal and enter the following:

systemctl status httpd

The result of this command tells you that the service is inactive.

```
[bencito@localhost ~]$ systemctl status httpd
● httpd.service - The Apache HTTP Server
   Loaded: loaded (/usr/lib/systemd/system/httpd.service; disabled; vendor preset: disabled)
   Active: inactive (dead)
     Docs: man:httpd(8)
          man:apachectl(8)
[bencito@localhost ~]$
```

5.2 Issue the following command to start the service:

sudo systemctl start httpd

(When prompted, enter the sudo password)


sudo firewall-cmd --add-port=80/tcp

(The result should be a success)

```
[bencito@localhost ~]$ sudo systemctl start httpd
[sudo] password for bencito:
[bencito@localhost ~]$ sudo firewall-cmd -add-port=80/tcp
usage: see firewall-cmd man page
firewall-cmd: error: unrecognized arguments: -add-port=80/tcp
[bencito@localhost ~]$ sudo firewall-cmd --add-port=80/tcp
success
[bencito@localhost ~]$ █
```

5.3 To verify the service is already running, go to CentOS VM and type its IP address on the browser. Was it successful? (Screenshot the browser)

yes, it was successful.



Task 2: Refactoring playbook

This time, we want to make sure that our playbook is efficient and that the codes are easier to read. This will also makes run ansible more quickly if it has to execute fewer tasks to do the same thing.

1. Edit the playbook *install_apache.yml*. Currently, we have three tasks targeting our Ubuntu machines and 3 tasks targeting our CentOS machine. Right now, we try to consolidate some tasks that are typically the same. For example, we

can consolidate two plays that install packages. We can do that by creating a list of installation packages as shown below:

```
---
- hosts: all
  become: true
  tasks:

    - name: update repository index Ubuntu
      apt:
        update_cache: yes
        when: ansible_distribution == "Ubuntu"

    - name: install apache2 and php packages for Ubuntu
      apt:
        name:
          - apache2
          - libapache2-mod-php
        state: latest
        when: ansible_distribution == "Ubuntu"

    - name: update repository index for CentOS
      dnf:
        update_cache: yes
        when: ansible_distribution == "CentOS"

    - name: install apache and php packages for CentOS
      dnf:
        name:
          - httpd
          - php
        state: latest
        when: ansible_distribution == "CentOS"
```

Make sure to save the file and exit.

```
bencito@bencito-VirtualBox: ~/CPE232_Bencito
GNU nano 6.2      install_apache.yml *
```

```
---
- hosts: all
  become: true
  tasks:

    - name: update repository index
      apt:
        update_cache: yes
      when: ansible_distribution == "Ubuntu"

    - name: install apache2 and php packages for Ubuntu
      apt:
        name:
          - apache2
          - libapache2-mod-php
        state: latest
      when: ansible_distribution == "Ubuntu"

    - name: update repository index
      dnf:
        update_cache: yes
      when: ansible_distribution == "CentOS"

    - name: install apache and php packages for CentOS
```

^G Help ^O Write Out ^W Where Is ^K Cut ^T Execute
^X Exit ^R Read File ^_ Replace ^U Paste ^J Justify

```
bencito@bencito-VirtualBox: ~/CPE232_Bencito
GNU nano 6.2      install_apache.yml *
```

```
apt:
  update_cache: yes
  when: ansible_distribution == "Ubuntu"

- name: install apache2 and php packages for Ubuntu
  apt:
    name:
      - apache2
      - libapache2-mod-php
    state: latest
  when: ansible_distribution == "Ubuntu"

- name: update repository index
  dnf:
    update_cache: yes
  when: ansible_distribution == "CentOS"

- name: install apache and php packages for CentOS
  dnf:
    name:
      - httpd
      - php
    state: latest
  when: ansible_distribution == "CentOS"
```

^G Help ^O Write Out ^W Where Is ^K Cut ^T Execute
^X Exit ^R Read File ^_ Replace ^U Paste ^J Justify

Run *ansible-playbook --ask-become-pass install_apache.yml* and describe the result.

```

bencito@bencito-VirtualBox:~/CPE232_Bencito$ nano install_apache.yml
bencito@bencito-VirtualBox:~/CPE232_Bencito$ ansible-playbook --ask-become-pass
install_apache.yml
BECOME password:

PLAY [all] *****
*

TASK [Gathering Facts] *****
*
fatal: [192.168.56.103]: UNREACHABLE! => {"changed": false, "msg": "Failed to c
onnect to the host via ssh: no such identity: /home/bencito/.ssh/ansible: No su
ch file or directory\r\nbencito@192.168.56.103: Permission denied (publickey,pa
ssword).", "unreachable": true}
ok: [192.168.56.104]
ok: [192.168.56.102]

TASK [update repository index] *****
*
skipping: [192.168.56.102]
changed: [192.168.56.104]

TASK [install apache2 and php packages for Ubuntu] *****
*
skipping: [192.168.56.102]
ok: [192.168.56.104]

TASK [update repository index] *****
*

```

```

bencito@bencito-VirtualBox: ~/CPE232_Bencito
*
skipping: [192.168.56.102]
changed: [192.168.56.104]

TASK [install apache2 and php packages for Ubuntu] *****
*
skipping: [192.168.56.102]
ok: [192.168.56.104]

TASK [update repository index] *****
*
skipping: [192.168.56.104]
ok: [192.168.56.102]

TASK [install apache and php packages for CentOS] *****
*
skipping: [192.168.56.104]
ok: [192.168.56.102]

PLAY RECAP *****
*
192.168.56.102      : ok=3    changed=0    unreachable=0    failed=0
skipped=2    rescued=0    ignored=0
192.168.56.103      : ok=0    changed=0    unreachable=1    failed=0
skipped=0    rescued=0    ignored=0
192.168.56.104      : ok=3    changed=1    unreachable=0    failed=0
skipped=2    rescued=0    ignored=0
bencito@bencito-VirtualBox:~/CPE232_Bencito$

```

2. Edit the playbook *install_apache.yml* again. In task 2.1, we consolidated the plays into one play. This time we can actually consolidated everything in just 2 plays. This can be done by removing the update repository play and putting the


command *update_cache: yes* below the command *state: latest*. See below for reference:

```
---
- hosts: all
  become: true
  tasks:

    - name: install apache2 and php packages for Ubuntu
      apt:
        name:
          - apache2
          - libapache2-mod-php
        state: latest
        update_cache: yes
      when: ansible_distribution == "Ubuntu"

    - name: install apache and php packages for CentOS
      dnf:
        name:
          - httpd
          - php
        state: latest
        update_cache: yes
      when: ansible_distribution == "CentOS"
```

Make sure to save the file and exit.



```
bencito@bencito-VirtualBox: ~/CPE232_Bencito
GNU nano 6.2      install_apache.yml *
---
- hosts: all
  become: true
  tasks:
    - name: install apache2 and php packages for Ubuntu
      apt:
        name:
          - apache2
          - libapache2-mod-php
        state: latest
        update_cache: yes
      when: ansible_distribution == "Ubuntu"
    - name: install apache and php packages for CentOS
      dnf:
        name:
          - httpd
          - php
        state: latest
        update_cache: yes
      when: ansible_distribution == "CentOS"
Save modified buffer? [Y] Yes
N No      ^C Cancel
```

Run *ansible-playbook --ask-become-pass install_apache.yml* and describe the result.

```
bencito@bencito-VirtualBox: ~/CPE232_Bencito
192.168.56.102      : ok=3    changed=0    unreachable=0    failed=0
skipped=2    rescued=0    ignored=0
192.168.56.103      : ok=0    changed=0    unreachable=1    failed=0
skipped=0    rescued=0    ignored=0
192.168.56.104      : ok=3    changed=1    unreachable=0    failed=0
skipped=2    rescued=0    ignored=0

bencito@bencito-VirtualBox:~/CPE232_Bencito$ nano install_apache.yml
bencito@bencito-VirtualBox:~/CPE232_Bencito$ ansible-playbook --ask-become-pass
install_apache.yml
BECOME password:

PLAY [all] *****
*

TASK [Gathering Facts] *****
*
fatal: [192.168.56.103]: UNREACHABLE! => {"changed": false, "msg": "Failed to c
onnect to the host via ssh: no such identity: /home/bencito/.ssh/ansible: No su
ch file or directory\r\nbencito@192.168.56.103: Permission denied (publickey,pa
ssword).", "unreachable": true}
ok: [192.168.56.104]
ok: [192.168.56.102]

TASK [install apache2 and php packages for Ubuntu] *****
*
skipping: [192.168.56.102]
ok: [192.168.56.104]
```

```
TASK [Gathering Facts] *****
*
fatal: [192.168.56.103]: UNREACHABLE! => {"changed": false, "msg": "Failed to c
onnect to the host via ssh: no such identity: /home/bencito/.ssh/ansible: No su
ch file or directory\r\nbencito@192.168.56.103: Permission denied (publickey,pa
ssword).", "unreachable": true}
ok: [192.168.56.104]
ok: [192.168.56.102]

TASK [install apache2 and php packages for Ubuntu] *****
*
skipping: [192.168.56.102]
ok: [192.168.56.104]

TASK [install apache and php packages for CentOS] *****
*
skipping: [192.168.56.104]
ok: [192.168.56.102]

PLAY RECAP *****
*
192.168.56.102      : ok=2    changed=0    unreachable=0    failed=0
skipped=1    rescued=0    ignored=0
192.168.56.103      : ok=0    changed=0    unreachable=1    failed=0
skipped=0    rescued=0    ignored=0
192.168.56.104      : ok=2    changed=0    unreachable=0    failed=0
skipped=1    rescued=0    ignored=0

bencito@bencito-VirtualBox:~/CPE232_Bencito$
```


The result is still the same nothing changed.

3. Finally, we can consolidate these 2 plays in just 1 play. This can be done by declaring variables that will represent the packages that we want to install.

Basically, the `apache_package` and `php_package` are variables. The names are arbitrary, which means we can choose different names. We also take out the line when: `ansible_distribution`. Edit the playbook `install_apache.yml` again and make sure to follow the below image. Make sure to save the file and exit.

```
---
- hosts: all
  become: true
  tasks:

    - name: install apache and php
      apt:
        name:
          - "{{ apache_package }}"
          - "{{ php_package }}"
        state: latest
        update_cache: yes
```



```
bencito@bencito-VirtualBox: ~/CPE232_Bencito
GNU nano 6.2                                install_apache.yml *
---
- hosts: all
  become: true
  tasks:

    - name: install apache and php
      apt:
        name:
          - "{{ apache_package }}"
          - "{{ php_package }}"
        state: latest
        update_cache: yes
```

Run *ansible-playbook --ask-become-pass install_apache.yml* and describe the result.

```
TASK [Gathering Facts] *****
*
fatal: [192.168.56.103]: UNREACHABLE! => {"changed": false, "msg": "Failed to connect to the host via ssh: no such identity: /home/bencito/.ssh/ansible: No such file or directory\r\nbencito@192.168.56.103: Permission denied (publickey,password).", "unreachable": true}
ok: [192.168.56.104]
ok: [192.168.56.102]

TASK [install apache and php] *****
*
[WARNING]: Updating cache and auto-installing missing dependency: python-apt
fatal: [192.168.56.102]: FAILED! => {"changed": false, "cmd": "apt-get update", "msg": "[Errno 2] No such file or directory", "rc": 2}
ok: [192.168.56.104]

PLAY RECAP *****
*
192.168.56.102      : ok=1    changed=0    unreachable=0    failed=1
skipped=0    rescued=0    ignored=0
192.168.56.103      : ok=0    changed=0    unreachable=1    failed=0
skipped=0    rescued=0    ignored=0
192.168.56.104      : ok=2    changed=0    unreachable=0    failed=0
skipped=0    rescued=0    ignored=0

bencito@bencito-VirtualBox: ~/CPE232_Bencito$
```

The result was not successful. because I need to change the inventory first and the cent os was not read.

4. Unfortunately, task 2.3 was not successful. It's because we need to change something in the inventory file so that the variables we declared will be in place. Edit the *inventory* file and follow the below configuration:

```
192.168.56.120 apache_package=apache2 php_package=libapache2-mod-php
192.168.56.121 apache_package=apache2 php_package=libapache2-mod-php
192.168.56.122 apache_package=httpd php_package=php
```

Make sure to save the *inventory* file and exit.

```
bencito@bencito-VirtualBox: ~/CPE232_Bencito
GNU nano 6.2 inventory *
192.168.56.103 apache_package=apache2 php_package=libapache2-mod-php
192.168.56.104 apache_package=apache2 php_package=libapache2-mod-php
192.168.56.102 apache_package=httpd php_package=php
```

Finally, we still have one more thing to change in our *install_apache.yml* file. In task 2.3, you may notice that the package is assign as *apt*, which will not run in CentOS. Replace the *apt* with *package*. Package is a module in ansible that is generic, which is going to use whatever package manager the underlying host or the target server uses. For Ubuntu it will automatically use *apt*, and for

CentOS it will automatically use *dnf*. Make sure to save the file and exit. For more details about the ansible package, you may refer to this documentation: [ansible.builtin.package – Generic OS package manager — Ansible Documentation](#)

```
GNU nano 6.2                                install_apache.yml *
```

```
---

- hosts: all
  become: true
  tasks:

    - name: install apache and php
      package:
        name:
          - "{{ apache_package }}"
          - "{{ php_package }}"
        state: latest
        update_cache: yes
```

Run *ansible-playbook --ask-become-pass install_apache.yml* and describe the result.

```
BECOME password:

PLAY [all] *****
*

TASK [Gathering Facts] *****
*
fatal: [192.168.56.103]: UNREACHABLE! => {"changed": false, "msg": "Failed to connect to the host via ssh: no such identity: /home/bencito/.ssh/ansible: No such file or directory\r\nbencito@192.168.56.103: Permission denied (publickey,password).", "unreachable": true}
ok: [192.168.56.104]
ok: [192.168.56.102]

TASK [install apache and php] *****
*
ok: [192.168.56.104]
ok: [192.168.56.102]

PLAY RECAP *****
*
192.168.56.102      : ok=2    changed=0    unreachable=0    failed=0
skipped=0    rescued=0    ignored=0
192.168.56.103      : ok=0    changed=0    unreachable=1    failed=0
skipped=0    rescued=0    ignored=0
192.168.56.104      : ok=2    changed=0    unreachable=0    failed=0
skipped=0    rescued=0    ignored=0

bencito@bencito-VirtualBox:~/CPE232_Bencito$
```

It was successful, because I changed the dnf and apt into package to read the CentOS.

Supplementary Activity:

1. Create a playbook that could do the previous tasks in Red Hat OS.

Reflections:

Answer the following:

1. Why do you think refactoring of playbook codes is important?

It is important. because when you refactor the playbook. It will allow you to write programs faster. Ultimately, it all comes down to one thing: refactoring helps speed up the development of a code and to read those servers that you added.

2. When do we use the “when” command in playbook?

We use the “when” command when you run the task on all hosts. For example , when all the server was on the firewall it would run the given package on that server.