

Furnish Hope — Codebase Summary

[What it is](#)
[By the numbers](#)
[Stack](#)
[Architecture](#)
[Auth + permissions](#)
[Feature domains \(12 themes from the ERD\)](#)
[Third-party integrations \(live\)](#)
[Repo layout](#)
[Generic admin layer](#)
[Operational features built on top of the admin layer](#)
[Tooling & dev workflow](#)
[What's notable about the design](#)
[How this PDF is maintained](#)

Furnish Hope — Codebase Summary

Last regenerated: 2026-06-23

What it is

An internal operations platform for a Central Oregon nonprofit that pairs donated furniture with families transitioning into housing. Covers the full lifecycle: donor intake → pickups → inventory → client referrals → matching → delivery, plus fundraising (campaigns, events, pledges, donations → QuickBooks), volunteer management, email, and an in-app issue tracker.

Built specifically for a **non-technical primary user** (a nonprofit's database admin) — every operational page has a friendly UI, but every table is also editable through a generic admin form for power use.

By the numbers

Metric	Count
TypeScript LOC (api + web)	~52,300
Schema migrations	89
Database tables (tbl_* + lkp_*)	77 + 65 = 142
Foreign keys	220
API route files	38
API endpoints	222
Frontend pages	81
Commits on main	120
Production bundle size	~1.9 MB JS, 506 KB gzipped

Stack

Back end (/api)

- **Node 22.x** (pinned in engines) — TypeScript 5.5
- **Express 4** — single service that serves both the REST API and the built React bundle in production
- **PostgreSQL 16/17** via pg (node-postgres) with a custom `withTransaction` helper
- **express-session + connect-pg-simple** — session store in the same Postgres DB
- **bcrypt** for password hashing
- **express-rate-limit + helmet** — login throttling + standard security headers
- **AES-256-GCM** (via Node crypto) — encryption at rest for OAuth tokens + IMAP/SMTP passwords

- **Idempotent startup migrations** — `api/src/auth/migrations.ts` runs every migration in order on every boot; safe to re-run

Front end (/web)

- **React 18 + TypeScript + Vite 5** (build + dev server)
- **React Router 6** — three “shells”: staff (main app), agency caseworker portal, public volunteer signup
- **Tailwind CSS** + custom design tokens (terracotta / sage / gold / paper palette + serif display font + sans-serif body)
- **TanStack React Query** — every server interaction is a query/mutation with optimistic invalidation
- **FullCalendar** (6 packages) for the unified ops calendar (pickups, deliveries, visits, events, shifts, vendor services)
- **Recharts** for the 16-chart Reports page
- **html2canvas** — captures the visible DOM as PNG for in-app issue reports
- **qrcode** — generates QR codes for printable manifests (driver directions)


Database (/db)

- `01_schema.sql` — initial schema
- `02_seed.sql` — realistic-looking sample data (donors, clients, etc.) for local dev
- `03_wipe_demo.sql` — CASCADE TRUNCATE for production launch day
- ERD generator at `scripts/generate_erd_pdf.py` (Python + Graphviz + pypdf) → `docs/FurnishHopeERD.pdf`

Deployment

- **DigitalOcean App Platform** (Node web service) + **Managed Postgres** dev tier
- `.do/app.yaml` describes the deploy as code
- Auto-deploys on every `git push` to main
- `app.set('trust proxy', 1)` in production; sessions become Secure cookies
- Health check at `GET /api/health`
- ~\$20/month total (~\$5 App + ~\$15 PG)

Architecture



Three shells served by the same app:

1. `/login, /*` — staff app (default)
2. `/agency/*` — partner-agency caseworker portal (no internal data visible)
3. `/volunteer, /volunteer-agreement` — public (unauthenticated) signup

Auth + permissions

Three role tiers enforced by middleware on every route:

Middleware	What
requireUser	Session must be authenticated
requireStaff	Excludes agency users (role === 'agency')
requireAdmin	is_admin = true
requireDeveloper	is_admin = true AND is_developer = true

Plus row-level scoping for agency caseworkers (they only see their own org's referrals) and per-user scoping for email accounts and mailbox (you only see your own mail).

Audit log records every mutation (tbl_audit_log) with field-level diffs. Sensitive fields (passwords, OAuth tokens, encrypted IMAP creds, screenshot blobs, lock codes, DOB, tax IDs) are masked to ***.

Feature domains (12 themes from the ERD)

1. **Contacts & Addresses** — shared people + place rows; address dedupe + shared-edit confirmation modal
2. **Clients & Households** — referral → intake → provisioning request → visit → waiver → delivery. Households can be multi-type (Veteran + Disaster + ...) via tbl_client_client_type. Multiple agencies can refer the same client; staff see the full referral history per client. Client-dedup search (“do you mean...?”) surfaces likely matches before a new client is created, scoped per-agency in the partner portal. Agency-submitted requests land in a staff **review queue** with Approve / Edit / Reject actions before joining the matching pipeline. Fulfillment methods: home / walkout / container pickup.
3. **Donors, Donations & QuickBooks** — gifts, designations, pledges, full QBO sync (donations → Sales Receipts), 6 QBO tables for OAuth + mappings + sync log
4. **Inventory & Storage** — items, reservations, container/lockbox flagging
5. **Facilities & Vehicles** — corporate sites, vehicle fleet + maintenance log
6. **Staff, Volunteers & Shifts** — public signup queue, approval flow, profile prefs (availability / activity / physical), shift templates + generated shifts, preference-aware shift signup picker
7. **Fundraising** — campaigns, events with attendees + sponsors, grants
8. **Vendors** — outside service providers + service log
9. **Partner Agencies** — agency contacts referring households
10. **Communications, Files & Notes** — per-user email accounts (IMAP/SMTP), Mailbox view, email templates, generic per-entity attachments
11. **System** — user accounts, audit log, app settings, in-app issue tracker, broadcast banner, org branding, user-manual screenshots

Third-party integrations (live)

Integration	What it does	Env vars
QuickBooks Online	Pushes donations → Sales Receipts with donor + fund mapping. OAuth refresh, sync history.	QBO_CLIENT_ID, QBO_CLIENT_SECRET, QBO_REDIRECT_URI, QBO_ENVIRONMENT
IMAP/SMTP (Gmail, iCloud, Outlook, Yahoo, ProtonMail Bridge, custom)	Per-user inbox + send. Preset wizard with provider host/port pre-fill.	(per-user; stored encrypted in DB)
Google + Microsoft OAuth	Sign-in-with-Google / Sign-in-with-Microsoft for email accounts.	GOOGLE_OAUTH_*, MICROSOFT_OAUTH_*

Not integrated (documented in docs/INTEGRATIONS.md): Google Calendar, S3/Spaces, Twilio/SMS, on-platform payments.

Repo layout

furnish-hope/	
├─ api/	<- Node + Express + TypeScript
│ └─ src/	
│ └─ routes/	<- 38 files, 216 endpoints
│ └─ auth/	<- migrations, audit, session, middleware
│ └─ admin/	<- metadata-driven generic admin (introspect.ts)
│ └─ email/	<- IMAP sync, OAuth, crypto
│ └─ quickbooks/	<- OAuth + sync engine
│ └─ storage/	<- pluggable attachment storage (pg_blob today)
│ └─ db/pool.ts	<- pg pool + withTransaction
├─ web/	<- React + Vite + TypeScript + Tailwind
│ └─ src/	
│ └─ pages/	<- 80 pages across staff / agency / dev / admin /
├─ help	
│ └─ components/	<- Sidebar, error boundary, issue reporter,
│ │	broadcast banner, FK select with create, etc.
│ └─ lib/	<- API client, auth context, admin metadata
│ └─ hooks/	
├─ db/	<- initial schema + seed + wipe + ERD generator
├─ docs/	<- 16 markdown docs (setup, integrations, ERD
├─ regen)	
│	+ ERD PDF + user manual sources
├─ scripts/	<- Python generators (ERD, codebase summary,
├─ import templates)	
├─ .do/app.yaml	<- DigitalOcean deployment spec
└─ DEPLOY.md	

Generic admin layer

The notable architectural piece. Every table can be edited at `/admin/<table>` through one metadata-driven form:

- `api/src/admin/introspect.ts` reads `information_schema` at startup to build a `SchemaMap` of every table, column, PK, FK, default, and nullability.
- `api/src/admin/config.ts` layers manual UX overrides (friendly labels, sidebar groups, enum value hints for CHECK-constrained VARCHARs, hide-in-form/ hide-in-list flags).
- `web/src/pages/admin/AdminForm.tsx` renders any table's form by walking the metadata — FK fields become searchable dropdowns, enum VARCHARs become `<select>`s, columns with SQL defaults get omitted from INSERT when the user leaves them blank, etc.

That's how all 140 tables get an editor without 140 hand-written forms.

Operational features built on top of the admin layer

- **Per-entity widgets:** Email widget (your mail with this donor/client), Attachments widget (per-entity files), and Notes widget all attach to any detail page via (`entity_type`, `entity_id`).
 - **Quick-create modals:** from any FK dropdown, “+ New ...” inline-creates the referenced row (Donor, Address, Vehicle, Contact, Facility, Staff, Pledge, Campaign).
 - **In-app User Manual** at `/help` with sticky TOC, anchor-aware Help buttons on every page header, retry-loop scroll for late-loading content, single-tab reuse.
 - **Issue reporter:** admin-only “Report issue” button captures a screenshot via `html2canvas`, posts to `/api/issues`. Developer console at `/dev/issues` triages with status workflow + broadcast banners.
 - **ERD PDF:** 12 themed pages, regenerated via `python scripts/generate_erd_pdf.py`, served from `/api/admin/erd`.
-

Tooling & dev workflow

- **Local dev:** two terminals — `api/ npm run dev (tsx watch on :4000) + web/ npm run dev (Vite on :5173)`

- **TypeScript** — `npx tsc --noEmit` for both; build verified via `vite build`
 - **No test suite** — verification is via `tsc + vite build + manual smoke tests + the in-app issue tracker`
 - **Deploy**: `git push origin main` → DigitalOcean rebuilds in 3–5 min → live at `hammerhead-app-tk838.ondigitalocean.app` (current dev URL)
 - **Docs**: 16+ markdown files under `docs/` cover setup (DO + Windows + Mac), integrations (QBO + email), ERD regen, user manual, OAuth setup, agency onboarding, third-party TODO list
-

What’s notable about the design

- **No ORM** — direct parameterized SQL throughout. Schema is the source of truth.
 - **No tests** — coverage is from runtime checks (CHECK constraints, FK constraints, audit log) plus `tsc + smoke tests + an in-app issue reporter` for what slips through.
 - **Idempotent migrations** — every migration is wrapped to skip if the change is already present. Every startup re-runs them; the system self-heals.
 - **Email is per-user, not shared** — every staff member connects their own inbox. No shared mailbox.
 - **One generic admin form** handles every table; operational forms (Clients, Donors, Visits, etc.) provide a friendly UI for the most-used tables.
 - **Three shells** under one Express service share auth + session storage; deploy is a single artifact.
-

How this PDF is maintained

This file’s source is `docs/CODEBASE_SUMMARY.md` and the rendered PDF lives at `docs/CodebaseSummary.pdf`. To regenerate after the codebase changes:

```
cd C:\Users\prest\furnish-hope
python scripts\generate_codebase_summary_pdf.py
git add docs\CODEBASE_SUMMARY.md docs\CodebaseSummary.pdf
git commit -m "docs: refresh codebase summary"
git push
```

The Python script reads the markdown source, runs the stat-collection queries above, refreshes the “By the numbers” table inline, then renders to PDF via Pandoc.