

[Dashboard](#) / [My courses](#) / [PSPP/PUP](#) / [Searching techniques: Linear and Binary](#) / [Week10 Coding](#)

Started on Wednesday, 19 June 2024, 9:44 PM

State Finished

Completed on Wednesday, 19 June 2024, 9:55 PM

Time taken 11 mins 48 secs

Marks 0.00/5.00

Grade **0.00** out of 100.00

Question **1**

Not answered

Mark 0.00 out of 1.00

Bubble Sort is the simplest [sorting](#) algorithm that works by repeatedly swapping the adjacent elements if they are in wrong order. You read an [list](#) of numbers. You need to arrange the elements in ascending order and print the result. The [sorting](#) should be done using bubble sort.

Input Format: The first line reads the number of elements in the array. The second line reads the array elements one by one.

Output Format: The output should be a sorted [list](#).

For example:

Input	Result
6 3 4 8 7 1 2	1 2 3 4 7 8
5 4 5 2 3 1	1 2 3 4 5

Answer: (penalty regime: 0 %)

1 | |

Question 2

Not answered

Mark 0.00 out of 1.00

Given an [list](#), find peak element in it. A peak element is an element that is greater than its neighbors.

An element $a[i]$ is a peak element if

$A[i-1] \leq A[i] \geq A[i+1]$ for middle elements. $[0 < i < n-1]$

$A[i-1] \leq A[i]$ for last element $[i=n-1]$

$A[i] \geq A[i+1]$ for first element $[i=0]$

Input Format

The first line contains a single integer n , the length of A .

The second line contains n space-separated integers, $A[i]$.

Output Format

Print peak numbers separated by space.

Sample Input

5
8 9 10 2 6

Sample Output

10 6

For example:

Input	Result
4 12 3 6 8	12 8

Answer: (penalty regime: 0 %)

1 | |

Question 3

Not answered

Mark 0.00 out of 1.00

Given an listof integers, sort the array in ascending order using the *Bubble Sort* algorithm above. Once sorted, print the following three lines:

1. [List](#) is sorted in numSwaps swaps., where numSwaps is the number of swaps that took place.
2. First Element: firstElement, the *first* element in the sorted [list](#).
3. Last Element: lastElement, the *last* element in the sorted [list](#).

For example, given a worst-case but small array to sort: a=[6,4,1]. It took 3 swaps to sort the array. Output would be

Array is sorted in 3 swaps.

First Element: 1

Last Element: 6

Input Format

The first line contains an integer, n , the size of the [list](#) a .

The second line contains n , space-separated integers $a[i]$.

Constraints

- $2 \leq n \leq 600$
- $1 \leq a[i] \leq 2 \times 10^6$.

Output Format

You must print the following three lines of output:

1. [List](#) is sorted in numSwaps swaps., where numSwaps is the number of swaps that took place.
2. First Element: firstElement, the *first* element in the sorted [list](#).
3. Last Element: lastElement, the *last* element in the sorted [list](#).

Sample Input 0

3
1 2 3

Sample Output 0

[List](#) is sorted in 0 swaps.

First Element: 1

Last Element: 3

For example:

Input	Result
3 3 2 1	List is sorted in 3 swaps. First Element: 1 Last Element: 3
5 1 9 2 8 4	List is sorted in 4 swaps. First Element: 1 Last Element: 9

Answer: (penalty regime: 0 %)

1 | |

Question 4

Not answered

Mark 0.00 out of 1.00

Write a Python program to sort a [list](#) of elements using the merge sort algorithm.

For example:

Input	Result
5 6 5 4 3 8	3 4 5 6 8

Answer: (penalty regime: 0 %)

1 | |

Question **5**

Not answered

Mark 0.00 out of 1.00

Write a Python program for binary search.

For example:

Input	Result
1, 2, 3, 5, 8 6	False
3, 5, 9, 45, 42 42	True

Answer: (penalty regime: 0 %)

1 | |

[◀ Week10_MCQ](#)

Jump to...

Sorting ►