

Text Data in Business and Economics

Basel University – Autumn 2024

5. Supervised and Unsupervised Learning from Text

Different Goals, Different Methods

- ▶ Supervised Learning
 - ▶ pursuing a known goal, e.g., predicting whether a political speech is from a Democrat or a Republican.
 - ▶ machine learns to replicate labels for new data points

Different Goals, Different Methods

- ▶ Supervised Learning
 - ▶ pursuing a known goal, e.g., predicting whether a political speech is from a Democrat or a Republican.
 - ▶ machine learns to replicate labels for new data points
- ▶ Unsupervised Learning
 - ▶ algorithm discovers themes/patterns in text (or other high-dimensional data)
 - ▶ human interprets the results (e.g. inspect content of topics or clusters)

Different Goals, Different Methods

- ▶ Supervised Learning
 - ▶ pursuing a known goal, e.g., predicting whether a political speech is from a Democrat or a Republican.
 - ▶ machine learns to replicate labels for new data points
- ▶ Unsupervised Learning
 - ▶ algorithm discovers themes/patterns in text (or other high-dimensional data)
 - ▶ human interprets the results (e.g. inspect content of topics or clusters)
- ▶ Both strategies amplify human effort, each in different ways.

Different Goals, Different Methods

- ▶ Supervised Learning
 - ▶ pursuing a known goal, e.g., predicting whether a political speech is from a Democrat or a Republican.
 - ▶ machine learns to replicate labels for new data points
- ▶ Unsupervised Learning
 - ▶ algorithm discovers themes/patterns in text (or other high-dimensional data)
 - ▶ human interprets the results (e.g. inspect content of topics or clusters)
- ▶ Both strategies amplify human effort, each in different ways.
- ▶ Distinctions are not clear-cut:
 - ▶ supervised learning models can be used to discover themes/patterns
 - ▶ unsupervised learning models can be used in service of prediction or known goals.

Objectives: Social-Science Research using Unsupervised Learning

1. **What is the research question?**

Objectives: Social-Science Research using Unsupervised Learning

1. **What is the research question?**
2. Corpus and Data:
 - ▶ obtain, clean, preprocess, and link.
 - ▶ Produce descriptive visuals and statistics on the text and metadata

Objectives: Social-Science Research using Unsupervised Learning

1. **What is the research question?**
2. Corpus and Data:
 - ▶ obtain, clean, preprocess, and link.
 - ▶ Produce descriptive visuals and statistics on the text and metadata
3. Unsupervised learning:
 - ▶ **What are we trying to measure?**

Objectives: Social-Science Research using Unsupervised Learning

1. **What is the research question?**
2. Corpus and Data:
 - ▶ obtain, clean, preprocess, and link.
 - ▶ Produce descriptive visuals and statistics on the text and metadata
3. Unsupervised learning:
 - ▶ **What are we trying to measure?**
 - ▶ Select a model and train it.
 - ▶ Probe sensitivity to hyperparameters.
 - ▶ Validate that the model is measuring what we want.

Objectives: Social-Science Research using Unsupervised Learning

1. **What is the research question?**
2. Corpus and Data:
 - ▶ obtain, clean, preprocess, and link.
 - ▶ Produce descriptive visuals and statistics on the text and metadata
3. Unsupervised learning:
 - ▶ **What are we trying to measure?**
 - ▶ Select a model and train it.
 - ▶ Probe sensitivity to hyperparameters.
 - ▶ Validate that the model is measuring what we want.
4. Empirical analysis
 - ▶ Produce statistics or predictions with the trained model.
 - ▶ **Answer the research question.**

Outline

Dimensionality Reduction

Topic Models

Supervised Learning

- Overview

- Regression / Regularization


- Binary Classification

- Multi-Class Models

Ensemble Learning with XGBoost



- ▶ Datasets are not distributed uniformly across the feature space.
- ▶ They have a lower-dimensional latent structure – a **manifold** – that can be learned.

“The Swiss Roll”



“The Swiss Roll”

- ▶ Datasets are not distributed uniformly across the feature space.
- ▶ They have a lower-dimensional latent structure – a **manifold** – that can be learned.



- ▶ **Dimensionality reduction** makes data more interpretable – for example by projecting down to two dimensions for visualization.
- ▶ improves computational tractability.
- ▶ can improve model performance.

What dimension reductions have you already tried in this class?

The Document-Term Matrix is high-dimensional

The **document-term matrix** \mathbf{X} :

- ▶ each row d represents a **document**, while each column w represents a word (or term more generally, e.g. n-grams).
- ▶ A matrix entry $\mathbf{X}_{[d,w]}$ quantifies the strength of association between a document and a word, generally its count or frequency

The Document-Term Matrix is high-dimensional

The **document-term matrix** \mathbf{X} :

- ▶ each row d represents a **document**, while each column w represents a word (or term more generally, e.g. n-grams).
 - ▶ A matrix entry $\mathbf{X}_{[d,w]}$ quantifies the strength of association between a document and a word, generally its count or frequency
- ▶ each document/row $\mathbf{X}_{[d,:]}$ is a distribution over terms
 - ▶ term vocabularies can be in the hundreds of thousands

The Document-Term Matrix is high-dimensional

The **document-term matrix** \mathbf{X} :

- ▶ each row d represents a **document**, while each column w represents a word (or term more generally, e.g. n-grams).
 - ▶ A matrix entry $\mathbf{X}_{[d,w]}$ quantifies the strength of association between a document and a word, generally its count or frequency
- ▶ each document/row $\mathbf{X}_{[d,:]}$ is a distribution over terms
 - ▶ term vocabularies can be in the hundreds of thousands
- ▶ each word/column $\mathbf{X}_{[:,w]}$ is a distribution over documents.
 - ▶ many interesting corpora have millions of documents

The Document-Term Matrix is high-dimensional


The **document-term matrix** \mathbf{X} :

- ▶ each row d represents a **document**, while each column w represents a word (or term more generally, e.g. n-grams).
 - ▶ A matrix entry $\mathbf{X}_{[d,w]}$ quantifies the strength of association between a document and a word, generally its count or frequency
- ▶ each document/row $\mathbf{X}_{[d,:]}$ is a distribution over terms
 - ▶ term vocabularies can be in the hundreds of thousands
- ▶ each word/column $\mathbf{X}_{[:,w]}$ is a distribution over documents.
 - ▶ many interesting corpora have millions of documents

→ \mathbf{X} often has billions of cells.

PCA (principal component analysis)


PCA (principal component analysis)



- PCA computes the dimension in data explaining most variance.


```
from sklearn.decomposition import PCA  
pca = PCA(n_components=10)  
X_train_pca = pca.fit_transform(X_train)
```

PCA (principal component analysis)



- PCA computes the dimension in data explaining most variance.

```
from sklearn.decomposition import PCA  
pca = PCA(n_components=10)  
X_train_pca = pca.fit_transform(X_train)
```



- after the first component, subsequent components learn the (orthogonal) dimensions explaining most variance in dataset after projecting out first component.

PCA and LSA

The document-term matrix \mathbf{X} can be reduced by projecting down to first principal component dimensions.

- ▶ This is known as “latent semantic analysis”
- ▶ Distance metrics between observations (e.g. cosine similarity) are approximately preserved.

PCA and LSA

The document-term matrix \mathbf{X} can be reduced by projecting down to first principal component dimensions.

- ▶ This is known as “latent semantic analysis”
- ▶ Distance metrics between observations (e.g. cosine similarity) are approximately preserved.
- ▶ PCA factors are not interpretable.
 - ▶ Hoffman (1999) fixes this and puts LSA on firmer foundations by assuming a generative model of text – the word counts in a document are generated by a multinomial distribution.
 - ▶ For non-negative data (e.g. counts or frequencies), **Non-negative Matrix Factorization (NMF)** provides more interpretable factors than PCA.

Outline

Dimensionality Reduction

Topic Models

Supervised Learning

- Overview

- Regression / Regularization

- Binary Classification

- Multi-Class Models

Ensemble Learning with XGBoost

Topic Models in Social Science

- ▶ Core methods for topic models were developed in computer science and statistics
 - ▶ summarize unstructured text
 - ▶ use words within document to infer subject
 - ▶ useful for dimension reduction

Topic Models in Social Science

- ▶ Core methods for topic models were developed in computer science and statistics
 - ▶ summarize unstructured text
 - ▶ use words within document to infer subject
 - ▶ useful for dimension reduction
- ▶ Social scientists use topics as a form of measurement
 - ▶ how observed covariates drive trends in language
 - ▶ tell a story not just about what, but how and why


Topic Models in Social Science

- ▶ Core methods for topic models were developed in computer science and statistics
 - ▶ summarize unstructured text
 - ▶ use words within document to infer subject
 - ▶ useful for dimension reduction
- ▶ Social scientists use topics as a form of measurement
 - ▶ how observed covariates drive trends in language
 - ▶ tell a story not just about what, but how and why
 - ▶ **topic models are more interpretable** than other dimension reduction methods, such as PCA.

- ▶ Latent Dirichlet Allocation (LDA):
 - ▶ Each topic is a distribution over words.
 - ▶ Each document is a distribution over topics.

- ▶ Latent Dirichlet Allocation (LDA):
 - ▶ Each topic is a distribution over words.
 - ▶ Each document is a distribution over topics.
- ▶ Input: $N \times M$ document-term count matrix X
- ▶ Assume: there are K topics (tunable hyperparameter, use coherence).
- ▶ Like PCA or NMF, LDA works by factorizing X into:
 - ▶ an $N \times K$ document-topic matrix
 - ▶ an $K \times M$ topic-term matrix.

- ▶ Latent Dirichlet Allocation (LDA):
 - ▶ Each topic is a distribution over words.
 - ▶ Each document is a distribution over topics.
- ▶ Input: $N \times M$ document-term count matrix X
- ▶ Assume: there are K topics (tunable hyperparameter, use coherence).
- ▶ Like PCA or NMF, LDA works by factorizing X into:
 - ▶ an $N \times K$ document-topic matrix
 - ▶ an $K \times M$ topic-term matrix.



Using an LDA Model

Once trained, can easily get topic proportions for a corpus.

- ▶ for any document – doesn't have to be in training corpus.
- ▶ main topic is the highest-probability topic

Using an LDA Model

Once trained, can easily get topic proportions for a corpus.

- ▶ for any document – doesn't have to be in training corpus.
- ▶ main topic is the highest-probability topic
- ▶ documents with highest share in a topic work as representative documents for the topic.

Using an LDA Model

Once trained, can easily get topic proportions for a corpus.

- ▶ for any document – doesn't have to be in training corpus.
- ▶ main topic is the highest-probability topic
- ▶ documents with highest share in a topic work as representative documents for the topic.

Can then use the topic proportions as variables in a social science analysis.

- ▶ e.g., Catalinac (2016) shows that after a Japanese political reform that reduced intraparty competition, candidate platforms reduced pork-barrel policies and increased national ones.




TABLE 1 A Summary of Common Assumptions and Relative Costs Across Different Methods of Discrete Text Categorization

	Method				
	<i>Reading</i>	<i>Human Coding</i>	<i>Dictionaries</i>	<i>Supervised Learning</i>	<i>Topic Model</i>
A. Assumptions					
<i>Categories are known</i>	No	Yes	Yes	Yes	No
<i>Category nesting, if any, is known</i>	No	Yes	Yes	Yes	No
<i>Relevant text features are known</i>	No	No	Yes	Yes	Yes
<i>Mapping is known</i>	No	No	Yes	No	No
<i>Coding can be automated</i>	No	No	Yes	Yes	Yes
B. Costs					
Preanalysis Costs					
<i>Person-hours spent conceptualizing</i>	Low	High	High	High	Low
<i>Level of substantive knowledge</i>	Moderate/High	High	High	High	Low
Analysis Costs					
<i>Person hours spent per text</i>	High	High	Low	Low	Low
<i>Level of substantive knowledge</i>	Moderate/High	Moderate	Low	Low	Low
Postanalysis Costs					
<i>Person-hours spent interpreting</i>	High	Low	Low	Low	Moderate
<i>Level of substantive knowledge</i>	High	High	High	High	High

Recommended: read this part of Quinn, Monroe, Colaresi, Crespin, and Radev (2010).

Structural Topic Model = LDA + Metadata

Roberts, Stewart, and Tingley

STM provides two ways to include contextual information:

- ▶ Topic prevalence can vary by metadata
 - ▶ e.g. Republicans talk about military issues more than Democrats

Structural Topic Model = LDA + Metadata

Roberts, Stewart, and Tingley

STM provides two ways to include contextual information:

- ▶ Topic prevalence can vary by metadata
 - ▶ e.g. Republicans talk about military issues more than Democrats
- ▶ Topic content can vary by metadata
 - ▶ e.g. Republicans talk about military issues more patriotically than Democrats.

Structural Topic Model = LDA + Metadata

Roberts, Stewart, and Tingley

STM provides two ways to include contextual information:

- ▶ Topic prevalence can vary by metadata
 - ▶ e.g. Republicans talk about military issues more than Democrats
- ▶ Topic content can vary by metadata
 - ▶ e.g. Republicans talk about military issues more patriotically than Democrats.
- ▶ Structural topic model is not a prediction model:
 - ▶ it will tell you which topics or features correlate with an outcome, but it will not provide an in-sample or out-of-sample prediction for an outcome

Structural Topic Model = LDA + Metadata

Roberts, Stewart, and Tingley

STM provides two ways to include contextual information:

- ▶ Topic prevalence can vary by metadata
 - ▶ e.g. Republicans talk about military issues more than Democrats
- ▶ Topic content can vary by metadata
 - ▶ e.g. Republicans talk about military issues more patriotically than Democrats.
- ▶ Structural topic model is not a prediction model:
 - ▶ it will tell you which topics or features correlate with an outcome, but it will not provide an in-sample or out-of-sample prediction for an outcome
- ▶ It actually uses another distribution of the priors (*not* Dirichlet) such that without covariates it replicates the correlated topic model (Blei and Lafferty, 2005)

Recent Advances in Topic Model

- ▶ Keyword-Assisted topic model (Eshima, Imai, and Sasaki, 2024)
 - ▶ allows *semi-supervised* creation of topics
 - ▶ input seed dictionaries and labeled topics

Recent Advances in Topic Model

- ▶ Keyword-Assisted topic model (Eshima, Imai, and Sasaki, 2024)
 - ▶ allows *semi-supervised* creation of topics
 - ▶ input seed dictionaries and labeled topics
- ▶ Generalized topic model (Gauthier, Widmer, and Ash, 2024)
 - ▶ includes covariates and auxiliary outcomes, allowing for these to affect the priors
 - ▶ allows for the use of both text and images

Recent Advances in Topic Model

- ▶ Keyword-Assisted topic model (Eshima, Imai, and Sasaki, 2024)
 - ▶ allows *semi-supervised* creation of topics
 - ▶ input seed dictionaries and labeled topics
- ▶ Generalized topic model (Gauthier, Widmer, and Ash, 2024)
 - ▶ includes covariates and auxiliary outcomes, allowing for these to affect the priors
 - ▶ allows for the use of both text and images
- ▶ Problems with unstructured data and casual inference (Battaglia et al., 2024)
 - ▶ shows that two-steps strategy leads to invalid inference
 - ▶ propose solutions with bias correction and a one-step strategy

Outline

Dimensionality Reduction

Topic Models

Supervised Learning

- Overview


- Regression / Regularization

- Binary Classification

- Multi-Class Models

Ensemble Learning with XGBoost

What is machine learning?



- ▶ In classical computer programming, humans input the rules and the data, and the computer provides answers.
- ▶ In machine learning, humans input the data and the answers, and the computer learns the rules.

What do ML Algorithms do? Fit a function to data points




Figure 4-14. High-degree Polynomial Regression

What do ML Algorithms do? Minimize a cost function

- ▶ A typical cost function (or loss function) for regression problems is Mean Squared Error (MSE):

$$\text{MSE}(\theta) = \frac{1}{n_D} \sum_{i=1}^{n_D} (h(x_i; \theta) - y_i)^2$$

- ▶ n_D , the number of rows/observations
- ▶ x , the matrix of predictors, with row x_i
- ▶ y , the vector of outcomes, with item y_i
- ▶ $h(x_i; \theta) = \hat{y}$ the model prediction (hypothesis)

The **data** (x, y) are taken as given, and the ML algorithm searches for **parameters** θ to minimize the cost function.

Linear Regression is Machine Learning

- ▶ Ordinary Least Squares Regression (OLS) assumes the functional form $f(x; \theta) = x'_i \theta$ and minimizes the mean squared error (MSE)

$$\min_{\hat{\theta}} \frac{1}{n_D} \sum_{i=1}^{n_D} (x'_i \hat{\theta} - y_i)^2$$

Linear Regression is Machine Learning

- ▶ Ordinary Least Squares Regression (OLS) assumes the functional form $f(x; \theta) = x'_i \theta$ and minimizes the mean squared error (MSE)

$$\min_{\hat{\theta}} \frac{1}{n_D} \sum_{i=1}^{n_D} (x'_i \hat{\theta} - y_i)^2$$

- ▶ This minimand has a closed form solution

$$\hat{\theta} = (\mathbf{x}' \mathbf{x})^{-1} \mathbf{x}' \mathbf{y}$$

- ▶ most machine learning models do **not** have a closed form solution → use numerical optimization instead (gradient descent).

$$\text{MSE}(\theta) = \frac{1}{n_D} \sum_{i=1}^{n_D} (h(\theta; \mathbf{x}_i) - y_i)^2$$

- The partial derivative for feature j is

$$\frac{\partial \text{MSE}}{\partial \theta_j} = \frac{2}{n_D} \sum_{i=1}^{n_D} \underbrace{(h(\theta; \mathbf{x}_i) - y_i)}_{\text{error for this obs}} \underbrace{\frac{\partial h(\theta; \mathbf{x}_i)}{\partial \theta_j}}_{\text{how } \theta_j \text{ shifts } h(\cdot)}$$

- → estimates how changing θ_j would reduce the error across the whole dataset.

$$\text{MSE}(\theta) = \frac{1}{n_D} \sum_{i=1}^{n_D} (h(\theta; \mathbf{x}_i) - y_i)^2$$

- ▶ The partial derivative for feature j is

$$\frac{\partial \text{MSE}}{\partial \theta_j} = \frac{2}{n_D} \sum_{i=1}^{n_D} \underbrace{(h(\theta; \mathbf{x}_i) - y_i)}_{\text{error for this obs}} \underbrace{\frac{\partial h(\theta; \mathbf{x}_i)}{\partial \theta_j}}_{\text{how } \theta_j \text{ shifts } h(\cdot)}$$

- ▶ → estimates how changing θ_j would reduce the error across the whole dataset.

- ▶ The **gradient** ∇ gives the vector of these partial derivatives for all features:
- ▶ **Gradient descent** nudges θ against the gradient (the direction that reduces MSE):

$$\nabla_{\theta} \text{MSE} = \begin{bmatrix} \frac{\partial \text{MSE}}{\partial \theta_1} \\ \frac{\partial \text{MSE}}{\partial \theta_2} \\ \vdots \\ \frac{\partial \text{MSE}}{\partial \theta_{n_x}} \end{bmatrix}$$

$$\theta_{t+1} = \theta_t - \eta \nabla_{\theta} \text{MSE}$$

- ▶ η = learning rate

$$\text{MSE}(\theta) = \frac{1}{n_D} \sum_{i=1}^{n_D} (h(\theta; \mathbf{x}_i) - y_i)^2$$

- ▶ The partial derivative for feature j is

$$\frac{\partial \text{MSE}}{\partial \theta_j} = \frac{2}{n_D} \sum_{i=1}^{n_D} \underbrace{(h(\theta; \mathbf{x}_i) - y_i)}_{\text{error for this obs}} \underbrace{\frac{\partial h(\theta; \mathbf{x}_i)}{\partial \theta_j}}_{\text{how } \theta_j \text{ shifts } h(\cdot)}$$

- ▶ → estimates how changing θ_j would reduce the error across the whole dataset.

- ▶ The **gradient** ∇ gives the vector of these partial derivatives for all features:
- ▶ **Gradient descent** nudges θ against the gradient (the direction that reduces MSE):

$$\nabla_{\theta} \text{MSE} = \begin{bmatrix} \frac{\partial \text{MSE}}{\partial \theta_1} \\ \frac{\partial \text{MSE}}{\partial \theta_2} \\ \vdots \\ \frac{\partial \text{MSE}}{\partial \theta_{n_x}} \end{bmatrix}$$

$$\theta_{t+1} = \theta_t - \eta \nabla_{\theta} \text{MSE}$$

- ▶ η = learning rate

- ▶ If the cost function is convex, gradient descent is guaranteed to find the global minimum.

Machine Learning with Text Data

- ▶ We have a corpus (or dataset) D of $n_D \geq 1$ documents d_i (or data points).

Machine Learning with Text Data

- ▶ We have a corpus (or dataset) D of $n_D \geq 1$ documents d_i (or data points).
- ▶ Each document i has an associated outcome or label \mathbf{y}_i with dimensions $n_y \geq 1$

Machine Learning with Text Data

- ▶ We have a corpus (or dataset) D of $n_D \geq 1$ documents d_i (or data points).
- ▶ Each document i has an associated outcome or label \mathbf{y}_i with dimensions $n_y \geq 1$
- ▶ Some documents are labeled and some are unlabeled \rightarrow
 - ▶ we would like to learn a function $\hat{\mathbf{y}}(d_i)$ based on the labeled data ...
 - ▶ ... to machine-classify the unlabeled data.

First Problem

- ▶ Each document is a sequence of symbols d_i , while (standard) ML algorithms work on numbers.

First Problem

- ▶ Each document is a sequence of symbols d_i , while (standard) ML algorithms work on numbers.
- ▶ The solution: all the methods from previous lectures for extracting informative numerical information from documents:
 - ▶ style features
 - ▶ counts over dictionary patterns
 - ▶ tokens
 - ▶ n-grams
 - ▶ principal components
 - ▶ topic shares
 - ▶ etc.
- ▶ documents can thus be **featurized** – represented as a matrix of vectors \mathbf{x} with $n_x \geq 1$ features.

Three Types of (Standard) Machine Learning Problems

Determined by the data type of the outcome variable (or label):

- ▶ **Binary classification:** two choices, normalized to zero and one.
 - ▶ e.g., guilty or innocent

Three Types of (Standard) Machine Learning Problems

Determined by the data type of the outcome variable (or label):

- ▶ **Binary classification:** two choices, normalized to zero and one.
 - ▶ e.g., guilty or innocent
- ▶ **Regression:** a one-dimensional, continuous, real-valued outcome.
 - ▶ e.g., number of days of prison assigned

Three Types of (Standard) Machine Learning Problems

Determined by the data type of the outcome variable (or label):

- ▶ **Binary classification:** two choices, normalized to zero and one.
 - ▶ e.g., guilty or innocent
- ▶ **Regression:** a one-dimensional, continuous, real-valued outcome.
 - ▶ e.g., number of days of prison assigned
- ▶ **Multinomial Classification:** Three or more discrete, un-ordered outcomes.
 - ▶ e.g., predict what judge is assigned to a case: Alito, Breyer, or Cardozo

Loss functions, more generally

- ▶ The loss function $L(\hat{\mathbf{y}}, \mathbf{y})$ assigns a score based on prediction and truth:
 - ▶ Should be bounded from below, with the minimum attained only for cases where the prediction is correct.
- ▶ The average loss for the test set is

$$\mathcal{L}(\theta) = \frac{1}{n_D} \sum_{i=1}^{n_D} L(h(\mathbf{x}_i; \theta), \mathbf{y}_i)$$

- ▶ The estimated parameter matrix θ solves

$$\hat{\theta} = \arg \min_{\theta} \mathcal{L}(\theta)$$

↪ optimizes over parameter space; treats the data as constants.

Gradient Descent

- ▶ even when cost function is not convex (eg neural nets), gradient descent often gets decent results.
- ▶ **Stochastic gradient descent (SGD)** computes the gradient for a single randomly sampled instance (at each iteration).
 - ▶ Much faster, still works well.

Use Cross-Validation During Model Training

- ▶ Train/Test Split:
 - ▶ ML models can achieve arbitrarily high accuracy in-sample, so performance should be evaluated out-of-sample.

Use Cross-Validation During Model Training

- ▶ Train/Test Split:
 - ▶ ML models can achieve arbitrarily high accuracy in-sample, so performance should be evaluated out-of-sample.
 - ▶ standard approach: randomly sample 80% training dataset to learn parameters, form predictions in 20% testing dataset for evaluating performance.
- ▶ Within the training set:
 - ▶ Use cross-validation with grid search to get model performance metrics across subsets of data using different hyperparameter specs.
 - ▶ Find the best hyperparameters for out-of-fold prediction in the training set.
- ▶ Then evaluate model performance in the test set using these hyperparameters.

Model Evaluation in Test Set

Evaluating a “good” model is context-dependent. Here are some basics.

Regression:

- ▶ mean squared error (MSE)
- ▶ R-squared (same ranking as MSE, but units are more interpretable)
- ▶ mean absolute error (MAE, $\sum |\hat{y}(\theta) - y|$) is less sensitive to outliers.

Model Evaluation in Test Set

Evaluating a “good” model is context-dependent. Here are some basics.

Regression:

- ▶ mean squared error (MSE)
- ▶ R-squared (same ranking as MSE, but units are more interpretable)
- ▶ mean absolute error (MAE, $\sum |\hat{y}(\theta) - y|$) is less sensitive to outliers.

Classification:

- ▶ more complicated, but accuracy is a good baseline:
accuracy = (# correct test-set predictions) / (# of test-set observations)

Model Evaluation in Test Set

Evaluating a “good” model is context-dependent. Here are some basics.

Regression:

- ▶ mean squared error (MSE)
- ▶ R-squared (same ranking as MSE, but units are more interpretable)
- ▶ mean absolute error (MAE, $\sum |\hat{y}(\theta) - y|$) is less sensitive to outliers.

Classification:

- ▶ more complicated, but accuracy is a good baseline:
accuracy = (# correct test-set predictions) / (# of test-set observations)
- ▶ What if one of the outcomes is over-represented – e.g., 19 out of 20? Then I can guess the modal class and get 95% accuracy.
 - ▶ Some alternative classifier metrics designed to address class imbalance (more below).

Regression models \leftrightarrow Continuous outcome

- ▶ If the outcome is continuous (e.g., Y = tax revenues collected, or criminal sentence imposed in months of prison):
 - ▶ Need a regression model.
- ▶ Problems with OLS:
 - ▶ tends to over-fit training data.
 - ▶ cannot handle multicollinearity.




Figure 4-14. High-degree Polynomial Regression

Regression models \leftrightarrow Continuous outcome

- ▶ If the outcome is continuous (e.g., Y = tax revenues collected, or criminal sentence imposed in months of prison):
 - ▶ Need a regression model.
- ▶ Problems with OLS:
 - ▶ tends to over-fit training data.
 - ▶ cannot handle multicollinearity.




Figure 4-14. High-degree Polynomial Regression

- ▶ **Regularization:** model training methods designed to reduce/prevent over-fitting.

Regularized Loss Function

$$\hat{\theta} = \arg \min_{\theta} \frac{1}{n_D} \sum_{i=1}^{n_D} L(h(\mathbf{x}_i; \theta), \mathbf{y}_i) + \lambda R(\theta)$$

- ▶ $R(\theta)$ is a “regularization function” or “regularizer”, designed to reduce over-fitting.
- ▶ λ is a hyperparameter where higher values increase regularization.

Regularized Loss Function

$$\hat{\theta} = \arg \min_{\theta} \frac{1}{n_D} \sum_{i=1}^{n_D} L(h(\mathbf{x}_i; \theta), \mathbf{y}_i) + \lambda R(\theta)$$

- ▶ $R(\theta)$ is a “regularization function” or “regularizer”, designed to reduce over-fitting.
- ▶ λ is a hyperparameter where higher values increase regularization.

In particular:

- ▶ “Lasso” (or L1) penalty:

$$R_1 = \|\theta\|_1 = \sum_{j=1}^{n_x} |\theta_j|$$

- ▶ shrinks coefficients toward zero. automatically performs feature selection and outputs a sparse model.

Regularized Loss Function

$$\hat{\theta} = \arg \min_{\theta} \frac{1}{n_D} \sum_{i=1}^{n_D} L(h(\mathbf{x}_i; \theta), \mathbf{y}_i) + \lambda R(\theta)$$

- ▶ $R(\theta)$ is a “regularization function” or “regularizer”, designed to reduce over-fitting.
- ▶ λ is a hyperparameter where higher values increase regularization.

In particular:

- ▶ “Lasso” (or L1) penalty:

$$R_1 = \|\theta\|_1 = \sum_{j=1}^{n_x} |\theta_j|$$

- ▶ shrinks coefficients toward zero. automatically performs feature selection and outputs a sparse model.
- ▶ “Ridge” (or L2) penalty:

$$R_2 = \|\theta\|_2^2 = \sum_{j=1}^{n_x} (\theta_j)^2$$

- ▶ shrinks coefficients toward zero and helps select between collinear predictors.

Regularized Loss Function

$$\hat{\theta} = \arg \min_{\theta} \frac{1}{n_D} \sum_{i=1}^{n_D} L(h(\mathbf{x}_i; \theta), \mathbf{y}_i) + \lambda R(\theta)$$

- ▶ $R(\theta)$ is a “regularization function” or “regularizer”, designed to reduce over-fitting.
- ▶ λ is a hyperparameter where higher values increase regularization.

In particular:

- ▶ “Lasso” (or L1) penalty:

$$R_1 = \|\theta\|_1 = \sum_{j=1}^{n_x} |\theta_j|$$

- ▶ shrinks coefficients toward zero. automatically performs feature selection and outputs a sparse model.
- ▶ “Ridge” (or L2) penalty:

$$R_2 = \|\theta\|_2^2 = \sum_{j=1}^{n_x} (\theta_j)^2$$

- ▶ shrinks coefficients toward zero and helps select between collinear predictors.
- ▶ Elastic Net: $R_{\text{enet}} = \lambda_1 R_1 + \lambda_2 R_2$

Binary Outcome \leftrightarrow Binary Classification

- ▶ Binary classifiers try to match a boolean outcome $y \in \{0, 1\}$.
 - ▶ The standard approach is to apply a transformation (e.g. sigmoid/logit) to normalize $\hat{y} \in [0, 1]$.
 - ▶ Prediction rule is 0 for $\hat{y} < .5$ and 1 otherwise.


Binary Outcome \leftrightarrow Binary Classification

- ▶ Binary classifiers try to match a boolean outcome $y \in \{0, 1\}$.
 - ▶ The standard approach is to apply a transformation (e.g. sigmoid/logit) to normalize $\hat{y} \in [0, 1]$.
 - ▶ Prediction rule is 0 for $\hat{y} < .5$ and 1 otherwise.
- ▶ The binary cross-entropy (or log loss) is:

$$L(\theta) = \underbrace{-\frac{1}{n_D}}_{\text{negative}} \sum_{i=1}^{n_D} \left[\underbrace{y_i}_{y_i=1} \underbrace{\log(\hat{y}_i)}_{\log \text{ prob}_{y_i=1}} + \underbrace{(1-y_i)}_{y_i=0} \underbrace{\log(1-\hat{y}_i)}_{\log \text{ prob}_{y_i=0}} \right]$$


- In **logistic regression** we use a sigmoid transformation:

$$\hat{y} = \text{sigmoid}(\mathbf{x} \cdot \theta) = \frac{1}{1 + \exp(-\mathbf{x} \cdot \theta)}$$



- In **logistic regression** we use a sigmoid transformation:

$$\hat{y} = \text{sigmoid}(\mathbf{x} \cdot \theta) = \frac{1}{1 + \exp(-\mathbf{x} \cdot \theta)}$$




- Plugging into the binary-cross entropy loss gives the logistic regression cost objective:

$$\min_{\theta} \sum_{i=1}^{n_D} -y_i \log(\text{sigmoid}(\mathbf{x}_i \cdot \theta)) - [1 - y_i] \log(1 - \text{sigmoid}(\mathbf{x}_i \cdot \theta))$$

- does not have a closed form solution, but it is convex (guaranteeing that gradient descent will find the global minimum).

- In **logistic regression** we use a sigmoid transformation:

$$\hat{y} = \text{sigmoid}(\mathbf{x} \cdot \theta) = \frac{1}{1 + \exp(-\mathbf{x} \cdot \theta)}$$



- Plugging into the binary-cross entropy loss gives the logistic regression cost objective:


$$\min_{\theta} \sum_{i=1}^{n_D} -y_i \log(\text{sigmoid}(\mathbf{x}_i \cdot \theta)) - [1 - y_i] \log(1 - \text{sigmoid}(\mathbf{x}_i \cdot \theta))$$

- does not have a closed form solution, but it is convex (guaranteeing that gradient descent will find the global minimum).
- The gradient for one data point is

$$\frac{\partial L(\theta)}{\partial \theta_j} = \underbrace{(\text{sigmoid}(\mathbf{x}_i \cdot \theta) - y_i)}_{\text{error for obs } i} \underbrace{x_i^j}_{\text{input } j}$$

- In **logistic regression** we use a sigmoid transformation:

$$\hat{y} = \text{sigmoid}(\mathbf{x} \cdot \theta) = \frac{1}{1 + \exp(-\mathbf{x} \cdot \theta)}$$



- Plugging into the binary-cross entropy loss gives the logistic regression cost objective:

$$\min_{\theta} \sum_{i=1}^{n_D} -y_i \log(\text{sigmoid}(\mathbf{x}_i \cdot \theta)) - [1 - y_i] \log(1 - \text{sigmoid}(\mathbf{x}_i \cdot \theta))$$

- does not have a closed form solution, but it is convex (guaranteeing that gradient descent will find the global minimum).
- The gradient for one data point is

$$\frac{\partial L(\theta)}{\partial \theta_j} = \underbrace{(\text{sigmoid}(\mathbf{x}_i \cdot \theta) - y_i)}_{\text{error for obs } i} \underbrace{x_i^j}_{\text{input } j}$$

- Like linear regression, logistic regression can be regularized with L1 or L2 penalties.

A **Confusion Matrix** is a nice way to visualize classifier performance:

		Predicted Class	
		Negative	Positive
2*True Class	Negative	# True Negatives	# False Positives
	Positive	# False Negatives	# True Positives

- ▶ Cell values give counts in the test set.

A **Confusion Matrix** is a nice way to visualize classifier performance:

		Predicted Class	
		Negative	Positive
2*True Class	Negative	# True Negatives	# False Positives
	Positive	# False Negatives	# True Positives

- Cell values give counts in the test set.

$$\text{Accuracy} = \frac{\text{True Positives} + \text{True Negatives}}{\text{True Positives} + \text{False Positives} + \text{False Negatives} + \text{True Negatives}}$$

A **Confusion Matrix** is a nice way to visualize classifier performance:

		Predicted Class	
		Negative	Positive
2*True Class	Negative	# True Negatives	# False Positives
	Positive	# False Negatives	# True Positives

- ▶ Cell values give counts in the test set.

$$\text{Accuracy} = \frac{\text{True Positives} + \text{True Negatives}}{\text{True Positives} + \text{False Positives} + \text{False Negatives} + \text{True Negatives}}$$

$$\text{Precision (for positive class)} = \frac{\text{True Positives}}{\text{True Positives} + \text{False Positives}}$$

- ▶ Precision decreases with false positives. “When I guess this outcome, I tend to guesses correctly.”

A **Confusion Matrix** is a nice way to visualize classifier performance:

		Predicted Class	
		Negative	Positive
2*True Class	Negative	# True Negatives	# False Positives
	Positive	# False Negatives	# True Positives

- ▶ Cell values give counts in the test set.

$$\text{Accuracy} = \frac{\text{True Positives} + \text{True Negatives}}{\text{True Positives} + \text{False Positives} + \text{False Negatives} + \text{True Negatives}}$$

$$\text{Precision (for positive class)} = \frac{\text{True Positives}}{\text{True Positives} + \text{False Positives}}$$

- ▶ Precision decreases with false positives. “When I guess this outcome, I tend to guesses correctly.”

$$\text{Recall (for positive class)} = \frac{\text{True Positives}}{\text{True Positives} + \text{False Negatives}}$$

- ▶ Recall decreases with false negatives. “When this outcome occurs, I don’t miss it.”

If labels are (almost) balanced, then accuracy is a decent metric.

- ▶ If not (say 90% in one category), accuracy will be uninformative/misleading.

If labels are (almost) balanced, then accuracy is a decent metric.

- ▶ If not (say 90% in one category), accuracy will be uninformative/misleading.

Balanced accuracy = the average recall in both classes:

$$\text{Balanced Accuracy} = \frac{1}{2} \left(\frac{\text{TP}}{\text{TP} + \text{FN}} + \frac{\text{TN}}{\text{TN} + \text{FP}} \right)$$

- ▶ → equal to accuracy when classes are balanced, or when performance is the same across classes.

If labels are (almost) balanced, then accuracy is a decent metric.

- ▶ If not (say 90% in one category), accuracy will be uninformative/misleading.

Balanced accuracy = the average recall in both classes:

$$\text{Balanced Accuracy} = \frac{1}{2} \left(\frac{\text{TP}}{\text{TP} + \text{FN}} + \frac{\text{TN}}{\text{TN} + \text{FP}} \right)$$

- ▶ → equal to accuracy when classes are balanced, or when performance is the same across classes.

F_1 **score** = the harmonic mean of precision and recall:

$$F_1 = \frac{2}{\frac{1}{\text{precision}} + \frac{1}{\text{recall}}} = 2 \times \frac{\text{precision} \times \text{recall}}{\text{precision} + \text{recall}}$$

- ▶ penalizes both false positives and false negatives; still ignores true negatives.

If labels are (almost) balanced, then accuracy is a decent metric.

- ▶ If not (say 90% in one category), accuracy will be uninformative/misleading.

Balanced accuracy = the average recall in both classes:

$$\text{Balanced Accuracy} = \frac{1}{2} \left(\frac{\text{TP}}{\text{TP} + \text{FN}} + \frac{\text{TN}}{\text{TN} + \text{FP}} \right)$$

- ▶ → equal to accuracy when classes are balanced, or when performance is the same across classes.

F_1 **score** = the harmonic mean of precision and recall:


$$F_1 = \frac{2}{\frac{1}{\text{precision}} + \frac{1}{\text{recall}}} = 2 \times \frac{\text{precision} \times \text{recall}}{\text{precision} + \text{recall}}$$

- ▶ penalizes both false positives and false negatives; still ignores true negatives.

AUC-ROC = Area Under the Receiver Operating Characteristic Curve

- ▶ provides an aggregate measure of performance across all possible classification thresholds.
- ▶ Interpretation: randomly sample one positive and one negative example. AUC = probability that the model correctly guesses which is which.

Evaluating Classification Models: Calibration Curves



- ▶ Plotting the binned fraction in a category (Y axis) against the predicted probability in a category (X axis):
- ▶ Provides evidence of whether the classifier is replicating the conditional distribution of the outcome.

Multiple Classes: Setup

- ▶ The outcome is $y_i \in \{1, \dots, k, \dots, n_y\}$ output classes, which can also be represented as a one-hot vector

$$\mathbf{y}_i = \{\mathbf{1}[y_i = 1], \dots, \mathbf{1}[y_i = n_y]\}$$

Multiple Classes: Setup

- ▶ The outcome is $y_i \in \{1, \dots, k, \dots, n_y\}$ output classes, which can also be represented as a one-hot vector

$$\mathbf{y}_i = \{\mathbf{1}[y_i = 1], \dots, \mathbf{1}[y_i = n_y]\}$$

- ▶ We want to learn a vector function

$$\mathbf{y} = \mathbf{h}(\mathbf{x}, \theta)$$

taking text features \mathbf{x} as inputs and outputting a vector of probabilities across outcome classes:

$$\hat{\mathbf{y}} = \{\hat{y}^1, \dots, \hat{y}^{n_y}\}, \sum_{k=1}^{n_y} \hat{y}^k = 1, \hat{y}^k \geq 0 \quad \forall k$$

- ▶ for prediction step, can select the highest-probability class:

$$\tilde{y} = \arg \max_k \hat{y}_{[k]}$$

- ▶ The standard loss function in multinomial classification is **categorical cross entropy**

Multinomial Logistic Regression

Multinomial logistic regression computes probabilities for each class k using the softmax transformation

$$\hat{y}_k(\mathbf{x}_i) = \Pr(y_i = k) = \frac{\exp(\theta'_k \mathbf{x}_i)}{\sum_{l=1}^{n_y} \exp(\theta'_l \mathbf{x}_i)}$$

- ▶ softmax is the multiclass generalization of sigmoid \rightarrow can then interpret \hat{y} as probabilities.
- ▶ n_x features and n_y output classes \rightarrow there is a $n_y \times n_x$ parameter matrix Θ , where the parameters for each class θ_k are stored as rows.

Multinomial Logistic Regression

Multinomial logistic regression computes probabilities for each class k using the softmax transformation

$$\hat{y}_k(\mathbf{x}_i) = \Pr(y_i = k) = \frac{\exp(\theta'_k \mathbf{x}_i)}{\sum_{l=1}^{n_y} \exp(\theta'_l \mathbf{x}_i)}$$

- ▶ softmax is the multiclass generalization of sigmoid \rightarrow can then interpret \hat{y} as probabilities.
- ▶ n_x features and n_y output classes \rightarrow there is a $n_y \times n_x$ parameter matrix Θ , where the parameters for each class θ_k are stored as rows.

The **L2-penalized logistic regression** has loss function

$$\mathcal{L}(\theta) = -\frac{1}{n_D} \sum_{i=1}^{n_D} \log \frac{\exp(\theta'_{k^*} \mathbf{x}_i)}{\sum_{l=1}^{n_y} \exp(\theta'_l \mathbf{x}_i)} + \lambda \sum_{j=1}^{n_x} \sum_{k=1}^{n_y} (\theta_{[j,k]})^2$$

- ▶ λ = strength of L2 penalty (could also add lasso penalty)
 - ▶ as before, predictors should be scaled to the same variance.

		Predicted Class		
		Class A	Class B	Class C
3*True Class	Class A	Correct A	A, classed as B	A, classed as C
	Class B	B, classed as A	Correct B	B, classed as C
	Class C	C, classed as A	C, classed as B	Correct C

More generally, with **multi-class confusion matrix** M with items M_{ij} (row i , column j):

$$\text{Precision for } k = \frac{\text{True Positives for } k}{\text{True Positives for } k + \text{False Positives for } k} = \frac{M_{kk}}{\sum_l M_{lk}}$$

$$\text{Recall for } k = \frac{\text{True Positives for } k}{\text{True Positives for } k + \text{False Negatives for } k} = \frac{M_{kk}}{\sum_l M_{kl}}$$

$$F_1(k) = 2 \times \frac{\text{precision}(k) \times \text{recall}(k)}{\text{precision}(k) + \text{recall}(k)}$$

		Predicted Class		
		Class A	Class B	Class C
3*True Class	Class A	Correct A	A, classed as B	A, classed as C
	Class B	B, classed as A	Correct B	B, classed as C
	Class C	C, classed as A	C, classed as B	Correct C

More generally, with **multi-class confusion matrix** M with items M_{ij} (row i , column j):

$$\text{Precision for } k = \frac{\text{True Positives for } k}{\text{True Positives for } k + \text{False Positives for } k} = \frac{M_{kk}}{\sum_l M_{lk}}$$

$$\text{Recall for } k = \frac{\text{True Positives for } k}{\text{True Positives for } k + \text{False Negatives for } k} = \frac{M_{kk}}{\sum_l M_{kl}}$$

$$F_1(k) = 2 \times \frac{\text{precision}(k) \times \text{recall}(k)}{\text{precision}(k) + \text{recall}(k)}$$

Can average these metrics across classes to get aggregate metrics.

- ▶ e.g., balanced accuracy = unweighted average of recalls across classes.
- ▶ can weight classes by their frequency in dataset

Outline

Dimensionality Reduction

Topic Models

Supervised Learning

- Overview


- Regression / Regularization

- Binary Classification

- Multi-Class Models

Ensemble Learning with XGBoost

XGBoost: Overview




XGBoost Ingredients: Decision Trees

Bootstrap aggregating or Bagging is an ensemble meta-algorithm combining predictions from multiple decision trees through a majority voting mechanism


Models are built sequentially by minimizing the errors from previous models while increasing (or boosting) influence of high-performing models

Optimized Gradient Boosting algorithm through parallel processing, tree-pruning, handling missing values and regularization to avoid overfitting/bias




Decision Trees

Classification Tree



- ▶ Decision trees learn a series of binary splits in the data based on hard thresholds.
 - ▶ if yes, go right; if no, go left.
- ▶ Can have additional splits as you move through the tree.
- ▶ fast and interpretable, but performance is often poor.

Voting Classifiers




- ▶ voting classifiers (ensembles of different models that vote on the prediction) generally out-perform the best classifier in the ensemble.
 - ▶ more diverse algorithms will make different types of errors, and improve your ensemble's robustness.

XGBoost Ingredients: Bootstrapping

Bootstrap aggregating or Bagging is a ensemble meta-algorithm combining predictions from multiple-decision trees through a majority voting mechanism


Models are built sequentially by minimizing the errors from previous models while increasing (or boosting) influence of high-performing models

Optimized Gradient Boosting algorithm through parallel processing, tree-pruning, handling missing values and regularization to avoid overfitting/bias





Bootstrapping

- Rather than use the same data on different classifiers, one can use different subsets of the data on the same classifier:



- can also use different subsets of features across subclassifiers.

Bootstrapping Benefits




- ▶ A bootstrapped ensemble generally has a similar bias but lower variance than a single predictor trained on all the data.
- ▶ Predictors can be trained in parallel using separate CPU cores.

XGBoost Ingredients: Random Forests

Bootstrap aggregating or Bagging is an ensemble meta-algorithm combining predictions from multiple decision trees through a majority voting mechanism

Models are built sequentially by minimizing the errors from previous models while increasing (or boosting) influence of high-performing models

Optimized Gradient Boosting algorithm through parallel processing, tree-pruning, handling missing values and regularization to avoid overfitting/bias



Random Forests

Random Forests are optimized ensembles of bootstrapped decision trees:

Random Forests

Random Forests are optimized ensembles of bootstrapped decision trees:

1. Each voting tree gets its own sample of data.

Random Forests

Random Forests are optimized ensembles of bootstrapped decision trees:

1. Each voting tree gets its own sample of data.
2. At each tree split, a random sample of features is drawn, only those features are considered for splitting.

Random Forests

Random Forests are optimized ensembles of bootstrapped decision trees:


1. Each voting tree gets its own sample of data.
2. At each tree split, a random sample of features is drawn, only those features are considered for splitting.
3. For each tree, error rate is computed using data outside its bootstrap sample.

XGBoost Ingredients: Gradient Boosting

Bootstrap aggregating or Bagging is an ensemble meta-algorithm combining predictions from multiple decision trees through a majority voting mechanism


Models are built sequentially by minimizing the errors from previous models while increasing (or boosting) influence of high-performing models

Optimized Gradient Boosting algorithm through parallel processing, tree-pruning, handling missing values and regularization to avoid overfitting/bias



Gradient Boosting Machines

- ▶ Gradient boosting refers to an additive ensemble of trees:




- ▶ Adds additional layers of trees to fit the residuals of the first layers

XGBoost Ingredients

Bootstrap aggregating or Bagging is an ensemble meta-algorithm combining predictions from multiple decision trees through a majority voting mechanism

Models are built sequentially by minimizing the errors from previous models while increasing (or boosting) influence of high-performing models

Optimized Gradient Boosting algorithm through parallel processing, tree-pruning, handling missing values and regularization to avoid overfitting/bias




XGBoost

- ▶ Feurer et al (2018) find that XGBoost beats a sophisticated AutoML procedure with grid search over 15 classifiers and 18 data preprocessors.
- ▶ A good starting point for any machine learning task.
- ▶ easy to use
- ▶ actively developed
- ▶ efficient / parallelizable
- ▶ provides model explanations
- ▶ takes sparse matrices as input



Tree Ensembles are Black Boxes

- Small decision trees have the advantage of being highly interpretable.



Tree Ensembles are Black Boxes

- ▶ Small decision trees have the advantage of being highly interpretable.



- ▶ Larger trees and ensembles (e.g. XGBoost) lose this nice feature.
- ▶ Best-performing ML models are hard to interpret because they use lots of features and exploit non-linearities and interactions.

Interpreting Tree Ensembles

XGBoost's Feature Importance Metric:

- ▶ At each decision node, compute **information gain** for feature j (**change in predicted probability**).
- ▶ Average across all nodes for each j .


Ranks predictors by their relative contributions.

```
from xgboost import plot_importance
plot_importance(xgb_reg, max_num_features=10)
```


Feature Importance

```
from xgboost import plot_importance
plot_importance(xgb_reg, max_num_features=20)
```

<IPython.core.display.Javascript object>



A baseline for machine learning using text

1. Take POS-filtered bigrams as inputs X .

A baseline for machine learning using text

1. Take POS-filtered bigrams as inputs X .
2. Select a machine learning model for predicting outcome y :
 - ▶ For regression (y is one-dimensional and continuous), elastic net or gradient boosted regressor.
 - ▶ For classification (y is discrete), L2-penalized logistic regression or gradient boosted classifier.

A baseline for machine learning using text

1. Take POS-filtered bigrams as inputs X .
2. Select a machine learning model for predicting outcome y :
 - ▶ For regression (y is one-dimensional and continuous), elastic net or gradient boosted regressor.
 - ▶ For classification (y is discrete), L2-penalized logistic regression or gradient boosted classifier.
 - ▶ *(If y is more complicated, e.g. a sequence of words, we use deep learning.)*

A baseline for machine learning using text

1. Take POS-filtered bigrams as inputs X .
2. Select a machine learning model for predicting outcome y :
 - ▶ For regression (y is one-dimensional and continuous), elastic net or gradient boosted regressor.
 - ▶ For classification (y is discrete), L2-penalized logistic regression or gradient boosted classifier.
 - ▶ (*If y is more complicated, e.g. a sequence of words, we use deep learning.*)
3. Use cross-validation grid search in training set to select model hyperparameters.
 - ▶ For classification, use cross entropy; for regression, use mean squared error.

A baseline for machine learning using text

1. Take POS-filtered bigrams as inputs X .
2. Select a machine learning model for predicting outcome y :
 - ▶ For regression (y is one-dimensional and continuous), elastic net or gradient boosted regressor.
 - ▶ For classification (y is discrete), L2-penalized logistic regression or gradient boosted classifier.
 - ▶ *(If y is more complicated, e.g. a sequence of words, we use deep learning.)*
3. Use cross-validation grid search in training set to select model hyperparameters.
 - ▶ For classification, use cross entropy; for regression, use mean squared error.
4. Evaluate model in held-out test set:
 - ▶ For classification, use balanced accuracy, confusion matrix, and calibration plot.
 - ▶ For regression, use R squared and binscatter plot.

A baseline for machine learning using text

1. Take POS-filtered bigrams as inputs X .
2. Select a machine learning model for predicting outcome y :
 - ▶ For regression (y is one-dimensional and continuous), elastic net or gradient boosted regressor.
 - ▶ For classification (y is discrete), L2-penalized logistic regression or gradient boosted classifier.
 - ▶ *(If y is more complicated, e.g. a sequence of words, we use deep learning.)*
3. Use cross-validation grid search in training set to select model hyperparameters.
 - ▶ For classification, use cross entropy; for regression, use mean squared error.
4. Evaluate model in held-out test set:
 - ▶ For classification, use balanced accuracy, confusion matrix, and calibration plot.
 - ▶ For regression, use R squared and binscatter plot.
5. Interpret the model predictions:
 - ▶ for gradient boosting, use feature importance ranking.
 - ▶ for linear models, examine coefficients
 - ▶ look at highest and lowest ranked documents for \hat{y}

A baseline for machine learning using text

1. Take POS-filtered bigrams as inputs X .
2. Select a machine learning model for predicting outcome y :
 - ▶ For regression (y is one-dimensional and continuous), elastic net or gradient boosted regressor.
 - ▶ For classification (y is discrete), L2-penalized logistic regression or gradient boosted classifier.
 - ▶ *(If y is more complicated, e.g. a sequence of words, we use deep learning.)*
3. Use cross-validation grid search in training set to select model hyperparameters.
 - ▶ For classification, use cross entropy; for regression, use mean squared error.
4. Evaluate model in held-out test set:
 - ▶ For classification, use balanced accuracy, confusion matrix, and calibration plot.
 - ▶ For regression, use R squared and binscatter plot.
5. Interpret the model predictions:
 - ▶ for gradient boosting, use feature importance ranking.
 - ▶ for linear models, examine coefficients
 - ▶ look at highest and lowest ranked documents for \hat{y}
6. Answer the research question!