
pt_extlist

TypoSript Reference

Name

agregateRowsPartial

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].agregateRowsPartial

Description

Path to the aggregate row partial.

Datatype: String

StdWrap: NO

Name

plugin.tx_ptextlist.settings

TS-Key:

plugin.tx_ptextlist.settings

Description

Main TS-key for all pt_extlist settings.

StdWrap: NO

Child elements

listConfig,

Name

listConfig

TS-Key:

plugin.tx_pextlist.settings.listConfig

Description

Holds configuration for all list identifiers configured by array key.

Datatype: Associative Array (listIdentifier => listConfiguration)

StdWrap: NO

Example

```
plugin.tx_pextlist.settings {  
  
    listConfig {  
  
        listIdentifier1 {  
  
            # Here goes the configuration for your first list  
            ...  
  
        }  
  
        listIdentifier2 {  
  
            # Here goes the configuration for your second list  
            ...  
  
        }  
  
        # Feel free to add more lists...  
        ...  
  
    }  
  
}
```

Child elements

[yourListId],

Name

[yourListId]

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId]

Description

Holds configuration for a single list identifier. This is where the main part of your list configuration has to be set up.

StdWrap: NO

Example

```
plugin.tx_ptextlist.settings {  
  
    listConfig {  
  
        demolist_mysql_01 {  
  
            backendConfig < plugin.tx_ptextlist.prototype.backend.mysql  
            backendConfig {  
                ...  
            }  
  
        }  
  
        fields {  
            ...  
        }  
  
        columns {  
            ...  
        }  
  
        filters {  
            ...  
        }  
  
        pager {  
            ...  
        }  
    }  
}
```

Child elements

default, backendConfig, fields, columns, rendererChain, aggregateData, aggregateRows, filters, headerPartial, bodyPartial, aggregateRowsPartial,

Name

default

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].default

Description

List default values.

StdWrap: NO

Child elements

sortingColumn,

Name

sortingColumn

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].default.sortingColumn

Description

The default sorting column while no other sorting is set.

Datatype: String

Possible values: Any column identifier

StdWrap: NO

Name

backendConfig

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].backendConfig

Description

Holds the configuration for the data backend to be used with this configuration. Configurable values depend on individual backend, e.g. Typo3-Backend, MySQL-Backen, ExtBase-Backend etc.

StdWrap: NO

Variants

backendConfig.mysql, backendConfig.typo3, backendConfig.extbase,

Variants of backendConfig:

Name

backendConfig.mysql

TS-Key:

plugin.tx_pextlist.settings.listConfig.[yourListId].backendConfig.backendConfig.mysql

Description

Backend configuration for connecting to native MySQL databases. DSN needs to be configured.

StdWrap: NO

Prototype: plugin.tx_pextlist.prototype.backend.mysql

Example

```
backendConfig {  
  
    dataSource {  
        username = t3ry21ptldev  
        password = xxxxxx  
        databaseName = t3ry21ptldev  
    }  
  
    tables (  
        City,  
        Country  
    )  
  
    baseFromClause (  
        Country  
        INNER JOIN City ON City.CountryCode = Country.Code  
        INNER JOIN CountryLanguage ON CountryLanguage.CountryCode = Country.Code  
    )  
  
    baseWhereClause (  
    )  
  
    baseGroupByClause (  
        Country.Code, City.ID  
    )  
}
```

Child elements

datasource, baseFromClause, baseWhereClause, baseGroupByClause,

Name

datasource

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].backendConfig.backendConfig.mysql.datasource

Description

Defines datasource for (MySQL) data backend.

StdWrap: NO

Example

```
dataSource {  
    host = mysql.db.hoster.tld  
    username = funnyrabbit  
    password = xxxxxxxx  
    databaseName = rabbitsdatabase  
}
```

Child elements

host, port, databaseName, username, password,

Name

host

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].backendConfig.backendConfig.mysql.datasource.host

Description

Defines hostname of mysql database server.

Datatype: String

Possible values: All valid addresses for servers (IP-Addresses and URLs)

Default: localhost

StdWrap: NO

Name

port

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].backendConfig.backendConfig.mysql.datasource.port

Description

Port number on which MySQL database server is listening.

Datatype: Int

Possible values: Any valid port number

Default: 3306

StdWrap: NO

Name

databaseName

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].backendConfig.backendConfig.mysql.datasource.databaseName

Description

Name of database to be used for connection.

Datatype: String

Possible values: Any valid database name

StdWrap: NO

Name

username

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].backendConfig.backendConfig.mysql.datasource.username

Description

Username to be used for database connection.

Datatype: String

Possible values: Valid username for MySQL connection.

StdWrap: NO

Name

password

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].backendConfig.backendConfig.mysql.datasource.password

Description

Password to be used for database connection.

Datatype: String

Possible values: Any valid password.

StdWrap: NO

Name

baseFromClause

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].backendConfig.backendConfig.mysql.baseFromClause

Description

Holds the FROM clause of a mysql query without the FROM keyword.

Datatype: String

StdWrap: YES

Example

```
static_countries  
LEFT JOIN static_territories AS st_subcontinent ON (static_countries.cn_parent_
```


Name

baseWhereClause

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].backendConfig.backendConfig.mysql.baseWhereClause

Description

Holds the WHERE clause of a mysql query without the WHERE keyword.

StdWrap: NO

Example

```
st_continent.tr_name_en [] ''
```

Name

baseGroupByClause

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].backendConfig.backendConfig.mysql.baseGroupByClause

Description

Holds the GROUP BY clause of a mysql query without the GROUP BY keyword.

Datatype: String

StdWrap: YES

Example

st_continent

Name

backendConfig.typo3

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].backendConfig.backendConfig.typo3

Description

Typo3 Backend. Inherits the Features from the MySQL Backend but the datasource is already configured. The Typo3 Backend handles enableFields automatically in where clauses.

StdWrap: NO

Example

```
backendConfig < plugin.tx_ptextlist.prototype.backend.typo3
backendConfig {
    tables (
        static_countries,
        static_territories st_continent,
        static_territories st_subcontinent
    )

    baseFromClause (
        static_countries
        LEFT JOIN static_territories AS st_subcontinent ON (static_countries.cn_parent_id = st_subcontinent.tr_parent_id)
        LEFT JOIN static_territories AS st_continent ON (st_subcontinent.tr_parent_id = st_continent.cn_id)
    )

    baseWhereClause (
        st_continent.tr_name_en <> ''
        AND st_subcontinent.tr_name_en <> ''
    )
}
```

Child elements

tables,

Name

tables

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].backendConfig.backendConfig.typo3.tables

Description

Define tables to be used with enable fields. Typo3 special fields (deleted, hidden) are automatically applied to query.

Datatype: Comma seperated list of table names and aliases (optional).

StdWrap: NO

Example

```
static_countries,  
static_territories st_continent
```

Name

backendConfig.extbase

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].backendConfig.backendConfig.extbase

Description

Extbase Repository Backend.

StdWrap: NO

Prototype: plugin.tx_ptextlist.prototype.backend.extbase

Name

fields

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].fields

Description

Defines raw datasource fields, wich can than combined and processed in to table fields.

Datatype: Associative array

StdWrap: NO

Child elements

[yourFieldId],

Name

[yourFieldId]

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].fields.[yourFieldId]

Description

Named definition of a single data field.

Datatype: String

StdWrap: NO

Example

```
name_local {
    table = static_countries
    field = cn_short_local
    isSortable = 1
}
```

Child elements

table, field, special, isSortable, expandGroupRows,

Name

table

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].fields.[yourFieldId].table

Description

The table, this field belongs to.

Datatype: String

StdWrap: NO

Name

field

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].fields.[yourFieldId].field

Description

Name of the tables field.

StdWrap: NO

Name

special

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].fields.[yourFieldId].special

Description

Insert a individual SQL snippet.

StdWrap: NO

Name

isSortable

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].fields.[yourFieldId].isSortable

Description

StdWrap: NO

Name

expandGroupRows

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].fields.[yourFieldId].expandGroupRows

Description

StdWrap: NO

Name

columns

TS-Key:

plugin.tx_pextlist.settings.listConfig.[yourListId].columns

Description

Holds the tables column definitions.

Datatype: Array

StdWrap: NO

Prototype: plugin.tx_pextlist.prototype.column.default

Example

```
10 {  
    label = LLL:EXT:pt_extlist/Configuration/TypoScript/Demolist/locallang.xml:cn_  
    columnIdentifier = cn_short_localColumn  
    fieldIdentifier = cn_short_local  
    isSortable = 1  
}
```

Child elements

10,20,30,

Name

10,20,30

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].columns.10,20,30

Description

StdWrap: NO

Child elements

fieldIdentifier, label, renderUserFunctions, renderTemplate, renderObj, sorting, sortingImageAsc, sortingImageDesc, sortingImageDefault, accessGroups, cellCSSClass,

Name

fieldIdentifier

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].columns.10,20,30.fieldIdentifier

Description

Identifier of a defined field.

StdWrap: NO

Name

label

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].columns.10,20,30.label

Description

A label for this element.

Datatype: String

StdWrap: YES

Name

renderUserFunctions

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].columns.10,20,30.renderUserFunctions

Description

A list of userfunctions to render the field value.

StdWrap: NO

Example

```
renderUserFunctions {  
    10 = EXT:pt_extlist/Resources/Private/UserFunctions/class.tx_ptextlist_demolis  
}
```

Name

renderTemplate

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].columns.10,20,30.renderTemplate

Description

StdWrap: NO

Name

renderObj

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].columns.10,20,30.renderObj

Description

StdWrap: NO

Name

sorting

TS-Key:

plugin.tx_pextlist.settings.listConfig.[yourListId].columns.10,20,30.sorting

Description

Define sorting for this column. A single sorting definition consists either of a fieldidentifier or a fieldidentifier followed by direction. The direction can be fixed with adding a '!' in front of the direction.

Datatype: Seperated list of fieldIdentifiers.

StdWrap: NO

Example

```
// Order by name_local ASC, name_en ASC
sorting = name_local, name_en

// Order by name_local DESC, name_en ASC
sorting = name_local DESC, name_en

// Order by name_local DESC, name_en ASC
// Sorting by name_local is fixed to DESC with the "!" and does not toggle
sorting = name_local !DESC, name_en
```

Name

sortingImageAsc

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].columns.10,20,30.sortingImageAsc

Description

Image for ascending ordered column header.

Default: EXT:pt_extlist/Resources/Public/List/icon_table_sort_asc.png

StdWrap: NO

Name

sortingImageDesc

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].columns.10,20,30.sortingImageDesc

Description

Image for descending ordered column header.

Default: EXT:pt_extlist/Resources/Public/List/icon_table_sort_desc.png

StdWrap: NO

Name

sortingImageDefault

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].columns.10,20,30.sortingImageDefault

Description

Image for unordered column header.

Default: EXT:pt_extlist/Resources/Public/List/icon_table_sort_default.png

StdWrap: NO

Name

accessGroups

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].columns.10,20,30.accessGroups

Description

StdWrap: NO

Name

cellCSSClass

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].columns.10,20,30.cellCSSClass

Description

StdWrap: NO

Name

rendererChain

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].rendererChain

Description

Holds the renderer configuration.

StdWrap: NO

Prototype: plugin.tx_ptextlist.prototype.rendererChain

Child elements

enabled, rendererConfigs,

Name

enabled

TS-Key:

plugin.tx_pextlist.settings.listConfig.[yourListId].rendererChain.enabled

Description

Datatype: Boolean

Possible values: 0,1

Default: 1

StdWrap: NO

Name

rendererConfigs

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].rendererChain.rendererConfigs

Description

A list of chained renderer classes that work on list data structures. The default renderer class uses the column configuration, to render the list of field data in a list of rows and columns. By default this renderer is called at position 100. All defined renderers before 100 work on a field data list, while renderers after 100 work on a column list data structure.

Datatype: Array (10,20,30)

StdWrap: NO

Child elements

[yourNumericRendererId],

Name

[yourNumericRendererId]

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].rendererChain.rendererConfigs.[yourNumericRendererId]

Description

Configuration of a single renderer.

Possible values: 10,20,30

StdWrap: NO

Child elements

renderClassName,

Name

renderClassName

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].rendererChain.rendererConfigs.[yourNumericRendererId].renderCla

Description

The class name of the renderers php class.

Datatype: String

StdWrap: NO

Name

aggregateData

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].aggregateData

Description

Defines aggregates of data fields.

Datatype: Associative array

StdWrap: NO

Child elements

[yourAggregateFieldId],

Name

[yourAggregateFieldId]

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].aggregateData.[yourAggregateFieldId]

Description

Named definition of a single data field.

Datatype: Associative array

StdWrap: NO

Example

```
sumPhone {  
    fieldIdentifier = phone  
    method = sum  
    scope = query  
}
```

Child elements

method, scope,

Name

method

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].aggregateData.[yourAggregateFieldId].method

Description

Defined aggregate methods.

Datatype: String

Possible values: min,max,sum,avg

StdWrap: NO

Name

scope

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].aggregateData.[yourAggregateFieldId].scope

Description

The scope for the aggregation can be either set to the current page or to the whole query. Aggregates for the current page are calculated internally without an additional database query.

Datatype: String

Possible values: page,query

StdWrap: NO

Name

aggregateRows

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].aggregateRows

Description

Holds the aggregates columns definitions.

Datatype: Associative array

Possible values: All columnIdentifiers

StdWrap: NO

Child elements

[yourColumnId],

Name

[yourColumnId]

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].aggregateRows.[yourColumnId]

Description

StdWrap: NO

Child elements

aggregateDataIdentifier,

Name

aggregateDataIdentifier

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].aggregateRows.[yourColumnId].aggregateDataIdentifier

Description

Datatype: String

StdWrap: NO

Name

filters

TS-Key:

plugin.tx_pextlist.settings.listConfig.[yourListId].filters

Description

Holds all filterbox configurations.

Datatype: Associative array

StdWrap: NO

Child elements

[yourFilterBoxId],

Name

[yourFilterBoxId]

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId]

Description

StdWrap: NO

Prototype: plugin.tx_ptextlist.prototype.filterBox

Child elements

showReset, showSubmit, filterConfigs,

Name

showReset

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].showReset

Description

Show a reset link for all filters of this filterBox.

Datatype: Boolean

Possible values: 0,1

Default: 1

StdWrap: NO

Name

showSubmit

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].showSubmit

Description

Show a submit button for this filterBox.

Datatype: Boolean

Possible values: 0,1

Default: 1

StdWrap: NO

Name

filterConfigs

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs

Description

Holds the configuration of the filters of this filter box.

Datatype: Array

Possible values: 10,20,30...

StdWrap: NO

Child elements

[yourNumericFilterId],

Name

[yourNumericFilterId]

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId]

Description

StdWrap: NO

Variants

String, Select, Checkbox, radiobutton, firstletter, Proxy,

Variants of [yourNumericFilterId]:

Name

String

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].String

Description

Shows a string filter.

StdWrap: NO

Prototype: plugin.tx_ptextlist.prototype.filter.string

Example

```
10 < plugin.tx_ptextlist.prototype.filter.string
10 {
    filterIdentifier = firstNameSearch
    label = Firstname
    fieldIdentifier = firstName
}
```

Child elements

filterIdentifier, label, defaultValue, accessGroups, filterClassName, partialPath, invert, invertable,

Name

filterIdentifier

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].String.

Description

The unique identifier of this filter.

Datatype: String

StdWrap: NO

Name

label

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].String.

Description

The label wich is displayed beside the filter.

Datatype: String

StdWrap: NO

Name

defaultValue

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].String.

Description

The default value which is shown or selected by default.

Datatype: String

StdWrap: NO

Name

accessGroups

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].String.

Description

Comma separated list of user groups wich have access to this filter.

Datatype: Comma eparated list.

Possible values: Typo3 Group Ids

StdWrap: NO

Name

filterClassName

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].String.

Description

Name of the PHP Class of this filter.

Datatype: String

StdWrap: NO

Example

Tx_PtExtlist_Domain_Model_Filter_StringFilter

Name

partialPath

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].String.

Description

StdWrap: NO

Name

invert

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].String.

Description

Invert the constraint of this filter.

Datatype: Boolean

Possible values: 0,1

Default: 0

StdWrap: NO

Name

invertable

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].String.

Description

Show a controle to invert this filter.

Datatype: Boolean

Possible values: 0,1

Default: 0

StdWrap: NO

Name

Select

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].Select

Description

StdWrap: NO

Prototype: plugin.tx_ptextlist.prototype.filter.select

Child elements

filterIdentifier, fieldIdentifier, label, partialPath, filterClassName, defaultValue, accessGroups, invert, invertable, displayFields, multiple, excludeFilters, showRowCount, submitOnChange, inactiveOption, inactiveValue,

Name

filterIdentifier

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].Select.

Description

The unique identifier of this filter.

Datatype: String

StdWrap: NO

Name

fieldIdentifier

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].Select.

Description

Identifier of a defined data field. The filter affects on this data field.

Datatype: String

StdWrap: NO

Name

label

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].Select.

Description

The label wich is displayed beside the filter.

Datatype: String

StdWrap: NO

Name

partialPath

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].Select.

Description

StdWrap: NO

Name

filterClassName

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].Select.

Description

Name of the PHP Class of this filter.

Datatype: String

StdWrap: NO

Example

Tx_PtExtlist_Domain_Model_Filter_StringFilter

Name

defaultValue

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].Select.

Description

The default value which is shown or selected by default.

Datatype: String

StdWrap: NO

Name

accessGroups

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].Select.

Description

Comma separated list of user groups wich have access to this filter.

Datatype: Comma eparated list.

Possible values: Typo3 Group Ids

StdWrap: NO

Name

invert

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].Select.

Description

Invert the constraint of this filter.

Datatype: Boolean

Possible values: 0,1

Default: 0

StdWrap: NO

Name

invertable

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].Select.

Description

Show a controle to invert this filter.

Datatype: Boolean

Possible values: 0,1

Default: 0

StdWrap: NO

Name

displayFields

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].Select.

Description

One or multiple identifiers of previously defined data fields.

Datatype: String / Comma separated list

Possible values: Previously defined field identifier.

Default: If not set, the field defined in fieldIdentifier is used.

StdWrap: NO

Name

multiple

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].Select.

Description

Datatype: Boolean

Possible values: 0,1

Default: 0

StdWrap: NO

Name

excludeFilters

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].Select.

Description

List of filters that are not considered for the group query of this filter.

Datatype: String / Comma separated list of filterIdentifiers.

StdWrap: NO

Name

showRowCount

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].Select.

Description

Show the rowcount if the select filter is filled with grouped data.

Datatype: Boolean

Possible values: 0,1

Default: 1

StdWrap: NO

Name

submitOnChange

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].Select.

Description

Instant submit filter if a value is selected.

Datatype: Boolean

Possible values: 0,1

Default: 0

StdWrap: NO

Name

inactiveOption

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].Select.

Description

Label of an option that is added to the select list. If this option is selected, the filter is inactive.

Datatype: String

StdWrap: NO

Name

inactiveValue

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].Select.

Description

The submitted value for the inactiveOption described above.

Datatype: String

StdWrap: NO

Name

Checkbox

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].Check

Description

StdWrap: NO

Prototype: plugin.tx_ptextlist.prototype.filter.checkbox

Child elements

filterIdentifier, fieldIdentifier, label, partialPath, filterClassName, defaultValue, accessGroups, invert, invertable, displayFields, multiple, excludeFilters, showRowCount, submitOnChange, inactiveOption, inactiveValue,

Name

filterIdentifier

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].Check

Description

The unique identifier of this filter.

Datatype: String

StdWrap: NO

Name

fieldIdentifier

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].Check

Description

Identifier of a defined data field. The filter affects on this data field.

Datatype: String

StdWrap: NO

Name

label

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].Check

Description

The label wich is displayed beside the filter.

Datatype: String

StdWrap: NO

Name

partialPath

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].Check

Description

StdWrap: NO

Name

filterClassName

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].Check

Description

Name of the PHP Class of this filter.

Datatype: String

StdWrap: NO

Example

Tx_PtExtlist_Domain_Model_Filter_StringFilter

Name

defaultValue

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].Check

Description

The default value which is shown or selected by default.

Datatype: String

StdWrap: NO

Name

accessGroups

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].Check

Description

Comma separated list of user groups wich have access to this filter.

Datatype: Comma eparated list.

Possible values: Typo3 Group Ids

StdWrap: NO

Name

invert

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].Check

Description

Invert the constraint of this filter.

Datatype: Boolean

Possible values: 0,1

Default: 0

StdWrap: NO

Name

invertable

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].Check

Description

Show a controle to invert this filter.

Datatype: Boolean

Possible values: 0,1

Default: 0

StdWrap: NO

Name

displayFields

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].Check

Description

One or multiple identifiers of previously defined data fields.

Datatype: String / Comma separated list

Possible values: Previously defined field identifier.

Default: If not set, the field defined in fieldIdentifier is used.

StdWrap: NO

Name

multiple

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].Check

Description

Datatype: Boolean

Possible values: 0,1

Default: 0

StdWrap: NO

Name

excludeFilters

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].Check

Description

List of filters that are not considered for the group query of this filter.

Datatype: String / Comma separated list of filterIdentifiers.

StdWrap: NO

Name

showRowCount

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].Check

Description

Show the rowcount if the select filter is filled with grouped data.

Datatype: Boolean

Possible values: 0,1

Default: 1

StdWrap: NO

Name

submitOnChange

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].Check

Description

Instant submit filter if a value is selected.

Datatype: Boolean

Possible values: 0,1

Default: 0

StdWrap: NO

Name

inactiveOption

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].Check

Description

Label of an option that is added to the select list. If this option is selected, the filter is inactive.

Datatype: String

StdWrap: NO

Name

inactiveValue

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].Check

Description

The submitted value for the inactiveOption described above.

Datatype: String

StdWrap: NO

Name

radiobutton

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].radiob

Description

StdWrap: NO

Prototype: plugin.tx_ptextlist.prototype.filter.checkbox

Child elements

filterIdentifier, fieldIdentifier, label, partialPath, filterClassName, defaultValue, accessGroups, invert, invertable, displayFields, multiple, excludeFilters, showRowCount, submitOnChange, inactiveOption, inactiveValue,

Name

filterIdentifier

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].radiob

Description

The unique identifier of this filter.

Datatype: String

StdWrap: NO

Name

fieldIdentifier

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].radiob

Description

Identifier of a defined data field. The filter affects on this data field.

Datatype: String

StdWrap: NO

Name

label

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].radiob

Description

The label wich is displayed beside the filter.

Datatype: String

StdWrap: NO

Name

partialPath

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].radiob

Description

StdWrap: NO

Name

filterClassName

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].radiob

Description

Name of the PHP Class of this filter.

Datatype: String

StdWrap: NO

Example

Tx_PtExtlist_Domain_Model_Filter_StringFilter

Name

defaultValue

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].radiob

Description

The default value which is shown or selected by default.

Datatype: String

StdWrap: NO

Name

accessGroups

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].radiob

Description

Comma separated list of user groups wich have access to this filter.

Datatype: Comma eparated list.

Possible values: Typo3 Group Ids

StdWrap: NO

Name

invert

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].radiob

Description

Invert the constraint of this filter.

Datatype: Boolean

Possible values: 0,1

Default: 0

StdWrap: NO

Name

invertable

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].radiob

Description

Show a controle to invert this filter.

Datatype: Boolean

Possible values: 0,1

Default: 0

StdWrap: NO

Name

displayFields

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].radiob

Description

One or multiple identifiers of previously defined data fields.

Datatype: String / Comma separated list

Possible values: Previously defined field identifier.

Default: If not set, the field defined in fieldIdentifier is used.

StdWrap: NO

Name

multiple

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].radiob

Description

Datatype: Boolean

Possible values: 0,1

Default: 0

StdWrap: NO

Name

excludeFilters

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].radiob

Description

List of filters that are not considered for the group query of this filter.

Datatype: String / Comma separated list of filterIdentifiers.

StdWrap: NO

Name

showRowCount

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].radiob

Description

Show the rowcount if the select filter is filled with grouped data.

Datatype: Boolean

Possible values: 0,1

Default: 1

StdWrap: NO

Name

submitOnChange

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].radiob

Description

Instant submit filter if a value is selected.

Datatype: Boolean

Possible values: 0,1

Default: 0

StdWrap: NO

Name

inactiveOption

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].radiob

Description

Label of an option that is added to the select list. If this option is selected, the filter is inactive.

Datatype: String

StdWrap: NO

Name

inactiveValue

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].radiob

Description

The submitted value for the inactiveOption described above.

Datatype: String

StdWrap: NO

Name

firstletter

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].firstletter

Description

StdWrap: NO

Prototype: plugin.tx_ptextlist.prototype.filter.firstletter

Child elements

filterIdentifier, fieldIdentifier, label, partialPath, filterClassName, defaultValue, accessGroups, invert, invertable, displayFields, multiple, excludeFilters, showRowCount, submitOnChange, inactiveOption, inactiveValue,

Name

filterIdentifier

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].firstlet

Description

The unique identifier of this filter.

Datatype: String

StdWrap: NO

Name

fieldIdentifier

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].firstlet

Description

Identifier of a defined data field. The filter affects on this data field.

Datatype: String

StdWrap: NO

Name

label

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].firstlet

Description

The label wich is displayed beside the filter.

Datatype: String

StdWrap: NO

Name

partialPath

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].firstlet

Description

StdWrap: NO

Name

filterClassName

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].firstlet

Description

Name of the PHP Class of this filter.

Datatype: String

StdWrap: NO

Example

Tx_PtExtlist_Domain_Model_Filter_StringFilter

Name

defaultValue

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].firstlet

Description

The default value which is shown or selected by default.

Datatype: String

StdWrap: NO

Name

accessGroups

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].firstlet

Description

Comma separated list of user groups wich have access to this filter.

Datatype: Comma eparated list.

Possible values: Typo3 Group Ids

StdWrap: NO

Name

invert

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].firstlet

Description

Invert the constraint of this filter.

Datatype: Boolean

Possible values: 0,1

Default: 0

StdWrap: NO

Name

invertable

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].firstlet

Description

Show a controle to invert this filter.

Datatype: Boolean

Possible values: 0,1

Default: 0

StdWrap: NO

Name

displayFields

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].firstlet

Description

One or multiple identifiers of previously defined data fields.

Datatype: String / Comma separated list

Possible values: Previously defined field identifier.

Default: If not set, the field defined in fieldIdentifier is used.

StdWrap: NO

Name

multiple

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].firstlet

Description

Datatype: Boolean

Possible values: 0,1

Default: 0

StdWrap: NO

Name

excludeFilters

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].firstlet

Description

List of filters that are not considered for the group query of this filter.

Datatype: String / Comma separated list of filterIdentifiers.

StdWrap: NO

Name

showRowCount

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].firstlet

Description

Show the rowcount if the select filter is filled with grouped data.

Datatype: Boolean

Possible values: 0,1

Default: 1

StdWrap: NO

Name

submitOnChange

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].firstlet

Description

Instant submit filter if a value is selected.

Datatype: Boolean

Possible values: 0,1

Default: 0

StdWrap: NO

Name

inactiveOption

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].firstlet

Description

Label of an option that is added to the select list. If this option is selected, the filter is inactive.

Datatype: String

StdWrap: NO

Name

inactiveValue

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].firstlet

Description

The submitted value for the inactiveOption described above.

Datatype: String

StdWrap: NO

Name

Proxy

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].Proxy

Description

A proxy filter is not displayed. It uses a filter from an other list defined by the proxy path and sets the result constraint to the given field.

StdWrap: NO

Prototype: plugin.tx_ptextlist.prototype.filter.proxy

Child elements

proxyPath,

Name

proxyPath

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].Proxy.

Description

Path to a filter from an other list. The path has the format [listId].[filterBoxId].[filterId]

Datatype: String

StdWrap: NO

Child elements

filterIdentifier, defaultValue, label, accessGroups, filterClassName, partialPath, invert,

Name

filterIdentifier

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].filterId

Description

The unique identifier of this filter.

Datatype: String

StdWrap: NO

Name

defaultValue

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].default

Description

The default value which is shown or selected by default.

Datatype: String

StdWrap: NO

Name

label

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].label

Description

The label wich is displayed beside the filter.

Datatype: String

StdWrap: NO

Name

accessGroups

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].access

Description

Comma separated list of user groups wich have access to this filter.

Datatype: Comma eparated list.

Possible values: Typo3 Group Ids

StdWrap: NO

Name

filterClassName

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].filterC

Description

Name of the PHP Class of this filter.

Datatype: String

StdWrap: NO

Example

Tx_PtExtlist_Domain_Model_Filter_StringFilter

Name

partialPath

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].partial

Description

StdWrap: NO

Name

invert

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].filters.[yourFilterBoxId].filterConfigs.[yourNumericFilterId].invert

Description

Invert the constraint of this filter.

Datatype: Boolean

Possible values: 0,1

Default: 0

StdWrap: NO

Name

headerPartial

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].headerPartial

Description

Path to the header partial.

Datatype: String

StdWrap: NO

Name

bodyPartial

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].bodyPartial

Description

Path to the body partial.

Datatype: String

StdWrap: NO

Name

agregateRowsPartial

TS-Key:

plugin.tx_ptextlist.settings.listConfig.[yourListId].agregateRowsPartial

Description

Path to the aggregate row partial.

Datatype: String

StdWrap: NO