

Computability and Complexity

Lecture 5

Reductions

Undecidable problems from language theory

Linear bounded automata

given by Jiri Srba

Informal Definition

A problem A is reducible to problem B iff the solution to problem B can be used to solve the problem A .

This means that solving A cannot be more difficult than solving B .

Informal Definition

A problem A is reducible to problem B iff the solution to problem B can be used to solve the problem A .

This means that solving A cannot be more difficult than solving B .

In the terms of computability theory:

A reduces to B means that

- if B is decidable then A is decidable too, and
- if A is undecidable then B is undecidable too.

The way we will use reducibility:

If we can reduce e.g. A_{TM} to some other problem (language) B , then B is undecidable.

Typical Proof Structure to Show Undecidability

We want to show that a language B is undecidable using the fact that we already know that the language A is undecidable.

Proof idea (proof by contradiction):

- 1 Assume for a while that we have a decider M_B for the language B .
- 2 Using M_B we construct a decider M_A for the language A .
- 3 Because we know that M_A cannot exist (A is undecidable), this implies that M_B cannot exist either.
- 4 Conclusion is that the language B is undecidable.

Typical Proof Structure to Show Undecidability

We want to show that a language B is undecidable using the fact that we already know that the language A is undecidable.

Proof idea (proof by contradiction):

- 1 Assume for a while that we have a decider M_B for the language B .
- 2 Using M_B we construct a decider M_A for the language A .
- 3 Because we know that M_A cannot exist (A is undecidable), this implies that M_B cannot exist either.
- 4 Conclusion is that the language B is undecidable.

In the proof we provided a reduction from an undecidable language A to the language B . Hence B is undecidable too.

The Language $HALT_{TM}$

Problem: "Given a TM M and a string w , does M halt on w ?"

Language formulation

$$HALT_{TM} \stackrel{\text{def}}{=} \{ \langle M, w \rangle \mid M \text{ is a TM and } M \text{ halts on the input } w \}$$

The Language $HALT_{TM}$

Problem: "Given a TM M and a string w , does M halt on w ?"

Language formulation

$$HALT_{TM} \stackrel{\text{def}}{=} \{ \langle M, w \rangle \mid M \text{ is a TM and } M \text{ halts on the input } w \}$$

Theorem

The language $HALT_{TM}$ is undecidable.

Proof: We reduce A_{TM} to $HALT_{TM}$.

Undecidability of $HALT_{TM}$ by Reduction from A_{TM}

$A_{TM} \stackrel{\text{def}}{=} \{ \langle M, w \rangle \mid M \text{ is a TM and } M \text{ accepts the input } w \}$

$HALT_{TM} \stackrel{\text{def}}{=} \{ \langle M, w \rangle \mid M \text{ is a TM and } M \text{ halts on the input } w \}$

- 1 By contradiction. Assume there is a decider R for $HALT_{TM}$.

Undecidability of $HALT_{TM}$ by Reduction from A_{TM}

$A_{TM} \stackrel{\text{def}}{=} \{ \langle M, w \rangle \mid M \text{ is a TM and } M \text{ accepts the input } w \}$

$HALT_{TM} \stackrel{\text{def}}{=} \{ \langle M, w \rangle \mid M \text{ is a TM and } M \text{ halts on the input } w \}$

- 1 By contradiction. Assume there is a decider R for $HALT_{TM}$.
- 2 Using the decider R , we construct a decider S for A_{TM} :

$S =$ " On input $\langle M, w \rangle$:

1. Run R on $\langle M, w \rangle$.
2. If R rejected then S rejects.
3. If R accepted then simulate M on w .
4. If M accepted then S accepts, else
If M rejected then S rejects. "

Undecidability of $HALT_{TM}$ by Reduction from A_{TM}

$A_{TM} \stackrel{\text{def}}{=} \{ \langle M, w \rangle \mid M \text{ is a TM and } M \text{ accepts the input } w \}$

$HALT_{TM} \stackrel{\text{def}}{=} \{ \langle M, w \rangle \mid M \text{ is a TM and } M \text{ halts on the input } w \}$

- 1 By contradiction. Assume there is a decider R for $HALT_{TM}$.
- 2 Using the decider R , we construct a decider S for A_{TM} :

$S =$ " On input $\langle M, w \rangle$:

1. Run R on $\langle M, w \rangle$.
2. If R rejected then S rejects.
3. If R accepted then simulate M on w .
4. If M accepted then S accepts, else
If M rejected then S rejects. "

- 3 So S is a decider for A_{TM} , but we know that S does not exist.

Undecidability of $HALT_{TM}$ by Reduction from A_{TM}

$A_{TM} \stackrel{\text{def}}{=} \{ \langle M, w \rangle \mid M \text{ is a TM and } M \text{ accepts the input } w \}$

$HALT_{TM} \stackrel{\text{def}}{=} \{ \langle M, w \rangle \mid M \text{ is a TM and } M \text{ halts on the input } w \}$

- ❶ By contradiction. Assume there is a decider R for $HALT_{TM}$.
- ❷ Using the decider R , we construct a decider S for A_{TM} :

$S =$ " On input $\langle M, w \rangle$:

1. Run R on $\langle M, w \rangle$.
2. If R rejected then S rejects.
3. If R accepted then simulate M on w .
4. If M accepted then S accepts, else
If M rejected then S rejects. "

- ❸ So S is a decider for A_{TM} , but we know that S does not exist.
- ❹ Conclusion: the decider R does not exist either and so $HALT_{TM}$ is undecidable. □

The Language E_{TM}

Problem: "Given a TM M is the language of M empty?"

Language formulation

$$E_{TM} \stackrel{\text{def}}{=} \{ \langle M \rangle \mid M \text{ is a TM such that } L(M) = \emptyset \}$$

The Language E_{TM}

Problem: "Given a TM M is the language of M empty?"

Language formulation

$$E_{TM} \stackrel{\text{def}}{=} \{ \langle M \rangle \mid M \text{ is a TM such that } L(M) = \emptyset \}$$

Theorem

The language E_{TM} is undecidable.

Proof: We reduce A_{TM} to E_{TM} .

Undecidability of E_{TM} by Reduction from A_{TM}

$$A_{TM} \stackrel{\text{def}}{=} \{ \langle M, w \rangle \mid M \text{ is a TM and } M \text{ accepts the input } w \}$$

$$E_{TM} \stackrel{\text{def}}{=} \{ \langle M \rangle \mid M \text{ is a TM such that } L(M) = \emptyset \}$$

- 1 By contradiction. Assume there is a decider R for E_{TM} .

Undecidability of E_{TM} by Reduction from A_{TM}

$A_{TM} \stackrel{\text{def}}{=} \{ \langle M, w \rangle \mid M \text{ is a TM and } M \text{ accepts the input } w \}$

$E_{TM} \stackrel{\text{def}}{=} \{ \langle M \rangle \mid M \text{ is a TM such that } L(M) = \emptyset \}$

- ① By contradiction. Assume there is a decider R for E_{TM} .
- ② Using the decider R , we construct a decider S for A_{TM} :

$S =$ " On input $\langle M, w \rangle$:

1. Using M and w construct the following TM M_1

$M_1 =$ " On input x :

1. If $x \neq w$ then M_1 rejects
2. If $x = w$ then simulate M on w .
If M accepted then M_1 accepts,
if M rejected then M_1 rejects."

2. Run R on $\langle M_1 \rangle$.
3. If R accepted, S rejects; if R rejected, S accepts. "

Undecidability of E_{TM} by Reduction from A_{TM}

$A_{TM} \stackrel{\text{def}}{=} \{ \langle M, w \rangle \mid M \text{ is a TM and } M \text{ accepts the input } w \}$

$E_{TM} \stackrel{\text{def}}{=} \{ \langle M \rangle \mid M \text{ is a TM such that } L(M) = \emptyset \}$

- ① By contradiction. Assume there is a decider R for E_{TM} .
- ② Using the decider R , we construct a decider S for A_{TM} :

$S =$ " On input $\langle M, w \rangle$:

1. Using M and w construct the following TM M_1

$M_1 =$ " On input x :

1. If $x \neq w$ then M_1 rejects
2. If $x = w$ then simulate M on w .
If M accepted then M_1 accepts,
if M rejected then M_1 rejects."

2. Run R on $\langle M_1 \rangle$.

3. If R accepted, S rejects; if R rejected, S accepts. "

- ③ So S is a decider for A_{TM} , but we know that S does not exist.

Undecidability of E_{TM} by Reduction from A_{TM}

$A_{TM} \stackrel{\text{def}}{=} \{ \langle M, w \rangle \mid M \text{ is a TM and } M \text{ accepts the input } w \}$

$E_{TM} \stackrel{\text{def}}{=} \{ \langle M \rangle \mid M \text{ is a TM such that } L(M) = \emptyset \}$

- ① By contradiction. Assume there is a decider R for E_{TM} .
- ② Using the decider R , we construct a decider S for A_{TM} :

$S =$ " On input $\langle M, w \rangle$:

1. Using M and w construct the following TM M_1

$M_1 =$ " On input x :

1. If $x \neq w$ then M_1 rejects
2. If $x = w$ then simulate M on w .
If M accepted then M_1 accepts,
if M rejected then M_1 rejects."

2. Run R on $\langle M_1 \rangle$.

3. If R accepted, S rejects; if R rejected, S accepts. "

- ③ So S is a decider for A_{TM} , but we know that S does not exist.
- ④ Conclusion: R cannot exist and hence E_{TM} is undecidable. \square

The Language EQ_{TM}

Problem: "Given two TMs M_1 and M_2 , do they recognize the same language?"

Language formulation

$$EQ_{TM} \stackrel{\text{def}}{=} \{ \langle M_1, M_2 \rangle \mid M_1 \text{ and } M_2 \text{ are TMs s.t. } L(M_1) = L(M_2) \}$$

The Language EQ_{TM}

Problem: "Given two TMs M_1 and M_2 , do they recognize the same language?"

Language formulation

$$EQ_{TM} \stackrel{\text{def}}{=} \{ \langle M_1, M_2 \rangle \mid M_1 \text{ and } M_2 \text{ are TMs s.t. } L(M_1) = L(M_2) \}$$

Theorem

The language EQ_{TM} is undecidable.

Proof: We reduce E_{TM} to EQ_{TM} .

Undecidability of EQ_{TM} by Reduction from E_{TM}

$$EQ_{TM} \stackrel{\text{def}}{=} \{ \langle M_1, M_2 \rangle \mid M_1 \text{ and } M_2 \text{ are TMs s.t. } L(M_1) = L(M_2) \}$$

$$E_{TM} \stackrel{\text{def}}{=} \{ \langle M \rangle \mid M \text{ is a TM such that } L(M) = \emptyset \}$$

- 1 By contradiction. Assume there is a decider R for EQ_{TM} .

Undecidability of EQ_{TM} by Reduction from E_{TM}

$EQ_{TM} \stackrel{\text{def}}{=} \{ \langle M_1, M_2 \rangle \mid M_1 \text{ and } M_2 \text{ are TMs s.t. } L(M_1) = L(M_2) \}$

$E_{TM} \stackrel{\text{def}}{=} \{ \langle M \rangle \mid M \text{ is a TM such that } L(M) = \emptyset \}$

- ① By contradiction. Assume there is a decider R for EQ_{TM} .
- ② Using the decider R , we construct a decider S for E_{TM} :

$S =$ " On input $\langle M \rangle$:

1. Let M_1 be a TM that rejects all inputs.
2. Run R on $\langle M, M_1 \rangle$.
3. If R accepted, S accepts; if R rejected, S rejects. "

Undecidability of EQ_{TM} by Reduction from E_{TM}

$$EQ_{TM} \stackrel{\text{def}}{=} \{ \langle M_1, M_2 \rangle \mid M_1 \text{ and } M_2 \text{ are TMs s.t. } L(M_1) = L(M_2) \}$$
$$E_{TM} \stackrel{\text{def}}{=} \{ \langle M \rangle \mid M \text{ is a TM such that } L(M) = \emptyset \}$$

- ① By contradiction. Assume there is a decider R for EQ_{TM} .
- ② Using the decider R , we construct a decider S for E_{TM} :

$S =$ " On input $\langle M \rangle$:

1. Let M_1 be a TM that rejects all inputs.
2. Run R on $\langle M, M_1 \rangle$.
3. If R accepted, S accepts; if R rejected, S rejects. "

- ③ So S is a decider for E_{TM} , but we know that S does not exist.

Undecidability of EQ_{TM} by Reduction from E_{TM}

$$EQ_{TM} \stackrel{\text{def}}{=} \{ \langle M_1, M_2 \rangle \mid M_1 \text{ and } M_2 \text{ are TMs s.t. } L(M_1) = L(M_2) \}$$
$$E_{TM} \stackrel{\text{def}}{=} \{ \langle M \rangle \mid M \text{ is a TM such that } L(M) = \emptyset \}$$

- ① By contradiction. Assume there is a decider R for EQ_{TM} .
- ② Using the decider R , we construct a decider S for E_{TM} :

$S =$ " On input $\langle M \rangle$:

1. Let M_1 be a TM that rejects all inputs.
2. Run R on $\langle M, M_1 \rangle$.
3. If R accepted, S accepts; if R rejected, S rejects. "

- ③ So S is a decider for E_{TM} , but we know that S does not exist.
- ④ Conclusion: R cannot exist and so EQ_{TM} is undecidable. \square

The Language $REGULAR_{TM}$

Problem: "Given a TM M , is $L(M)$ regular?"

Language formulation

$$REGULAR_{TM} \stackrel{\text{def}}{=} \{ \langle M \rangle \mid M \text{ is a TM s.t. } L(M) \text{ is regular} \}$$

The Language $REGULAR_{TM}$

Problem: "Given a TM M , is $L(M)$ regular?"

Language formulation

$$REGULAR_{TM} \stackrel{\text{def}}{=} \{ \langle M \rangle \mid M \text{ is a TM s.t. } L(M) \text{ is regular} \}$$

Theorem

The language $REGULAR_{TM}$ is undecidable.

Proof: We reduce A_{TM} to $REGULAR_{TM}$.

Undecidability of $REGULAR_{TM}$ by Reduction from A_{TM}

$A_{TM} \stackrel{\text{def}}{=} \{ \langle M, w \rangle \mid M \text{ is a TM such that } M \text{ accepts } w \}$

$REGULAR_{TM} \stackrel{\text{def}}{=} \{ \langle M \rangle \mid M \text{ is a TM such that } L(M) \text{ is regular} \}$

- 1 By contradiction. Assume a decider R for $REGULAR_{TM}$.

Undecidability of $REGULAR_{TM}$ by Reduction from A_{TM}

$A_{TM} \stackrel{\text{def}}{=} \{ \langle M, w \rangle \mid M \text{ is a TM such that } M \text{ accepts } w \}$

$REGULAR_{TM} \stackrel{\text{def}}{=} \{ \langle M \rangle \mid M \text{ is a TM such that } L(M) \text{ is regular} \}$

- ❶ By contradiction. Assume a decider R for $REGULAR_{TM}$.
- ❷ Using the decider R , we construct a decider S for A_{TM} :

$S =$ " On input $\langle M, w \rangle$:

1. Construct the following TM M_1 :

$M_1 =$ "On input x :

1. If x of the form $0^n 1^n$ then M_1 accepts, else
2. run M on w and M_1 accepts iff M accepted."
2. Run R on $\langle M_1 \rangle$.
3. If R accepted, S accepts; if R rejected, S rejects."

Undecidability of $REGULAR_{TM}$ by Reduction from A_{TM}

$A_{TM} \stackrel{\text{def}}{=} \{ \langle M, w \rangle \mid M \text{ is a TM such that } M \text{ accepts } w \}$

$REGULAR_{TM} \stackrel{\text{def}}{=} \{ \langle M \rangle \mid M \text{ is a TM such that } L(M) \text{ is regular} \}$

- ❶ By contradiction. Assume a decider R for $REGULAR_{TM}$.
- ❷ Using the decider R , we construct a decider S for A_{TM} :

$S =$ " On input $\langle M, w \rangle$:

1. Construct the following TM M_1 :

$M_1 =$ "On input x :

1. If x of the form $0^n 1^n$ then M_1 accepts, else
2. run M on w and M_1 accepts iff M accepted."
2. Run R on $\langle M_1 \rangle$.
3. If R accepted, S accepts; if R rejected, S rejects."

- ❸ So S is a decider for A_{TM} , but we know that S does not exist.

Undecidability of $REGULAR_{TM}$ by Reduction from A_{TM}

$A_{TM} \stackrel{\text{def}}{=} \{ \langle M, w \rangle \mid M \text{ is a TM such that } M \text{ accepts } w \}$

$REGULAR_{TM} \stackrel{\text{def}}{=} \{ \langle M \rangle \mid M \text{ is a TM such that } L(M) \text{ is regular} \}$

- ① By contradiction. Assume a decider R for $REGULAR_{TM}$.
- ② Using the decider R , we construct a decider S for A_{TM} :

$S =$ " On input $\langle M, w \rangle$:

1. Construct the following TM M_1 :

$M_1 =$ "On input x :

1. If x of the form $0^n 1^n$ then M_1 accepts, else
2. run M on w and M_1 accepts iff M accepted."
2. Run R on $\langle M_1 \rangle$.
3. If R accepted, S accepts; if R rejected, S rejects."

- ③ So S is a decider for A_{TM} , but we know that S does not exist.
- ④ So R cannot exist and $REGULAR_{TM}$ is undecidable. □

Linear Bounded Automaton

Idea:

- Limit the memory (tape cells) of a TM.
- The available memory is proportional (by a constant factor) to the length of the input string.

Linear Bounded Automaton

Idea:

- Limit the memory (tape cells) of a TM.
- The available memory is proportional (by a constant factor) to the length of the input string.

Definition

Linear bounded automaton (LBA) is a restricted Turing machine M such that when M runs on any input string w , its head always stays within the first $|w|$ cells (should the head move to the right of the string, it stays at the end instead).

Linear Bounded Automaton

Idea:

- Limit the memory (tape cells) of a TM.
- The available memory is proportional (by a constant factor) to the length of the input string.

Definition

Linear bounded automaton (LBA) is a restricted Turing machine M such that when M runs on any input string w , its head always stays within the first $|w|$ cells (should the head move to the right of the string, it stays at the end instead).

Lemma

Let M be an LBA with q states and g tape symbols. When M is run on w then there are at most $q \cdot g^n$ distinct configurations of M where $n = |w|$.

Linear Bounded Automaton

Idea:

- Limit the memory (tape cells) of a TM.
- The available memory is proportional (by a constant factor) to the length of the input string.

Definition

Linear bounded automaton (LBA) is a restricted Turing machine M such that when M runs on any input string w , its head always stays within the first $|w|$ cells (should the head move to the right of the string, it stays at the end instead).

Lemma

Let M be an LBA with q states and g tape symbols. When M is run on w then there are at most qng^n distinct configurations of M where $n = |w|$.

Acceptance Problem of Linear Bounded Automaton

Problem: "Does a given LBA accept a given string?"

Language formulation

$$A_{LBA} \stackrel{\text{def}}{=} \{ \langle M, w \rangle \mid M \text{ is an LBA such that } M \text{ accepts } w \}$$

Acceptance Problem of Linear Bounded Automaton

Problem: "Does a given LBA accept a given string?"

Language formulation

$$A_{LBA} \stackrel{\text{def}}{=} \{ \langle M, w \rangle \mid M \text{ is an LBA such that } M \text{ accepts } w \}$$

Theorem

The language A_{LBA} is decidable.

Proof: The following algorithm decides A_{LBA} :

"On input $\langle M, w \rangle$ where M is an LBA and w a string:

1. Simulate M on w for at most $q \cdot |w| \cdot g^{|w|}$ steps where q is the number of states in M , and g the number of tape symbols in M .
2. If M accepted, then accept.
If M rejected, then reject.
If M did not halt (in $q \cdot |w| \cdot g^{|w|}$ steps), then reject."



- Notion of reduction from problem A to problem B .
- Undecidability proofs using the reduction.
- Linear bounded automata: definition, decidability of the acceptance problem.