

Benjamin Haase

425-773-1586 | haase.t.benjamin@gmail.com | [linkedin.com/in/benjamin-t-haase-ee/](https://www.linkedin.com/in/benjamin-t-haase-ee/) | <https://benjaminhaaset.github.io>

EDUCATION

University of Washington Bothell

Bothell, WA

Bachelor of Science in Electrical Engineering | GPA: 3.98/4.0

Expected June 2028

Relevant Coursework: Intro to Power Electronics (In Progress), Analog Circuits (In Progress)

TECHNICAL SKILLS

Hardware & PCB: Altium Designer, KiCad, Schematic Capture, PCB Layout, Component Selection

Embedded Systems: Bare-metal C, STM32 Microcontrollers, OpenOCD, GDB, SPI, I2C

Software & Tools: LTspice, Git/Github, Power Supplies, Oscilloscopes, Digital Multimeters, Function Generators

Familiar with: Matlab, Python, Verilog

EXPERIENCE

Shell Eco-marathon EV Design Team (UWB Supermileage)

Bothell, WA

Electrical Hardware Engineer

January 2026 – Present

- Designed and routed a custom printed circuit board using Altium Designer to consolidate the vehicle's auxiliary functions on a single board, allowing the driver to control the lights, horn, windshield wiper, and observe the vehicle's speed.
- Designed and tested a filter to integrate a Hall-effect sensor with an STM32F446RET6 timer channel to compute vehicle speed in real time.
- Developed firmware in C using an interrupt-driven timer and SPI communication to calculate and display vehicle speed in real time.
- Engineered a battery disconnect and safety isolation system utilizing a TE Connectivity Kilovac EV200 contactor to ensure strict competition compliance.

PERSONAL PROJECTS

Bass Guitar Tremolo Effect Pedal | *Mixed-Signal PCB, Altium, LTspice, C*

- Designed and simulated a discrete analog voltage-controlled amplifier and a passive peak finder circuit in LTspice to achieve a dynamic tremolo effect with a 40dB modulation depth.
- Routed a mixed-signal PCB in Altium Designer, strictly partitioning analog and digital domains to mitigate digital switching noise and preserve audio signal integrity.
- Developed bare-metal C firmware using a timer-driven ADC via SPI to sample the peak voltage at a calculated frequency, ensuring the modulation rate remained highly responsive to the musician's playing dynamics.