




**National Centre for  
Atmospheric Science**

NATURAL ENVIRONMENT RESEARCH COUNCIL



**Centre for Environmental  
Data Analysis**

SCIENCE AND TECHNOLOGY FACILITIES COUNCIL  
NATURAL ENVIRONMENT RESEARCH COUNCIL

# Parallel processing of large datasets


Thanks to all contributors:

Alison Pamment, Sam Pepler, Ag Stephens, Stephen Pascoe,  
Anabelle Guillory, Esther Conway, Alan Iwi and Matt Pritchard.



**National Centre for  
Atmospheric Science**

NATURAL ENVIRONMENT RESEARCH COUNCIL



**Centre for Environmental  
Data Analysis**

SCIENCE AND TECHNOLOGY FACILITIES COUNCIL  
NATURAL ENVIRONMENT RESEARCH COUNCIL


# What is Big Data?

**1 ZETTABYTE = 1,000,000,000 TERABYTES**

## 40 ZETTABYTES

[ 43 TRILLION GIGABYTES ]

of data will be created by 2020, an increase of 300 times from 2005




It's estimated that

## 2.5 QUINTILLION BYTES

[ 2.3 TRILLION GIGABYTES ]

of data are created each day




## Volume SCALE OF DATA



## 6 BILLION PEOPLE

have cell  
phones



WORLD POPULATION: 7 BILLION



Most companies in the  
U.S. have at least

## 100 TERABYTES

[ 100,000 GIGABYTES ]

of data stored

T  
F  
O  
D

From tr  
history  
stored,  
and se  
But wh  
massive

As a le  
break



# Processing big data: the issues

- Parallel processing in the Environmental Sciences has historically focussed on running highly-parallelised models.
- Data analysis was typically run sequentially because:
  - It was a smaller problem
  - It didn't have parallel resources available
  - The software/scientists were not equipped to work in parallel
- The generation of enormous datasets (e.g. UPSCALE – around 300Tb) means that:
  - Processing big data **requires** a parallel approach, but
  - Platforms, tools, and programmers are becoming better equipped

# Some Terminology

**Concurrency:** A property of a system in which multiple tasks that comprise the system remain active and make progress at the same time.

**Parallelism:** Exploiting concurrency in a programme with the goal of solving a problem in less time.


**Race condition:** A race condition occurs within concurrent environments. It is when a piece of code prevents code that is running elsewhere from accessing a shared resource, e.g., memory, and thus delays the other process.

# How does my computer do so many things at once?

These days most computers, and even phones, have multiple processors.

However, even on a single processor modern operating systems can give the illusion that multiple tasks are running at the same time by rapidly switching between many active **threads**.

This is because the modern CPU clock is measuring time at the nanosecond scale where we humans can only keep track of milliseconds.



Picture: <http://www.python-course.eu/threads.php>

# Parallel processing for data analysis

- Data analysis tools do not (typically) do parallelisation automatically.
- But parallelisation is normally achievable at a small price.
- A lot can be done with:
  - Decomposition of large jobs into smaller jobs
  - Batch processing
  - Understanding tools and schedulers

We will look at these and show examples.

# (Almost) everything is parallel these days

YOUR DESKTOP MACHINE IS  
A PARALLEL COMPUTER!

It runs a multi-core processor...

...which means you can speed up processing by asking different parts of your programme to run on different cores.

*“But what about **race conditions**?”...*

...True: you still need to design your approach to avoid things getting out of hand!

# Simple parallelism by hand (1)

- Running on a multi-core machine you can exploit local processes, e.g.:

Long list (100,000) of text files: each file contains the text from a whole book.

Some processing code

A text file: listing all lines in all books that match the word “dog”


grep\_for\_dog.sh

```
#!/bin/bash
input_file=$1
while read FILENAME; do
    grep dog $FILENAME >> ${input_file}_result.txt
done < $input_file
```



# Simple parallelism by hand (2)

- A simple re-factoring splits the job into five parts:



```
$ split -l 20000 -d list_of_files.txt # Writes to "x00", "x01", ..., "x04"
$ for i in x?; do grep_for_dog.sh $i & done
$ cat *_result.txt > output.txt
```

# Simple parallelism by hand (3)

```
$ for i in x??.; do grep for dog.sh $i & done
```

```
[2] 3325
```

```
[3] 3326
```

```
[4] 3327
```

```
[5] 3328
```

```
[6] 3329
```

```
$ ps -ef | grep grep_for_dog
```

```
alison  3325  2669  0 00:40 pts/1  00:00:00 /bin/bash  ./grep_for_dog.sh  x00
```

```
alison  3326  2669  0 00:40 pts/1  00:00:00 /bin/bash  ./grep_for_dog.sh  x01
```

```
alison  3327  2669  0 00:40 pts/1  00:00:00 /bin/bash  ./grep_for_dog.sh  x02
```

```
alison  3328  2669  0 00:40 pts/1  00:00:00 /bin/bash  ./grep_for_dog.sh  x03
```

```
alison  3329  2669  0 00:40 pts/1  00:00:00 /bin/bash  ./grep_for_dog.sh  x04
```

# Simple parallelism by hand (4)

Some time later...


```
$ ps -ef | grep grep_for_dog
```

```
[2] Done          ./grep_for_dog.sh $i  
[3] Done          ./grep_for_dog.sh $i  
[4] Done          ./grep_for_dog.sh $i  
[5]- Done         ./grep_for_dog.sh $i  
[6]+ Done         ./grep_for_dog.sh $i
```

# JASMIN & LOTUS




# JASMIN in pictures

## JASMIN



---

## firewall



# The LOTUS cluster on JASMIN

- The **LOTUS cluster** is a far bigger resource for running compute intensive jobs than the JASMIN Scientific Analysis Servers.
- Having the same software installed on the JASMIN-Sci machines and LOTUS means you can:
  - 1. develop code on the generic Analysis Servers**
  - THEN**
  - 2. run in batch mode via LOTUS**

# What is a batch job?

- “Interactive processing” is when a user enters individual commands to be processed immediately by the computer.
- A “batch job” is a program or a sequence of commands that are executed without user interaction.

# LOTUS: Job Control

Submitting a job (you must SSH to **lotus.jc.rl.ac.uk**):

```
$ bsub [options] <command>
```

View the status of jobs:

```
$ bjobs
```

```
JOBID USER STAT QUEUE FROM_HOST EXEC_HOST JOB_NAME SUBMIT_TIME  
71880 fred PEND lotus lotus.jc.rl */hostname Mar 18 16:26
```

Cancel a job with:

```
$ bkill <job_id>
```

See details at:

<http://www.ceda.ac.uk/help/users-guide/lotus/>



# Batch job example: extract spatial subsets from CMIP5 experiments (1)

## Processing requirement:

For each model:

For each variable (hus, ps, ta, ua & va):

- Extract a spatial subset  
(80° to 140° Longitude; -30° to 40° Latitude)
- Where:
  - Frequency: 6hr
  - Realm: atmosphere
  - Ensemble: r1i1p1

# Batch job example: extract spatial subsets from CMIP5 experiments (2)

## Basic (Sequential) Implementation:

### Script 1 (bash):

- For each variable (hus, ps, ta, ua & va):
  - Make output directory
  - Find all relevant input NetCDF files
  - Loop through list of input files and for each one call Python script

```
import cf
f = cf.read(infile)
subset = f[2].subspace(latitude=cf.wi(bb.south, bb.north), longitude=cf.wi(bb.west, bb.east))
cf.write(subset, outfile)
```

*Extract from:* **extract\_cmip5\_subset.py**

- Main code used: cf-python library

# Batch job example: extract spatial subsets from CMIP5 experiments (3)

## Parallel Implementation using LOTUS:

### Script 1 (bash):

- For each variable (hus, ps, ta, ua & va):
  - Make output directory
  - Find all relevant input NetCDF files
  - Loop through list of files and for each one submit a batch job to LOTUS to call the Python script using **bsub**

```
bsub -q par-single -o $outdir/`date +%s`.txt  
~/extract_cmip5_subset.py $nc_file $this_dir $var
```

# Batch job example: extract spatial subsets from CMIP5 experiments (4)


## Why use this approach?

- Because you can submit 200 jobs in one go.
- Lotus executes jobs when resource becomes available
- They will all run and complete in parallel

```
bsub -q par-single -o $outdir/`date +%s`.txt  
~/extract_cmip5_subset.py $nc_file $this_dir $var
```

# Job Submission

- Jobs are submitted using the LSF scheduler
- Resources are allocated as they become available
- Fair share of resources between users



# Efficiency gains through re-factoring (1)

Major gains can be made by changing the order and structure of your code. Issues might be:

1. Code runs sequentially and takes a long time
2. Code will not run because of memory requirements
3. Code does run but falls over because of resource limits

In some cases you can create loops that can be scripted as separate processes allowing you to submit them in parallel.

# Efficiency gains through re-factoring (2)

Here is a real-world example:

**The Problem:** Trying to run the NCO tool “ncea” to calculate an average from a large dataset. It will not run!

**Why?** The “ncea” command reports this...and then exits:

- “unable to allocate 7932598800 bytes” (which is about 8 Gbytes)

Possible solutions:

**1. Data files hold multiple variables: Operate on one at a time:**

```
ncea -v vosaline means/199[45678]/*y01T.nc -o test.nc
```

**2. Reduce the number of files (i.e. years) processed each time:**

```
ncea means/199[45]/*y01T.nc -o test.nc
```

# Many Python-based Parallel tools

The following page brings together details of many different parallel tools available for python users:

- <https://wiki.python.org/moin/ParallelProcessing>



# The future of parallel data analysis (1)

- Analysing Big Data is a challenge! Software needs to adapt and scientists need to be able to adapt their code to keep up!

Number of files	3,222,967
Number of datasets	54,274
Archive Volume (TB)	1,483
Models with data published	64
Models with documentation published in archive	38
Experiments	108
Modelling centres	32
Data Nodes	22

# The future of parallel data analysis (2)

We are likely to see more:

- Parallel I/O in software libraries;
- Web processing services that do the parallel analysis remotely;
- Analysis Platforms (like JASMIN) that allow scientists to run code next to the data;
- Learning to write parallel code now is likely to be of great benefit in future;

# Further information

JASMIN Analysis Platform (software packages):

[jasmin.ac.uk/services/jasmin-analysis-platform/](https://jasmin.ac.uk/services/jasmin-analysis-platform/)

LOTUS Overview:

[help.ceda.ac.uk/article/110-lotus-overview](https://help.ceda.ac.uk/article/110-lotus-overview)

LOTUS User Guide

[help.ceda.ac.uk/category/107-batch-computing-on-lotus](https://help.ceda.ac.uk/category/107-batch-computing-on-lotus)

Jug:

[jug.readthedocs.io/en/latest/](https://jug.readthedocs.io/en/latest/)

Parallel processing:

[https://computing.llnl.gov/tutorials/parallel\\_comp/](https://computing.llnl.gov/tutorials/parallel_comp/)