





# The Unix Shell


The Secure Shell











\$ pwd


























Password: \*\*\*\*\*\*



















Password: \*\*\*\*\*\*

\$

















Password: \*\*\*\*\*\*

moon>











































\$ pwd
/users/vlad

\$ ssh vlad@moon

Password:









\$ pwd

/users/vlad

\$ ssh vlad@moon

Password: \*\*\*

Access denied

Password:









```
$ pwd
/users/vlad
$ ssh vlad@moon
Password:
           * * *
Access denied
           * * * * * * * *
Password:
moon> pwd
/home/vlad
moon> ls -F
```





bin/ cheese.txt dark\_side/ rocks.cfg



```
$ pwd
/users/vlad
$ ssh vlad@moon
          * * *
Password:
Access denied
Password: ******
moon> pwd
/home/vlad
moon> ls -F
bin/ cheese.txt dark_side/ rocks.cfg
moon> exit
$ pwd
/users/vlad
```







```
$ ssh vlad@moon
Password:
          * * * * * * * *
moon> pwd
/home/vlad
moon> ls -F
         cheese.txt
bin/
                      dark_side/ rocks.cfg
moon> exit
$ pwd
/users/vlad
$ ls -F
bin/
             data/ mail/ music/
             papers/ pizza.cfg solar/
notes.txt
solar.pdf
             SWC/
```









```
$ scp vlad@moon:/home/vlad/cheese.txt vlad@earth:/users/vlad
```

















source file...

...to destination directory source and destination are written as

user@computer:path









\$ scp vlad@moon:/home/vlad/cheese.txt

vlad@earth:/users/vlad

Password: \*\*\*\*\*\*

cheese.txt

100% 9 1.0 KB/s 00:00



















```
$ scp -r vlad@moon:/home/vlad/dark_side
        vlad@earth:/users/vlad 🔨
$ scp -r vlad@moon:/home/vlad/dark_side
        /users/vlad
$ pwd
/users/vlad
$ scp -r vlad@moon:/home/vlad/dark_side
                        same destination path
```











\$ ssh vlad@moon

Password: \*\*\*\*\*\*

moon> df -h

Filesystem Size Used Avail Use% Mounted On

/dev/sda1 7.9G 2.1G 5.5G 28% /

/dev/sda2 791G 150G 642G 19% /home

moon> df -h > usage.txt

moon> exit

\$ scp vlad@moon:/home/vlad/usage.txt .

Password: \*\*\*\*\*\*

usage.txt 100% 134 1.0 KB/s 00:00











\$ ssh vlad@moon 'df -h'

Password: \*\*\*\*\*\*

Filesystem Size Used Avail Use% Mounted On /dev/sda1 7.9G 2.1G 5.5G 28% / /dev/sda2 791G 150G 642G 19% /home







\$ ssh vlad@moon 'df -h'

Password: \*\*\*\*\*\*

Filesystem Size Used Avail Use% Mounted On

/dev/sda1 7.9G 2.1G 5.5G 28% /

/dev/sda2 791G 150G 642G 19% /home

\$ ssh vlad@moon 'df -h' >> usage.log

Password: \*\*\*\*\*\*

\$ ls -F

bin/ data/ mail/ music/

notes.txt papers/ pizza.cfg solar/

solar.pdf swc/ usage.log usage.txt

same result











#### character stream

\$ echo "open sesame, please" | ssh vlad@moon 'cat > magic.txt'

Password: \*\*\*\*\*\*









character stream

\$ echo "open sesame, please" |
 vlad@moon 'cat > magic.txt'

Password: \*\*\*\*\*\*

remote command receives input piped to ssh cat repeats input stream as output

remote shell receives stream from pipe

ssh

redirection within remote shell









```
before
$ ssh vlad@moon 'ls -F /home/vlad'
          * * * * * * * *
Password:
bin/ cheese.txt dark_side/ rocks.cfg
                              | ssh
$ echo "open sesame, please"
   vlad@moon 'cat > magic.txt'
Password: ******
                                               after
$ ssh vlad@moon 'ls -F /home/vlad'
          * * * * * * * *
Password:
                                    magic.txt
bin/ cheese.txt dark side/
rocks.cfg
```









```
before
$ ssh vlad@moon 'ls -F /home/vlad'
          * * * * * * * *
Password:
bin/ cheese.txt dark_side/ rocks.cfg
$ echo "open sesame, please"
                                ssh
   vlad@moon 'cat > magic.txt'
Password: ******
                                               after
$ ssh vlad@moon 'ls -F /home/vlad'
          *****
Password:
                                    magic.txt
bin/ cheese.txt dark_side/
rocks.cfg
$ scp vlad@moon:/home/vlad/magic.txt .
          * * * * * * * *
Password:
```















Password: \*\*\*\*\*\*



































Password: thriller





















shell






Password: thriller
































































public key





encryption using private key public key (only 1 copy)
shell














Password: \*\*\*\*\*\*\*




huxyo ew: xdvw

uqfcmjbn: lhiujdbj




shell



















```
$ ssh vlad@moon
```

The authenticity of host 'moon (10.1.2.3)' can't be established.

RSA key fingerprint is

f1:68:f5:90:47:dc:a8:e9:62:df:c9:21:f0:8b:c5:39.

Are you sure you want to continue connecting (yes/no)? yes

Warning: Permanently added 'moon, 10.1.2.3' (RSA) to the list of known hosts.

Password: \*\*\*\*\*\*

moon>












encryption using public keys

Send message to moon locked with moon's public key

(Only readable by moon)




Send message to Vlad locked with Vlad's public key

(Only readable by Vlad)







private key (only 1 copy)

private key
(only 1 copy)













### created by

Elango Cheran

February 2011



Copyright © Software Carpentry 2011

This work is licensed under the Creative Commons Attribution License

See http://software-carpentry.org/license.html for more information.

## The ssh agent

- Stores secret keys in memory.
- Avoids repeated typing of the pass phrases.
- Can talk to a forwarding mechanism.
   For example:
  - your workstation → jasmin-login1 → jasmin-sci1
  - jasmin-login1 does not have the private key
  - authentication traffic forwarded from end to end:
    - jasmin-sci1 sends challenge
    - workstation sends response, proving your identity







# The ssh agent (continued)

- To start the agent and load your secret key:
  - Linux: session manager should start agent for you. Use ssh-add to load key (if not done automatically when ssh first used).
  - Windows: launch Pageant and click "add key".
  - Enter your pass phrase.
- For authentication forwarding:
  - Linux: use "ssh -A" (often the default)
  - Windows: in PuTTY, go to Connection → SSH → Auth, and "Allow agent forwarding"







### Exercise

- 1. Ssh to user01@10.23.23.254. password pyth0nrules.
- 2. Use ls, pwd and other commands to prove to yourself it's a different computer.
- 3. Logout (use exit or ^D)
- 4. Use scp to copy some files to the remote computer.
- 5. Login again and Is the files.
- 6. Logout
- 7. Use ssh to run df on the remote computer.







