
```

    name: <unnamed>
    log: /Users/connorbrennan/Library/CloudStorage/OneDrive-TheUniversityof
> fChicago/mmb/output/stepwise_regressions/y_timing_max_nomrig.smcl
    log type: smcl
    opened on: 12 Sep 2025, 19:25:17
- capture ! rm ./output/stepwise_regressions/`depvar'`type'.pdf
= capture ! rm ./output/stepwise_regressions/y_timing_max_nomrig.pdf
- di "*****"
> *****"
*****
> **
- di "Outcomes of bi-directional stepwise regressions with `depvar' (type = `t
> ype'))"
= di "Outcomes of bi-directional stepwise regressions with y_timing_max (type
> = nomrig)"
Outcomes of bi-directional stepwise regressions with y_timing_max (type = nomr
> ig)
- di "*****"
> *****"
*****
> **
- ${reg_`depvar'`type'}
= poisson y_timing_max rule_g rule_itr estimated if y_timing_max < 99 , vce(r
> obust) nolog

```

```

> ----- begin pois
> son -----
- if _by() {
    local BY `"'by `'_byvars'`'_byrc0':"'
}
- `BY' _vce_parserun poisson, mark(Exposure OFFset CLuster) : `0'
= _vce_parserun poisson, mark(Exposure OFFset CLuster) : y_timing_max rule_
> g rule_itr estimated if y_timing_max < 99 , vce(robust) nolog

```

```

> ----- begin _vce_parse
> run -----
- version 9
- local version : di "version " string(_caller()) ":"
- local bycall = _by()
- _on_colon_parse `0'
= _on_colon_parse poisson, mark(Exposure OFFset CLuster) : y_timing_max ru
> le_g rule_itr estimated if y_timing_max < 99 , vce(robust) nolog

```

```

> ----- begin _on_colon_pa
> rse -----

```

```

- version 8.2
- sreturn local before ""
- sreturn local after ""
- gettoken before after : 0, parse(":") bind match(par) quotes
- if ""par"" != "" {
= if "" != "" {
  local before `(`before')`
}
- if ``before`` == ":" {
= if ``poisson, mark(Exposure OFFset CLuster) `` == ":" {
  sreturn local after ``after``
  exit
}
- while ``COLON`` != ":" & ``after`` != "" {
= while `` != ":" & ``: y_timing_max rule_g rule_itr estimated if y_t
> iming_max < 99 , vce(robust) nolog"" != "" {
- gettoken COLON after : after, parse(":") bind match(par) quotes
- if ""par"" != "" {
= if "" != "" {
  local before `before' (`COLON')
  local COLON
}
- else if ``COLON`` != ":" {
= else if ``:`` != ":" {
  local before ``before' `COLON``
  local COLON
}
- }
- while ``COLON`` != ":" & ``after`` != "" {
= while ``:`` != ":" & `` y_timing_max rule_g rule_itr estimated if y_t
> iming_max < 99 , vce(robust) nolog"" != "" {
  gettoken COLON after : after, parse(":") bind match(par) quotes
  if ""par"" != "" {
    local before `before' (`COLON')
    local COLON
  }
  else if ``COLON`` != ":" {
    local before ``before' `COLON``
    local COLON
  }
}
- if ``COLON`` != ":" {
= if ``:`` != ":" {
  di as err "" found where ':' expected"
  exit 198
}
}

```

```

- sreturn local before ```before'''
= sreturn local before ```poisson, mark(Exposure OFFset CLuster) ```
- sreturn local after ```after'''
= sreturn local after ``` y_timing_max rule_g rule_itr estimated if y_ti
> ming_max < 99 , vce(robust) nolog'''

> _____ end _on_colon_pa
> rse _____
- local ZERO ```s(before)'''
= local ZERO ```poisson, mark(Exposure OFFset CLuster) ```
- local 0 ```s(after)'''
= local 0 ``` y_timing_max rule_g rule_itr estimated if y_timing_max < 99
> , vce(robust) nolog'''
- quietly syntax [anything(equalok)] [if] [in] [fw aw pw iw] [, VCE(string
> asis) VCE1(string asis) LRMODEL * ]
- if ```vce''' == "" {
= if ```robust''' == "" {
MYRESULT
exit
}
- local AFTER ```0'''
= local AFTER ``` y_timing_max rule_g rule_itr estimated if y_timing_max <
> 99 , vce(robust) nolog'''
- local 0 ```ZERO'''
= local 0 ```poisson, mark(Exposure OFFset CLuster) ```
- syntax name(name=caller id="calling command name") [, WYPES(string) NOB
> OOTstrap NOJACKknife NOOTHERvce NOTEST PANELdata STdata bootopts(string asis
> ) jkopts(string asis) robustok multivce REQUIREDopts(namelist) NOEQLIST EQop
> ts(passthru) EQARGopts(passthru) noNEEDVARLIST COMMONopts(namelist) MARKopts
> (passthru) SMARKopts(passthru) RMCOLLOpts(passthru) RMDCOLLOpts(passthru) NU
> MDEPvars(passthru) NEEDEQUAL ALLDEPSMISSing PAREntheses UNPARFIRSTeq OR EQUA
> L UNEQUALFIRSTeq IGNORENOCONS ]
- if ```requiredopts''' != "" {
= if ```''' != "" {
tempname reqopts
.`reqopts' = `._optlist.new
foreach req of local requiredopts {
.`reqopts'.addopt `req', passthru
}
}
- if ```wtypes''' == "" {
= if ```''' == "" {
- local wtypes fw aw pw iw
- }
- if ```paneldata''' != "" {
= if ```''' != "" {

```

```

    local panelopt "Cluster(varname) I(varname)"
  }
- if "`stdata'" != "" {
= if "" != "" {
    local stopt "Cluster(varname) SHared(varname)"
  }
- local typelist svy jackknife bootstrap
- if "`stdata'" == "" & replay() & ! _by() {
= if "" == "" & replay() & ! _by() {
    local ecmd `e(cmd)'
    local ecmdname `e(cmdname)'
    if ``ecmd' == "" {
      error 301
    }
    else if ``ecmd' != "`caller'" & ``ecmdname' == "`caller'" & `:list
> ecmd in typelist' {
    `ecmd' `0'
    MYRESULT exit
  }
  MYRESULT
  exit
}
- gettoken svy typelist : typelist
- if "`reqopts'" != "" {
= if "" != "" {
    local REQOPTLIST ``'.`reqopts'.dumpoptions'
    local REQOPTNAMES ``'.`reqopts'.dumpnames'
  }
- local 0 ``AFTER'
= local 0 `` y_timing_max rule_g rule_itr estimated if y_timing_max < 99
> , vce(robust) nolog"
- quietly syntax [anything(equalok)] [if/] [in] [`wtypes'] [, VCE(string a
> sis) VCE1(string asis) Robust NODOTS `panelopt' `stopt' `REQOPTLIST' * ]
= quietly syntax [anything(equalok)] [if/] [in] [fw aw pw iw] [, VCE(strin
> g asis) VCE1(string asis) Robust NODOTS * ]
- if `:list vce' == vce1' {
= if 0 {
    local vce1
  }
- if ``vce1' != "" & "`multivce'" == "" {
= if ``'" != "" & "" == "" {
    di as err "option vce() specified multiple times"
    exit 198
  }
- if "`robust'" != "" & "`robustok'" == "" {
= if "" != "" & "" == "" {

```

```

    di as err "options vce() and robust may not be combined"
    exit 198
  }
- if ``if'' != "" {
= if ``y_timing_max < 99 '' != "" {
- local if ``if (`if')''
= local if ``if (y_timing_max < 99 )''
- }
- if ``robust'' != "" {
= if "" != "" {
    local options ``robust' `options''
  }
- if ``weight'' != "" {
= if "" != "" {
    local wgt [`weight'`exp']
  }
- if ``options'' != "" {
= if ``nolog'' != "" {
- local opts ``:list retok options''
= local opts ``nolog''
- }
- gettoken uvcetype vceopts : vce, parse(" ,")
- capture unabVCetype, `uvcetype'
= capture unabVCetype, robust
}

> _____ begin _vce_parserun.unabVCet
> ype _____
- syntax [, B00Tstrap BStrap JACKknife JACKNife JKnife Robust * ]
- if ``bstrap'' != "" {
= if "" != "" {
    local bootstrap bootstrap
  }
- if ``jknife'' != "" | ``jackknife'' != "" {
= if "" != "" | "" != "" {
    local jackknife jackknife
  }
- local vcetype ``jackknife' `bootstrap' `robust' `options''
= local vcetype ``robust''
- sreturn local vcetype ``:list retok vcetype''
= sreturn local vcetype ``robust''
}

> _____ end _vce_parserun.unabVCet
> ype _____
- if c(rc) {
    di as err "invalid vce() option"
    exit c(rc)
  }

```

```

    }
- local vcetype `s(vcetype)'
= local vcetype robust
- if "`lrmodel'"!="" {
= if ""!="" {
    _check_lrmodel `caller', vcetype(`vcetype')
    }
- if "`vce1'"!="" & "`multivce'"!="" {
= if `""' != "" & "" != "" {
    gettoken uvceltype vcelopts : vce1, parse(" ,")
    capture unabVCEtype, `uvceltype'
    if c(rc) {
        di as err "invalid vce() option"
        exit c(rc)
    }
    local vceltype `s(vcetype)'
    if `:list vceltype in typelist' | `:list vcetype in typelist' {
        di as err "options vce(`vce') and vce(`vce1') cannot be combined"
        exit 198
    }
    MYRESULT
    exit
    }
- if _caller() >= 17 {
- if "`vcetype'" == "cluster" {
= if "robust" == "cluster" {
    gettoken vceopts vcelopts: vceopts, parse(",")
    if `:list sizeof vceopts' > 1 {
        local typelist "`typelist' cluster_multiway"
        local vcetype cluster_multiway
        if `:list sizeof vcelopts' > 0 {
            gettoken comma vcelopts: vcelopts, parse(",")
            local vcelopts: list retokenize vcelopts
            di as err "{p}VCE option " "{bf:`vcelopts'} not allowed{p_end}"
            exit 198
        }
        if !inlist("`caller'", "areg", "regress", "xtreg") {
            di as err "{p}multiway cluster VCE " "not allowed{p_end}"
            exit 198
        }
        MYRESULT
        exit
        }
    }
- }
- if ! `:list vcetype in typelist' {

```

```

= if ! 0 {
- if "`vcetype'" != "robust" & "`noothervce'" == "noothervce" {
= if "robust" != "robust" & "" == "noothervce" {
  di as err "option vce(`vcetype') not allowed"
  exit 198
}
- MYRESULT
}

> _____ begin _vce_parserun.MYRES
> ULT _____
  - args exit
  - sreturn local exit ``exit'''
  = sreturn local exit `'''
}

> _____ end _vce_parserun.MYRES
> ULT _____
  - exit
}

> _____ end _vce_parse
> run _____
- if "`s(exit)'" != "" {
= if "" != "" {
  version 10: ereturn local cmdline `"poisson `0'''
  exit
}
- version 6, missing
- local version : di "version " string(_caller()) ":"
- if replay() {
  if "`e(cmd)'" != "poisson" {
    error 301
  }
  if _by() { error(190) }
  Display `0'
  error `e(rc)'
  exit
}
- `version' `BY' Estimate `0'
= version 18.5: Estimate y_timing_max rule_g rule_itr estimated if y_timin
> g_max < 99 , vce(robust) nolog

> _____ begin poisson.Estim
> ate _____
  - local vv "version 8.1:"
  - local mm d2
  - local eval poiss_lf
  - version 6, missing

```

```

- local awopt = cond(_caller()<7, "aw", "")
- syntax varlist(numeric fv ts) [fw `awopt' pw iw] [if] [in] [, IRr FROM(s
> tring) Level(cilevel) OFFset(varname numeric ts) Exposure(varname numeric ts
> ) noCONstant Robust CLuster(varname) SCore(string) noDISPLAY CRITTYPE(passth
> ru) MATAevaluator moptobj(passthru) * ]
= syntax varlist(numeric fv ts) [fw pw iw] [if] [in] [, IRr FROM(string)
> Level(cilevel) OFFset(varname numeric ts) Exposure(varname numeric ts) noCON
> stant Robust CLuster(varname) SCore(string) noDISPLAY CRITTYPE(passthru) MAT
> Aevaluator moptobj(passthru) * ]
- local fvops = "`s(fvops)'" == "true" | _caller() >= 11
= local fvops = "" == "true" | _caller() >= 11
- if `fvops' {
= if 1 {
- local vv : di "version " string(max(11,_caller())) ", missing:"
- local mm e2
- if "`mataevaluator'" != "" {
= if "" != "" {
local eval mopt__poisson_e2()
}
- local negh negh
- }
- if _by() {
_byoptnotallowed score ``score'``
}
- _get_diopts diopts options, `options'
= _get_diopts diopts options, vce(robust) nolog


---


> ----- begin _get_dio
> pts -----
- version 11
- syntax namelist(max=2) [, *]
- gettoken name1 namelist : namelist
- gettoken name2 namelist : namelist
- GetDiopts diopts options, `options'
= GetDiopts diopts options, vce(robust) nolog


---


> ----- begin _get_diopts.GetDio
> pts -----
- local DIOPTS Level(cilevel) vsquish NOALLBASElevels ALLBASElevels NO
> BASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EMPTYcells NOOM
> ITted OMITted NOLSTRETCH LSTRETCH COEFlegend SELEGEND cformat(string) sforma
> t(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru) FVWRAPON(st
> ring) NOFVLABEL FVLABEL NOCI NOPvalues MARKDOWN CITYPE(passthru) NOABBREV AB
> BREV
- syntax namelist(max=2) [, `DIOPTS' *]
= syntax namelist(max=2) [, Level(cilevel) vsquish NOALLBASElevels ALL

```



```

> BASElevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EM
> PTYcells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cformat(s
> tring) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru
> ) FVWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(passthru
> ) NOABBREV ABBREV *)
    - opts_exclusive "'allbaselevels' `noallbaselevels'"
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts'' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____
> _____ end opts_exclus
> ive _____
    - opts_exclusive "'allbaselevels' `nobaselevels'"
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts'' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____
> _____ end opts_exclus

```

```

> ive
- opts_exclusive "`baselevels' `nobaselevels'"
= opts_exclusive " "
-----
> ----- begin opts_exclus
> ive
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
-----
> ----- end opts_exclus
> ive
- opts_exclusive "`emptycells' `noemptycells'"
= opts_exclusive " "
-----
> ----- begin opts_exclus
> ive
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
-----
> ----- end opts_exclus
> ive
- opts_exclusive "`fvlabel' `nofvlabel'"
= opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

> ----- end opts_exclus
> ive
    - opts_exclusive "`omitted' `noomitted'"
    = opts_exclusive " "

> ----- begin opts_exclus
> ive
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

> ----- end opts_exclus
> ive
    - opts_exclusive "`lstretch' `nolstretch'"
    = opts_exclusive " "

> ----- begin opts_exclus
> ive
    - version 8.2
    - args opts optname errcode optslab

```

```

- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
  }
- if `n' < 2 {
= if 0 < 2 {
- exit

```

```

> ----- end opts_exclus
> ive -----
- opts_exclusive "`cnsreport' `fullcnsreport'"
= opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
  }
- if `n' < 2 {
= if 0 < 2 {
- exit

```

```

> ----- end opts_exclus
> ive -----
- opts_exclusive "`coeflegend' `selegend'"
= opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {

```

```

= while `""` != "" {
    local ++n
    gettoken item`n` opts : opts, bind
}
- if `n` < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`noci` `nopvalues`"
= opts_exclusive " "
}

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts`
= local opts
    - local n 0
    - while `""opts`"" != "" {
= while `""` != "" {
    local ++n
    gettoken item`n` opts : opts, bind
}
    - if `n` < 2 {
= if 0 < 2 {
    - exit
}

> ----- end opts_exclus
> ive -----
    - local K : list sizeof namelist
    - gettoken c_diopts c_opts : namelist
    - opts_exclusive "`coding` `compare`"
= opts_exclusive " "
}

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts`
= local opts
    - local n 0
    - while `""opts`"" != "" {
= while `""` != "" {
    local ++n

```

```

        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`versus' `compare'"
= opts_exclusive " "
}
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ```opts'"" != "" {
= while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`abbrev' `noabbrev'"
= opts_exclusive " "
}
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ```opts'"" != "" {
= while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {

```

```

- exit


---


> 

---

 end opts_exclus
> ive 

---


- local allbaselevels `allbaselevels' `noallbaselevels'
= local allbaselevels
- local baselevels `baselevels' `nobaselevels'
= local baselevels
- local emptycells `emptycells' `noemptycells'
= local emptycells
- local omitted `omitted' `noomitted'
= local omitted
- local lstretch `lstretch' `nolstretch'
= local lstretch
- local fvlabel `fvlabel' `nofvlabel'
= local fvlabel
- local abbrev `abbrev' `noabbrev'
= local abbrev
- if "`allbaselevels'`baselevels'" == "" {
= if "" == "" {
- if c(showbaselevels) == "all" {
  local allbaselevels allbaselevels
}
- else if c(showbaselevels) == "on" {
  local baselevels baselevels
}
- }
- if "`emptycells'" == "" {
= if "" == "" {
- if c(showemptycells) == "off" {
  local emptycells noemptycells
}
- }
- if "`omitted'" == "" {
= if "" == "" {
- if c(showomitted) == "off" {
  local omitted noomitted
}
- }
- if "`lstretch'" == "" {
= if "" == "" {
- if c(lstretch) == "off" {
  local lstretch nolstretch
}
- }
- if `:length local cformat' {

```

```

= if 0 {
    confirm numeric format `cformat'
    if fmtwidth(`""cformat'""') > 9 {
        local cformat "%9.0g"
        di "{txt}note: invalid cformat(), using default"
    }
    sreturn local cformat `""cformat'""'
    local cformat `"cformat(`cformat')"'
}
- if `:length local sformat' {
= if 0 {
    confirm numeric format `sformat'
    if fmtwidth(`""sformat'""') > 8 {
        local sformat "%8.2f"
        di "{txt}note: invalid sformat(), using default"
    }
    sreturn local sformat `""sformat'""'
    local sformat `"sformat(`sformat')"'
}
- if `:length local pformat' {
= if 0 {
    confirm numeric format `pformat'
    if fmtwidth(`""pformat'""') > 5 {
        local pformat "%5.3f"
        di "{txt}note: invalid pformat(), using default"
    }
    sreturn local pformat `""pformat'""'
    local pformat `"pformat(`pformat')"'
}
- if `K' == 1 & `:length local options' {
= if 2 == 1 & 17 {
    syntax namelist(max=2) [, `DIOPTS']
}
- if reldif(`level', c(level)) > 1e-3 {
= if reldif(95, c(level)) > 1e-3 {
    local levelopt level(`level')
}
- Wraon , `fvwraon'
= Wraon ,

> _____ begin _get_diopts.Wra
> pon _____
    - capture syntax [, W0rd WIdth]
    - if c(rc) {
        di as err "invalid fvwraon() option;"
        syntax [, W0rd WIdth]
    }

```



```

        exit 198
    }
    - opts_exclusive "`word' `width'" fwrapon
    = opts_exclusive " " fwrapon
}
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
        - exit
    }
}
> ----- end opts_exclus
> ive -----
    - local fwrapon `word' `width'
    = local fwrapon
    - if `:length local fwrapon' {
    = if 0 {
        c_local fwrapon fwrapon(`fwrapon')
    }
}
> ----- end _get_diopts.Wra
> pon -----
    - if "`fwrap'" != "" {
    = if "" != "" {
        FVWrap, `fwrap'
    }
    - c_local `c_diopts' `levelopt' `vsquish' `allbaselevels' `baselevels'
> `cnsreport' `fullcnsreport' `emptycells' `omitted' `lstretch' `coeflegend'
> `selegend' `cformat' `sformat' `pformat' `coding' `versus' `compare' `fwrap
> ' `fwrapon' `fvlabel' `nocl' `nopvalues' `markdown' `citype' `abbrev'
    = c_local diopts
    - if `K' == 2 {
    = if 2 == 2 {
        - c_local `c_opts' ``options'
    = c_local options `"vce(robust) nolog"
    - }

```

```

- sreturn local coding `coding'
= sreturn local coding
- sreturn local versus `versus'
= sreturn local versus
- sreturn local compare `compare'
= sreturn local compare
- sreturn local level `level'
= sreturn local level 95

```

```

> _____ end _get_diopts.GetDio
> pts _____
- c_local `name1' ```diopts'``
= c_local diopts `''''
- local snames : s(macros)
- foreach sname of local snames {
- local S_`sname' = s(`sname')
= local S_level = s(level)
- }
- sreturn clear
- GetDiopts DEFAULT

```

```

> _____ begin _get_diopts.GetDio
> pts _____
- local DIOPTS Level(cilevel) vsquish NOALLBASElevels ALLBASElevels NO
> BASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EMPTYcells NOOM
> ITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cformat(string) sforma
> t(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru) FVWRAPON(st
> ring) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(passthru) NOABBREV AB
> BREV
- syntax namelist(max=2) [, `DIOPTS' *]
= syntax namelist(max=2) [, Level(cilevel) vsquish NOALLBASElevels ALL
> BASElevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EM
> PTYcells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cformat(s
> tring) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru
> ) FVWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(passthru
> ) NOABBREV ABBREV *]
- opts_exclusive "`allbaselevels' `noallbaselevels'"
= opts_exclusive " "

```

```

> _____ begin opts_exclus
> ive _____
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0

```

```

- while ``opts'' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
  }
- if `n' < 2 {
= if 0 < 2 {
- exit

```

```

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`allbaselevels' `nobaselevels'"
    = opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts'' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
      }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

```

```

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`baselevels' `nobaselevels'"
    = opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts'' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind

```

```

    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`emptycells' `noemptycells'"
= opts_exclusive " "
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ``opts' != "" {
= while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`fvlabel' `nofvlabel'"
= opts_exclusive " "
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ``opts' != "" {
= while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}

```

```

> _____ end opts_exclus
> ive _____
  - opts_exclusive "`omitted' `noomitted'"
  = opts_exclusive " "
  _____

> _____ begin opts_exclus
> ive _____
  - version 8.2
  - args opts optname errcode optslab
  - local opts `opts'
  = local opts
  - local n 0
  - while ``"opts" != "" {
  = while `"" != "" {
    local ++n
    gettoken item`n' opts : opts, bind
  }
  - if `n' < 2 {
  = if 0 < 2 {
  - exit
  _____

> _____ end opts_exclus
> ive _____
  - opts_exclusive "`lstretch' `nolstretch'"
  = opts_exclusive " "
  _____

> _____ begin opts_exclus
> ive _____
  - version 8.2
  - args opts optname errcode optslab
  - local opts `opts'
  = local opts
  - local n 0
  - while ``"opts" != "" {
  = while `"" != "" {
    local ++n
    gettoken item`n' opts : opts, bind
  }
  - if `n' < 2 {
  = if 0 < 2 {
  - exit
  _____

> _____ end opts_exclus
> ive _____
  - opts_exclusive "`cnsreport' `fullcnsreport'"

```

```

= opts_exclusive " "
> ----- begin opts_exclus
> ive
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

> ----- end opts_exclus
> ive
    - opts_exclusive ``coeflegend' `selegend'
    = opts_exclusive " "

> ----- begin opts_exclus
> ive
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

> ----- end opts_exclus
> ive
    - opts_exclusive ``noci' `nopvalues'
    = opts_exclusive " "

> ----- begin opts_exclus
> ive

```

```

- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `'' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit

```

```

> ----- end opts_exclus
> ive -----
    - local K : list sizeof namelist
    - gettoken c_diopts c_opts : namelist
    - opts_exclusive "`coding' `compare'"
    = opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `'' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

```

```

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`versus' `compare'"
    = opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab

```

```

- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
  }
- if `n' < 2 {
= if 0 < 2 {
- exit

```

```

> ----- end opts_exclus
> ive -----
- opts_exclusive "`abbrev' `noabbrev'"
= opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
  }
- if `n' < 2 {
= if 0 < 2 {
- exit

```

```

> ----- end opts_exclus
> ive -----
- local allbaselevels `allbaselevels' `noallbaselevels'
= local allbaselevels
- local baselevels `baselevels' `nobaselevels'
= local baselevels
- local emptycells `emptycells' `noemptycells'
= local emptycells
- local omitted `omitted' `noomitted'
= local omitted
- local lstretch `lstretch' `nolstretch'
= local lstretch
- local fvlabel `fvlabel' `nofvlabel'

```



```

= local fvlabel
- local abbrev `abbrev' `noabbrev'
= local abbrev
- if "`allbaselevels'`baselevels'" == "" {
= if "" == "" {
- if c(showbaselevels) == "all" {
    local allbaselevels allbaselevels
  }
- else if c(showbaselevels) == "on" {
    local baselevels baselevels
  }
- }
- if "`emptycells'" == "" {
= if "" == "" {
- if c(showemptycells) == "off" {
    local emptycells noemptycells
  }
- }
- if "`omitted'" == "" {
= if "" == "" {
- if c(showomitted) == "off" {
    local omitted noomitted
  }
- }
- if "`lstretch'" == "" {
= if "" == "" {
- if c(lstretch) == "off" {
    local lstretch nolstretch
  }
- }
- if `:length local cformat' {
= if 0 {
    confirm numeric format `cformat'
    if fmtwidth("`cformat'") > 9 {
      local cformat "%9.0g"
      di "{txt}note: invalid cformat(), using default"
    }
    sreturn local cformat "`cformat'"
    local cformat `cformat(`cformat')'
  }
- if `:length local sformat' {
= if 0 {
    confirm numeric format `sformat'
    if fmtwidth("`sformat'") > 8 {
      local sformat "%8.2f"
      di "{txt}note: invalid sformat(), using default"
    }
  }

```

```

    }
    sreturn local sformat ``sformat'''
    local sformat `sformat(`sformat')''
  }
- if `:length local pformat' {
= if 0 {
  confirm numeric format `pformat'
  if fmtwidth(`pformat') > 5 {
    local pformat "%5.3f"
    di "{txt}note: invalid pformat(), using default"
  }
  sreturn local pformat ``pformat'''
  local pformat `pformat(`pformat')''
}
- if `K' == 1 & `:length local options' {
= if 1 == 1 & 0 {
  syntax namelist(max=2) [, `DIOPTS']
}
- if reldif(`level', c(level)) > 1e-3 {
= if reldif(95, c(level)) > 1e-3 {
  local levelopt level(`level')
}
- Wraapon , `fvwraapon'
= Wraapon ,

> ----- begin _get_diopts.Wra
> pon -----
  - capture syntax [, W0rd WIdth]
  - if c(rc) {
    di as err "invalid fvwraapon() option;"
    syntax [, W0rd WIdth]
    exit 198
  }
  - opts_exclusive ``word' `width'" fvwraapon
= opts_exclusive " " fvwraapon

> ----- begin opts_exclus
> ive -----
  - version 8.2
  - args opts optname errcode optslab
  - local opts `opts'
= local opts
  - local n 0
  - while ``opts' != "" {
= while `"' != "" {
    local ++n

```

```

        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    }
}
> _____ end opts_exclus
> ive _____
    - local fvwrapon `word' `width'
    = local fvwrapon
    - if `:length local fvwrapon' {
    = if 0 {
        c_local fvwrapon fvwrapon(`fvwrapon')
    }
}
> _____ end _get_diopts.Wra
> pon _____
    - if "`fvwrap'" != "" {
    = if "" != "" {
        FVWrap, `fvwrap'
    }
    - c_local `c_diopts' `levelopt' `vsquish' `allbaselevels' `baselevels'
> `cnsreport' `fullcnsreport' `emptycells' `omitted' `lstretch' `coeflegend'
> `selegend' `cformat' `sformat' `pformat' `coding' `versus' `compare' `fvwrap
> ' `fvwrapon' `fvlabel' `noci' `nopvalues' `markdown' `citype' `abbrev'
    = c_local DEFAULT
    - if `K' == 2 {
    = if 1 == 2 {
        c_local `c_opts' ``options''
    }
    - sreturn local coding `coding'
    = sreturn local coding
    - sreturn local versus `versus'
    = sreturn local versus
    - sreturn local compare `compare'
    = sreturn local compare
    - sreturn local level `level'
    = sreturn local level 95
}
> _____ end _get_diopts.GetDio
> pts _____
    - if ``name2'' == "" {
    = if ``options'' == "" {
        GetDiopts DUPS, `options'
    }
    - else {

```

```

- GetDiopts DUPS options, `options'
= GetDiopts DUPS options, vce(robust) nolog

```

```

> ----- begin _get_diopts.GetDio
> pts
    - local DIOPTS Level(cilevel) vsquish NOALLBASElevels ALLBASElevels NO
> BASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EMPTYcells NOOM
> ITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cformat(string) sforma
> t(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru) FVWRAPON(st
> ring) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(passthru) NOABBREV AB
> BREV
    - syntax namelist(max=2) [, `DIOPTS' *]
    = syntax namelist(max=2) [, Level(cilevel) vsquish NOALLBASElevels ALL
> BASElevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EM
> PTYcells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cformat(s
> tring) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru
> ) FVWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(passthru
> ) NOABBREV ABBREV *]
    - opts_exclusive "`allbaselevels' `noallbaselevels'"
    = opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

```

```

> ----- end opts_exclus
> ive
    - opts_exclusive "`allbaselevels' `nobaselevels'"
    = opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive
    - version 8.2
    - args opts optname errcode optslab

```

```

- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
  }
- if `n' < 2 {
= if 0 < 2 {
- exit

```

```

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`baselevels' `nobaselevels'"
    = opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
      }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

```

```

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`emptycells' `noemptycells'"
    = opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {

```

```

= while `""` != "" {
    local ++n
    gettoken item`n` opts : opts, bind
}
- if `n` < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`fvlabel` `nofvlabel`"
= opts_exclusive " "
}

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts`
= local opts
    - local n 0
    - while `""opts`"" != "" {
= while `""` != "" {
    local ++n
    gettoken item`n` opts : opts, bind
}
    - if `n` < 2 {
= if 0 < 2 {
    - exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`omitted` `noomitted`"
= opts_exclusive " "
}

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts`
= local opts
    - local n 0
    - while `""opts`"" != "" {
= while `""` != "" {
    local ++n
    gettoken item`n` opts : opts, bind
}

```

```

- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive
- opts_exclusive "`lstretch' `nolstretch'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while "`opts'" != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive
- opts_exclusive "`cnsreport' `fullcnsreport'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while "`opts'" != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

```

```

> _____ end opts_exclus
> ive _____
    - opts_exclusive ``coeflegend' `selegend''
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ```opts'`` != "" {
    = while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - opts_exclusive ``noci' `nopvalues''
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ```opts'`` != "" {
    = while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - local K : list sizeof namelist
    - gettoken c_diopts c_opts : namelist

```



```

- opts_exclusive "`coding' `compare'"
= opts_exclusive " "


---


> 

---

 begin opts_exclus
> ive 

---


- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ```opts'`` != "" {
= while `""' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit


---


> 

---

 end opts_exclus
> ive 

---


- opts_exclusive "`versus' `compare'"
= opts_exclusive " "


---


> 

---

 begin opts_exclus
> ive 

---


- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ```opts'`` != "" {
= while `""' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit


---


> 

---

 end opts_exclus
> ive 

---


- opts_exclusive "`abbrev' `noabbrev'"
= opts_exclusive " "


---


> 

---

 begin opts_exclus

```

```

> ive
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
  }
- if `n' < 2 {
= if 0 < 2 {
- exit

> ----- end opts_exclus
> ive
- local allbaselevels `allbaselevels' `noallbaselevels'
= local allbaselevels
- local baselevels `baselevels' `nobaselevels'
= local baselevels
- local emptycells `emptycells' `noemptycells'
= local emptycells
- local omitted `omitted' `noomitted'
= local omitted
- local lstretch `lstretch' `nolstretch'
= local lstretch
- local fvlabel `fvlabel' `nofvlabel'
= local fvlabel
- local abbrev `abbrev' `noabbrev'
= local abbrev
- if "`allbaselevels'`baselevels'" == "" {
= if "" == "" {
- if c(showbaselevels) == "all" {
    local allbaselevels allbaselevels
  }
- else if c(showbaselevels) == "on" {
    local baselevels baselevels
  }
- }
- if "`emptycells'" == "" {
= if "" == "" {
- if c(showemptycells) == "off" {
    local emptycells noemptycells
  }
- }

```

```

- if "`omitted'" == "" {
= if "" == "" {
- if c(showomitted) == "off" {
    local omitted noomitted
  }
- }
- if "`lstretch'" == "" {
= if "" == "" {
- if c(lstretch) == "off" {
    local lstretch nolstretch
  }
- }
- if `:length local cformat' {
= if 0 {
    confirm numeric format `cformat'
    if fmtwidth("`cformat'") > 9 {
      local cformat "%9.0g"
      di "{txt}note: invalid cformat(), using default"
    }
    sreturn local cformat "`cformat'"
    local cformat `"cformat(`cformat')"'
  }
- if `:length local sformat' {
= if 0 {
    confirm numeric format `sformat'
    if fmtwidth("`sformat'") > 8 {
      local sformat "%8.2f"
      di "{txt}note: invalid sformat(), using default"
    }
    sreturn local sformat "`sformat'"
    local sformat `"sformat(`sformat')"'
  }
- if `:length local pformat' {
= if 0 {
    confirm numeric format `pformat'
    if fmtwidth("`pformat'") > 5 {
      local pformat "%5.3f"
      di "{txt}note: invalid pformat(), using default"
    }
    sreturn local pformat "`pformat'"
    local pformat `"pformat(`pformat')"'
  }
- if `K' == 1 & `:length local options' {
= if 2 == 1 & 17 {
    syntax namelist(max=2) [, `DIOPTS']
  }

```

```

- if reldif(`level', c(level)) > 1e-3 {
= if reldif(95, c(level)) > 1e-3 {
    local levelopt level(`level')
    }
- Wraapon , `fvwraapon'
= Wraapon ,

> _____ begin _get_diopts.Wra
> pon _____
    - capture syntax [, W0rd WIdth]
    - if c(rc) {
        di as err "invalid fvwraapon() option;"
        syntax [, W0rd WIdth]
        exit 198
    }
    - opts_exclusive "`word' `width'" fvwraapon
    = opts_exclusive " " fvwraapon

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ```opts'"" != "" {
    = while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
        - exit

> _____ end opts_exclus
> ive _____
    - local fvwraapon `word' `width'
    = local fvwraapon
    - if `:length local fvwraapon' {
    = if 0 {
        c_local fvwraapon fvwraapon(`fvwraapon')
    }

> _____ end _get_diopts.Wra
> pon _____
    - if "`fvwrap'" != "" {

```

```

    = if "" != "" {
        FVWrap, `fvwrap'
    }
    - c_local `c_diopts' `levelopt' `vsquish' `allbaselevels' `baselevels'
> `cnsreport' `fullcnsreport' `emptycells' `omitted' `lstretch' `coeflegend'
> `selegend' `cformat' `sformat' `pformat' `coding' `versus' `compare' `fvwrap
> `fvwrapon' `fvlabel' `noci' `nopvalues' `markdown' `citype' `abbrev'
    = c_local DUPS
    - if `K' == 2 {
    = if 2 == 2 {
    - c_local `c_opts' ``options'''
    = c_local options `"vce(robust) nolog"'
    - }
    - sreturn local coding `coding'
    = sreturn local coding
    - sreturn local versus `versus'
    = sreturn local versus
    - sreturn local compare `compare'
    = sreturn local compare
    - sreturn local level `level'
    = sreturn local level 95

```

```

> _____ end _get_diopts.GetDio
> pts _____

```

```

    - c_local `name2' ``options'''
    = c_local options `"vce(robust) nolog"'
    - }
    - local DUPS : list DUPS - DEFAULT
    - gettoken DUPS : DUPS
    - if ``DUPS''' != "" {
    = if `''' != "" {
        if (strpos(`DUPS'', "(")) {
            gettoken DUPS : DUPS, parse("(")
            local DUPS `DUPS'()'
        }
        di as err "duplicate {bf:`DUPS'} option not allowed"
        exit 198
    }
    - sreturn clear
    - foreach sname of local snames {
    - sreturn local `sname' = `S_`sname'''
    = sreturn local level = `95"'
    - }

```

```

> _____ end _get_dio
> pts _____

```

```

- mlopts mlopts, `options'
= mlopts mlopts, vce(robust) nolog

```

```

> _____ begin mlo
> pts _____
    - version 8.0
    - local maxoptlist MLOPTs(string) TRace TRACEDiffs GRADient HESSian SHOW
> STEP ITERate(int -1) TOLerance(real -1) LTOLerance(real -1) GTOLerance(real
> -1) NONRTOLerance SHOWNRtolerance SHOWTOLerance NRTOLerance(real -1) QTOLera
> nce(real -1) DIFFicult HALFSTEPonly CONSTraints(string) noCNSNOTes COLLinear
> TECHnique(passthru) VCE(passthru) DOTS depsilon(passthru) SHOWH NOTCONCAVE(
> passthru) USEVIEWS NOLOg LOg nrderiv
    - syntax namelist(id="macro names" min=1 max=2) [, `maxoptlist' * ]
    = syntax namelist(id="macro names" min=1 max=2) [, MLOPTs(string) TRace
> TRACEDiffs GRADient HESSian SHOWSTEP ITERate(int -1) TOLerance(real -1) LTOL
> erance(real -1) GTOLerance(real -1) NONRTOLerance SHOWNRtolerance SHOWTOLera
> nce NRTOLerance(real -1) QTOLerance(real -1) DIFFicult HALFSTEPonly CONSTrai
> nts(string) noCNSNOTes COLLinear TECHnique(passthru) VCE(passthru) DOTS deps
> ilon(passthru) SHOWH NOTCONCAVE(passthru) USEVIEWS NOLOg LOg nrderiv * ]
    - gettoken dest rest : namelist
    - if "`rest'" == "" {
    = if "" == "" {
    - syntax namelist [, `maxoptlist' ]
    = syntax namelist [, MLOPTs(string) TRace TRACEDiffs GRADient HESSian SH
> OWSTEP ITERate(int -1) TOLerance(real -1) LTOLerance(real -1) GTOLerance(rea
> l -1) NONRTOLerance SHOWNRtolerance SHOWTOLerance NRTOLerance(real -1) QTOLe
> rance(real -1) DIFFicult HALFSTEPonly CONSTraints(string) noCNSNOTes COLLine
> ar TECHnique(passthru) VCE(passthru) DOTS depsilon(passthru) SHOWH NOTCONCAV
> E(passthru) USEVIEWS NOLOg LOg nrderiv ]
    - }
    - local mlopts `mlopts' `trace' `tracediffs' `gradient' `hessian' `shows
> tep' `difficult' `halfsteponly' `nonrtolerance' `shownrtolerance' `showtoler
> ance' `dots' `depsilon' `showh' `notconcave' `useviews' `log' `nolog' `nrder
> iv'
    = local mlopts                                nolog
    - if `tolerance' != -1 {
    = if -1 != -1 {
        local tol "tolerance(`tolerance')"
    }
    - if `ltolerance' != -1 {
    = if -1 != -1 {
        local ltol "ltolerance(`ltolerance')"
    }
    - if `gtolerance' != -1 {
    = if -1 != -1 {
        local gtol "gtolerance(`gtolerance')"

```

```

    }
    - if `nrtolerance' != -1 {
= if -1 != -1 {
    local nrtol "nrtolerance(`nrtolerance')"
```

```

    }
    - if `qtolerance' != -1 {
= if -1 != -1 {
    local qtol "qtolerance(`qtolerance')"
```

```

    }
    - if `iterate' != -1 {
= if -1 != -1 {
    local iter "iterate(`iterate')"
```

```

    }
    - sreturn clear
    - if "`technique'\vce'" != "" {
= if "vce(robust)" != "" {
    - ml_technique, `technique' `vce' nodefault
= ml_technique, vce(robust) nodefault
```

```

> ----- begin ml_technique
> que
    - version 8.0
    - syntax [, TECHnique(string) VCE(passthru) noDEFault ]
    - sreturn clear
    - _vce_parse, argopt(CLuster) opt(Hessian OIM Opg NATIVE Robust) :, `v
> ce'
    = _vce_parse, argopt(CLuster) opt(Hessian OIM Opg NATIVE Robust) :, vc
> e(robust)
```

```

> ----- begin _vce_parse
> rse
    - version 10
    - _on_colon_parse `0'
    = _on_colon_parse , argopt(CLuster) opt(Hessian OIM Opg NATIVE Robus
> t) :, vce(robust)
```

```

> ----- begin _on_colon_parse
> rse
    - version 8.2
    - sreturn local before ""
    - sreturn local after ""
    - gettoken before after : 0, parse(":") bind match(par) quotes
    - if "`par'" != "" {
= if "" != "" {
    local before `"(before)'"
    }
```

```

- if ``before''' == ":" {
= if `", argopt(Cluster) opt(Hessian OIM Opg NATIVE Robust) '' ==
> ":" {
    sreturn local after ``after'''
    exit
    }
- while ``COLON''' != ":" & ``after''' != "" {
= while `''' != ":" & `:", vce(robust)'' != "" {
- gettoken COLON after : after, parse(":") bind match(par) quotes
- if "par'" != "" {
= if "" != "" {
    local before `before' (`COLON')
    local COLON
    }
- else if ``COLON''' != ":" {
= else if `:"' != ":" {
    local before ``before' `COLON'''
    local COLON
    }
- }
- while ``COLON''' != ":" & ``after''' != "" {
= while `:"' != ":" & `", vce(robust)'' != "" {
    gettoken COLON after : after, parse(":") bind match(par) quotes
    if "par'" != "" {
        local before `before' (`COLON')
        local COLON
        }
    else if ``COLON''' != ":" {
        local before ``before' `COLON'''
        local COLON
        }
    }
- if ``COLON''' != ":" {
= if `:"' != ":" {
    di as err "" found where ':' expected"
    exit 198
    }
- sreturn local before ``before'''
= sreturn local before `", argopt(Cluster) opt(Hessian OIM Opg NAT
> IVE Robust) ''
- sreturn local after ``after'''
= sreturn local after `", vce(robust)''

> _____ end _on_colon_pa
> rse _____
- local 0 ``s(before)'''

```



```

= local 0 `", argopt(CLuster) opt(Hessian OIM Opg NATIVE Robust) ""
- local user ``s(after)""
= local user `", vce(robust)""
- syntax [varname(default=none)], [ OPTlist(namelist) ARGOPTlist(nam
> elist) PWallowed(namelist) OLD_is_ok NOARGOPT_is_ok ]
- local touse `varlist'
= local touse
- tempname o a
- .`o' = ._optlist.new
= .__000000 = ._optlist.new
- class {
- instance:
-     array options = {}
-     array names = {}
- }
- local optlist : list uniq optlist
- foreach name of local optlist {
- .`o'.adopt `name'
= .__000000.adopt Hessian
}

> _____ begin _optlist.add
> opt _____
- version 9
- syntax name(name=optspec) [, PASSthru]
- local mname = lower("`optspec'")
= local mname = lower("Hessian")
- if "`passthru'" != "" {
= if "" != "" {
    local optspec `optspec'(passthru)
}
- .options.Arrpush "`optspec'"
= .options.Arrpush "Hessian"
- .names.Arrpush "`mname'"
= .names.Arrpush "hessian"
}

> _____ end _optlist.add
> opt _____
- }
- .`o'.adopt `name'
= .__000000.adopt OIM
}

> _____ begin _optlist.add
> opt _____
- version 9
- syntax name(name=optspec) [, PASSthru]
- local mname = lower("`optspec'")

```

```

= local mname = lower("OIM")
- if "`passthru'" != "" {
= if "" != "" {
    local optspec `optspec'(passthru)
  }
- .options.Arrpush "`optspec'"
= .options.Arrpush "OIM"
- .names.Arrpush "`mname'"
= .names.Arrpush "oim"

```

```

> _____ end _optlist.add
> opt _____
- }
- .`o'.addopt `name'
= .__000000.addopt Opg

```

```

> _____ begin _optlist.add
> opt _____
- version 9
- syntax name(name=optspec) [, PASSthru]
- local mname = lower("`optspec'")
= local mname = lower("Opg")
- if "`passthru'" != "" {
= if "" != "" {
    local optspec `optspec'(passthru)
  }
- .options.Arrpush "`optspec'"
= .options.Arrpush "Opg"
- .names.Arrpush "`mname'"
= .names.Arrpush "opg"

```

```

> _____ end _optlist.add
> opt _____
- }
- .`o'.addopt `name'
= .__000000.addopt NATIVE

```

```

> _____ begin _optlist.add
> opt _____
- version 9
- syntax name(name=optspec) [, PASSthru]
- local mname = lower("`optspec'")
= local mname = lower("NATIVE")
- if "`passthru'" != "" {
= if "" != "" {
    local optspec `optspec'(passthru)

```

```

        }
        - .options.Arrpush "`optspec'"
        = .options.Arrpush "NATIVE"
        - .names.Arrpush "`mname'"
        = .names.Arrpush "native"
    }
end _optlist.add

> opt
    - }
    - .`o'.addopt `name'
    = .__000000.addopt Robust

begin _optlist.add

> opt
    - version 9
    - syntax name(name=optspec) [, PASSthru]
    - local mname = lower("`optspec'")
    = local mname = lower("Robust")
    - if "`passthru'" != "" {
    = if "" != "" {
        local optspec `optspec'(passthru)
    }
    - .options.Arrpush "`optspec'"
    = .options.Arrpush "Robust"
    - .names.Arrpush "`mname'"
    = .names.Arrpush "robust"

end _optlist.add

> opt
    - }
    - .`a' = ._optlist.new
    = .__000001 = ._optlist.new
    - local argoptlist : list uniq argoptlist
    - foreach name of local argoptlist {
    - .`a'.addopt `name'
    = .__000001.addopt CLuster

begin _optlist.add

> opt
    - version 9
    - syntax name(name=optspec) [, PASSthru]
    - local mname = lower("`optspec'")
    = local mname = lower("CLuster")
    - if "`passthru'" != "" {
    = if "" != "" {
        local optspec `optspec'(passthru)

```

```

        }
        - .options.Arrpush "`optspec'"
        = .options.Arrpush "CLuster"
        - .names.Arrpush "`mname'"
        = .names.Arrpush "cluster"
    }
end _optlist.add
> opt
    - }
    - local OPTNAMES ```. `o'.dumpnames'''
end _optlist.dumpna
> mes
    - version 9
    - forval i = 1/`.names.arnels' {
    = forval i = 1/5 {
    - local namelist `namelist' `.names[`i']'
    = local namelist hessian
    - }
    - local namelist `namelist' `.names[`i']'
    = local namelist hessian oim
    - }
    - local namelist `namelist' `.names[`i']'
    = local namelist hessian oim opg
    - }
    - local namelist `namelist' `.names[`i']'
    = local namelist hessian oim opg native
    - }
    - local namelist `namelist' `.names[`i']'
    = local namelist hessian oim opg native robust
    - }
    - local namelist : list uniq namelist
    - sreturn local namelist ```. `namelist'''
    = sreturn local namelist `hessian oim opg native robust''
    - class exit ```. `namelist'''
    = class exit `hessian oim opg native robust''
end _optlist.dumpna
> mes
    = local OPTNAMES `hessian oim opg native robust''
    - local ARGOPTNAMES ```. `a'.dumpnames'''
end _optlist.dumpna
> mes
    - version 9
    - forval i = 1/`.names.arnels' {

```

```

= forval i = 1/1 {
- local namelist `namelist' `.names[`i']'
= local namelist cluster
- }
- local namelist : list uniq namelist
- sreturn local namelist ``namelist'''
= sreturn local namelist "cluster"
- class exit ``namelist'''
= class exit "cluster"

```

```
> end _optlist.dumpna
```

```

> mes
= local ARGOPTNAMES "cluster"
- local AND : list OPTNAMES & ARGOPTNAMES
- if `:list sizeof AND' {
= if 0 {
di as err "vctype `:word 1 of `AND'' specified twice"
exit 198
}
- local pwallowed : list uniq pwallowed
- local pwlist robust cluster
- foreach n of local pwallowed {
local lc = lower("`n'")
local pwlist `pwlist' `lc'
}
- if "`old_is_ok'" != "" {
= if "" != "" {
local ROBUST robust
if `:list ROBUST in OPTNAMES' {
local robust Robust
}
local CLUSTER cluster
if `:list CLUSTER in ARGOPTNAMES' {
local cluster CLuster(varname)
}
}
- local 0 ``user'''
= local 0 `", vce(robust)'''
- syntax [fw aw pw iw] [, VCE(string asis) `robust' `cluster' ]
= syntax [fw aw pw iw] [, VCE(string asis) ]
- if ``vce''' != "" {
= if "robust" != "" {
- gettoken name args : vce, parse(" ,")
- local args : list retok args
- capture ParseVCE `o' `a' , `name'
= capture ParseVCE __000000 __000001 , robust

```

```

> _____ begin _vce_parse.Parse
> VCE _____
    - gettoken 0 0 : 0, parse(" ,")
    - gettoken A 0 : 0, parse(" ,")
    - local OPTSPECS ```.`0'.dumpoptions' `.`A'.dumpoptions'''
> _____ begin _optlist.dumpopti
> ons _____
    - version 9
    - forval i = 1/`.options.arnels' {
    = forval i = 1/5 {
    - local optlist `optlist' `.options[`i']'
    = local optlist Hessian
    - }
    - local optlist `optlist' `.options[`i']'
    = local optlist Hessian OIM
    - }
    - local optlist `optlist' `.options[`i']'
    = local optlist Hessian OIM Opg
    - }
    - local optlist `optlist' `.options[`i']'
    = local optlist Hessian OIM Opg NATIVE
    - }
    - local optlist `optlist' `.options[`i']'
    = local optlist Hessian OIM Opg NATIVE Robust
    - }
    - local optlist : list uniq optlist
    - sreturn local optlist ```optlist'''
    = sreturn local optlist `"Hessian OIM Opg NATIVE Robust"'
    - class exit ```optlist'''
    = class exit `"Hessian OIM Opg NATIVE Robust"'
> _____ end _optlist.dumpopti
> ons _____
> _____ begin _optlist.dumpopti
> ons _____
    - version 9
    - forval i = 1/`.options.arnels' {
    = forval i = 1/1 {
    - local optlist `optlist' `.options[`i']'
    = local optlist CLuster
    - }
    - local optlist : list uniq optlist
    - sreturn local optlist ```optlist'''

```

```

        = sreturn local optlist `"CLuster"'
        - class exit `"'optlist'"'
        = class exit `"CLuster"'
    _____
> _____ end _optlist.dumpopti
> ons _____
        = local OPTSPECS `"Hessian OIM Opg NATIVE Robust CLuster"'
        - local OPTNAMES `"'`0'.dumpnames' `".`A'.dumpnames'"'
    _____
> _____ begin _optlist.dumpna
> mes _____
        - version 9
        - forval i = 1/`.names.arnels' {
        = forval i = 1/5 {
        - local namelist `namelist' `'.names[`i']'
        = local namelist hessian
        - }
        - local namelist `namelist' `'.names[`i']'
        = local namelist hessian oim
        - }
        - local namelist `namelist' `'.names[`i']'
        = local namelist hessian oim opg
        - }
        - local namelist `namelist' `'.names[`i']'
        = local namelist hessian oim opg native
        - }
        - local namelist `namelist' `'.names[`i']'
        = local namelist hessian oim opg native robust
        - }
        - local namelist : list uniq namelist
        - sreturn local namelist `"'namelist'"'
        = sreturn local namelist `"hessian oim opg native robust"'
        - class exit `"'namelist'"'
        = class exit `"hessian oim opg native robust"'
    _____
> _____ end _optlist.dumpna
> mes _____
    _____
> _____ begin _optlist.dumpna
> mes _____
        - version 9
        - forval i = 1/`.names.arnels' {
        = forval i = 1/1 {
        - local namelist `namelist' `'.names[`i']'
        = local namelist cluster
        - }

```

```

- local namelist : list uniq namelist
- sreturn local namelist ``namelist'''
= sreturn local namelist "cluster"
- class exit ``namelist'''
= class exit "cluster"

> _____ end _optlist.dumpna
> mes _____
= local OPTNAMES "hessian oim opg native robust cluster"
- syntax [, `OPTSPECS']
= syntax [, Hessian OIM Opg NATIVE Robust CLuster]
- foreach OPT of local OPTNAMES {
- if ````OPT'''' != "" {
= if ``'' != "" {
return local vce `OPT'
continue, break
}
- }
- if ````OPT'''' != "" {
= if ``'' != "" {
return local vce `OPT'
continue, break
}
- }
- if ````OPT'''' != "" {
= if ``'' != "" {
return local vce `OPT'
continue, break
}
- }
- if ````OPT'''' != "" {
= if ``'' != "" {
return local vce `OPT'
continue, break
}
- }
- if ````OPT'''' != "" {
= if "robust" != "" {
- return local vce `OPT'
= return local vce robust
- continue, break
}
}

> _____ end _vce_parse.Parse
> VCE _____

```



```

- if c(rc) {
  di as err "vcetype {bf:`name'} not allowed"
  exit 198
}
- local name `r(vce)'
= local name robust
- if "`weight'" == "pweight" & !`:list name in pwlist' {
= if "" == "pweight" & !1 {
  di as err "pweights are not allowed with vce(`name')"
  exit 198
}
- return add
- if ```robust'"" != "" & !inlist("`name'", "", "robust", "eim", "oim", "
> cluster") {
= if ```` != "" & !inlist("robust", "", "robust", "eim", "oim", "cluster"
> ) {
  opts_exclusive "`robust' vce(`name')"
}
- if "`name'" == "cluster" {
= if "robust" == "cluster" {
  if ```args'"" == "" {
    di as err "invalid vce(cluster) option"
    exit 198
  }
  confirm var `args'
  unab args : `args'
  local markout `args'
  if "`cluster'" != "" {
    if !`:list args == cluster' {
      di as err "options cluster() and vce(cluster) are in conflict"
      exit 100
    }
  }
}
- else if "`cluster'" != "" & !inlist("`name'", "eim", "oim") {
= else if "" != "" & !inlist("robust", "eim", "oim") {
  opts_exclusive "cluster() vce(`name')"
}
- if ```args'"" != "" {
= if ```` != "" {
  if !`:list name in ARGOPTNAMES' {
    di as err "invalid vce() option"
    exit 198
  }
  if "`name'" == "hc2" {
    confirm var `args'

```

```

unab args : `args'
local markout `args'
}
return local vceargs ```:list retok args'''
}
- else if `:list name in ARGOPTNAMES' {
= else if 0 {
  if "`noargopt_is_ok'" == "" {
    di as err "invalid vce() option"
    exit 198
  }
}
- }
- else {
  if "`weight'" == "pweight" | "`robust'" != "" {
    local vce robust
  }
  if "`cluster'" != "" {
    local vce cluster
    local args `cluster'
    local markout `cluster'
  }
  return local vce ```:vce'''
  return local vceargs ```:args'''
}
- if "`return(vce)'" != "" {
= if "robust" != "" {
- if ```:return(vceargs)''' != "" {
= if `''' != "" {
  local ss " "
}
- return local vceopt `"vce(`return(vce)''ss'`return(vceargs)')'"
= return local vceopt `"vce(robust)'"
- }
- if "`return(vce)'" == "cluster" {
= if "robust" == "cluster" {
  return local cluster `return(vceargs)'
}
- if inlist("`return(vce)'", "robust", "cluster") {
= if inlist("robust", "robust", "cluster") {
- return local robust robust
- }
- if "`touse'" != "" {
= if "" != "" {
  if "`markout'" != "" {
    markout `touse' `markout', strok

```

```

    }
    }

> ----- end _vce_pa
> rse -----
    - sreturn local vce ``r(vce)'''
    = sreturn local vce ``robust''
    - sreturn local vceargs ``r(vceargs)'''
    = sreturn local vceargs `'''
    - sreturn local vceopt ``r(vceopt)'''
    = sreturn local vceopt ``vce(robust)''
    - if ``s(vce)'' == "hessian" {
    = if "robust" == "hessian" {
        sreturn local vce "oim"
        sreturn local vceopt "vce(oim)"
    }
    - if "$ML_vce" == "robust" & !inlist("s(vce)", "", "oim", "robust")
> {
    = if "" == "robust" & !inlist("robust", "", "oim", "robust") {
        di as err "options robust and vce(`s(vce)') may not be combined"
        exit 198
    }
    - get_technique `technique', `default'
    = get_technique , nodefault

> ----- begin ml_technique.get_techni
> que -----
    - syntax [anything(equalok)] [, noDefault ]
    - local 0 ``anything'''
    = local 0 `'''
    - if ``default'' == "" {
    = if "nodefault" == "" {
        local default_num 5
    }
    - else local default_num 0
    - gettoken tname rest : 0, parse(" =")
    - while ``tname'' != "" {
    = while "" != "" {
        local tname = lower(``tname'')
        capture confirm name `tname'
        if _rc {
            local rc = _rc
            di as err ``tname' is an invalid name in technique() option"
            exit `rc'
        }
        get_tech tech , `tname'

```

```

gettoken num : rest, parse(" =")
if "`num'" == "" {
gettoken num rest : rest, parse(" =")
gettoken num : rest, parse(" =")
}
capture confirm integer number `num'
if !_rc gettoken num rest : rest, parse(" =")
else local num `default_num'
if `num' < 0 {
di as err "negative integers are not allowed in technique() option
> "

exit 125
}
else if `num' > 0 {
local techlist `techlist' `tech'
local numlist `numlist' `num'
local technique `technique' `tech' `num'
}
else if "`default'" != "" {
local techlist `techlist' `tech'
local numlist `numlist' `num'
local technique `technique' `tech'
}
gettoken tname rest : rest, parse(" =")
}
- if "`default'`techlist'" == "" {
= if "nodefault" == "" {
local techlist nr
local numlist `default_num'
}
- if "`default'" == "" {
= if "nodefault" == "" {
sreturn local techlist `:list retok techlist'
sreturn local numlist `:list retok numlist'
}
- sreturn local technique `:list retok technique'
= sreturn local technique

> _____ end ml_technique.get_techni
> que _____
> _____ end ml_techni
> que _____
- if ``s(technique)'' != "" {
= if `'' != "" {
local technique "technique(`s(technique)'"

```

```

    }
    - if "`s(vce)'" != "" {
= if "robust" != "" {
    - local vce "`s(vceopt)'"
= local vce "vce(robust)"
    - }
    - sreturn local technique "`technique'"
= sreturn local technique ""
    - sreturn local vce "`vce'"
= sreturn local vce "vce(robust)"
    - }
    - if "`constraints'" != "" {
= if "" != "" {
    capture confirm name `constraints'
    if _rc {
        CheckClist constraints , constraints(`constraints')
    }
    else {
        CheckCmat `constraints'
    }
    local const "constraints(`constraints')"
    sreturn local constraints "`constraints'"
    }
    - sreturn local collinear "`collinear'"
= sreturn local collinear ""
    - c_local `dest' `mlopts' `tol' `ltol' `gtol' `nrtol' `iter' `const' `cn
> snotes' `collinear' `technique' `vce' `qtol'
    = c_local mlopts nolog          vce(robust)
    - if "`rest'" != "" {
= if "" != "" {
    c_local `rest' ``options''
    }
}



---


> _____ end mlo
> pts _____
    - local coll `s(collinear)'
= local coll
    - local cns `s(constraints)'
= local cns
    - local mlopts `mlopts' `crittype'
= local mlopts nolog          vce(robust)
    - if ``score'' != "" {
= if `""' != "" {
    confirm new variable `score'
    local nword : word count `score'
    if `nword' > 1 {

```

```

di in red "score() must contain the name of only " "one new variable"
exit 198
}
tempvar scvar
local scopt score(`scvar')
}
- if "`offset'"!="" & "`exposur'"!="" {
= if ""!="" & ""!="" {
di in red "only one of offset() or exposure() can be specified"
exit 198
}
- if "`constan'"!="" {
= if ""!="" {
local nvar : word count `varlist'
if `nvar' == 1 {
di in red "independent variables required with " "noconstant option"
exit 100
}
}
- marksample touse
- if ``cluster'"!="" {
= if `""'!="" {
markout `touse' `cluster', strok
local clopt cluster(`cluster')
}
- if "`exposur'"!="" {
= if ""!="" {
capture assert `exposur' > 0 if `touse'
if _rc {
di in red "exposure() must be greater than zero"
exit 459
}
tempvar offset
qui gen double `offset' = ln(`exposur')
local offvar "ln(`exposur')"
```

```

= _fv_check_depvar y_timing_max
- tsunab y : `y'
= tsunab y : y_timing_max

```

```

> ----- begin tsu
> nab -----
- version 6
- gettoken user 0: 0, parse(" :")
- gettoken colon 0: 0, parse(" :")
- if ``colon'' != ":" { error 198 }
= if ``:"' != ":" { error 198 }
- syntax [varlist(ts default=empty)] [, MIN(integer 1) MAX(integer 32000
> ) NAME(string)]
- c_local `user' `varlist'
= c_local y y_timing_max
- local n : word count `varlist'
= local n : word count y_timing_max
- if `n'>=`min' & `n'<=`max' { exit }
= if 1>=1 & 1<=32000 { exit }

```

```

> ----- end tsu
> nab -----
- local yname : subinstr local y "." "_"
- if ``weight''!= "" {
= if ""!= "" {
if ``weight''=="fweight" {
local wt `[fw`exp']''
}
else if ``weight''=="iweight" {
local wt `[iw`exp']''
}
else local wt `[aw`exp']''
}
- summarize `y' `wt' if `touse', meanonly
= summarize y_timing_max if __000000, meanonly
- if r(N) == 0 { error 2000 }
- if r(N) == 1 { error 2001 }
- if r(min) < 0 {
di in red ``y' must be greater than or equal to zero"
exit 459
}
- if r(min) == r(max) & r(min) == 0 {
di in red ``y' is zero for all observations"
exit 498
}
- tempname mean nobis

```

```

- scalar `mean' = r(mean)
= scalar __000001 = r(mean)
- scalar `nobs' = r(N)
= scalar __000002 = r(N)
- if "`display'"==" " {
= if ""==" " {
- capture assert `y' == int(`y') if `touse'
= capture assert y_timing_max == int(y_timing_max) if __000000
- if _rc {
__New_Note `0'
}
- }
- if "`display'"==" " & "`weight'"=="aweight" {
= if ""==" " & ""=="aweight" {
di in blu "note: you are responsible for interpretation " "of analytic w
> eights."
}
- if "`constan``cns'"==" " & "`cluster'"==" " & "`weight'"!="pweight" {
= if ""==" " & ""==" " & ""!="pweight" {
- tempname c
- if "`offset'"!=" " {
= if ""!=" " {
SolveC `y' `offset' [`weight'`exp'] if `touse', n(`nobs') mean(`mean')
scalar `c' = r(_cons)
if `c'>=. {
di in blu "note: exposure = exp(`offvar') overflows;" _n " could no
> t estimate constant-only model" _c
if "`exposur'"==" " {
di in blu _n " use exposure() option for exposure = `offvar'."
}
else di in blu "."
local cfail 1
}
local c "`c'+`offset'"
}
- else scalar `c' = ln(`mean')
= else scalar __000003 = ln(__000001)
- if "`cfail'"==" " {
= if ""==" " {
- LikePois `y' `c' [`weight'`exp'] if `touse', n(`nobs')
= LikePois y_timing_max __000003 [] if __000000, n(__000002)
}
}
> _____ begin poisson.LikeP
> ois _____
- gettoken y 0 : 0
- gettoken xb 0 : 0

```



```

- syntax [fw aw pw iw] [if] , Nobs(string)
- if "`weight'"!="" {
= if ""!="" {
  if "`weight'"=="fweight" {
    local wt `[fw`exp']"
  }
  else if "`weight'"=="iweight" {
    local wt `[iw`exp']"
  }
  else local wt `[aw`exp']"
}
- tempvar lnf
- qui gen double `lnf' = `y'*(`xb')-exp(`xb')-lgamma(`y'+1) `if'
= qui gen double __000004 = y_timing_max*(__000003)-exp(__000003)-lgamma
> a(y_timing_max+1) if __000000
- summarize `lnf' `wt' `if', meanonly
= summarize __000004 if __000000, meanonly
- if r(N) != `nobs' { exit }
= if r(N) != __000002 { exit }
- if "`weight'"=="aweight" {
= if ""=="aweight" {
  ret scalar lnf = r(N)*r(mean)
}
- else ret scalar lnf = r(sum)

> _____ end poisson.LikeP
> ois _____
- if r(lnf)<. {
- local ll0 "lf0(1 `r(lnf)')"
= local ll0 "lf0(1 -420.2971615663282)"
- }
- else {
di in blu "note: could not compute " "constant-only model log likelihood
> ."
}
- }
- }
- if `fvops' {
= if 1 {
- local rmcoll "version 11: _rmcoll"
- }
- else local rmcoll _rmcoll
- if "`display'"!="" & "`weight'"=="aweight" {
= if ""!="" & ""=="aweight" {
  `rmcoll' `xvars' [iw`exp'] if `touse', `constan' `coll'
}
}

```

```

- else `rmcoll' `xvars' [`weight'`exp'] if `touse', `constan' `coll'
= else version 11: _rmcoll rule_g rule_itr estimated [] if __000000,
- local xvars `r(varlist)'
= local xvars rule_g rule_itr estimated
- if "`from'"==" " {
= if ""==" " {
- `vv' Ipois `y' `xvars' [`weight'`exp'] if `touse', n(`nobs') mean(`mean'
> ) `constan' `offopt'
= version 18.5, missing: Ipois y_timing_max rule_g rule_itr estimated [] i
> f __000000, n(__000002) mean(__000001)

-----
> ----- begin poisson.Ip
> ois -----
- local vv : display "version " string(_caller()) ", missing:"
- version 6, missing
- syntax varlist(fv ts) [fw aw pw iw/] [if] , Nobs(string) Mean(string)
> [ noCONstant OFFset(string) ]
- gettoken y xvars : varlist
- tempvar xb z
- tempname b1 b2 lnf1
- if "`weight'"!=" " {
= if ""!=" " {
local awt "`[aw=`exp']"
local wt "`(`exp')*"
local exp "`=`exp'"
}
- quietly {
- if "`offset'"!=" " {
= if ""!=" " {
tempvar ynew
gen double `ynew' = `y' - `offset'*`mean' `if'
local poff "+`offset'"
}
- else local ynew `y'
= else local ynew y_timing_max
- `vv' _regress `ynew' `xvars' `awt' `if', `constan'
= version 18.5, missing: _regress y_timing_max rule_g rule_itr estimate
> d if __000000,

-----
> ----- begin _ereturn_disp
> lay -----
- version 11
- if "`e(b)'" == "" & "`e(V)'" == "" {
= if "matrix" == "" & "matrix" == "" {
exit
}

```

```

- if "`e(cmd)'" == "regress" {
= if "regress" == "regress" {
- local ALTOPT Beta
- }
- syntax [, eform(passthru) First neq(integer -1) PLus `ALTOPT' *]
= syntax [, eform(passthru) First neq(integer -1) PLus Beta *]
- _get_mcompare, `options'
= _get_mcompare, level(95.00) fwrap(1)

```

```

> _____ begin _get_mcomp
> are _____
- version 11
- local cmd ``e(cmd)''
= local cmd ``regress''
- syntax [name(name=caller)] [, *]
- local is_pwc = inlist("pwcompare", "`cmd'", "`caller'") | inlist("
> pwmean", "`cmd'", "`caller'")
= local is_pwc = inlist("pwcompare", "regress", "") | inlist("pwmean
> ", "regress", "")
- local is_marg = inlist("margins", "`cmd'", "`e(cmd2)'", "`caller'"
> )
= local is_marg = inlist("margins", "regress", "", "")
- local OPTIONS NOADJust BONferroni DUNCan DUNNett SCHeffe SIDak SNK
> TUKey ADJustall
- if `is_pwc' {
= if 0 {
syntax [name] [, `OPTIONS' MCOMPare(string) *]
}
- else {
- syntax [name] [, MCOMPare(string) *]
- local suboption mcompare()
- }
- sreturn clear
- sreturn local options ``options''
= sreturn local options ``level(95.00) fwrap(1)''
- if `is_pwc' {
= if 0 {
local METHOD `noadjust' `bonferroni' `duncan' `dunnett' `scheffe'
> `sidak' `snk' `tukey'
local METHOD : list uniq METHOD
opts_exclusive ``METHOD''
local ALL `adjustall'
opts_exclusive ``noadjust' `ALL''
}
- local 0 `", `mcompare''
= local 0 `", ""

```

```

        - capture syntax [, `OPTIONS']
        = capture syntax [, NOADJust BONferroni DUNCAn DUNNett SCHeffe SIDak
> SNK TUKey ADJustall]
        - if c(rc) {
            di as err "invalid mcompare() option;"
            di as err "method ``mcompare'' not allowed"
            error 198
        }
        - local METHOD `METHOD' `noadjust' `bonferroni' `duncan' `dunnett' `
> scheffe' `sidak' `snk' `tukey'
        = local METHOD
        - local METHOD : list uniq METHOD
        - local ALL `ALL' `adjustall'
        = local ALL
        - local ALL : list uniq ALL
        - opts_exclusive "" `METHOD' "" `suboption'
        = opts_exclusive "" mcompare()

> _____ begin opts_exclus
> ive _____
        - version 8.2
        - args opts optname errcode optslab
        - local opts `opts'
        = local opts
        - local n 0
        - while ```opts'"" != "" {
        = while `""' != "" {
            local ++n
            gettoken item`n' opts : opts, bind
        }
        - if `n' < 2 {
        = if 0 < 2 {
            - exit

> _____ end opts_exclus
> ive _____
        - if "" `METHOD' "" == "" {
        = if "" == "" {
            - if "" `ALL' "" != "" {
            = if "" != "" {
                di as err "multiple comparison method required with the adjustall
> option"
                exit 198
            }
            - local METHOD noadjust
            - local noadjust noadjust

```

```

- }
- opts_exclusive "`ALL' `noadjust'" `suboption'
= opts_exclusive " noadjust" mcompare()

```

```

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts noadjust
- local n 0
- while ``opts'" != "" {
= while `"noadjust'" != "" {
- local ++n
- gettoken item`n' opts : opts, bind
= gettoken item1 opts : opts, bind
- }
- while ``opts'" != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 1 < 2 {
- exit

```

```

> ----- end opts_exclus
> ive -----
- local EXCLUDE duncan dunnett snk tukey
- if `:list METHOD in EXCLUDE' {
= if 0 {
  if `is_pwc' {
    local opt : copy local METHOD
  }
  else {
    local opt "mcompare(`METHOD')"
  }
  local cmdlist anova manova regress mvreg pwmean
  if "`cmd'" == "pwcompare" {
    local cmd ``e(cmd_est)'"
  }
  if `is_marg' {
    local cmd margins
  }
  if !`:list cmd in cmdlist' | !`is_pwc' {
    di as err `"method `opt' is not allowed with results from `cmd'"

```

```

        exit 322
    }
    if ``e(prefix)'' == "svy" {
di as err ``method `opt' is not allowed with results using the svy
> prefix''
        exit 322
    }
    local vce ``e(vce)''
    if !inlist("`vce'", "", "ols") {
di as err ``method `opt' is not allowed with results using vce(`vc
> e')''
        exit 322
    }
}
- local EXCLUDE duncan dunnett snk tukey scheffe
- if `:list METHOD in EXCLUDE' {
= if 0 {
    if ""ALL"" != "" {
di as err ``option adjustall is not allowed with method `METHOD''
exit 198
    }
}
- sreturn local method ``METHOD''
= sreturn local method ``noadjust''
- sreturn local adjustall ``ALL''
= sreturn local adjustall ``''

> _____ end _get_mcomp
> are _____
    - if ``s(method)'' != "" {
= if "noadjust" != "" {
    - loca mcopt mcompare(`s(method)' `s(adjustall)')
= loca mcopt mcompare(noadjust )
    - }
    - _get_diopts diopts, `s(options)'
= _get_diopts diopts, level(95.00) fvwrap(1)

> _____ begin _get_dio
> pts _____
    - version 11
    - syntax namelist(max=2) [, *]
    - gettoken name1 namelist : namelist
    - gettoken name2 namelist : namelist
    - GetDiopts diopts options, `options'
= GetDiopts diopts options, level(95.00) fvwrap(1)

```

```

> _____ begin _get_diopts.GetDio
> pts _____
    - local DIOPTS Level(cilevel) vsquish NOALLBASElevels ALLBASElevel
> s NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EMPTYcells
> NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cformat(string) sf
> ormat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru) FVWRAP0
> N(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(passthru) NOABBRE
> V ABBREV
    - syntax namelist(max=2) [, `DIOPTS' *]
    = syntax namelist(max=2) [, Level(cilevel) vsquish NOALLBASElevels
> ALLBASElevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcell
> s EMPTYcells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cform
> at(string) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(pass
> thru) FVWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(pass
> thru) NOABBREV ABBREV *]
    - opts_exclusive "`allbaselevels' `noallbaselevels'"
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ```opts'`` != "" {
    = while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`allbaselevels' `nobaselevels'"
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0

```

```

- while ``opts'' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
  - opts_exclusive "`baselevels' `nobaselevels'"
  = opts_exclusive " "
}

> ----- begin opts_exclus
> ive -----
  - version 8.2
  - args opts optname errcode optslab
  - local opts `opts'
  = local opts
  - local n 0
  - while ``opts'' != "" {
  = while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
  }
  - if `n' < 2 {
  = if 0 < 2 {
  - exit
}

> ----- end opts_exclus
> ive -----
  - opts_exclusive "`emptycells' `noemptycells'"
  = opts_exclusive " "
}

> ----- begin opts_exclus
> ive -----
  - version 8.2
  - args opts optname errcode optslab
  - local opts `opts'
  = local opts
  - local n 0
  - while ``opts'' != "" {
  = while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
  }

```



```

    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`fvlabel' `nofvlabel'"
= opts_exclusive " "
}
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ``opts' != "" {
= while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`omitted' `noomitted'"
= opts_exclusive " "
}
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ``opts' != "" {
= while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}

```

```

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`lstretch' `nolstretch'"
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`cnsreport' `fullcnsreport'"
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`coeflegend' `selegend'"

```

```

= opts_exclusive " "


---


> 

---

 begin opts_exclus
> ive 

---


    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit


---


> 

---

 end opts_exclus
> ive 

---


    - opts_exclusive "`noci' `nopvalues'"
    = opts_exclusive " "


---


> 

---

 begin opts_exclus
> ive 

---


    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit


---


> 

---

 end opts_exclus
> ive 

---


    - local K : list sizeof namelist
    - gettoken c_diopts c_opts : namelist
    - opts_exclusive "`coding' `compare'"
    = opts_exclusive " "


---



```

```

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ```opts'`` != "" {
    = while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    -----

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`versus' `compare'"
    = opts_exclusive " "
    -----

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ```opts'`` != "" {
    = while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    -----

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`abbrev' `noabbrev'"
    = opts_exclusive " "
    -----

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab

```

```

- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- local allbaselevels `allbaselevels' `noallbaselevels'
= local allbaselevels
- local baselevels `baselevels' `nobaselevels'
= local baselevels
- local emptycells `emptycells' `noemptycells'
= local emptycells
- local omitted `omitted' `noomitted'
= local omitted
- local lstretch `lstretch' `nolstretch'
= local lstretch
- local fvlabel `fvlabel' `nofvlabel'
= local fvlabel
- local abbrev `abbrev' `noabbrev'
= local abbrev
- if "`allbaselevels'`baselevels'" == "" {
= if "" == "" {
- if c(showbaselevels) == "all" {
    local allbaselevels allbaselevels
  }
- else if c(showbaselevels) == "on" {
    local baselevels baselevels
  }
- }
- if "`emptycells'" == "" {
= if "" == "" {
- if c(showemptycells) == "off" {
    local emptycells noemptycells
  }
- }
- if "`omitted'" == "" {
= if "" == "" {
- if c(showomitted) == "off" {

```

```

    local omitted noomitted
  }
- }
- if "`lstretch'" == "" {
= if "" == "" {
- if c(lstretch) == "off" {
  local lstretch nolstretch
}
- }
- if `:length local cformat' {
= if 0 {
  confirm numeric format `cformat'
  if fmtwidth("`cformat'") > 9 {
    local cformat "%9.0g"
    di "{txt}note: invalid cformat(), using default"
  }
  sreturn local cformat "`cformat'"
  local cformat `cformat(`cformat')'
}
- if `:length local sformat' {
= if 0 {
  confirm numeric format `sformat'
  if fmtwidth("`sformat'") > 8 {
    local sformat "%8.2f"
    di "{txt}note: invalid sformat(), using default"
  }
  sreturn local sformat "`sformat'"
  local sformat `sformat(`sformat')'
}
- if `:length local pformat' {
= if 0 {
  confirm numeric format `pformat'
  if fmtwidth("`pformat'") > 5 {
    local pformat "%5.3f"
    di "{txt}note: invalid pformat(), using default"
  }
  sreturn local pformat "`pformat'"
  local pformat `pformat(`pformat')'
}
- if `K' == 1 & `:length local options' {
= if 2 == 1 & 0 {
  syntax namelist(max=2) [, `DIOPTS']
}
- if reldif(`level', c(level)) > 1e-3 {
= if reldif(95, c(level)) > 1e-3 {
  local levelopt level(`level')

```

```

    }
    - Wraupon , `fvwraupon'
    = Wraupon ,

```

```

> ----- begin _get_diopts.Wra
> pon
    - capture syntax [, W0rd WIdth]
    - if c(rc) {
        di as err "invalid fvwraupon() option;"
        syntax [, W0rd WIdth]
        exit 198
    }
    - opts_exclusive "`word' `width'" fvwraupon
    = opts_exclusive " " fvwraupon

```

```

> ----- begin opts_exclus
> ive
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ```opts'"" != "" {
    = while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
        - exit
    }

```

```

> ----- end opts_exclus
> ive
    - local fvwraupon `word' `width'
    = local fvwraupon
    - if `:length local fvwraupon' {
    = if 0 {
        c_local fvwraupon fvwraupon(`fvwraupon')
    }

```

```

> ----- end _get_diopts.Wra
> pon
    - if "`fvwrap'" != "" {
    = if "fvwrap(1)" != "" {
        - FVWrap, `fvwrap'
    = FVWrap, fvwraupon(1)

```

```

> _____ begin _get_diopts.FVW
> rap _____
      - syntax, fvwrap(integer)
      - if `fvwrap' < 0 {
      = if 1 < 0 {
          di as err "{p}invalid option {bf:fvwrap(`fvwrap')}); " "nonnega
> tive integer required{p_end}"
          exit 198
      }

> _____ end _get_diopts.FVW
> rap _____
      - }
      - c_local `c_diopts' `levelopt' `vsquish' `allbaselevels' `baselev
> els' `cnsreport' `fullcnsreport' `emptycells' `omitted' `lstretch' `coeflege
> nd' `selegend' `cformat' `sformat' `pformat' `coding' `versus' `compare' `fv
> wrap' `fvwrapon' `fvlabel' `nocl' `nopvalues' `markdown' `citype' `abbrev'
      = c_local diopts          fvwrap(1)
      - if `K' == 2 {
      = if 2 == 2 {
      - c_local `c_opts' ``options'''
      = c_local options `'''
      - }
      - sreturn local coding `coding'
      = sreturn local coding
      - sreturn local versus `versus'
      = sreturn local versus
      - sreturn local compare `compare'
      = sreturn local compare
      - sreturn local level `level'
      = sreturn local level 95

> _____ end _get_diopts.GetDio
> pts _____
      - c_local `name1' ``diopts'''
      = c_local diopts ``fvwrap(1)'''
      - local snames : s(macros)
      - foreach sname of local snames {
      - local S_`sname' = s(`sname')
      = local S_level = s(level)
      - }
      - local S_`sname' = s(`sname')
      = local S_method = s(method)
      - }
      - local S_`sname' = s(`sname')

```



```

        = local S_options = s(options)
        - }
        - sreturn clear
        - GetDiopts DEFAULT
    }
}

> ----- begin _get_diopts.GetDio
> pts -----
    - local DIOPTS Level(cilevel) vsquish NOALLBASElevels ALLBASElevel
> s NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EMPTYcells
> NOOMITted OMITted NOLSTRETCH LSTRETCH COEFlegend SELEGEND cformat(string) sf
> ormat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru) FVWRAP0
> N(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(passthru) NOABBRE
> V ABBREV
    - syntax namelist(max=2) [, `DIOPTS' *]
    = syntax namelist(max=2) [, Level(cilevel) vsquish NOALLBASElevels
> ALLBASElevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcell
> s EMPTYcells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFlegend SELEGEND cform
> at(string) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(pass
> thru) FVWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(pass
> thru) NOABBREV ABBREV *]
    - opts_exclusive "`allbaselevels' `noallbaselevels'"
    = opts_exclusive " "
}

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while `"'opts'" != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`allbaselevels' `nobaselevels'"
    = opts_exclusive " "
}

> ----- begin opts_exclus
> ive -----

```

```

- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit

```

```

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`baselevels' `nobaselevels'"
    = opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
        }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

```

```

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`emptycells' `noemptycells'"
    = opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts

```

```

- local n 0
- while ``opts'' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`fvlabel' `nofvlabel'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts'' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`omitted' `noomitted'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts'' != "" {
= while `"' != "" {
  local ++n

```

```

        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`lstretch' `nolstretch'"
= opts_exclusive " "
}
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ```opts'`' != "" {
= while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`cnsreport' `fullcnsreport'"
= opts_exclusive " "
}
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ```opts'`' != "" {
= while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {

```

```

- exit
> ----- end opts_exclus
> ive -----
- opts_exclusive ``coeflegend' `selegend'
= opts_exclusive " "
> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `'' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
> ----- end opts_exclus
> ive -----
- opts_exclusive ``noci' `nopvalues'
= opts_exclusive " "
> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `'' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
> ----- end opts_exclus
> ive -----

```

```

- local K : list sizeof namelist
- gettoken c_diopts c_opts : namelist
- opts_exclusive ""coding' `compare'"
= opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ""`opts'" != "" {
= while "" != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit

```

```

> ----- end opts_exclus
> ive -----
- opts_exclusive ""versus' `compare'"
= opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ""`opts'" != "" {
= while "" != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit

```

```

> ----- end opts_exclus
> ive -----
- opts_exclusive ""abbrev' `noabbrev'"
= opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `'' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    -----
> ----- end opts_exclus
> ive
    - local allbaselevels `allbaselevels' `noallbaselevels'
    = local allbaselevels
    - local baselevels `baselevels' `nobaselevels'
    = local baselevels
    - local emptycells `emptycells' `noemptycells'
    = local emptycells
    - local omitted `omitted' `noomitted'
    = local omitted
    - local lstretch `lstretch' `nolstretch'
    = local lstretch
    - local fvlabel `fvlabel' `nofvlabel'
    = local fvlabel
    - local abbrev `abbrev' `noabbrev'
    = local abbrev
    - if "`allbaselevels'`baselevels'" == "" {
    = if "" == "" {
    - if c(showbaselevels) == "all" {
        local allbaselevels allbaselevels
    }
    - else if c(showbaselevels) == "on" {
        local baselevels baselevels
    }
    - }
    - if "`emptycells'" == "" {
    = if "" == "" {
    - if c(showemptycells) == "off" {
        local emptycells noemptycells

```

```

    }
- }
- if "`omitted'" == "" {
= if "" == "" {
- if c(showomitted) == "off" {
    local omitted noomitted
  }
- }
- if "`lstretch'" == "" {
= if "" == "" {
- if c(lstretch) == "off" {
    local lstretch nolstretch
  }
- }
- if `:length local cformat' {
= if 0 {
    confirm numeric format `cformat'
    if fmtwidth("`cformat'") > 9 {
      local cformat "%9.0g"
      di "{txt}note: invalid cformat(), using default"
    }
    sreturn local cformat "`cformat'"
    local cformat `cformat(`cformat')"'
  }
- if `:length local sformat' {
= if 0 {
    confirm numeric format `sformat'
    if fmtwidth("`sformat'") > 8 {
      local sformat "%8.2f"
      di "{txt}note: invalid sformat(), using default"
    }
    sreturn local sformat "`sformat'"
    local sformat `sformat(`sformat')"'
  }
- if `:length local pformat' {
= if 0 {
    confirm numeric format `pformat'
    if fmtwidth("`pformat'") > 5 {
      local pformat "%5.3f"
      di "{txt}note: invalid pformat(), using default"
    }
    sreturn local pformat "`pformat'"
    local pformat `pformat(`pformat')"'
  }
- if `K' == 1 & `:length local options' {
= if 1 == 1 & 0 {

```



```

        syntax namelist(max=2) [, `DIOPTS']
    }
    - if reldif(`level', c(level)) > 1e-3 {
= if reldif(95, c(level)) > 1e-3 {
        local levelopt level(`level')
    }
    - Wrapon , `fvwrapon'
= Wrapon ,

> _____ begin _get_diopts.Wra
> pon _____
        - capture syntax [, W0rd WIdth]
        - if c(rc) {
            di as err "invalid fvwrapon() option;"
            syntax [, W0rd WIdth]
            exit 198
        }
        - opts_exclusive "`word' `width'" fvwrapon
= opts_exclusive " " fvwrapon

> _____ begin opts_exclus
> ive _____
        - version 8.2
        - args opts optname errcode optslab
        - local opts `opts'
= local opts
        - local n 0
        - while ``opts' != "" {
= while `"' != "" {
            local ++n
            gettoken item`n' opts : opts, bind
        }
        - if `n' < 2 {
= if 0 < 2 {
            - exit

> _____ end opts_exclus
> ive _____
        - local fvwrapon `word' `width'
= local fvwrapon
        - if `:length local fvwrapon' {
= if 0 {
            c_local fvwrapon fvwrapon(`fvwrapon')
        }

> _____ end _get_diopts.Wra

```

```

> pon
    - if "`fvwrap'" != "" {
    = if "" != "" {
        FVWrap, `fvwrap'
    }
    - c_local `c_diopts' `levelopt' `vsquish' `allbaselevels' `baselev
> els' `cnsreport' `fullcnsreport' `emptycells' `omitted' `lstretch' `coeflege
> nd' `selegend' `cformat' `sformat' `pformat' `coding' `versus' `compare' `fv
> wrap' `fvwrapon' `fvlabel' `nocl' `nopvalues' `markdown' `citype' `abbrev'
    = c_local DEFAULT
    - if `K' == 2 {
    = if 1 == 2 {
        c_local `c_opts' ``options''
    }
    - sreturn local coding `coding'
    = sreturn local coding
    - sreturn local versus `versus'
    = sreturn local versus
    - sreturn local compare `compare'
    = sreturn local compare
    - sreturn local level `level'
    = sreturn local level 95

> _____ end _get_diopts.GetDio
> pts
    - if ``name2'' == "" {
    = if ``' == "" {
    - GetDiopts DUPS, `options'
    = GetDiopts DUPS,

> _____ begin _get_diopts.GetDio
> pts
    - local DIOPTS Level(cilevel) vsquish NOALLBASElevels ALLBASElevel
> s NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EMPTYcells
> NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cformat(string) sf
> ormat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru) FVWRAP0
> N(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(passthru) NOABBRE
> V ABBREV
    - syntax namelist(max=2) [, `DIOPTS' *]
    = syntax namelist(max=2) [, Level(cilevel) vsquish NOALLBASElevels
> ALLBASElevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcell
> s EMPTYcells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cform
> at(string) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(pass
> thru) FVWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(pass
> thru) NOABBREV ABBREV *]
    - opts_exclusive ``allbaselevels' `noallbaselevels''

```

```

= opts_exclusive " "
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`allbaselevels' `nbaselevels'"
    = opts_exclusive " "
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`baselevels' `nbaselevels'"
    = opts_exclusive " "
> _____ begin opts_exclus
> ive _____

```

```

- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit

```

```

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`emptycells' `noemptycells'"
    = opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

```

```

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`fvlabel' `nofvlabel'"
    = opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts

```

```

- local n 0
- while ``opts'' != "" {
= while `'' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`omitted' `noomitted'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts'' != "" {
= while `'' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`lstretch' `nolstretch'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts'' != "" {
= while `'' != "" {
  local ++n

```

```

        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`cnsreport' `fullcnsreport'"
= opts_exclusive " "
}
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ```opts'` != "" {
= while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`coeflegend' `selegend'"
= opts_exclusive " "
}
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ```opts'` != "" {
= while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {

```

```

        - exit
    _____
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`noci' `nopvalues'"
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ```opts'`` != "" {
    = while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____
> _____ end opts_exclus
> ive _____
    - local K : list sizeof namelist
    - gettoken c_diopts c_opts : namelist
    - opts_exclusive "`coding' `compare'"
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ```opts'`` != "" {
    = while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

```

```

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`versus' `compare'"
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while `""opts'" != "" {
    = while `"" != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`abbrev' `noabbrev'"
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while `""opts'" != "" {
    = while `"" != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - local allbaselevels `allbaselevels' `noallbaselevels'
    = local allbaselevels

```



```

- local baselevels `baselevels' `nobaselevels'
= local baselevels
- local emptycells `emptycells' `noemptycells'
= local emptycells
- local omitted `omitted' `noomitted'
= local omitted
- local lstretch `lstretch' `nolstretch'
= local lstretch
- local fvlabel `fvlabel' `nofvlabel'
= local fvlabel
- local abbrev `abbrev' `noabbrev'
= local abbrev
- if "`allbaselevels'`baselevels'" == "" {
= if "" == "" {
- if c(showbaselevels) == "all" {
    local allbaselevels allbaselevels
  }
- else if c(showbaselevels) == "on" {
    local baselevels baselevels
  }
- }
- if "`emptycells'" == "" {
= if "" == "" {
- if c(showemptycells) == "off" {
    local emptycells noemptycells
  }
- }
- if "`omitted'" == "" {
= if "" == "" {
- if c(showomitted) == "off" {
    local omitted noomitted
  }
- }
- if "`lstretch'" == "" {
= if "" == "" {
- if c(lstretch) == "off" {
    local lstretch nolstretch
  }
- }
- if `:length local cformat' {
= if 0 {
    confirm numeric format `cformat'
    if fmtwidth("`cformat'") > 9 {
      local cformat "%9.0g"
    }
    di "{txt}note: invalid cformat(), using default"
  }
}

```

```

    sreturn local cformat ``cformat'''
    local cformat `cformat(`cformat')''
}
- if `:length local sformat' {
= if 0 {
    confirm numeric format `sformat'
    if fmtwidth(`sformat') > 8 {
        local sformat "%8.2f"
        di "{txt}note: invalid sformat(), using default"
    }
    sreturn local sformat ``sformat'''
    local sformat `sformat(`sformat')''
}
- if `:length local pformat' {
= if 0 {
    confirm numeric format `pformat'
    if fmtwidth(`pformat') > 5 {
        local pformat "%5.3f"
        di "{txt}note: invalid pformat(), using default"
    }
    sreturn local pformat ``pformat'''
    local pformat `pformat(`pformat')''
}
- if `K' == 1 & `:length local options' {
= if 1 == 1 & 0 {
    syntax namelist(max=2) [, `DIOPTS']
}
- if reldif(`level', c(level)) > 1e-3 {
= if reldif(95, c(level)) > 1e-3 {
    local levelopt level(`level')
}
- Wraapon , `fvwraapon'
= Wraapon ,

```

> _____ begin _get_diopts.Wra

> pon _____

```

- capture syntax [, W0rd WIdth]
- if c(rc) {
    di as err "invalid fvwraapon() option;"
    syntax [, W0rd WIdth]
    exit 198
}
- opts_exclusive ``word' `width'" fvwraapon
= opts_exclusive " " fvwraapon

```

> _____ begin opts_exclus

```

> ive
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ```opts'"" != "" {
    = while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

> _____ end opts_exclus
> ive
    - local fvwrapon `word' `width'
    = local fvwrapon
    - if `:length local fvwrapon' {
    = if 0 {
        c_local fvwrapon fvwrapon(`fvwrapon')
    }

> _____ end _get_diopts.Wra
> pon
    - if ``fvwrap'"" != "" {
    = if "" != "" {
        FVWrap, `fvwrap'
    }
    - c_local `c_diopts' `levelopt' `vsquish' `allbaselevels' `baselev
> els' `cnsreport' `fullcnsreport' `emptycells' `omitted' `lstretch' `coeflege
> nd' `selegend' `cformat' `sformat' `pformat' `coding' `versus' `compare' `fv
> wrap' `fvwrapon' `fvlabel' `nocl' `nopvalues' `markdown' `citype' `abbrev'
    = c_local DUPS
    - if `K' == 2 {
    = if 1 == 2 {
        c_local `c_opts' ```options'""
    }
    - sreturn local coding `coding'
    = sreturn local coding
    - sreturn local versus `versus'
    = sreturn local versus
    - sreturn local compare `compare'
    = sreturn local compare
    - sreturn local level `level'

```

```

= sreturn local level 95


---


> 

---

 end _get_diopts.GetDio
> pts 

---


- }
- else {
  GetDiopts DUPS options, `options'
  c_local `name2' ``options'
}
- local DUPS : list DUPS - DEFAULT
- gettoken DUPS : DUPS
- if ``DUPS' != "" {
= if `'' != "" {
  if (strpos(`DUPS', "(")) {
    gettoken DUPS : DUPS, parse("(")
    local DUPS `DUPS'()'
  }
  di as err "duplicate {bf:`DUPS'} option not allowed"
  exit 198
}
- sreturn clear
- foreach sname of local snames {
- sreturn local `sname' = ``S_`sname'
= sreturn local level = `95'
- }
- sreturn local `sname' = ``S_`sname'
= sreturn local method = `noadjust'
- }
- sreturn local `sname' = ``S_`sname'
= sreturn local options = `level(95.00) fvwrap(1)'
- }


---


> 

---

 end _get_dio
> pts 

---


- if !`:length local first' {
= if !0 {
- local first showeqns
- }
- if `neq' < 1 {
= if -1 < 1 {
- _ms_eq_info
- local neqopt neq(`r(k_eq)')
= local neqopt neq(1)
- }
- else {
  local neqopt neq(`neq')

```

```

    }
    - _coef_table, nodiparm nocnsreport noeqcheck eformall `eform' `first'
> `neqopt' `plus' `beta' `mcopt' `diopts'
    = _coef_table, nodiparm nocnsreport noeqcheck eformall showeqns neq(1
> ) mcompare(noadjust ) fvwrap(1)

> _____ begin _coef_ta
> ble _____
    - version 11
    - local vv : di "version " string(max(11,_caller())) ", missing:"
    - if (!c(noisily) & c(coeftabresults) == "off") {
        exit
    }
    - _check_eclass
    - syntax [, BMATrix(passthru) VMATrix(passthru) * ]
    - if "`e(b)'" == "" & "`e(V)'" == "" & "`bmatrix'`vmatrix'""=="" {
= if "matrix" == "" & "matrix" == "" & ""=="" {
        exit
    }
    - local mc_cmds contrast margins pwcompare pwmean
    - local cmd "`e(cmd)'"
= local cmd "regress"
    - local keepmc : list cmd in mc_cmds
    - if inlist("`cmd'", "pwcompare", "pwmean") {
= if inlist("regress", "pwcompare", "pwmean") {
        local groups GROUPS
    }
    - if "`cmd'" == "regress" {
= if "regress" == "regress" {
        - local beta Beta
        - }
        - if "`cmd'" == "gsem" {
= if "regress" == "gsem" {
            local fvignore fvignore(int 0)
            local flignore flignore
        }
        - if "`cmd'" == "sem" {
= if "regress" == "sem" {
            local standardized STANDARDIZED
            local showginvariant SHOWGINvariant
            local nolabel NOLABel LABel NOFVLABel FVLABel
            local nofootnote NOFOOTnote
            local wrap wrap(numlist max=1) fvwrap(passthru)
        }
        - if "`e(mi)'"=="mi" {
= if ""=="mi" {

```

```

    local dftable DFTable
    local dfonly DFONLY
    local noclustreport NOCLUSTReport
    local pisematrix PISEMATrix(string)
}

- syntax [, cmdextras BMATrix(string) VMATrix(string) EMATrix(string)
> ) DFMATrix(string) EQMATrix(string) ROWMATrix(string) CIMATrix(string) PMATr
> ix(string) TSMATrix(string) ROWCFormat(string) ROWPFormat(string) ROWSFormat
> (string) NOROWCI MMATrix(string) MVMATrix(string) MEMATrix(string) BSTDMATri
> x(string) CNSMATrix(string) PCLASSMATrix(string) Level(cilevel) prefix(name)
> cnszero(string) suffix(name) OFFSETlist(string asis) `beta' `standardized'
> NOCI NOPValues `dftable' `dfonly' dfci DFPValues dfmissing `groups' COEFLege
> nd selegend `fvignore' `flignore' `showginvariant' `nolabel' `nofootnote' `w
> rap' sort `pisematrix' depname(string) COEFTitle(string) coeftitle2(string)
> ptitle(string) cititle(string) NOMCLEgend noCNSReport FULLCNSReport `noclust
> report' cformat(passthru) sformat(passthru) pformat(passthru) NOFirst First
> SHOWEQns neq(integer -1) NODIPARM NOTEST SEPARATOR(integer 0) NOSKIP OFFSET0
> NLY1 PLus NOEQCHECK EFORMALL CITYPE(string) eqselect(string) cidisjoint noEF
> ORMNOTE * ]

= syntax [, cmdextras BMATrix(string) VMATrix(string) EMATrix(string)
> ) DFMATrix(string) EQMATrix(string) ROWMATrix(string) CIMATrix(string) PMATr
> ix(string) TSMATrix(string) ROWCFormat(string) ROWPFormat(string) ROWSFormat
> (string) NOROWCI MMATrix(string) MVMATrix(string) MEMATrix(string) BSTDMATri
> x(string) CNSMATrix(string) PCLASSMATrix(string) Level(cilevel) prefix(name)
> cnszero(string) suffix(name) OFFSETlist(string asis) Beta NOCI NOPValues
> dfci DFPValues dfmissing COEFLegend selegend sort depname(string) C
> OEFTitle(string) coeftitle2(string) ptitle(string) cititle(string) NOMCLEgen
> d noCNSReport FULLCNSReport cformat(passthru) sformat(passthru) pformat(pas
> sthru) NOFirst First SHOWEQns neq(integer -1) NODIPARM NOTEST SEPARATOR(inte
> ger 0) NOSKIP OFFSETONLY1 PLus NOEQCHECK EFORMALL CITYPE(string) eqselect(st
> ring) cidisjoint noEFORMNOTE * ]

- if "`wrap'" != "" {
= if "" != "" {
    opts_exclusive `"wrap(`wrap')' `fvwrap'"
    local fvwrap fvwrap(`wrap')
}
- if "`nolabel'`label'" != "" {
= if "" != "" {
    opts_exclusive "`nolabel' `label'"
    opts_exclusive "`nofvlabel' `fvlabel'"
    opts_exclusive "`nolabel' `fvlabel'"
    opts_exclusive "`nofvlabel' `label'"
    if "`nolabel'" != "" {
        local fvlabel nofvlabel
    }
    else {

```

```

        local fvlable fvlable
    }
}
- _novce_other_mats, cimatrix("`cimatrix'") pmatrix("`pmatrix'") tsm
> atrix("`tsmatrix'") `noci' `nopvalues' `dfci' `dfpvalues' `cidisjoint'
= _novce_other_mats, cimatrix("") pmatrix("") tsmatrix("")

-----
> ----- begin _coef_table._novce_other_m
> ats -----
- syntax [anything], [ CIMATrix(string) PMATrix(string) TSMATrix(s
> tring) NOCI NOPValues dfci DFPValues cidisjoint ]
- if("`pmatrix'"=="" & "`tsmatrix'"=="" & "`e(V)'"=="" & "`cimatr
> ix'"!=" & "`noci'"!=")) {
= if ("==" & "==" & "matrix"==" & "!=" & "!=")) {
sreturn local cimatrix "empty"
}
- if("`pmatrix'"=="" & "`tsmatrix'"!=" & "`e(V)'"=="" & "`cimatr
> ix'"==" & ("`noci'"!="|"`nopvalues'"!=")) {
= if ("==" & "!=" & "matrix"==" & "==" & ("!="|"!=")) {
sreturn local noci "empty"
sreturn local nopvalues "empty"
}
- if("`pmatrix'"=="" & "`tsmatrix'"=="" & "`e(V)'"=="" & "`cimatr
> ix'"!=" & "`noci'"!=")) {
= if ("==" & "==" & "matrix"==" & "!=" & "!=")) {
sreturn local cimatrix "empty"
}
- if("`pmatrix'"!=" & "`tsmatrix'"=="" & "`e(V)'"=="" & "`cimatr
> ix'"==" & "`nopvalues'"!=")) {
= if ("!=" & "==" & "matrix"==" & "==" & "!=")) {
sreturn local pmatrix "empty"
}
- if("`pmatrix'"!=" & "`tsmatrix'"=="" & "`e(V)'"=="" & "`cimatr
> ix'"==" & "`noci'"!=")) {
= if ("!=" & "==" & "matrix"==" & "==" & "!=")) {
sreturn local noci "empty"
}
- if("`pmatrix'"!=") {
= if ("!=") {
tempname pmat isvalid
capture matrix `pmat' = `pmatrix'
local rc = _rc
if (`rc') {
display as error "invalid {bf:pmatrix()}"
exit 198
}
}
}

```

```

else {
    local k: rowsof `pmat'
    if (`k'>1 | `k'==0) {
        display as error "{bf:pmatrx()}" should be a row vector"
        exit 198
    }
}

scalar `isvalid' = 1
mata: _is_in_0_1void("`pmat'", "`isvalid'")
if (`isvalid'==0) {
    display as error "invalid {bf:pmatrx()}"
    di as txt "{p 4 4 2}"
    di as smcl as err "{bf:pmatrx()}"
    di as smcl as err "should contain values inside"
    di as smcl as err "the interval [0,1]."
    di as smcl as err "{p_end}"
    exit 198
}

- if("`tsmatrix'"!="") {
= if ("!=") {
    tempname tmat
    capture matrix `tmat' = `tsmatrix'
    local rc = _rc
    if (`rc') {
        display as error "invalid {bf:tsmatrix()}"
        exit 198
    }
    else {
        local k: rowsof `tmat'
        if (`k'>1 | `k'==0) {
            display as error "{bf:tsmatrix()}" should be a row vector"
            exit 198
        }
    }
}

- if("`cimatrx'"!="") {
= if ("!=") {
    tempname cimat isvalid
    capture matrix `cimat' = `cimatrx'
    local rc = _rc
    if (`rc') {
        display as error "invalid {bf:cimatrx()}"
        exit 198
    }
    if ("`cidisjoint'"==" & "`e(disjoint)'"=="") {

```



```

scalar `isvalid' = 1
mata: _is_in_ci("`cimat'", "`isvalid'")
if (`isvalid'==0) {
display as error "invalid {bf:cimatrix()}"
di as txt "{p 4 4 2}"
di as smcl as err "{bf:cimatrix()}"
di as smcl as err "lower limit should be"
di as smcl as err "smaller than the upper"
di as smcl as err "limit."
di as smcl as err "{p_end}"
exit 198
}
}
}
- if (`e(V)'==" & "`dfci'!=" & "`pmatrx'!=") {
= if ("matrix"==" & ""!=" & ""!=") {
opts_exclusive "pmatrx() `dfci'"
}
- if (`e(V)'==" & "`dfci'!=" & "`tsmatrix'!=") {
= if ("matrix"==" & ""!=" & ""!=") {
opts_exclusive "tsmatrix() `dfci'"
}
- if (`e(V)'==" & "`dfci'!=" & "`cimatrx'!=") {
= if ("matrix"==" & ""!=" & ""!=") {
opts_exclusive "cimatrx() `dfci'"
}
- if (`e(V)'==" & "`dfpvalues'!=" & "`pmatrx'!=") {
= if ("matrix"==" & ""!=" & ""!=") {
opts_exclusive "pmatrx() `dfci'"
}
- if (`e(V)'==" & "`dfpvalues'!=" & "`tsmatrix'!=") {
= if ("matrix"==" & ""!=" & ""!=") {
opts_exclusive "tsmatrix() `dfpvalues'"
}
- if (`e(V)'==" & "`dfpvalues'!=" & "`cimatrx'!=") {
= if ("matrix"==" & ""!=" & ""!=") {
opts_exclusive "cimatrx() `dfpvalues'"
}
}

```

```

> _____ end _coef_table._novce_other_m
> ats _____

```

```

- if (`s(cimatrx)'=="empt") {
= if (""=="empt") {
local cimatrx ""
}
- if (`s(pmatrx)'=="empt") {

```

```

= if (""=="empt") {
  local pmatrix ""
}
- if ("`s(noci)'"=="empt") {
= if (""=="empt") {
  local noci ""
}
- if ("`s(nopvalues)'"=="empt") {
= if (""=="empt") {
  local nopvalues ""
}
- if ("`e(V)'"!=" & "`cidisjoint'"!="") {
= if ("matrix"!=" & ""!="") {
  display in red "option {bf:cidisjoint} not allowed when e(V) is po
> sted"
  exit 198
}
- else local fvlabel `nofvlabel' `fvlabel'
= else local fvlabel
- local type `coeflegend' `selegend'
= local type
- opts_exclusive "`type' `standardized'"
= opts_exclusive " "
}

> ----- begin opts_exclus
> ive -----
  - version 8.2
  - args opts optname errcode optslab
  - local opts `opts'
  = local opts
  - local n 0
  - while ``opts'" != "" {
  = while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
  }
  - if `n' < 2 {
  = if 0 < 2 {
    - exit
  }

> ----- end opts_exclus
> ive -----
  - if (``rowmatrix'"==" & "`norowci'"!="") {
  = if (``'"==" & ""!="") {
    di as err "{bf:norowci} requires {bf:rowmatrix()}"
    exit 198
  }

```

```

    }
- if ("`dftable`"!=" & "`norowci`"!=") {
= if ("!=" & "!=") {
    di as err "{bf:norowci} is not allowed with {bf:`dftable`}"
    exit 198
    }
- if ("`dfonly`"!=" & "`norowci`"!=") {
= if ("!=" & "!=") {
    di as err "{bf:norowci} is not allowed with {bf:`dfonly`}"
    exit 198
    }
- if ("`noci`"!=" & "`norowci`"!=") {
= if ("!=" & "!=") {
    di as err "{bf:norowci} is not allowed with {bf:`noci`}"
    exit 198
    }
- if "`standardized`" != "" & "`bstdmatrix`" != "" {
= if "" != "" & "" != "" {
    local beta beta
    local standardized
    }
- if `:length local type' == 0 {
= if 0 == 0 {
- local type `beta' `noci' `nopvalues' `dftable' `dfonly' `groups' `
> dfci' `dfpvalues'
    = local type
    - }
- opts_exclusive "`type`"
= opts_exclusive ""

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while "`opts`" != "" {
    = while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
        }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

```

```

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`first' `nofirst'"
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while `""opts'" != "" {
    = while `"" != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`first' `showeqns'"
    = opts_exclusive " showeqns"
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts showeqns
    - local n 0
    - while `""opts'" != "" {
    = while `"showeqns"' != "" {
    - local ++n
    - gettoken item`n' opts : opts, bind
    = gettoken item1 opts : opts, bind
    - }
    - while `""opts'" != "" {
    = while `"" != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 1 < 2 {

```

```

- exit


---


> 

---

 end opts_exclus
> ive 

---


- local cnsreport `cnsreport' `fullcnsreport'
= local cnsreport nocnsreport
- opts_exclusive "`cnsreport'"
= opts_exclusive "nocnsreport"


---


> 

---

 begin opts_exclus
> ive 

---


- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts nocnsreport
- local n 0
- while ```opts'` != "" {
= while `"nocnsreport" != "" {
- local ++n
- gettoken item`n' opts : opts, bind
= gettoken item1 opts : opts, bind
- }
- while ```opts'` != "" {
= while `"" != "" {
- local ++n
- gettoken item`n' opts : opts, bind
- }
- if `n' < 2 {
= if 1 < 2 {
- exit


---


> 

---

 end opts_exclus
> ive 

---


- if ```showeqns'` != "" {
= if `"showeqns" != "" {
- local nofirst nofirst
- }
- if ```ematrix'`noeqcheck'` == "" {
= if `"noeqcheck" == "" {
- if ```e(error)'` == "matrix" {
- local ematrix e(error)
- }
- }
- _get_mcompare, `options'
= _get_mcompare, mcompare(noadjust ) fwrap(1)


---



```

```

> _____ begin _get_mcomp
> are _____
      - version 11
      - local cmd ``e(cmd)''
      = local cmd ``regress''
      - syntax [name(name=caller)] [, *]
      - local is_pwc = inlist("pwcompare", ``cmd'', ``caller'') | inlist
> ("pwmean", ``cmd'', ``caller'')
      = local is_pwc = inlist("pwcompare", "regress", "") | inlist("pwme
> an", "regress", "")
      - local is_marg = inlist("margins", ``cmd'', ``e(cmd2)'', ``caller
> '')
      = local is_marg = inlist("margins", "regress", "", "")
      - local OPTIONS NOADJust BONferroni DUNCAn DUNNett SCHeffe SIDak S
> NK TUKey ADJustall
      - if `is_pwc' {
      = if 0 {
          syntax [name] [, `OPTIONS' MCOMPare(string) *]
          }
      - else {
      - syntax [name] [, MCOMPare(string) *]
      - local suboption mcompare()
      - }
      - sreturn clear
      - sreturn local options ``options''
      = sreturn local options ``fvwrap(1)''
      - if `is_pwc' {
      = if 0 {
          local METHOD `noadjust' `bonferroni' `duncan' `dunnett' `scheffe
> ' `sidak' `snk' `tukey'
          local METHOD : list uniq METHOD
          opts_exclusive ``METHOD''
          local ALL `adjustall'
          opts_exclusive ``noadjust' `ALL''
          }
      - local 0 `", `mcompare''
      = local 0 `", noadjust''
      - capture syntax [, `OPTIONS']
      = capture syntax [, NOADJust BONferroni DUNCAn DUNNett SCHeffe SID
> ak SNK TUKey ADJustall]
      - if c(rc) {
          di as err "invalid mcompare() option;"
          di as err "method ``mcompare'' not allowed"
          error 198
          }
      - local METHOD `METHOD' `noadjust' `bonferroni' `duncan' `dunnett'

```

```

> `scheffe' `sidak' `snk' `tukey'
    = local METHOD noadjust
    - local METHOD : list uniq METHOD
    - local ALL `ALL' `adjustall'
    = local ALL
    - local ALL : list uniq ALL
    - opts_exclusive "`METHOD'" `suboption'
    = opts_exclusive "noadjust" mcompare()

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts noadjust
    - local n 0
    - while ```opts'"' != "" {
    = while `"noadjust"' != "" {
    - local ++n
    - gettoken item`n' opts : opts, bind
    = gettoken item1 opts : opts, bind
    - }
    - while ```opts'"' != "" {
    = while `"' != "" {
      local ++n
      gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 1 < 2 {
    - exit

> _____ end opts_exclus
> ive _____
    - if "`METHOD'" == "" {
    = if "noadjust" == "" {
      if "`ALL'" != "" {
        di as err "multiple comparison method required with the adjustal
> l option"
        exit 198
      }
      local METHOD noadjust
      local noadjust noadjust
    }
    - opts_exclusive "`ALL' `noadjust'" `suboption'
    = opts_exclusive " noadjust" mcompare()

```

```

> ----- begin opts_exclus
> ive
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts noadjust
    - local n 0
    - while ```opts'"" != "" {
    = while `"noadjust" != "" {
    - local ++n
    - gettoken item`n' opts : opts, bind
    = gettoken item1 opts : opts, bind
    - }
    - while ```opts'"" != "" {
    = while `"" != "" {
      local ++n
      gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 1 < 2 {
    - exit
    -----
> ----- end opts_exclus
> ive
    - local EXCLUDE duncan dunnett snk tukey
    - if `:list METHOD in EXCLUDE' {
    = if 0 {
      if `is_pwc' {
        local opt : copy local METHOD
      }
      else {
        local opt "mcompare(`METHOD')"
      }
      local cmdlist anova manova regress mvreg pwmean
      if ""`cmd' == "pwcompare" {
        local cmd ```e(cmd_est)''
      }
      if `is_marg' {
        local cmd margins
      }
      if !`:list cmd in cmdlist' | !`is_pwc' {
        di as err `"method `opt' is not allowed with results from `cmd'"
      }
    }
    exit 322
  }
  if ```e(prefix)'' == "svy" {

```



```

        di as err `"method `opt' is not allowed with results using the s
> vy prefix""
        exit 322
    }
    local vce ``e(vce)'''
    if !inlist("`vce'", "", "ols") {
        di as err `"method `opt' is not allowed with results using vce(`
> vce')"'
        exit 322
    }
    }
    - local EXCLUDE duncan dunnett snk tukey scheffe
    - if `:list METHOD in EXCLUDE' {
= if 0 {
    if ""ALL"" != "" {
        di as err `"option adjustall is not allowed with method `METHOD'
> ""
        exit 198
    }
    }
    - sreturn local method ``METHOD'''
= sreturn local method `noadjust"'
    - sreturn local adjustall ``ALL'''
= sreturn local adjustall `""'



---


> ----- end _get_mcomp
> are -----
    - local method ``s(method)'''
= local method `noadjust"'
    - local all ``s(adjustall)'''
= local all `""'
    - local options ``s(options)'''
= local options `fvwrap(1)''
    - if "`method'" != "noadjust" {
= if "noadjust" != "noadjust" {
    local keepmc 1
    }
    - opts_exclusive "`all' `groups'"
= opts_exclusive " "



---


> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts

```

```

- local n 0
- while ``opts'' != "" {
= while `'' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> _____ end opts_exclus
> ive _____
- if ``method'' == "dunnett" {
= if "noadjust" == "dunnett" {
  opts_exclusive ``method' `groups'
}
- _get_diopts diopts options, `options' `fvwrap' `fvlabel'
= _get_diopts diopts options, fvwrap(1)

> _____ begin _get_dio
> pts _____
- version 11
- syntax namelist(max=2) [, *]
- gettoken name1 namelist : namelist
- gettoken name2 namelist : namelist
- GetDiopts diopts options, `options'
= GetDiopts diopts options, fvwrap(1)

> _____ begin _get_diopts.GetDio
> pts _____
- local DIOPTS Level(cilevel) vsquish NOALLBASElevels ALLBASElev
> els NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EMPTYcell
> s NOOMITted OMITted NOLSTRETCH LSTRETCH COEFlegend SELEGEND cformat(string)
> sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru) FVWRA
> PON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(passthru) NOABB
> REV ABBREV
- syntax namelist(max=2) [, `DIOPTS' *]
= syntax namelist(max=2) [, Level(cilevel) vsquish NOALLBASEleve
> ls ALLBASElevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYce
> lls EMPTYcells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFlegend SELEGEND cfo
> rmat(string) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(pa
> ssthru) FVWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(pa
> ssthru) NOABBREV ABBREV *]
- opts_exclusive ``allbaselevels' `noallbaselevels'
= opts_exclusive " "

```

```

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`allbaselevels' `nobaselevels'"
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`baselevels' `nobaselevels'"
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab

```

```

- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
  }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`emptycells' `noemptycells'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
  }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`fvlabel' `nofvlabel'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {

```

```

= while `""` != "" {
    local ++n
    gettoken item`n` opts : opts, bind
}
- if `n` < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`omitted` `noomitted`"
= opts_exclusive " "
}

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts`
= local opts
    - local n 0
    - while `""opts`"" != "" {
= while `""` != "" {
    local ++n
    gettoken item`n` opts : opts, bind
}
    - if `n` < 2 {
= if 0 < 2 {
    - exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`lstretch` `nolstretch`"
= opts_exclusive " "
}

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts`
= local opts
    - local n 0
    - while `""opts`"" != "" {
= while `""` != "" {
    local ++n
    gettoken item`n` opts : opts, bind
}

```

```

- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`cnsreport' `fullcnsreport'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ```opts' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`coeflegend' `selegend'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ```opts' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

```

```

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`noci' `nopvalues'"
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ```opts'`` != "" {
    = while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - local K : list sizeof namelist
    - gettoken c_diopts c_opts : namelist
    - opts_exclusive "`coding' `compare'"
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ```opts'`` != "" {
    = while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____

```

```

- opts_exclusive "`versus' `compare'"
= opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ```opts'`` != "" {
= while `""' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit

```

```

> ----- end opts_exclus
> ive -----
- opts_exclusive "`abbrev' `noabbrev'"
= opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ```opts'`` != "" {
= while `""' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit

```

```

> ----- end opts_exclus
> ive -----
- local allbaselevels `allbaselevels' `noallbaselevels'
= local allbaselevels
- local baselevels `baselevels' `nobaselevels'
= local baselevels

```



```

- local emptycells `emptycells' `noemptycells'
= local emptycells
- local omitted `omitted' `noomitted'
= local omitted
- local lstretch `lstretch' `nolstretch'
= local lstretch
- local fvlabel `fvlabel' `nofvlabel'
= local fvlabel
- local abbrev `abbrev' `noabbrev'
= local abbrev
- if "`allbaselevels'`baselevels'" == "" {
= if "" == "" {
- if c(showbaselevels) == "all" {
    local allbaselevels allbaselevels
  }
- else if c(showbaselevels) == "on" {
    local baselevels baselevels
  }
- }
- if "`emptycells'" == "" {
= if "" == "" {
- if c(showemptycells) == "off" {
    local emptycells noemptycells
  }
- }
- if "`omitted'" == "" {
= if "" == "" {
- if c(showomitted) == "off" {
    local omitted noomitted
  }
- }
- if "`lstretch'" == "" {
= if "" == "" {
- if c(lstretch) == "off" {
    local lstretch nolstretch
  }
- }
- if `:length local cformat' {
= if 0 {
    confirm numeric format `cformat'
    if fmtwidth("`cformat'") > 9 {
      local cformat "%9.0g"
      di "{txt}note: invalid cformat(), using default"
    }
    sreturn local cformat "`cformat'"
    local cformat `cformat(`cformat')'

```

```

    }
- if `:length local sformat' {
= if 0 {
    confirm numeric format `sformat'
    if fmtwidth(`"'sformat'"') > 8 {
        local sformat "%8.2f"
        di "{txt}note: invalid sformat(), using default"
    }
    sreturn local sformat `"'sformat'"'
    local sformat `"sformat(`sformat')"'
}
- if `:length local pformat' {
= if 0 {
    confirm numeric format `pformat'
    if fmtwidth(`"'pformat'"') > 5 {
        local pformat "%5.3f"
        di "{txt}note: invalid pformat(), using default"
    }
    sreturn local pformat `"'pformat'"'
    local pformat `"pformat(`pformat')"'
}
- if `K' == 1 & `:length local options' {
= if 2 == 1 & 0 {
    syntax namelist(max=2) [, `DIOPTS']
}
- if reldif(`level', c(level)) > 1e-3 {
= if reldif(95, c(level)) > 1e-3 {
    local levelopt level(`level')
}
- Wraapon , `fvwraapon'
= Wraapon ,

```

> _____ begin _get_diopts.Wra

> pon _____

```

- capture syntax [, W0rd WIdth]
- if c(rc) {
    di as err "invalid fvwraapon() option;"
    syntax [, W0rd WIdth]
    exit 198
}
- opts_exclusive "`word' `width'" fvwraapon
= opts_exclusive " " fvwraapon

```

> _____ begin opts_exclus

> ive _____

```

- version 8.2

```

```

- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit

> _____ end opts_exclus
> ive _____
- local fwwrapon `word' `width'
= local fwwrapon
- if `:length local fwwrapon' {
= if 0 {
    c_local fwwrapon fwwrapon(`fwwrapon')
    }

> _____ end _get_diopts.Wra
> pon _____
- if "`fwwrap'" != "" {
= if "fwwrap(1)" != "" {
- FWWrap, `fwwrap'
= FWWrap, fwwrap(1)

> _____ begin _get_diopts.FWV
> rap _____
- syntax, fwwrap(integer)
- if `fwwrap' < 0 {
= if 1 < 0 {
    di as err "{p}invalid option {bf:fwwrap(`fwwrap')}"; " "nonne
> gative integer required{p_end}"
    exit 198
    }

> _____ end _get_diopts.FWV
> rap _____
- }
- c_local `c_diopts' `levelopt' `vsquish' `allbaselevels' `basel
> evels' `cnsreport' `fullcnsreport' `emptycells' `omitted' `lstretch' `coefle
> gend' `selegend' `cformat' `sformat' `pformat' `coding' `versus' `compare' `
> fwwrap' `fwwrapon' `fvlabel' `nocl' `nopvalues' `markdown' `citype' `abbrev'

```

```

= c_local diopts                                fvwrap(1)
- if `K' == 2 {
= if 2 == 2 {
- c_local `c_opts' ``options''
= c_local options ``''
- }
- sreturn local coding `coding'
= sreturn local coding
- sreturn local versus `versus'
= sreturn local versus
- sreturn local compare `compare'
= sreturn local compare
- sreturn local level `level'
= sreturn local level 95

```

```

> _____ end _get_diopts.GetDio
> pts _____
- c_local `name1' ``diopts''
= c_local diopts ``fvwrap(1)''
- local snames : s(macros)
- foreach sname of local snames {
- local S_`sname' = s(`sname')
= local S_level = s(level)
- }
- local S_`sname' = s(`sname')
= local S_method = s(method)
- }
- local S_`sname' = s(`sname')
= local S_options = s(options)
- }
- sreturn clear
- GetDiopts DEFAULT

```

```

> _____ begin _get_diopts.GetDio
> pts _____
- local DIOPTS Level(cilevel) vsquish NOALLBASElevels ALLBASElev
> els NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EMPTYcell
> s NOOMITtd OMITtd NOLSTRETCH LSTRETCH COEFLegend SELEGEND cformat(string)
> sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru) FVWRA
> PON(string) NOFVLAbel FVLAbel NOCI NOPValues MARKDOWN CITYPE(passthru) NOABB
> REV ABBREV
- syntax namelist(max=2) [, `DIOPTS' *]
= syntax namelist(max=2) [, Level(cilevel) vsquish NOALLBASEleve
> ls ALLBASElevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYce
> lls EMPTYcells NOOMITtd OMITtd NOLSTRETCH LSTRETCH COEFLegend SELEGEND cfo
> rmat(string) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(pa

```

```

> ssthru) FVWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYTYPE(pa
> ssthru) NOABBREV ABBREV *)
    - opts_exclusive "`allbaselevels' `noallbaselevels'"
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`allbaselevels' `nobaselevels'"
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`baselevels' `nobaselevels'"
    = opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`emptycells' `noemptycells'"
    = opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`fvlabel' `nofvlabel'"
    = opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2

```

```

- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`omitted' `noomitted'"
= opts_exclusive " "
}

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`lstretch' `nolstretch'"
= opts_exclusive " "
}

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0

```

```

- while ``opts'' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`cnsreport' `fullcnsreport'"
    = opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts'' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
        }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    }

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`coeflegend' `selegend'"
    = opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts'' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind

```



```

        }
        - if `n' < 2 {
        = if 0 < 2 {
        - exit
    }
}
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`noci' `nopvalues'"
    = opts_exclusive " "
}
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
}
}
> ----- end opts_exclus
> ive -----
    - local K : list sizeof namelist
    - gettoken c_diopts c_opts : namelist
    - opts_exclusive "`coding' `compare'"
    = opts_exclusive " "
}
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {

```

```

        = if 0 < 2 {
        - exit
    }
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`versus' `compare'"
    = opts_exclusive " "
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ```opts'`` != "" {
    = while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
        - exit
    }
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`abbrev' `noabbrev'"
    = opts_exclusive " "
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ```opts'`` != "" {
    = while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
        - exit
    }
> ----- end opts_exclus

```

> ive

```
- local allbaselevels `allbaselevels' `noallbaselevels'
= local allbaselevels
- local baselevels `baselevels' `nobaselevels'
= local baselevels
- local emptycells `emptycells' `noemptycells'
= local emptycells
- local omitted `omitted' `noomitted'
= local omitted
- local lstretch `lstretch' `nolstretch'
= local lstretch
- local fvlabel `fvlabel' `nofvlabel'
= local fvlabel
- local abbrev `abbrev' `noabbrev'
= local abbrev
- if "`allbaselevels'`baselevels'" == "" {
= if "" == "" {
- if c(showbaselevels) == "all" {
  local allbaselevels allbaselevels
}
- else if c(showbaselevels) == "on" {
  local baselevels baselevels
}
- }
- if "`emptycells'" == "" {
= if "" == "" {
- if c(showemptycells) == "off" {
  local emptycells noemptycells
}
- }
- if "`omitted'" == "" {
= if "" == "" {
- if c(showomitted) == "off" {
  local omitted noomitted
}
- }
- if "`lstretch'" == "" {
= if "" == "" {
- if c(lstretch) == "off" {
  local lstretch nolstretch
}
- }
- if `:length local cformat' {
= if 0 {
  confirm numeric format `cformat'
  if fmtwidth("`cformat'") > 9 {
```

```

    local cformat "%9.0g"
    di "{txt}note: invalid cformat(), using default"
    }
    sreturn local cformat ``cformat'''
    local cformat `cformat(`cformat')''
    }
- if `:length local sformat' {
= if 0 {
    confirm numeric format `sformat'
    if fmtwidth(`sformat') > 8 {
        local sformat "%8.2f"
        di "{txt}note: invalid sformat(), using default"
        }
    sreturn local sformat ``sformat'''
    local sformat `sformat(`sformat')''
    }
- if `:length local pformat' {
= if 0 {
    confirm numeric format `pformat'
    if fmtwidth(`pformat') > 5 {
        local pformat "%5.3f"
        di "{txt}note: invalid pformat(), using default"
        }
    sreturn local pformat ``pformat'''
    local pformat `pformat(`pformat')''
    }
- if `K' == 1 & `:length local options' {
= if 1 == 1 & 0 {
    syntax namelist(max=2) [, `DIOPTS']
    }
- if reldif(`level', c(level)) > 1e-3 {
= if reldif(95, c(level)) > 1e-3 {
    local levelopt level(`level')
    }
- Wraapon , `fvwraapon'
= Wraapon ,

```

> _____ begin _get_diopts.Wra

> pon _____

```

- capture syntax [, W0rd WIdth]
- if c(rc) {
    di as err "invalid fvwraapon() option;"
    syntax [, W0rd WIdth]
    exit 198
    }
- opts_exclusive ``word' `width' fvwraapon

```

```

= opts_exclusive " " fvwrapon
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
> _____ end opts_exclus
> ive _____
    - local fvwrapon `word' `width'
    = local fvwrapon
    - if `:length local fvwrapon' {
    = if 0 {
        c_local fvwrapon fvwrapon(`fvwrapon')
    }
> _____ end _get_diopts.Wra
> pon _____
    - if "`fvwrap'" != "" {
    = if "" != "" {
        FVWrap, `fvwrap'
    }
    - c_local `c_diopts' `levelopt' `vsquish' `allbaselevels' `basel
> evels' `cnsreport' `fullcnsreport' `emptycells' `omitted' `lstretch' `coefle
> gend' `selegend' `cformat' `sformat' `pformat' `coding' `versus' `compare' `
> fvwrap' `fvwrapon' `fvlabel' `noci' `nopvalues' `markdown' `citype' `abbrev'
    = c_local DEFAULT
    - if `K' == 2 {
    = if 1 == 2 {
        c_local `c_opts' ``options'
    }
    - sreturn local coding `coding'
    = sreturn local coding
    - sreturn local versus `versus'
    = sreturn local versus

```

```

        - sreturn local compare `compare'
        = sreturn local compare
        - sreturn local level `level'
        = sreturn local level 95
    }
}

> _____ end _get_diopts.GetDio
> pts _____
    - if ``name2''' == "" {
    = if `"options"' == "" {
        GetDiopts DUPS, `options'
    }
    - else {
    - GetDiopts DUPS options, `options'
    = GetDiopts DUPS options,
    }
}

> _____ begin _get_diopts.GetDio
> pts _____
    - local DIOPTS Level(cilevel) vsquish NOALLBASElevels ALLBASElev
> els NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EMPTYcell
> s NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cformat(string)
> sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru) FVWRA
> PON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(passthru) NOABB
> REV ABBREV
    - syntax namelist(max=2) [, `DIOPTS' *]
    = syntax namelist(max=2) [, Level(cilevel) vsquish NOALLBASEleve
> ls ALLBASElevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYce
> lls EMPTYcells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cfo
> rmat(string) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(pa
> ssthru) FVWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(pa
> ssthru) NOABBREV ABBREV *]
    - opts_exclusive "`allbaselevels' `noallbaselevels'"
    = opts_exclusive " "
}

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts''' != "" {
    = while `''' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {

```

```

        = if 0 < 2 {
        - exit
    }
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`allbaselevels' `nobaselevels'"
    = opts_exclusive " "
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    }
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`baselevels' `nobaselevels'"
    = opts_exclusive " "
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    }
> ----- end opts_exclus

```

```

> ive
- opts_exclusive "`emptycells' `noemptycells'"
= opts_exclusive " "
-
>
- begin opts_exclus
> ive
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while "`opts'" != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
-
>
- end opts_exclus
> ive
- opts_exclusive "`fvlabel' `nofvlabel'"
= opts_exclusive " "
-
>
- begin opts_exclus
> ive
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while "`opts'" != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
-
>
- end opts_exclus
> ive
- opts_exclusive "`omitted' `noomitted'"
= opts_exclusive " "

```



```

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
        }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`lstretch' `nolstretch'"
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
        }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`cnsreport' `fullcnsreport'"
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab

```

```

- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
  }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`coeflegend' `selegend'"
= opts_exclusive " "
}

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
  }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`noci' `nopvalues'"
= opts_exclusive " "
}

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {

```

```

= while `""` != "" {
    local ++n
    gettoken item`n` opts : opts, bind
}
- if `n` < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
    - local K : list sizeof namelist
    - gettoken c_diopts c_opts : namelist
    - opts_exclusive "`coding` `compare`"
= opts_exclusive " "
}

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts`
= local opts
    - local n 0
    - while `""`opts`"" != "" {
= while `""` != "" {
        local ++n
        gettoken item`n` opts : opts, bind
    }
    - if `n` < 2 {
= if 0 < 2 {
    - exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`versus` `compare`"
= opts_exclusive " "
}

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts`
= local opts
    - local n 0
    - while `""`opts`"" != "" {
= while `""` != "" {
        local ++n

```

```

        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`abbrev' `noabbrev'"
= opts_exclusive " "
}
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ``opts' != "" {
= while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}
> ----- end opts_exclus
> ive -----
    - local allbaselevels `allbaselevels' `noallbaselevels'
= local allbaselevels
    - local baselevels `baselevels' `nobaselevels'
= local baselevels
    - local emptycells `emptycells' `noemptycells'
= local emptycells
    - local omitted `omitted' `noomitted'
= local omitted
    - local lstretch `lstretch' `nolstretch'
= local lstretch
    - local fvlabel `fvlabel' `nofvlabel'
= local fvlabel
    - local abbrev `abbrev' `noabbrev'
= local abbrev
    - if "`allbaselevels'`baselevels'" == "" {
= if "" == "" {
    - if c(showbaselevels) == "all" {

```

```

    local allbaselevels allbaselevels
  }
- else if c(showbaselevels) == "on" {
  local baselevels baselevels
  }
- }
- if "`emptycells'" == "" {
= if "" == "" {
- if c(showemptycells) == "off" {
  local emptycells noemptycells
  }
- }
- if "`omitted'" == "" {
= if "" == "" {
- if c(showomitted) == "off" {
  local omitted noomitted
  }
- }
- if "`lstretch'" == "" {
= if "" == "" {
- if c(lstretch) == "off" {
  local lstretch nolstretch
  }
- }
- if `:length local cformat' {
= if 0 {
  confirm numeric format `cformat'
  if fmtwidth("`cformat'") > 9 {
    local cformat "%9.0g"
    di "{txt}note: invalid cformat(), using default"
  }
  sreturn local cformat "`cformat'"
  local cformat `cformat(`cformat')"'
}
- if `:length local sformat' {
= if 0 {
  confirm numeric format `sformat'
  if fmtwidth("`sformat'") > 8 {
    local sformat "%8.2f"
    di "{txt}note: invalid sformat(), using default"
  }
  sreturn local sformat "`sformat'"
  local sformat `sformat(`sformat')"'
}
- if `:length local pformat' {
= if 0 {

```

```

confirm numeric format `pformat'
if fmtwidth("`pformat'") > 5 {
local pformat "%5.3f"
di "{txt}note: invalid pformat(), using default"
}
sreturn local pformat "`pformat'"
local pformat `pformat(`pformat')'
}
- if `K' == 1 & `:length local options' {
= if 2 == 1 & 0 {
syntax namelist(max=2) [, `DIOPTS']
}
- if reldif(`level', c(level)) > 1e-3 {
= if reldif(95, c(level)) > 1e-3 {
local levelopt level(`level')
}
- Wraapon , `fvwraapon'
= Wraapon ,

```

> _____ begin _get_diopts.Wra

> pon _____

```

- capture syntax [, W0rd WIdth]
- if c(rc) {
di as err "invalid fvwrapon() option;"
syntax [, W0rd WIdth]
exit 198
}
- opts_exclusive "`word' `width'" fvwrapon
= opts_exclusive " " fvwrapon

```

> _____ begin opts_exclus

> ive _____

```

- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while "`opts'" != "" {
= while `"' != "" {
local ++n
gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit

```

```

> _____ end opts_exclus
> ive _____
    - local fvwrapon `word' `width'
    = local fvwrapon
    - if `:length local fvwrapon' {
    = if 0 {
        c_local fvwrapon fvwrapon(`fvwrapon')
    }
    _____

> _____ end _get_diopts.Wra
> pon _____
    - if "`fvwrap'" != "" {
    = if "" != "" {
        FVWrap, `fvwrap'
    }
    - c_local `c_diopts' `levelopt' `vsquish' `allbaselevels' `basel
> evels' `cnsreport' `fullcnsreport' `emptycells' `omitted' `lstretch' `coefle
> gend' `selegend' `cformat' `sformat' `pformat' `coding' `versus' `compare' `
> fvwrap' `fvwrapon' `fvlabel' `nocl' `nopvalues' `markdown' `citype' `abbrev'
    = c_local DUPS
    - if `K' == 2 {
    = if 2 == 2 {
        - c_local `c_opts' ``options'
    = c_local options `''
        - }
        - sreturn local coding `coding'
    = sreturn local coding
        - sreturn local versus `versus'
    = sreturn local versus
        - sreturn local compare `compare'
    = sreturn local compare
        - sreturn local level `level'
    = sreturn local level 95
    _____

> _____ end _get_diopts.GetDio
> pts _____
    - c_local `name2' ``options'
    = c_local options `''
    - }
    - local DUPS : list DUPS - DEFAULT
    - gettoken DUPS : DUPS
    - if ``DUPS' != "" {
    = if `'' != "" {
        if (strpos(`DUPS', "(")) {
            gettoken DUPS : DUPS, parse("(")
            local DUPS `DUPS'()'

```

```

    }
    di as err "duplicate {bf:`DUPS`} option not allowed"
    exit 198
  }
  - sreturn clear
  - foreach sname of local snames {
  - sreturn local `sname' = ``S_`sname''''
  = sreturn local level = ``95''
  - }
  - sreturn local `sname' = ``S_`sname''''
  = sreturn local method = ``noadjust''
  - }
  - sreturn local `sname' = ``S_`sname''''
  = sreturn local options = ``fvwrap(1)''
  - }
}

> _____ end _get_dio
> pts _____
  - local legend coeflegend selegend
  - local legend : list legend & diopts
  - local diopts : list diopts - legend
  - local lstretch lstretch nolstretch
  - local lstretch : list lstretch & diopts
  - local diopts : list diopts - lstretch
  - local markdown markdown
  - local markdown : list markdown & diopts
  - local diopts : list diopts - markdown
  - _get_diopts ignore, `diopts' `cformat' `sformat' `pformat'
  = _get_diopts ignore, fvwrap(1)
}

> _____ begin _get_dio
> pts _____
  - version 11
  - syntax namelist(max=2) [, *]
  - gettoken name1 namelist : namelist
  - gettoken name2 namelist : namelist
  - GetDiopts diopts options, `options'
  = GetDiopts diopts options, fvwrap(1)
}

> _____ begin _get_diopts.GetDio
> pts _____
  - local DIOPTS Level(cilevel) vsquish NOALLBASElevels ALLBASElev
> els NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EMPTYcell
> s NOOMITtd OMITtd NOLSTRETCH LSTRETCH COEFLegend SELEGEND cformat(string)
> sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru) FVWRA
> PON(string) NOFVLAbel FVLAbel NOCI NOPValues MARKDOWN CITYPE(passthru) NOABB

```



```

> REV ABBREV
    - syntax namelist(max=2) [, `DIOPTS' *]
    = syntax namelist(max=2) [, Level(cilevel) vsquish NOALLBASEleve
> ls ALLBASElevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYce
> lls EMPTYcells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cfo
> rmat(string) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(pa
> ssthru) FVWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(pa
> ssthru) NOABBREV ABBREV *]
    - opts_exclusive "`allbaselevels' `noallbaselevels'"
    = opts_exclusive " "


---


> 

---

 begin opts_exclus
> ive 

---


    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while `""opts"" != "" {
    = while `"" != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit


---


> 

---

 end opts_exclus
> ive 

---


    - opts_exclusive "`allbaselevels' `nobaselevels'"
    = opts_exclusive " "


---


> 

---

 begin opts_exclus
> ive 

---


    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while `""opts"" != "" {
    = while `"" != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {

```

```

- exit
> ----- end opts_exclus
> ive -----
- opts_exclusive "`baselevels' `nobaselevels'"
= opts_exclusive " "
> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
> ----- end opts_exclus
> ive -----
- opts_exclusive "`emptycells' `noemptycells'"
= opts_exclusive " "
> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
> ----- end opts_exclus
> ive -----

```

```

- opts_exclusive "`fvlabel' `nofvlabel'"
= opts_exclusive " "
_____
> _____ begin opts_exclus
> ive _____
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ```opts' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
_____
> _____ end opts_exclus
> ive _____
- opts_exclusive "`omitted' `noomitted'"
= opts_exclusive " "
_____
> _____ begin opts_exclus
> ive _____
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ```opts' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
_____
> _____ end opts_exclus
> ive _____
- opts_exclusive "`lstretch' `nolstretch'"
= opts_exclusive " "
_____
> _____ begin opts_exclus

```

```

> ive
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
      local ++n
      gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

>
> end opts_exclus
> ive
    - opts_exclusive "`cnsreport' `fullcnsreport'"
    = opts_exclusive " "

>
> begin opts_exclus
> ive
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
      local ++n
      gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

>
> end opts_exclus
> ive
    - opts_exclusive "`coeflegend' `selegend'"
    = opts_exclusive " "

>
> begin opts_exclus
> ive
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'

```

```

= local opts
- local n 0
- while ``opts'' != "" {
= while `'' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`noci' `nopvalues'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
- local n 0
- while ``opts'' != "" {
= while `'' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
    - local K : list sizeof namelist
    - gettoken c_diopts c_opts : namelist
    - opts_exclusive "`coding' `compare'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
- local n 0

```

```

- while ``opts'' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> _____ end opts_exclus
> ive _____
- opts_exclusive "`versus' `compare'"
= opts_exclusive " "

> _____ begin opts_exclus
> ive _____
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts'' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> _____ end opts_exclus
> ive _____
- opts_exclusive "`abbrev' `noabbrev'"
= opts_exclusive " "

> _____ begin opts_exclus
> ive _____
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts'' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}

```

```

    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
}
> ----- end opts_exclus
> ive -----
    - local allbaselevels `allbaselevels' `noallbaselevels'
    = local allbaselevels
    - local baselevels `baselevels' `nobaselevels'
    = local baselevels
    - local emptycells `emptycells' `noemptycells'
    = local emptycells
    - local omitted `omitted' `noomitted'
    = local omitted
    - local lstretch `lstretch' `nolstretch'
    = local lstretch
    - local fvlabel `fvlabel' `nofvlabel'
    = local fvlabel
    - local abbrev `abbrev' `noabbrev'
    = local abbrev
    - if "`allbaselevels'`baselevels'" == "" {
    = if "" == "" {
    - if c(showbaselevels) == "all" {
      local allbaselevels allbaselevels
    }
    - else if c(showbaselevels) == "on" {
      local baselevels baselevels
    }
    - }
    - if "`emptycells'" == "" {
    = if "" == "" {
    - if c(showemptycells) == "off" {
      local emptycells noemptycells
    }
    - }
    - if "`omitted'" == "" {
    = if "" == "" {
    - if c(showomitted) == "off" {
      local omitted noomitted
    }
    - }
    - if "`lstretch'" == "" {
    = if "" == "" {
    - if c(lstretch) == "off" {
      local lstretch nolstretch

```

```

    }
- }
- if `:length local cformat' {
= if 0 {
    confirm numeric format `cformat'
    if fmtwidth("`cformat'") > 9 {
        local cformat "%9.0g"
        di "{txt}note: invalid cformat(), using default"
    }
    sreturn local cformat "`cformat'"
    local cformat `cformat(`cformat')"'
}
- if `:length local sformat' {
= if 0 {
    confirm numeric format `sformat'
    if fmtwidth("`sformat'") > 8 {
        local sformat "%8.2f"
        di "{txt}note: invalid sformat(), using default"
    }
    sreturn local sformat "`sformat'"
    local sformat `sformat(`sformat')"'
}
- if `:length local pformat' {
= if 0 {
    confirm numeric format `pformat'
    if fmtwidth("`pformat'") > 5 {
        local pformat "%5.3f"
        di "{txt}note: invalid pformat(), using default"
    }
    sreturn local pformat "`pformat'"
    local pformat `pformat(`pformat')"'
}
- if `K' == 1 & `:length local options' {
= if 2 == 1 & 0 {
    syntax namelist(max=2) [, `DIOPTS']
}
- if reldif(`level', c(level)) > 1e-3 {
= if reldif(95, c(level)) > 1e-3 {
    local levelopt level(`level')
}
- Wraon , `fvwraon'
= Wraon ,

```

```
> _____ begin _get_diopts.Wra
```

```
> pon _____
      - capture syntax [, W0rd WIdth]
```



```

- if c(rc) {
  di as err "invalid fvwrapon() option;"
  syntax [, WOrd WIdth]
  exit 198
}
- opts_exclusive "`word' `width'" fvwrapon
= opts_exclusive " " fvwrapon

```

```

> ----- begin opts_exclus
> ive -----
  - version 8.2
  - args opts optname errcode optslab
  - local opts `opts'
  = local opts
  - local n 0
  - while ``opts' != "" {
  = while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
  }
  - if `n' < 2 {
  = if 0 < 2 {
    - exit
  }

```

```

> ----- end opts_exclus
> ive -----
  - local fvwrapon `word' `width'
  = local fvwrapon
  - if `:length local fvwrapon' {
  = if 0 {
    c_local fvwrapon fvwrapon(`fvwrapon')
  }

```

```

> ----- end _get_diopts.Wra
> pon -----
  - if "`fvwrap'" != "" {
  = if "fvwrap(1)" != "" {
    - FVWrap, `fvwrap'
  = FVWrap, fvwrap(1)

```

```

> ----- begin _get_diopts.FVW
> rap -----
  - syntax, fvwrap(integer)
  - if `fvwrap' < 0 {
  = if 1 < 0 {
    di as err "{p}invalid option {bf:fvwrap(`fvwrap')}; " "nonne

```

```

> gative integer required{p_end}"
        exit 198
    }
}

> ----- end _get_diopts.FVW
> rap -----
    - }
    - c_local `c_diopts' `levelopt' `vsquish' `allbaselevels' `basele
> evels' `cnsreport' `fullcnsreport' `emptycells' `omitted' `lstretch' `coefle
> gend' `selegend' `cformat' `sformat' `pformat' `coding' `versus' `compare' `
> fvwrap' `fvwrapon' `fvlabel' `nocl' `nopvalues' `markdown' `citype' `abbrev'
    = c_local diopts                                fvwrap(1)
    - if `K' == 2 {
    = if 2 == 2 {
    - c_local `c_opts' ``options'``
    = c_local options ``''
    - }
    - sreturn local coding `coding'
    = sreturn local coding
    - sreturn local versus `versus'
    = sreturn local versus
    - sreturn local compare `compare'
    = sreturn local compare
    - sreturn local level `level'
    = sreturn local level 95
}

> ----- end _get_diopts.GetDio
> pts -----
    - c_local `name1' ``diopts'``
    = c_local ignore ``fvwrap(1)``
    - local snames : s(macros)
    - foreach sname of local snames {
    - local S_`sname' = s(`sname')
    = local S_level = s(level)
    - }
    - local S_`sname' = s(`sname')
    = local S_options = s(options)
    - }
    - local S_`sname' = s(`sname')
    = local S_method = s(method)
    - }
    - sreturn clear
    - GetDiopts DEFAULT
}

> ----- begin _get_diopts.GetDio
> pts -----

```

```

        - local DIOPTS Level(cilevel) vsquish NOALLBASElevels ALLBASElev
> els NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EMPTYcell
> s NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cformat(string)
> sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru) FVWRA
> PON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(passthru) NOABB
> REV ABBREV
        - syntax namelist(max=2) [, `DIOPTS' *]
        = syntax namelist(max=2) [, Level(cilevel) vsquish NOALLBASEleve
> ls ALLBASElevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYce
> lls EMPTYcells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cfo
> rmat(string) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(pa
> ssthru) FVWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(pa
> ssthru) NOABBREV ABBREV *]
        - opts_exclusive "`allbaselevels' `noallbaselevels'"
        = opts_exclusive " "


---


> 

---

 begin opts_exclus
> ive 

---


        - version 8.2
        - args opts optname errcode optslab
        - local opts `opts'
        = local opts
        - local n 0
        - while ``opts' != "" {
        = while `"' != "" {
            local ++n
            gettoken item`n' opts : opts, bind
        }
        - if `n' < 2 {
        = if 0 < 2 {
        - exit


---


> 

---

 end opts_exclus
> ive 

---


        - opts_exclusive "`allbaselevels' `nobaselevels'"
        = opts_exclusive " "


---


> 

---

 begin opts_exclus
> ive 

---


        - version 8.2
        - args opts optname errcode optslab
        - local opts `opts'
        = local opts
        - local n 0
        - while ``opts' != "" {
        = while `"' != "" {

```

```

        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`baselevels' `nobaselevels'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ``opts' != "" {
= while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`emptycells' `noemptycells'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ``opts' != "" {
= while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {

```

```

        = if 0 < 2 {
        - exit
    }
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`fvlabel' `nofvlabel'"
    = opts_exclusive " "
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
        - exit
    }
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`omitted' `noomitted'"
    = opts_exclusive " "
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
        - exit
    }
> ----- end opts_exclus

```

```

> ive
- opts_exclusive "`\lststretch' \nolstretch'"
= opts_exclusive " "
-
>
- begin opts_exclus
> ive
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``\opts' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
-
>
- end opts_exclus
> ive
- opts_exclusive "`cnsreport' \fullcnsreport'"
= opts_exclusive " "
-
>
- begin opts_exclus
> ive
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``\opts' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
-
>
- end opts_exclus
> ive
- opts_exclusive "`coeflegend' \selegend'"
= opts_exclusive " "

```

```

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
        }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`nocl' `nopvalues'"
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
        }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - local K : list sizeof namelist
    - gettoken c_diopts c_opts : namelist
    - opts_exclusive "`coding' `compare'"
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____

```

```

- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`versus' `compare'"
    = opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    }

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`abbrev' `noabbrev'"
    = opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts

```



```

- local n 0
- while ``opts'' != "" {
= while `'' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- local allbaselevels `allbaselevels' `noallbaselevels'
= local allbaselevels
- local baselevels `baselevels' `nobaselevels'
= local baselevels
- local emptycells `emptycells' `noemptycells'
= local emptycells
- local omitted `omitted' `noomitted'
= local omitted
- local lstretch `lstretch' `nolstretch'
= local lstretch
- local fvlabel `fvlabel' `nofvlabel'
= local fvlabel
- local abbrev `abbrev' `noabbrev'
= local abbrev
- if "`allbaselevels'`baselevels'" == "" {
= if "" == "" {
- if c(showbaselevels) == "all" {
    local allbaselevels allbaselevels
  }
- else if c(showbaselevels) == "on" {
    local baselevels baselevels
  }
- }
- if "`emptycells'" == "" {
= if "" == "" {
- if c(showemptycells) == "off" {
    local emptycells noemptycells
  }
- }
- if "`omitted'" == "" {
= if "" == "" {
- if c(showomitted) == "off" {
    local omitted noomitted
  }
}

```

```

- }
- if "`lstretch'" == "" {
= if "" == "" {
- if c(lstretch) == "off" {
  local lstretch nolstretch
  }
- }
- if `:length local cformat' {
= if 0 {
  confirm numeric format `cformat'
  if fmtwidth("`cformat'") > 9 {
    local cformat "%9.0g"
    di "{txt}note: invalid cformat(), using default"
  }
  sreturn local cformat "`cformat'"
  local cformat `cformat(`cformat')'
}
- if `:length local sformat' {
= if 0 {
  confirm numeric format `sformat'
  if fmtwidth("`sformat'") > 8 {
    local sformat "%8.2f"
    di "{txt}note: invalid sformat(), using default"
  }
  sreturn local sformat "`sformat'"
  local sformat `sformat(`sformat')'
}
- if `:length local pformat' {
= if 0 {
  confirm numeric format `pformat'
  if fmtwidth("`pformat'") > 5 {
    local pformat "%5.3f"
    di "{txt}note: invalid pformat(), using default"
  }
  sreturn local pformat "`pformat'"
  local pformat `pformat(`pformat')'
}
- if `K' == 1 & `:length local options' {
= if 1 == 1 & 0 {
  syntax namelist(max=2) [, `DIOPTS']
}
- if reldif(`level', c(level)) > 1e-3 {
= if reldif(95, c(level)) > 1e-3 {
  local levelopt level(`level')
}
- Wraon , `fvwraon'

```

```

= Wraapon ,
> _____ begin _get_diopts.Wra
> pon _____
    - capture syntax [, W0rd WIdth]
    - if c(rc) {
      di as err "invalid fwraapon() option;"
      syntax [, W0rd WIdth]
      exit 198
    }
    - opts_exclusive "`word' `width'" fwraapon
= opts_exclusive " " fwraapon
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ``opts' != "" {
= while `"' != "" {
      local ++n
      gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
> _____ end opts_exclus
> ive _____
    - local fwraapon `word' `width'
= local fwraapon
    - if `:length local fwraapon' {
= if 0 {
      c_local fwraapon fwraapon(`fwraapon')
    }
> _____ end _get_diopts.Wra
> pon _____
    - if "`fwwrap'" != "" {
= if "" != "" {
      FWWrap, `fwwrap'
    }
    - c_local `c_diopts' `levelopt' `vsquish' `allbaselevels' `basel
> evels' `cnsreport' `fullcnsreport' `emptycells' `omitted' `lstretch' `coefle

```

```

> gend' `selegend' `cformat' `sformat' `pformat' `coding' `versus' `compare' `
> fvwrap' `fvwrapon' `fvlabel' `nocl' `nopvalues' `markdown' `citype' `abbrev'
    = c_local DEFAULT
    - if `K' == 2 {
    = if 1 == 2 {
        c_local `c_opts' ``options''
    }
    - sreturn local coding `coding'
    = sreturn local coding
    - sreturn local versus `versus'
    = sreturn local versus
    - sreturn local compare `compare'
    = sreturn local compare
    - sreturn local level `level'
    = sreturn local level 95
    _____
> _____ end _get_diopts.GetDio
> pts _____
    - if ``name2'' == "" {
    = if ``'' == "" {
    - GetDiopts DUPS, `options'
    = GetDiopts DUPS,
    _____
> _____ begin _get_diopts.GetDio
> pts _____
    - local DIOPTS Level(cilevel) vsquish NOALLBASElevels ALLBASElev
> els NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EMPTYcell
> s NOOMITted OMITted NOLSTRETCH LSTRETCH COEFlegend SELEGEND cformat(string)
> sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru) FVWRA
> PON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(passthru) NOABB
> REV ABBREV
    - syntax namelist(max=2) [, `DIOPTS' *]
    = syntax namelist(max=2) [, Level(cilevel) vsquish NOALLBASEleve
> ls ALLBASElevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYce
> lls EMPTYcells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFlegend SELEGEND cfo
> rmat(string) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(pa
> ssthru) FVWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(pa
> ssthru) NOABBREV ABBREV *]
    - opts_exclusive ``allbaselevels' `noallbaselevels''
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'

```

```

= local opts
- local n 0
- while ``opts'' != "" {
= while `'' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive ``allbaselevels' `nbaselevels'
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
- local n 0
- while ``opts'' != "" {
= while `'' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive ``baselevels' `nbaselevels'
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
- local n 0
- while ``opts'' != "" {
= while `'' != "" {

```

```

        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`emptycells' `noemptycells'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ```opts'"" != "" {
= while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`fvlabel' `nofvlabel'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ```opts'"" != "" {
= while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {

```

```

        = if 0 < 2 {
        - exit
    }
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`omitted' `noomitted'"
    = opts_exclusive " "
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    }
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`lstretch' `nolstretch'"
    = opts_exclusive " "
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    }
> ----- end opts_exclus

```

```

> ive -----
      - opts_exclusive "`cnsreport' `fullcnsreport'"
      = opts_exclusive " "
-----

> ----- begin opts_exclus
> ive -----
      - version 8.2
      - args opts optname errcode optslab
      - local opts `opts'
      = local opts
      - local n 0
      - while ``opts' != "" {
      = while `'' != "" {
          local ++n
          gettoken item`n' opts : opts, bind
        }
      - if `n' < 2 {
      = if 0 < 2 {
      - exit
-----

> ----- end opts_exclus
> ive -----
      - opts_exclusive "`coeflegend' `selegend'"
      = opts_exclusive " "
-----

> ----- begin opts_exclus
> ive -----
      - version 8.2
      - args opts optname errcode optslab
      - local opts `opts'
      = local opts
      - local n 0
      - while ``opts' != "" {
      = while `'' != "" {
          local ++n
          gettoken item`n' opts : opts, bind
        }
      - if `n' < 2 {
      = if 0 < 2 {
      - exit
-----

> ----- end opts_exclus
> ive -----
      - opts_exclusive "`noci' `nopvalues'"
      = opts_exclusive " "
-----

```



```

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ```opts'"" != "" {
    = while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
        }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - local K : list sizeof namelist
    - gettoken c_diopts c_opts : namelist
    - opts_exclusive ``coding' `compare'
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ```opts'"" != "" {
    = while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
        }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - opts_exclusive ``versus' `compare'
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____

```

```

- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`abbrev' `noabbrev'"
    = opts_exclusive " "
}

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
        }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    }

> ----- end opts_exclus
> ive -----
    - local allbaselevels `allbaselevels' `noallbaselevels'
    = local allbaselevels
    - local baselevels `baselevels' `nobaselevels'
    = local baselevels
    - local emptycells `emptycells' `noemptycells'
    = local emptycells
    - local omitted `omitted' `noomitted'
    = local omitted
    - local lstretch `lstretch' `nolstretch'

```

```

= local lstretch
- local fvlabel `fvlabel' `nofvlabel'
= local fvlabel
- local abbrev `abbrev' `noabbrev'
= local abbrev
- if "`allbaselevels'`baselevels'" == "" {
= if "" == "" {
- if c(showbaselevels) == "all" {
    local allbaselevels allbaselevels
  }
- else if c(showbaselevels) == "on" {
    local baselevels baselevels
  }
- }
- if "`emptycells'" == "" {
= if "" == "" {
- if c(showemptycells) == "off" {
    local emptycells noemptycells
  }
- }
- if "`omitted'" == "" {
= if "" == "" {
- if c(showomitted) == "off" {
    local omitted noomitted
  }
- }
- if "`lstretch'" == "" {
= if "" == "" {
- if c(lstretch) == "off" {
    local lstretch nolstretch
  }
- }
- if `:length local cformat' {
= if 0 {
    confirm numeric format `cformat'
    if fmtwidth("`cformat'") > 9 {
      local cformat "%9.0g"
      di "{txt}note: invalid cformat(), using default"
    }
    sreturn local cformat "`cformat'"
    local cformat `cformat(`cformat')'
  }
- if `:length local sformat' {
= if 0 {
    confirm numeric format `sformat'
    if fmtwidth("`sformat'") > 8 {

```

```

    local sformat "%8.2f"
    di "{txt}note: invalid sformat(), using default"
  }
  sreturn local sformat ``sformat''
  local sformat `sformat(`sformat')''
}
- if `:length local pformat' {
= if 0 {
  confirm numeric format `pformat'
  if fmtwidth(`pformat') > 5 {
    local pformat "%5.3f"
    di "{txt}note: invalid pformat(), using default"
  }
  sreturn local pformat ``pformat''
  local pformat `pformat(`pformat')''
}
- if `K' == 1 & `:length local options' {
= if 1 == 1 & 0 {
  syntax namelist(max=2) [, `DIOPTS']
}
- if reldif(`level', c(level)) > 1e-3 {
= if reldif(95, c(level)) > 1e-3 {
  local levelopt level(`level')
}
- Wraupon , `fvwraupon'
= Wraupon ,

```

> _____ begin _get_diopts.Wra

> pon _____

```

  - capture syntax [, W0rd WIdth]
  - if c(rc) {
    di as err "invalid fvwraupon() option;"
    syntax [, W0rd WIdth]
    exit 198
  }
  - opts_exclusive ``word' `width' fvwraupon
= opts_exclusive " " fvwraupon

```

> _____ begin opts_exclus

> ive _____

```

  - version 8.2
  - args opts optname errcode optslab
  - local opts `opts'
= local opts
  - local n 0
  - while ``opts'' != "" {

```

```

        = while `""` != "" {
            local ++n
            gettoken item`n' opts : opts, bind
        }
        - if `n' < 2 {
        = if 0 < 2 {
        - exit
    }

> _____ end opts_exclus
> ive _____
    - local fvwrapon `word' `width'
    = local fvwrapon
    - if `:length local fvwrapon' {
    = if 0 {
        c_local fvwrapon fvwrapon(`fvwrapon')
    }

> _____ end _get_diopts.Wra
> pon _____
    - if "`fvwrap'" != "" {
    = if "" != "" {
        FVWrap, `fvwrap'
    }
    - c_local `c_diopts' `levelopt' `vsquish' `allbaselevels' `basel
> evels' `cnsreport' `fullcnsreport' `emptycells' `omitted' `lstretch' `coefle
> gend' `selegend' `cformat' `sformat' `pformat' `coding' `versus' `compare' `
> fvwrap' `fvwrapon' `fvlabel' `nocl' `nopvalues' `markdown' `citype' `abbrev'
    = c_local DUPS
    - if `K' == 2 {
    = if 1 == 2 {
        c_local `c_opts' ``options'
    }
    - sreturn local coding `coding'
    = sreturn local coding
    - sreturn local versus `versus'
    = sreturn local versus
    - sreturn local compare `compare'
    = sreturn local compare
    - sreturn local level `level'
    = sreturn local level 95

> _____ end _get_diopts.GetDio
> pts _____
    - }
    - else {
        GetDiopts DUPS options, `options'

```

```

        c_local `name2' ``options'
    }
    - local DUPS : list DUPS - DEFAULT
    - gettoken DUPS : DUPS
    - if ``DUPS' != "" {
= if `"' != "" {
    if (strpos(`DUPS', "(")) {
        gettoken DUPS : DUPS, parse("(")
        local DUPS `DUPS'()'
    }
    di as err "duplicate {bf:`DUPS'} option not allowed"
    exit 198
}
    - sreturn clear
    - foreach sname of local snames {
    - sreturn local `sname' = ``S_`sname'
= sreturn local level = `95'
    - }
    - sreturn local `sname' = ``S_`sname'
= sreturn local options = `fvwrap(1)'
    - }
    - sreturn local `sname' = ``S_`sname'
= sreturn local method = `noadjust'
    - }

```

> _____ end _get_dio

> pts _____

```

    - local cformat ``s(cformat)'
= local cformat `"'
    - local sformat ``s(sformat)'
= local sformat `"'
    - local pformat ``s(pformat)'
= local pformat `"'
    - _get_eformopts , eformopts(`options') allowed(__all__) soptions
= _get_eformopts , eformopts() allowed(__all__) soptions

```

> _____ begin _get_eformo

> pts _____

```

    - version 8.0
    - syntax [, eformopts(string asis) soptions ALLOWed(string) ]
    - local 0 , `eformopts'
= local 0 ,
    - local EFALL NOHR hr NOSHR shr or IRr RRr tr TRatio
    - if ``soptions' != "" {
= if "soptions" != "" {
    - syntax [, EForm1(passthru) EForm `EFALL' * ]

```

```

= syntax [, EForm1(passthru) EForm NOHR hr NOSHR shr or IRr RRr tr
> TRatio * ]
- local opts ``options''
= local opts ``''
- local 0 , `eform1' `eform' `nohr' `hr' `noshr' `shr' `or' `irr'
> `rrr' `tr' `tratio'
= local 0 ,
- }
- if ``allowed'' == "__all__" {
= if "__all__" == "__all__" {
- local allowed `EFALL'
= local allowed NOHR hr NOSHR shr or IRr RRr tr TRatio
- }
- foreach ef of local allowed {
- capture confirm name `ef'
= capture confirm name NOHR
- if _rc {
di as err ``ef' is not a valid name"
exit 198
}
- local efopts `efopts' `=lower("`ef'")'
= local efopts nohr
- }
- capture confirm name `ef'
= capture confirm name hr
- if _rc {
di as err ``ef' is not a valid name"
exit 198
}
- local efopts `efopts' `=lower("`ef'")'
= local efopts nohr hr
- }
- capture confirm name `ef'
= capture confirmname NOSHR
- if _rc {
di as err ``ef' is not a valid name"
exit 198
}
- local efopts `efopts' `=lower("`ef'")'
= local efopts nohr hr noshr
- }
- capture confirm name `ef'
= capture confirm name shr
- if _rc {
di as err ``ef' is not a valid name"
exit 198
}

```

```

    }
- local efopts `efopts' `=lower("`ef'")'
= local efopts nohr hr noshr shr
- }
- capture confirm name `ef'
= capture confirm name or
- if _rc {
    di as err "`ef' is not a valid name"
    exit 198
  }
- local efopts `efopts' `=lower("`ef'")'
= local efopts nohr hr noshr shr or
- }
- capture confirm name `ef'
= capture confirm name IRr
- if _rc {
    di as err "`ef' is not a valid name"
    exit 198
  }
- local efopts `efopts' `=lower("`ef'")'
= local efopts nohr hr noshr shr or irr
- }
- capture confirm name `ef'
= capture confirm name RRr
- if _rc {
    di as err "`ef' is not a valid name"
    exit 198
  }
- local efopts `efopts' `=lower("`ef'")'
= local efopts nohr hr noshr shr or irr rrr
- }
- capture confirm name `ef'
= capture confirm name tr
- if _rc {
    di as err "`ef' is not a valid name"
    exit 198
  }
- local efopts `efopts' `=lower("`ef'")'
= local efopts nohr hr noshr shr or irr rrr tr
- }
- capture confirm name `ef'
= capture confirm name TRatio
- if _rc {
    di as err "`ef' is not a valid name"
    exit 198
  }

```



```

= else if `""'=="Time ratio" {
  local eform_cons_ti = "Time"
  local eform_cons_note = "time ratios"
}
- else if ```eform1'""'=="IRR" {
= else if `""'=="IRR" {
  local eform_cons_ti = "Inc. rate"
  local eform_cons_note = "incidence-rate ratios"
  local eform_cons_ti2 = "incidence rate"
}
- else if ```eform1'""'=="Risk ratio" {
= else if `""'=="Risk ratio" {
  local eform_cons_ti = "Risk"
  local eform_cons_note = "risk ratios"
}
- else if ```eform1'""'=="Hlth ratio" {
= else if `""'=="Hlth ratio" {
  local eform_cons_ti = "Health"
  local eform_cons_note = "health ratios"
}
- local k : list sizeof eform
- if `k' {
= if 0 {
  opts_exclusive ``eform'
  if `:length local eform1' {
    opts_exclusive "eform() `eform'"
  }
}
- if `k' {
= if 0 {
  if (``eform'=="eform") local eform1 = "exp(b)"
  else if (``eform'=="hr") {
    local eform1 = "Haz. ratio"
    local eform_cons_ti = "Hazard"
    local eform_cons_note = "hazard ratios"
  }
  else if (``eform'=="shr") {
    local eform1 = "SHR"
    local eform_cons_ti = "Subhazard"
    local eform_cons_note = "subhazard ratios"
  }
  else if (``eform'=="tr") {
    local eform1 = "Time ratio"
    local eform_cons_ti = "Time"
    local eform_cons_note = "time ratios"
  }
}

```

```

else if ("`eform'"=="tratio") {
  local eform1 = "Time ratio"
  local eform_cons_ti = "Time"
  local eform_cons_note = "time ratios"
}
else if ("`eform'"=="or") {
  local eform1 = "Odds ratio"
  if ("`e(cmd)'"=="asclogit" | "`e(cmd)'"=="cmclogit" | "`e(cmd)'"
> == "cmmixlogit" | "`e(cmd)'"=="cmxtmixlogit" ) {
    local eform_cons_ti = "Rel. risk"
    local eform_cons_note = "relative-risk ratios"
    local eform_cons_ti2 = "relative risk"
  }
  else {
    local eform_cons_ti = "Odds"
    local eform_cons_note = "odds ratios"
  }
}
else if ("`eform'"=="irr") {
  local eform1 = "IRR"
  local eform_cons_ti = "Inc. rate"
  local eform_cons_note = "incidence-rate ratios"
  local eform_cons_ti2 = "incidence rate"
}
else if ("`eform'"=="rrr") {
  local eform1 = "RRR"
  local eform_cons_ti = "Rel. risk"
  local eform_cons_note = "relative-risk ratios"
  local eform_cons_ti2 = "relative risk"
}
else if ("`eform'"!="nohr") & ("`eform'"!="noshr") {
  local eform1 = upper("`eform'")
}
}

- sreturn clear
- sreturn local options ```opts'``
= sreturn local options `""'
- sreturn local opt `eform'
= sreturn local opt
- sreturn local str `eform1'
= sreturn local str
- if ```eform1'`` != "" {
= if `""' != "" {
  sreturn local eform eform("`eform1'")
}
- else sreturn local eform ""

```

```

- sreturn local eform_cons_ti `eform_cons_ti'
= sreturn local eform_cons_ti
- sreturn local eform_cons_note `eform_cons_note'
= sreturn local eform_cons_note
- sreturn local eform_cons_ti2 `eform_cons_ti2'
= sreturn local eform_cons_ti2

> _____ end _get_eformo
> pts _____
- local tr_item = ``s(eform_cons_note)'''
= local tr_item = `'''
- if inlist("`bmatrix'", "", "e(b)") & "`e(k_eform)'" == "0" {
= if inlist("", "", "e(b)") & "" == "0" {
  local eform
  }
- else local eform ``s(str)'''
= else local eform `'''
- local eform_cons_ti ``s(eform_cons_ti)'''
= local eform_cons_ti `'''
- local eform_cons_ti2 ``s(eform_cons_ti2)'''
= local eform_cons_ti2 `'''
- if (`e(consonly)''!="1" | ``eform_cons_ti'')=="" ) {
= if (""!="1" | `''')=="" ) {
- local eformdi ``s(str)'''
= local eformdi `'''
- }
- else {
  local eformdi ``eform_cons_ti'''
  local tr_item = cond(missing("`eform_cons_ti2'"), strlower("`eform_
> m_cons_ti'''), ``eform_cons_ti2''')
  }
- local coefttl = cond("`eform'')==`'', ``coeftitle''', ``eformd
> i''')
= local coefttl = cond(`''')==`'', `'', `''')
- local options ``s(options)'''
= local options `'''
- _get_diparmopts, diparmopts(`options') level(`level')
= _get_diparmopts, diparmopts() level(95)

> _____ begin _get_diparmo
> pts _____
- if _caller() < 8.2 {
  _get_diparmopts_8 `0'
  exit
  }
- version 9

```

```

- local version : di "version " string(_caller()) ":"
- syntax [, diparmopts(string asis) EXECute soptions bottom plus S
> YNTAXonly * ]
- local goptions `options'
= local goptions level(95)
- SpliceGlobals junk , `goptions'
= SpliceGlobals junk , level(95)

> _____ begin _get_diparmopts.SpliceGlob
> als _____
- syntax name(id="macro name" name=c_diparm) [, diparm(string as
> is) Level(cilevel) dof(passthru) syntaxonly ]
- if ```dof``' == "" & ```e(df_r)``' != "" {
= if `""' == "" & ``213``' != "" {
- capture confirm integer number `e(df_r) '
= capture confirm integer number 213
- if !c(rc) {
- local gdof dof(`e(df_r)')
= local gdof dof(213)
- }
- capture
- }
- else local gdof ```dof``'
= else local gdof `""'
- local glevel `level'
= local glevel 95
- local lopt level(`glevel')
= local lopt level(95)
- if (```diparm``' == "") exit
= if (````' == "") exit

> _____ end _get_diparmopts.SpliceGlob
> als _____
- local 0 `", `diparmopts``'
= local 0 `", ""
- local diparmopts
- local k 0
- syntax [, diparm(string asis) * ]
- while ```diparm``' != "" {
= while `""' != "" {
local ++k
local single 1
local after
capture _on_colon_parse `diparm'
if !c(rc) {
local single 0

```

```

local diparm ``s(before)'''
local after ``s(after)'''
}
capture
SpliceGlobals diparm , diparm(`diparm') `syntaxonly' `goptions'
local diparm`k' ``diparm'''
local diparmopts ``diparmopts' : `diparm'''
if `single' | ``:list retok after''' == "" {
local 0 `", `options'''
syntax [, diparm(string asis) * ]
}
else {
local diparm ``after'''
}
}
- if ``soptions''' == "" {
= if `''' == "" {
- syntax [, diparm(string asis) ]
- }
- if ("`execute" == "") {
= if (" == "") {
- sreturn clear
- sreturn local options ``options'''
= sreturn local options `'''
- sreturn local diparm ``diparmopts'''
= sreturn local diparm `'''
- forval i = 1/`k' {
= forval i = 1/0 {
sreturn local diparm`i' ``diparm`i'''''
}
- sreturn local k `k'
= sreturn local k 0
- exit

```

> _____ end _get_diparmo

> pts

```

- local NODIPARM : length local nodiparm
- if `NODIPARM' {
= if 8 {
- local options
- }
- local GTOPTS parse(":") bind quotes
- local k 0
- if !`NODIPARM' {
= if !8 {
if ``e(diparm)''' != "" {

```

```

local i 0
local diparm ``e(diparm)''
}
else if ``e(diparm1)'' != "" {
local i 1
local diparm ``e(diparm1)''
}
while `:length local diparm' {
gettoken diparm rest : diparm, `GTPTS'
while `:length local rest' {
local ++k
local diparm`k' : copy local diparm
gettoken COLON rest : rest, `GTPTS'
gettoken diparm rest : rest, `GTPTS'
}
local ++k
local diparm`k' : copy local diparm
local ++i
local diparm ``e(diparm`i)''
}
}
- if `:length local options' {
= if 0 {
local 0 `", `options''
syntax [, diparm(string asis) *]
if `k' & `:length local diparm' {
local ++k
local diparm`k' __sep__
}
while `:length local diparm' {
gettoken diparm rest : diparm, `GTPTS'
while `:length local rest' {
local ++k
local diparm`k' : copy local diparm
gettoken COLON rest : rest, `GTPTS'
gettoken diparm rest : rest, `GTPTS'
}
local ++k
local diparm`k' : copy local diparm
local 0 `", `options''
syntax [, diparm(string asis) *]
}
}
- if "`markdown'" != "" {
= if "" != "" {
local lsize = c(linesize)

```

```

        set linesize 255
    }
    - `vv' mata: _coef_table()
    = version 11, missing: mata: _coef_table()

```

```

> _____ begin _get_dio
> pts _____
    - version 11
    - syntax namelist(max=2) [, *]
    - gettoken name1 namelist : namelist
    - gettoken name2 namelist : namelist
    - GetDiopts diopts options, `options'
    = GetDiopts diopts options, fwrap(1)

```

```

> _____ begin _get_diopts.GetDio
> pts _____
    - local DIOPTS Level(cilevel) vsquish NOALLBASElevels ALLBASElev
> els NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EMPTYcell
> s NOOMITted OMITted NOLSTRETCH LSTRETCH COEFlegend SELEGEND cformat(string)
> sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru) FVWRA
> PON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(passthru) NOABB
> REV ABBREV
    - syntax namelist(max=2) [, `DIOPTS' *]
    = syntax namelist(max=2) [, Level(cilevel) vsquish NOALLBASEleve
> ls ALLBASElevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYce
> lls EMPTYcells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFlegend SELEGEND cfo
> rmat(string) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(pa
> ssthru) FVWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(pa
> ssthru) NOABBREV ABBREV *]
    - opts_exclusive "`allbaselevels' `noallbaselevels'"
    = opts_exclusive " "

```

```

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {

```



```

        - exit
    _____
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`allbaselevels' `nbaselevels'"
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`baselevels' `nbaselevels'"
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____
> _____ end opts_exclus
> ive _____

```

```

- opts_exclusive "`emptycells' `noemptycells'"
= opts_exclusive " "


---


> 

---

 begin opts_exclus
> ive 

---


- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ```opts'` != "" {
= while ``` != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit


---


> 

---

 end opts_exclus
> ive 

---


- opts_exclusive "`fvlabel' `nofvlabel'"
= opts_exclusive " "


---


> 

---

 begin opts_exclus
> ive 

---


- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ```opts'` != "" {
= while ``` != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit


---


> 

---

 end opts_exclus
> ive 

---


- opts_exclusive "`omitted' `noomitted'"
= opts_exclusive " "


---


> 

---

 begin opts_exclus

```

```

> ive
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
      local ++n
      gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

>
> end opts_exclus
> ive
    - opts_exclusive "`lstretch' `nolstretch'"
    = opts_exclusive " "

>
> begin opts_exclus
> ive
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
      local ++n
      gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

>
> end opts_exclus
> ive
    - opts_exclusive "`cnsreport' `fullcnsreport'"
    = opts_exclusive " "

>
> begin opts_exclus
> ive
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'

```

```

= local opts
- local n 0
- while ``opts'' != "" {
= while `'' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive ``coeflegend' `selegend'
= opts_exclusive " "
}

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
- local n 0
- while ``opts'' != "" {
= while `'' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive ``noci' `nopvalues'
= opts_exclusive " "
}

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
- local n 0
- while ``opts'' != "" {
= while `'' != "" {

```

```

        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}
}
> ----- end opts_exclus
> ive -----
    - local K : list sizeof namelist
    - gettoken c_diopts c_opts : namelist
    - opts_exclusive "`coding' `compare'"
= opts_exclusive " "
}
}
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ```opts'"" != "" {
= while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
        - exit
    }
}
}
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`versus' `compare'"
= opts_exclusive " "
}
}
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ```opts'"" != "" {
= while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
}
}

```

```

        }
        - if `n' < 2 {
        = if 0 < 2 {
        - exit
    }
}
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`abbrev' `noabbrev'"
    = opts_exclusive " "
}
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
}
}
> ----- end opts_exclus
> ive -----
    - local allbaselevels `allbaselevels' `noallbaselevels'
    = local allbaselevels
    - local baselevels `baselevels' `nobaselevels'
    = local baselevels
    - local emptycells `emptycells' `noemptycells'
    = local emptycells
    - local omitted `omitted' `noomitted'
    = local omitted
    - local lstretch `lstretch' `nolstretch'
    = local lstretch
    - local fvlabel `fvlabel' `nofvlabel'
    = local fvlabel
    - local abbrev `abbrev' `noabbrev'
    = local abbrev
    - if "`allbaselevels'`baselevels'" == "" {
    = if "" == "" {
    - if c(showbaselevels) == "all" {
        local allbaselevels allbaselevels
    }
}
}

```

```

    }
- else if c(showbaselevels) == "on" {
    local baselevels baselevels
  }
- }
- if "`emptycells'" == "" {
= if "" == "" {
- if c(showemptycells) == "off" {
    local emptycells noemptycells
  }
- }
- if "`omitted'" == "" {
= if "" == "" {
- if c(showomitted) == "off" {
    local omitted noomitted
  }
- }
- if "`lstretch'" == "" {
= if "" == "" {
- if c(lstretch) == "off" {
    local lstretch nolstretch
  }
- }
- if `:length local cformat' {
= if 0 {
    confirm numeric format `cformat'
    if fmtwidth("`cformat'") > 9 {
      local cformat "%9.0g"
      di "{txt}note: invalid cformat(), using default"
    }
    sreturn local cformat "`cformat'"
    local cformat `cformat(`cformat')'
  }
- if `:length local sformat' {
= if 0 {
    confirm numeric format `sformat'
    if fmtwidth("`sformat'") > 8 {
      local sformat "%8.2f"
      di "{txt}note: invalid sformat(), using default"
    }
    sreturn local sformat "`sformat'"
    local sformat `sformat(`sformat')'
  }
- if `:length local pformat' {
= if 0 {
    confirm numeric format `pformat'

```

```

        if fmtwidth("`pformat'") > 5 {
        local pformat "%5.3f"
        di "{txt}note: invalid pformat(), using default"
        }
        sreturn local pformat "`pformat'"
        local pformat `pformat(`pformat')`
        }
- if `K' == 1 & `:length local options' {
= if 2 == 1 & 0 {
    syntax namelist(max=2) [, `DIOPTS']
    }
- if reldif(`level', c(level)) > 1e-3 {
= if reldif(95, c(level)) > 1e-3 {
    local levelopt level(`level')
    }
- Wrapon , `fvwrapon'
= Wrapon ,

> ----- begin _get_diopts.Wra
> pon -----
    - capture syntax [, WOrd WIdth]
    - if c(rc) {
        di as err "invalid fvwrapon() option;"
        syntax [, WOrd WIdth]
        exit 198
    }
    - opts_exclusive "`word' `width'" fvwrapon
    = opts_exclusive " " fvwrapon

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
        - exit

> ----- end opts_exclus

```



```

> ive -----
      - local fvwrapon `word' `width'
      = local fvwrapon
      - if `:length local fvwrapon' {
      = if 0 {
          c_local fvwrapon fvwrapon(`fvwrapon')
        }
      -----

> ----- end _get_diopts.Wra
> pon -----
      - if "`fvwrap'" != "" {
      = if "fvwrap(1)" != "" {
      - FVWrap, `fvwrap'
      = FVWrap, fvwrap(1)
      -----

> ----- begin _get_diopts.FVW
> rap -----
      - syntax, fvwrap(integer)
      - if `fvwrap' < 0 {
      = if 1 < 0 {
          di as err "{p}invalid option {bf:fvwrap(`fvwrap')}"; " "nonne
> gative integer required{p_end}"
          exit 198
        }
      -----

> ----- end _get_diopts.FVW
> rap -----
      - }
      - c_local `c_diopts' `levelopt' `vsquish' `allbaselevels' `basel
> evels' `cnsreport' `fullcnsreport' `emptycells' `omitted' `lstretch' `coefle
> gend' `selegend' `cformat' `sformat' `pformat' `coding' `versus' `compare' `
> fvwrap' `fvwrapon' `fvlabel' `nocl' `nopvalues' `markdown' `citype' `abbrev'
      = c_local diopts fvwrap(1)
      - if `K' == 2 {
      = if 2 == 2 {
      - c_local `c_opts' ``options'``
      = c_local options `""'
      - }
      - sreturn local coding `coding'
      = sreturn local coding
      - sreturn local versus `versus'
      = sreturn local versus
      - sreturn local compare `compare'
      = sreturn local compare
      - sreturn local level `level'
      = sreturn local level 95

```

```

> _____ end _get_diopts.GetDio
> pts _____
    - c_local `name1' ```diopts''
    = c_local __000009 ``fvwrap(1)''
    - local snames : s(macros)
    - foreach sname of local snames {
    - local S_`sname' = s(`sname')
    = local S_level = s(level)
    - }
    - local S_`sname' = s(`sname')
    = local S_k = s(k)
    - }
    - sreturn clear
    - GetDiopts DEFAULT
> _____ begin _get_diopts.GetDio
> pts _____
    - local DIOPTS Level(cilevel) vsquish NOALLBASElevels ALLBASElev
> els NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EMPTYcell
> s NOOMITted OMITted NOLSTRETCH LSTRETCH COEFlegend SELEGEND cformat(string)
> sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru) FVWRA
> PON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(passthru) NOABB
> REV ABBREV
    - syntax namelist(max=2) [, `DIOPTS' *]
    = syntax namelist(max=2) [, Level(cilevel) vsquish NOALLBASEleve
> ls ALLBASElevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYce
> lls EMPTYcells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFlegend SELEGEND cfo
> rmat(string) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(pa
> ssthru) FVWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(pa
> ssthru) NOABBREV ABBREV *]
    - opts_exclusive ``allbaselevels' `noallbaselevels''
    = opts_exclusive " "
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ```opts'' != "" {
    = while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }

```

```

- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`allbaselevels' `nbaselevels'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while "`opts'" != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`baselevels' `nbaselevels'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while "`opts'" != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

```

```

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`emptycells' `noemptycells'"
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ```opts'`` != "" {
    = while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`fvlabel' `nofvlabel'"
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ```opts'`` != "" {
    = while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`omitted' `noomitted'"
    = opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `'' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`lstretch' `nolstretch'"
    = opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `'' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`cnsreport' `fullcnsreport'"
    = opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2

```

```

- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`coeflegend' `selegend'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`nocl' `nopvalues'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0

```

```

- while ``opts'' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit

```

```

> ----- end opts_exclus
> ive -----
    - local K : list sizeof namelist
    - gettoken c_diopts c_opts : namelist
    - opts_exclusive "`coding' `compare'"
    = opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts'' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

```

```

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`versus' `compare'"
    = opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts'' != "" {
    = while `"' != "" {

```

```

        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`abbrev' `noabbrev'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ``opts' != "" {
= while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}

> ----- end opts_exclus
> ive -----
    - local allbaselevels `allbaselevels' `noallbaselevels'
= local allbaselevels
    - local baselevels `baselevels' `nobaselevels'
= local baselevels
    - local emptycells `emptycells' `noemptycells'
= local emptycells
    - local omitted `omitted' `noomitted'
= local omitted
    - local lstretch `lstretch' `nolstretch'
= local lstretch
    - local fvlabel `fvlabel' `nofvlabel'
= local fvlabel
    - local abbrev `abbrev' `noabbrev'
= local abbrev
    - if "`allbaselevels'`baselevels'" == "" {
= if "" == "" {

```



```

- if c(showbaselevels) == "all" {
  local allbaselevels allbaselevels
}
- else if c(showbaselevels) == "on" {
  local baselevels baselevels
}
- }
- if "`emptycells'" == "" {
= if "" == "" {
- if c(showemptycells) == "off" {
  local emptycells noemptycells
}
- }
- if "`omitted'" == "" {
= if "" == "" {
- if c(showomitted) == "off" {
  local omitted noomitted
}
- }
- if "`lstretch'" == "" {
= if "" == "" {
- if c(lstretch) == "off" {
  local lstretch nolstretch
}
- }
- if `:length local cformat' {
= if 0 {
  confirm numeric format `cformat'
  if fmtwidth("`cformat'") > 9 {
    local cformat "%9.0g"
    di "{txt}note: invalid cformat(), using default"
  }
  sreturn local cformat "`cformat'"
  local cformat `cformat(`cformat')'
}
- if `:length local sformat' {
= if 0 {
  confirm numeric format `sformat'
  if fmtwidth("`sformat'") > 8 {
    local sformat "%8.2f"
    di "{txt}note: invalid sformat(), using default"
  }
  sreturn local sformat "`sformat'"
  local sformat `sformat(`sformat')'
}
- if `:length local pformat' {

```

```

= if 0 {
    confirm numeric format `pformat'
    if fmtwidth(`""pformat'') > 5 {
        local pformat "%5.3f"
        di "{txt}note: invalid pformat(), using default"
    }
    sreturn local pformat `""pformat'
    local pformat `pformat(`pformat')'
}
- if `K' == 1 & `:length local options' {
= if 1 == 1 & 0 {
    syntax namelist(max=2) [, `DIOPTS']
}
- if reldif(`level', c(level)) > 1e-3 {
= if reldif(95, c(level)) > 1e-3 {
    local levelopt level(`level')
}
- Wraon , `fvwraon'
= Wraon ,

```

> _____ begin _get_diopts.Wra

> pon _____

```

- capture syntax [, W0rd WIdth]
- if c(rc) {
    di as err "invalid fvwrapon() option;"
    syntax [, W0rd WIdth]
    exit 198
}
- opts_exclusive "`word' `width'" fvwrapon
= opts_exclusive " " fvwrapon

```

> _____ begin opts_exclus

> ive _____

```

- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while `""opts' != "" {
= while `"" != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit

```

```

> _____ end opts_exclus
> ive _____
      - local fvwrapon `word' `width'
      = local fvwrapon
      - if `:length local fvwrapon' {
      = if 0 {
          c_local fvwrapon fvwrapon(`fvwrapon')
      }
      _____

> _____ end _get_diopts.Wra
> pon _____
      - if "`fvwrap'" != "" {
      = if "" != "" {
          FVWrap, `fvwrap'
      }
      - c_local `c_diopts' `levelopt' `vsquish' `allbaselevels' `basel
> evels' `cnsreport' `fullcnsreport' `emptycells' `omitted' `lstretch' `coefle
> gend' `selegend' `cformat' `sformat' `pformat' `coding' `versus' `compare' `
> fvwrap' `fvwrapon' `fvlabel' `noci' `nopvalues' `markdown' `citype' `abbrev'
      = c_local DEFAULT
      - if `K' == 2 {
      = if 1 == 2 {
          c_local `c_opts' ``options'
      }
      - sreturn local coding `coding'
      = sreturn local coding
      - sreturn local versus `versus'
      = sreturn local versus
      - sreturn local compare `compare'
      = sreturn local compare
      - sreturn local level `level'
      = sreturn local level 95
      _____

> _____ end _get_diopts.GetDio
> pts _____
      - if ``name2' == "" {
      = if `'' == "" {
      - GetDiopts DUPS, `options'
      = GetDiopts DUPS,
      _____

> _____ begin _get_diopts.GetDio
> pts _____
      - local DIOPTS Level(cilevel) vsquish NOALLBASElevels ALLBASElev
> els NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EMPTYcell
> s NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cformat(string)

```

```

> sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru) FVWRA
> PON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(passthru) NOABB
> REV ABBREV
    - syntax namelist(max=2) [, `DIOPTS' *]
    = syntax namelist(max=2) [, Level(cilevel) vsquish NOALLBASEleve
> ls ALLBASElevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYce
> lls EMPTYcells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cfo
> rmat(string) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(pa
> ssthru) FVWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(pa
> ssthru) NOABBREV ABBREV *]
    - opts_exclusive "`allbaselevels' `noallbaselevels'"
    = opts_exclusive " "


---


> 

---

 begin opts_exclus
> ive 

---


    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit


---


> 

---

 end opts_exclus
> ive 

---


    - opts_exclusive "`allbaselevels' `nobaselevels'"
    = opts_exclusive " "


---


> 

---

 begin opts_exclus
> ive 

---


    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }

```

```

- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`baselevels' `nobaselevels'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`emptycells' `noemptycells'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

```

```

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`fvlabel' `nofvlabel'"
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while `""opts'" != "" {
    = while `"" != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`omitted' `noomitted'"
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while `""opts'" != "" {
    = while `"" != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`lstretch' `nolstretch'"
    = opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`cnsreport' `fullcnsreport'"
    = opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`coeflegend' `selegend'"
    = opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2

```

```

- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`noci' `nopvalues'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- local K : list sizeof namelist
- gettoken c_diopts c_opts : namelist
- opts_exclusive "`coding' `compare'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'

```



```

= local opts
- local n 0
- while ``opts'' != "" {
= while `'' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`versus' `compare'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
- local n 0
- while ``opts'' != "" {
= while `'' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`abbrev' `noabbrev'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
- local n 0
- while ``opts'' != "" {
= while `'' != "" {

```

```

        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}
}
> ----- end opts_exclus
> ive -----
    - local allbaselevels `allbaselevels' `noallbaselevels'
= local allbaselevels
    - local baselevels `baselevels' `nobaselevels'
= local baselevels
    - local emptycells `emptycells' `noemptycells'
= local emptycells
    - local omitted `omitted' `noomitted'
= local omitted
    - local lstretch `lstretch' `nolstretch'
= local lstretch
    - local fvlabel `fvlabel' `nofvlabel'
= local fvlabel
    - local abbrev `abbrev' `noabbrev'
= local abbrev
    - if "`allbaselevels'`baselevels'" == "" {
= if "" == "" {
    - if c(showbaselevels) == "all" {
        local allbaselevels allbaselevels
    }
    - else if c(showbaselevels) == "on" {
        local baselevels baselevels
    }
    - }
    - if "`emptycells'" == "" {
= if "" == "" {
    - if c(showemptycells) == "off" {
        local emptycells noemptycells
    }
    - }
    - if "`omitted'" == "" {
= if "" == "" {
    - if c(showomitted) == "off" {
        local omitted noomitted
    }
    - }
    - if "`lstretch'" == "" {
= if "" == "" {

```

```

- if c(lstretch) == "off" {
  local lstretch nolstretch
}
- }
- if `:length local cformat' {
= if 0 {
  confirm numeric format `cformat'
  if fmtwidth("`cformat'") > 9 {
    local cformat "%9.0g"
    di "{txt}note: invalid cformat(), using default"
  }
  sreturn local cformat "`cformat'"
  local cformat `cformat(`cformat')"'
}
- if `:length local sformat' {
= if 0 {
  confirm numeric format `sformat'
  if fmtwidth("`sformat'") > 8 {
    local sformat "%8.2f"
    di "{txt}note: invalid sformat(), using default"
  }
  sreturn local sformat "`sformat'"
  local sformat `sformat(`sformat')"'
}
- if `:length local pformat' {
= if 0 {
  confirm numeric format `pformat'
  if fmtwidth("`pformat'") > 5 {
    local pformat "%5.3f"
    di "{txt}note: invalid pformat(), using default"
  }
  sreturn local pformat "`pformat'"
  local pformat `pformat(`pformat')"'
}
- if `K' == 1 & `:length local options' {
= if 1 == 1 & 0 {
  syntax namelist(max=2) [, `DIOPTS']
}
- if reldif(`level', c(level)) > 1e-3 {
= if reldif(95, c(level)) > 1e-3 {
  local levelopt level(`level')
}
- Wraon , `fvwraon'
= Wraon ,

```

> _____ begin _get_diopts.Wra

```

> pon
    - capture syntax [, WOrd Width]
    - if c(rc) {
      di as err "invalid fwwrapon() option;"
      syntax [, WOrd Width]
      exit 198
    }
    - opts_exclusive "`word' `width'" fwwrapon
    = opts_exclusive " " fwwrapon

> ----- begin opts_exclus
> ive
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
      local ++n
      gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
      - exit

> ----- end opts_exclus
> ive
    - local fwwrapon `word' `width'
    = local fwwrapon
    - if `:length local fwwrapon' {
    = if 0 {
      c_local fwwrapon fwwrapon(`fwwrapon')
    }

> ----- end _get_diopts.Wra
> pon
    - if "`fwwrap'" != "" {
    = if "" != "" {
      FWWrap, `fwwrap'
    }
    - c_local `c_diopts' `levelopt' `vsquish' `allbaselevels' `basel
> evels' `cnsreport' `fullcnsreport' `emptycells' `omitted' `lstretch' `coefle
> gend' `selegend' `cformat' `sformat' `pformat' `coding' `versus' `compare' `
> fwwrap' `fwwrapon' `fvlabel' `nocl' `nopvalues' `markdown' `citype' `abbrev'
    = c_local DUPS

```

```

- if `K' == 2 {
= if 1 == 2 {
    c_local `c_opts' ``options'''
  }
- sreturn local coding `coding'
= sreturn local coding
- sreturn local versus `versus'
= sreturn local versus
- sreturn local compare `compare'
= sreturn local compare
- sreturn local level `level'
= sreturn local level 95
}

> _____ end _get_diopts.GetDio
> pts _____
- }
- else {
  GetDiopts DUPS options, `options'
  c_local `name2' ``options'''
}
- local DUPS : list DUPS - DEFAULT
- gettoken DUPS : DUPS
- if ``DUPS''' != "" {
= if `''' != "" {
  if (strpos(`DUPS'', "(")) {
    gettoken DUPS : DUPS, parse("(")
    local DUPS `DUPS'()'
  }
  di as err "duplicate {bf:`DUPS'} option not allowed"
  exit 198
}
- sreturn clear
- foreach sname of local snames {
- sreturn local `sname' = ``S_`sname''''
= sreturn local level = `95''
- }
- sreturn local `sname' = ``S_`sname''''
= sreturn local k = `0''
- }
}

> _____ end _get_dio
> pts _____
- if ``markdown''' != "" {
= if "" != "" {
  set linesize `lsize'
}
}

```

```

- if "`eqselect'" == "" & "`eformnote'" != "noeformnote" {
= if "" == "" & "" != "noeformnote" {
- if ``"eformdi"!= "" & ("`e(cmd)'"!="gnbreg" | "`e(prefix)'"=="svy
> ") {
= if ``"!=" & ("regress"!="gnbreg" | ""=="svy") {
    local k_eform `r(k_eform)'
    if ("`k_eform'"=="") {
        local k_eform = 1
    }
    local k_eq `e(k_eq)'
    if ("`k_eq'"=="") {
        local k_eq = 1
    }
    if (`k_eform'<`k_eq' & `k_eform') {
        if ("`e(cmd2)'" == "stintreg" | "`e(cmd2)'" == "streg") & ("`e(cmd
> )" == "weibull" | "`e(cmd)'" == "gompertz") {
        }
        else {
            _eform_multeq_note efnote : `k_eform' ``tr_item'
            di as txt "`efnote'"
        }
    }
}
- if (``"eformdi"!= "" & "`e(noconstant)'"=="0" & ``"eform_cons_ti'
> "!=" & "`e(consonly)'"!="1") {
    = if (``"!=" & ""=="0" & ``"!=" & ""!="1") {
        if ("`e(cmd)'"=="asclogit" | "`e(cmd)'"=="cmclogit" | "`e(cmd)'"==
> "cmmixlogit" | "`e(cmd)'"=="cmxtmixlogit" ) {
            local asvar = ``"e(ranvars)'"`e(fixvars)'"`e(indvars)'" != ""
            if ``"e(casevars)'" != "" & `asvar' {
                local note1 "Exponentiated coefficients represent odds ratios for
> "
                local note2 "alternative-specific variables (first equation) and "
                local note3 "{help j_cmrisk##_new:relative-risk ratios} "
                local note4 "for case-specific variables."
                di as txt "{p 0 6 2}Note: `note1'`note2'`note3'`note4'{p_end}"
            }
        }
        if "`eform_cons_ti'" == "Inc. rate" {
            local eform_cons_note "incidence rate"
        }
        else if "`eform_cons_ti'" == "Rel. risk" {
            local eform_cons_note "relative risk"
        }
        else if "`eform_cons_ti'" == "Health" {
            local eform_cons_note "health (probability of no disease)"

```

```

    }
    else {
        local eform_cons_note = strlower("`eform_cons_ti'")
    }
    local eform_cons_note "baseline `eform_cons_note'"
    if ("`e(cmd2)'"=="") {
        local cmd `e(cmd)'
    }
    else {
        local cmd `e(cmd2)'
    }
    local f2 = udsustr("`cmd'",1,2)
    local is_re = ("`f2'"=="xt" | "`f2'"=="me")
    if `is_re' {
        local extranote " (conditional on zero random effects)"
    }
    di as txt "{p 0 6 2}Note: {bf:_cons} estimates " "`eform_cons_note
> ``extranote'" _c
    if ("`e(cmd)'"=="mlogit" | "`e(cmd)'"=="asclogit" | "`e(cmd)'"=="c
> mclogit" | "`e(cmd)'"=="cmmixlogit" | "`e(cmd)'"=="cmxtmixlogit" ) {
        di as txt " for each outcome" _c
    }
    di as txt ".{p_end}"
    }
- }
- return add
- if !`keepmc' {
= if !0 {
- return local mcmethod
- return local mctitle
- }

_____  

> _____ end _coef_ta  

> ble _____  

_____  

> _____ end _ereturn_disp  

> lay _____  

- mat `b1' = (1/`mean')*e(b)  

= mat __000006 = (1/__000001)*e(b)  

- mat score double `xb' = `b1' `if'  

= mat score double __000004 = __000006 if __000000  

- LikePois `y' `xb' `poff' [`weight'`exp'] `if', n(`nobs')  

= LikePois y_timing_max __000004 [] if __000000, n(__000002)  

_____  

> _____ begin poisson.LikeP  

> ois _____

```

```

- gettoken y 0 : 0
- gettoken xb 0 : 0
- syntax [fw aw pw iw] [if] , Nobs(string)
- if "`weight'"!="" {
= if ""!="" {
    if "`weight'"=="fweight" {
        local wt `[fw`exp']
    }
    else if "`weight'"=="iweight" {
        local wt `[iw`exp']
    }
    else local wt `[aw`exp']
}
- tempvar lnf
- qui gen double `lnf' = `y'*(`xb')-exp(`xb')-lngamma(`y'+1) `if'
= qui gen double __000009 = y_timing_max*(__000004)-exp(__000004)-lnga
> mma(y_timing_max+1) if __000000
- summarize `lnf' `wt' `if', meanonly
= summarize __000009 if __000000, meanonly
- if r(N) != `nobs' { exit }
= if r(N) != __000002 { exit }
- if "`weight'"=="aweight" {
= if ""=="aweight" {
    ret scalar lnf = r(N)*r(mean)
}
- else ret scalar lnf = r(sum)

> _____ end poisson.LikeP
> ois _____
- scalar `lnf1' = r(lnf)
= scalar __000008 = r(lnf)
- }
- if "`constan'"==" " {
= if ""==" " {
- SolveC `y' `xb'`poff' [`weight'`exp'] `if', n(`nobs') mean(`mean')
= SolveC y_timing_max __000004 [] if __000000, n(__000002) mean(__000001
> )

> _____ begin poisson.Sol
> veC _____
- gettoken y 0 : 0
- gettoken xb 0 : 0
- syntax [fw aw pw iw] [if] , Nobs(string) Mean(string)
- if "`weight'"=="pweight" {
= if ""=="pweight" {
    local weight "aweight"

```



```

    }
    - capture confirm variable `xb'
    = capture confirm variable __000004
    - if _rc {
        tempvar xbnew
        qui gen double `xbnew' = (`xb') `if'
        local xb `xbnew'
    }
    - summarize `xb' [`weight'`exp'] `if', meanonly
    = summarize __000004 [] if __000000, meanonly
    - if r(N) != `nobs' { exit }
    = if r(N) != __000002 { exit }
    - if r(max) - r(min) > 2*709 {
        exit
    }
    - if r(max) > 709 | r(min) < -709 {
        tempname shift
        if r(max) > 709 { scalar `shift' = 709 - r(max) }
        else scalar `shift' = -709 - r(min)
        local shift "+`shift'"
    }
    - tempvar expoff
    - qui gen double `expoff' = exp(`xb'`shift') `if'
    = qui gen double __000009 = exp(__000004) if __000000
    - summarize `expoff' [`weight'`exp'], meanonly
    = summarize __000009 [], meanonly
    - if r(N) != `nobs' { exit }
    = if r(N) != __000002 { exit }
    - return scalar _cons = ln(`mean')-ln(r(mean))`shift'
    = return scalar _cons = ln(__000001)-ln(r(mean))

```

```

> ----- end poisson.Sol
> veC -----
    - tempname c
    - scalar `c' = r(_cons)
    = scalar __000009 = r(_cons)
    - if `c'<. {
    = if __000009<. {
    - local c "+`c'"
    = local c "+__000009"
    - }
    - else local c
    - LikePois `y' `xb'`poff'`c' [`weight'`exp'] `if', n(`nobs')
    = LikePois y_timing_max __000004+__000009 [] if __000000, n(__000002)

```

```

> ----- begin poisson.LikeP

```

```

> ois
- gettoken y 0 : 0
- gettoken xb 0 : 0
- syntax [fw aw pw iw] [if] , Nobs(string)
- if "`weight'"!=" " {
= if ""!=" " {
  if "`weight'"=="fweight" {
    local wt `[fw`exp']"
  }
  else if "`weight'"=="iweight" {
    local wt `[iw`exp']"
  }
  else local wt `[aw`exp']"
}
- tempvar lnf
- qui gen double `lnf' = `y'*(`xb')-exp(`xb')-lgamma(`y'+1) `if'
= qui gen double __00000A = y_timing_max*(__000004+__000009)-exp(__000
> 004+__000009)-lgamma(y_timing_max+1) if __000000
- summarize `lnf' `wt' `if', meanonly
= summarize __00000A if __000000, meanonly
- if r(N) != `nobs' { exit }
= if r(N) != __000002 { exit }
- if "`weight'"=="aweight" {
= if ""=="aweight" {
  ret scalar lnf = r(N)*r(mean)
}
- else ret scalar lnf = r(sum)

> _____ end poisson.LikeP
> ois
- tempname lnf1c
- scalar `lnf1c' = r(lnf)
= scalar __00000A = r(lnf)
- }
- else local lnf1c .
- capture {
- gen double `z' = `y'*exp(-(`xb'`poff'`c'))-1 +`xb'`c' `if'
= gen double __000005 = y_timing_max*exp(-(__000004+__000009))-1 +__0000
> 04+__000009 if __000000
- `vv' _regress `z' `xvars' [aw=`wt'exp(`xb'`poff'`c')]' `if', `constan'
= version 18.5, missing: _regress __000005 rule_g rule_itr estimated [a
> w=exp(__000004+__000009)] if __000000,

> _____ begin _ereturn_disp
> lay
- version 11

```

```

- if "`e(b)'" == "" & "`e(V)'" == "" {
= if "matrix" == "" & "matrix" == "" {
    exit
  }
- if "`e(cmd)'" == "regress" {
= if "regress" == "regress" {
- local ALTOPT Beta
- }
- syntax [, eform(passthru) First neq(integer -1) PPlus `ALTOPT' *]
= syntax [, eform(passthru) First neq(integer -1) PPlus Beta *]
- _get_mcompare, `options'
= _get_mcompare, level(95.00) fwrap(1)

```

```

> ----- begin _get_mcomp
> are -----
    - version 11
    - local cmd ``e(cmd)''
    = local cmd `regress'
    - syntax [name(name=caller)] [, *]
    - local is_pwc = inlist("pwcompare", "`cmd'", "`caller'") | inlist("
> pwmean", "`cmd'", "`caller'")
    = local is_pwc = inlist("pwcompare", "regress", "") | inlist("pwmean
> ", "regress", "")
    - local is_marg = inlist("margins", "`cmd'", "`e(cmd2)'", "`caller'")
> )
    = local is_marg = inlist("margins", "regress", "", "")
    - local OPTIONS NOADJust BONferroni DUNCAn DUNNett SCHeffe SIDak SNK
> TUKey ADJustall
    - if `is_pwc' {
    = if 0 {
        syntax [name] [, `OPTIONS' MCOMPare(string) *]
    }
    - else {
    - syntax [name] [, MCOMPare(string) *]
    - local suboption mcompare()
    - }
    - sreturn clear
    - sreturn local options ``options''
    = sreturn local options `level(95.00) fwrap(1)''
    - if `is_pwc' {
    = if 0 {
        local METHOD `noadjust' `bonferroni' `duncan' `dunnett' `scheffe'
> `sidak' `snk' `tukey'
        local METHOD : list uniq METHOD
        opts_exclusive ``METHOD''
        local ALL `adjustall'

```

```

        opts_exclusive "`noadjust' `ALL'"
    }
    - local 0 `", `mcompare'""
    = local 0 `", ""
    - capture syntax [, `OPTIONS']
    = capture syntax [, NOADJUST BONferroni DUNCAn DUNNett SCHeffe SIDak
> SNK TUKey ADJustall]
    - if c(rc) {
        di as err "invalid mcompare() option;"
        di as err "method ``mcompare'' not allowed"
        error 198
    }
    - local METHOD `METHOD' `noadjust' `bonferroni' `duncan' `dunnett' `
> scheffe' `sidak' `snk' `tukey'
    = local METHOD
    - local METHOD : list uniq METHOD
    - local ALL `ALL' `adjustall'
    = local ALL
    - local ALL : list uniq ALL
    - opts_exclusive "`METHOD'" `suboption'
    = opts_exclusive "" mcompare()

_____  

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ```opts'"" != "" {
    = while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

_____  

> _____ end opts_exclus
> ive _____
    - if "`METHOD'" == "" {
    = if "" == "" {
    - if "`ALL'" != "" {
    = if "" != "" {
        di as err "multiple comparison method required with the adjustall
> option"

```

```

        exit 198
    }
    - local METHOD noadjust
    - local noadjust noadjust
    - }
    - opts_exclusive "`ALL' `noadjust'" `suboption'
= opts_exclusive " noadjust" mcompare()


---


> 

---

 begin opts_exclus
> ive 

---


    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts noadjust
    - local n 0
    - while ``opts'" != "" {
= while `"noadjust'" != "" {
    - local ++n
    - gettoken item`n' opts : opts, bind
= gettoken item1 opts : opts, bind
    - }
    - while ``opts'" != "" {
= while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 1 < 2 {
    - exit


---


> 

---

 end opts_exclus
> ive 

---


    - local EXCLUDE duncan dunnett snk tukey
    - if `:list METHOD in EXCLUDE' {
= if 0 {
    if `is_pwc' {
        local opt : copy local METHOD
    }
    else {
        local opt "mcompare(`METHOD')"
    }
    local cmdlist anova manova regress mvreg pwmean
    if "`cmd'" == "pwcompare" {
        local cmd ``e(cmd_est)'"
    }
    if `is_marg' {

```

```

        local cmd margins
    }
    if !`:list cmd in cmdlist' | !`is_pwc' {
        di as err `"method `opt' is not allowed with results from `cmd'"
        exit 322
    }
    if ```e(prefix)'' == "svy" {
        di as err `"method `opt' is not allowed with results using the svy
> prefix"
        exit 322
    }
    local vce ```e(vce)''
    if !inlist("`vce'", "", "ols") {
        di as err `"method `opt' is not allowed with results using vce(`vc
> e')"
        exit 322
    }
    }
    - local EXCLUDE duncan dunnett snk tukey scheffe
    - if `:list METHOD in EXCLUDE' {
    = if 0 {
        if "`ALL'" != "" {
            di as err `"option adjustall is not allowed with method `METHOD'"
            exit 198
        }
    }
    - sreturn local method ```METHOD''
    = sreturn local method `noadjust'
    - sreturn local adjustall ```ALL''
    = sreturn local adjustall `""'



---


> ----- end _get_mcomp
> are -----
    - if "`s(method)'" != "" {
    = if "noadjust" != "" {
    - loca mcopt mcompare(`s(method)' `s(adjustall)')
    = loca mcopt mcompare(noadjust )
    - }
    - _get_diopts diopts, `s(options)'
    = _get_diopts diopts, level(95.00) fwrap(1)



---


> ----- begin _get_dio
> pts -----
    - version 11
    - syntax namelist(max=2) [, *]
    - gettoken name1 namelist : namelist

```

```

- gettoken name2 namelist : namelist
- GetDiopts diopts options, `options'
= GetDiopts diopts options, level(95.00) fvwrap(1)

```

```

> ----- begin _get_diopts.GetDio
> pts -----
- local DIOPTS Level(cilevel) vsquish NOALLBASElevels ALLBASElevel
> s NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EMPTYcells
> NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cformat(string) sf
> ormat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru) FVWRAP0
> N(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(passthru) NOABBRE
> V ABBREV
- syntax namelist(max=2) [, `DIOPTS' *]
= syntax namelist(max=2) [, Level(cilevel) vsquish NOALLBASElevels
> ALLBASElevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcell
> s EMPTYcells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cform
> at(string) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(pass
> thru) FVWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(pass
> thru) NOABBREV ABBREV *]
- opts_exclusive "`allbaselevels' `noallbaselevels'"
= opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts'' != "" {
= while `'' != "" {
local ++n
gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit

```

```

> ----- end opts_exclus
> ive -----
- opts_exclusive "`allbaselevels' `nobaselevels'"
= opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
- version 8.2

```

```

- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`baselevels' `nobaselevels'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`emptycells' `noemptycells'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0

```



```

- while ``opts'' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`fvlabel' `nofvlabel'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts'' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`omitted' `noomitted'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts'' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}

```

```

    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`lstretch' `nolstretch'"
= opts_exclusive " "
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ``opts' != "" {
= while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`cnsreport' `fullcnsreport'"
= opts_exclusive " "
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ``opts' != "" {
= while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}

```

```

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`coeflegend' `selegend'"
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`noci' `nopvalues'"
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____
> _____ end opts_exclus
> ive _____
    - local K : list sizeof namelist

```

```

- gettoken c_diopts c_opts : namelist
- opts_exclusive "`coding' `compare'"
= opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ```opts'"" != "" {
= while `""' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit

```

```

> ----- end opts_exclus
> ive -----
- opts_exclusive "`versus' `compare'"
= opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ```opts'"" != "" {
= while `""' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit

```

```

> ----- end opts_exclus
> ive -----
- opts_exclusive "`abbrev' `noabbrev'"
= opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ```opts'`` != "" {
    = while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    -----

> ----- end opts_exclus
> ive
    - local allbaselevels `allbaselevels' `noallbaselevels'
    = local allbaselevels
    - local baselevels `baselevels' `nobaselevels'
    = local baselevels
    - local emptycells `emptycells' `noemptycells'
    = local emptycells
    - local omitted `omitted' `noomitted'
    = local omitted
    - local lstretch `lstretch' `nolstretch'
    = local lstretch
    - local fvlabel `fvlabel' `nofvlabel'
    = local fvlabel
    - local abbrev `abbrev' `noabbrev'
    = local abbrev
    - if "`allbaselevels'`baselevels'" == "" {
    = if "" == "" {
    - if c(showbaselevels) == "all" {
        local allbaselevels allbaselevels
    }
    - else if c(showbaselevels) == "on" {
        local baselevels baselevels
    }
    - }
    - if "`emptycells'" == "" {
    = if "" == "" {
    - if c(showemptycells) == "off" {
        local emptycells noemptycells
    }

```

```

- }
- if "`omitted'" == "" {
= if "" == "" {
- if c(showomitted) == "off" {
    local omitted noomitted
  }
- }
- if "`lstretch'" == "" {
= if "" == "" {
- if c(lstretch) == "off" {
    local lstretch nolstretch
  }
- }
- if `:length local cformat' {
= if 0 {
    confirm numeric format `cformat'
    if fmtwidth("`cformat'") > 9 {
      local cformat "%9.0g"
      di "{txt}note: invalid cformat(), using default"
    }
    sreturn local cformat "`cformat'"
    local cformat `cformat(`cformat')'
  }
- if `:length local sformat' {
= if 0 {
    confirm numeric format `sformat'
    if fmtwidth("`sformat'") > 8 {
      local sformat "%8.2f"
      di "{txt}note: invalid sformat(), using default"
    }
    sreturn local sformat "`sformat'"
    local sformat `sformat(`sformat')'
  }
- if `:length local pformat' {
= if 0 {
    confirm numeric format `pformat'
    if fmtwidth("`pformat'") > 5 {
      local pformat "%5.3f"
      di "{txt}note: invalid pformat(), using default"
    }
    sreturn local pformat "`pformat'"
    local pformat `pformat(`pformat')'
  }
- if `K' == 1 & `:length local options' {
= if 2 == 1 & 0 {
    syntax namelist(max=2) [, `DIOPTS']

```

```

    }
    - if reldif(`level', c(level)) > 1e-3 {
= if reldif(95, c(level)) > 1e-3 {
    local levelopt level(`level')
    }
    - Wraapon , `fvwraapon'
= Wraapon ,
    _____
> _____ begin _get_diopts.Wra
> pon _____
    - capture syntax [, W0rd WIdth]
    - if c(rc) {
        di as err "invalid fvwraapon() option;"
        syntax [, W0rd WIdth]
        exit 198
    }
    - opts_exclusive "`word' `width'" fvwraapon
= opts_exclusive " " fvwraapon
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ``opts' != "" {
= while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
        - exit
    }
    _____
> _____ end opts_exclus
> ive _____
    - local fvwraapon `word' `width'
= local fvwraapon
    - if `:length local fvwraapon' {
= if 0 {
        c_local fvwraapon fvwraapon(`fvwraapon')
    }
    _____
> _____ end _get_diopts.Wra
> pon _____

```

```

- if "`fvwrap'" != "" {
= if "fvwrap(1)" != "" {
- FVWrap, `fvwrap'
= FVWrap, fvwrap(1)
}

> _____ begin _get_diopts.FVW
> rap _____
- syntax, fvwrap(integer)
- if `fvwrap' < 0 {
= if 1 < 0 {
di as err "{p}invalid option {bf:fvwrap(`fvwrap')}"; " "nonnega
> tive integer required{p_end}"
exit 198
}

> _____ end _get_diopts.FVW
> rap _____
- }
- c_local `c_diopts' `levelopt' `vsquish' `allbaselevels' `baselev
> els' `cnsreport' `fullcnsreport' `emptycells' `omitted' `lstretch' `coeflege
> nd' `selegend' `cformat' `sformat' `pformat' `coding' `versus' `compare' `fv
> wrap' `fvwrapon' `fvlabel' `nocl' `nopvalues' `markdown' `citype' `abbrev'
= c_local diopts fvwrap(1)
- if `K' == 2 {
= if 2 == 2 {
- c_local `c_opts' ``options''
= c_local options ``''
- }
- sreturn local coding `coding'
= sreturn local coding
- sreturn local versus `versus'
= sreturn local versus
- sreturn local compare `compare'
= sreturn local compare
- sreturn local level `level'
= sreturn local level 95

> _____ end _get_diopts.GetDio
> pts _____
- c_local `name1' ``diopts''
= c_local diopts `fvwrap(1)''
- local snames : s(macros)
- foreach sname of local snames {
- local S_`sname' = s(`sname')
= local S_level = s(level)
- }

```



```

- local S_`sname' = s(`sname')
= local S_method = s(method)
- }
- local S_`sname' = s(`sname')
= local S_options = s(options)
- }
- sreturn clear
- GetDiopts DEFAULT

```

```

> _____ begin _get_diopts.GetDio
> pts _____
- local DIOPTS Level(cilevel) vsquish NOALLBASElevels ALLBASElevel
> s NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EMPTYcells
> NOOMITted OMITted NOLSTRETCH LSTRETCH COEFlegend SELEGEND cformat(string) sf
> ormat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru) FVWRAP0
> N(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(passthru) NOABBRE
> V ABBREV
- syntax namelist(max=2) [, `DIOPTS' *]
= syntax namelist(max=2) [, Level(cilevel) vsquish NOALLBASElevels
> ALLBASElevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcell
> s EMPTYcells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFlegend SELEGEND cform
> at(string) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(pass
> thru) FVWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(pass
> thru) NOABBREV ABBREV *]
- opts_exclusive "`allbaselevels' `noallbaselevels'"
= opts_exclusive " "

```

```

> _____ begin opts_exclus
> ive _____
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
local ++n
gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit

```

```

> _____ end opts_exclus
> ive _____
- opts_exclusive "`allbaselevels' `nobaselevels'"

```

```

= opts_exclusive " "
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
> _____ end opts_exclus
> ive _____
    - opts_exclusive ``baselevels' `nobaselevels'
    = opts_exclusive " "
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
> _____ end opts_exclus
> ive _____
    - opts_exclusive ``emptycells' `noemptycells'
    = opts_exclusive " "
> _____ begin opts_exclus
> ive _____

```

```

- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`fvlabel' `nofvlabel'"
    = opts_exclusive " "
}

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    }

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`omitted' `noomitted'"
    = opts_exclusive " "
}

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts

```

```

- local n 0
- while ``opts'' != "" {
= while `'' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`lstretch' `nolstretch'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts'' != "" {
= while `'' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`cnsreport' `fullcnsreport'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts'' != "" {
= while `'' != "" {
  local ++n

```

```

        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`coeflegend' `selegend'"
= opts_exclusive " "
}
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ```opts'"" != "" {
= while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`noci' `nopvalues'"
= opts_exclusive " "
}
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ```opts'"" != "" {
= while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {

```

```

        - exit
    _____
> _____ end opts_exclus
> ive _____
    - local K : list sizeof namelist
    - gettoken c_diopts c_opts : namelist
    - opts_exclusive "`coding' `compare'"
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ```opts'`` != "" {
    = while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
        - exit
    _____
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`versus' `compare'"
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ```opts'`` != "" {
    = while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
        - exit
    _____

```

```

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`abbrev' `noabbrev'"
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - local allbaselevels `allbaselevels' `noallbaselevels'
    = local allbaselevels
    - local baselevels `baselevels' `nobaselevels'
    = local baselevels
    - local emptycells `emptycells' `noemptycells'
    = local emptycells
    - local omitted `omitted' `noomitted'
    = local omitted
    - local lstretch `lstretch' `nolstretch'
    = local lstretch
    - local fvlabel `fvlabel' `nofvlabel'
    = local fvlabel
    - local abbrev `abbrev' `noabbrev'
    = local abbrev
    - if "`allbaselevels'`baselevels'" == "" {
    = if "" == "" {
    - if c(showbaselevels) == "all" {
        local allbaselevels allbaselevels
    }
    - else if c(showbaselevels) == "on" {
        local baselevels baselevels
    }
    - }

```

```

- if "`emptycells'" == "" {
= if "" == "" {
- if c(showemptycells) == "off" {
    local emptycells noemptycells
  }
- }
- if "`omitted'" == "" {
= if "" == "" {
- if c(showomitted) == "off" {
    local omitted noomitted
  }
- }
- if "`lstretch'" == "" {
= if "" == "" {
- if c(lstretch) == "off" {
    local lstretch nolstretch
  }
- }
- if `:length local cformat' {
= if 0 {
    confirm numeric format `cformat'
    if fmtwidth("`cformat'") > 9 {
      local cformat "%9.0g"
      di "{txt}note: invalid cformat(), using default"
    }
    sreturn local cformat "`cformat'"
    local cformat `cformat(`cformat')'
  }
- if `:length local sformat' {
= if 0 {
    confirm numeric format `sformat'
    if fmtwidth("`sformat'") > 8 {
      local sformat "%8.2f"
      di "{txt}note: invalid sformat(), using default"
    }
    sreturn local sformat "`sformat'"
    local sformat `sformat(`sformat')'
  }
- if `:length local pformat' {
= if 0 {
    confirm numeric format `pformat'
    if fmtwidth("`pformat'") > 5 {
      local pformat "%5.3f"
      di "{txt}note: invalid pformat(), using default"
    }
    sreturn local pformat "`pformat'"
  }

```



```

        local pformat `"pformat(`pformat`)"'
    }
- if `K' == 1 & `:length local options' {
= if 1 == 1 & 0 {
    syntax namelist(max=2) [, `DIOPTS']
    }
- if reldif(`level', c(level)) > 1e-3 {
= if reldif(95, c(level)) > 1e-3 {
    local levelopt level(`level')
    }
- Wrapon , `fvwrapon'
= Wrapon ,

> _____ begin _get_diopts.Wra
> pon _____
    - capture syntax [, W0rd WIdth]
    - if c(rc) {
        di as err "invalid fvwrapon() option;"
        syntax [, W0rd WIdth]
        exit 198
    }
    - opts_exclusive "`word' `width'" fvwrapon
= opts_exclusive " " fvwrapon

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ```opts`"' != "" {
= while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
        }
    - if `n' < 2 {
= if 0 < 2 {
        - exit

> _____ end opts_exclus
> ive _____
    - local fvwrapon `word' `width'
= local fvwrapon
    - if `:length local fvwrapon' {
= if 0 {

```

```

        c_local fwrapon fwrapon(`fwrapon')
    }
}
> ----- end _get_diopts.Wra
> pon
    - if "`fwrap'" != "" {
    = if "" != "" {
        FVWrap, `fwrap'
    }
    - c_local `c_diopts' `levelopt' `vsquish' `allbaselevels' `baselev
> els' `cnsreport' `fullcnsreport' `emptycells' `omitted' `lstretch' `coeflege
> nd' `selegend' `cformat' `sformat' `pformat' `coding' `versus' `compare' `fv
> wrap' `fwrapon' `fvlabel' `noci' `nopvalues' `markdown' `citype' `abbrev'
    = c_local DEFAULT
    - if `K' == 2 {
    = if 1 == 2 {
        c_local `c_opts' ``options'
    }
    - sreturn local coding `coding'
    = sreturn local coding
    - sreturn local versus `versus'
    = sreturn local versus
    - sreturn local compare `compare'
    = sreturn local compare
    - sreturn local level `level'
    = sreturn local level 95
}
> ----- end _get_diopts.GetDio
> pts
    - if ``name2' == "" {
    = if '' == "" {
        GetDiopts DUPS, `options'
    = GetDiopts DUPS,
}
> ----- begin _get_diopts.GetDio
> pts
    - local DIOPTS Level(cilevel) vsquish NOALLBASElevels ALLBASElevel
> s NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EMPTYcells
> NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cformat(string) sf
> ormat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru) FVWRAP0
> N(string) NOFVLabel FVLabel NOCI NOPValues MARKDOWN CITYPE(passthru) NOABBRE
> V ABBREV
    - syntax namelist(max=2) [, `DIOPTS' *]
    = syntax namelist(max=2) [, Level(cilevel) vsquish NOALLBASElevels
> ALLBASElevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcell
> s EMPTYcells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cform

```

```

> at(string) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(pass
> thru) FVWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(pass
> thru) NOABBREV ABBREV *)
    - opts_exclusive "`allbaselevels' `noallbaselevels'"
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`allbaselevels' `nobaselevels'"
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`baselevels' `nobaselevels'"

```

```

= opts_exclusive " "
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
> _____ end opts_exclus
> ive _____
    - opts_exclusive ``emptycells' `noemptycells'
    = opts_exclusive " "
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
> _____ end opts_exclus
> ive _____
    - opts_exclusive ``fvlabel' `nofvlabel'
    = opts_exclusive " "
> _____ begin opts_exclus
> ive _____

```

```

- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit

```

```

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`omitted' `noomitted'"
    = opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
        }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

```

```

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`lstretch' `nolstretch'"
    = opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts

```

```

- local n 0
- while ``opts'' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`cnsreport' `fullcnsreport'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts'' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`coeflegend' `selegend'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts'' != "" {
= while `"' != "" {
  local ++n

```

```

        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`noci' `nopvalues'"
= opts_exclusive " "
}
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ```opts'` != "" {
= while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}
> ----- end opts_exclus
> ive -----
    - local K : list sizeof namelist
    - gettoken c_diopts c_opts : namelist
    - opts_exclusive "`coding' `compare'"
= opts_exclusive " "
}
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ```opts'` != "" {
= while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
}

```

```

- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`versus' `compare'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while "`opts'" != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`abbrev' `noabbrev'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while "`opts'" != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

```



```

> ----- end opts_exclus
> ive
- local allbaselevels `allbaselevels' `noallbaselevels'
= local allbaselevels
- local baselevels `baselevels' `nobaselevels'
= local baselevels
- local emptycells `emptycells' `noemptycells'
= local emptycells
- local omitted `omitted' `noomitted'
= local omitted
- local lstretch `lstretch' `nolstretch'
= local lstretch
- local fvlabel `fvlabel' `nofvlabel'
= local fvlabel
- local abbrev `abbrev' `noabbrev'
= local abbrev
- if "`allbaselevels'`baselevels'" == "" {
= if "" == "" {
- if c(showbaselevels) == "all" {
  local allbaselevels allbaselevels
}
- else if c(showbaselevels) == "on" {
  local baselevels baselevels
}
- }
- if "`emptycells'" == "" {
= if "" == "" {
- if c(showemptycells) == "off" {
  local emptycells noemptycells
}
- }
- if "`omitted'" == "" {
= if "" == "" {
- if c(showomitted) == "off" {
  local omitted noomitted
}
- }
- if "`lstretch'" == "" {
= if "" == "" {
- if c(lstretch) == "off" {
  local lstretch nolstretch
}
- }
- if `:length local cformat' {
= if 0 {
  confirm numeric format `cformat'

```

```

    if fmtwidth(`"`cformat'`) > 9 {
    local cformat "%9.0g"
    di "{txt}note: invalid cformat(), using default"
    }
    sreturn local cformat `"`cformat'`'
    local cformat `"cformat(`cformat')"'
    }
- if `:length local sformat' {
= if 0 {
    confirm numeric format `sformat'
    if fmtwidth(`"`sformat'`) > 8 {
    local sformat "%8.2f"
    di "{txt}note: invalid sformat(), using default"
    }
    sreturn local sformat `"`sformat'`'
    local sformat `"sformat(`sformat')"'
    }
- if `:length local pformat' {
= if 0 {
    confirm numeric format `pformat'
    if fmtwidth(`"`pformat'`) > 5 {
    local pformat "%5.3f"
    di "{txt}note: invalid pformat(), using default"
    }
    sreturn local pformat `"`pformat'`'
    local pformat `"pformat(`pformat')"'
    }
- if `K' == 1 & `:length local options' {
= if 1 == 1 & 0 {
    syntax namelist(max=2) [, `DIOPTS']
    }
- if reldif(`level', c(level)) > 1e-3 {
= if reldif(95, c(level)) > 1e-3 {
    local levelopt level(`level')
    }
- Wraon , `fvwraon'
= Wraon ,

```

```

> _____ begin _get_diopts.Wra
> pon _____

```

```

- capture syntax [, W0rd WIdth]
- if c(rc) {
    di as err "invalid fvwrapon() option;"
    syntax [, W0rd WIdth]
    exit 198
    }

```

```

- opts_exclusive "`word' `width'" fvwrapon
= opts_exclusive " " fvwrapon

```

```

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit

```

```

> ----- end opts_exclus
> ive -----
- local fvwrapon `word' `width'
= local fvwrapon
- if `:length local fvwrapon' {
= if 0 {
  c_local fvwrapon fvwrapon(`fvwrapon')
}

```

```

> ----- end _get_diopts.Wra
> pon -----
- if "`fvwrap'" != "" {
= if "" != "" {
  FVWrap, `fvwrap'
}
- c_local `c_diopts' `levelopt' `vsquish' `allbaselevels' `baselev
> els' `cnsreport' `fullcnsreport' `emptycells' `omitted' `lstretch' `coeflege
> nd' `selegend' `cformat' `sformat' `pformat' `coding' `versus' `compare' `fv
> wrap' `fvwrapon' `fvlabel' `nocl' `nopvalues' `markdown' `citype' `abbrev'
= c_local DUPS
- if `K' == 2 {
= if 1 == 2 {
  c_local `c_opts' ``options'
}
- sreturn local coding `coding'
= sreturn local coding
- sreturn local versus `versus'

```

```

= sreturn local versus
- sreturn local compare `compare'
= sreturn local compare
- sreturn local level `level'
= sreturn local level 95

```

```

> _____ end _get_diopts.GetDio
> pts _____
- }
- else {
  GetDiopts DUPS options, `options'
  c_local `name2' ``options'
}
- local DUPS : list DUPS - DEFAULT
- gettoken DUPS : DUPS
- if ``DUPS' != "" {
= if ``' != "" {
  if (strpos(`DUPS', "(")) {
    gettoken DUPS : DUPS, parse("(")
    local DUPS `DUPS'()'
  }
  di as err "duplicate {bf:`DUPS'} option not allowed"
  exit 198
}
- sreturn clear
- foreach sname of local snames {
- sreturn local `sname' = ``S_`sname'
= sreturn local level = `95'
- }
- sreturn local `sname' = ``S_`sname'
= sreturn local method = `noadjust'
- }
- sreturn local `sname' = ``S_`sname'
= sreturn local options = `level(95.00) fvwrap(1)'
- }

```

```

> _____ end _get_dio
> pts _____
- if !`:length local first' {
= if !0 {
- local first showeqns
- }
- if `neq' < 1 {
= if -1 < 1 {
- _ms_eq_info
- local neqopt neq(`r(k_eq)')

```

```

= local neqopt neq(1)
- }
- else {
  local neqopt neq(`neq')
}
- _coef_table, nodiparm nocnsreport noeqcheck eformall `eform' `first'
> `neqopt' `plus' `beta' `mcopt' `diopts'
  = _coef_table, nodiparm nocnsreport noeqcheck eformall showeqns neq(1
> ) mcompare(noadjust ) fvwrap(1)



---


> 

---

 begin _coef_ta
> ble 

---


- version 11
- local vv : di "version " string(max(11,_caller())) ", missing:"
- if (!c(noisily) & c(coeftabresults) == "off") {
  exit
}
- _check_eclass
- syntax [, BMATrix(passthru) VMATrix(passthru) * ]
- if "`e(b)'" == "" & "`e(V)'" == "" & "`bmatrix'`vmatrix'""=="" {
= if "matrix" == "" & "matrix" == "" & ""=="" {
  exit
}
- local mc_cmds contrast margins pwcompare pwmean
- local cmd "`e(cmd)'"
= local cmd "regress"
- local keepmc : list cmd in mc_cmds
- if inlist("`cmd'", "pwcompare", "pwmean") {
= if inlist("regress", "pwcompare", "pwmean") {
  local groups GROUPS
}
- if "`cmd'" == "regress" {
= if "regress" == "regress" {
- local beta Beta
- }
- if "`cmd'" == "gsem" {
= if "regress" == "gsem" {
  local fvignore fvignore(int 0)
  local flignore flignore
}
- if "`cmd'" == "sem" {
= if "regress" == "sem" {
  local standardized STANDARDIZED
  local showginvariant SHOWGINvariant
  local nolabel NOLABel LABel NOFVLABel FVLABel
  local nofootnote NOFOOTnote

```

```

        local wrap wrap(numlist max=1) fvwrap(passthru)
    }
    - if "`e(mi)'"=="mi" {
= if ""=="mi" {
    local dftable DFTable
    local dfonly DFONLY
    local noclustreport NOCLUSTReport
    local pisematrix PISEMATrix(string)
}
    - syntax [, cmdextras BMATrix(string) VMATrix(string) EMATrix(string
> ) DFMATrix(string) EQMATrix(string) ROWMATrix(string) CIMATrix(string) PMATr
> ix(string) TSMATrix(string) ROWCFormat(string) ROWPFormat(string) ROWSFormat
> (string) NOROWCI MMATrix(string) MVMATrix(string) MEMATrix(string) BSTDMATri
> x(string) CNSMATrix(string) PCLASSMATrix(string) Level(cilevel) prefix(name)
> cnszero(string) suffix(name) OFFSETlist(string asis) `beta' `standardized'
> NOCI NOPValues `dftable' `dfonly' dfci DFPValues dfmissing `groups' COEFLege
> nd selegend `fvignore' `flignore' `showginvariant' `nolabel' `nofootnote' `w
> rap' sort `pisematrix' depname(string) COEFTitle(string) coeftitle2(string)
> ptitle(string) cititle(string) NOMCLEGen noCNSReport FULLCNSReport `noclust
> report' cformat(passthru) sformat(passthru) pformat(passthru) NOFirst First
> SHOWEQns neq(integer -1) NODIPARM NOTEST SEPARATOR(integer 0) NOSKIP OFFSET0
> NLY1 Plus NOEQCHECK EFORMALL CITYPE(string) eqselect(string) cidisjoint noEF
> ORMNOTE * ]

    = syntax [, cmdextras BMATrix(string) VMATrix(string) EMATrix(string
> ) DFMATrix(string) EQMATrix(string) ROWMATrix(string) CIMATrix(string) PMATr
> ix(string) TSMATrix(string) ROWCFormat(string) ROWPFormat(string) ROWSFormat
> (string) NOROWCI MMATrix(string) MVMATrix(string) MEMATrix(string) BSTDMATri
> x(string) CNSMATrix(string) PCLASSMATrix(string) Level(cilevel) prefix(name)
> cnszero(string) suffix(name) OFFSETlist(string asis) Beta NOCI NOPValues
> dfci DFPValues dfmissing COEFLegend selegend      sort depname(string) C
> OEFTitle(string) coeftitle2(string) ptitle(string) cititle(string) NOMCLEGen
> d noCNSReport FULLCNSReport cformat(passthru) sformat(passthru) pformat(pas
> sthru) NOFirst First SHOWEQns neq(integer -1) NODIPARM NOTEST SEPARATOR(inte
> ger 0) NOSKIP OFFSETONLY1 Plus NOEQCHECK EFORMALL CITYPE(string) eqselect(st
> ring) cidisjoint noEFORMNOTE * ]
    - if "`wrap'" != "" {
= if "" != "" {
    opts_exclusive `wrap(`wrap') `fvwrap'
    local fvwrap fvwrap(`wrap')
}
    - if "`nolabel'`label'" != "" {
= if "" != "" {
    opts_exclusive "`nolabel' `label'"
    opts_exclusive "`nofvlabel' `fvlabel'"
    opts_exclusive "`nolabel' `fvlabel'"
    opts_exclusive "`nofvlabel' `label'"

```

```

        if "`nolabel'" != "" {
            local fvlablel nofvlablel
        }
        else {
            local fvlablel fvlablel
        }
    }
    - _novce_other_mats, cimatrix("`cimatrix'") pmatrix("`pmatrix'") tsm
> atrix("`tsmatrix'") `noci' `nopvalues' `dfci' `dfpvalues' `cidisjoint'
    = _novce_other_mats, cimatrix("") pmatrix("") tsmatrix("")

_____  

> _____ begin _coef_table._novce_other_m
> ats _____
        - syntax [anything], [ CIMATrix(string) PMATrix(string) TSMATrix(s
> tring) NOCI NOPValues dfci DFPValues cidisjoint ]
        - if ("`pmatrix'"=="" & "`tsmatrix'"=="" & "`e(V)'"=="" & "`cimatr
> ix'"!="") {
            = if ("""=="" & """"=="" & "matrix"=="" & ""!=" & ""!=") {
                sreturn local cimatrix "empt"
            }
            - if ("`pmatrix'"=="" & "`tsmatrix'"!=" & "`e(V)'"=="" & "`cimatr
> ix'"=="" & ("`noci'"!="|"`nopvalues'"!=")) {
                = if ("""=="" & ""!=" & "matrix"=="" & ""=="" & ("!"="|!"=")) {
                    sreturn local noci "empt"
                    sreturn local nopvalues "empt"
                }
            - if ("`pmatrix'"=="" & "`tsmatrix'"=="" & "`e(V)'"=="" & "`cimatr
> ix'"!=" & "`noci'"!=") {
                = if ("""=="" & """"=="" & "matrix"=="" & ""!=" & ""!=") {
                    sreturn local cimatrix "empt"
                }
            - if ("`pmatrix'"!=" & "`tsmatrix'"=="" & "`e(V)'"=="" & "`cimatr
> ix'"=="" & "`nopvalues'"!=") {
                = if ("!"=" & ""=="" & "matrix"=="" & ""=="" & ""!=") {
                    sreturn local pmatrix "empt"
                }
            - if ("`pmatrix'"!=" & "`tsmatrix'"=="" & "`e(V)'"=="" & "`cimatr
> ix'"=="" & "`noci'"!=") {
                = if ("!"=" & ""=="" & "matrix"=="" & ""=="" & ""!=") {
                    sreturn local noci "empt"
                }
            - if ("`pmatrix'"!=") {
            = if ("!"=") {
                tempname pmat invalid
                capture matrix `pmat' = `pmatrix'
                local rc = _rc

```

```

if (`rc') {
display as error "invalid {bf:pmatrix()}"
exit 198
}
else {
local k: rowsof `pmat'
if (`k'>1 | `k'==0) {
display as error "{bf:pmatrix()} should be a row vector"
exit 198
}
}
scalar `isvalid' = 1
mata: _is_in_0_1void("`pmat'", "`isvalid'")
if (`isvalid'==0) {
display as error "invalid {bf:pmatrix()}"
di as txt "{p 4 4 2}"
di as smcl as err "{bf:pmatrix()}"
di as smcl as err "should contain values inside"
di as smcl as err "the interval [0,1]."
di as smcl as err "{p_end}"
exit 198
}
}
- if ("`tsmatrix'"!="") {
= if ("!=") {
tempname tmat
capture matrix `tmat' = `tsmatrix'
local rc = _rc
if (`rc') {
display as error "invalid {bf:tsmatrix()}"
exit 198
}
else {
local k: rowsof `tmat'
if (`k'>1 | `k'==0) {
display as error "{bf:tsmatrix()} should be a row vector"
exit 198
}
}
}
- if ("`cimatix'"!="") {
= if ("!=") {
tempname cimat isvalid
capture matrix `cimat' = `cimatix'
local rc = _rc
if (`rc') {

```



```

display as error "invalid {bf:cimatrix()}"
exit 198
}
if ("`cidisjoint'"=="" & "`e(disjoint)'"=="") {
  scalar `isvalid' = 1
  mata: _is_in_ci("`cimat'", "`isvalid'")
  if (`isvalid'==0) {
    display as error "invalid {bf:cimatrix()}"
    di as txt "{p 4 4 2}"
    di as smcl as err "{bf:cimatrix()}"
    di as smcl as err "lower limit should be"
    di as smcl as err "smaller than the upper"
    di as smcl as err "limit."
    di as smcl as err "{p_end}"
    exit 198
  }
}
}
}
- if ("`e(V)'"=="" & "`dfci'"!="" & "`pmatrx'"!="") {
= if ("matrix"=="" & ""!="" & ""!="") {
  opts_exclusive "pmatrx()" `dfci'
}
- if ("`e(V)'"=="" & "`dfci'"!="" & "`tsmatrx'"!="") {
= if ("matrix"=="" & ""!="" & ""!="") {
  opts_exclusive "tsmatrx()" `dfci'
}
- if ("`e(V)'"=="" & "`dfci'"!="" & "`cimatrix'"!="") {
= if ("matrix"=="" & ""!="" & ""!="") {
  opts_exclusive "cimatrix()" `dfci'
}
- if ("`e(V)'"=="" & "`dfpvalues'"!="" & "`pmatrx'"!="") {
= if ("matrix"=="" & ""!="" & ""!="") {
  opts_exclusive "pmatrx()" `dfci'
}
- if ("`e(V)'"=="" & "`dfpvalues'"!="" & "`tsmatrx'"!="") {
= if ("matrix"=="" & ""!="" & ""!="") {
  opts_exclusive "tsmatrx()" `dfpvalues'
}
- if ("`e(V)'"=="" & "`dfpvalues'"!="" & "`cimatrix'"!="") {
= if ("matrix"=="" & ""!="" & ""!="") {
  opts_exclusive "cimatrix()" `dfpvalues'
}
}

```

```
> _____ end _coef_table._novce_other_m
```

```
> ats _____
- if ("`s(cimatrix)'"=="empt") {
```

```

= if (""=="empt") {
  local cimatix ""
}
- if ("`s(pmatrix)""=="empt") {
= if (""=="empt") {
  local pmatrix ""
}
- if ("`s(noci)""=="empt") {
= if (""=="empt") {
  local noci ""
}
- if ("`s(nopvalues)""=="empt") {
= if (""=="empt") {
  local nopvalues ""
}
- if ("`e(V)""!=" & "`cidisjoint""!=") {
= if ("matrix"!=" & ""!=") {
  display in red "option {bf:cidisjoint} not allowed when e(V) is po
> sted"
  exit 198
}
- else local fvlabel `nofvlabel' `fvlabel'
= else local fvlabel
- local type `coeflegend' `selegend'
= local type
- opts_exclusive "`type' `standardized'"
= opts_exclusive " "

> _____ begin opts_exclus
> ive _____
  - version 8.2
  - args opts optname errcode optslab
  - local opts `opts'
  = local opts
  - local n 0
  - while "`opts'" != "" {
  = while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
  }
  - if `n' < 2 {
  = if 0 < 2 {
  - exit

> _____ end opts_exclus
> ive _____

```

```

- if ("`rowmatrix'"=="" & "`norowci'"!="") {
= if ("'"=="" & "'!='") {
    di as err "{bf:norowci} requires {bf:rowmatrix()}"
    exit 198
}
- if ("`dftable'"!=" & "`norowci'"!="") {
= if ("'"!=" & "'!='") {
    di as err "{bf:norowci} is not allowed with {bf:`dftable'}"
    exit 198
}
- if ("`dfonly'"!=" & "`norowci'"!="") {
= if ("'"!=" & "'!='") {
    di as err "{bf:norowci} is not allowed with {bf:`dfonly'}"
    exit 198
}
- if ("`noci'"!=" & "`norowci'"!="") {
= if ("'"!=" & "'!='") {
    di as err "{bf:norowci} is not allowed with {bf:`noci'}"
    exit 198
}
- if "`standardized'" != "" & "`bstdmatrix'" != "" {
= if "" != "" & "" != "" {
    local beta beta
    local standardized
}
- if `:length local type' == 0 {
= if 0 == 0 {
- local type `beta' `noci' `nopvalues' `dftable' `dfonly' `groups' `
> dfci' `dfpvalues'
= local type
- }
- opts_exclusive "`type'"
= opts_exclusive ""

> _____ begin opts_exclus
> ive _____
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while "`opts'" != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}

```

```

- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive
- opts_exclusive "`first' `nofirst'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ```opts' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive
- opts_exclusive "`first' `showeqns'"
= opts_exclusive " showeqns"

> ----- begin opts_exclus
> ive
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts showeqns
- local n 0
- while ```opts' != "" {
= while `"showeqns" != "" {
  local ++n
  gettoken item`n' opts : opts, bind
= gettoken item1 opts : opts, bind
- }
- while ```opts' != "" {
= while `"' != "" {
  local ++n

```

```

        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 1 < 2 {
    - exit
}
> ----- end opts_exclus
> ive -----
    - local cnsreport `cnsreport' `fullcnsreport'
= local cnsreport nocnsreport
    - opts_exclusive "`cnsreport'"
= opts_exclusive "nocnsreport"
}
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts nocnsreport
    - local n 0
    - while ```opts'"" != "" {
= while `"nocnsreport"" != "" {
    - local ++n
    - gettoken item`n' opts : opts, bind
= gettoken item1 opts : opts, bind
    - }
    - while ```opts'"" != "" {
= while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 1 < 2 {
    - exit
}
> ----- end opts_exclus
> ive -----
    - if ```showeqns'"" != "" {
= if `"showeqns"" != "" {
    - local nofirst nofirst
    - }
    - if ```ematrix'`noeqcheck'"" == "" {
= if `"noeqcheck"" == "" {
        if ```e(error)'" == "matrix" {
            local ematrix e(error)
        }
    }
}

```

```

    }
    - _get_mcompare, `options'
    = _get_mcompare, mcompare(noadjust ) fvwrap(1)
  }
}

> ----- begin _get_mcomp
> are -----
    - version 11
    - local cmd ``e(cmd)'''
    = local cmd ``regress'''
    - syntax [name(name=caller)] [, *]
    - local is_pwc = inlist("pwcompare", ``cmd'", ``caller'") | inlist
> ("pwmean", ``cmd'", ``caller'")
    = local is_pwc = inlist("pwcompare", "regress", "") | inlist("pwme
> an", "regress", "")
    - local is_marg = inlist("margins", ``cmd'", ``e(cmd2)'", ``caller
> '")
    = local is_marg = inlist("margins", "regress", "", "")
    - local OPTIONS NOADJust BONferroni DUNCAn DUNNett SCHeffe SIDak S
> NK TUKey ADJustall
    - if `is_pwc' {
    = if 0 {
        syntax [name] [, `OPTIONS' MCOMPare(string) *]
    }
    - else {
    - syntax [name] [, MCOMPare(string) *]
    - local suboption mcompare()
    - }
    - sreturn clear
    - sreturn local options ``options'''
    = sreturn local options ``fvwrap(1)'''
    - if `is_pwc' {
    = if 0 {
        local METHOD `noadjust' `bonferroni' `duncan' `dunnett' `scheffe
> ' `sidak' `snk' `tukey'
        local METHOD : list uniq METHOD
        opts_exclusive ``METHOD'''
        local ALL `adjustall'
        opts_exclusive ``noadjust' `ALL'''
    }
    - local 0 `", `mcompare'''
    = local 0 `", noadjust'''
    - capture syntax [, `OPTIONS']
    = capture syntax [, NOADJust BONferroni DUNCAn DUNNett SCHeffe SID
> ak SNK TUKey ADJustall]
    - if c(rc) {
        di as err "invalid mcompare() option;"

```

```

        di as err "method ``mcompare'' not allowed"
        error 198
    }
    - local METHOD `METHOD' `noadjust' `bonferroni' `duncan' `dunnett'
> `scheffe' `sidak' `snk' `tukey'
    = local METHOD noadjust
    - local METHOD : list uniq METHOD
    - local ALL `ALL' `adjustall'
    = local ALL
    - local ALL : list uniq ALL
    - opts_exclusive ``METHOD'' `suboption'
    = opts_exclusive "noadjust" mcompare()

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts noadjust
    - local n 0
    - while ``opts'' != "" {
    = while "noadjust" != "" {
    - local ++n
    - gettoken item`n' opts : opts, bind
    = gettoken item1 opts : opts, bind
    - }
    - while ``opts'' != "" {
    = while `'' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 1 < 2 {
    - exit

> _____ end opts_exclus
> ive _____
    - if ``METHOD'' == "" {
    = if "noadjust" == "" {
        if ``ALL'' != "" {
            di as err "multiple comparison method required with the adjustal
> l option"
        exit 198
    }
    local METHOD noadjust
    local noadjust noadjust

```

```

    }
    - opts_exclusive "`ALL' `noadjust'" `suboption'
    = opts_exclusive " noadjust" mcompare()
  }
}

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts noadjust
    - local n 0
    - while ``opts'" != "" {
    = while ``noadjust'" != "" {
    - local ++n
    - gettoken item`n' opts : opts, bind
    = gettoken item1 opts : opts, bind
    - }
    - while ``opts'" != "" {
    = while `'"'"' != "" {
      local ++n
      gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 1 < 2 {
    - exit
  }
}

> ----- end opts_exclus
> ive -----
    - local EXCLUDE duncan dunnett snk tukey
    - if `:list METHOD in EXCLUDE' {
    = if 0 {
      if `is_pwc' {
        local opt : copy local METHOD
      }
      else {
        local opt "mcompare(`METHOD')"
      }
      local cmdlist anova manova regress mvreg pwmean
      if "`cmd'" == "pwcompare" {
        local cmd ``e(cmd_est)'"
      }
      if `is_marg' {
        local cmd margins
      }
      if !`:list cmd in cmdlist' | !`is_pwc' {
        di as err ``method `opt' is not allowed with results from `cmd'"
      }
    }
  }

```



```

> '
    exit 322
    }
    if ``e(prefix)'' == "svy" {
di as err `"method `opt' is not allowed with results using the s
> vy prefix"
    exit 322
    }
    local vce ``e(vce)''
    if !inlist("`vce'", "", "ols") {
di as err `"method `opt' is not allowed with results using vce(`
> vce')"
    exit 322
    }
    }
    - local EXCLUDE duncan dunnett snk tukey scheffe
    - if `:list METHOD in EXCLUDE' {
= if 0 {
    if ""ALL"" != "" {
di as err `"option adjustall is not allowed with method `METHOD'
> ""
    exit 198
    }
    }
    - sreturn local method ``METHOD''
= sreturn local method "noadjust"
    - sreturn local adjustall ``ALL''
= sreturn local adjustall ""

> _____ end _get_mcomp
> are _____
    - local method ``s(method)''
= local method "noadjust"
    - local all ``s(adjustall)''
= local all ""
    - local options ``s(options)''
= local options "fvwrap(1)"
    - if ""method"" != "noadjust" {
= if "noadjust" != "noadjust" {
    local keepmc 1
    }
    - opts_exclusive ""all' `groups""
= opts_exclusive " "

> _____ begin opts_exclus
> ive _____

```

```

- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> _____ end opts_exclus
> ive _____
- if "`method'" == "dunnett" {
= if "noadjust" == "dunnett" {
    opts_exclusive "`method' `groups'"
}
- _get_diopts diopts options, `options' `fvwrap' `fvlabel'
= _get_diopts diopts options, fvwrap(1)
}

> _____ begin _get_dio
> pts _____
- version 11
- syntax namelist(max=2) [, *]
- gettoken name1 namelist : namelist
- gettoken name2 namelist : namelist
- GetDiopts diopts options, `options'
= GetDiopts diopts options, fvwrap(1)
}

> _____ begin _get_diopts.GetDio
> pts _____
- local DIOPTS Level(cilevel) vsquish NOALLBASElevels ALLBASElev
> els NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EMPTYcell
> s NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cformat(string)
> sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru) FVWRA
> PON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(passthru) NOABB
> REV ABBREV
- syntax namelist(max=2) [, `DIOPTS' *]
= syntax namelist(max=2) [, Level(cilevel) vsquish NOALLBASEleve
> ls ALLBASElevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYce
> lls EMPTYcells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cfo
> rmat(string) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(pa
> ssthru) FVWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(pa

```

```

> ssthru) NOABBREV ABBREV *]
      - opts_exclusive "`allbaselevels' `noallbaselevels'"
      = opts_exclusive " "


---


> 

---

 begin opts_exclus
> ive 

---


      - version 8.2
      - args opts optname errcode optslab
      - local opts `opts'
      = local opts
      - local n 0
      - while ```opts'`` != "" {
      = while `'''' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
      }
      - if `n' < 2 {
      = if 0 < 2 {
      - exit


---


> 

---

 end opts_exclus
> ive 

---


      - opts_exclusive "`allbaselevels' `nobaselevels'"
      = opts_exclusive " "


---


> 

---

 begin opts_exclus
> ive 

---


      - version 8.2
      - args opts optname errcode optslab
      - local opts `opts'
      = local opts
      - local n 0
      - while ```opts'`` != "" {
      = while `'''' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
      }
      - if `n' < 2 {
      = if 0 < 2 {
      - exit


---


> 

---

 end opts_exclus
> ive 

---


      - opts_exclusive "`baselevels' `nobaselevels'"
      = opts_exclusive " "


---



```

```

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`emptycells' `noemptycells'"
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`fvlabel' `nofvlabel'"
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab

```

```

- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
  }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`omitted' `noomitted'"
= opts_exclusive " "
}

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
  }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`lstretch' `nolstretch'"
= opts_exclusive " "
}

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {

```

```

= while `""` != "" {
    local ++n
    gettoken item`n` opts : opts, bind
}
- if `n` < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`cnsreport` `fullcnsreport`"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts`
= local opts
    - local n 0
    - while `""opts`"" != "" {
= while `""` != "" {
    local ++n
    gettoken item`n` opts : opts, bind
}
    - if `n` < 2 {
= if 0 < 2 {
    - exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`coeflegend` `selegend`"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts`
= local opts
    - local n 0
    - while `""opts`"" != "" {
= while `""` != "" {
    local ++n
    gettoken item`n` opts : opts, bind
}

```

```

- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`noci' `nopvalues'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while "`opts'" != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- local K : list sizeof namelist
- gettoken c_diopts c_opts : namelist
- opts_exclusive "`coding' `compare'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while "`opts'" != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {

```

```

        - exit
    _____
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`versus' `compare'"
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`abbrev' `noabbrev'"
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____
> _____ end opts_exclus
> ive _____

```



```

- local allbaselevels `allbaselevels' `noallbaselevels'
= local allbaselevels
- local baselevels `baselevels' `nobaselevels'
= local baselevels
- local emptycells `emptycells' `noemptycells'
= local emptycells
- local omitted `omitted' `noomitted'
= local omitted
- local lstretch `lstretch' `nolstretch'
= local lstretch
- local fvlabel `fvlabel' `nofvlabel'
= local fvlabel
- local abbrev `abbrev' `noabbrev'
= local abbrev
- if "`allbaselevels'`baselevels'" == "" {
= if "" == "" {
- if c(showbaselevels) == "all" {
  local allbaselevels allbaselevels
}
- else if c(showbaselevels) == "on" {
  local baselevels baselevels
}
- }
- if "`emptycells'" == "" {
= if "" == "" {
- if c(showemptycells) == "off" {
  local emptycells noemptycells
}
- }
- if "`omitted'" == "" {
= if "" == "" {
- if c(showomitted) == "off" {
  local omitted noomitted
}
- }
- if "`lstretch'" == "" {
= if "" == "" {
- if c(lstretch) == "off" {
  local lstretch nolstretch
}
- }
- if `:length local cformat' {
= if 0 {
  confirm numeric format `cformat'
  if fmtwidth("`cformat'") > 9 {
    local cformat "%9.0g"
  }
}

```

```

di "{txt}note: invalid cformat(), using default"
}
sreturn local cformat ``cformat''
local cformat `cformat(`cformat')''
}
- if `:length local sformat' {
= if 0 {
confirm numeric format `sformat'
if fmtwidth(`sformat') > 8 {
local sformat "%8.2f"
di "{txt}note: invalid sformat(), using default"
}
sreturn local sformat ``sformat''
local sformat `sformat(`sformat')''
}
- if `:length local pformat' {
= if 0 {
confirm numeric format `pformat'
if fmtwidth(`pformat') > 5 {
local pformat "%5.3f"
di "{txt}note: invalid pformat(), using default"
}
sreturn local pformat ``pformat''
local pformat `pformat(`pformat')''
}
- if `K' == 1 & `:length local options' {
= if 2 == 1 & 0 {
syntax namelist(max=2) [, `DIOPTS']
}
- if reldif(`level', c(level)) > 1e-3 {
= if reldif(95, c(level)) > 1e-3 {
local levelopt level(`level')
}
- Wraapon , `fvwraapon'
= Wraapon ,

```

```

> _____ begin _get_diopts.Wra
> pon _____

```

```

- capture syntax [, W0rd WIdth]
- if c(rc) {
di as err "invalid fvwrapon() option;"
syntax [, W0rd WIdth]
exit 198
}
- opts_exclusive ``word' `width'' fvwrapon
= opts_exclusive " " fvwrapon

```

```

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - local fwwrapon `word' `width'
    = local fwwrapon
    - if `:length local fwwrapon' {
    = if 0 {
        c_local fwwrapon fwwrapon(`fwwrapon')
    }
    _____

> _____ end _get_diopts.Wra
> pon _____
    - if "`fwwrap'" != "" {
    = if "fwwrap(1)" != "" {
    - FWWrap, `fwwrap'
    = FWWrap, fwwrap(1)
    _____

> _____ begin _get_diopts.FWV
> rap _____
    - syntax, fwwrap(integer)
    - if `fwwrap' < 0 {
    = if 1 < 0 {
        di as err "{p}invalid option {bf:fwwrap(`fwwrap')}"; " "nonne
> gative integer required{p_end}"
        exit 198
    }
    _____

> _____ end _get_diopts.FWV
> rap _____
    - }

```

```

- c_local `c_diopts' `levelopt' `vsquish' `allbaselevels' `baselev
> evels' `cnsreport' `fullcnsreport' `emptycells' `omitted' `lstretch' `coefle
> gend' `selegend' `cformat' `sformat' `pformat' `coding' `versus' `compare' `
> fvwrap' `fvwrapon' `fvlabel' `nocl' `nopvalues' `markdown' `citype' `abbrev'
= c_local diopts          fvwrap(1)
- if `K' == 2 {
= if 2 == 2 {
- c_local `c_opts' `""options""
= c_local options `""'
- }
- sreturn local coding `coding'
= sreturn local coding
- sreturn local versus `versus'
= sreturn local versus
- sreturn local compare `compare'
= sreturn local compare
- sreturn local level `level'
= sreturn local level 95
}

> ----- end _get_diopts.GetDio
> pts -----
- c_local `name1' `""diopts""
= c_local diopts `""fvwrap(1)""
- local snames : s(macros)
- foreach sname of local snames {
- local S_`sname' = s(`sname')
= local S_level = s(level)
- }
- local S_`sname' = s(`sname')
= local S_method = s(method)
- }
- local S_`sname' = s(`sname')
= local S_options = s(options)
- }
- sreturn clear
- GetDiopts DEFAULT
}

> ----- begin _get_diopts.GetDio
> pts -----
- local DIOPTS Level(cilevel) vsquish NOALLBASElevels ALLBASElev
> els NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EMPTYcell
> s NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cformat(string)
> sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru) FVWRA
> PON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(passthru) NOABB
> REV ABBREV
- syntax namelist(max=2) [, `DIOPTS' *]

```

```

= syntax namelist(max=2) [, Level(cilevel) vsquish NOALLBASEleve
> ls ALLBASElevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYce
> lls EMPTYcells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cfo
> rmat(string) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(pa
> ssthru) FVWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(pa
> ssthru) NOABBREV ABBREV *]
    - opts_exclusive "'allbaselevels' 'noallbaselevels'"
= opts_exclusive " "
_____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts 'opts'
    = local opts
    - local n 0
    - while "'opts'" != "" {
    = while '""' != "" {
        local ++n
        gettoken item'n' opts : opts, bind
    }
    - if 'n' < 2 {
    = if 0 < 2 {
    - exit
    _____
> _____ end opts_exclus
> ive _____
    - opts_exclusive "'allbaselevels' 'nobaselevels'"
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts 'opts'
    = local opts
    - local n 0
    - while "'opts'" != "" {
    = while '""' != "" {
        local ++n
        gettoken item'n' opts : opts, bind
    }
    - if 'n' < 2 {
    = if 0 < 2 {
    - exit
    _____

```

```

> _____ end opts_exclus
> ive _____
    - opts_exclusive ``baselevels' `nobaselevels'
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - opts_exclusive ``emptycells' `noemptycells'
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - opts_exclusive ``fvlabel' `nofvlabel'
    = opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`omitted' `noomitted'"
    = opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`lstretch' `nolstretch'"
    = opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2

```

```

- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`cnsreport' `fullcnsreport'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`coeflegend' `selegend'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0

```



```

- while ``opts'' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit

```

```

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`nocl' `nopvalues'"
    = opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts'' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

```

```

> ----- end opts_exclus
> ive -----
    - local K : list sizeof namelist
    - gettoken c_diopts c_opts : namelist
    - opts_exclusive "`coding' `compare'"
    = opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts'' != "" {
    = while `"' != "" {

```

```

        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}
}
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`versus' `compare'"
= opts_exclusive " "
}
}
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ```opts'"" != "" {
= while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}
}
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`abbrev' `noabbrev'"
= opts_exclusive " "
}
}
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ```opts'"" != "" {
= while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {

```

```

        = if 0 < 2 {
        - exit
    }
}
> ----- end opts_exclus
> ive -----
    - local allbaselevels `allbaselevels' `noallbaselevels'
    = local allbaselevels
    - local baselevels `baselevels' `nobaselevels'
    = local baselevels
    - local emptycells `emptycells' `noemptycells'
    = local emptycells
    - local omitted `omitted' `noomitted'
    = local omitted
    - local lstretch `lstretch' `nolstretch'
    = local lstretch
    - local fvlabel `fvlabel' `nofvlabel'
    = local fvlabel
    - local abbrev `abbrev' `noabbrev'
    = local abbrev
    - if "`allbaselevels'`baselevels'" == "" {
    = if "" == "" {
    - if c(showbaselevels) == "all" {
      local allbaselevels allbaselevels
    }
    - else if c(showbaselevels) == "on" {
      local baselevels baselevels
    }
    - }
    - if "`emptycells'" == "" {
    = if "" == "" {
    - if c(showemptycells) == "off" {
      local emptycells noemptycells
    }
    - }
    - if "`omitted'" == "" {
    = if "" == "" {
    - if c(showomitted) == "off" {
      local omitted noomitted
    }
    - }
    - if "`lstretch'" == "" {
    = if "" == "" {
    - if c(lstretch) == "off" {
      local lstretch nolstretch
    }
    - }

```

```

- if `:length local cformat' {
= if 0 {
  confirm numeric format `cformat'
  if fmtwidth(`"'cformat'"') > 9 {
    local cformat "%9.0g"
    di "{txt}note: invalid cformat(), using default"
  }
  sreturn local cformat `"'cformat'"'
  local cformat `"cformat(`cformat')"'
}
- if `:length local sformat' {
= if 0 {
  confirm numeric format `sformat'
  if fmtwidth(`"'sformat'"') > 8 {
    local sformat "%8.2f"
    di "{txt}note: invalid sformat(), using default"
  }
  sreturn local sformat `"'sformat'"'
  local sformat `"sformat(`sformat')"'
}
- if `:length local pformat' {
= if 0 {
  confirm numeric format `pformat'
  if fmtwidth(`"'pformat'"') > 5 {
    local pformat "%5.3f"
    di "{txt}note: invalid pformat(), using default"
  }
  sreturn local pformat `"'pformat'"'
  local pformat `"pformat(`pformat')"'
}
- if `K' == 1 & `:length local options' {
= if 1 == 1 & 0 {
  syntax namelist(max=2) [, `DIOPTS']
}
- if reldif(`level', c(level)) > 1e-3 {
= if reldif(95, c(level)) > 1e-3 {
  local levelopt level(`level')
}
- Wraapon , `fvwraapon'
= Wraapon ,

```

> _____ begin _get_diopts.Wra

> pon _____

```

- capture syntax [, W0rd WIdth]
- if c(rc) {
  di as err "invalid fvwraapon() option;"
}

```

```

        syntax [, WOrd WIdth]
        exit 198
    }
    - opts_exclusive "`word' `width'" fvwrapon
= opts_exclusive " " fvwrapon


---


> 

---

 begin opts_exclus
> ive 

---


        - version 8.2
        - args opts optname errcode optslab
        - local opts `opts'
= local opts
        - local n 0
        - while ```opts'"" != "" {
= while `""' != "" {
            local ++n
            gettoken item`n' opts : opts, bind
        }
        - if `n' < 2 {
= if 0 < 2 {
            - exit


---


> 

---

 end opts_exclus
> ive 

---


        - local fvwrapon `word' `width'
= local fvwrapon
        - if `:length local fvwrapon' {
= if 0 {
            c_local fvwrapon fvwrapon(`fvwrapon')
        }


---


> 

---

 end _get_diopts.Wra
> pon 

---


        - if "`fvwrap'" != "" {
= if "" != "" {
            FVWrap, `fvwrap'
        }
        - c_local `c_diopts' `levelopt' `vsquish' `allbaselevels' `basel
> evels' `cnsreport' `fullcnsreport' `emptycells' `omitted' `lstretch' `coefle
> gend' `selegend' `cformat' `sformat' `pformat' `coding' `versus' `compare' `
> fvwrap' `fvwrapon' `fvlabel' `noci' `nopvalues' `markdown' `citype' `abbrev'
= c_local DEFAULT
        - if `K' == 2 {
= if 1 == 2 {
            c_local `c_opts' ```options'""
        }

```

```

        - sreturn local coding `coding'
        = sreturn local coding
        - sreturn local versus `versus'
        = sreturn local versus
        - sreturn local compare `compare'
        = sreturn local compare
        - sreturn local level `level'
        = sreturn local level 95
    }
}

> _____ end _get_diopts.GetDio
> pts _____
    - if ``name2''' == "" {
    = if "options" == "" {
        GetDiopts DUPS, `options'
    }
    - else {
    - GetDiopts DUPS options, `options'
    = GetDiopts DUPS options,
    }

> _____ begin _get_diopts.GetDio
> pts _____
    - local DIOPTS Level(cilevel) vsquish NOALLBASElevels ALLBASElev
> els NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EMPTYcell
> s NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cformat(string)
> sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru) FVWRA
> PON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(passthru) NOABB
> REV ABBREV
    - syntax namelist(max=2) [, `DIOPTS' *]
    = syntax namelist(max=2) [, Level(cilevel) vsquish NOALLBASEleve
> ls ALLBASElevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYce
> lls EMPTYcells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cfo
> rmat(string) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(pa
> ssthru) FVWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(pa
> ssthru) NOABBREV ABBREV *]
    - opts_exclusive "`allbaselevels' `noallbaselevels'"
    = opts_exclusive " "

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts''' != "" {
    = while `''' != "" {

```

```

        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`allbaselevels' `nbaselevels'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ``opts' != "" {
= while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`baselevels' `nbaselevels'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ``opts' != "" {
= while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {

```

```

        = if 0 < 2 {
        - exit
    }
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`emptycells' `noemptycells'"
    = opts_exclusive " "
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    }
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`fvlabel' `nofvlabel'"
    = opts_exclusive " "
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    }
> ----- end opts_exclus

```



```

> ive
- opts_exclusive "`omitted' `noomitted'"
= opts_exclusive " "
-
>
- begin opts_exclus
> ive
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while `"'`opts'" != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
-
>
- end opts_exclus
> ive
- opts_exclusive "`lstretch' `nolstretch'"
= opts_exclusive " "
-
>
- begin opts_exclus
> ive
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while `"'`opts'" != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
-
>
- end opts_exclus
> ive
- opts_exclusive "`cnsreport' `fullcnsreport'"
= opts_exclusive " "

```

```

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
        }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`coeflegend' `selegend'"
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
        }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`noci' `nopvalues'"
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab

```

```

- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- local K : list sizeof namelist
- gettoken c_diopts c_opts : namelist
- opts_exclusive "`coding' `compare'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`versus' `compare'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts

```

```

- local n 0
- while ``opts'' != "" {
= while `'' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`abbrev' `noabbrev'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts'' != "" {
= while `'' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- local allbaselevels `allbaselevels' `noallbaselevels'
= local allbaselevels
- local baselevels `baselevels' `nobaselevels'
= local baselevels
- local emptycells `emptycells' `noemptycells'
= local emptycells
- local omitted `omitted' `noomitted'
= local omitted
- local lstretch `lstretch' `nolstretch'
= local lstretch
- local fvlabel `fvlabel' `nofvlabel'
= local fvlabel
- local abbrev `abbrev' `noabbrev'

```

```

= local abbrev
- if "`allbaselevels'"`baselevels'" == "" {
= if "" == "" {
- if c(showbaselevels) == "all" {
  local allbaselevels allbaselevels
}
- else if c(showbaselevels) == "on" {
  local baselevels baselevels
}
- }
- if "`emptycells'" == "" {
= if "" == "" {
- if c(showemptycells) == "off" {
  local emptycells noemptycells
}
- }
- if "`omitted'" == "" {
= if "" == "" {
- if c(showomitted) == "off" {
  local omitted noomitted
}
- }
- if "`lstretch'" == "" {
= if "" == "" {
- if c(lstretch) == "off" {
  local lstretch nolstretch
}
- }
- if `:length local cformat' {
= if 0 {
  confirm numeric format `cformat'
  if fmtwidth("`cformat'") > 9 {
    local cformat "%9.0g"
    di "{txt}note: invalid cformat(), using default"
  }
  sreturn local cformat "`cformat'"
  local cformat `cformat(`cformat')'
}
- if `:length local sformat' {
= if 0 {
  confirm numeric format `sformat'
  if fmtwidth("`sformat'") > 8 {
    local sformat "%8.2f"
    di "{txt}note: invalid sformat(), using default"
  }
  sreturn local sformat "`sformat'"

```

```

    local sformat `"sformat(`sformat')"'
  }
- if `:length local pformat' {
= if 0 {
  confirm numeric format `pformat'
  if fmtwidth(`"'pformat'"') > 5 {
    local pformat "%5.3f"
    di "{txt}note: invalid pformat(), using default"
  }
  sreturn local pformat `"pformat'"
  local pformat `pformat(`pformat')"'
}
- if `K' == 1 & `:length local options' {
= if 2 == 1 & 0 {
  syntax namelist(max=2) [, `DIOPTS']
}
- if reldif(`level', c(level)) > 1e-3 {
= if reldif(95, c(level)) > 1e-3 {
  local levelopt level(`level')
}
- Wrapon , `fvwrapon'
= Wrapon ,

```

```

> _____ begin _get_diopts.Wra
> pon _____

```

```

- capture syntax [, W0rd WIdth]
- if c(rc) {
  di as err "invalid fvwrapon() option;"
  syntax [, W0rd WIdth]
  exit 198
}
- opts_exclusive "`word' `width'" fvwrapon
= opts_exclusive " " fvwrapon

```

```

> _____ begin opts_exclus
> ive _____

```

```

- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while `"'opts'"' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}

```

```

        - if `n' < 2 {
        = if 0 < 2 {
        - exit
    }
}
> ----- end opts_exclus
> ive -----
    - local fvwrapon `word' `width'
    = local fvwrapon
    - if `:length local fvwrapon' {
    = if 0 {
        c_local fvwrapon fvwrapon(`fvwrapon')
    }
}
> ----- end _get_diopts.Wrap
> pon -----
    - if "`fvwrap'" != "" {
    = if "" != "" {
        FVWrap, `fvwrap'
    }
    - c_local `c_diopts' `levelopt' `vsquish' `allbaselevels' `baselevels'
> evels' `cnsreport' `fullcnsreport' `emptycells' `omitted' `lstretch' `coefle
> gend' `selegend' `cformat' `sformat' `pformat' `coding' `versus' `compare' `
> fvwrap' `fvwrapon' `fvlabel' `nocl' `nopvalues' `markdown' `citype' `abbrev'
    = c_local DUPS
    - if `K' == 2 {
    = if 2 == 2 {
        - c_local `c_opts' ``options'
    = c_local options ``'
        - }
        - sreturn local coding `coding'
    = sreturn local coding
        - sreturn local versus `versus'
    = sreturn local versus
        - sreturn local compare `compare'
    = sreturn local compare
        - sreturn local level `level'
    = sreturn local level 95
}
> ----- end _get_diopts.GetDio
> pts -----
    - c_local `name2' ``options'
    = c_local options ``'
    - }
    - local DUPS : list DUPS - DEFAULT
    - gettoken DUPS : DUPS
    - if ``DUPS' != "" {

```

```

= if `""` != "" {
  if (strpos("`DUPS'", "(")) {
    gettoken DUPS : DUPS, parse("(")
    local DUPS "`DUPS'()"
  }
  di as err "duplicate {bf:`DUPS'} option not allowed"
  exit 198
}
- sreturn clear
- foreach sname of local snames {
- sreturn local `sname' = "`S_`sname'"
= sreturn local level = `95'
- }
- sreturn local `sname' = "`S_`sname'"
= sreturn local method = `noadjust'
- }
- sreturn local `sname' = "`S_`sname'"
= sreturn local options = `fvwrap(1)'
- }

> _____ end _get_dio
> pts _____
- local legend coeflegend selegend
- local legend : list legend & diopts
- local diopts : list diopts - legend
- local lstretch lstretch nolstretch
- local lstretch : list lstretch & diopts
- local diopts : list diopts - lstretch
- local markdown markdown
- local markdown : list markdown & diopts
- local diopts : list diopts - markdown
- _get_diopts ignore, `diopts' `cformat' `sformat' `pformat'
= _get_diopts ignore, fvwrap(1)

> _____ begin _get_dio
> pts _____
- version 11
- syntax namelist(max=2) [, *]
- gettoken name1 namelist : namelist
- gettoken name2 namelist : namelist
- GetDiopts diopts options, `options'
= GetDiopts diopts options, fvwrap(1)

> _____ begin _get_diopts.GetDio
> pts _____
- local DIOPTS Level(cilevel) vsquish NOALLBASElevels ALLBASElev

```



```

> els NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EMPTYcell
> s NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cformat(string)
> sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru) FVWRA
> PON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(passthru) NOABB
> REV ABBREV
    - syntax namelist(max=2) [, `DIOPTS' *]
    = syntax namelist(max=2) [, Level(cilevel) vsquish NOALLBASEleve
> ls ALLBASElevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYce
> lls EMPTYcells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cfo
> rmat(string) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(pa
> ssthru) FVWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(pa
> ssthru) NOABBREV ABBREV *]
    - opts_exclusive "`allbaselevels' `noallbaselevels'"
    = opts_exclusive " "


---


> 

---

 begin opts_exclus
> ive 

---


    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ```opts'`` != "" {
    = while `""' != "" {
      local ++n
      gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit


---


> 

---

 end opts_exclus
> ive 

---


    - opts_exclusive "`allbaselevels' `nobaselevels'"
    = opts_exclusive " "


---


> 

---

 begin opts_exclus
> ive 

---


    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ```opts'`` != "" {
    = while `""' != "" {
      local ++n

```

```

        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`baselevels' `nobaselevels'"
= opts_exclusive " "
}
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ```opts'` != "" {
= while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`emptycells' `noemptycells'"
= opts_exclusive " "
}
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ```opts'` != "" {
= while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {

```

```

- exit
- end opts_exclus
>
> ive
- opts_exclusive "`fvlabel' `nofvlabel'"
= opts_exclusive " "
- begin opts_exclus
>
> ive
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
- end opts_exclus
>
> ive
- opts_exclusive "`omitted' `noomitted'"
= opts_exclusive " "
- begin opts_exclus
>
> ive
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
- end opts_exclus
>
> ive

```

```

- opts_exclusive "`lstretch' `nolstretch'"
= opts_exclusive " "


---


> 

---

 begin opts_exclus
> ive 

---


- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ```opts'` != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit


---


> 

---

 end opts_exclus
> ive 

---


- opts_exclusive "`cnsreport' `fullcnsreport'"
= opts_exclusive " "


---


> 

---

 begin opts_exclus
> ive 

---


- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ```opts'` != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit


---


> 

---

 end opts_exclus
> ive 

---


- opts_exclusive "`coeflegend' `selegend'"
= opts_exclusive " "


---


> 

---

 begin opts_exclus

```

```

> ive
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

>
> end opts_exclus
> ive
    - opts_exclusive "`nocl' `nopvalues'"
    = opts_exclusive " "

>
> begin opts_exclus
> ive
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

>
> end opts_exclus
> ive
    - local K : list sizeof namelist
    - gettoken c_diopts c_opts : namelist
    - opts_exclusive "`coding' `compare'"
    = opts_exclusive " "

>
> begin opts_exclus
> ive
    - version 8.2

```

```

- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while `"'`opts'"' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> _____ end opts_exclus
> ive _____
- opts_exclusive "`versus' `compare'"
= opts_exclusive " "
}

> _____ begin opts_exclus
> ive _____
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while `"'`opts'"' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> _____ end opts_exclus
> ive _____
- opts_exclusive "`abbrev' `noabbrev'"
= opts_exclusive " "
}

> _____ begin opts_exclus
> ive _____
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0

```

```

- while ``opts'' != "" {
= while `'' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit

```

```

> ----- end opts_exclus
> ive -----
    - local allbaselevels `allbaselevels' `noallbaselevels'
    = local allbaselevels
    - local baselevels `baselevels' `nobaselevels'
    = local baselevels
    - local emptycells `emptycells' `noemptycells'
    = local emptycells
    - local omitted `omitted' `noomitted'
    = local omitted
    - local lstretch `lstretch' `nolstretch'
    = local lstretch
    - local fvlabel `fvlabel' `nofvlabel'
    = local fvlabel
    - local abbrev `abbrev' `noabbrev'
    = local abbrev
    - if "`allbaselevels'`baselevels'" == "" {
    = if "" == "" {
    - if c(showbaselevels) == "all" {
        local allbaselevels allbaselevels
    }
    - else if c(showbaselevels) == "on" {
        local baselevels baselevels
    }
    - }
    - if "`emptycells'" == "" {
    = if "" == "" {
    - if c(showemptycells) == "off" {
        local emptycells noemptycells
    }
    - }
    - if "`omitted'" == "" {
    = if "" == "" {
    - if c(showomitted) == "off" {
        local omitted noomitted
    }
    - }

```

```

- if "`lstretch'" == "" {
= if "" == "" {
- if c(lstretch) == "off" {
    local lstretch nolstretch
  }
- }
- if `:length local cformat' {
= if 0 {
    confirm numeric format `cformat'
    if fmtwidth("`cformat'") > 9 {
      local cformat "%9.0g"
      di "{txt}note: invalid cformat(), using default"
    }
    sreturn local cformat "`cformat'"
    local cformat `"cformat(`cformat')"'
  }
- if `:length local sformat' {
= if 0 {
    confirm numeric format `sformat'
    if fmtwidth("`sformat'") > 8 {
      local sformat "%8.2f"
      di "{txt}note: invalid sformat(), using default"
    }
    sreturn local sformat "`sformat'"
    local sformat `"sformat(`sformat')"'
  }
- if `:length local pformat' {
= if 0 {
    confirm numeric format `pformat'
    if fmtwidth("`pformat'") > 5 {
      local pformat "%5.3f"
      di "{txt}note: invalid pformat(), using default"
    }
    sreturn local pformat "`pformat'"
    local pformat `"pformat(`pformat')"'
  }
- if `K' == 1 & `:length local options' {
= if 2 == 1 & 0 {
    syntax namelist(max=2) [, `DIOPTS']
  }
- if reldif(`level', c(level)) > 1e-3 {
= if reldif(95, c(level)) > 1e-3 {
    local levelopt level(`level')
  }
- Wraon , `fvwraon'
= Wraon ,

```



```

> _____ begin _get_diopts.Wra
> pon _____
    - capture syntax [, W0rd WIdth]
    - if c(rc) {
      di as err "invalid fvwrapon() option;"
      syntax [, W0rd WIdth]
      exit 198
    }
    - opts_exclusive "`word' `width'" fvwrapon
= opts_exclusive " " fvwrapon
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ```opts'"" != "" {
= while `""' != "" {
      local ++n
      gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - local fvwrapon `word' `width'
= local fvwrapon
    - if `:length local fvwrapon' {
= if 0 {
      c_local fvwrapon fvwrapon(`fvwrapon')
    }
    _____

> _____ end _get_diopts.Wra
> pon _____
    - if "`fvwrap'" != "" {
= if "fvwrap(1)" != "" {
    - FVWrap, `fvwrap'
= FVWrap, fvwrap(1)
    _____

> _____ begin _get_diopts.FVW
> rap _____

```

```

- syntax, fvwrap(integer)
- if `fvwrap' < 0 {
= if 1 < 0 {
    di as err "{p}invalid option {bf:fvwrap(`fvwrap')}"; " "nonne
> gative integer required{p_end}"
    exit 198
}
}

> _____ end _get_diopts.FVW
> rap _____
- }
- c_local `c_diopts' `levelopt' `vsquish' `allbaselevels' `basel
> evels' `cnsreport' `fullcnsreport' `emptycells' `omitted' `lstretch' `coefle
> gend' `selegend' `cformat' `sformat' `pformat' `coding' `versus' `compare' `
> fvwrap' `fvwrapon' `fvlabel' `noci' `nopvalues' `markdown' `citype' `abbrev'
= c_local diopts fvwrap(1)
- if `K' == 2 {
= if 2 == 2 {
- c_local `c_opts' ``options'''
= c_local options `'''
- }
- sreturn local coding `coding'
= sreturn local coding
- sreturn local versus `versus'
= sreturn local versus
- sreturn local compare `compare'
= sreturn local compare
- sreturn local level `level'
= sreturn local level 95
}

> _____ end _get_diopts.GetDio
> pts _____
- c_local `name1' ``diopts'''
= c_local ignore ``fvwrap(1)'''
- local snames : s(macros)
- foreach sname of local snames {
- local S_`sname' = s(`sname')
= local S_level = s(level)
- }
- local S_`sname' = s(`sname')
= local S_options = s(options)
- }
- local S_`sname' = s(`sname')
= local S_method = s(method)
- }
- sreturn clear

```

- GetDiopts DEFAULT

```
> _____ begin _get_diopts.GetDio
> pts _____
    - local DIOPTS Level(cilevel) vsquish NOALLBASElevels ALLBASElev
> els NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EMPTYcell
> s NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cformat(string)
> sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru) FVWRA
> PON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(passthru) NOABB
> REV ABBREV
    - syntax namelist(max=2) [, `DIOPTS' *]
    = syntax namelist(max=2) [, Level(cilevel) vsquish NOALLBASEleve
> ls ALLBASElevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYce
> lls EMPTYcells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cfo
> rmat(string) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(pa
> ssthru) FVWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(pa
> ssthru) NOABBREV ABBREV *]
    - opts_exclusive "`allbaselevels' `noallbaselevels'"
    = opts_exclusive " "
> _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
> _____
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`allbaselevels' `nobaselevels'"
    = opts_exclusive " "
> _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
```

```

        = local opts
        - local n 0
        - while ``opts'' != "" {
        = while `'' != "" {
            local ++n
            gettoken item`n' opts : opts, bind
        }
        - if `n' < 2 {
        = if 0 < 2 {
        - exit
    }
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive ``baselevels' `nobaselevels'
    = opts_exclusive " "
}

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts'' != "" {
    = while `'' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive ``emptycells' `noemptycells'
    = opts_exclusive " "
}

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts'' != "" {
    = while `'' != "" {

```

```

        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}
}
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`fvlabel' `nofvlabel'"
= opts_exclusive " "
}
}
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ```opts'"" != "" {
= while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}
}
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`omitted' `noomitted'"
= opts_exclusive " "
}
}
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ```opts'"" != "" {
= while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {

```

```

        = if 0 < 2 {
        - exit
    }
> ----- end opts_exclus
> ive -----
    - opts_exclusive "'\lstretch' \nolstretch'"
    = opts_exclusive " "
    -----
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``\opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    }
    -----
> ----- end opts_exclus
> ive -----
    - opts_exclusive "'\cnsreport' \fullcnsreport'"
    = opts_exclusive " "
    -----
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``\opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    }
    -----
> ----- end opts_exclus

```

```

> ive -----
      - opts_exclusive ``coeflegend' `selegend'
      = opts_exclusive " "
-----

> ----- begin opts_exclus
> ive -----
      - version 8.2
      - args opts optname errcode optslab
      - local opts `opts'
      = local opts
      - local n 0
      - while ``opts' != "" {
      = while `'' != "" {
          local ++n
          gettoken item`n' opts : opts, bind
          }
      - if `n' < 2 {
      = if 0 < 2 {
      - exit
-----

> ----- end opts_exclus
> ive -----
      - opts_exclusive ``noci' `nopvalues'
      = opts_exclusive " "
-----

> ----- begin opts_exclus
> ive -----
      - version 8.2
      - args opts optname errcode optslab
      - local opts `opts'
      = local opts
      - local n 0
      - while ``opts' != "" {
      = while `'' != "" {
          local ++n
          gettoken item`n' opts : opts, bind
          }
      - if `n' < 2 {
      = if 0 < 2 {
      - exit
-----

> ----- end opts_exclus
> ive -----
      - local K : list sizeof namelist
      - gettoken c_diopts c_opts : namelist
      - opts_exclusive ``coding' `compare'

```

```

= opts_exclusive " "
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`versus' `compare'"
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`abbrev' `noabbrev'"
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____

```



```

- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- local allbaselevels `allbaselevels' `noallbaselevels'
= local allbaselevels
- local baselevels `baselevels' `nobaselevels'
= local baselevels
- local emptycells `emptycells' `noemptycells'
= local emptycells
- local omitted `omitted' `noomitted'
= local omitted
- local lstretch `lstretch' `nolstretch'
= local lstretch
- local fvlabel `fvlabel' `nofvlabel'
= local fvlabel
- local abbrev `abbrev' `noabbrev'
= local abbrev
- if "`allbaselevels'`baselevels'" == "" {
= if "" == "" {
- if c(showbaselevels) == "all" {
    local allbaselevels allbaselevels
}
- else if c(showbaselevels) == "on" {
    local baselevels baselevels
}
- }
- if "`emptycells'" == "" {
= if "" == "" {
- if c(showemptycells) == "off" {
    local emptycells noemptycells
}
- }
- if "`omitted'" == "" {

```

```

= if "" == "" {
- if c(showomitted) == "off" {
  local omitted noomitted
}
- }
- if "`lstretch'" == "" {
= if "" == "" {
- if c(lstretch) == "off" {
  local lstretch nolstretch
}
- }
- if `:length local cformat' {
= if 0 {
  confirm numeric format `cformat'
  if fmtwidth("`cformat'") > 9 {
    local cformat "%9.0g"
    di "{txt}note: invalid cformat(), using default"
  }
  sreturn local cformat "`cformat'"
  local cformat `cformat(`cformat')'
}
- if `:length local sformat' {
= if 0 {
  confirm numeric format `sformat'
  if fmtwidth("`sformat'") > 8 {
    local sformat "%8.2f"
    di "{txt}note: invalid sformat(), using default"
  }
  sreturn local sformat "`sformat'"
  local sformat `sformat(`sformat')'
}
- if `:length local pformat' {
= if 0 {
  confirm numeric format `pformat'
  if fmtwidth("`pformat'") > 5 {
    local pformat "%5.3f"
    di "{txt}note: invalid pformat(), using default"
  }
  sreturn local pformat "`pformat'"
  local pformat `pformat(`pformat')'
}
- if `K' == 1 & `:length local options' {
= if 1 == 1 & 0 {
  syntax namelist(max=2) [, `DIOPTS']
}
- if reldif(`level', c(level)) > 1e-3 {

```

```

= if reldif(95, c(level)) > 1e-3 {
  local levelopt level(`level')
}
- Wraapon , `fvwraapon'
= Wraapon ,

> _____ begin _get_diopts.Wra
> pon _____
  - capture syntax [, W0rd WIdth]
  - if c(rc) {
    di as err "invalid fvwraapon() option;"
    syntax [, W0rd WIdth]
    exit 198
  }
  - opts_exclusive "`word' `width'" fvwraapon
= opts_exclusive " " fvwraapon

> _____ begin opts_exclus
> ive _____
  - version 8.2
  - args opts optname errcode optslab
  - local opts `opts'
= local opts
  - local n 0
  - while ```opts'"" != "" {
= while `""' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
  }
  - if `n' < 2 {
= if 0 < 2 {
  - exit

> _____ end opts_exclus
> ive _____
  - local fvwraapon `word' `width'
= local fvwraapon
  - if `:length local fvwraapon' {
= if 0 {
    c_local fvwraapon fvwraapon(`fvwraapon')
  }

> _____ end _get_diopts.Wra
> pon _____
  - if "`fvwrap'" != "" {
= if "" != "" {

```

```

        FWWrap, `fvwrap'
    }
    - c_local `c_diopts' `levelopt' `vsquish' `allbaselevels' `basel
> evels' `cnsreport' `fullcnsreport' `emptycells' `omitted' `lstretch' `coefle
> gend' `selegend' `cformat' `sformat' `pformat' `coding' `versus' `compare' `
> fvwrap' `fvwrapon' `fvlabel' `nocl' `nopvalues' `markdown' `citype' `abbrev'
        = c_local DEFAULT
        - if `K' == 2 {
        = if 1 == 2 {
            c_local `c_opts' ``options''
        }
        - sreturn local coding `coding'
        = sreturn local coding
        - sreturn local versus `versus'
        = sreturn local versus
        - sreturn local compare `compare'
        = sreturn local compare
        - sreturn local level `level'
        = sreturn local level 95
    }
}

> _____ end _get_diopts.GetDio
> pts _____
    - if ``name2'' == "" {
    = if ``' == "" {
    - GetDiopts DUPS, `options'
    = GetDiopts DUPS,
    }
}

> _____ begin _get_diopts.GetDio
> pts _____
    - local DIOPTS Level(cilevel) vsquish NOALLBASElevels ALLBASElev
> els NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EMPTYcell
> s NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cformat(string)
> sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru) FVWRA
> PON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(passthru) NOABB
> REV ABBREV
    - syntax namelist(max=2) [, `DIOPTS' *]
    = syntax namelist(max=2) [, Level(cilevel) vsquish NOALLBASEleve
> ls ALLBASElevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYce
> lls EMPTYcells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cfo
> rmat(string) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(pa
> ssthru) FVWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(pa
> ssthru) NOABBREV ABBREV *]
    - opts_exclusive ``allbaselevels' `noallbaselevels''
    = opts_exclusive " "
}

> _____ begin opts_exclus

```

```

> ive
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
      local ++n
      gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

>
> end opts_exclus
> ive
    - opts_exclusive "`allbaselevels' `nbaselevels'"
    = opts_exclusive " "

>
> begin opts_exclus
> ive
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
      local ++n
      gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

>
> end opts_exclus
> ive
    - opts_exclusive "`baselevels' `nbaselevels'"
    = opts_exclusive " "

>
> begin opts_exclus
> ive
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'

```

```

= local opts
- local n 0
- while ``opts'' != "" {
= while `'' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive ``emptycells' `noemptycells'
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
- local n 0
- while ``opts'' != "" {
= while `'' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive ``fvlabel' `nofvlabel'
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
- local n 0
- while ``opts'' != "" {
= while `'' != "" {

```

```

        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}
}
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`omitted' `noomitted'"
= opts_exclusive " "
}
}
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ```opts'"" != "" {
= while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}
}
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`lstretch' `nolstretch'"
= opts_exclusive " "
}
}
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ```opts'"" != "" {
= while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {

```

```

        = if 0 < 2 {
        - exit
    }
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`cnsreport' `fullcnsreport'"
    = opts_exclusive " "
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ```opts'`` != "" {
    = while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    }
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`coeflegend' `selegend'"
    = opts_exclusive " "
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ```opts'`` != "" {
    = while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    }
> ----- end opts_exclus

```



```

> ive -----
      - opts_exclusive "`noci' `nopvalues'"
      = opts_exclusive " "
-----

> ----- begin opts_exclus
> ive -----
      - version 8.2
      - args opts optname errcode optslab
      - local opts `opts'
      = local opts
      - local n 0
      - while ``opts' != "" {
      = while `"' != "" {
          local ++n
          gettoken item`n' opts : opts, bind
        }
      - if `n' < 2 {
      = if 0 < 2 {
      - exit
-----

> ----- end opts_exclus
> ive -----
      - local K : list sizeof namelist
      - gettoken c_diopts c_opts : namelist
      - opts_exclusive "`coding' `compare'"
      = opts_exclusive " "
-----

> ----- begin opts_exclus
> ive -----
      - version 8.2
      - args opts optname errcode optslab
      - local opts `opts'
      = local opts
      - local n 0
      - while ``opts' != "" {
      = while `"' != "" {
          local ++n
          gettoken item`n' opts : opts, bind
        }
      - if `n' < 2 {
      = if 0 < 2 {
      - exit
-----

> ----- end opts_exclus
> ive -----
      - opts_exclusive "`versus' `compare'"

```

```

= opts_exclusive " "
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while `"'opts'"' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`abbrev' `noabbrev'"
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while `"'opts'"' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____
> _____ end opts_exclus
> ive _____
    - local allbaselevels `allbaselevels' `noallbaselevels'
    = local allbaselevels
    - local baselevels `baselevels' `nobaselevels'
    = local baselevels
    - local emptycells `emptycells' `noemptycells'

```

```

= local emptycells
- local omitted `omitted' `noomitted'
= local omitted
- local lstretch `lstretch' `nolstretch'
= local lstretch
- local fvlabel `fvlabel' `nofvlabel'
= local fvlabel
- local abbrev `abbrev' `noabbrev'
= local abbrev
- if "`allbaselevels'`baselevels'" == "" {
= if "" == "" {
- if c(showbaselevels) == "all" {
  local allbaselevels allbaselevels
}
- else if c(showbaselevels) == "on" {
  local baselevels baselevels
}
- }
- if "`emptycells'" == "" {
= if "" == "" {
- if c(showemptycells) == "off" {
  local emptycells noemptycells
}
- }
- if "`omitted'" == "" {
= if "" == "" {
- if c(showomitted) == "off" {
  local omitted noomitted
}
- }
- if "`lstretch'" == "" {
= if "" == "" {
- if c(lstretch) == "off" {
  local lstretch nolstretch
}
- }
- if `:length local cformat' {
= if 0 {
  confirm numeric format `cformat'
  if fmtwidth("`cformat'") > 9 {
    local cformat "%9.0g"
    di "{txt}note: invalid cformat(), using default"
  }
  sreturn local cformat "`cformat'"
  local cformat `cformat(`cformat')'
}
}

```

```

- if `:length local sformat' {
= if 0 {
  confirm numeric format `sformat'
  if fmtwidth(`"'sformat'"') > 8 {
    local sformat "%8.2f"
    di "{txt}note: invalid sformat(), using default"
  }
  sreturn local sformat `"'sformat'"'
  local sformat `"sformat(`sformat')"'
}
- if `:length local pformat' {
= if 0 {
  confirm numeric format `pformat'
  if fmtwidth(`"'pformat'"') > 5 {
    local pformat "%5.3f"
    di "{txt}note: invalid pformat(), using default"
  }
  sreturn local pformat `"'pformat'"'
  local pformat `"pformat(`pformat')"'
}
- if `K' == 1 & `:length local options' {
= if 1 == 1 & 0 {
  syntax namelist(max=2) [, `DIOPTS']
}
- if reldif(`level', c(level)) > 1e-3 {
= if reldif(95, c(level)) > 1e-3 {
  local levelopt level(`level')
}
- Wraapon , `fvwraapon'
= Wraapon ,

```

> _____ begin _get_diopts.Wra

> pon _____

```

- capture syntax [, W0rd WIdth]
- if c(rc) {
  di as err "invalid fvwraapon() option;"
  syntax [, W0rd WIdth]
  exit 198
}
- opts_exclusive "`word' `width'" fvwraapon
= opts_exclusive " " fvwraapon

```

> _____ begin opts_exclus

> ive _____

```

- version 8.2
- args opts optname errcode optslab

```

```

- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> _____ end opts_exclus
> ive _____
- local fwwrapon `word' `width'
= local fwwrapon
- if `:length local fwwrapon' {
= if 0 {
    c_local fwwrapon fwwrapon(`fwwrapon')
}

> _____ end _get_diopts.Wra
> pon _____
- if "`fwwrap'" != "" {
= if "" != "" {
    FWWrap, `fwwrap'
}
- c_local `c_diopts' `levelopt' `vsquish' `allbaselevels' `basel
> evels' `cnsreport' `fullcnsreport' `emptycells' `omitted' `lstretch' `coefle
> gend' `selegend' `cformat' `sformat' `pformat' `coding' `versus' `compare' `
> fwwrap' `fwwrapon' `fvlabel' `nocl' `nopvalues' `markdown' `citype' `abbrev'
= c_local DUPS
- if `K' == 2 {
= if 1 == 2 {
    c_local `c_opts' ``options'
}
- sreturn local coding `coding'
= sreturn local coding
- sreturn local versus `versus'
= sreturn local versus
- sreturn local compare `compare'
= sreturn local compare
- sreturn local level `level'
= sreturn local level 95

> _____ end _get_diopts.GetDio

```

```

> pts
- }
- else {
  GetDiopts DUPS options, `options'
  c_local `name2' ``options'
}
- local DUPS : list DUPS - DEFAULT
- gettoken DUPS : DUPS
- if ``DUPS' != "" {
= if `"' != "" {
  if (strpos(`DUPS', "(")) {
    gettoken DUPS : DUPS, parse("(")
    local DUPS `DUPS'()'
  }
  di as err "duplicate {bf:`DUPS'} option not allowed"
  exit 198
}
- sreturn clear
- foreach sname of local snames {
- sreturn local `sname' = ``S_`sname'
= sreturn local level = `95'
- }
- sreturn local `sname' = ``S_`sname'
= sreturn local options = `fvwrap(1)'
- }
- sreturn local `sname' = ``S_`sname'
= sreturn local method = `noadjust'
- }

> _____ end _get_dio
> pts
- local cformat ``s(cformat)'
= local cformat `"'
- local sformat ``s(sformat)'
= local sformat `"'
- local pformat ``s(pformat)'
= local pformat `"'
- _get_eformopts , eformopts(`options') allowed(__all__) soptions
= _get_eformopts , eformopts() allowed(__all__) soptions

> _____ begin _get_eformo
> pts
- version 8.0
- syntax [, eformopts(string asis) soptions ALLOWed(string) ]
- local 0 , `eformopts'
= local 0 ,

```

```

- local EFALL NOHR hr NOSHR shr or IRr RRr tr TRatio
- if ""options"" != "" {
= if "options" != "" {
- syntax [, EForm1(passthru) EForm `EFALL' * ]
= syntax [, EForm1(passthru) EForm NOHR hr NOSHR shr or IRr RRr tr
> TRatio * ]
- local opts ``options''
= local opts ``''
- local 0 , `eform1' `eform' `nohr' `hr' `noshr' `shr' `or' `irr'
> `rrr' `tr' `tratio'
= local 0 ,
- }
- if ""allowed"" == "__all__" {
= if "__all__" == "__all__" {
- local allowed `EFALL'
= local allowed NOHR hr NOSHR shr or IRr RRr tr TRatio
- }
- foreach ef of local allowed {
- capture confirm name `ef'
= capture confirm name NOHR
- if _rc {
di as err "`ef' is not a valid name"
exit 198
}
- local efopts `efopts' `=lower("`ef'")'
= local efopts nohr
- }
- capture confirm name `ef'
= capture confirm name hr
- if _rc {
di as err "`ef' is not a valid name"
exit 198
}
- local efopts `efopts' `=lower("`ef'")'
= local efopts nohr hr
- }
- capture confirm name `ef'
= capture confirm name NOSHR
- if _rc {
di as err "`ef' is not a valid name"
exit 198
}
- local efopts `efopts' `=lower("`ef'")'
= local efopts nohr hr noshr
- }
- capture confirm name `ef'

```

```

= capture confirm name shr
- if _rc {
  di as err "`ef' is not a valid name"
  exit 198
}
- local efopts `efopts' `=lower("`ef'")'
= local efopts nohr hr noshr shr
- }
- capture confirm name `ef'
= capture confirm name or
- if _rc {
  di as err "`ef' is not a valid name"
  exit 198
}
- local efopts `efopts' `=lower("`ef'")'
= local efopts nohr hr noshr shr or
- }
- capture confirm name `ef'
= capture confirm name IRr
- if _rc {
  di as err "`ef' is not a valid name"
  exit 198
}
- local efopts `efopts' `=lower("`ef'")'
= local efopts nohr hr noshr shr or irr
- }
- capture confirm name `ef'
= capture confirm name RRr
- if _rc {
  di as err "`ef' is not a valid name"
  exit 198
}
- local efopts `efopts' `=lower("`ef'")'
= local efopts nohr hr noshr shr or irr rrr
- }
- capture confirm name `ef'
= capture confirm name tr
- if _rc {
  di as err "`ef' is not a valid name"
  exit 198
}
- local efopts `efopts' `=lower("`ef'")'
= local efopts nohr hr noshr shr or irr rrr tr
- }
- capture confirm name `ef'
= capture confirm name TRatio

```



```

- if _rc {
  di as err "`ef' is not a valid name"
  exit 198
}
- local efopts `efopts' `=lower("`ef'")'
= local efopts nohr hr noshr shr or irr rrr tr tratio
- }
- local efopts : list uniq efopts
- syntax [, EForm1(string) EForm `allowed' ]
= syntax [, EForm1(string) EForm NOHR hr NOSHR shr or IRr RRr tr T

> Ratio ]

- foreach ef of local efopts {
- local eform `eform' ``ef''
= local eform
- }
- local eform `eform' ``ef''
= local eform
- }
- local eform `eform' ``ef''
= local eform
- }
- local eform `eform' ``ef''
= local eform
- }
- local eform `eform' ``ef''
= local eform
- }
- local eform `eform' ``ef''
= local eform
- }
- local eform `eform' ``ef''
= local eform
- }
- local eform `eform' ``ef''
= local eform
- }
- local eform `eform' ``ef''
= local eform
- }
- local eform `eform' ``ef''
= local eform
- }
- if ```eform1'``'=="Odds ratio" {
= if `""'=="Odds ratio" {
  local eform_cons_ti = "Odds"
  local eform_cons_note = "odds ratios"
}
- else if ```eform1'``'=="Haz. ratio" {
= else if `""'=="Haz. ratio" {

```

```

    local eform_cons_ti = "Hazard"
    local eform_cons_note = "hazard ratios"
  }
- else if ``eform1''=="Time ratio" {
= else if ``''=="Time ratio" {
    local eform_cons_ti = "Time"
    local eform_cons_note = "time ratios"
  }
- else if ``eform1''=="IRR" {
= else if ``''=="IRR" {
    local eform_cons_ti = "Inc. rate"
    local eform_cons_note = "incidence-rate ratios"
    local eform_cons_ti2 = "incidence rate"
  }
- else if ``eform1''=="Risk ratio" {
= else if ``''=="Risk ratio" {
    local eform_cons_ti = "Risk"
    local eform_cons_note = "risk ratios"
  }
- else if ``eform1''=="Hlth ratio" {
= else if ``''=="Hlth ratio" {
    local eform_cons_ti = "Health"
    local eform_cons_note = "health ratios"
  }
- local k : list sizeof eform
- if `k' {
= if 0 {
    opts_exclusive ``eform''
    if `:length local eform1' {
      opts_exclusive "eform() `eform'"
    }
  }
- if `k' {
= if 0 {
    if (``eform'=="eform") local eform1 = "exp(b)"
    else if (``eform'=="hr") {
      local eform1 = "Haz. ratio"
      local eform_cons_ti = "Hazard"
      local eform_cons_note = "hazard ratios"
    }
    else if (``eform'=="shr") {
      local eform1 = "SHR"
      local eform_cons_ti = "Subhazard"
      local eform_cons_note = "subhazard ratios"
    }
    else if (``eform'=="tr") {

```

```

local eform1 = "Time ratio"
local eform_cons_ti = "Time"
local eform_cons_note = "time ratios"
}
else if ("`eform'"=="tratio") {
local eform1 = "Time ratio"
local eform_cons_ti = "Time"
local eform_cons_note = "time ratios"
}
else if ("`eform'"=="or") {
local eform1 = "Odds ratio"
if ("`e(cmd)'"=="asclogit" | "`e(cmd)'"=="cmclogit" | "`e(cmd)'"
> == "cmmixlogit" | "`e(cmd)'"=="cmxtmixlogit" ) {
local eform_cons_ti = "Rel. risk"
local eform_cons_note = "relative-risk ratios"
local eform_cons_ti2 = "relative risk"
}
else {
local eform_cons_ti = "Odds"
local eform_cons_note = "odds ratios"
}
}
else if ("`eform'"=="irr") {
local eform1 = "IRR"
local eform_cons_ti = "Inc. rate"
local eform_cons_note = "incidence-rate ratios"
local eform_cons_ti2 = "incidence rate"
}
else if ("`eform'"=="rrr") {
local eform1 = "RRR"
local eform_cons_ti = "Rel. risk"
local eform_cons_note = "relative-risk ratios"
local eform_cons_ti2 = "relative risk"
}
else if ("`eform'"!="nohr") & ("`eform'"!="noshr") {
local eform1 = upper("`eform'")
}
}
- sreturn clear
- sreturn local options ``opts'''
= sreturn local options `'''
- sreturn local opt `eform'
= sreturn local opt
- sreturn local str `eform1'
= sreturn local str
- if ``eform1''' != "" {

```

```

= if `""` != "" {
  sreturn local eform eform("`eform1'")
}
- else sreturn local eform ""
- sreturn local eform_cons_ti `eform_cons_ti'
= sreturn local eform_cons_ti
- sreturn local eform_cons_note `eform_cons_note'
= sreturn local eform_cons_note
- sreturn local eform_cons_ti2 `eform_cons_ti2'
= sreturn local eform_cons_ti2

```

```

> ----- end _get_eformo
> pts -----
- local tr_item = ``s(eform_cons_note)''
= local tr_item = ``''
- if inlist("`bmatrix'", "", "e(b)") & "`e(k_eform)'" == "0" {
= if inlist("", "", "e(b)") & "" == "0" {
  local eform
}
- else local eform ``s(str)''
= else local eform ``''
- local eform_cons_ti ``s(eform_cons_ti)''
= local eform_cons_ti ``''
- local eform_cons_ti2 ``s(eform_cons_ti2)''
= local eform_cons_ti2 ``''
- if (`e(consonly)''!="1" | ``eform_cons_ti'')=="" ) {
= if (""!="1" | ``'')=="" ) {
- local eformdi ``s(str)''
= local eformdi ``''
- }
- else {
  local eformdi ``eform_cons_ti''
  local tr_item = cond(missing("`eform_cons_ti2'"), strlower("`eform_
> m_cons_ti'"), ``eform_cons_ti2'")
}
- local coefttl = cond("`eform'=="", ``coeftitle'', ``eformd
> i'')
= local coefttl = cond(`""=="", `'', `')
- local options ``s(options)''
= local options ``''
- _get_diparmopts, diparmopts(`options') level(`level')
= _get_diparmopts, diparmopts() level(95)

```

```

> ----- begin _get_diparmo
> pts -----
- if _caller() < 8.2 {

```

```

        _get_diparmopts_8 `0'
        exit
    }
- version 9
- local version : di "version " string(_caller()) ":"
- syntax [, diparmopts(string asis) EXECute soptions bottom plus S
> YNTAXonly * ]
- local goptions `options'
= local goptions level(95)
- SpliceGlobals junk , `goptions'
= SpliceGlobals junk , level(95)

> _____ begin _get_diparmopts.SpliceGlob
> als _____
- syntax name(id="macro name" name=c_diparm) [, diparm(string as
> is) Level(cilevel) dof(passthru) syntaxonly ]
- if ```dof`'' == "" & ```e(df_r)`'' != "" {
= if `''` == "" & ``213`'' != "" {
- capture confirm integer number `e(df_r)'
= capture confirm integer number 213
- if !c(rc) {
- local gdof dof(`e(df_r)')
= local gdof dof(213)
- }
- capture
- }
- else local gdof ```dof`''
= else local gdof `''`
- local glevel `level'
= local glevel 95
- local lopt level(`glevel')
= local lopt level(95)
- if (```diparm`'' == "") exit
= if (``'' == "") exit

> _____ end _get_diparmopts.SpliceGlob
> als _____
- local 0 `", `diparmopts`''
= local 0 `", ``
- local diparmopts
- local k 0
- syntax [, diparm(string asis) * ]
- while ```diparm`'' != "" {
= while `''` != "" {
    local ++k
    local single 1

```

```

local after
capture _on_colon_parse `diparm'
if !c(rc) {
    local single 0
    local diparm ``s(before)'''
    local after ``s(after)'''
}
capture
SpliceGlobals diparm , diparm(`diparm') `syntaxonly' `goptions'
local diparm`k' ``diparm'''
local diparmopts ``diparmopts' : `diparm'''
if `single' | ``:list retok after''' == "" {
    local 0 `", `options'''
    syntax [, diparm(string asis) * ]
}
else {
    local diparm ``after'''
}
}
- if ``soptions''' == "" {
= if `''' == "" {
- syntax [, diparm(string asis) ]
- }
- if ("`execute'" == "") {
= if ("" == "") {
- sreturn clear
- sreturn local options ``options'''
= sreturn local options `'''
- sreturn local diparm ``diparmopts'''
= sreturn local diparm `'''
- forval i = 1/`k' {
= forval i = 1/0 {
    sreturn local diparm`i' ``diparm`i'''''
}
- sreturn local k `k'
= sreturn local k 0
- exit

```

> _____ end _get_diparmo

> pts

```

- local NODIPARM : length local nodiparm
- if `NODIPARM' {
= if 8 {
- local options
- }
- local GTOPTS parse(":") bind quotes

```

```

- local k 0
- if !`NODIPARM' {
= if !8 {
  if ``e(diparm)'' != "" {
    local i 0
    local diparm ``e(diparm)''
  }
  else if ``e(diparm1)'' != "" {
    local i 1
    local diparm ``e(diparm1)''
  }
  while `:length local diparm' {
    gettoken diparm rest : diparm, `GTPTS'
    while `:length local rest' {
      local ++k
      local diparm`k' : copy local diparm
      gettoken COLON rest : rest, `GTPTS'
      gettoken diparm rest : rest, `GTPTS'
    }
    local ++k
    local diparm`k' : copy local diparm
    local ++i
    local diparm ``e(diparm`i)''
  }
}
- if `:length local options' {
= if 0 {
  local 0 `", `options''
  syntax [, diparm(string asis) *]
  if `k' & `:length local diparm' {
    local ++k
    local diparm`k' __sep__
  }
  while `:length local diparm' {
    gettoken diparm rest : diparm, `GTPTS'
    while `:length local rest' {
      local ++k
      local diparm`k' : copy local diparm
      gettoken COLON rest : rest, `GTPTS'
      gettoken diparm rest : rest, `GTPTS'
    }
    local ++k
    local diparm`k' : copy local diparm
    local 0 `", `options''
    syntax [, diparm(string asis) *]
  }
}

```

```

    }
    - if "`markdown'" != "" {
= if "" != "" {
    local lsize = c(linesize)
    set linesize 255
    }
    - `vv' mata: _coef_table()
= version 11, missing: mata: _coef_table()
}

> _____ begin _get_dio
> pts _____
    - version 11
    - syntax namelist(max=2) [, *]
    - gettoken name1 namelist : namelist
    - gettoken name2 namelist : namelist
    - GetDiopts diopts options, `options'
= GetDiopts diopts options, fwrap(1)
}

> _____ begin _get_diopts.GetDio
> pts _____
    - local DIOPTS Level(cilevel) vsquish NOALLBASElevels ALLBASElev
> els NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EMPTYcell
> s NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cformat(string)
> sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru) FVWRA
> PON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(passthru) NOABB
> REV ABBREV
    - syntax namelist(max=2) [, `DIOPTS' *]
    = syntax namelist(max=2) [, Level(cilevel) vsquish NOALLBASEleve
> ls ALLBASElevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYce
> lls EMPTYcells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cfo
> rmat(string) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(pa
> ssthru) FVWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(pa
> ssthru) NOABBREV ABBREV *]
    - opts_exclusive "`allbaselevels' `noallbaselevels'"
    = opts_exclusive " "
}

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts'" != "" {
= while `"' != "" {
    local ++n

```



```

        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`allbaselevels' `nbaselevels'"
= opts_exclusive " "
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ```opts'"" != "" {
= while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`baselevels' `nbaselevels'"
= opts_exclusive " "
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ```opts'"" != "" {
= while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {

```

```

        - exit
    _____
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`emptycells' `noemptycells'"
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`fvlabel' `nofvlabel'"
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____
> _____ end opts_exclus
> ive _____

```

```

- opts_exclusive "`omitted' `noomitted'"
= opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while "`opts'" != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit

```

```

> ----- end opts_exclus
> ive -----
- opts_exclusive "`lstretch' `nolstretch'"
= opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while "`opts'" != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit

```

```

> ----- end opts_exclus
> ive -----
- opts_exclusive "`cnsreport' `fullcnsreport'"
= opts_exclusive " "

```

```

> ----- begin opts_exclus

```

```

> ive
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ```opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

>
> end opts_exclus
> ive
    - opts_exclusive "`coeflegend' `selegend'"
    = opts_exclusive " "

>
> begin opts_exclus
> ive
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ```opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

>
> end opts_exclus
> ive
    - opts_exclusive "`noci' `nopvalues'"
    = opts_exclusive " "

>
> begin opts_exclus
> ive
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'

```

```

= local opts
- local n 0
- while ``opts'' != "" {
= while `'' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
    - local K : list sizeof namelist
    - gettoken c_diopts c_opts : namelist
    - opts_exclusive "`coding' `compare'"
    = opts_exclusive " "
}

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts'' != "" {
    = while `'' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
        }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    }

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`versus' `compare'"
    = opts_exclusive " "
}

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0

```

```

- while ``opts'' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`abbrev' `noabbrev'"
= opts_exclusive " "
}

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts'' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- local allbaselevels `allbaselevels' `noallbaselevels'
= local allbaselevels
- local baselevels `baselevels' `nobaselevels'
= local baselevels
- local emptycells `emptycells' `noemptycells'
= local emptycells
- local omitted `omitted' `noomitted'
= local omitted
- local lstretch `lstretch' `nolstretch'
= local lstretch
- local fvlabel `fvlabel' `nofvlabel'
= local fvlabel
- local abbrev `abbrev' `noabbrev'
= local abbrev

```

```

- if "`allbaselevels'"`baselevels'" == "" {
= if "" == "" {
- if c(showbaselevels) == "all" {
  local allbaselevels allbaselevels
}
- else if c(showbaselevels) == "on" {
  local baselevels baselevels
}
- }
- if "`emptycells'" == "" {
= if "" == "" {
- if c(showemptycells) == "off" {
  local emptycells noemptycells
}
- }
- if "`omitted'" == "" {
= if "" == "" {
- if c(showomitted) == "off" {
  local omitted noomitted
}
- }
- if "`lstretch'" == "" {
= if "" == "" {
- if c(lstretch) == "off" {
  local lstretch nolstretch
}
- }
- if `:length local cformat' {
= if 0 {
  confirm numeric format `cformat'
  if fmtwidth("`cformat'") > 9 {
    local cformat "%9.0g"
    di "{txt}note: invalid cformat(), using default"
  }
  sreturn local cformat "`cformat'"
  local cformat `cformat(`cformat')'
}
- if `:length local sformat' {
= if 0 {
  confirm numeric format `sformat'
  if fmtwidth("`sformat'") > 8 {
    local sformat "%8.2f"
    di "{txt}note: invalid sformat(), using default"
  }
  sreturn local sformat "`sformat'"
  local sformat `sformat(`sformat')'
}

```

```

    }
- if `:length local pformat' {
= if 0 {
    confirm numeric format `pformat'
    if fmtwidth(`"'pformat'"') > 5 {
        local pformat "%5.3f"
        di "{txt}note: invalid pformat(), using default"
    }
    sreturn local pformat `"'pformat'"'
    local pformat `"pformat(`pformat')"'
}
- if `K' == 1 & `:length local options' {
= if 2 == 1 & 0 {
    syntax namelist(max=2) [, `DIOPTS']
}
- if reldif(`level', c(level)) > 1e-3 {
= if reldif(95, c(level)) > 1e-3 {
    local levelopt level(`level')
}
- Wraupon , `fvwraupon'
= Wraupon ,

> _____ begin _get_diopts.Wra
> pon _____
    - capture syntax [, W0rd WIdth]
    - if c(rc) {
        di as err "invalid fvwraupon() option;"
        syntax [, W0rd WIdth]
        exit 198
    }
    - opts_exclusive "'word' `width'" fvwraupon
    = opts_exclusive " " fvwraupon

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while `"'opts'"' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {

```



```

        = if 0 < 2 {
        - exit
    }
}
> ----- end opts_exclus
> ive -----
    - local fwwrapon `word' `width'
    = local fwwrapon
    - if `:length local fwwrapon' {
    = if 0 {
        c_local fwwrapon fwwrapon(`fwwrapon')
    }
}
> ----- end _get_diopts.Wra
> pon -----
    - if "`fwwrap'" != "" {
    = if "fwwrap(1)" != "" {
    - FWWrap, `fwwrap'
    = FWWrap, fwwrap(1)
}
> ----- begin _get_diopts.FW
> rap -----
    - syntax, fwwrap(integer)
    - if `fwwrap' < 0 {
    = if 1 < 0 {
        di as err "{p}invalid option {bf:fwwrap(`fwwrap')}"; " "nonne
> gative integer required{p_end}"
        exit 198
    }
}
> ----- end _get_diopts.FW
> rap -----
    - }
    - c_local `c_diopts' `levelopt' `vsquish' `allbaselevels' `basel
> evels' `cnsreport' `fullcnsreport' `emptycells' `omitted' `lstretch' `coefle
> gend' `selegend' `cformat' `sformat' `pformat' `coding' `versus' `compare' `
> fwwrap' `fwwrapon' `fvlabel' `noci' `nopvalues' `markdown' `citype' `abbrev'
    = c_local diopts fwwrap(1)
    - if `K' == 2 {
    = if 2 == 2 {
    - c_local `c_opts' ``options'
    = c_local options `''
    - }
    - sreturn local coding `coding'
    = sreturn local coding
    - sreturn local versus `versus'
    = sreturn local versus

```

```

- sreturn local compare `compare'
= sreturn local compare
- sreturn local level `level'
= sreturn local level 95

```

```

> _____ end _get_diopts.GetDio
> pts _____
- c_local `name1' ``diopts'''
= c_local __00000B ``fvwrap(1)''
- local snames : s(macros)
- foreach sname of local snames {
- local S_`sname' = s(`sname')
= local S_level = s(level)
- }
- local S_`sname' = s(`sname')
= local S_k = s(k)
- }
- sreturn clear
- GetDiopts DEFAULT

```

```

> _____ begin _get_diopts.GetDio
> pts _____
- local DIOPTS Level(cilevel) vsquish NOALLBASElevels ALLBASElev
> els NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EMPTYcell
> s NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cformat(string)
> sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru) FVWRA
> PON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(passthru) NOABB
> REV ABBREV
- syntax namelist(max=2) [, `DIOPTS' *]
= syntax namelist(max=2) [, Level(cilevel) vsquish NOALLBASEleve
> ls ALLBASElevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYce
> lls EMPTYcells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cfo
> rmat(string) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(pa
> ssthru) FVWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(pa
> ssthru) NOABBREV ABBREV *]
- opts_exclusive ``allbaselevels' `noallbaselevels''
= opts_exclusive " "

```

```

> _____ begin opts_exclus
> ive _____
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts''' != "" {

```

```

= while `""` != "" {
    local ++n
    gettoken item`n` opts : opts, bind
}
- if `n` < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`allbaselevels` `nobaselevels`"
= opts_exclusive " "
}

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts`
= local opts
    - local n 0
    - while `""opts`"" != "" {
= while `""` != "" {
    local ++n
    gettoken item`n` opts : opts, bind
}
    - if `n` < 2 {
= if 0 < 2 {
    - exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`baselevels` `nobaselevels`"
= opts_exclusive " "
}

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts`
= local opts
    - local n 0
    - while `""opts`"" != "" {
= while `""` != "" {
    local ++n
    gettoken item`n` opts : opts, bind
}

```

```

- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`emptycells' `noemptycells'"
= opts_exclusive " "
}

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while "`opts'" != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`fvlabel' `nofvlabel'"
= opts_exclusive " "
}

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while "`opts'" != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

```

```

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`omitted' `noomitted'"
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while `""opts'" != "" {
    = while `"" != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`lstretch' `nolstretch'"
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while `""opts'" != "" {
    = while `"" != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`cnsreport' `fullcnsreport'"
    = opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `'' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

> ----- end opts_exclus
> ive -----
    - opts_exclusive ``coeflegend' `selegend'
    = opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `'' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

> ----- end opts_exclus
> ive -----
    - opts_exclusive ``noci' `nopvalues'
    = opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2

```

```

- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- local K : list sizeof namelist
- gettoken c_diopts c_opts : namelist
- opts_exclusive "`coding' `compare'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`versus' `compare'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'

```

```

= local opts
- local n 0
- while ``opts'' != "" {
= while `'' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`abbrev' `noabbrev'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ``opts'' != "" {
= while `'' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
        }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}

> ----- end opts_exclus
> ive -----
    - local allbaselevels `allbaselevels' `noallbaselevels'
= local allbaselevels
    - local baselevels `baselevels' `nobaselevels'
= local baselevels
    - local emptycells `emptycells' `noemptycells'
= local emptycells
    - local omitted `omitted' `noomitted'
= local omitted
    - local lstretch `lstretch' `nolstretch'
= local lstretch
    - local fvlabel `fvlabel' `nofvlabel'
= local fvlabel

```



```

- local abbrev `abbrev' `noabbrev'
= local abbrev
- if "`allbaselevels'`baselevels'" == "" {
= if "" == "" {
- if c(showbaselevels) == "all" {
  local allbaselevels allbaselevels
}
- else if c(showbaselevels) == "on" {
  local baselevels baselevels
}
- }
- if "`emptycells'" == "" {
= if "" == "" {
- if c(showemptycells) == "off" {
  local emptycells noemptycells
}
- }
- if "`omitted'" == "" {
= if "" == "" {
- if c(showomitted) == "off" {
  local omitted noomitted
}
- }
- if "`lstretch'" == "" {
= if "" == "" {
- if c(lstretch) == "off" {
  local lstretch nolstretch
}
- }
- if `:length local cformat' {
= if 0 {
  confirm numeric format `cformat'
  if fmtwidth("`cformat'") > 9 {
    local cformat "%9.0g"
    di "{txt}note: invalid cformat(), using default"
  }
  sreturn local cformat "`cformat'"
  local cformat `cformat(`cformat')'
}
- if `:length local sformat' {
= if 0 {
  confirm numeric format `sformat'
  if fmtwidth("`sformat'") > 8 {
    local sformat "%8.2f"
    di "{txt}note: invalid sformat(), using default"
  }
}

```

```

        sreturn local sformat ``sformat'''
        local sformat `sformat(`sformat')''
    }
- if `:length local pformat' {
= if 0 {
    confirm numeric format `pformat'
    if fmtwidth(`pformat') > 5 {
        local pformat "%5.3f"
        di "{txt}note: invalid pformat(), using default"
    }
    sreturn local pformat ``pformat'''
    local pformat `pformat(`pformat')''
}
- if `K' == 1 & `:length local options' {
= if 1 == 1 & 0 {
    syntax namelist(max=2) [, `DIOPTS']
}
- if reldif(`level', c(level)) > 1e-3 {
= if reldif(95, c(level)) > 1e-3 {
    local levelopt level(`level')
}
- Wrapon , `fvwrapon'
= Wrapon ,

```

> _____ begin _get_diopts.Wra

> pon _____

```

- capture syntax [, W0rd WIdth]
- if c(rc) {
    di as err "invalid fvwrapon() option;"
    syntax [, W0rd WIdth]
    exit 198
}
- opts_exclusive ``word' `width'" fvwrapon
= opts_exclusive " " fvwrapon

```

> _____ begin opts_exclus

> ive _____

```

- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts''' != "" {
= while `''' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
}

```

```

    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
}
> ----- end opts_exclus
> ive -----
    - local fvwrapon `word' `width'
    = local fvwrapon
    - if `:length local fvwrapon' {
    = if 0 {
        c_local fvwrapon fvwrapon(`fvwrapon')
    }
}
> ----- end _get_diopts.Wra
> pon -----
    - if "`fvwrap'" != "" {
    = if "" != "" {
        FWWrap, `fvwrap'
    }
    - c_local `c_diopts' `levelopt' `vsquish' `allbaselevels' `basel
> evels' `cnsreport' `fullcnsreport' `emptycells' `omitted' `lstretch' `coefle
> gend' `selegend' `cformat' `sformat' `pformat' `coding' `versus' `compare' `
> fvwrap' `fvwrapon' `fvlabel' `noci' `nopvalues' `markdown' `citype' `abbrev'
    = c_local DEFAULT
    - if `K' == 2 {
    = if 1 == 2 {
        c_local `c_opts' ``options''
    }
    - sreturn local coding `coding'
    = sreturn local coding
    - sreturn local versus `versus'
    = sreturn local versus
    - sreturn local compare `compare'
    = sreturn local compare
    - sreturn local level `level'
    = sreturn local level 95
}
> ----- end _get_diopts.GetDio
> pts -----
    - if ``name2'' == "" {
    = if ``' == "" {
    - GetDiopts DUPS, `options'
    = GetDiopts DUPS,
}
> ----- begin _get_diopts.GetDio

```

```

> pts -----
      - local DIOPTS Level(cilevel) vsquish NOALLBASElevels ALLBASElev
> els NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EMPTYcell
> s NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cformat(string)
> sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru) FVWRA
> PON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(passthru) NOABB
> REV ABBREV
      - syntax namelist(max=2) [, `DIOPTS' *]
      = syntax namelist(max=2) [, Level(cilevel) vsquish NOALLBASEleve
> ls ALLBASElevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYce
> lls EMPTYcells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cfo
> rmat(string) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(pa
> ssthru) FVWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(pa
> ssthru) NOABBREV ABBREV *]
      - opts_exclusive "`allbaselevels' `noallbaselevels'"
      = opts_exclusive " "
-----
> ----- begin opts_exclus
> ive -----
      - version 8.2
      - args opts optname errcode optslab
      - local opts `opts'
      = local opts
      - local n 0
      - while `""opts"" != "" {
      = while `"" != "" {
        local ++n
        gettoken item`n' opts : opts, bind
      }
      - if `n' < 2 {
      = if 0 < 2 {
      - exit
-----
> ----- end opts_exclus
> ive -----
      - opts_exclusive "`allbaselevels' `nobaselevels'"
      = opts_exclusive " "
-----
> ----- begin opts_exclus
> ive -----
      - version 8.2
      - args opts optname errcode optslab
      - local opts `opts'
      = local opts
      - local n 0
      - while `""opts"" != "" {

```

```

= while `""` != "" {
    local ++n
    gettoken item`n` opts : opts, bind
}
- if `n` < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`baselevels` `nobaselevels`"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts`
= local opts
    - local n 0
    - while `""opts`"" != "" {
= while `""` != "" {
    local ++n
    gettoken item`n` opts : opts, bind
}
    - if `n` < 2 {
= if 0 < 2 {
    - exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`emptycells` `noemptycells`"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts`
= local opts
    - local n 0
    - while `""opts`"" != "" {
= while `""` != "" {
    local ++n
    gettoken item`n` opts : opts, bind
}

```

```

- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`fvlabel' `nofvlabel'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`omitted' `noomitted'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

```

```

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`lstretch' `nolstretch'"
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ```opts'`` != "" {
    = while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`cnsreport' `fullcnsreport'"
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ```opts'`` != "" {
    = while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`coeflegend' `selegend'"
    = opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `'' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`noci' `nopvalues'"
    = opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `'' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

> ----- end opts_exclus
> ive -----
    - local K : list sizeof namelist
    - gettoken c_diopts c_opts : namelist
    - opts_exclusive "`coding' `compare'"
    = opts_exclusive " "

> ----- begin opts_exclus

```



```

> ive
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ```opts'`` != "" {
    = while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

>
> end opts_exclus
> ive
    - opts_exclusive ``versus' `compare'
    = opts_exclusive " "

>
> begin opts_exclus
> ive
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ```opts'`` != "" {
    = while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

>
> end opts_exclus
> ive
    - opts_exclusive ``abbrev' `noabbrev'
    = opts_exclusive " "

>
> begin opts_exclus
> ive
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'

```

```

= local opts
- local n 0
- while ``opts'' != "" {
= while `'' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- local allbaselevels `allbaselevels' `noallbaselevels'
= local allbaselevels
- local baselevels `baselevels' `nobaselevels'
= local baselevels
- local emptycells `emptycells' `noemptycells'
= local emptycells
- local omitted `omitted' `noomitted'
= local omitted
- local lstretch `lstretch' `nolstretch'
= local lstretch
- local fvlabel `fvlabel' `nofvlabel'
= local fvlabel
- local abbrev `abbrev' `noabbrev'
= local abbrev
- if ``allbaselevels'`baselevels' == "" {
= if "" == "" {
- if c(showbaselevels) == "all" {
    local allbaselevels allbaselevels
  }
- else if c(showbaselevels) == "on" {
    local baselevels baselevels
  }
- }
- if ``emptycells' == "" {
= if "" == "" {
- if c(showemptycells) == "off" {
    local emptycells noemptycells
  }
- }
- if ``omitted' == "" {
= if "" == "" {
- if c(showomitted) == "off" {
    local omitted noomitted
  }

```

```

    }
- }
- if "`lstretch'" == "" {
= if "" == "" {
- if c(lstretch) == "off" {
    local lstretch nolstretch
  }
- }
- if `:length local cformat' {
= if 0 {
    confirm numeric format `cformat'
    if fmtwidth("`cformat'") > 9 {
      local cformat "%9.0g"
      di "{txt}note: invalid cformat(), using default"
    }
    sreturn local cformat "`cformat'"
    local cformat `cformat(`cformat')'
  }
- if `:length local sformat' {
= if 0 {
    confirm numeric format `sformat'
    if fmtwidth("`sformat'") > 8 {
      local sformat "%8.2f"
      di "{txt}note: invalid sformat(), using default"
    }
    sreturn local sformat "`sformat'"
    local sformat `sformat(`sformat')'
  }
- if `:length local pformat' {
= if 0 {
    confirm numeric format `pformat'
    if fmtwidth("`pformat'") > 5 {
      local pformat "%5.3f"
      di "{txt}note: invalid pformat(), using default"
    }
    sreturn local pformat "`pformat'"
    local pformat `pformat(`pformat')'
  }
- if `K' == 1 & `:length local options' {
= if 1 == 1 & 0 {
    syntax namelist(max=2) [, `DIOPTS']
  }
- if reldif(`level', c(level)) > 1e-3 {
= if reldif(95, c(level)) > 1e-3 {
    local levelopt level(`level')
  }
}

```

```

- Wraapon , `fvwraapon'
= Wraapon ,

```

```

> ----- begin _get_diopts.Wra
> pon -----
    - capture syntax [, W0rd WIdth]
    - if c(rc) {
        di as err "invalid fvwrapon() option;"
        syntax [, W0rd WIdth]
        exit 198
    }
    - opts_exclusive "`word' `width'" fvwrapon
= opts_exclusive " " fvwrapon

```

```

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ``opts' != "" {
= while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit

```

```

> ----- end opts_exclus
> ive -----
    - local fvwrapon `word' `width'
= local fvwrapon
    - if `:length local fvwrapon' {
= if 0 {
        c_local fvwrapon fvwrapon(`fvwrapon')
    }

```

```

> ----- end _get_diopts.Wra
> pon -----
    - if "`fvwrap'" != "" {
= if "" != "" {
        FVWrap, `fvwrap'
    }
    - c_local `c_diopts' `levelopt' `vsquish' `allbaselevels' `basel

```

```

> evels' `cnsreport' `fullcnsreport' `emptycells' `omitted' `lstretch' `coefle
> gend' `selegend' `cformat' `sformat' `pformat' `coding' `versus' `compare' `
> fvwrap' `fvwrapon' `fvlabel' `nocl' `nopvalues' `markdown' `citype' `abbrev'
    = c_local DUPS
    - if `K' == 2 {
    = if 1 == 2 {
        c_local `c_opts' ``options''
    }
    - sreturn local coding `coding'
    = sreturn local coding
    - sreturn local versus `versus'
    = sreturn local versus
    - sreturn local compare `compare'
    = sreturn local compare
    - sreturn local level `level'
    = sreturn local level 95
    _____
> _____ end _get_diopts.GetDio
> pts _____
    - }
    - else {
        GetDiopts DUPS options, `options'
        c_local `name2' ``options''
    }
    - local DUPS : list DUPS - DEFAULT
    - gettoken DUPS : DUPS
    - if ``DUPS'' != "" {
    = if `'' != "" {
        if (strpos(`DUPS', "(")) {
            gettoken DUPS : DUPS, parse("(")
            local DUPS `DUPS'()'
        }
        di as err "duplicate {bf:`DUPS'} option not allowed"
        exit 198
    }
    - sreturn clear
    - foreach sname of local snames {
    - sreturn local `sname' = ``S_`sname''
    = sreturn local level = `95'
    - }
    - sreturn local `sname' = ``S_`sname''
    = sreturn local k = `0'
    - }
    _____
> _____ end _get_dio
> pts _____

```

```

- if "`markdown'" != "" {
= if "" != "" {
    set linesize `lsize'
}
- if "`eqselect'" == "" & "`eformnote'" != "noeformnote" {
= if "" == "" & "" != "noeformnote" {
- if ``"eformdi"" != "" & ("`e(cmd)'" != "gnbreg" | "`e(prefix)'" == "svy
> ") {
= if ``"" != "" & ("regress" != "gnbreg" | "" == "svy") {
    local k_eform `r(k_eform)'
    if ("`k_eform'" == "") {
        local k_eform = 1
    }
    local k_eq `e(k_eq)'
    if ("`k_eq'" == "") {
        local k_eq = 1
    }
    if (`k_eform' < `k_eq' & `k_eform') {
        if ("`e(cmd2)'" == "stintreg" | "`e(cmd2)'" == "streg") & ("`e(cmd
> )" == "weibull" | "`e(cmd)'" == "gompertz") {
        }
        else {
            _eform_multeq_note efnote : `k_eform' ``tr_item'''
            di as txt "`efnote'"
        }
    }
}
- if (``"eformdi"" != "" & "`e(noconstant)'" == "0" & ``"eform_cons_ti'
> "" != "" & "`e(consonly)'" != "1") {
    = if (``"" != "" & "" == "0" & ``"" != "" & "" != "1") {
        if ("`e(cmd)'" == "asclogit" | "`e(cmd)'" == "cmclogit" | "`e(cmd)'" ==
> "cmmixlogit" | "`e(cmd)'" == "cmxtmixlogit" ) {
            local asvar = ``"e(ranvars)'"`e(fixvars)'"`e(indvars)'" != ""
            if ``"e(casevars)'" != "" & `asvar' {
                local note1 "Exponentiated coefficients represent odds ratios for
> "
                local note2 "alternative-specific variables (first equation) and "
                local note3 "{help j_cmrisk##|_new:relative-risk ratios} "
                local note4 "for case-specific variables."
                di as txt "{p 0 6 2}Note: `note1'`note2'`note3'`note4'{p_end}"
            }
        }
        if "`eform_cons_ti'" == "Inc. rate" {
            local eform_cons_note "incidence rate"
        }
        else if "`eform_cons_ti'" == "Rel. risk" {

```

```

        local eform_cons_note "relative risk"
    }
    else if "`eform_cons_ti'" == "Health" {
        local eform_cons_note "health (probability of no disease)"
    }
    else {
        local eform_cons_note = strlower("`eform_cons_ti'")
    }
    local eform_cons_note "baseline `eform_cons_note'"
    if ("`e(cmd2)'"=="") {
        local cmd `e(cmd)'
    }
    else {
        local cmd `e(cmd2)'
    }
    local f2 = udsustr("`cmd'",1,2)
    local is_re = ("`f2'"=="xt" | "`f2'"=="me")
    if `is_re' {
        local extranote " (conditional on zero random effects)"
    }
    di as txt "{p 0 6 2}Note: {bf:_cons} estimates " "`eform_cons_note
> ``extranote'" _c
        if ("`e(cmd)'"=="mlogit" | "`e(cmd)'"=="asclogit" | "`e(cmd)'"=="c
> mclogit" | "`e(cmd)'"=="cmmixlogit" | "`e(cmd)'"=="cmxtmixlogit" ) {
        di as txt " for each outcome" _c
    }
    di as txt ".{p_end}"
    }
- }
- return add
- if !`keepmc' {
= if !0 {
- return local mcmethod
- return local mctitle
- }

_____  

> _____ end _coef_ta  

> ble _____  

_____  

> _____ end _ereturn_disp  

> lay _____
- mat `b2' = e(b)
= mat __000007 = e(b)
- drop `xb'
= drop __000004
- _predict double `xb' `if'

```

```

= _predict double __000004 if __000000
- LikePois `y' `xb'`poff' [`weight'`exp'] `if', n(`nobs')
= LikePois y_timing_max __000004 [] if __000000, n(__000002)

> _____ begin poisson.LikeP
> ois _____
- gettoken y 0 : 0
- gettoken xb 0 : 0
- syntax [fw aw pw iw] [if] , Nobs(string)
- if "`weight'"!=" " {
= if ""!=" " {
  if "`weight'"=="fweight" {
    local wt `[fw`exp']"
  }
  else if "`weight'"=="iweight" {
    local wt `[iw`exp']"
  }
  else local wt `[aw`exp']"
}
- tempvar lnf
- qui gen double `lnf' = `y'*(`xb')-exp(`xb')-lngamma(`y'+1) `if'
= qui gen double __00000B = y_timing_max*(__000004)-exp(__000004)-lnga
> mma(y_timing_max+1) if __000000
- summarize `lnf' `wt' `if', meanonly
= summarize __00000B if __000000, meanonly
- if r(N) != `nobs' { exit }
= if r(N) != __000002 { exit }
- if "`weight'"=="aweight" {
= if ""=="aweight" {
  ret scalar lnf = r(N)*r(mean)
}
- else ret scalar lnf = r(sum)

> _____ end poisson.LikeP
> ois _____
- tempname lnf2
- scalar `lnf2' = r(lnf)
= scalar __00000B = r(lnf)
- }
- if _rc { local lnf2 . }
- if `lnf1'>=. & `lnf1c'>=. & `lnf2'>=. { exit }
= if __000008>=. & __00000A>=. & __00000B>=. { exit }
- if `lnf2'<.&(`lnf2'>`lnf1'|`lnf1'>=.)&(`lnf2'>`lnf1c'|`lnf1c'>=.) {
= if __00000B<.&(__00000B>__000008|__000008>=.)&(__00000B>__00000A|__000
> 00A>=.) {
- ret matrix b0 `b2'

```



```

        = ret matrix b0 __000007
        - exit
    }
}
end poisson.Ip
ois
- if "`r(b0)'"!="" {
= if "matrix"!=" " {
- tempname from
- mat `from' = r(b0)
= mat __000004 = r(b0)
- }
- }
- if "`from'"!="" {
= if "__000004"!=" " {
- local initopt `"init(`from') search(off)'"
= local initopt `"init(__000004) search(off)'"
- }
- else local initopt "search(on) maxfeas(50)"
- `vv' ml model `mm' `eval' (`yname': `y' = `xvars', `constan' `offopt') [
> `weight'`exp'] if `touse', collinear missing max nooutput nopreserve `mlopts
> ' title(Poisson regression) `scopt' `robust' `clopt' `initopt' `ll0' `negh'
> `moptobj'
= version 18.5, missing: ml model e2 poiss_lf (y_timing_max: y_timing_max
> = rule_g rule_itr estimated, ) [] if __000000, collinear missing max nooutp
> ut nopreserve nolog vce(robust) title(Poisson regression) init(_
> _000004) search(off) lf0(1 -420.2971615663282) negh
}
}
begin
ml
- if _caller()>=11 {
- mopt `0'
= mopt model e2 poiss_lf (y_timing_max: y_timing_max = rule_g rule_itr e
> stimated, ) [] if __000000, collinear missing max nooutput nopreserve nolog
> vce(robust) title(Poisson regression) init(__000004) search(off
> ) lf0(1 -420.2971615663282) negh
}
}
begin m
opt
- local vv : di "version " string(_caller()) ":"
- version 12
- gettoken subcmd 0 : 0, parse(" ,")
- local lcmd : length local subcmd
- if "`subcmd'" == "clear" {
= if "model" == "clear" {
Clear
exit
}
}
}

```

```

}
- if ``subcmd`` == "hold" {
= if "model" == "hold" {
  ml_hold `0'
  exit
}
- if ``subcmd`` == "unhold" {
= if "model" == "unhold" {
  ml_unhold `0'
  exit
}
- if "subcmd" == "score" {
= if "model" == "score" {
  if _caller() > 12 {
    `vv' Score `0'
  }
  else {
    Score `0'
  }
  exit
}
- if "subcmd" == "count" {
= if "model" == "count" {
  Count `0'
  exit
}
- if "subcmd" == "trace" {
= if "model" == "trace" {
  Trace `0'
  exit
}
- if "subcmd" == bsubstr("graph",1,max(2,`lcmd')) {
= if "model" == bsubstr("graph",1,max(2,5)) {
  Graph `0'
  exit
}
- if "subcmd" == "init" {
= if "model" == "init" {
  Interactive 0
  `vv' Init `0'
  exit
}
- if "subcmd" == bsubstr("maximize",1,max(3,`lcmd')) {
= if "model" == bsubstr("maximize",1,max(3,5)) {
  Interactive 1
  `vv' MaxMin maximize `0'

```

```

        exit
    }
    - if "`subcmd'" == bsubstr("minimize",1,max(3,`lcmd')) {
    = if "model" == bsubstr("minimize",1,max(3,5)) {
        Interactive 1
        `vv' MaxMin minimize `0'
        exit
    }
    - if "`subcmd'" == bsubstr("display",1,max(2,`lcmd')) {
    = if "model" == bsubstr("display",1,max(2,5)) {
        Display `0'
        exit
    }
    - if "`subcmd'" == bsubstr("footnote",1,max(4,`lcmd')) {
    = if "model" == bsubstr("footnote",1,max(4,5)) {
        ml_footnote `0'
        exit
    }
    - if "`subcmd'" == "," {
    = if "model" == "," {
        Display, `0'
        exit
    }
    - if "`subcmd'" == bsubstr("model",1,max(3,`lcmd')) {
    = if "model" == bsubstr("model",1,max(3,5)) {
        - `vv' capture noi Model `0'
        = version 18.5: capture noi Model e2 poiss_lf (y_timing_max: y_timing
> _max = rule_g rule_itr estimated, ) [] if __000000, collinear missing max n
> ooutput nopreserve nolog vce(robust) title(Poisson regression) i
> nit(__000004) search(off) lf0(1 -420.2971615663282) negh

> _____ begin mopt.Mo
> del _____
        - local version = string(_caller())
        - local vv : di "version `version':"
        = local vv : di "version 18.5:"
        - version 12
        - syntax anything(id="model" name=spec) [if] [in] [fw aw pw iw] [, B
> RACKET COLLinear MISSing CONTinue lf0(string) INIT(string) CONSTraints(strin
> g) noCNSNOTes VCE(passthru) NEGh NOPREserve TECHnique(string) ITERID(string)
> CRITtype(string) OBS(numlist max=1 >0) TITle(string) WALDtest(integer -1) S
> VY SUBpop(string) SRSsubpop noSVYadjust SCore(passthru) noOUTput noSCVARS GR
> OUP(varname) ITERPROLOG(string) DERIVPROLOG(string) DERIVH(string) DERIVSCAL
> E(string) DERIV(string) nrderiv GNWMATrix(string) KAUXiliary(numlist int >=0
> ) MAXimize MINimize USERinfo(namelist) PUPDATED Robust CLuster(passthru) mop
> tobj(string) USEVIEWS * ]

```

```

- if ``moptobj''' == "" {
= if `''' == "" {
- Clear

```

```

> ----- begin mopt.Cl
> ear
    - syntax [, NOTANOPTION]
    - capture drop $ML_w
    = capture drop
    - capture drop $ML_samp
    = capture drop
    - capture drop $ML_sample
    = capture drop
    - capture drop $ML_subv
    = capture drop
    - capture drop $ML_grp
    = capture drop
    - mata: Mopt_drop_external()
    - macro drop ML_*

```

```

> ----- end mopt.Cl
> ear
    - }
    - local maxmin `minimize' `maximize'
    = local maxmin maximize
    - opts_exclusive ``maxmin''
    = opts_exclusive "maximize"

```

```

> ----- begin opts_exclus
> ive
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts maximize
    - local n 0
    - while ``opts''' != "" {
    = while ``maximize'' != "" {
    - local ++n
    - gettoken item`n' opts : opts, bind
    = gettoken item1 opts : opts, bind
    - }
    - while ``opts''' != "" {
    = while `''' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }

```

```

- if `n' < 2 {
= if 1 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- if `:length local maxmin' {
= if 8 {
- local interactive 0
- }
- else local interactive 1
- _get_diparmopts, diparmopts(`options') options syntaxonly
= _get_diparmopts, diparmopts(nolog search(off)) options syntaxonly
}

> ----- begin _get_diparmo
> pts -----
- if _caller() < 8.2 {
  _get_diparmopts_8 `0'
  exit
}
- version 9
- local version : di "version " string(_caller()) ":"
- syntax [, diparmopts(string asis) EXECute soptions bottom plus S
> YNTAXonly * ]
- local goptions `options'
= local goptions
- SpliceGlobals junk , `goptions'
= SpliceGlobals junk ,
}

> ----- begin _get_diparmopts.SpliceGlob
> als -----
- syntax name(id="macro name" name=c_diparm) [, diparm(string as
> is) Level(cilevel) dof(passthru) syntaxonly ]
- if ``dof''' == "" & ``e(df_r)''' != "" {
= if `''' == "" & `213''' != "" {
- capture confirm integer number `e(df_r)'
= capture confirm integer number 213
- if !c(rc) {
- local gdof dof(`e(df_r)')
= local gdof dof(213)
- }
- capture
- }
- else local gdof ``dof'''
= else local gdof `'''
- local glevel `level'

```

```

= local glevel 95
- local lopt level(`glevel')
= local lopt level(95)
- if (`"diparm"' == "") exit
= if (`"' == "") exit

> _____ end _get_diparmopts.SpliceGlob
> als _____
- local 0 `", `diparmopts'""
= local 0 `", nolog search(off)""
- local diparmopts
- local k 0
- syntax [, diparm(string asis) * ]
- while `"diparm"' != "" {
= while `"' != "" {
  local ++k
  local single 1
  local after
  capture _on_colon_parse `diparm'
  if !c(rc) {
    local single 0
    local diparm `"'s(before)'"
    local after `"'s(after)'"
  }
  capture
  SpliceGlobals diparm , diparm(`diparm') `syntaxononly' `goptions'
  local diparm`k' `"'diparm'"
  local diparmopts `"'diparmopts' : `diparm'"
  if `single' | `"' :list retok after'" == "" {
    local 0 `", `options'""
    syntax [, diparm(string asis) * ]
  }
  else {
    local diparm `"'after'"
  }
}
- if `"'soptions'" == "" {
= if `"soptions" == "" {
  syntax [, diparm(string asis) ]
}
- if (`execute' == "") {
= if ("" == "") {
- sreturn clear
- sreturn local options `"'options'"
= sreturn local options `"nolog search(off)""
- sreturn local diparm `"'diparmopts'"

```

```

= sreturn local diparm `""'
- forval i = 1/`k' {
= forval i = 1/0 {
    sreturn local diparm`i' ``diparm`i'""
  }
- sreturn local k `k'
= sreturn local k 0
- exit

```

```
> _____ end _get_diparmo
```

```
> pts _____
- forval k = 1/`s(k)' {
= forval k = 1/0 {
    local diparm`k' ``s(diparm`k')""
  }
- local ndiparm `s(k)'
= local ndiparm 0
- local options ``s(options)""
= local options ``nolog search(off)""
- if `interactive' & `:length local options' {
= if 0 & 17 {
    local 0 , `options'
    syntax [, NOTANOPTION]
  }
- if `:length local nopreserve' | `:length local score' {
= if 10 | 0 {
- global ML_preserve no
- }
- else global ML_preserve yes
- gettoken evaltype spec : spec
- confirm name `evaltype'
= confirm name e2
- gettoken evaluator spec : spec
- global ML_evaltype : copy local evaltype
- if `:length local srssubpop' {
= if 0 {
    local 0 , srssubpop
    syntax [, NONOPTION]
    exit 198
  }
- if `:length local subpop' {
= if 0 {
    local svy svy
  }
- if `:length local svy' {
= if 0 {

```

```

opts_exclusive "`vce' `svy'" vce
if `:length local weight' {
di as err "svy option not allowed with weights"
exit 198
}
global ML_noadj : copy local svyadjust
}
- global ML_svy : copy local svy
- if _caller() >= 15 & c(userversion) >= 15 {
- local fparm "", freeparm"
- }
- local eqspec : copy local spec
- local ieq 0
- while `:length local eqspec' {
= while 63 {
- local ++ieq
- gettoken eq eqspec : eqspec, bind
- if bsubstr(trim("`eq'"),1,1) == "/" {
= if bsubstr(trim("(y_timing_max: y_timing_max = rule_g rule_itr est
> imated, )"),1,1) == "/" {
local eq = bsubstr(trim("`eq'"),2,.)
local spec : subinstr local spec "/"`eq'" "("("`eq'":`fparm')"'', wor
> d
}
- else {
- gettoken p1 p2 : eq, parse("(")
- local p2 = trim("`p2'")
= local p2 = trim("`y_timing_max: y_timing_max = rule_g rule_itr est
> imated, )'")
- if bsubstr("`p2'",1,1) == "," {
= if bsubstr("y_timing_max: y_timing_max = rule_g rule_itr estimated
> , )",1,1) == "," {
gettoken comma p2 : p2, parse(",")
local p2 = trim("`p2'")
}
- if "`p1'`p2'" == "(" {
= if `(y_timing_max: y_timing_max = rule_g rule_itr estimated, )"'
> == "(" {
local spec : subinstr local spec "`eq'" "(eq`ieq':)", word
}
- }
- }
- while `:length local eqspec' {
= while 3 {
- local ++ieq
- gettoken eq eqspec : eqspec, bind

```



```

- if bsubstr(trim("`eq'"),1,1) == "/" {
= if bsubstr(trim("[]"),1,1) == "/" {
  local eq = bsubstr(trim("`eq'"),2,.)
  local spec : subinstr local spec "/"`eq' "(`eq':`fparm')", wor
> d
  }
- else {
- gettoken p1 p2 : eq, parse("(")
- local p2 = trim("`p2'")
= local p2 = trim('')
- if bsubstr("`p2'",1,1) == "," {
= if bsubstr("",1,1) == "," {
  gettoken comma p2 : p2, parse(",")
  local p2 = trim("`p2'")
  }
- if "`p1'`p2'" == "()" {
= if "`[]" == "()" {
  local spec : subinstr local spec "`eq' "(eq`ieq:)", word
  }
- }
- }
- while `:length local eqspec' {
= while 0 {
  local ++ieq
  gettoken eq eqspec : eqspec, bind
  if bsubstr(trim("`eq'"),1,1) == "/" {
    local eq = bsubstr(trim("`eq'"),2,.)
    local spec : subinstr local spec "/"`eq' "(`eq':`fparm')", wor
> d
  }
  else {
    gettoken p1 p2 : eq, parse("(")
    local p2 = trim("`p2'")
    if bsubstr("`p2'",1,1) == "," {
      gettoken comma p2 : p2, parse(",")
      local p2 = trim("`p2'")
    }
    if "`p1'`p2'" == "()" {
      local spec : subinstr local spec "`eq' "(eq`ieq:)", word
    }
  }
- if `interactive' {
= if 0 {
  SetGlobalVar ML_sample : _MLtua
}

```

```

- else {
- global ML_sample : tempvar
- if ``moptobj''' != "" {
= if `''' != "" {
    global ML_sample `moptobj'$ML_sample
    }
- }
- if ``moptobj''' != "" {
= if `''' != "" {
    cap drop $ML_sample
    }
- `vv' mark $ML_sample `if' `in' [`weight'`exp'], `zeroweight'
= version 18.5: mark __000005 if __000000 [],
- tempname eqlist
- `eqlist' = _eqlist.new, eqopts(NOCONSTant FREEParam) eqargopts(OF
> Fset EXPosure) noneedvarlist numdepvars(0) needequal
    = __000006 = _eqlist.new, eqopts(NOCONSTant FREEParam) eqargopts(OF
> Fset EXPosure) noneedvarlist numdepvars(0) needequal
    -class {
    -instance:
    -      array          n_depvars
    -      string          needequal
    -      string          noneedvarlist
    -      string          wtypes
    -      string          collinear
    -      string          nocons
    -      string          nocons_ignore
    -      double          n_eq
    -      string          gl_if
    -      string          gl_in
    -      string          gl_wgt
    -      string          gl_options
    -      _optlist         eq_opts_allowed
    -class {
    -instance:
    -      array options    = {}
    -      array names      = {}
    -}
    -      array          eq_list
    -      _optlist       mark_opts
    -      array          mark_list
    -      array          mark_name
    -      _optlist       smark_opts
    -      array          smark_list
    -      array          smark_name
    -      _optlist       rmcoll_opts

```

```

-      array      rmcoll_list
-      array      rmcoll_name
-      _optlist    rmdcoll_opts
-      array      rmdcoll_list
-      array      rmdcoll_name
-}

```

```

> ----- begin _eqlist.
> new -----
- version 9.2
- ._init

```

```

> ----- begin _eqlist._i
> nit -----
- version 9.2
- .n_eq = 0
- .gl_if = ""
- .gl_in = ""
- .gl_wgt = ""
- .gl_options = ""
- .eq_list = {}

```

```

> ----- end _eqlist._i
> nit -----
- ._setup `0'
  = ._setup , eqopts(NOCONSTant FREEParam) eqargopts(OFFset EXPosure)
> noneedvarlist numdepvars(0) needequal

```

```

> ----- begin _eqlist._se
> tup -----
- version 9.2
- .mark_list = {}
- .mark_name = {}
- .mark_opts.reset

```

```

> ----- begin _optlist.re
> set -----
- version 9
- .options = {}
- .names = {}

```

```

> ----- end _optlist.re
> set -----
- .smark_list = {}
- .smark_name = {}
- .smark_opts.reset

```

```

> _____ begin _optlist.re
> set _____
      - version 9
      - .options = {}
      - .names = {}
      _____

> _____ end _optlist.re
> set _____
      - .rmcoll_list = {}
      - .rmcoll_name = {}
      - .rmcoll_opts.reset
      _____

> _____ begin _optlist.re
> set _____
      - version 9
      - .options = {}
      - .names = {}
      _____

> _____ end _optlist.re
> set _____
      - .rmdcoll_list = {}
      - .rmdcoll_name = {}
      - .rmdcoll_opts.reset
      _____

> _____ begin _optlist.re
> set _____
      - version 9
      - .options = {}
      - .names = {}
      _____

> _____ end _optlist.re
> set _____
      - syntax [, EQopts(namelist) EQARGopts(namelist) noNEEDVARLIST C
> OMMONopts(string asis) MARKopts(namelist) SMARKopts(namelist) RMCOLLOpts(nam
> elist) RMDCOLLOpts(namelist) NUMDEPvars(numlist integer >=0) NEEDEQUAL WTYPE
> S(string) IGNORENOCONS ]
      - .eq_opts_allowed.reset
      _____

> _____ begin _optlist.re
> set _____
      - version 9
      - .options = {}
      - .names = {}
      _____

> _____ end _optlist.re

```

```

> set -----
    - foreach opt of local eqopts {
    - .eq_opts_allowed.addopt `opt'
    = .eq_opts_allowed.addopt NOCONSTant
    -----

> ----- begin _optlist.add
> opt -----
    - version 9
    - syntax name(name=optspec) [, PASSthru]
    - local mname = lower("`optspec'")
    = local mname = lower("NOCONSTant")
    - if "`passthru'" != "" {
    = if "" != "" {
      local optspec `optspec'(passthru)
    }
    - .options.Arrpush "`optspec'"
    = .options.Arrpush "NOCONSTant"
    - .names.Arrpush "`mname'"
    = .names.Arrpush "noconstant"
    -----

> ----- end _optlist.add
> opt -----
    - }
    - .eq_opts_allowed.addopt `opt'
    = .eq_opts_allowed.addopt FREEParam
    -----

> ----- begin _optlist.add
> opt -----
    - version 9
    - syntax name(name=optspec) [, PASSthru]
    - local mname = lower("`optspec'")
    = local mname = lower("FREEParam")
    - if "`passthru'" != "" {
    = if "" != "" {
      local optspec `optspec'(passthru)
    }
    - .options.Arrpush "`optspec'"
    = .options.Arrpush "FREEParam"
    - .names.Arrpush "`mname'"
    = .names.Arrpush "freeparm"
    -----

> ----- end _optlist.add
> opt -----
    - }
    - foreach opt of local eqargopts {
    - .eq_opts_allowed.addopt `opt', passthru

```

```

= .eq_opts_allowed.addopt OFFset, passthru
> _____ begin _optlist.add
> opt _____
    - version 9
    - syntax name(name=optspec) [, PASSthru]
    - local mname = lower("`optspec'")
    = local mname = lower("OFFset")
    - if "`passthru'" != "" {
    = if "passthru" != "" {
    - local optspec `optspec'(passthru)
    = local optspec OFFset(passthru)
    - }
    - .options.Arrpush "`optspec'"
    = .options.Arrpush "OFFset(passthru)"
    - .names.Arrpush "`mname'"
    = .names.Arrpush "offset"
> _____ end _optlist.add
> opt _____
    - }
    - .eq_opts_allowed.addopt `opt', passthru
    = .eq_opts_allowed.addopt EXPosure, passthru
> _____ begin _optlist.add
> opt _____
    - version 9
    - syntax name(name=optspec) [, PASSthru]
    - local mname = lower("`optspec'")
    = local mname = lower("EXPosure")
    - if "`passthru'" != "" {
    = if "passthru" != "" {
    - local optspec `optspec'(passthru)
    = local optspec EXPosure(passthru)
    - }
    - .options.Arrpush "`optspec'"
    = .options.Arrpush "EXPosure(passthru)"
    - .names.Arrpush "`mname'"
    = .names.Arrpush "exposure"
> _____ end _optlist.add
> opt _____
    - }
    - local i 0
    - foreach opt of local markopts {
      .mark_opts.addopt `opt', passthru

```

```

    }
    - local i 0
    - foreach opt of local smarkopts {
      .smark_opts.addopt `opt', passthru
    }
    - local i 0
    - foreach opt of local rmcollopts {
      .rmcoll_opts.addopt `opt', passthru
    }
    - local i 0
    - foreach opt of local rmdcollopts {
      .rmdcoll_opts.addopt `opt', passthru
    }
    - .n_depvars.Arrdropall
    - if "`numdepvars'" != "" {
    = if "0" != "" {
    - foreach ndep of local numdepvars {
    - .n_depvars.Arrpush `ndep'
    = .n_depvars.Arrpush 0
    - }
    - }
    - else .n_depvars.Arrpush 1
    - .needequal = "`needequal'"
    = .needequal = "needequal"
    - .wtypes = "`wtypes'"
    = .wtypes = ""
    - .noneedvarlist = "`needvarlist'"
    = .noneedvarlist = "noneedvarlist"
    - .nocons_ignore = "`ignorenocons'"
    = .nocons_ignore = ""
  _____
> _____ end _eqlist._se
> tup _____
  _____
> _____ end _eqlist.
> new _____
    - .`eqlist'.parse `spec'
    = .__000006.parse (y_timing_max: y_timing_max = rule_g rule_itr est
> imated, ) []
  _____
> _____ begin _eqlist.pa
> rse _____
    - version 9.2
    - .__init
  _____
> _____ begin _eqlist._i

```

```

> nit
- version 9.2
- .n_eq = 0
- .gl_if = ""
- .gl_in = ""
- .gl_wgt = ""
- .gl_options = ""
- .eq_list = {}

> _____ end _eqlist._i
> nit
- local MARKOPTLIST ```.mark_opts.dumpoptions'''

> _____ begin _optlist.dumpopti
> ons
- version 9
- forval i = 1/`.options.arnels' {
= forval i = 1/0 {
  local optlist `optlist' `.options['i']'
  }
- local optlist : list uniq optlist
- sreturn local optlist ```optlist'''
= sreturn local optlist `'''
- class exit ```optlist'''
= class exit `'''

> _____ end _optlist.dumpopti
> ons
= local MARKOPTLIST `'''
- local SMARKOPTLIST ```.smark_opts.dumpoptions'''

> _____ begin _optlist.dumpopti
> ons
- version 9
- forval i = 1/`.options.arnels' {
= forval i = 1/0 {
  local optlist `optlist' `.options['i']'
  }
- local optlist : list uniq optlist
- sreturn local optlist ```optlist'''
= sreturn local optlist `'''
- class exit ```optlist'''
= class exit `'''

> _____ end _optlist.dumpopti
> ons

```



```

= local SMARKOPTLIST `""'
- local RMCOLLOPTLIST ```.rmcoll_opts.dumpoptions'''

> _____ begin _optlist.dumpopti
> ons _____
    - version 9
    - forval i = 1/`.options.arnels' {
= forval i = 1/0 {
    local optlist `optlist' `options['i']'
    }
    - local optlist : list uniq optlist
    - sreturn local optlist ```optlist'''
= sreturn local optlist `""'
    - class exit ```optlist'''
= class exit `""'

> _____ end _optlist.dumpopti
> ons _____
    = local RMCOLLOPTLIST `""'
    - local RMDCOLLOPTLIST ```.rmdcoll_opts.dumpoptions'''

> _____ begin _optlist.dumpopti
> ons _____
    - version 9
    - forval i = 1/`.options.arnels' {
= forval i = 1/0 {
    local optlist `optlist' `options['i']'
    }
    - local optlist : list uniq optlist
    - sreturn local optlist ```optlist'''
= sreturn local optlist `""'
    - class exit ```optlist'''
= class exit `""'

> _____ end _optlist.dumpopti
> ons _____
    = local RMDCOLLOPTLIST `""'
    - _parse expand EQ GL : 0, gweight common( `MARKOPTLIST' `SMARKOPT
> LIST' `RMCOLLOPTLIST' `RMDCOLLOPTLIST' COLLlinear )
    = _parse expand EQ GL : 0, gweight common( COLLlinear )
    - if `EQ_n' == 0 & ``.noneedvarlist' == "" {
= if 1 == 0 & "noneedvarlist" == "" {
    syntax varlist
    }
    - local rebind = `EQ_n' == 1
= local rebind = 1 == 1

```

```

- if `rebind' {
= if 1 {
- tokenize ``0'', parse(",()[]")
= tokenize ``(y_timing_max: y_timing_max = rule_g rule_itr estimat
> ed, ) []'', parse(",()[]")
- local rebind = ``1'' != "(" & ``2'' == "("
= local rebind = ``( '' != "(" & ``y_timing_max: y_timing_max = rul
> e_g rule_itr estimated'' == "("
- }
- if `rebind' {
= if 0 {
while `:length local 0' {
gettoken tok 0 : 0, parse(" ,") bind match(par)
if ``par'' == "(" {
gettoken nxt : 0
local nxt = substr(``nxt'',1,1)
if inlist(``nxt'', "#", "|") {
local ZERO ``ZERO' (`tok')''
}
else {
local ZERO ``(`ZERO') (`tok') `0''
local 0
}
}
else if inlist(``tok'', "if", "in", ",") {
local ZERO ``(`ZERO') `tok' `0''
local 0
}
else if inlist(substr(``tok'',1,1), "#", "|") {
local ZERO ``ZERO`tok''
}
else {
local ZERO ``ZERO' `tok''
}
}
}
_parse expand EQ GL : ZERO, gweight common( `MARKOPTLIST' `SMARK
> OPTLIST' `RMCOLLOPTLIST' `RMDCOLLOPTLIST' COLLlinear )
}
- forval i = 1/`EQ_n' {
= forval i = 1/1 {
- if `i' <= `.n_depvars.arrnels' {
= if 1 <= 1 {
- local ndep = `.n_depvars[`i']'
= local ndep = 0
- }
- .eq_list[`i'] = .eqspec.new, numdepvars(`ndep') `.needequal' `.

```

```

> noneedvarlist' wtypes(`.wtypes') `.nocons_ignore'
      = .eq_list[1] = ._eqspec.new, numdepvars(0) needequal noneedvarlis
> t wtypes()
      -class {
      -instance:
      -      double  n_depvars
      -      double  needequal
      -      double  needvarlist
      -      string  wtypes
      -      string  name
      -      string  depvars
      -      double  hasequal
      -      string  indepvars
      -      string  other_markvars
      -      double  nocons
      -      double  nocons_ignore
      -      string  offset
      -      double  exposure
      -      double  freeparm
      -      string  if
      -      string  in
      -      string  wgt
      -      string  options
      -}

> _____ begin _eqspec.
> new _____
      - version 9.2
      - syntax [, NUMDEPvars(numlist integer >=0 max=1) NEEDEQUAL noNE
> EDVARLIST WTYPES(string) IGNORENOCONS ]
      - .n_depvars = 1
      - if `:list sizeof numdepvars' {
      = if 1 {
      - .n_depvars = `numdepvars'
      = .n_depvars = 0
      - }
      - .needequal = ("`needequal'" != "")
      = .needequal = ("needequal" != "")
      - .needvarlist = ("`needvarlist'" == "")
      = .needvarlist = ("noneedvarlist" == "")
      - .nocons_ignore = ("`ignorenocons'" != "")
      = .nocons_ignore = (" " != "")
      - .wtypes = "`wtypes'"
      = .wtypes = ""

> _____ end _eqspec.

```

```

> new -----
      - .eq_list['i'].parse `.eq_opts_allowed.objkey':`EQ`i''
      = .eq_list[1].parse __key(60000026e440):y_timing_max: y_timing_max
> = rule_g rule_itr estimated
-----

> ----- begin _eqspec.pa
> rse -----
      - version 9.2
      - _on_colon_parse `0'
      = _on_colon_parse __key(60000026e440):y_timing_max: y_timing_max
> = rule_g rule_itr estimated
-----

> ----- begin _on_colon_pa
> rse -----
      - version 8.2
      - sreturn local before ""
      - sreturn local after ""
      - gettoken before after : 0, parse(":") bind match(par) quotes
      - if "`par'" != "" {
      = if "" != "" {
        local before `(`before')'
      }
      - if ``before'"" == ":" {
      = if `__key(60000026e440)' == ":" {
        sreturn local after ``after'""
        exit
      }
      - while ``COLON'"" != ":" & ``after'"" != "" {
      = while `"" != ":" & `":y_timing_max: y_timing_max = rule_g r
> ule_itr estimated'"" != "" {
      - gettoken COLON after : after, parse(":") bind match(par) quo
> tes
      - if "`par'" != "" {
      = if "" != "" {
        local before `before' (`COLON')
        local COLON
      }
      - else if ``COLON'"" != ":" {
      = else if `":'"" != ":" {
        local before ``before' `COLON'""
        local COLON
      }
      - }
      - while ``COLON'"" != ":" & ``after'"" != "" {
      = while `":'"" != ":" & `":y_timing_max: y_timing_max = rule_g r
> ule_itr estimated'"" != "" {

```

```

gettoken COLON after : after, parse(":") bind match(par) quo
> tes
  if "`par'" != "" {
    local before `before' (`COLON')
    local COLON
  }
  else if `""COLON""' != ":" {
    local before `""before' `COLON""'
    local COLON
  }
  }
- if `""COLON""' != ":" {
= if `":'" != ":" {
  di as err ""' found where ':' expected"
  exit 198
}
- sreturn local before `""before""'
= sreturn local before `__key(60000026e440)'"
- sreturn local after `""after""'
= sreturn local after `y_timing_max: y_timing_max = rule_g ru
> le_itr estimated"'
_____
> _____ end _on_colon_pa
> rse _____
  - local ol `s(before)'
  = local ol __key(60000026e440)
  - if `:list sizeof ol' {
  = if 1 {
  - local OPTLIST `""`.ol'.dumpoptions"'
  _____
> _____ begin _optlist.dumpopti
> ons _____
  - version 9
  - forval i = 1/`.options.arnels' {
  = forval i = 1/4 {
  - local optlist `optlist' `.options['i']'
  = local optlist NOCONSTant
  - }
  - local optlist `optlist' `.options['i']'
  = local optlist NOCONSTant FREEParm
  - }
  - local optlist `optlist' `.options['i']'
  = local optlist NOCONSTant FREEParm OFFset(passthru)
  - }
  - local optlist `optlist' `.options['i']'
  = local optlist NOCONSTant FREEParm OFFset(passthru) EXPosure(

```

```

> passthru)
    - }
    - local optlist : list uniq optlist
    - sreturn local optlist ```optlist'''
    = sreturn local optlist ``NOCONSTant FREEParm OFFset(passthru)
> EXPosure(passthru)''
    - class exit ```optlist'''
    = class exit ``NOCONSTant FREEParm OFFset(passthru) EXPosure(p
> assthru)''
    _____
> _____ end _optlist.dumpopti
> ons _____
    = local OPTLIST ``NOCONSTant FREEParm OFFset(passthru) EXPosure(
> passthru)''
    - local OPTNAMES ```.ol'.dumpnames'''
    _____
> _____ begin _optlist.dumpna
> mes _____
    - version 9
    - forval i = 1/`.names.arnels' {
    = forval i = 1/4 {
    - local namelist `namelist' `.names['i']'
    = local namelist noconstant
    - }
    - local namelist `namelist' `.names['i']'
    = local namelist noconstant freeparm
    - }
    - local namelist `namelist' `.names['i']'
    = local namelist noconstant freeparm offset
    - }
    - local namelist `namelist' `.names['i']'
    = local namelist noconstant freeparm offset exposure
    - }
    - local namelist : list uniq namelist
    - sreturn local namelist ```namelist'''
    = sreturn local namelist ``noconstant freeparm offset exposure
> ''
    - class exit ```namelist'''
    = class exit ``noconstant freeparm offset exposure''
    _____
> _____ end _optlist.dumpna
> mes _____
    = local OPTNAMES ``noconstant freeparm offset exposure''
    - local NOCONS constant noconstant
    - if ```:list NOCONS & OPTNAMES''' == '' {
    = if ``noconstant'' == '' {

```

```

        local NOCONS noCONSTant
    }
- else local NOCONS
- }
- local 0 ``s(after)''
= local 0 ``y_timing_max: y_timing_max = rule_g rule_itr estimat
> ed''
- if ``.wtypes'' != '' {
= if ``'' != '' {
    local wgt '['.wtypes']"
    }
- syntax [anything(equalok)] [if] [in] `wgt' [, `OPTLIST' `NOCON
> S' *]
    = syntax [anything(equalok)] [if] [in]  [, NOCONSTant FREEParam 0
> FFset(passthru) EXPosure(passthru) *]
- local HOLDIF ``if''
= local HOLDIF ``''
- local HOLDIN ``in''
= local HOLDIN ``''
- if ``wgt'' != '' & ``weight'' != '' {
= if '' != '' & '' != '' {
    local HOLDWGT ``['weight'`exp']"
    }
- gettoken NAME REST : anything, parse(":")
- if trim("`NAME'") == ":" {
= if trim("y_timing_max") == ":" {
    di as err "nothing found where equation name expected"
    exit 198
    }
- if `:list sizeof REST' {
= if 6 {
- if strpos("`NAME'", ":") {
= if strpos("y_timing_max", ":") {
    capture _msparse `NAME'
    if c(rc) {
        di as err "{bf:`NAME'} invalid equation specification"
        exit 198
    }
    }
- else {
- .confirm_eqname `NAME'
= .confirm_eqname y_timing_max
}

> _____ begin _eqspec._confirm_eqn
> ame _____
- version 9.2

```

```

- capture confirm number `0'
= capture confirm number y_timing_max
- if (! c(rc)) exit
- local hasdot = strpos("`0'", ".")
= local hasdot = strpos("`y_timing_max'", ".")
- if `hasdot' {
= if 0 {
    syntax varname(ts)
    exit
  }
- capture syntax name(id="equation name")
- if (! c(rc)) exit

```

```

> _____ end _eqspec._confirm_eqn
> ame _____
- }
- local NAME : list retok NAME
- gettoken COLON anything : REST, parse(":")
- }
- else {
    local NAME
  }
- gettoken DEPVARS REST : anything, parse("=") bind
- if "`DEPVARS'" == "=" {
= if "y_timing_max " == "=" {
    local REST : copy local anything
    local DEPVARS
  }
- if (`:length local DEPVARS' == 0 & `.n_depvars') {
= if (13 == 0 & 0) {
    di as err "nothing found where depvar expected"
    exit 198
  }
- if ``REST' == "" {
= if `"'= rule_g rule_itr estimated"' == "" {
    if 0`.needequal' {
    if `.needvarlist' | (`:length local DEPVARS' != 0 & `.n_depvar
> s') {
    di as err "equal sign required to separate depvars from indepv
> ars"
    exit 198
  }
  }
  local DEPVARS
  local n_deps : list sizeof anything
  if `n_deps' != 0 | `.needvarlist' {

```



```

        if `n_deps' < `.n_depvars' {
            error 102
        }
        forval j = 1/`.n_depvars' {
            gettoken YY anything : anything
            local DEPVARs `DEPVARs' `YY'
        }
        local INDEPVARs : list retok anything
    }
    local hasequal 0
}
- else {
- gettoken EQ INDEPVARs : REST, parse("=") bind
- local hasequal 1
- }
- if `:list sizeof DEPVARs' {
= if 1 {
- _fv_check_depvar `DEPVARs'
= _fv_check_depvar y_timing_max
- tsunab DEPVARs : `DEPVARs'
= tsunab DEPVARs : y_timing_max
}

> _____ begin tsu
> nab _____
        - version 6
        - gettoken user 0: 0, parse(" :")
        - gettoken colon 0: 0, parse(" :")
        - if `"'colon'"' != ":" { error 198 }
        = if `":'"' != ":" { error 198 }
        - syntax [varlist(ts default=empty)] [, MIN(integer 1) MAX(int
> eger 32000) NAME(string)]
        - c_local `user' `varlist'
        = c_local DEPVARs y_timing_max
        - local n : word count `varlist'
        = local n : word count y_timing_max
        - if `n'>=`min' & `n'<=`max' { exit }
        = if 1>=1 & 1<=32000 { exit }

> _____ end tsu
> nab _____
        - }
        - if `:list sizeof INDEPVARs' {
        = if 3 {
        - fvunab INDEPVARs : `INDEPVARs'
        = fvunab INDEPVARs : rule_g rule_itr estimated

```

```

> ----- begin fvu
> nab -----
    - version 11
    - _on_colon_parse `0'
    = _on_colon_parse INDEPVARs : rule_g rule_itr estimated
    -----

> ----- begin _on_colon_pa
> rse -----
    - version 8.2
    - sreturn local before ""
    - sreturn local after ""
    - gettoken before after : 0, parse(":") bind match(par) quot

> es
    - if "`par'" != "" {
    = if "" != "" {
      local before "`('before)'"
    }
    - if ``"before" == ":" {
    = if `"INDEPVARs " == ":" {
      sreturn local after ``"after"
      exit
    }
    - while ``"COLON" != ":" & ``"after" != "" {
    = while `"" != ":" & `": rule_g rule_itr estimated" != ""

> {
    - gettoken COLON after : after, parse(":") bind match(par) q

> uotes
    - if "`par'" != "" {
    = if "" != "" {
      local before `before' (`COLON')
      local COLON
    }
    - else if ``"COLON" != ":" {
    = else if `":'" != ":" {
      local before ``"before' `COLON"
      local COLON
    }
    - }
    - while ``"COLON" != ":" & ``"after" != "" {
    = while `":'" != ":" & `": rule_g rule_itr estimated" != ""

> {
    gettoken COLON after : after, parse(":") bind match(par) q

> uotes
    if "`par'" != "" {
    local before `before' (`COLON')
    local COLON

```

```

    }
    else if ```COLON`` != ":" {
        local before ```before' `COLON``
        local COLON
    }
}
- if ```COLON`` != ":" {
= if `":`` != ":" {
    di as err "" found where ':' expected"
    exit 198
}
- sreturn local before ```before``
= sreturn local before ``INDEPVARs ``
- sreturn local after ```after``
= sreturn local after `` rule_g rule_itr estimated``
}

> _____ end _on_colon_pa
> rse _____
    - local 0 ```s(before)``
    = local 0 ``INDEPVARs ``
    - syntax name(id="macro name" name=user)
    - local 0 ```s(after)``
    = local 0 `` rule_g rule_itr estimated``
    - syntax [varlist(ts fv default=none)] [, MIN(integer 1) MAX(i
> nteger 32000) NAME(string) ]
    - c_local `user' `varlist'
    = c_local INDEPVARs rule_g rule_itr estimated
    - local n : list sizeof varlist
    - if (`min' <= `n' & `n' <= `max') exit
    = if (1 <= 3 & 3 <= 32000) exit
}

> _____ end fvu
> nab _____
    - }
    - if inlist("noconstant", ``noconstant``, ``constant``) {
    = if inlist("noconstant", "", "") {
        if ``INDEPVARs`` == "" & !`.nocons_ignore' {
            di as err "independent variables are required when option noco
> nstant is specified"
            exit 102
        }
        if ``NOCONS`` != "" {
            local options `options' noconstant
        }
        local NOCONS 1
    }
}

```

```

- else local NOCONS 0
- if ``offset'exposure' != "" {
= if `'' != "" {
    ._check_offset, `offset' `exposure'
    local OFFSET ``s(offset)'
    local EXPOSURE = (`exposure' != "")
    local OTHER `s(offset)'
  }
- else local EXPOSURE 0
- local FREEARM = ``freeparm' != ""
= local FREEARM = `'' != ""
- local OPTIONS
- local SPACE
- foreach OPTNAME of local OPTNAMES {
- if ``OPTNAME' != "" {
= if `'' != "" {
    local OPTIONS ``OPTIONS' `SPACE' `OPTNAME'
    local SPACE " "
  }
- }
- if ``OPTNAME' != "" {
= if `'' != "" {
    local OPTIONS ``OPTIONS' `SPACE' `OPTNAME'
    local SPACE " "
  }
- }
- if ``OPTNAME' != "" {
= if `'' != "" {
    local OPTIONS ``OPTIONS' `SPACE' `OPTNAME'
    local SPACE " "
  }
- }
- if ``OPTNAME' != "" {
= if `'' != "" {
    local OPTIONS ``OPTIONS' `SPACE' `OPTNAME'
    local SPACE " "
  }
- }
- if ``options' != "" {
= if `'' != "" {
    local OPTIONS ``OPTIONS' `SPACE' `options'
  }
- .name = ``NAME'
= .name = `y_timing_max'
- .depvars = ``DEPVARs'
= .depvars = `y_timing_max'

```

```

- .hasequal = `hasequal'
= .hasequal = 1
- .indepvars = ``:list retok INDEPVARs'''
= .indepvars = `rule_g rule_itr estimated'''
- .other_markvars = ``:list retok OTHER'''
= .other_markvars = `'''
- .nocons = `NOCONS'
= .nocons = 0
- .if = ``HOLDIF'''
= .if = `'''
- .in = ``HOLDIN'''
= .in = `'''
- .wgt = ``HOLDWGT'''
= .wgt = `'''
- .offset = ``OFFSET'''
= .offset = `'''
- .exposure = `EXPOSURE'
= .exposure = 0
- .freeparm = `FREEPARM'
= .freeparm = 0
- .options = ``OPTIONS'''
= .options = `'''

> _____ end _eqspec.pa
> rse _____
- }
- local MARKOPTLIST ``.mark_opts.dumpoptions'''

> _____ begin _optlist.dumpopti
> ons _____
- version 9
- forval i = 1/`.options.arrnells' {
= forval i = 1/0 {
    local optlist `optlist' `.options['i']'
    }
- local optlist : list uniq optlist
- sreturn local optlist ``optlist'''
= sreturn local optlist `'''
- class exit ``optlist'''
= class exit `'''

> _____ end _optlist.dumpopti
> ons _____
= local MARKOPTLIST `'''
- local MARKOPTNAMES ``.mark_opts.dumpnames'''

```

```

> _____ begin _optlist.dumpna
> mes _____
    - version 9
    - forval i = 1/`.names.arnels' {
= forval i = 1/0 {
    local namelist `namelist' `.names['i']'
    }
    - local namelist : list uniq namelist
    - sreturn local namelist ``namelist'''
= sreturn local namelist `''''
    - class exit ``namelist'''
= class exit `''''
    _____

> _____ end _optlist.dumpna
> mes _____
    = local MARKOPTNAMES `''''
    - local OPTLIST1 : substr local MARKOPTLIST "(passthru)" "(strin
> g asis)", all
    - local SMARKOPTLIST ```.smark_opts.dumpoptions'''
    _____

> _____ begin _optlist.dumpopti
> ons _____
    - version 9
    - forval i = 1/`.options.arnels' {
= forval i = 1/0 {
    local optlist `optlist' `.options['i']'
    }
    - local optlist : list uniq optlist
    - sreturn local optlist ``optlist'''
= sreturn local optlist `''''
    - class exit ``optlist'''
= class exit `''''
    _____

> _____ end _optlist.dumpopti
> ons _____
    = local SMARKOPTLIST `''''
    - local SMARKOPTNAMES ```.smark_opts.dumpnames'''
    _____

> _____ begin _optlist.dumpna
> mes _____
    - version 9
    - forval i = 1/`.names.arnels' {
= forval i = 1/0 {
    local namelist `namelist' `.names['i']'
    }
    - local namelist : list uniq namelist

```

```

- sreturn local namelist ``namelist'''
= sreturn local namelist `'''
- class exit ``namelist'''
= class exit `'''

```

```

> ----- end _optlist.dumpna
> mes -----
    = local SMARKOPTNAMES `'''
    - local OPTLIST1s : substr local SMARKOPTLIST "(passthru)" "(str
> ing asis)", all
    - local RMCOLLOPTLIST ``.rmcoll_opts.dumpoptions'''

```

```

> ----- begin _optlist.dumpopti
> ons -----
    - version 9
    - forval i = 1/`.options.arnels' {
= forval i = 1/0 {
    local optlist `optlist' `.options['i']'
    }
    - local optlist : list uniq optlist
    - sreturn local optlist ``optlist'''
= sreturn local optlist `'''
    - class exit ``optlist'''
= class exit `'''

```

```

> ----- end _optlist.dumpopti
> ons -----
    = local RMCOLLOPTLIST `'''
    - local RMCOLLOPTNAMES ``.rmcoll_opts.dumpnames'''

```

```

> ----- begin _optlist.dumpna
> mes -----
    - version 9
    - forval i = 1/`.names.arnels' {
= forval i = 1/0 {
    local namelist `namelist' `.names['i']'
    }
    - local namelist : list uniq namelist
    - sreturn local namelist ``namelist'''
= sreturn local namelist `'''
    - class exit ``namelist'''
= class exit `'''

```

```

> ----- end _optlist.dumpna
> mes -----
    = local RMCOLLOPTNAMES `'''

```

```

- local OPTLIST2 : subinstr local RMDCOLLOPTLIST "(passthru)" "(str
> ing asis)", all
- local RMDCOLLOPTLIST ```.rmdcoll_opts.dumpoptions'''

> _____ begin _optlist.dumpopti
> ons _____
- version 9
- forval i = 1/`.options.arrnells' {
= forval i = 1/0 {
  local optlist `optlist' `.options['i']'
}
- local optlist : list uniq optlist
- sreturn local optlist ```optlist'''
= sreturn local optlist `'''
- class exit ```optlist'''
= class exit `'''

> _____ end _optlist.dumpopti
> ons _____
= local RMDCOLLOPTLIST `'''
- local RMDCOLLOPTNAMES ```.rmdcoll_opts.dumpnames'''

> _____ begin _optlist.dumpna
> mes _____
- version 9
- forval i = 1/`.names.arrnells' {
= forval i = 1/0 {
  local namelist `namelist' `.names['i']'
}
- local namelist : list uniq namelist
- sreturn local namelist ```namelist'''
= sreturn local namelist `'''
- class exit ```namelist'''
= class exit `'''

> _____ end _optlist.dumpna
> mes _____
= local RMDCOLLOPTNAMES `'''
- local OPTLIST3 : subinstr local RMDCOLLOPTLIST "(passthru)" "(st
> ring asis)", all
- local 0 `", `GL_op'''
= local 0 `", ""
- syntax [, `OPTLIST1' `OPTLIST1s' `OPTLIST2' `OPTLIST3' COLlinear
> noCONSTant * ]
= syntax [, COLlinear noCONSTant * ]
- local GL_op ```options'''

```



```

= local GL_op `""'
- if `""`collinear`""' != "" {
= if `""' != "" {
    local GL_op `""GL_op' `collinear`""
    .collinear = ""collinear""
}
- if `""`constant`""' != "" {
= if `""' != "" {
    local GL_op `""GL_op' `constant`""
    .nocons = ""constant""
}
- local I 0
- foreach OPT of local MARKOPTNAMES {
    if `:list sizeof `OPT'' {
        .mark_list[`++I'] = .eqspec.new, numdep(0) wtypes(`.wtypes')
        .mark_list[`I'].parse "" : ``OPT''
        .mark_name.Arrpush ""OPT""
    }
}
- local I 0
- foreach OPT of local SMARKOPTNAMES {
    if `:list sizeof `OPT'' {
        .smark_list[`++I'] = .eqspec.new, numdep(0) wtypes(`.wtypes')
        .smark_list[`I'].parse "" : ``OPT''
        .smark_name.Arrpush ""OPT""
    }
}
- local I 0
- foreach OPT of local RMCOLLOPTNAMES {
    if `:list sizeof `OPT'' {
        .rmcoll_list[`++I'] = .eqspec.new, numdep(0) wtypes(`.wtypes')
        .rmcoll_list[`I'].parse "" : ``OPT''
        .rmcoll_name.Arrpush ""OPT""
    }
}
- local I 0
- foreach OPT of local RMDCOLLOPTNAMES {
    if `:list sizeof `OPT'' {
        .rmdcoll_list[`++I'] = .eqspec.new, wtypes(`.wtypes')
        .rmdcoll_list[`I'].parse "" : ``OPT''
        .rmdcoll_name.Arrpush ""OPT""
    }
}
- .n_eq = `EQ_n'
= .n_eq = 1
- .gl_if = `""GL_if`""'

```

```

= .gl_if = `""'
- .gl_in = ``GL_in'''
= .gl_in = `""'
- .gl_wgt = ``GL_wt'''
= .gl_wgt = ``[]'''
- .gl_options = ``:list retok GL_op'''
= .gl_options = `""'

> _____ end _eqlist.pa
> rse _____
- if ``subpop'' != '' & ``missing'' == '' {
= if '' != '' & "missing" == '' {
  if `interactive' {
    SetGlobalVar ML_samp : _MLtu
  }
  else {
    global ML_samp : tempvar
    if ``moptobj''' != '' {
      global ML_samp `moptobj'$ML_samp
    }
  }
  tempvar markuse
  _svy_setup $ML_sample $ML_samp, svy subpop(`subpop')
  quietly gen byte `markuse' = $ML_samp
}
- else global ML_samp $ML_sample
= else global ML_samp __000005
- if ``collinear'' == '' {
= if "collinear" == '' {
  .`eqlist'.rmcoll $ML_samp, replace `missing'
}
- else if ``missing'' == '' {
= else if "missing" == '' {
  .`eqlist'.markout $ML_samp, replace
}
- if "$ML_samp" != "$ML_sample" {
= if "__000005" != "__000005" {
  `vv' quietly replace $ML_sample = 0 if `markuse' & !$ML_samp
  drop `markuse'
}
- local eq_n = `.`eqlist'.eq count'

> _____ begin _eqlist
> .eq _____
- version 9.2
- args item idx

```

```

- if "`item'" == "count" {
= if "count" == "count" {
- sreturn local value ```.n_eq'''
= sreturn local value `1'
- class exit ```s(value)'''
= class exit `1'
}
}

> _____ end _eqlist
> .eq _____
= local eq_n = 1
- global ML_n : copy local eq_n
- global ML_dim = `.`eqlist'.dim'
}

> _____ begin _eqlist.
> dim _____
- version 9.2
- syntax
- local neq = `.eq count'
}

> _____ begin _eqlist
> .eq _____
- version 9.2
- args item idx
- if "`item'" == "count" {
= if "count" == "count" {
- sreturn local value ```.n_eq'''
= sreturn local value `1'
- class exit ```s(value)'''
= class exit `1'
}
}

> _____ end _eqlist
> .eq _____
= local neq = 1
- forval i = 1/`neq' {
= forval i = 1/1 {
- local xvarsi ```.eq indepvars `i'
}
}

> _____ begin _eqlist
> .eq _____
- version 9.2
- args item idx
- if "`item'" == "count" {
= if "indepvars" == "count" {
sreturn local value ```.n_eq'''
class exit ```s(value)'''
}
}

```

```

- else if 0 < `idx' & `idx' <= `.n_eq' {
= else if 0 < 1 & 1 <= 1 {
- .eq_list[`idx'].item `item'
= .eq_list[1].item indepvars

```

```

> _____ begin _eqspec.i
> tem _____
- version 9.2
- args item
- .check_eq_item_name item, `item'
= .check_eq_item_name item, indepvars

```

```

> _____ begin _eqspec._check_eq_item_n
> ame _____
- version 9.2
- capture syntax name(name=c_item) [, NAME DEPvars INDEPvars
> IF IN WGT OTHER NOCONS OFFset EXPosure FREEParam OPTions ]
- if c(rc) error 198
- if `:list sizeof other' {
= if 0 {
local other other_markvars
}
- local item `name' `depvars' `indepvars' `if' `in' `wgt' `o
> ther' `nocons' `offset' `exposure' `freeparm' `options'
= local item indepvars
- if `:list sizeof item' != 1 {
= if 1 != 1 {
error 198
}
- c_local `c_item' `item'
= c_local item indepvars

```

```

> _____ end _eqspec._check_eq_item_n
> ame _____
- local value ```.`item'```
= local value `"rule_g rule_itr estimated"'
- sreturn local value ```.value```
= sreturn local value `"rule_g rule_itr estimated"'
- class exit ```.value```
= class exit `"rule_g rule_itr estimated"'

```

```

> _____ end _eqspec.i
> tem _____
- class exit ```.s(value)```
= class exit `"rule_g rule_itr estimated"'

```

```

> _____ end _eqlist
> .eq _____
    = local xvarsi `"rule_g rule_itr estimated"'
    - local noconsi `"'`eq nocons `i'`"'
    _____

> _____ begin _eqlist
> .eq _____
    - version 9.2
    - args item idx
    - if "`item'" == "count" {
    = if "nocons" == "count" {
        sreturn local value `"'`.n_eq'`"'
        class exit `"'s(value)'`"'
    }
    - else if 0 < `idx' & `idx' <= `.n_eq' {
    = else if 0 < 1 & 1 <= 1 {
        - .eq_list[`idx'].item `item'
    = .eq_list[1].item nocons
    _____

> _____ begin _eqspec.i
> tem _____
    - version 9.2
    - args item
    - .check_eq_item_name item, `item'
    = .check_eq_item_name item, nocons
    _____

> _____ begin _eqspec._check_eq_item_n
> ame _____
    - version 9.2
    - capture syntax name(name=c_item) [, NAME DEPvars INDEPvars
> IF IN WGT OTHER NOCONS OFFset EXPosure FREEparm OPTions ]
    - if c(rc) error 198
    - if `:list sizeof other' {
    = if 0 {
        local other other_markvars
    }
    - local item `name' `depvars' `indepvars' `if' `in' `wgt' `o
> ther' `nocons' `offset' `exposure' `freeparm' `options'
    = local item nocons
    - if `:list sizeof item' != 1 {
    = if 1 != 1 {
        error 198
    }
    - c_local `c_item' `item'
    = c_local item nocons
    _____

```

```

> _____ end _eqspec._check_eq_item_n
> ame _____
    - local value ```.`item'```
    = local value ``0```
    - sreturn local value ```.`value'```
    = sreturn local value ``0```
    - class exit ```.`value'```
    = class exit ``0```

> _____ end _eqspec.i
> tem _____
    - class exit ```.s(value)```
    = class exit ``0```

> _____ end _eqlist
> .eq _____
    = local noconsi ``0```
    - local dim = `dim' + `:list sizeof xvarsi'
    = local dim = + 3
    - if ``noconsi' == "0" {
    = if "0" == "0" {
    - local ++dim
    - }
    - }
    - sreturn local value ```.`dim'```
    = sreturn local value ``4```
    - class exit ```.s(value)```
    = class exit ``4```

> _____ end _eqlist.
> dim _____
    = global ML_dim = 4
    - forval i = 1/`eq_n' {
    = forval i = 1/1 {
    - local depvars `.`eqlist'.eq depvars `i'

> _____ begin _eqlist
> .eq _____
    - version 9.2
    - args item idx
    - if ``item' == "count" {
    = if "depvars" == "count" {
    sreturn local value ```.n_eq'```
    class exit ```.s(value)```
    }
    - else if 0 < `idx' & `idx' <= `.n_eq' {

```

```

= else if 0 < 1 & 1 <= 1 {
- .eq_list['idx'].item `item'
= .eq_list[1].item depvars
}

> _____ begin _eqspec.i
> tem _____
- version 9.2
- args item
- .check_eq_item_name item, `item'
= .check_eq_item_name item, depvars
}

> _____ begin _eqspec._check_eq_item_n
> ame _____
- version 9.2
- capture syntax name(name=c_item) [, NAME DEPvars INDEPvars I
> F IN WGT OTHER NOCONS OFFset EXPosure FREEParam OPTions ]
- if c(rc) error 198
- if `:list sizeof other' {
= if 0 {
local other other_markvars
}
- local item `name' `depvars' `indepvars' `if' `in' `wgt' `oth
> er' `nocons' `offset' `exposure' `freeparm' `options'
= local item depvars
- if `:list sizeof item' != 1 {
= if 1 != 1 {
error 198
}
- c_local `c_item' `item'
= c_local item depvars
}

> _____ end _eqspec._check_eq_item_n
> ame _____
- local value ```.item'''
= local value `y_timing_max'
- sreturn local value ``value'''
= sreturn local value `y_timing_max'
- class exit ``value'''
= class exit `y_timing_max'
}

> _____ end _eqspec.i
> tem _____
- class exit ``s(value)'''
= class exit `y_timing_max'
}

> _____ end _eqlist

```

```

> .eq
    = local depvars y_timing_max
    - local eq ``.eqlist'.eq name `i'

>
> .eq
    - version 9.2
    - args item idx
    - if ``item' == "count" {
    = if "name" == "count" {
        sreturn local value ``.n_eq'
        class exit ``s(value)''
    }
    - else if 0 < `idx' & `idx' <= `.n_eq' {
    = else if 0 < 1 & 1 <= 1 {
        - .eq_list[`idx'].item `item'
    = .eq_list[1].item name

>
> tem
    - version 9.2
    - args item
    - .check_eq_item_name item, `item'
    = .check_eq_item_name item, name

>
> ame
    - version 9.2
    - capture syntax name(name=c_item) [, NAME DEPvars INDEPvars I
> F IN WGT OTHER NOCONS OFFset EXPosure FREEParm OPTions ]
    - if c(rc) error 198
    - if `:list sizeof other' {
    = if 0 {
        local other other_markvars
    }
    - local item `name' `depvars' `indepvars' `if' `in' `wgt' `oth
> er' `nocons' `offset' `exposure' `freeparm' `options'
    = local item name
    - if `:list sizeof item' != 1 {
    = if 1 != 1 {
        error 198
    }
    - c_local `c_item' `item'
    = c_local item name

>
>
    end _eqspec._check_eq_item_n

```



```

> ame -----
    - local value ```.item'''
    = local value `y_timing_max`
    - sreturn local value ``value'''
    = sreturn local value `y_timing_max`
    - class exit ``value'''
    = class exit `y_timing_max`
-----

> ----- end _eqspec.i
> tem -----
    - class exit ``s(value)'''
    = class exit `y_timing_max`
-----

> ----- end _eqlist
> .eq -----
    = local eq y_timing_max
    - if !`:length local eq' {
    = if !12 {
        local eq eq`i'
    }
    - if `:list eq in eqnames' {
    = if 0 {
        di as err "equation ``eq'' multiply defined"
        exit 110
    }
    - local eqnames `eqnames' `eq'
    = local eqnames y_timing_max
    - fvexpand `.`eqlist'.eq indepvars `i'' if $ML_samp
-----

> ----- begin _eqlist
> .eq -----
    - version 9.2
    - args item idx
    - if ``item' == "count" {
    = if "indepvars" == "count" {
        sreturn local value ``.n_eq'''
        class exit ``s(value)'''
    }
    - else if 0 < `idx' & `idx' <= `.n_eq' {
    = else if 0 < 1 & 1 <= 1 {
        - .eq_list[`idx'].item `item'
    = .eq_list[1].item indepvars
-----

> ----- begin _eqspec.i
> tem -----
    - version 9.2

```

```

- args item
- .check_eq_item_name item, `item'
= .check_eq_item_name item, indepvars

```

```

> _____ begin _eqspec._check_eq_item_n
> ame _____
- version 9.2
- capture syntax name(name=c_item) [, NAME DEPvars INDEPvars I
> F IN WGT OTHER NOCONS OFFset EXPosure FREEParM OPTions ]
- if c(rc) error 198
- if `:list sizeof other' {
= if 0 {
local other other_markvars
}
- local item `name' `depvars' `indepvars' `if' `in' `wgt' `oth
> er' `nocons' `offset' `exposure' `freeparm' `options'
= local item indepvars
- if `:list sizeof item' != 1 {
= if 1 != 1 {
error 198
}
- c_local `c_item' `item'
= c_local item indepvars

```

```

> _____ end _eqspec._check_eq_item_n
> ame _____
- local value ```. `item'``
= local value ``rule_g rule_itr estimated''
- sreturn local value ```value'``
= sreturn local value ``rule_g rule_itr estimated''
- class exit ```value'``
= class exit ``rule_g rule_itr estimated''

```

```

> _____ end _eqspec.i
> tem _____
- class exit ```s(value)'``
= class exit ``rule_g rule_itr estimated''

```

```

> _____ end _eqlist
> .eq _____
= fvexpand rule_g rule_itr estimated if __000005
- if ``r(tsops)' == "true" {
= if "" == "true" {
global ML_preserve no
}
- local eq_rhs`i' ```r(varlist)'``

```

```

= local eq_rhs1 `"rule_g rule_itr estimated"'
- local eq_nocons`i' `.`eqlist'.eq nocons `i''

> _____ begin _eqlist
> .eq _____
    - version 9.2
    - args item idx
    - if ``item'" == "count" {
= if "nocons" == "count" {
    sreturn local value ```.n_eq'''
    class exit ``"s(value)'''
    }
    - else if 0 < `idx' & `idx' <= `.n_eq' {
= else if 0 < 1 & 1 <= 1 {
    - .eq_list[`idx'].item `item'
= .eq_list[1].item nocons

> _____ begin _eqspec.i
> tem _____
    - version 9.2
    - args item
    - .check_eq_item_name item, `item'
= .check_eq_item_name item, nocons

> _____ begin _eqspec._check_eq_item_n
> ame _____
    - version 9.2
    - capture syntax name(name=c_item) [, NAME DEPvars INDEPvars I
> F IN WGT OTHER NOCONS OFFset EXPosure FREEparm OPTions ]
    - if c(rc) error 198
    - if `:list sizeof other' {
= if 0 {
    local other other_markvars
    }
    - local item `name' `depvars' `indepvars' `if' `in' `wgt' `oth
> er' `nocons' `offset' `exposure' `freeparm' `options'
    = local item      nocons
    - if `:list sizeof item' != 1 {
= if 1 != 1 {
    error 198
    }
    - c_local `c_item' `item'
= c_local item nocons

> _____ end _eqspec._check_eq_item_n
> ame _____

```

```

- local value ```.item'''
= local value ``0'''
- sreturn local value ``value'''
= sreturn local value ``0'''
- class exit ``value'''
= class exit ``0'''

> _____ end _eqspec.i
> tem _____
- class exit ``s(value)'''
= class exit ``0'''

> _____ end _eqlist
> .eq _____
= local eq_nocons1 0
- local eq_offset`i' ``.eqlist'.eq offset `i''

> _____ begin _eqlist
> .eq _____
- version 9.2
- args item idx
- if ``item' == "count" {
= if "offset" == "count" {
sreturn local value ``.n_eq'''
class exit ``s(value)'''
}
- else if 0 < `idx' & `idx' <= `.n_eq' {
= else if 0 < 1 & 1 <= 1 {
- .eq_list[`idx'].item `item'
= .eq_list[1].item offset

> _____ begin _eqspec.i
> tem _____
- version 9.2
- args item
- .check_eq_item_name item, `item'
= .check_eq_item_name item, offset

> _____ begin _eqspec._check_eq_item_n
> ame _____
- version 9.2
- capture syntax name(name=c_item) [, NAME DEPvars INDEPvars I
> F IN WGT OTHER NOCONS OFFset EXPosure FREEParam OPTions ]
- if c(rc) error 198
- if `:list sizeof other' {
= if 0 {

```

```

        local other other_markvars
    }
    - local item `name' `depvars' `indepvars' `if' `in' `wgt' `oth
> er' `nocons' `offset' `exposure' `freeparm' `options'
    = local item      offset
    - if `:list sizeof item' != 1 {
    = if 1 != 1 {
        error 198
    }
    - c_local `c_item' `item'
    = c_local item offset
    _____
> _____ end _eqspec._check_eq_item_n
> ame _____
    - local value ```.`item'```
    = local value ````
    - sreturn local value ```.value```
    = sreturn local value ````
    - class exit ```.value```
    = class exit ````
    _____
> _____ end _eqspec.i
> tem _____
    - class exit ```.s(value)```
    = class exit ````
    _____
> _____ end _eqlist
> .eq _____
    = local eq_offset1
    - local eq_exposure`i' ``.eqlist'.eq exposure `i'
    _____
> _____ begin _eqlist
> .eq _____
    - version 9.2
    - args item idx
    - if ``item' == "count" {
    = if "exposure" == "count" {
        sreturn local value ```.n_eq```
        class exit ```.s(value)```
    }
    - else if 0 < `idx' & `idx' <= `.n_eq' {
    = else if 0 < 1 & 1 <= 1 {
        - .eq_list[`idx'].item `item'
        = .eq_list[1].item exposure
    _____
> _____ begin _eqspec.i

```

```

> tem -----
      - version 9.2
      - args item
      - ._check_eq_item_name item, `item'
      = ._check_eq_item_name item, exposure
-----

> ----- begin _eqspec._check_eq_item_n
> ame -----
      - version 9.2
      - capture syntax name(name=c_item) [, NAME DEPvars INDEPvars I
> F IN WGT OTHER NOCONS OFFset EXPosure FREEparm OPTions ]
      - if c(rc) error 198
      - if `:list sizeof other' {
      = if 0 {
          local other other_markvars
      }
      - local item `name' `depvars' `indepvars' `if' `in' `wgt' `oth
> er' `nocons' `offset' `exposure' `freeparm' `options'
      = local item exposure
      - if `:list sizeof item' != 1 {
      = if 1 != 1 {
          error 198
      }
      - c_local `c_item' `item'
      = c_local item exposure
-----

> ----- end _eqspec._check_eq_item_n
> ame -----
      - local value ```.`item'```
      = local value ``0```
      - sreturn local value ```value```
      = sreturn local value ``0```
      - class exit ```value```
      = class exit ``0```
-----

> ----- end _eqspec.i
> tem -----
      - class exit ```s(value)```
      = class exit ``0```
-----

> ----- end _eqlist
> .eq -----
      = local eq_exposure1 0
      - local eq_freeparm`i' `.`eqlist'.eq freeparm `i'
-----

> ----- begin _eqlist

```

```

> .eq
- version 9.2
- args item idx
- if "`item'" == "count" {
= if "freeparm" == "count" {
  sreturn local value ```.n_eq'''
  class exit ```s(value)'''
}
- else if 0 < `idx' & `idx' <= `.n_eq' {
= else if 0 < 1 & 1 <= 1 {
- .eq_list[`idx'].item `item'
= .eq_list[1].item freeparm

> _____ begin _eqspec.i
> tem
- version 9.2
- args item
- .check_eq_item_name item, `item'
= .check_eq_item_name item, freeparm

> _____ begin _eqspec._check_eq_item_n
> ame
- version 9.2
- capture syntax name(name=c_item) [, NAME DEPvars INDEPvars I
> F IN WGT OTHER NOCONS OFFset EXPosure FREEParM OPTions ]
- if c(rc) error 198
- if `:list sizeof other' {
= if 0 {
  local other other_markvars
}
- local item `name' `depvars' `indepvars' `if' `in' `wgt' `oth
> er' `nocons' `offset' `exposure' `freeparm' `options'
= local item freeparm
- if `:list sizeof item' != 1 {
= if 1 != 1 {
  error 198
}
- c_local `c_item' `item'
= c_local item freeparm

> _____ end _eqspec._check_eq_item_n
> ame
- local value ```.item'''
= local value ``0'''
- sreturn local value ```value'''
= sreturn local value ``0'''

```

```

        - class exit ``value''
        = class exit ``0''
    _____
> _____ end _eqspec.i
> tem _____
        - class exit ``s(value)''
        = class exit ``0''
    _____
> _____ end _eqlist
> .eq _____
    = local eq_freeparm1 0
    - local lhs `lhs' `depvars'
    = local lhs y_timing_max
    - local eq_names `eq_names' `eq'
    = local eq_names y_timing_max
    - local nxvars :list sizeof eq_rhs`i'
    = local nxvars :list sizeof eq_rhs1
    - local TMP : copy local eq_rhs`i'
    = local TMP : copy local eq_rhs1
    - forval j = 1/`nxvars' {
    = forval j = 1/3 {
    - gettoken xvar TMP : TMP
    - local colna ``colna' `eq':`xvar''
    = local colna `` y_timing_max:rule_g''
    - }
    - gettoken xvar TMP : TMP
    - local colna ``colna' `eq':`xvar''
    = local colna `` y_timing_max:rule_g y_timing_max:rule_itr''
    - }
    - gettoken xvar TMP : TMP
    - local colna ``colna' `eq':`xvar''
    = local colna `` y_timing_max:rule_g y_timing_max:rule_itr y_timing_
> max:estimated''
    - }
    - if `eq_freeparm`i' {
    = if 0 {
        if `nxvars' {
            di as err "{it:xvars} not allowed with option {bf:freeparm}"
            exit 198
        }
        if strpos(`eq', ":") {
            local colna ``colna' /\`eq''
        }
        else {
            local colna ``colna' /\`eq''
        }
    }

```



```

    }
    - else if !`eq_nocons`i'' {
    = else if !0 {
    - local colna ``colna' `eq':_cons''
    = local colna `` y_timing_max:rule_g y_timing_max:rule_itr y_timing_
> max:estimated y_timing_max:_cons''
    - }
    - if ``moptobj'' != "" {
    = if "" != "" {
        if ``eq_offset`i'' != "" {
            if usubstr("eq_offset`i'",1,2)=="__" {
                capture clonevar `moptobj'`eq_offset`i' = `eq_offset`i'
                local dropmetoo `dropmetoo' `moptobj'`eq_offset`i'
            }
        }
    }
    - }
    - if ``moptobj'' != "" {
    = if "" != "" {
        foreach y of local lhs {
            if usubstr("`y'",1,2)=="__" {
                capture clonevar `moptobj'`y' = `y'
                local tmp `tmp' `moptobj'`y'
                local dropmetoo `dropmetoo' `moptobj'`y'
            }
            else {
                local tmp `tmp' `y'
            }
        }
        local lhs `tmp'
    }
    - if `waldtest' > 0 & `:length local lf0' {
    = if -1 > 0 & 20 {
        opts_exclusive "waldtest() lf0()"
    }
    - if `:length local continue' {
    = if 0 {
        if !`:length local init' {
            tempname init
            local ub0 `init'
        }
        else tempname ub0
        mat `ub0' = e(b)
        tempname v0 iv0
        mat `v0' = e(V)
        mat `iv0' = syminv(`v0')
    }

```

```

global ML_rank0 = colsof(`v0') - diag0cnt(`iv0')
if !':length local lf0' & !missing(e(ll)) {
local lf0 `=colsof(`ub0')' `e(ll)'
}
local ub0
}
- if `:length local init' {
= if 8 {
- tempname b0
- local dim : list sizeof colna
- matrix `b0' = J(1,`dim',0)
= matrix __000007 = J(1,4,0)
- matrix colna `b0' = `colna'
= matrix colna __000007 = y_timing_max:rule_g y_timing_max:rule_itr
> y_timing_max:estimated y_timing_max:_cons
- `vv' _mkvec `b0', from(`init') update first error("initial vector"
> )
= version 18.5: _mkvec __000007, from(__000004) update first error("
> initial vector")
_____
> _____ begin _mk
> vec _____
- local vv : display "version " string(_caller()) ":"
- version 6
- gettoken matout 0 : 0, parse(", ")
- if "`matout'"==" | "`matout'"=="," {
= if "__000007"==" | "__000007"=="," {
error 198
}
- syntax [, FROM(str) UPdate COLnames(str) ERRor(str) FIRST ]
- if "`update'"!=" {
= if "update"!=" {
- if "`colname'"!=" {
= if ""!=" {
di in red "update and colnames() cannot both be " "specified"
exit 198
}
- capture local colname : colfullnames `matout'
= capture local colname : colfullnames __000007
- if _rc {
di in red "matrix `matout' not found"
exit 111
}
- if rowsof(matrix(`matout')) != 1 {
= if rowsof(matrix(__000007)) != 1 {
di in red "`matout' matrix to be updated must be " "a row vector

```

```

> "
    exit 503
    }
- local matin `matout'
= local matin __000007
- }
- if ``error''!= "" {
= if `"initial vector''!= "" {
- local error ``error': ''
= local error `"initial vector: ''
- }
- tempname mat
- if ``from''!= "" {
= if `__000004''!= "" {
- From `from'
= From __000004
}

> _____ begin _mkvec.F
> rom _____
    - gettoken from 0 : 0, parse(",") bind
    - sret clear
    - sret local from `from'
    = sret local from __000004
    - if ``0''!= "" {
    = if `''!= "" {
        syntax [, COPY SKIP ]
    }
    - sret local copy `copy'
    = sret local copy
    - sret local skip `skip'
    = sret local skip
}

> _____ end _mkvec.F
> rom _____
    - local copy `s(copy)'
    = local copy
    - local skip `s(skip)'
    = local skip
    - if ``copy''!= "" {
    = if `''!= "" {
        CopyMat `mat' ``error'' `s(from)'
        if ``colname''!= "" {
            local dim : list sizeof colname
            if `dim' != colsof(matrix(`mat')) {
                di in red ``error'matrix must '' `be dimension '' `dim'
            exit 503
        }
    }
}

```

```

    }
    `vv' mat colnames `mat' = `colname'
  }
}
- else {
- `vv' BuildMat `mat' ``error'"" ""skip'"" `s(from)'
= version 18.5: BuildMat __000008 ``initial vector: "" "" __000004

```

```

> _____ begin _mkvec.Build
> Mat _____
    - local vv : display "version " string(_caller()) ":"
    - version 6
    - args matall error skip
    - macro shift 3
    - tokenize ``*''', parse(" =")
    = tokenize ``__000004'', parse(" =")
    - tempname matadd
    - local i 1
    - while ``i'!='' {
    = while "__000004"!='' {
    - local k = `i' + 1
    = local k = 1 + 1
    - if ``k'=='=' {
    = if "=="=" {
      local j = `i' + 2
      `vv' MkMat `matadd' ``i' ``j' `skip'
      local i = `i' + 3
    }
    - else {
    - ChkMat `matadd' ``i' ``error'""
    = ChkMat __000009 __000004 ``initial vector: ""

```

```

> _____ begin _mkvec.Chk
> Mat _____
    - args matout matin error
    - capture di matrix(`matin'[1,1])
    = capture di matrix(__000004[1,1])
    - if _rc {
      capture confirm number `matin'
      if _rc {
        di in red ``error'matrix `matin' not found''
        exit 111
      }
      di in red ``error'list of numbers requires copy option''
      exit 198
    }

```

```

- if matrix(rowsof(`matin`)!=1 & colsof(`matin`)!=1) {
= if matrix(rowsof(__000004)!=1 & colsof(__000004)!=1) {
  di in red "`matin' " matrix(rowsof(`matin`)) " x " matrix(co
> lsof(`matin`)) " is not a vector"
  exit 503
}
- if matrix(rowsof(`matin`)) == 1 {
= if matrix(rowsof(__000004)) == 1 {
- mat `matout' = `matin'
= mat __000009 = __000004
- }
- else mat `matout' = `matin''
= else mat __000009 = __000004'
}

> _____ end _mkvec.Chk
> Mat _____
- local i = `i' + 1
= local i = 1 + 1
- }
- mat `matall' = nullmat(`matall') , `matadd'
= mat __000008 = nullmat(__000008) , __000009
- }
- while ""`i'""!=" " {
= while ""!=" " {
  local k = `i' + 1
  if ""`k'""==" " {
    local j = `i' + 2
    `vv' MkMat `matadd' ``i' ``j' `skip'
    local i = `i' + 3
  }
  else {
    ChkMat `matadd' ``i' ``error'
    local i = `i' + 1
  }
  mat `matall' = nullmat(`matall') , `matadd'
}

> _____ end _mkvec.Build
> Mat _____
- if ``colname'""!=" " {
= if ``y_timing_max:rule_g y_timing_max:rule_itr y_timing_max:esti
> mated y_timing_max:_cons'""!=" " {
- `vv' ChkNames `mat' "`matin'" ``colname'"" ``error'"" `skip'
> "`first'"
= version 18.5: ChkNames __000008 "__000007" ``y_timing_max:rule_g
> y_timing_max:rule_itr y_timing_max:estimated y_timing_max:_cons' ``initial

```

```

> vector: '' "" "first"
> _____ begin _mkvec.ChkNa
> mes _____
    - local vv : display "version " string(_caller()) ":"
    - version 6
    - args mat matin names error skip first
    - local dim = colsof(matrix(`mat`))
    = local dim = colsof(matrix(__000008))
    - if "`first'"!="" {
    = if "first"!=" {
    - gettoken name : names
    - local eq1 = bsubstr("`name'",1,index("`name'",":"))
    = local eq1 = bsubstr("`y_timing_max:rule_g'",1,index("`y_timing
> _max:rule_g'",":"))
    - }
    - tempname new fill x
    - local k : list sizeof names
    - if "`matin'"!="" {
    = if "__000007"!=" {
    - mat `new' = `matin'
    = mat __000009 = __000007
    - }
    - else {
      mat `new' = J(1,`k',0)
      `vv' mat colnames `new' = `names'
    }
    - mat `fill' = J(1,`k',0)
    = mat __00000A = J(1,4,0)
    - local i 1
    - while `i' <= `dim' {
    = while 1 <= 4 {
    - mat `x' = `mat'[1,`i'..`i']
    = mat __00000B = __000008[1,1..1]
    - local eq : coleq `x'
    = local eq : coleq __00000B
    - local name : colname `x'
    = local name : colname __00000B
    - if "`eq'" == "/" {
    = if "_" == "/" {
      local spec "/"`name'"
    }
    - else {
    - local spec "`eq':`name'"
    = local spec "_:rule_g"
    - if (usubstr("`eq'",1,1) != "/") {

```

```

= if (usubstr("_",1,1) != "/") {
- local sspec "/`eq':`name'"
= local sspec "/_:rule_g"
- }
- }
- local oname
- local ospec
- capture _msparse `name', noomit
= capture _msparse rule_g, noomit
- if c(rc) == 0 {
- if r(omit) {
  local oname ``r(stripe)''
  local ospec ``eq':`oname'
  }
- }
- `vv' local j = colnumb(`new',``spec'')
= version 18.5: local j = colnumb(__000009,``_:rule_g'')
- if `j' == . & ``oname' != "" {
= if 1 == . & "" != "" {
  `vv' local j = colnumb(`new',``ospec'')
  }
- if `j' == . & ``sspec' != "" {
= if 1 == . & "/_:rule_g" != "" {
  `vv' local j = colnumb(`new',``sspec'')
  }
- if `j'==. & ``eq'=="_" & ``eq1'!="" {
= if 1==. & ``_'=="_" & ``y_timing_max:'!="" {
  `vv' local j = colnumb(`new',``eq1`name'')
  if `j' == . & ``oname' != "" {
    `vv' local j = colnumb(`new',``eq1`oname'')
  }
}
- if `j'!=. {
= if 1!=. {
- if `fill'[1,`j'] {
= if __00000A[1,1] {
  _ms_parse_parts `name'
  if !r(omit) {
    if ``eq'=="_" {
      di in red ``error'duplicate '' ``entries for `name' found''
    }
    else di in red ``error'' ``duplicate entries for `eq':`name'
> found''
  }
  exit 507
}
else if !missing(`new'[1,`j']) {

```

```

        matrix `mat'[1,`i'] = `new'[1,`j']
    }
}
- else mat `fill'[1,`j'] = 1
= else mat __00000A[1,1] = 1
- mat `new'[1,`j'] = `mat'[1,`i']
= mat __000009[1,1] = __000008[1,1]
- }
- else if "`skip'"==" {
= else if ""==" {
    if "`eq'"=="_" {
        local spec : copy local name
    }
    di in red ``error'extra parameter "' `"'spec' found"' _n "spe
> cify skip option if necessary"
    exit 111
}
- local i = `i' + 1
= local i = 1 + 1
- }
- while `i' <= `dim' {
= while 2 <= 4 {
- mat `x' = `mat'[1,`i'..`i']
= mat __00000B = __000008[1,2..2]
- local eq : coleq `x'
= local eq : coleq __00000B
- local name : colname `x'
= local name : colname __00000B
- if "`eq'" == "/" {
= if "_" == "/" {
    local spec "/"`name'
}
- else {
- local spec "`eq':`name'
= local spec "._:rule_itr"
- if (usubstr("`eq'",1,1) != "/") {
= if (usubstr("_",1,1) != "/") {
- local sspec "/"`eq':`name'
= local sspec "._:rule_itr"
- }
- }
- local oname
- local ospec
- capture _msparse `name', noomit
= capture _msparse rule_itr, noomit
- if c(rc) == 0 {

```



```

- if r(omit) {
  local oname ``r(stripe)''
  local ospec ``eq':`oname''
}
- }
- `vv' local j = colnumb(`new',``spec'')
= version 18.5: local j = colnumb(__000009,``_:rule_itr'')
- if `j' == . & ``oname'' != "" {
= if 2 == . & "" != "" {
  `vv' local j = colnumb(`new',``ospec'')
}
- if `j' == . & ``sspec'' != "" {
= if 2 == . & "/_:rule_itr" != "" {
  `vv' local j = colnumb(`new',``sspec'')
}
- if `j'==. & ``eq''=="_" & ``eq1''!="" {
= if 2==. & ``_''=="_" & ``y_timing_max:''!="" {
  `vv' local j = colnumb(`new',``eq1``name'')
  if `j' == . & ``oname'' != "" {
    `vv' local j = colnumb(`new',``eq1``oname'')
  }
}
- if `j'!=. {
= if 2!=. {
- if `fill'[1,`j'] {
= if __00000A[1,2] {
  _ms_parse_parts `name'
  if !r(omit) {
    if ``eq''=="_" {
      di in red ``error'duplicate '' ``entries for `name' found''
    }
    else di in red ``error'' ``duplicate entries for `eq':`name'
> found''

  exit 507
}
else if !missing(`new'[1,`j']) {
  matrix `mat'[1,`i'] = `new'[1,`j']
}
}
- else mat `fill'[1,`j'] = 1
= else mat __00000A[1,2] = 1
- mat `new'[1,`j'] = `mat'[1,`i']
= mat __000009[1,2] = __000008[1,2]
- }
- else if ``skip''="" {
= else if ""="" {

```

```

        if "`eq'"=="_" {
            local spec : copy local name
        }
        di in red `"'error'extra parameter "' `"'spec' found"' _n "spe
> cify skip option if necessary"
        exit 111
    }
    - local i = `i' + 1
    = local i = 2 + 1
    - }
    - while `i' <= `dim' {
    = while 3 <= 4 {
    - mat `x' = `mat'[1,`i'..`i']
    = mat __00000B = __000008[1,3..3]
    - local eq : coleq `x'
    = local eq : coleq __00000B
    - local name : colname `x'
    = local name : colname __00000B
    - if "`eq'" == "/" {
    = if "_" == "/" {
        local spec "/"`name'
    }
    - else {
    - local spec "`eq':`name'
    = local spec "_:estimated"
    - if (usubstr("`eq'",1,1) != "/") {
    = if (usubstr("_",1,1) != "/") {
    - local sspec "/"`eq':`name'
    = local sspec "/_:estimated"
    - }
    - }
    - local oname
    - local ospec
    - capture _msparse `name', noomit
    = capture _msparse estimated, noomit
    - if c(rc) == 0 {
    - if r(omit) {
        local oname `"'r(stripe)'"
        local ospec "`eq':`oname'
    }
    - }
    - `vv' local j = colnumb(`new',`"'spec'')
    = version 18.5: local j = colnumb(__000009,`"_:estimated'')
    - if `j' == . & "`oname'" != "" {
    = if 3 == . & "" != "" {
        `vv' local j = colnumb(`new',`"'ospec'')

```

```

    }
- if `j' == . & "`sspec'" != "" {
= if 3 == . & "/_:estimated" != "" {
  `vv' local j = colnumb(`new', "`sspec'")
}
- if `j'==. & "`eq'"=="_" & "`eq1'"!="" {
= if 3==. & "`_"=="_" & "`y_timing_max:'"!="" {
  `vv' local j = colnumb(`new', "`eq1`name'")
  if `j' == . & "oname'" != "" {
    `vv' local j = colnumb(`new', "`eq1`oname'")
  }
}
- if `j'!=. {
= if 3!=. {
- if `fill'[1,`j'] {
= if __00000A[1,3] {
  _ms_parse_parts `name'
  if !r(omit) {
    if "`eq'"=="_" {
      di in red "`error'duplicate '" "`entries for `name' found"
    }
    else di in red "`error'" "`duplicate entries for `eq':`name'
> found"

    exit 507
  }
  else if !missing(`new'[1,`j']) {
    matrix `mat'[1,`i'] = `new'[1,`j']
  }
}
- else mat `fill'[1,`j'] = 1
= else mat __00000A[1,3] = 1
- mat `new'[1,`j'] = `mat'[1,`i']
= mat __000009[1,3] = __000008[1,3]
- }
- else if "`skip'"=="" {
= else if ""=="" {
  if "`eq'"=="_" {
    local spec : copy local name
  }
  di in red "`error'extra parameter '" "`spec' found" _n "spe
> cify skip option if necessary"
  exit 111
}
- local i = `i' + 1
= local i = 3 + 1
- }

```

```

- while `i' <= `dim' {
= while 4 <= 4 {
- mat `x' = `mat'[1,`i'..`i']
= mat __00000B = __000008[1,4..4]
- local eq : coleq `x'
= local eq : coleq __00000B
- local name : colname `x'
= local name : colname __00000B
- if "`eq'" == "/" {
= if "_" == "/" {
    local spec "/"`name'
  }
- else {
- local spec "`eq':`name'"
= local spec ":_cons"
- if (usubstr("`eq'",1,1) != "/") {
= if (usubstr("_",1,1) != "/") {
- local sspec "/"`eq':`name'"
= local sspec "/_:_cons"
- }
- }
- local oname
- local ospec
- capture _msparse `name', noomit
= capture _msparse _cons, noomit
- if c(rc) == 0 {
- if r(omit) {
    local oname ``r(stripe)''
    local ospec "`eq':`oname'"
  }
- }
- `vv' local j = colnumb(`new',``spec'')
= version 18.5: local j = colnumb(__000009,``:_cons'')
- if `j' == . & "`oname'" != "" {
= if 4 == . & "" != "" {
    `vv' local j = colnumb(`new',``ospec'')
  }
- if `j' == . & "`sspec'" != "" {
= if 4 == . & "/_:_cons" != "" {
    `vv' local j = colnumb(`new',``sspec'')
  }
- if `j'==. & ``eq'""=="_" & ``eq1'""!="" {
= if 4==. & ``_'"=="_" & ``y_timing_max:'""!="" {
    `vv' local j = colnumb(`new',``eq1``name'')
    if `j' == . & "`oname'" != "" {
      `vv' local j = colnumb(`new',``eq1``oname'')
    }
  }
}

```

```

    }
    }
- if `j'!=. {
= if 4!=. {
- if `fill'[1,`j'] {
= if __00000A[1,4] {
    _ms_parse_parts `name'
    if !r(omit) {
    if "`eq'"=="_" {
    di in red `""`error'duplicate "' `"'entries for `name' found"'
    }
    else di in red `""`error'""' `"'duplicate entries for `eq':`name'
> found"'

    exit 507
    }
    else if !missing(`new'[1,`j']) {
    matrix `mat'[1,`i'] = `new'[1,`j']
    }
    }
- else mat `fill'[1,`j'] = 1
= else mat __00000A[1,4] = 1
- mat `new'[1,`j'] = `mat'[1,`i']
= mat __000009[1,4] = __000008[1,4]
- }
- else if "`skip'"==" " {
= else if ""==" " {
    if "`eq'"=="_" {
    local spec : copy local name
    }
    di in red `""`error'extra parameter "' `""`spec' found"' _n "spe
> cify skip option if necessary"
    exit 111
    }
- local i = `i'+ 1
= local i = 4 + 1
- }
- while `i' <= `dim' {
= while 5 <= 4 {
    mat `x' = `mat'[1,`i'..`i']
    local eq : coleq `x'
    local name : colname `x'
    if "`eq'" == "/" {
    local spec "/"`name'
    }
    else {
    local spec "`eq':`name'"

```

```

if (usubstr("`eq'",1,1) != "/") {
  local sspec "/"`eq':`name'
}
}
local oname
local ospec
capture _msparse `name', noomit
if c(rc) == 0 {
  if r(omit) {
    local oname ``r(stripe)''
    local ospec ``eq':`oname'
  }
}
`vv' local j = colnumb(`new',``spec'')
if `j' == . & ``oname' != "" {
  `vv' local j = colnumb(`new',``ospec'')
}
if `j' == . & ``sspec' != "" {
  `vv' local j = colnumb(`new',``sspec'')
}
if `j'==. & ``eq'=="_" & ``eq1'!="" {
  `vv' local j = colnumb(`new',``eq1``name'')
  if `j' == . & ``oname' != "" {
    `vv' local j = colnumb(`new',``eq1``oname'')
  }
}
if `j'!=. {
  if `fill'[1,`j'] {
    _ms_parse_parts `name'
    if !r(omit) {
      if "`eq'=="_" {
        di in red ``error'duplicate "" ``entries for `name' found''
      }
      else di in red ``error'' ``duplicate entries for `eq':`name'
    }
  }
  exit 507
}
else if !missing(`new'[1,`j']) {
  matrix `mat'[1,`i'] = `new'[1,`j']
}
}
else mat `fill'[1,`j'] = 1
mat `new'[1,`j'] = `mat'[1,`i']
}
else if ``skip'==" " {
  if "`eq'=="_" {

```

> found''

```

        local spec : copy local name
    }
    di in red ``error'extra parameter "' ``spec' found"' _n "spe
> cify skip option if necessary"
    exit 111
    }
    local i = `i' + 1
    }
    - mat `fill' = `fill'*`fill''
    = mat __00000A = __00000A*__00000A'
    - sret clear
    - sret local k_fill = `fill'[1,1]
    = sret local k_fill = __00000A[1,1]
    - mat `mat' = `new'
    = mat __000008 = __000009



---


> _____ end _mkvec.ChkNa
> mes _____
    - local fill `s(k_fill)'
    = local fill 4
    - }
    - }
    - }
    - else {
        local fill 0
        if ``update'!='' {
            mat `mat' = `matin'
        }
        else if ``colname'!='' {
            local dim : list sizeof colname
            mat `mat' = J(1,`dim',0)
            `vv' mat colnames `mat' = `colname'
        }
        else {
            di in red "from() must be specified"
            exit 198
        }
    }
    - sret clear
    - sret local copy `copy'
    = sret local copy
    - sret local skip `skip'
    = sret local skip
    - sret local k = colsof(matrix(`mat'))
    = sret local k = colsof(matrix(__000008))
    - if ``fill'!='' {

```

```

= if "4"!=" {
- sret local k_fill `fill'
= sret local k_fill 4
- }
- else sret local k_fill = colsof(matrix(`mat'))
= else sret local k_fill = colsof(matrix(__000008))
- matrix rename `mat' `matout', replace
= matrix rename __000008 __000007, replace

```

```

> _____ end _mk
> vec _____
- }
- tempname bomit
- matrix `bomit' = J(1,`:list sizeof colna',0)
= matrix __000008 = J(1,4,0)
- matrix colna `bomit' = `colna'
= matrix colna __000008 = y_timing_max:rule_g y_timing_max:rule_itr
> y_timing_max:estimated y_timing_max:_cons
- _ms_omit_info `bomit'
= _ms_omit_info __000008
- if r(k_omit) | `:length local constraints' {
= if r(k_omit) | 0 {
nobreak {
capture noisily break {
_b_post0 `colna'
local clist : subinstr local constraints "," " ", all
`vv' makecns `clist', `cnsnotes'
local constraints ``r(clist)'''
local k_autoCns = e(k_autoCns)
tempname C
capture matrix `C' = e(Cns)
local rcc = c(rc)
}
local rc = c(rc)
ereturn clear
}
if (`rc') exit `rc'
if (`rcc') {
local C
local k_autoCns
}
}
- if `:length local constraints' {
= if 0 {
local lf0
}
}

```



```

- local vce `vce' `robust' `cluster'
= local vce vce(robust)
- if `:length local vce' {
= if 11 {
- _vce_parse, argoptlist(CLuster) optlist(OIM OPG Robust) old : `wt'
> , `vce'
= _vce_parse, argoptlist(CLuster) optlist(OIM OPG Robust) old : , vc
> e(robust)
_____
> _____ begin _vce_pa
> rse _____
- version 10
- _on_colon_parse `0'
= _on_colon_parse , argoptlist(CLuster) optlist(OIM OPG Robust) ol
> d : , vce(robust)
_____
> _____ begin _on_colon_pa
> rse _____
- version 8.2
- sreturn local before ""
- sreturn local after ""
- gettoken before after : 0, parse(":") bind match(par) quotes
- if "`par'" != "" {
= if "" != "" {
local before `("`before')"'
}
- if ``"before"' == ":" {
= if `", argoptlist(CLuster) optlist(OIM OPG Robust) old "" == "
> ":" {
sreturn local after ``"after"'
exit
}
- while ``COLON'" != ":" & ``"after'" != "" {
= while `""' != ":" & `": , vce(robust)'" != "" {
- gettoken COLON after : after, parse(":") bind match(par) quote
> s
- if "`par'" != "" {
= if "" != "" {
local before `before' (`COLON')
local COLON
}
- else if ``COLON'" != ":" {
= else if `":'" != ":" {
local before ``before' `COLON'"
local COLON
}

```

```

- }
- while `""COLON"" != ":" & `""after"" != "" {
= while `":"" != ":" & `", vce(robust)"" != "" {
  gettoken COLON after : after, parse(":") bind match(par) quote
> s
    if "`par'" != "" {
      local before `before' (`COLON')
      local COLON
    }
    else if `""COLON"" != ":" {
      local before `""before' `COLON""
      local COLON
    }
  }
- if `""COLON"" != ":" {
= if `":"" != ":" {
  di as err ""' found where ':' expected"
  exit 198
}
- sreturn local before `""before""
= sreturn local before `", argoptlist(CLuster) optlist(OIM OPG R
> obust) old ""
  - sreturn local after `""after""
  = sreturn local after `", vce(robust)""
}
}
> _____ end _on_colon_pa
> rse _____
  - local 0 `""s(before)""
  = local 0 `", argoptlist(CLuster) optlist(OIM OPG Robust) old ""
  - local user `""s(after)""
  = local user `", vce(robust)""
  - syntax [varname(default=none)], [ OPTlist(namelist) ARGOPTlist(n
> amelist) Pwallowed(namelist) OLD_is_ok NOARGOPT_is_ok ]
  - local touse `varlist'
  = local touse
  - tempname o a
  - `o' = ._optlist.new
  = __000009 = ._optlist.new
  - local optlist : list uniq optlist
  - foreach name of local optlist {
  - `o'.addopt `name'
  = __000009.addopt OIM
}
}
> _____ begin _optlist.add
> opt _____
  - version 9

```

```

- syntax name(name=optspec) [, PASSthru]
- local mname = lower("`optspec'")
= local mname = lower("OIM")
- if "`passthru'" != "" {
= if "" != "" {
    local optspec `optspec'(passthru)
  }
- .options.Arrpush "`optspec'"
= .options.Arrpush "OIM"
- .names.Arrpush "`mname'"
= .names.Arrpush "oim"

```

```

> _____ end _optlist.add
> opt _____
    - }
    - .`o'.addopt `name'
    = .__000009.addopt OPG

```

```

> _____ begin _optlist.add
> opt _____
    - version 9
    - syntax name(name=optspec) [, PASSthru]
    - local mname = lower("`optspec'")
    = local mname = lower("OPG")
    - if "`passthru'" != "" {
    = if "" != "" {
        local optspec `optspec'(passthru)
      }
    - .options.Arrpush "`optspec'"
    = .options.Arrpush "OPG"
    - .names.Arrpush "`mname'"
    = .names.Arrpush "opg"

```

```

> _____ end _optlist.add
> opt _____
    - }
    - .`o'.addopt `name'
    = .__000009.addopt Robust

```

```

> _____ begin _optlist.add
> opt _____
    - version 9
    - syntax name(name=optspec) [, PASSthru]
    - local mname = lower("`optspec'")
    = local mname = lower("Robust")
    - if "`passthru'" != "" {

```

```

        = if "" != "" {
            local optspec `optspec'(passthru)
        }
        - .options.Arrpush "`optspec'"
        = .options.Arrpush "Robust"
        - .names.Arrpush "`mname'"
        = .names.Arrpush "robust"
    }
> ----- end _optlist.add
> opt
    - }
    - .`a' = ._optlist.new
    = __00000A = ._optlist.new
    - local argoptlist : list uniq argoptlist
    - foreach name of local argoptlist {
        - .`a'.addopt `name'
    = __00000A.addopt CLuster
    }
> ----- begin _optlist.add
> opt
    - version 9
    - syntax name(name=optspec) [, PASSthru]
    - local mname = lower("`optspec'")
    = local mname = lower("CLuster")
    - if "`passthru'" != "" {
    = if "" != "" {
        local optspec `optspec'(passthru)
    }
    - .options.Arrpush "`optspec'"
    = .options.Arrpush "CLuster"
    - .names.Arrpush "`mname'"
    = .names.Arrpush "cluster"
    }
> ----- end _optlist.add
> opt
    - }
    - local OPTNAMES ```.`o'.dumpnames'''
    }
> ----- begin _optlist.dumpna
> mes
    - version 9
    - forval i = 1/`.names.arnels' {
    = forval i = 1/3 {
        - local namelist `namelist' `.names['i']'
    = local namelist oim
    - }

```

```

- local namelist `namelist' `.names['i']'
= local namelist oim opg
- }
- local namelist `namelist' `.names['i']'
= local namelist oim opg robust
- }
- local namelist : list uniq namelist
- sreturn local namelist ``namelist'''
= sreturn local namelist `oim opg robust'
- class exit ``namelist'''
= class exit `oim opg robust'

> _____ end _optlist.dumpna
> mes _____
= local OPTNAMES `oim opg robust'
- local ARGOPTNAMES ```.a'.dumpnames'''

> _____ begin _optlist.dumpna
> mes _____
- version 9
- forval i = 1/`.names.arnels' {
= forval i = 1/1 {
- local namelist `namelist' `.names['i']'
= local namelist cluster
- }
- local namelist : list uniq namelist
- sreturn local namelist ``namelist'''
= sreturn local namelist `cluster'
- class exit ``namelist'''
= class exit `cluster'

> _____ end _optlist.dumpna
> mes _____
= local ARGOPTNAMES `cluster'
- local AND : list OPTNAMES & ARGOPTNAMES
- if `:list sizeof AND' {
= if 0 {
di as err "vcetype `:word 1 of `AND'' specified twice"
exit 198
}
- local pwallowed : list uniq pwallowed
- local pwlist robust cluster
- foreach n of local pwallowed {
local lc = lower("`n'")
local pwlist `pwlist' `lc'
}

```

```

- if "`old_is_ok'" != "" {
= if "old_is_ok" != "" {
- local ROBUST robust
- if `:list ROBUST in OPTNAMES' {
= if 1 {
- local robust Robust
- }
- local CLUSTER cluster
- if `:list CLUSTER in ARGOPTNAMES' {
= if 1 {
- local cluster CLuster(varname)
- }
- }
- local 0 ``user'''
= local 0 `` , vce(robust)'''
- syntax [fw aw pw iw] [, VCE(string asis) `robust' `cluster' ]
= syntax [fw aw pw iw] [, VCE(string asis) Robust CLuster(varname)

> ]

- if ``vce''' != "" {
= if ``robust''' != "" {
- gettoken name args : vce, parse(" ,")
- local args : list retok args
- capture ParseVCE `o' `a' , `name'
= capture ParseVCE __000009 __00000A , robust

> _____ begin _vce_parse.Parse
> VCE _____
- gettoken 0 0 : 0, parse(" ,")
- gettoken A 0 : 0, parse(" ,")
- local OPTSPECS ```. `0'.dumpoptions' `.`A'.dumpoptions'''

> _____ begin _optlist.dumpopti
> ons _____
- version 9
- forval i = 1/`.options.arnels' {
= forval i = 1/3 {
- local optlist `optlist' `.options[`i']'
= local optlist OIM
- }
- local optlist `optlist' `.options[`i']'
= local optlist OIM OPG
- }
- local optlist `optlist' `.options[`i']'
= local optlist OIM OPG Robust
- }
- local optlist : list uniq optlist

```

```

- sreturn local optlist ``optlist'''
= sreturn local optlist ``OIM OPG Robust'''
- class exit ``optlist'''
= class exit ``OIM OPG Robust'''

> _____ end _optlist.dumpopti
> ons _____

> _____ begin _optlist.dumpopti
> ons _____
- version 9
- forval i = 1/`.options.arnels' {
= forval i = 1/1 {
- local optlist `optlist' `.options['i']'
= local optlist CCluster
- }
- local optlist : list uniq optlist
- sreturn local optlist ``optlist'''
= sreturn local optlist ``CCluster'''
- class exit ``optlist'''
= class exit ``CCluster'''

> _____ end _optlist.dumpopti
> ons _____
= local OPTSPECS ``OIM OPG Robust CCluster'''
- local OPTNAMES ```. `O'.dumpnames' `.`A'.dumpnames'''

> _____ begin _optlist.dumpna
> mes _____
- version 9
- forval i = 1/`.names.arnels' {
= forval i = 1/3 {
- local namelist `namelist' `.names['i']'
= local namelist oim
- }
- local namelist `namelist' `.names['i']'
= local namelist oim opg
- }
- local namelist `namelist' `.names['i']'
= local namelist oim opg robust
- }
- local namelist : list uniq namelist
- sreturn local namelist ``namelist'''
= sreturn local namelist ``oim opg robust'''
- class exit ``namelist'''
= class exit ``oim opg robust'''

```

```

> _____ end _optlist.dumpna
> mes _____

> _____ begin _optlist.dumpna
> mes _____
    - version 9
    - forval i = 1/`.names.arnels' {
    = forval i = 1/1 {
    - local namelist `namelist' `.names[`i']'
    = local namelist cluster
    - }
    - local namelist : list uniq namelist
    - sreturn local namelist ``namelist'''
    = sreturn local namelist "cluster"
    - class exit ``namelist'''
    = class exit "cluster"

> _____ end _optlist.dumpna
> mes _____
    = local OPTNAMES `oim opg robust cluster"'
    - syntax [, `OPTSPECS']
    = syntax [, OIM OPG Robust CLuster]
    - foreach OPT of local OPTNAMES {
    - if ````OPT'''' != "" {
    = if `""' != "" {
      return local vce `OPT'
      continue, break
    }
    - }
    - if ````OPT'''' != "" {
    = if `""' != "" {
      return local vce `OPT'
      continue, break
    }
    - }
    - if ````OPT'''' != "" {
    = if "robust" != "" {
      return local vce `OPT'
    = return local vce robust
    - continue, break
    }
    }

> _____ end _vce_parse.Parse
> VCE _____

```



```

- if c(rc) {
  di as err "vcetype {bf:`name`} not allowed"
  exit 198
}
- local name `r(vce)'
= local name robust
- if "`weight'" == "pweight" & !`:list name in pwlist' {
= if "" == "pweight" & !1 {
  di as err "pweights are not allowed with vce(`name')"
  exit 198
}
- return add
- if ```robust'"" != "" & !inlist("`name'", "", "robust", "eim", "oim"
> , "cluster") {
= if ```` != "" & !inlist("robust", "", "robust", "eim", "oim", "cluste
> r") {
  opts_exclusive "`robust' vce(`name')"
}
- if "`name'" == "cluster" {
= if "robust" == "cluster" {
  if ```args'"" == "" {
    di as err "invalid vce(cluster) option"
    exit 198
  }
  confirm var `args'
  unab args : `args'
  local markout `args'
  if "`cluster'" != "" {
    if !`:list args == cluster' {
      di as err "options cluster() and vce(cluster) are in conflict"
      exit 100
    }
  }
}
- else if "`cluster'" != "" & !inlist("`name'", "eim", "oim") {
= else if "" != "" & !inlist("robust", "eim", "oim") {
  opts_exclusive "cluster() vce(`name')"
}
- if ```args'"" != "" {
= if ```` != "" {
  if !`:list name in ARGOPTNAMES' {
    di as err "invalid vce() option"
    exit 198
  }
  if "`name'" == "hc2" {
    confirm var `args'

```

```

unab args : `args'
local markout `args'
}
return local vceargs ```:list retok args'''
}
- else if `:list name in ARGOPTNAMES' {
= else if 0 {
  if "`noargopt_is_ok'" == "" {
    di as err "invalid vce() option"
    exit 198
  }
}
- }
- else {
  if "`weight'" == "pweight" | "`robust'" != "" {
    local vce robust
  }
  if "`cluster'" != "" {
    local vce cluster
    local args `cluster'
    local markout `cluster'
  }
  return local vce ```:vce'''
  return local vceargs ```:args'''
}
- if "`return(vce)'" != "" {
= if "robust" != "" {
- if ```:return(vceargs)''' != "" {
= if `''' != "" {
  local ss " "
}
- return local vceopt `"vce(`return(vce)''ss'`return(vceargs)')'"
= return local vceopt `"vce(robust)'"
- }
- if "`return(vce)'" == "cluster" {
= if "robust" == "cluster" {
  return local cluster `return(vceargs)'
}
- if inlist("`return(vce)'", "robust", "cluster") {
= if inlist("robust", "robust", "cluster") {
- return local robust robust
- }
- if "`touse'" != "" {
= if "" != "" {
  if "`markout'" != "" {
    markout `touse' `markout', strok

```

```

    }
    }
}


---


> end _vce_pa
> rse
    - local vce `r(vce)'
    = local vce robust
    - }
    - else if "`weight'" == "pweight" {
    = else if "" == "pweight" {
        local vce robust
    }
    - if `:length local svy' {
    = if 0 {
        local vce svy
    }
    - if ``"vce"' == "cluster" {
    = if `"robust"' == "cluster" {
        local cluster `r(cluster)'
        markout $ML_sample `cluster', strok
    }
    - if `:length local group' {
    = if 0 {
        markout $ML_sample `group', strok
        global ML_group : copy local group
        if bsubstr("`type `group'",1,3) == "str" {
            if `interactive' {
                SetGlobalVar ML_grp : _MLgr
            }
            else {
                global ML_grp : tempvar
                if ``moptobj'" != "" {
                    global ML_grp `moptobj'$ML_grp
                }
            }
            quietly egen $ML_grp = group(`group')
            if ! `:length local cluster' {
                local cluster : copy global ML_grp
            }
        }
        else {
            if ! `:length local cluster' {
                local cluster : copy global ML_group
            }
        }
    }
}

```

```

- if "$ML_samp" != "$ML_sample" {
= if "__000005" != "__000005" {
  quietly replace $ML_samp = 0 if $ML_samp & $ML_sample == 0
}
- if `:length local vce' == 0 {
= if 6 == 0 {
  if ``technique''' == "bhhh" {
    local vce opg
  }
  else local vce oim
}
- if inlist("`vce'", "robust", "cluster") & bsubstr("`evaltype'",1,1
> ) == "d" {
= if inlist("robust", "robust", "cluster") & bsubstr("e2",1,1) == "d
> " {
  local optname = cond("`svy'"=="" ,"vce(`vce')","svy")
  di as err "option `optname' is not allowed with evaltype `evaltype
> '"
  exit 198
}
- if `:length local crittype' == 0 {
= if 0 == 0 {
- if inlist("`vce'", "cluster", "robust", "svy") {
= if inlist("robust", "cluster", "robust", "svy") {
- local crittype "log pseudolikelihood"
- }
- else local crittype "log likelihood"
- }
- global ML_waldtest `waldtest'
= global ML_waldtest -1
- if `:length local svy' | `:length local weight' {
= if 0 | 0 {
  if `interactive' {
    SetGlobalVar ML_w : _MLw
  }
  else {
    global ML_w : tempvar
    if ``moptobj''' != "" {
      global ML_w `moptobj'$ML_w
    }
  }
}
- if `:length local weight' {
= if 0 {
  if ``moptobj''' != "" {
    cap drop $ML_w

```

```

}
quietly gen double $ML_w `exp' if $ML_samp
local wtype ``weight'""
local wexp ``exp'""
global ML_wtyp : copy local wtype
global ML_wexp : copy local wexp
if "`wtype'" == "iweight" | "`svy'" != "" {
    local zeroweight zeroweight
}
}
- if inlist("`vce'", "svy", "cluster") {
= if inlist("robust", "svy", "cluster") {
    if `interactive' {
        SetGlobalVar ML_subv : _MLsu
    }
    else {
        global ML_subv : tempvar
        if ``moptobj'"" != "" {
            global ML_subv `moptobj'$ML_subv
        }
    }
}
- quietly count if $ML_sample
= quietly count if __000005
- if r(N) == 0 {
    error 2000
}
- if ``weight'"" != "" {
= if `""' != "" {
    quietly count if $ML_sample & $ML_w != 0
    if r(N) == 0 {
        di in gr "all observation have zero weights"
        exit 2000
    }
}
- if `:length local lf0' {
= if 20 {
- if `:list sizeof lf0' != 2 {
= if 2 != 2 {
    di as err "lf0(`lf0') invalid"
    exit 198
}
- global ML_k0 : word 1 of `lf0'
= global ML_k0 : word 1 of 1 -420.2971615663282
- global ML_ll_0 : word 2 of `lf0'
= global ML_ll_0 : word 2 of 1 -420.2971615663282

```

```

- confirm integer number $ML_k0
= confirm integer number 1
- confirm number $ML_ll_0
= confirm number -420.2971615663282
- if $ML_k0 < 0 {
= if 1 < 0 {
    di as err "lf0(`lf0') invalid"
    exit 198
  }
- }
- if "`obs'" == "" {
= if "" == "" {
- if "`wtype'" != "fweight" {
= if "" != "fweight" {
- quietly count if $ML_sample
= quietly count if __000005
- local obs = r(N)
- }
- else {
    sum $ML_w if $ML_sample, mean
    local obs = r(sum)
  }
- }
- if `:length local iterid' {
= if 0 {
    local iterid = trim(bsubstr("`iterid'",1,32))
  }
- if `:length local crittype' {
= if 20 {
- local crittype = trim(bsubstr("`crittype'",1,32))
= local crittype = trim(bsubstr("`log pseudolikelihood'",1,32))
- }
- if `:length local derivscale' {
= if 0 {
    confirm matrix `derivscale'
  }
- if `:length local derivh' {
= if 0 {
    confirm matrix `derivh'
  }
- local l : strlen local deriv
- ParseUsemin, `deriv' len(`l')
= ParseUsemin, len(0)

```

```

> _____ begin mopt.ParseUse
> min _____

```

```

- capture syntax [, LEN(integer 0), MIN1(numlist min=2 max=2 missi
> ngokay) NOMIN MIN]
- if (_rc) {
  syntax [, LEN(integer 0) MIN1(string) NOMIN MIN]
}
- if ``min1'' != "" & ``nomin'' != "" {
= if ``'' != "" & ``'' != "" {
  di as err "options {bf:min()} and {bf:nomin} are mutually exclus
> ive"
  exit 198
}
- if ``min1'' != "" & ``nomin'' != "" {
= if ``'' != "" & ``'' != "" {
  di as err "options {bf:min} and {bf:nomin} are mutually exclusiv
> e"
  exit 198
}
- if (``min1'' != "") {
= if (``'' != "") {
  if (_rc) {
    capture confirm matrix `min1'
    if (_rc) {
      di as err "option {bf:min()} requires that either two numbers or
> a 1X2 matrix be specified"
      exit 198
    }
  }
  local deriv `min1'
}
- else if (``min1'' != "") {
= else if (``'' != "") {
  if (`len' > length(``min1')) {
    di as err "option {bf:min()} requires that either two numbers or
> a 1X2 matrix be specified"
    exit 198
  }
  local deriv 1
}
- else {
- if (`len' > 0) {
= if (0 > 0) {
  if (``nomin' == "") {
    di as err "option {bf:min()} requires that either two numbers or
> a 1X2 matrix be specified"
    exit 198
  }
}

```

```

        else if (`len' > length(`"'nomin'"')) {
        di as err "options {bf:min()} and {bf:nomin} are mutually exclus
> ive"
        exit 198
        }
        else {
        local deriv 0
        }
        }
- else {
- local deriv 0
- }
- }
- sreturn local deriv `deriv'
= sreturn local deriv 0
_____
> _____ end mopt.ParseUse
> min _____
- local deriv = s(deriv)
- if `:length local gnwmatrix' {
= if 0 {
confirm matrix `gnwmatrix'
}
- `vv' mata: Mopt_model()
= version 18.5: mata: Mopt_model()
_____
> _____ begin mopt_check_prog
> ram _____
- version 10
- args name
- capture confirm name `name'
= capture confirm name poiss_lf
- if c(rc) {
di as err "unrecognized command: `name' invalid command name"
exit 199
}
- capture which `name'
= capture which poiss_lf
- if !c(rc) {
- exit
_____
> _____ end mopt_check_prog
> ram _____
- global ML_stat model
- if !`interactive' {
= if !0 {

```



```

- `vv' MaxMin `maxmin', nooutput `score' `options' moptobj(`moptobj'
> )
= version 18.5: MaxMin maximize, nooutput nolog search(off) moptobj
> ()

-----
> ----- begin mopt.Max
> Min -----
- local vv : di "version " string(_caller()) ":"
- version 12
- ChkMacros

-----
> ----- begin mopt.ChkMac
> ros -----
- if "$ML_stat" != "model" {
= if "model" != "model" {
di as err "you must issue -ml model- first"
exit 198
}
- capture confirm var $ML_samp $ML_w $ML_subv
= capture confirm var __000005 __000005
- if c(rc) {
di as err "Since issuing the -ml model- statement, you have do
> ne something to drop" _n "temporary variables ml added to your data. You mu
> st start again."
Clear
exit 111
}

-----
> ----- end mopt.ChkMac
> ros -----
- syntax name(name=maxmin) [, NEGH TOLerance(numlist max=1 >=0) LT
> OLerance(numlist max=1 >=0) NONRTOLerance NRTOLerance(numlist max=1 >=0) QTO
> Lerance(numlist max=1 >=0) GTOLerance(numlist max=1 >=0) ITERate(numlist max
> =1 >=0) NOTCONCAVE(numlist max=1 >=0) ndami DIFficult HALFSTEPonly DOOPT SEA
> rch(name) Repeat(passthru) Bounds(string) SCore(string) noWARNing noCLEAR NO
> LOf LOG DOTs SHOWTOLerance SHOWNRTolerance SHOWSTEP TRace COEFDIFFs GRADient
> HESSian noSKIPline noOUTput Level(cilevel) moptobj(string) * ]
- if `:length local nrtolerance' {
= if 0 {
opts_exclusive "nrtolerance() `nonrtolerance'"
}
- if `:length local qtolerance' {
= if 0 {
opts_exclusive "qtolerance() `nonrtolerance'"
}
- opts_exclusive "`nonrtolerance' `shownrtolerance'"

```

```

= opts_exclusive " "
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

> ----- end opts_exclus
> ive -----
    - if `:length local shownrtolerance' {
    = if 0 {
        local showtolerance showtolerance
    }
    - if "$ML_preserve" != "no" {
    = if "no" != "no" {
        if `:length local score' {
            di as smcl as err "May not specify {bf:score()} option unless" _
> n "      a) estimation subsample is the entire data in memory, or" _n "      b
> ) you specify option {bf:nopreserve} on {bf:ml model} statement (meaning" _n
> "      your evaluation program explicitly restricts itself to obs" _n "
> for which {bf:$}" "{bf:ML_samp==1}."
        exit 198
    }
    preserve
    local N = c(N)
    quietly keep if $ML_sample
    if (`N' != c(N)) {
        mata: Mopt_init_regetviews()
    }
    }
    - if `:length local score' {
    = if 0 {
        SetupScore ``$ML_evaltype' ``score' $ML_n $ML_dim
        local scores `s(scores)'
    }

```

```

- _parse_iterlog, `nolog' `log'
= _parse_iterlog, nolog

```

```

> ----- begin _parse_iter
> log -----
    - version 16
    - syntax [, NOLOG LOG]
    - if "`log'`nolog'" != "" {
= if "nolog" != "" {
    - opts_exclusive "`log' `nolog'"
= opts_exclusive " nolog"

```

```

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts  nolog
    - local n 0
    - while ```opts'"" != "" {
= while `"nolog"' != "" {
    - local ++n
    - gettoken item`n' opts : opts, bind
= gettoken item1 opts : opts, bind
    - }
    - while ```opts'"" != "" {
= while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 1 < 2 {
    - exit

```

```

> ----- end opts_exclus
> ive -----
    - }
    - else if "`c(iterlog)'" == "on" {
= else if "on" == "on" {
        local log log
    }
    - else {
        local nolog nolog
    }
    - sreturn local log `log'
= sreturn local log

```

```

        - sreturn local nolog `nolog'
        = sreturn local nolog nolog
    _____
> _____ end _parse_iter
> log _____
    - local log ``s(nolog)''
    = local log "nolog"
    - local tropts `log' `dots' `showtolerance' `showstep' `trace' `co
> efdiffs'
    = local tropts nolog
    - if ``tropts'' != "nolog" {
    = if "nolog" != "nolog" {
        local tropts `tropts' `gradient' `hessian'
        if ``skipline'' == "" {
            if ``iterate'' != "0" | `:length local tropts' {
                di
            }
        }
    }
    - else {
    - local gradient
    - local hessian
    - local nolog nolog
    - }
    - if ``search'' != "off" & ``iterate'' != "0" {
    = if "off" != "off" & "" != "0" {
        if ``search'' == "quietly" {
            local sopts nolog
        }
        else {
            if `:length local tropts' {
                if ``tropts'' != "nolog" {
                    local sopts trace
                }
            }
            else local sopts nolog
        }
    }
    if ``search'' == "norescale" {
        local sopts `sopts' norescale
    }
    Search `bounds', nopreserve `sopts' `repeat' `maxmin'
}
    - tempname value b V iV
    - `vv' mata: Mopt_maxmin()
    = version 18.5: mata: Mopt_maxmin()
    _____

```

```

> _____ begin poiss
> _lf _____
    - version 6
    - args todo b lnf g H score
    - tempvar xb
    - mlevel `xb' = `b'
    = mlevel __000000 = __00000I
    - mlsun `lnf' = -exp(`xb') + `xb'*$ML_y1 - lngamma($ML_y1+1)
    = mlsun __00000J = -exp(__000000) + __000000*y_timing_max - lnga
> mma(y_timing_max+1)
    - if `todo' == 0 | `lnf'==. {
    = if 2 == 0 | __00000J==. {
        exit
    }
    - qui replace `score' = $ML_y1 - exp(`xb') if $ML_samp
    = qui replace __00000M = y_timing_max - exp(__000000) if __00000
> 5
    - $ML_ec mlvecsum `lnf' `g' = `score'
    = * mlvecsum __00000J __00000K = __00000M
    - if `todo' == 1 | `lnf'==. {
    = if 2 == 1 | __00000J==. {
        exit
    }
    - mlmatsum `lnf' `H' = exp(`xb')
    = mlmatsum __00000J __00000L = exp(__000000)
    _____
> _____ end poiss
> _lf _____
    _____
> _____ begin poiss
> _lf _____
    - version 6
    - args todo b lnf g H score
    - tempvar xb
    - mlevel `xb' = `b'
    = mlevel __000000 = __00000I
    - mlsun `lnf' = -exp(`xb') + `xb'*$ML_y1 - lngamma($ML_y1+1)
    = mlsun __00000J = -exp(__000000) + __000000*y_timing_max - lnga
> mma(y_timing_max+1)
    - if `todo' == 0 | `lnf'==. {
    = if 0 == 0 | __00000J==. {
        - exit
    }
    _____
> _____ end poiss
> _lf _____
    _____

```

```

> _____ begin poiss
> _lf _____
    - version 6
    - args todo b lnf g H score
    - tempvar xb
    - mlevel `xb' = `b'
    = mlevel __000000 = __00000I
    - mlsun `lnf' = -exp(`xb') + `xb'*$ML_y1 - lngamma($ML_y1+1)
    = mlsun __00000J = -exp(__000000) + __000000*y_timing_max - lnga
> mma(y_timing_max+1)
    - if `todo' == 0 | `lnf'==. {
    = if 0 == 0 | __00000J==. {
    - exit
    _____

> _____ end poiss
> _lf _____

> _____ begin poiss
> _lf _____
    - version 6
    - args todo b lnf g H score
    - tempvar xb
    - mlevel `xb' = `b'
    = mlevel __000000 = __00000I
    - mlsun `lnf' = -exp(`xb') + `xb'*$ML_y1 - lngamma($ML_y1+1)
    = mlsun __00000J = -exp(__000000) + __000000*y_timing_max - lnga
> mma(y_timing_max+1)
    - if `todo' == 0 | `lnf'==. {
    = if 2 == 0 | __00000J==. {
        exit
    }
    - qui replace `score' = $ML_y1 - exp(`xb') if $ML_samp
    = qui replace __00000M = y_timing_max - exp(__000000) if __00000
> 5
    - $ML_ec mlvecsum `lnf' `g' = `score'
    = * mlvecsum __00000J __00000K = __00000M
    - if `todo' == 1 | `lnf'==. {
    = if 2 == 1 | __00000J==. {
        exit
    }
    - mlmatsum `lnf' `H' = exp(`xb')
    = mlmatsum __00000J __00000L = exp(__000000)
    _____

> _____ end poiss
> _lf _____
    _____

```

```

> _____ begin poiss
> _lf _____
      - version 6
      - args todo b lnf g H score
      - tempvar xb
      - mlevel `xb' = `b'
      = mlevel __000000 = __00000I
      - mlsun `lnf' = -exp(`xb') + `xb'*$ML_y1 - lngamma($ML_y1+1)
      = mlsun __00000J = -exp(__000000) + __000000*y_timing_max - lnga
> mma(y_timing_max+1)
      - if `todo' == 0 | `lnf'==. {
      = if 0 == 0 | __00000J==. {
      - exit
      _____

> _____ end poiss
> _lf _____

> _____ begin poiss
> _lf _____
      - version 6
      - args todo b lnf g H score
      - tempvar xb
      - mlevel `xb' = `b'
      = mlevel __000000 = __00000I
      - mlsun `lnf' = -exp(`xb') + `xb'*$ML_y1 - lngamma($ML_y1+1)
      = mlsun __00000J = -exp(__000000) + __000000*y_timing_max - lnga
> mma(y_timing_max+1)
      - if `todo' == 0 | `lnf'==. {
      = if 0 == 0 | __00000J==. {
      - exit
      _____

> _____ end poiss
> _lf _____

> _____ begin poiss
> _lf _____
      - version 6
      - args todo b lnf g H score
      - tempvar xb
      - mlevel `xb' = `b'
      = mlevel __000000 = __00000I
      - mlsun `lnf' = -exp(`xb') + `xb'*$ML_y1 - lngamma($ML_y1+1)
      = mlsun __00000J = -exp(__000000) + __000000*y_timing_max - lnga
> mma(y_timing_max+1)
      - if `todo' == 0 | `lnf'==. {
      = if 2 == 0 | __00000J==. {

```

```

        exit
    }
    - qui replace `score' = $ML_y1 - exp(`xb') if $ML_samp
    = qui replace __00000M = y_timing_max - exp(__000000) if __00000
> 5

    - $ML_ec mlvecsum `lnf' `g' = `score'
    = * mlvecsum __00000J __00000K = __00000M
    - if `todo' == 1 | `lnf'==. {
    = if 2 == 1 | __00000J==. {
        exit
    }
    - mlmatsum `lnf' `H' = exp(`xb')
    = mlmatsum __00000J __00000L = exp(__000000)
    _____
> _____ end poiss
> _lf _____
    _____
> _____ begin mopt_p
> ost _____
    - args b V C wgt touse depvar
    - if `:length local touse' {
    = if 8 {
    - tempname esamp
    - quietly gen byte `esamp' = `touse'
    = quietly gen byte __00000Q = __000005
    - }
    - ereturn post `b' `V' `C' `wgt', esample(`esamp') depname(`depv
> ar') buildfvinfo
    = ereturn post __000000 __00000P [], esample(__00000Q) depname(
> y_timing_max) buildfvinfo
    _____
> _____ end mopt_p
> ost _____
    - ereturn scalar k_eq_model = abs($ML_waldtest)
    = ereturn scalar k_eq_model = abs(-1)
    - if `:length global ML_ll_0' {
    = if 18 {
    - ereturn scalar ll_0 = $ML_ll_0
    = ereturn scalar ll_0 = -420.2971615663282
    - if `:length global ML_rank0' {
    = if 0 {
        ereturn scalar rank0 = $ML_rank0
        ereturn scalar df_m = e(rank) - $ML_rank0
    }
    - else ereturn scalar df_m = e(rank) - $ML_k0
    = else ereturn scalar df_m = e(rank) - 1

```



```

- }
- if !':length global ML_ll_0' | inlist(e(vce), "robust", "cluster
> ", "linearized") {
= if !18 | inlist(e(vce), "robust", "cluster", "linearized") {
- if "$ML_svy" == "" {
= if "" == "" {
- _prefix_model_test, minimum
}
}
> ----- begin _prefix_model_t
> est -----
- version 9
- syntax [name(name=cmd)] [, svy noADJust noSVYadjust MINimum ]
- if (inlist("`cmd'", "asmixlogit", "cmmixlogit", "cmxtmixlogit"))
> {
= if (inlist("", "asmixlogit", "cmmixlogit", "cmxtmixlogit")) {
_asmixtest, `svy' `adjust' `svyadjust'
exit
}
- local K = 1
- if "`e(k_eq_model)'" != "" {
= if "1" != "" {
- capture confirm integer number `e(k_eq_model)'
= capture confirm integer number 1
- if ! c(rc) {
- local K = e(k_eq_model)
- }
- }
- if "`e(k_eq_model_skip)'" != "" {
= if "" != "" {
capture confirm integer number `e(k_eq_model_skip)'
if ! c(rc) {
local skip = e(k_eq_model_skip)
}
}
- ereturn local df_m
- ereturn local F
- ereturn local chi2
- ereturn local chi2type
- ereturn local p
- if (`K' == 0) {
= if (1 == 0) {
exit
}
- forval i = 1/`K' {
= forval i = 1/1 {
- if !':list i in skip' {

```

```

= if !0 {
- local spec "`spec' ([#`i'])"
= local spec " ([#1])"
- }
- }
- tempname cns omit
- capture matrix `cns' = get(Cns)
= capture matrix __00000Q = get(Cns)
- if (c(rc)) local cns
- if "`cns'" != "" {
= if "" != "" {
  local k_autoCns = e(k_autoCns)
  if missing(`k_autoCns') {
    local k_autoCns 0
  }
  if rowsof(`cns') == `k_autoCns' {
    local cns
  }
}
- if "`svy'" != "" & "`adjust'`svyadjust'" != "" {
= if "" != "" & "" != "" {
  local adjust nosvyadjust
}
- else local adjust
- _ms_omit_info e(b), nocons
- matrix `omit' = r(omit)
= matrix __00000R = r(omit)
- capture test `spec', `adjust'
= capture test ([#1]),

```

```

> ----- begin t
> est -----

```

```

- if "`e(cmd)'" == "anova" | "`e(cmd)'" == "manova" {
= if "mopt" == "anova" | "mopt" == "manova" {
  AnovaTestChooser `0'
  return add
  exit
}
- if "`e(cmd)'" == "mixed" {
= if "mopt" == "mixed" {
  MixedTestChooser `0'
  return add
  exit
}
- if _caller() < 8 {
  _test `0'

```

```

        return add
        exit
    }
    - is_svy
    _____
> _____ begin is_
> svy _____
    - version 8
    - syntax [, Regression]
    - if ``e(prefix)'' == "svy" {
= if `""' == "svy" {
    return scalar is_svy = 1
    }
    - else if ``regression'' == "" {
= else if "" == "" {
    - return scalar is_svy = (`e(N_psu)'' != "")
= return scalar is_svy = ("" != "")
    - }
    - else {
        capt mat list e(b)
        local rc = _rc
        return scalar is_svy = (`e(N_psu)'' != "") & (`rc' == 0)
    }
    _____
> _____ end is_
> svy _____
    - local is_svy = r(is_svy)
    - if replay() & `is_svy' == 0 {
= if replay() & 0 == 0 {
    _test `0'
    return add
    exit
    }
    - version 8
    - WaldTest `is_svy' `0'
= WaldTest 0 ([#1]),
    _____
> _____ begin test.WaldT
> est _____
    - gettoken is_svy 0 : 0
    - if ``is_svy'' == "1" {
= if "0" == "1" {
        if ``e(complete)'' == "available" {
            di as err ``must run svy command with "complete" "" "optio
> n before using this command"
            exit 301

```

```

    }
  }
  - gettoken tok : 0, parse(" (,") bind
  - local single single
  - local zero ``0'''
  = local zero `` ([#1]), ''
  - if ``tok''' == "(" {
  = if ``('' == "(" {
  - local single
  - while ``tok''' == "(" {
  = while ``('' == "(" {
  - gettoken tok 0 : 0, parse(" (,") match(paren) bind
  - local eqns ``eqns' ``tok''''
  = local eqns `` ``[#1]''''
  - gettoken tok : 0, parse(" (,") bind
  - }
  - while ``tok''' == "(" {
  = while ``,"' == "(" {
    gettoken tok 0 : 0, parse(" (,") match(paren) bind
    local eqns ``eqns' ``tok''''
    gettoken tok : 0, parse(" (,") bind
  }
  - if ``tok''' != "," & ``tok''' != "" {
  = if ``,"' != "," & ``,"' != "" {
    local single single
  }
  - }
  - if ``single'=="single" {
  = if ""=="single" {
    local eqns
    local 0 ``zero'''
    while ``tok''' != "" & ``tok''' != "," {
    gettoken tok 0 : 0, parse(" ,") bind
    local eqns ``eqns' `tok'''
    gettoken tok : 0, parse(" ,") bind
    }
    local eqns ````eqns''''
  }
  - syntax [, Accumulate noSVYadjust common CONSTant MINimum M
> test Mtest2(passthru) noTest COEF matvlc(passthru) DF(numlist max=1 >0) ]
  - if ``df''' != "" {
  = if "" != "" {
    local dof = `df'
  }
  - else if ``e(df_r)''' != "" {
  = else if "" != "" {

```

```

        local dof = e(df_r)
    }
    - else {
    - local dof = .
    - }
    - if ``mtest'`mtest2'`` != "" {
= if `""' != "" {
    if inlist("`e(cmd)'", "svymean", "svytotal", "svyratio") {
    di as err "`mtest option not allowed after `e(cmd)'"
    exit 301
    }
    _mtest syntax, `mtest' `mtest2'
    local mtmethod `r(method)'
    }
    - if "`mtmethod'" != "" {
= if "" != "" {
    if "`test'" != "" {
    di as err "options mtest and notest may not be combined"
    exit 198
    }
    if "`accumulate'" != "" {
    di as err "options mtest and accumulate may not be combine
> d"

    exit 198
    }
    }
    - if `is_svy' {
= if 0 {
    if ``e(cmd)`` == "margins" {
    local vce ``e(model_vce)``
    }
    else local vce ``e(vce)``
    if inlist(`"vce"', "bootstrap", "sdr") {
    if missing(`dof') {
    local svyadjust nosvyadjust
    }
    }
    }
    - if !`is_svy' & "`svyadjust'" != "" {
= if !0 & "" != "" {
    di as err "option nosvyadjust is allowed only with svy dat
> a"

    exit 198
    }
    - local svy_adjust = `is_svy' & "`svyadjust'" == ""
= local svy_adjust = 0 & "" == ""

```

```

- if `svy_adjust' & missing(`dof') & (missing(e(N_psu)) | mi
> ssing(e(N_strata))) {
= if 0 & missing(.) & (missing(e(N_psu)) | missing(e(N_strat
> a))) {

    di as err "impossible to adjust p-values"
    exit 198
}
- if `is_svy' & ``test' == "" {
= if 0 & ``' == "" {
    if "`svyadjust'" == "" {
        di _n as txt "Adjusted Wald test"
    }
    else di _n as txt "Unadjusted Wald test"
}
- local tmp : subinstr local eqns "==" "", all count(local
> nch)

- if `nch' > 0 {
= if 0 > 0 {
    di as err "==" invalid operator"
    exit 198
}
- local eqns : subinstr local eqns "==" "=", all
- ExpandExpsn ``eqns' "common" "constant"
= ExpandExpsn ``[#1]' " " " "

> _____ begin test.ExpandEx
> pns _____

- args expns common constant
- gettoken exp expns : expns
- while ``exp' != "" {
= while ``[#1]' != "" {
- Expand ``exp' "common" "constant"
= Expand ``[#1]' " " " "

> _____ begin test.Exp
> and _____

- args exp common constant
- local junk : subinstr local exp "=" "=", count(local n
> ch) all

- if `nch' <= 1 {
= if 0 <= 1 {
- return local explist ``exp'
= return local explist ``[#1]'
- return local nexp 1
- exit

```

```

> ----- end test.Exp
> and
    - local explist ``explist' `r(explist)''
    = local explist ``#[1]''
    - local nexpt = `nexpt' + `r(nexpt)'
    = local nexpt = + 1
    - gettoken exp expns : expns
    - }
    - while ``exp'' != "" {
    = while ``'' != "" {
        Expand ``exp'' ``common'' ``constant''
        local explist ``explist' `r(explist)''
        local nexpt = `nexpt' + `r(nexpt)'
        gettoken exp expns : expns
    }
    - return local explist ``explist''
    = return local explist ``#[1]''
    - return local nexpt `nexpt'
    = return local nexpt 1

> ----- end test.ExpandEx
> pns
    - local explist ``r(explist)''
    = local explist ``#[1]''
    - local nexpt `r(nexpt)'
    = local nexpt 1
    - local acc `accumulate'
    = local acc
    - foreach exp of local explist {
    - quietly _test `exp' , `acc' `common' `constant' notest
    = quietly _test [1] , notest
    - local acc acc
    - }
    - if ``test'' == "notest" {
    = if "" == "notest" {
        _test , notest
        exit
    }
    - quietly _test , `matvlt'
    = quietly _test ,
    - if `dof' < . {
    = if . < . {
        local testtype F
        tempname F df1 df2 p drop
        if ``r(F)'' != "" {
            scalar `F' = r(F)

```

```

    }
    else {
        scalar `F' = r(chi2)/r(df)
    }
    scalar `df1' = r(df)
    scalar `df2' = `dof'
    scalar `p' = Ftail(`df1', `df2', `F')
    scalar `drop' = r(drop)
}
- else {
- local testtype chi2
- tempname chi2 df1 p drop
- scalar `chi2' = r(chi2)
= scalar __00000S = r(chi2)
- scalar `df1' = r(df)
= scalar __00000T = r(df)
- scalar `p' = r(p)
= scalar __00000U = r(p)
- scalar `drop' = r(drop)
= scalar __00000V = r(drop)
- }
- local i 1
- while "`r(dropped_`i')'" != "" {
= while "" != "" {
    local dropped_`i' `r(dropped_`i')'
    local ++i
}
- if `svy_adjust' {
= if 0 {
    if "`df'" != "" {
        local svy_d = `df'
    }
    else if !missing(e(df_r)) {
        local svy_d = e(df_r)
    }
    else local svy_d = e(N_psu)-e(N_strata)
    if missing(`svy_d') {
        di as err "internal error in adjustment for svy"
        exit 10001
    }
    if "`testtype'" == "F" {
        scalar `F' = ((`svy_d'-`df1'+1)/`svy_d') * `F'
    }
    else {
        tempname F df2
        scalar `F' = ((`svy_d'-`df1'+1)/(`svy_d'*`df1')) * `chi2'
    }
}

```



```

}
scalar `df2' = `svy_d' - `df1' + 1
if `df2' < 0 {
scalar `F' = .
}
scalar `p' = Ftail(`df1', `df2', `F')
local testtype F
}
- if "`mtmethod'" != "" {
= if "" != "" {
tempname R r Rr V b VR tm Wald
mat `V' = e(V)
mat `b' = e(b)
mat `Rr' = get(Rr)
local nb = rowsof(`V')
local nr = rowsof(`Rr')
mat `R' = `Rr'[1...,1..`nb']
mat `VR' = `R'*`V'*`R''
mat `r' = `R'*`b'' - `Rr'[1...,`= `nb'+1']
mat `Wald' = `r'*syminv(`VR')*`r'
mat `tm' = J(`nr', 3, .)
mat colnames `tm' = `testtype' df p
forvalues it = 1 / `nr' {
mat `Wald' = `r'[`it',1]^2 / `VR'[`it',`it']
mat `tm'[`it',1] = `Wald'[1,1]
mat `tm'[`it',2] = 1
if `svy_adjust' {
mat `tm'[`it',3] = Ftail(1,`svy_d',`tm'[`it',1])
}
else if "`testtype'" == "chi2" {
mat `tm'[`it',3] = chi2tail(1,`tm'[`it',1])
}
else {
mat `tm'[`it',3] = Ftail(1,`df2',`tm'[`it',1])
}
}
if "`mtmethod'" != "noadjust" {
_mtest adjust `tm', mtest(`mtmethod') pindex(3) append
mat `tm' = r(result)
local pindex 4
}
else local pindex 3
}
- _test, notest
- local i 1
- while "`dropped_`i'" != "" {

```

```

= while "" != "" {
    di as txt "          Constraint `dropped_`i` dropped"
    local ++i
}
- if "`mtmethod'" == "" {
= if "" == "" {
- di
- if "`testtype'" == "chi2" {
= if "chi2" == "chi2" {
- di as txt _col(12) "chi2(" %3.0f `df1' ") =" as res %8.2f
> `chi2'
= di as txt _col(12) "chi2(" %3.0f __00000T ") =" as res %8.
> 2f __00000S
- di as txt _col(10) "Prob > chi2 = " as res %8.4f `p'
= di as txt _col(10) "Prob > chi2 = " as res %8.4f __00000U
- }
- else {
di as txt "          F(" %3.0f `df1' "," %6.0f `df2' ") =" as
> res %8.2f `F'
di as txt _col(13) "Prob > F =" as res %10.4f `p'
}
- }
- else {
local nexp = rowsof(`tm')
local nc = colsof(`tm')
if "`testtype'" == "F" {
local d "F(df,`= `df2`)"
local dip "p > F"
}
else {
local d chi2
local dip "p > chi2"
}
di
di as txt "{hline 7}{c TT}{hline 30}"
di as txt "          {c |}{ralign 12: `d'}          df{ralign 11: `d
> ip'}"
di as txt "{hline 7}{c +}{hline 30}"
forvalues it = 1 / `nexp' {
di as txt "          (`it') {c |}" as res _col(12) %9.2f `tm'[`it
> ',1] _col(22) %6.0f `tm'[`it',2] _col(33) %6.4f `tm'[`it',`pindex'] as txt "
> *"
}
di as txt "{hline 7}{c +}{hline 30}"
di as txt "          All {c |}" as res _col(12) %9.2f ``testtype'
> ' _col(22) %6.0f `df1' _col(33) %6.4f `p'

```

```

        di as txt "{hline 7}{c BT}{hline 30}"
        _mtest footer 1 "`mtmethod'" "*" "
    }
    - if "`coef'" != "" {
= if "" != "" {
        Table
    }
    - return scalar p = `p'
= return scalar p = __00000U
    - return scalar df = `df1'
= return scalar df = __00000T
    - if "`testtype'" == "F" {
= if "chi2" == "F" {
        return scalar F = `F'
        return scalar df_r = `df2'
    }
    - else return scalar chi2 = `chi2'
= else return scalar chi2 = __00000S
    - return scalar drop = `drop'
= return scalar drop = __00000V
    - local i 1
    - while "`dropped_`i'" != "" {
= while "" != "" {
        return scalar dropped_`i' = `dropped_`i''
        local ++i
    }
    - if "`mtmethod'" != "" {
= if "" != "" {
        return matrix mtest `tm'
        return local mtmethod `mtmethod'
    }
}

> _____ end test.WaldT
> est _____
        - return add
    _____

> _____ end t
> est _____
        - if !c(rc) {
        - if `:length local minimum' {
= if 7 {
        - quietly test, min
    _____

> _____ begin t
> est _____
        - if "`e(cmd)'" == "anova" | "`e(cmd)'" == "manova" {

```

```

= if "mopt" == "anova" | "mopt" == "manova" {
  AnovaTestChooser `0'
  return add
  exit
}
- if "`e(cmd)'" == "mixed" {
= if "mopt" == "mixed" {
  MixedTestChooser `0'
  return add
  exit
}
- if _caller() < 8 {
  _test `0'
  return add
  exit
}
- is_svy
}

> ----- begin is_
> svy -----
  - version 8
  - syntax [, Regression]
  - if "`e(prefix)'" == "svy" {
= if `""' == "svy" {
  return scalar is_svy = 1
}
- else if "`regression'" == "" {
= else if "" == "" {
  - return scalar is_svy = ("`e(N_psu)'" != "")
= return scalar is_svy = (" " != " ")
- }
- else {
  capt mat list e(b)
  local rc = _rc
  return scalar is_svy = ("`e(N_psu)'" != "") & (`rc' == 0)
}
}

> ----- end is_
> svy -----
  - local is_svy = r(is_svy)
  - if replay() & `is_svy' == 0 {
= if replay() & 0 == 0 {
  - _test `0'
= _test , min
  - return add
  - exit
}
}

```

```

> ----- end t
> est -----
- }
- ereturn scalar df_m = r(df)
- local drop = r(drop)
- if `drop' {
= if 0 {
  local drop 0
  local i 1
  local idrop ``r(dropped_`i')'''
  while ``idrop' != "" {
    if !`omit'[1,`idrop'] {
      local ++drop
    }
    local ++i
    local idrop ``r(dropped_`i')'''
  }
}
- if `drop' == 0 | ``cns' != "" {
= if 0 == 0 | "" != "" {
- if !missing(e(df_r)) {
  ereturn scalar F = r(F)
}
- else {
- ereturn scalar chi2 = r(chi2)
- ereturn local chi2type Wald
- }
- ereturn scalar p = r(p)
- }
- else {
  if !missing(e(df_r)) {
    ereturn scalar F = .
  }
  else {
    ereturn scalar chi2 = .
    ereturn local chi2type Wald
  }
  ereturn scalar p = .
}
- }
- else {
  if missing(e(df_r)) {
    ereturn local chi2type Wald
  }
  ereturn scalar df_m = 0

```

```

        }
    }
end _prefix_model_t
> est
    - }
    - else {
        _prefix_model_test, $ML_svy $ML_noadj
    }
    - }
    - else if `:length global ML_ll_0' {
= else if 18 {
        if ``"maxmin" == "minimize" {
            ereturn scalar chi2 = -2*(e(ll)-e(ll_0))
        }
        else {
            ereturn scalar chi2 = 2*(e(ll)-e(ll_0))
        }
        ereturn scalar p = chi2tail(e(df_m), e(chi2))
        ereturn local chi2type "LR"
    }
    - if `:length global ML_wexp' {
= if 0 {
        ereturn local wtype ``$ML_wtyp"
        ereturn local wexp ``$ML_wexp"
    }
    - if `:length global ML_group' {
= if 0 {
        ereturn local group ``$ML_group"
        if ``"e(clustvar)" == "$ML_grp" & "$ML_grp" != "" {
            ereturn local clustvar ``$ML_group"
        }
    }
    - ereturn local cmd "ml"
    - if `:length local score' {
= if 0 {
        mata: Mopt_score(0)
        ereturn local scorevars `scores'
    }
    - if "$ML_preserve" != "no" {
= if "no" != "no" {
        restore
        if ""e(prefix)" == "svy" & e(N_strata_omit) {
            tempname v
            quietly _svy2 $ML_sample if $ML_sample, type(total) svy v(`v') s
> ubpop(`e(subpop)') touse($ML_sample)
        }
    }

```

```

        ereturn repost, esample($ML_sample)
    }
- if ``moptobj`` != "" {
= if ``"" != "" {
    local clear noclear
    }
- if `:length local clear' {
= if !0 {
- Clear
}

> _____ begin mopt.Cl
> ear _____
    - syntax [, NOTANOPTION]
    - capture drop $ML_w
    = capture drop __000005
    - capture drop $ML_samp
    = capture drop __000005
    - capture drop $ML_sample
    = capture drop __000005
    - capture drop $ML_subv
    = capture drop
    - capture drop $ML_grp
    = capture drop
    - mata: Mopt_drop_external()
    - macro drop ML_*
}

> _____ end mopt.Cl
> ear _____
    - }
    - else {
        capture confirm var $ML_sample
        if c(rc) {
            quietly gen byte $ML_sample = e(sample)
        }
    }
- if `:length local output' == 0 {
= if 8 == 0 {
    Display, level(`level') `options'
}

> _____ end mopt.Max
> Min _____
    - }

> _____ end mopt.Mo
> del _____

```

```

- if c(rc) {
  local rc = c(rc)
  Clear
  exit `rc'
}
- exit

> _____ end m
> opt _____
- exit

> _____ end
> ml _____
- if "`score'" != "" {
= if "" != "" {
  label var `scvar' "Score index from poisson"
  rename `scvar' `score'
  est local scorevars `score'
}
- est scalar r2_p = 1 - e(ll)/e(ll_0)
- est hidden local gof "poiss_g"
- est local offset "`offvar'"
= est local offset ""
- est local offset1
- est local estat_cmd "poisson_estat"
- est hidden local marginsderiv default N IR
- est local predict "poisso_p"
- est local cmd "poisson"
- global S_E_ll = e(ll)
- global S_E_ll0 `e(ll_0)'
= global S_E_ll0 -420.2971615663282
- global S_E_chi2 = e(chi2)
- global S_E_mdf = e(df_m)
- global S_E_pr2 `e(r2_p)'
= global S_E_pr2 .0893032948798476
- global S_E_nobs = e(N)
- global S_E_tdf = e(N)
- global S_E_off `e(offset)'
= global S_E_off
- global S_E_depv `e(depvar)'
= global S_E_depv y_timing_max
- global S_E_cmd `e(cmd)'
= global S_E_cmd poisson
- if "`display'"==" " {
= if ""==" " {
- Display, `irr' level(`level') `diopts'

```



```

    = Display, level(95)


---


> 

---

 begin poisson.Disp
> lay 

---


    - syntax [, Level(cilevel) IRr *]
    - if "`irr'"!="" {
    = if ""!="" {
        local eopt "eform(IRR)"
    }
    - _get_diopts diopts, `options'
    = _get_diopts diopts,


---


> 

---

 begin _get_dio
> pts 

---


    - version 11
    - syntax namelist(max=2) [, *]
    - gettoken name1 namelist : namelist
    - gettoken name2 namelist : namelist
    - GetDiopts diopts options, `options'
    = GetDiopts diopts options,


---


> 

---

 begin _get_diopts.GetDio
> pts 

---


    - local DIOPTS Level(cilevel) vsquish NOALLBASElevels ALLBASElevels
> NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EMPTYcells NO
> OMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cformat(string) sfor
> mat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru) FVWRAPON(
> string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(passthru) NOABBREV
> ABBREV
    - syntax namelist(max=2) [, `DIOPTS' *]
    = syntax namelist(max=2) [, Level(cilevel) vsquish NOALLBASElevels A
> LLBASElevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells
> EMPTYcells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cformat
> (string) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passth
> ru) FVWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(passth
> ru) NOABBREV ABBREV *]
    - opts_exclusive "`allbaselevels' `noallbaselevels'"
    = opts_exclusive " "


---


> 

---

 begin opts_exclus
> ive 

---


    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0

```

```

- while ``opts'' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit

```

```

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`allbaselevels' `nobaselevels'"
    = opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts'' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

```

```

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`baselevels' `nobaselevels'"
    = opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts'' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind

```

```

        }
        - if `n' < 2 {
        = if 0 < 2 {
        - exit
    }
}
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`emptycells' `noemptycells'"
    = opts_exclusive " "
}
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ```opts'`` != "" {
    = while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
}
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`fvlabel' `nofvlabel'"
    = opts_exclusive " "
}
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ```opts'`` != "" {
    = while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
}

```

```

> _____ end opts_exclus
> ive _____
    - opts_exclusive "'omitted' `noomitted'"
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while `"'opts'" != "" {
    = while `"" != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`lstretch' `nolstretch'"
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while `"'opts'" != "" {
    = while `"" != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`cnsreport' `fullcnsreport'"

```

```

= opts_exclusive " "
> ----- begin opts_exclus
> ive
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
> ----- end opts_exclus
> ive
    - opts_exclusive ``coeflegend' `selegend'
    = opts_exclusive " "
> ----- begin opts_exclus
> ive
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
> ----- end opts_exclus
> ive
    - opts_exclusive ``noci' `nopvalues'
    = opts_exclusive " "
> ----- begin opts_exclus
> ive

```

```

- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while `"'opts'"' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit

```

```

> ----- end opts_exclus
> ive -----
    - local K : list sizeof namelist
    - gettoken c_diopts c_opts : namelist
    - opts_exclusive "`coding' `compare'"
    = opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while `"'opts'"' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
        }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

```

```

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`versus' `compare'"
    = opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab

```

```

- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
  }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`abbrev' `noabbrev'"
= opts_exclusive " "
}

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
  }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- local allbaselevels `allbaselevels' `noallbaselevels'
= local allbaselevels
- local baselevels `baselevels' `nobaselevels'
= local baselevels
- local emptycells `emptycells' `noemptycells'
= local emptycells
- local omitted `omitted' `noomitted'
= local omitted
- local lstretch `lstretch' `nolstretch'
= local lstretch
- local fvlabel `fvlabel' `nofvlabel'

```

```

= local fvlabel
- local abbrev `abbrev' `noabbrev'
= local abbrev
- if "`allbaselevels'`baselevels'" == "" {
= if "" == "" {
- if c(showbaselevels) == "all" {
    local allbaselevels allbaselevels
  }
- else if c(showbaselevels) == "on" {
    local baselevels baselevels
  }
- }
- if "`emptycells'" == "" {
= if "" == "" {
- if c(showemptycells) == "off" {
    local emptycells noemptycells
  }
- }
- if "`omitted'" == "" {
= if "" == "" {
- if c(showomitted) == "off" {
    local omitted noomitted
  }
- }
- if "`lstretch'" == "" {
= if "" == "" {
- if c(lstretch) == "off" {
    local lstretch nolstretch
  }
- }
- if `:length local cformat' {
= if 0 {
    confirm numeric format `cformat'
    if fmtwidth("`cformat'") > 9 {
      local cformat "%9.0g"
      di "{txt}note: invalid cformat(), using default"
    }
    sreturn local cformat "`cformat'"
    local cformat `cformat(`cformat')'
  }
- if `:length local sformat' {
= if 0 {
    confirm numeric format `sformat'
    if fmtwidth("`sformat'") > 8 {
      local sformat "%8.2f"
      di "{txt}note: invalid sformat(), using default"
    }
  }

```



```

    }
    sreturn local sformat ``sformat'''
    local sformat `sformat(`sformat')'
  }
- if `:length local pformat' {
= if 0 {
  confirm numeric format `pformat'
  if fmtwidth(`pformat') > 5 {
    local pformat "%5.3f"
    di "{txt}note: invalid pformat(), using default"
  }
  sreturn local pformat ``pformat'''
  local pformat `pformat(`pformat')'
}
- if `K' == 1 & `:length local options' {
= if 2 == 1 & 0 {
  syntax namelist(max=2) [, `DIOPTS']
}
- if reldif(`level', c(level)) > 1e-3 {
= if reldif(95, c(level)) > 1e-3 {
  local levelopt level(`level')
}
- Wraapon , `fvwraapon'
= Wraapon ,

```

> _____ begin _get_diopts.Wra

> pon _____

```

- capture syntax [, W0rd WIdth]
- if c(rc) {
  di as err "invalid fvwraapon() option;"
  syntax [, W0rd WIdth]
  exit 198
}
- opts_exclusive ``word' `width'" fvwraapon
= opts_exclusive " " fvwraapon

```

> _____ begin opts_exclus

> ive _____

```

- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts''' != "" {
= while `''' != "" {
  local ++n

```

```

        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    }
}
> _____ end opts_exclus
> ive _____
    - local fvwrapon `word' `width'
    = local fvwrapon
    - if `:length local fvwrapon' {
    = if 0 {
        c_local fvwrapon fvwrapon(`fvwrapon')
    }
}
> _____ end _get_diopts.Wra
> pon _____
    - if "`fvwrap'" != "" {
    = if "" != "" {
        FVWrap, `fvwrap'
    }
    - c_local `c_diopts' `levelopt' `vsquish' `allbaselevels' `baselevel
> s' `cnsreport' `fullcnsreport' `emptycells' `omitted' `lstretch' `coeflegend
> ' `selegend' `cformat' `sformat' `pformat' `coding' `versus' `compare' `fvwr
> ap' `fvwrapon' `fvlabel' `nocl' `nopvalues' `markdown' `citype' `abbrev'
    = c_local diopts
    - if `K' == 2 {
    = if 2 == 2 {
    - c_local `c_opts' ``options'
    = c_local options `''
    - }
    - sreturn local coding `coding'
    = sreturn local coding
    - sreturn local versus `versus'
    = sreturn local versus
    - sreturn local compare `compare'
    = sreturn local compare
    - sreturn local level `level'
    = sreturn local level 95
}
> _____ end _get_diopts.GetDio
> pts _____
    - c_local `name1' ``diopts'
    = c_local diopts `''
    - local snames : s(macros)
    - foreach sname of local snames {

```

```

- local S_`sname' = s(`sname')
= local S_level = s(level)
- }
- local S_`sname' = s(`sname')
= local S_nolog = s(nolog)
- }
- local S_`sname' = s(`sname')
= local S_deriv = s(deriv)
- }
- local S_`sname' = s(`sname')
= local S_namelist = s(namelist)
- }
- local S_`sname' = s(`sname')
= local S_optlist = s(optlist)
- }
- local S_`sname' = s(`sname')
= local S_after = s(after)
- }
- local S_`sname' = s(`sname')
= local S_before = s(before)
- }
- local S_`sname' = s(`sname')
= local S_k_fill = s(k_fill)
- }
- local S_`sname' = s(`sname')
= local S_k = s(k)
- }
- sreturn clear
- GetDiopts DEFAULT

```

```

> _____ begin _get_diopts.GetDio
> pts _____
- local DIOPTS Level(cilevel) vsquish NOALLBASElevels ALLBASElevels
> NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EMPTYcells NO
> OMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cformat(string) sfor
> mat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru) FVWRAPON(
> string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(passthru) NOABBREV
> ABBREV
- syntax namelist(max=2) [, `DIOPTS' *]
= syntax namelist(max=2) [, Level(cilevel) vsquish NOALLBASElevels A
> LLBASElevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells
> EMPTYcells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cformat
> (string) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passth
> ru) FVWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(passth
> ru) NOABBREV ABBREV *]
- opts_exclusive "`allbaselevels' `noallbaselevels'"

```

```

= opts_exclusive " "
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`allbaselevels' `nbaselevels'"
    = opts_exclusive " "
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`baselevels' `nbaselevels'"
    = opts_exclusive " "
> _____ begin opts_exclus
> ive _____

```

```

- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit

```

```

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`emptycells' `noemptycells'"
    = opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

```

```

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`fvlabel' `nofvlabel'"
    = opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts

```

```

- local n 0
- while ``opts'' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`omitted' `noomitted'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts'' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`lstretch' `nolstretch'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts'' != "" {
= while `"' != "" {
  local ++n

```

```

        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`cnsreport' `fullcnsreport'"
= opts_exclusive " "
}
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ```opts'"" != "" {
= while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`coeflegend' `selegend'"
= opts_exclusive " "
}
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ```opts'"" != "" {
= while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {

```

```

        - exit
    _____
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`noci' `nopvalues'"
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ```opts'`` != "" {
    = while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____
> _____ end opts_exclus
> ive _____
    - local K : list sizeof namelist
    - gettoken c_diopts c_opts : namelist
    - opts_exclusive "`coding' `compare'"
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ```opts'`` != "" {
    = while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

```



```

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`versus' `compare'"
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while `""opts'" != "" {
    = while `"" != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`abbrev' `noabbrev'"
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while `""opts'" != "" {
    = while `"" != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - local allbaselevels `allbaselevels' `noallbaselevels'
    = local allbaselevels

```

```

- local baselevels `baselevels' `nobaselevels'
= local baselevels
- local emptycells `emptycells' `noemptycells'
= local emptycells
- local omitted `omitted' `noomitted'
= local omitted
- local lstretch `lstretch' `nolstretch'
= local lstretch
- local fvlabel `fvlabel' `nofvlabel'
= local fvlabel
- local abbrev `abbrev' `noabbrev'
= local abbrev
- if "`allbaselevels'`baselevels'" == "" {
= if "" == "" {
- if c(showbaselevels) == "all" {
    local allbaselevels allbaselevels
  }
- else if c(showbaselevels) == "on" {
    local baselevels baselevels
  }
- }
- if "`emptycells'" == "" {
= if "" == "" {
- if c(showemptycells) == "off" {
    local emptycells noemptycells
  }
- }
- if "`omitted'" == "" {
= if "" == "" {
- if c(showomitted) == "off" {
    local omitted noomitted
  }
- }
- if "`lstretch'" == "" {
= if "" == "" {
- if c(lstretch) == "off" {
    local lstretch nolstretch
  }
- }
- if `:length local cformat' {
= if 0 {
    confirm numeric format `cformat'
    if fmtwidth("`cformat'") > 9 {
      local cformat "%9.0g"
    }
    di "{txt}note: invalid cformat(), using default"
  }
}

```

```

    sreturn local cformat ``cformat'''
    local cformat `cformat(`cformat')''
}
- if `:length local sformat' {
= if 0 {
    confirm numeric format `sformat'
    if fmtwidth(`sformat') > 8 {
        local sformat "%8.2f"
        di "{txt}note: invalid sformat(), using default"
    }
    sreturn local sformat ``sformat'''
    local sformat `sformat(`sformat')''
}
- if `:length local pformat' {
= if 0 {
    confirm numeric format `pformat'
    if fmtwidth(`pformat') > 5 {
        local pformat "%5.3f"
        di "{txt}note: invalid pformat(), using default"
    }
    sreturn local pformat ``pformat'''
    local pformat `pformat(`pformat')''
}
- if `K' == 1 & `:length local options' {
= if 1 == 1 & 0 {
    syntax namelist(max=2) [, `DIOPTS']
}
- if reldif(`level', c(level)) > 1e-3 {
= if reldif(95, c(level)) > 1e-3 {
    local levelopt level(`level')
}
- Wraupon , `fvwraupon'
= Wraupon ,

```

> _____ begin _get_diopts.Wra

> pon _____

```

- capture syntax [, W0rd WIdth]
- if c(rc) {
    di as err "invalid fvwraupon() option;"
    syntax [, W0rd WIdth]
    exit 198
}
- opts_exclusive ``word' `width'" fvwraupon
= opts_exclusive " " fvwraupon

```

> _____ begin opts_exclus

```

> ive
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

> ----- end opts_exclus
> ive
    - local fvwrapon `word' `width'
    = local fvwrapon
    - if `:length local fvwrapon' {
    = if 0 {
        c_local fvwrapon fvwrapon(`fvwrapon')
    }

> ----- end _get_diopts.Wra
> pon
    - if "`fvwrap'" != "" {
    = if "" != "" {
        FVWrap, `fvwrap'
    }
    - c_local `c_diopts' `levelopt' `vsquish' `allbaselevels' `baselevel
> s' `cnsreport' `fullcnsreport' `emptycells' `omitted' `lstretch' `coeflegend
> ' `selegend' `cformat' `sformat' `pformat' `coding' `versus' `compare' `fvwr
> ap' `fvwrapon' `fvlabel' `nocl' `nopvalues' `markdown' `citype' `abbrev'
    = c_local DEFAULT
    - if `K' == 2 {
    = if 1 == 2 {
        c_local `c_opts' ``options'
    }
    - sreturn local coding `coding'
    = sreturn local coding
    - sreturn local versus `versus'
    = sreturn local versus
    - sreturn local compare `compare'
    = sreturn local compare
    - sreturn local level `level'

```

```

        = sreturn local level 95
    _____
> _____ end _get_diopts.GetDio
> pts _____
    - if ``name2`` == "" {
    = if `` == "" {
    - GetDiopts DUPS, `options'
    = GetDiopts DUPS,
    _____
> _____ begin _get_diopts.GetDio
> pts _____
    - local DIOPTS Level(cilevel) vsquish NOALLBASElevels ALLBASElevels
> NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EMPTYcells NO
> OMITted OMITted NOLSTRETCH LSTRETCH COEFlegend SELEGEND cformat(string) sfor
> mat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru) FVWRAPON(
> string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(passthru) NOABBREV
> ABBREV
    - syntax namelist(max=2) [, `DIOPTS' *]
    = syntax namelist(max=2) [, Level(cilevel) vsquish NOALLBASElevels A
> LLBASElevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells
> EMPTYcells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFlegend SELEGEND cformat
> (string) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passth
> ru) FVWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(passth
> ru) NOABBREV ABBREV *]
    - opts_exclusive "`allbaselevels' `noallbaselevels'"
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts`` != "" {
    = while `` != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`allbaselevels' `nobaselevels'"

```

```

= opts_exclusive " "
> ----- begin opts_exclus
> ive
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

> ----- end opts_exclus
> ive
    - opts_exclusive ``baselevels' `nobaselevels'
    = opts_exclusive " "

> ----- begin opts_exclus
> ive
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

> ----- end opts_exclus
> ive
    - opts_exclusive ``emptycells' `noemptycells'
    = opts_exclusive " "

> ----- begin opts_exclus
> ive

```

```

- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit

```

```

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`fvlabel' `nofvlabel'"
    = opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

```

```

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`omitted' `noomitted'"
    = opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts

```

```

- local n 0
- while ``opts'' != "" {
= while `'' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`lstretch' `nolstretch'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts'' != "" {
= while `'' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`cnsreport' `fullcnsreport'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts'' != "" {
= while `'' != "" {
    local ++n

```



```

        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`coeflegend' `selegend'"
= opts_exclusive " "
}
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ```opts'"" != "" {
= while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`noci' `nopvalues'"
= opts_exclusive " "
}
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ```opts'"" != "" {
= while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {

```

```

- exit


---


> 

---

 end opts_exclus
> ive 

---


- local K : list sizeof namelist
- gettoken c_diopts c_opts : namelist
- opts_exclusive "`coding' `compare'"
= opts_exclusive " "


---


> 

---

 begin opts_exclus
> ive 

---


- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ```opts'`` != "" {
= while `""' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit


---


> 

---

 end opts_exclus
> ive 

---


- opts_exclusive "`versus' `compare'"
= opts_exclusive " "


---


> 

---

 begin opts_exclus
> ive 

---


- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ```opts'`` != "" {
= while `""' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit


---



```

```

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`abbrev' `noabbrev'"
    = opts_exclusive " "
    -----

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while "`opts'" != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
        - exit
    -----

> ----- end opts_exclus
> ive -----
    - local allbaselevels `allbaselevels' `noallbaselevels'
    = local allbaselevels
    - local baselevels `baselevels' `nobaselevels'
    = local baselevels
    - local emptycells `emptycells' `noemptycells'
    = local emptycells
    - local omitted `omitted' `noomitted'
    = local omitted
    - local lstretch `lstretch' `nolstretch'
    = local lstretch
    - local fvlabel `fvlabel' `nofvlabel'
    = local fvlabel
    - local abbrev `abbrev' `noabbrev'
    = local abbrev
    - if "`allbaselevels'`baselevels'" == "" {
    = if "" == "" {
        - if c(showbaselevels) == "all" {
            local allbaselevels allbaselevels
        }
        - else if c(showbaselevels) == "on" {
            local baselevels baselevels
        }
    - }

```

```

- if "`emptycells'" == "" {
= if "" == "" {
- if c(showemptycells) == "off" {
    local emptycells noemptycells
  }
- }
- if "`omitted'" == "" {
= if "" == "" {
- if c(showomitted) == "off" {
    local omitted noomitted
  }
- }
- if "`lstretch'" == "" {
= if "" == "" {
- if c(lstretch) == "off" {
    local lstretch nolstretch
  }
- }
- if `:length local cformat' {
= if 0 {
    confirm numeric format `cformat'
    if fmtwidth("`cformat'") > 9 {
      local cformat "%9.0g"
      di "{txt}note: invalid cformat(), using default"
    }
    sreturn local cformat "`cformat'"
    local cformat `cformat(`cformat')'
  }
- if `:length local sformat' {
= if 0 {
    confirm numeric format `sformat'
    if fmtwidth("`sformat'") > 8 {
      local sformat "%8.2f"
      di "{txt}note: invalid sformat(), using default"
    }
    sreturn local sformat "`sformat'"
    local sformat `sformat(`sformat')'
  }
- if `:length local pformat' {
= if 0 {
    confirm numeric format `pformat'
    if fmtwidth("`pformat'") > 5 {
      local pformat "%5.3f"
      di "{txt}note: invalid pformat(), using default"
    }
    sreturn local pformat "`pformat'"
  }

```

```

        local pformat `"pformat(`pformat`)"'
    }
    - if `K' == 1 & `:length local options' {
= if 1 == 1 & 0 {
        syntax namelist(max=2) [, `DIOPTS']
    }
    - if reldif(`level', c(level)) > 1e-3 {
= if reldif(95, c(level)) > 1e-3 {
        local levelopt level(`level')
    }
    - Wraapon , `fvwraapon'
= Wraapon ,

> ----- begin _get_diopts.Wra
> pon -----
    - capture syntax [, W0rd WIdth]
    - if c(rc) {
        di as err "invalid fvwraapon() option;"
        syntax [, W0rd WIdth]
        exit 198
    }
    - opts_exclusive "`word' `width'" fvwraapon
= opts_exclusive " " fvwraapon

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ```opts`"' != "" {
= while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
        - exit

> ----- end opts_exclus
> ive -----
    - local fvwraapon `word' `width'
= local fvwraapon
    - if `:length local fvwraapon' {
= if 0 {

```

```

        c_local fvwrapon fvrapon(`fvrapon')
    }
}
> ----- end _get_diopts.Wra
> pon
    - if "`fvwrap'" != "" {
    = if "" != "" {
        FVWrap, `fvwrap'
    }
    - c_local `c_diopts' `levelopt' `vsquish' `allbaselevels' `baselevel
> s' `cnsreport' `fullcnsreport' `emptycells' `omitted' `lstretch' `coeflegend
> ' `selegend' `cformat' `sformat' `pformat' `coding' `versus' `compare' `fvwr
> ap' `fvrapon' `fvlabel' `nocl' `nopvalues' `markdown' `citype' `abbrev'
    = c_local DUPS
    - if `K' == 2 {
    = if 1 == 2 {
        c_local `c_opts' ``options'
    }
    - sreturn local coding `coding'
    = sreturn local coding
    - sreturn local versus `versus'
    = sreturn local versus
    - sreturn local compare `compare'
    = sreturn local compare
    - sreturn local level `level'
    = sreturn local level 95
}
> ----- end _get_diopts.GetDio
> pts
    - }
    - else {
        GetDiopts DUPS options, `options'
        c_local `name2' ``options'
    }
    - local DUPS : list DUPS - DEFAULT
    - gettoken DUPS : DUPS
    - if ``DUPS' != "" {
    = if `'' != "" {
        if (strpos(`DUPS', "(")) {
            gettoken DUPS : DUPS, parse("(")
            local DUPS `DUPS'()'
        }
        di as err "duplicate {bf:`DUPS'} option not allowed"
        exit 198
    }
    - sreturn clear

```

```

- foreach sname of local snames {
- sreturn local `sname' = ``S_`sname''''
= sreturn local level = ``95''
- }
- sreturn local `sname' = ``S_`sname''''
= sreturn local nolog = ``nolog''
- }
- sreturn local `sname' = ``S_`sname''''
= sreturn local deriv = ``0''
- }
- sreturn local `sname' = ``S_`sname''''
= sreturn local namelist = ``cluster''
- }
- sreturn local `sname' = ``S_`sname''''
= sreturn local optlist = ``CLuster''
- }
- sreturn local `sname' = ``S_`sname''''
= sreturn local after = `", vce(robust)''
- }
- sreturn local `sname' = ``S_`sname''''
= sreturn local before = `", argoptlist(CLuster) optlist(OIM OPG Robus
> t) old ''
- }
- sreturn local `sname' = ``S_`sname''''
= sreturn local k_fill = ``4''
- }
- sreturn local `sname' = ``S_`sname''''
= sreturn local k = ``4''
- }

> _____ end _get_dio
> pts _____
- version 9: ml di, level(`level') `eopt' nofootnote `diopts'
= version 9: ml di, level(95) nofootnote

> _____ begin
> ml _____
- if _caller()>=11 {
  mopt `0'
  exit
}
- version 8.2, missing
- version 6, missing
- if _caller()<6 {
  ml_5 `0'
  exit
}

```

```

}
- local caller : display string(_caller())
- gettoken cmd 0: 0, parse(" ,")
- local l = length(`""`cmd'`)
= local l = length(`"di"`)
- if `""`cmd'` == "technique" {
= if `"di"` == "technique" {
  ml_technique `0'
  exit
}
- if `""`cmd'` == "clear" {
= if `"di"` == "clear" {
  ml_clear `0'
  exit
}
- if `""`cmd'` == "hold" {
= if `"di"` == "hold" {
  ml_hold `0'
  exit
}
- if `""`cmd'` == "unhold" {
= if `"di"` == "unhold" {
  ml_unhold `0'
  exit
}
- if `""`cmd'` == "score" {
= if `"di"` == "score" {
  if "'e(opt)'" == "moptimize" {
    mopt score `0'
    exit
  }
  ml_score `0'
  exit
}
- if `""`cmd'`=="count" {
= if `"di"`=="count" {
  ml_c_d count `0'
  exit
}
- if `""`cmd'` == "trace" {
= if `"di"` == "trace" {
  ml_c_d trace `0'
  exit
}
- if `""`cmd'`==bsubstr("graph",1,max(2,`l`)) {
= if `"di"`==bsubstr("graph",1,max(2,2)) {

```



```

ml_graph `0'
exit
}
- if ``cmd''' == "init" {
= if ``di''' == "init" {
ml_init `0'
exit
}
- if ``cmd''' == bsubstr("maximize",1,max(3,`l')) {
= if ``di''' == bsubstr("maximize",1,max(3,2)) {
version `caller', missing: AllowEv ml_max `0'
exit
}
- if ``cmd''' == bsubstr("display",1,max(2,`l')) | ``cmd''' == bsubs
> tr("mlout", 1,max(3,`l')) {
= if ``di''' == bsubstr("display",1,max(2,2)) | ``di''' == bsubstr("mlou
> t", 1,max(3,2)) {
- if "e(opt)'" == "moptimize" {
= if "moptimize" == "moptimize" {
- mopt display `0'
= mopt display , level(95) nofootnote
}

> _____ begin m
> opt _____
- local vv : di "version " string(_caller()) ":"
- version 12
- gettoken subcmd 0 : 0, parse(" ,")
- local lcmd : length local subcmd
- if "subcmd'" == "clear" {
= if "display" == "clear" {
Clear
exit
}
- if "subcmd'" == "hold" {
= if "display" == "hold" {
ml_hold `0'
exit
}
- if "subcmd'" == "unhold" {
= if "display" == "unhold" {
ml_unhold `0'
exit
}
- if "subcmd'" == "score" {
= if "display" == "score" {
if _caller() > 12 {

```

```

`vv' Score `0'
}
else {
Score `0'
}
exit
}
- if "`subcmd'" == "count" {
= if "display" == "count" {
Count `0'
exit
}
- if "`subcmd'" == "trace" {
= if "display" == "trace" {
Trace `0'
exit
}
- if "`subcmd'" == bsubstr("graph",1,max(2,`lcmd')) {
= if "display" == bsubstr("graph",1,max(2,7)) {
Graph `0'
exit
}
- if "`subcmd'" == "init" {
= if "display" == "init" {
Interactive 0
`vv' Init `0'
exit
}
- if "`subcmd'" == bsubstr("maximize",1,max(3,`lcmd')) {
= if "display" == bsubstr("maximize",1,max(3,7)) {
Interactive 1
`vv' MaxMin maximize `0'
exit
}
- if "`subcmd'" == bsubstr("minimize",1,max(3,`lcmd')) {
= if "display" == bsubstr("minimize",1,max(3,7)) {
Interactive 1
`vv' MaxMin minimize `0'
exit
}
- if "`subcmd'" == bsubstr("display",1,max(2,`lcmd')) {
= if "display" == bsubstr("display",1,max(2,7)) {
- Display `0'
= Display , level(95) nofootnote

```

> begin mopt.Disp

```

> lay
    - if !inlist("`e(opt)'", "ml", "moptimize") {
    = if !inlist("moptimize", "ml", "moptimize") {
      error 301
    }
    - if "`e(svyml)'" != "" | "`e(prefix)'" == "svy" {
    = if "" != "" | "" == "svy" {
      _prefix_display `0'
      exit
    }
    - syntax [, Level(cilevel) Plus noHeader First SHOWEQns NEQ(intege
> r -1) noFOOTnote NOSKIP Title(passthru) NOTEST * ]
    - if "`plus'" != "" {
    = if "" != "" {
      local footnote nofootnote
    }
    - if `neq' >= 0 {
    = if -1 >= 0 {
      local neqopt neq(`neq')
    }
    - _get_diopts diopts options, `options'
    = _get_diopts diopts options,

> _____ begin _get_dio
> pts
    - version 11
    - syntax namelist(max=2) [, *]
    - gettoken name1 namelist : namelist
    - gettoken name2 namelist : namelist
    - GetDiopts diopts options, `options'
    = GetDiopts diopts options,

> _____ begin _get_diopts.GetDio
> pts
    - local DIOPTS Level(cilevel) vsquish NOALLBASElevels ALLBASEl
> evels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EMPTYce
> lls NOOMITted OMITted NOLSTRETCH LSTRETCH COEFlegend SELEGEND cformat(string
> ) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru) FVW
> RAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(passthru) NOA
> BBREV ABBREV
    - syntax namelist(max=2) [, `DIOPTS' *]
    = syntax namelist(max=2) [, Level(cilevel) vsquish NOALLBASEle
> vels ALLBASElevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTY
> cells EMPTYcells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFlegend SELEGEND c
> format(string) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(
> passthru) FVWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(

```

```

> passthru) NOABBREV ABBREV *]
      - opts_exclusive "`allbaselevels' `noallbaselevels'"
      = opts_exclusive " "


---


> 

---

 begin opts_exclus
> ive 

---


      - version 8.2
      - args opts optname errcode optslab
      - local opts `opts'
      = local opts
      - local n 0
      - while ``opts' != "" {
      = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
      }
      - if `n' < 2 {
      = if 0 < 2 {
      - exit


---


> 

---

 end opts_exclus
> ive 

---


      - opts_exclusive "`allbaselevels' `nobaselevels'"
      = opts_exclusive " "


---


> 

---

 begin opts_exclus
> ive 

---


      - version 8.2
      - args opts optname errcode optslab
      - local opts `opts'
      = local opts
      - local n 0
      - while ``opts' != "" {
      = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
      }
      - if `n' < 2 {
      = if 0 < 2 {
      - exit


---


> 

---

 end opts_exclus
> ive 

---


      - opts_exclusive "`baselevels' `nobaselevels'"
      = opts_exclusive " "


---



```

```

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`emptycells' `noemptycells'"
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`fvlabel' `nofvlabel'"
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab

```

```

- local opts `opts'
= local opts
- local n 0
- while `"'opts'"' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
  }
- if `n' < 2 {
= if 0 < 2 {
- exit

```

```

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`omitted' `noomitted'"
    = opts_exclusive " "

```

```

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while `"'opts'"' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
      }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

```

```

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`lstretch' `nolstretch'"
    = opts_exclusive " "

```

```

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while `"'opts'"' != "" {

```

```

= while `""` != "" {
    local ++n
    gettoken item`n` opts : opts, bind
}
- if `n` < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`cnsreport` `fullcnsreport`"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts`
= local opts
    - local n 0
    - while `""opts`"" != "" {
= while `""` != "" {
    local ++n
    gettoken item`n` opts : opts, bind
}
    - if `n` < 2 {
= if 0 < 2 {
    - exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`coeflegend` `selegend`"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts`
= local opts
    - local n 0
    - while `""opts`"" != "" {
= while `""` != "" {
    local ++n
    gettoken item`n` opts : opts, bind
}

```

```

- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`noci' `nopvalues'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while "`opts'" != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- local K : list sizeof namelist
- gettoken c_diopts c_opts : namelist
- opts_exclusive "`coding' `compare'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while "`opts'" != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {

```



```

        - exit
    _____
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`versus' `compare'"
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`abbrev' `noabbrev'"
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____
> _____ end opts_exclus
> ive _____

```

```

- local allbaselevels `allbaselevels' `noallbaselevels'
= local allbaselevels
- local baselevels `baselevels' `nobaselevels'
= local baselevels
- local emptycells `emptycells' `noemptycells'
= local emptycells
- local omitted `omitted' `noomitted'
= local omitted
- local lstretch `lstretch' `nolstretch'
= local lstretch
- local fvlabel `fvlabel' `nofvlabel'
= local fvlabel
- local abbrev `abbrev' `noabbrev'
= local abbrev
- if "`allbaselevels'`baselevels'" == "" {
= if "" == "" {
- if c(showbaselevels) == "all" {
    local allbaselevels allbaselevels
  }
- else if c(showbaselevels) == "on" {
    local baselevels baselevels
  }
- }
- if "`emptycells'" == "" {
= if "" == "" {
- if c(showemptycells) == "off" {
    local emptycells noemptycells
  }
- }
- if "`omitted'" == "" {
= if "" == "" {
- if c(showomitted) == "off" {
    local omitted noomitted
  }
- }
- if "`lstretch'" == "" {
= if "" == "" {
- if c(lstretch) == "off" {
    local lstretch nolstretch
  }
- }
- if `:length local cformat' {
= if 0 {
    confirm numeric format `cformat'
    if fmtwidth("`cformat'") > 9 {
      local cformat "%9.0g"
    }
  }
}

```

```

di "{txt}note: invalid cformat(), using default"
}
sreturn local cformat ``cformat''
local cformat `cformat(`cformat')''
}
- if `:length local sformat' {
= if 0 {
confirm numeric format `sformat'
if fmtwidth(`sformat') > 8 {
local sformat "%8.2f"
di "{txt}note: invalid sformat(), using default"
}
sreturn local sformat ``sformat''
local sformat `sformat(`sformat')''
}
- if `:length local pformat' {
= if 0 {
confirm numeric format `pformat'
if fmtwidth(`pformat') > 5 {
local pformat "%5.3f"
di "{txt}note: invalid pformat(), using default"
}
sreturn local pformat ``pformat''
local pformat `pformat(`pformat')''
}
- if `K' == 1 & `:length local options' {
= if 2 == 1 & 0 {
syntax namelist(max=2) [, `DIOPTS']
}
- if reldif(`level', c(level)) > 1e-3 {
= if reldif(95, c(level)) > 1e-3 {
local levelopt level(`level')
}
- Wraapon , `fvwraapon'
= Wraapon ,

```

```

> _____ begin _get_diopts.Wra
> pon _____

```

```

- capture syntax [, W0rd WIdth]
- if c(rc) {
di as err "invalid fvwrapon() option;"
syntax [, W0rd WIdth]
exit 198
}
- opts_exclusive ``word' `width'' fvwrapon
= opts_exclusive " " fvwrapon

```

```

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - local fwraupon `word' `width'
    = local fwraupon
    - if `:length local fwraupon' {
    = if 0 {
        c_local fwraupon fwraupon(`fwraupon')
    }
    _____

> _____ end _get_diopts.Wra
> pon _____
    - if "`fwwrap'" != "" {
    = if "" != "" {
        FWWrap, `fwwrap'
    }
    - c_local `c_diopts' `levelopt' `vsquish' `allbaselevels' `bas
> elevels' `cnsreport' `fullcnsreport' `emptycells' `omitted' `lstretch' `coef
> legend' `selegend' `cformat' `sformat' `pformat' `coding' `versus' `compare'
> `fwwrap' `fwraupon' `fvlabel' `nocl' `nopvalues' `markdown' `citype' `abbre
> v'
    = c_local diopts
    - if `K' == 2 {
    = if 2 == 2 {
        - c_local `c_opts' ``options'
    = c_local options `"'
        - }
    - sreturn local coding `coding'
    = sreturn local coding
    - sreturn local versus `versus'

```

```

= sreturn local versus
- sreturn local compare `compare'
= sreturn local compare
- sreturn local level `level'
= sreturn local level 95


---


> 

---

 end _get_diopts.GetDio
> pts 

---


- c_local `name1' ``diopsts'""
= c_local diopsts `""'
- local snames : s(macros)
- foreach sname of local snames {
- local S_`sname' = s(`sname')
= local S_level = s(level)
- }
- local S_`sname' = s(`sname')
= local S_k = s(k)
- }
- local S_`sname' = s(`sname')
= local S_k_fill = s(k_fill)
- }
- local S_`sname' = s(`sname')
= local S_before = s(before)
- }
- local S_`sname' = s(`sname')
= local S_after = s(after)
- }
- local S_`sname' = s(`sname')
= local S_optlist = s(optlist)
- }
- local S_`sname' = s(`sname')
= local S_namelist = s(namelist)
- }
- local S_`sname' = s(`sname')
= local S_deriv = s(deriv)
- }
- local S_`sname' = s(`sname')
= local S_nolog = s(nolog)
- }
- sreturn clear
- GetDiopts DEFAULT


---


> 

---

 begin _get_diopts.GetDio
> pts 

---


- local DIOPTS Level(cilevel) vsquish NOALLBASElevels ALLBASEl
> evels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EMPTYce

```

```

> lls NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cformat(string
> ) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru) FVW
> RAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(passthru) NOA
> BBREV ABBREV
    - syntax namelist(max=2) [, `DIOPTS' *]
    = syntax namelist(max=2) [, Level(cilevel) vsquish NOALLBASEle
> vels ALLBASElevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTY
> cells EMPTYcells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND c
> format(string) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(
> passthru) FVWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(
> passthru) NOABBREV ABBREV *]
    - opts_exclusive "`allbaselevels' `noallbaselevels'"
    = opts_exclusive " "


---


> 

---

 begin opts_exclus
> ive 

---


    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit


---


> 

---

 end opts_exclus
> ive 

---


    - opts_exclusive "`allbaselevels' `nobaselevels'"
    = opts_exclusive " "


---


> 

---

 begin opts_exclus
> ive 

---


    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind

```

```

        }
        - if `n' < 2 {
        = if 0 < 2 {
        - exit
    }
}
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`baselevels' `nobaselevels'"
    = opts_exclusive " "
}
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
}
}
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`emptycells' `noemptycells'"
    = opts_exclusive " "
}
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
}
}

```

```

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`fvlabel' `nofvlabel'"
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ```opts'`` != "" {
    = while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`omitted' `noomitted'"
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ```opts'`` != "" {
    = while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`lstretch' `nolstretch'"

```



```

= opts_exclusive " "
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____
> _____ end opts_exclus
> ive _____
    - opts_exclusive ``cnsreport' `fullcnsreport'
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____
> _____ end opts_exclus
> ive _____
    - opts_exclusive ``coeflegend' `selegend'
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____

```

```

- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit

```

```

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`noci' `nopvalues'"
    = opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

```

```

> ----- end opts_exclus
> ive -----
    - local K : list sizeof namelist
    - gettoken c_diopts c_opts : namelist
    - opts_exclusive "`coding' `compare'"
    = opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab

```

```

- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
  }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`versus' `compare'"
= opts_exclusive " "
}

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
  }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`abbrev' `noabbrev'"
= opts_exclusive " "
}

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {

```

```

= while `""` != "" {
    local ++n
    gettoken item`n` opts : opts, bind
}
- if `n` < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- local allbaselevels `allbaselevels' `noallbaselevels'
= local allbaselevels
- local baselevels `baselevels' `nobaselevels'
= local baselevels
- local emptycells `emptycells' `noemptycells'
= local emptycells
- local omitted `omitted' `noomitted'
= local omitted
- local lstretch `lstretch' `nolstretch'
= local lstretch
- local fvlabel `fvlabel' `nofvlabel'
= local fvlabel
- local abbrev `abbrev' `noabbrev'
= local abbrev
- if "`allbaselevels'`baselevels'" == "" {
= if "" == "" {
- if c(showbaselevels) == "all" {
    local allbaselevels allbaselevels
}
- else if c(showbaselevels) == "on" {
    local baselevels baselevels
}
- }
- if "`emptycells'" == "" {
= if "" == "" {
- if c(showemptycells) == "off" {
    local emptycells noemptycells
}
- }
- if "`omitted'" == "" {
= if "" == "" {
- if c(showomitted) == "off" {
    local omitted noomitted
}
- }
- if "`lstretch'" == "" {

```

```

= if "" == "" {
- if c(lstretch) == "off" {
  local lstretch nolstretch
}
- }
- if `:length local cformat' {
= if 0 {
  confirm numeric format `cformat'
  if fmtwidth(`""cformat'') > 9 {
    local cformat "%9.0g"
    di "{txt}note: invalid cformat(), using default"
  }
  sreturn local cformat `""cformat''
  local cformat `cformat(`cformat')''
}
- if `:length local sformat' {
= if 0 {
  confirm numeric format `sformat'
  if fmtwidth(`""sformat'') > 8 {
    local sformat "%8.2f"
    di "{txt}note: invalid sformat(), using default"
  }
  sreturn local sformat `""sformat''
  local sformat `sformat(`sformat')''
}
- if `:length local pformat' {
= if 0 {
  confirm numeric format `pformat'
  if fmtwidth(`""pformat'') > 5 {
    local pformat "%5.3f"
    di "{txt}note: invalid pformat(), using default"
  }
  sreturn local pformat `""pformat''
  local pformat `pformat(`pformat')''
}
- if `K' == 1 & `:length local options' {
= if 1 == 1 & 0 {
  syntax namelist(max=2) [, `DIOPTS']
}
- if reldif(`level', c(level)) > 1e-3 {
= if reldif(95, c(level)) > 1e-3 {
  local levelopt level(`level')
}
- Wraon , `fvwraon'
= Wraon ,

```

```

> ----- begin _get_diopts.Wra
> pon -----
    - capture syntax [, W0rd WIdth]
    - if c(rc) {
        di as err "invalid fvwrapon() option;"
        syntax [, W0rd WIdth]
        exit 198
    }
    - opts_exclusive "`word' `width'" fvwrapon
    = opts_exclusive " " fvwrapon
    -----

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ```opts'"" != "" {
    = while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
        - exit
    -----

> ----- end opts_exclus
> ive -----
    - local fvwrapon `word' `width'
    = local fvwrapon
    - if `:length local fvwrapon' {
    = if 0 {
        c_local fvwrapon fvwrapon(`fvwrapon')
    }
    -----

> ----- end _get_diopts.Wra
> pon -----
    - if "`fvwrap'" != "" {
    = if "" != "" {
        FVWrap, `fvwrap'
    }
    - c_local `c_diopts' `levelopt' `vsquish' `allbaselevels' `bas
> elevels' `cnsreport' `fullcnsreport' `emptycells' `omitted' `lstretch' `coef
> legend' `selegend' `cformat' `sformat' `pformat' `coding' `versus' `compare'
> `fvwrap' `fvwrapon' `fvlabel' `nocl' `nopvalues' `markdown' `citype' `abbre

```

```

> v'
    = c_local DEFAULT
    - if `K' == 2 {
    = if 1 == 2 {
        c_local `c_opts' ``options''
    }
    - sreturn local coding `coding'
    = sreturn local coding
    - sreturn local versus `versus'
    = sreturn local versus
    - sreturn local compare `compare'
    = sreturn local compare
    - sreturn local level `level'
    = sreturn local level 95
    _____
> _____ end _get_diopts.GetDio
> pts _____
    - if ``name2'' == "" {
    = if ``options'' == "" {
        GetDiopts DUPS, `options'
    }
    - else {
    - GetDiopts DUPS options, `options'
    = GetDiopts DUPS options,
    _____
> _____ begin _get_diopts.GetDio
> pts _____
    - local DIOPTS Level(cilevel) vsquish NOALLBASElevels ALLBASEle
> evels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EMPTYce
> lls NOOMITted OMITted NOLSTRETCH LSTRETCH COEFlegend SELEGEND cformat(string
> ) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru) FVW
> RAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(passthru) NOA
> BBREV ABBREV
    - syntax namelist(max=2) [, `DIOPTS' *]
    = syntax namelist(max=2) [, Level(cilevel) vsquish NOALLBASEle
> vels ALLBASElevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTY
> cells EMPTYcells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFlegend SELEGEND c
> format(string) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(
> passthru) FVWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(
> passthru) NOABBREV ABBREV *]
    - opts_exclusive ``allbaselevels' `noallbaselevels''
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2

```

```

- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`allbaselevels' `nbaselevels'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`baselevels' `nbaselevels'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0

```



```

- while ``opts'' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> _____ end opts_exclus
> ive _____
- opts_exclusive "`emptycells' `noemptycells'"
= opts_exclusive " "
}

> _____ begin opts_exclus
> ive _____
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts'' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> _____ end opts_exclus
> ive _____
- opts_exclusive "`fvlabel' `nofvlabel'"
= opts_exclusive " "
}

> _____ begin opts_exclus
> ive _____
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts'' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}

```

```

        }
        - if `n' < 2 {
        = if 0 < 2 {
        - exit
    }
}
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`omitted' `noomitted'"
    = opts_exclusive " "
}
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
}
}
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`lstretch' `nolstretch'"
    = opts_exclusive " "
}
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
}
}

```

```

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`cnsreport' `fullcnsreport'"
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`coeflegend' `selegend'"
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`noci' `nopvalues'"

```

```

= opts_exclusive " "


---


> 

---

 begin opts_exclus
> ive 

---


    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit


---


> 

---

 end opts_exclus
> ive 

---


    - local K : list sizeof namelist
    - gettoken c_diopts c_opts : namelist
    - opts_exclusive "`coding' `compare'"
    = opts_exclusive " "


---


> 

---

 begin opts_exclus
> ive 

---


    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit


---


> 

---

 end opts_exclus
> ive 

---


    - opts_exclusive "`versus' `compare'"
    = opts_exclusive " "


---



```

```

> ----- begin opts_exclus
> ive
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    -----

> ----- end opts_exclus
> ive
    - opts_exclusive "`abbrev' `noabbrev'"
    = opts_exclusive " "
    -----

> ----- begin opts_exclus
> ive
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    -----

> ----- end opts_exclus
> ive
    - local allbaselevels `allbaselevels' `noallbaselevels'
    = local allbaselevels
    - local baselevels `baselevels' `nobaselevels'
    = local baselevels
    - local emptycells `emptycells' `noemptycells'
    = local emptycells
    - local omitted `omitted' `noomitted'

```

```

= local omitted
- local lstretch `lstretch' `nolstretch'
= local lstretch
- local fvlabel `fvlabel' `nofvlabel'
= local fvlabel
- local abbrev `abbrev' `noabbrev'
= local abbrev
- if "`allbaselevels'`baselevels'" == "" {
= if "" == "" {
- if c(showbaselevels) == "all" {
  local allbaselevels allbaselevels
}
- else if c(showbaselevels) == "on" {
  local baselevels baselevels
}
- }
- if "`emptycells'" == "" {
= if "" == "" {
- if c(showemptycells) == "off" {
  local emptycells noemptycells
}
- }
- if "`omitted'" == "" {
= if "" == "" {
- if c(showomitted) == "off" {
  local omitted noomitted
}
- }
- if "`lstretch'" == "" {
= if "" == "" {
- if c(lstretch) == "off" {
  local lstretch nolstretch
}
- }
- if `:length local cformat' {
= if 0 {
  confirm numeric format `cformat'
  if fmtwidth("`cformat'") > 9 {
    local cformat "%9.0g"
    di "{txt}note: invalid cformat(), using default"
  }
  sreturn local cformat "`cformat'"
  local cformat `cformat(`cformat')'
}
- if `:length local sformat' {
= if 0 {

```

```

confirm numeric format `sformat'
if fmtwidth("`sformat'") > 8 {
local sformat "%8.2f"
di "{txt}note: invalid sformat(), using default"
}
sreturn local sformat "`sformat'"
local sformat `sformat(`sformat')"'
}
- if `:length local pformat' {
= if 0 {
confirm numeric format `pformat'
if fmtwidth("`pformat'") > 5 {
local pformat "%5.3f"
di "{txt}note: invalid pformat(), using default"
}
sreturn local pformat "`pformat'"
local pformat `pformat(`pformat')"'
}
- if `K' == 1 & `:length local options' {
= if 2 == 1 & 0 {
syntax namelist(max=2) [, `DIOPTS']
}
- if reldif(`level', c(level)) > 1e-3 {
= if reldif(95, c(level)) > 1e-3 {
local levelopt level(`level')
}
- Wrapon , `fvwrapon'
= Wrapon ,

```

```

> _____ begin _get_diopts.Wra
> pon _____

```

```

- capture syntax [, W0rd WIdth]
- if c(rc) {
di as err "invalid fvwrapon() option;"
syntax [, W0rd WIdth]
exit 198
}
- opts_exclusive "`word' `width'" fvwrapon
= opts_exclusive " " fvwrapon

```

```

> _____ begin opts_exclus
> ive _____

```

```

- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts

```

```

- local n 0
- while ``opts'' != "" {
= while `""' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> _____ end opts_exclus
> ive _____
- local fvwrapon `word' `width'
= local fvwrapon
- if `:length local fvwrapon' {
= if 0 {
    c_local fvwrapon fvwrapon(`fvwrapon')
    }
}

> _____ end _get_diopts.Wra
> pon _____
- if ``fvwrap'' != "" {
= if "" != "" {
    FVWrap, `fvwrap'
    }
- c_local `c_diopts' `levelopt' `vsquish' `allbaselevels' `bas
> elevels' `cnsreport' `fullcnsreport' `emptycells' `omitted' `lstretch' `coef
> legend' `selegend' `cformat' `sformat' `pformat' `coding' `versus' `compare'
> `fvwrap' `fvwrapon' `fvlabel' `nocl' `nopvalues' `markdown' `citype' `abbre
> v'
= c_local DUPS
- if `K' == 2 {
= if 2 == 2 {
- c_local `c_opts' ``options''
= c_local options `""'
- }
- sreturn local coding `coding'
= sreturn local coding
- sreturn local versus `versus'
= sreturn local versus
- sreturn local compare `compare'
= sreturn local compare
- sreturn local level `level'
= sreturn local level 95

> _____ end _get_diopts.GetDio

```

```

> pts
- c_local `name2' ``options'''
= c_local options `'''
- }
- local DUPS : list DUPS - DEFAULT
- gettoken DUPS : DUPS
- if ``DUPS''' != "" {
= if `''' != "" {
    if (strpos(`DUPS'', "(")) {
    gettoken DUPS : DUPS, parse("(")
    local DUPS `DUPS'()'
    }
    di as err "duplicate {bf:`DUPS'} option not allowed"
    exit 198
  }
- sreturn clear
- foreach sname of local snames {
- sreturn local `sname' = ``S_`sname''''
= sreturn local level = `95''
- }
- sreturn local `sname' = ``S_`sname''''
= sreturn local k = `4''
- }
- sreturn local `sname' = ``S_`sname''''
= sreturn local k_fill = `4''
- }
- sreturn local `sname' = ``S_`sname''''
= sreturn local before = `, argoptlist(CLister) optlist(OIM OPG
> Robust) old ''
- }
- sreturn local `sname' = ``S_`sname''''
= sreturn local after = `, vce(robust)''
- }
- sreturn local `sname' = ``S_`sname''''
= sreturn local optlist = `CLuster''
- }
- sreturn local `sname' = ``S_`sname''''
= sreturn local namelist = `cluster''
- }
- sreturn local `sname' = ``S_`sname''''
= sreturn local deriv = `0''
- }
- sreturn local `sname' = ``S_`sname''''
= sreturn local nolog = `nolog''
- }

```

```

> _____ end _get_dio
> pts _____
    - _get_eformopts , eformopts(`options`) soptions allowed(__all__)
    = _get_eformopts , eformopts() soptions allowed(__all__)
    _____

> _____ begin _get_eformo
> pts _____
    - version 8.0
    - syntax [, eformopts(string asis) soptions ALLOWed(string) ]
    - local 0 , `eformopts'
    = local 0 ,
    - local EFALL NOHR hr NOSHR shr or IRr RRr tr TRatio
    - if "`soptions'" != "" {
    = if "soptions" != "" {
    - syntax [, EForm1(passthru) EForm `EFALL' * ]
    = syntax [, EForm1(passthru) EForm NOHR hr NOSHR shr or IRr RRr
> tr TRatio * ]
    - local opts ``options'`
    = local opts `''`
    - local 0 , `eform1' `eform' `nohr' `hr' `noshr' `shr' `or' `irr
> ' `rrr' `tr' `tratio'
    = local 0 ,
    - }
    - if "`allowed'" == "__all__" {
    = if "__all__" == "__all__" {
    - local allowed `EFALL'
    = local allowed NOHR hr NOSHR shr or IRr RRr tr TRatio
    - }
    - foreach ef of local allowed {
    - capture confirm name `ef'
    = capture confirm name NOHR
    - if _rc {
    di as err "`ef' is not a valid name"
    exit 198
    }
    - local efopts `efopts' `=lower("`ef'")'
    = local efopts nohr
    - }
    - capture confirm name `ef'
    = capture confirm name hr
    - if _rc {
    di as err "`ef' is not a valid name"
    exit 198
    }
    - local efopts `efopts' `=lower("`ef'")'
    = local efopts nohr hr

```

```

- }
- capture confirm name `ef'
= capture confirm name NOSHR
- if _rc {
  di as err "`ef' is not a valid name"
  exit 198
}
- local efopts `efopts' `=lower("`ef'")'
= local efopts nohr hr noshr
- }
- capture confirm name `ef'
= capture confirm name shr
- if _rc {
  di as err "`ef' is not a valid name"
  exit 198
}
- local efopts `efopts' `=lower("`ef'")'
= local efopts nohr hr noshr shr
- }
- capture confirm name `ef'
= capture confirm name or
- if _rc {
  di as err "`ef' is not a valid name"
  exit 198
}
- local efopts `efopts' `=lower("`ef'")'
= local efopts nohr hr noshr shr or
- }
- capture confirm name `ef'
= capture confirm name IRr
- if _rc {
  di as err "`ef' is not a valid name"
  exit 198
}
- local efopts `efopts' `=lower("`ef'")'
= local efopts nohr hr noshr shr or irr
- }
- capture confirm name `ef'
= capture confirm name RRr
- if _rc {
  di as err "`ef' is not a valid name"
  exit 198
}
- local efopts `efopts' `=lower("`ef'")'
= local efopts nohr hr noshr shr or irr rrr
- }

```



```

- }
- local eform `eform' ``ef''
= local eform
- }
- if ```eform1''=="Odds ratio" {
= if ``""=="Odds ratio" {
    local eform_cons_ti = "Odds"
    local eform_cons_note = "odds ratios"
    }
- else if ```eform1''=="Haz. ratio" {
= else if ``""=="Haz. ratio" {
    local eform_cons_ti = "Hazard"
    local eform_cons_note = "hazard ratios"
    }
- else if ```eform1''=="Time ratio" {
= else if ``""=="Time ratio" {
    local eform_cons_ti = "Time"
    local eform_cons_note = "time ratios"
    }
- else if ```eform1''=="IRR" {
= else if ``""=="IRR" {
    local eform_cons_ti = "Inc. rate"
    local eform_cons_note = "incidence-rate ratios"
    local eform_cons_ti2 = "incidence rate"
    }
- else if ```eform1''=="Risk ratio" {
= else if ``""=="Risk ratio" {
    local eform_cons_ti = "Risk"
    local eform_cons_note = "risk ratios"
    }
- else if ```eform1''=="Hlth ratio" {
= else if ``""=="Hlth ratio" {
    local eform_cons_ti = "Health"
    local eform_cons_note = "health ratios"
    }
- local k : list sizeof eform
- if `k' {
= if 0 {
    opts_exclusive "`eform'"
    if `:length local eform1' {
    opts_exclusive "eform() `eform'"
    }
    }
- if `k' {
= if 0 {
    if ("`eform'"=="eform") local eform1 = "exp(b)"

```

```

else if ("`eform`"=="hr") {
  local eform1 = "Haz. ratio"
  local eform_cons_ti = "Hazard"
  local eform_cons_note = "hazard ratios"
}
else if ("`eform`"=="shr") {
  local eform1 = "SHR"
  local eform_cons_ti = "Subhazard"
  local eform_cons_note = "subhazard ratios"
}
else if ("`eform`"=="tr") {
  local eform1 = "Time ratio"
  local eform_cons_ti = "Time"
  local eform_cons_note = "time ratios"
}
else if ("`eform`"=="tratio") {
  local eform1 = "Time ratio"
  local eform_cons_ti = "Time"
  local eform_cons_note = "time ratios"
}
else if ("`eform`"=="or") {
  local eform1 = "Odds ratio"
  if ("`e(cmd)`"=="asclogit" | "`e(cmd)`"=="cmclogit" | "`e(cmd)
> "`=="cmmixlogit" | "`e(cmd)`"=="cmxtmixlogit" ) {
    local eform_cons_ti = "Rel. risk"
    local eform_cons_note = "relative-risk ratios"
    local eform_cons_ti2 = "relative risk"
  }
  else {
    local eform_cons_ti = "Odds"
    local eform_cons_note = "odds ratios"
  }
}
else if ("`eform`"=="irr") {
  local eform1 = "IRR"
  local eform_cons_ti = "Inc. rate"
  local eform_cons_note = "incidence-rate ratios"
  local eform_cons_ti2 = "incidence rate"
}
else if ("`eform`"=="rrr") {
  local eform1 = "RRR"
  local eform_cons_ti = "Rel. risk"
  local eform_cons_note = "relative-risk ratios"
  local eform_cons_ti2 = "relative risk"
}
else if ("`eform`"!="nohr") & ("`eform`"!="noshr") {

```

```

        local eform1 = upper("`eform'")
    }
}
- sreturn clear
- sreturn local options ``opts'''
= sreturn local options `'''
- sreturn local opt `eform'
= sreturn local opt
- sreturn local str `eform1'
= sreturn local str
- if ``eform1''' != "" {
= if `''' != "" {
    sreturn local eform eform("`eform1'")
}
- else sreturn local eform ""
- sreturn local eform_cons_ti `eform_cons_ti'
= sreturn local eform_cons_ti
- sreturn local eform_cons_note `eform_cons_note'
= sreturn local eform_cons_note
- sreturn local eform_cons_ti2 `eform_cons_ti2'
= sreturn local eform_cons_ti2
}

> _____ end _get_eformo
> pts _____
    - local eform `s(eform)'
    = local eform
    - local diparm `s(options)'
    = local diparm
    - _get_diparmopts , diparmopts(`diparm') level(`level')
    = _get_diparmopts , diparmopts() level(95)
}

> _____ begin _get_diparmo
> pts _____
    - if _caller() < 8.2 {
        _get_diparmopts_8 `0'
        exit
    }
    - version 9
    - local version : di "version " string(_caller()) ":"
    - syntax [, diparmopts(string asis) EXECute soptions bottom plus
> SYNTAXonly * ]
    - local goptions `options'
    = local goptions level(95)
    - SpliceGlobals junk , `goptions'
    = SpliceGlobals junk , level(95)
}

```

```

> _____ begin _get_diparmopts.SpliceGlob
> als _____
    - syntax name(id="macro name" name=c_diparm) [, diparm(string
> asis) Level(cilevel) dof(passthru) syntaxonly ]
    - if ``dof`` == "" & ``e(df_r)`` != "" {
= if ```` == "" & ```` != "" {
    capture confirm integer number `e(df_r)`
    if !c(rc) {
    local gdof dof(`e(df_r)`)
    }
    capture
    }
    - else local gdof ``dof``
= else local gdof ````
    - local glevel `level`
= local glevel 95
    - local lopt level(`glevel`)
= local lopt level(95)
    - if (``diparm`` == "") exit
= if (```` == "") exit

> _____ end _get_diparmopts.SpliceGlob
> als _____
    - local 0 `", `diparmopts``
= local 0 `", ""
    - local diparmopts
    - local k 0
    - syntax [, diparm(string asis) * ]
    - while ``diparm`` != "" {
= while ```` != "" {
    local ++k
    local single 1
    local after
    capture _on_colon_parse `diparm`
    if !c(rc) {
    local single 0
    local diparm ``s(before)``
    local after ``s(after)``
    }
    capture
    SpliceGlobals diparm , diparm(`diparm`) `syntaxonly` `goptions

> `

    local diparm`k` ``diparm``
    local diparmopts ``diparmopts` : `diparm``
    if `single` | ``:list retok after`` == "" {
    local 0 `", `options``

```



```

syntax [, diparm(string asis) * ]
}
else {
local diparm ``after'''
}
}
- if ``soptions''' == "" {
= if `''' == "" {
- syntax [, diparm(string asis) ]
- }
- if (``execute'' == "") {
= if ("" == "") {
- sreturn clear
- sreturn local options ``options'''
= sreturn local options `'''
- sreturn local diparm ``diparmopts'''
= sreturn local diparm `'''
- forval i = 1/`k' {
= forval i = 1/0 {
sreturn local diparm`i' ``diparm`i''''
}
- sreturn local k `k'
= sreturn local k 0
- exit
}

> _____ end _get_diparmo
> pts _____
- if ``header'''=="" {
= if `'''=="" {
- _coef_table_header, `title'
= _coef_table_header,
}

> _____ begin _coef_table_he
> der _____
- version 9
- if !c(noisily) {
exit
}
- syntax [, rclass noHeader obj(string) head1left(numlist max=1
> integer >=0) head1right(numlist max=1 integer >=0) head2left(numlist max=1 i
> nteger >=0) head2right(numlist max=1 integer >=0) head2start(numlist max=1 i
> nteger >=1) width(numlist max=1 integer >=1) * ]
- if (``header'' != "") exit
= if ("" != "") exit
- if (``head2start'' != "" & ``width'' != "") {
= if ("" != "" & "" != "") {

```

```

opts_exclusive "head2start() width()"
exit 198
}
- local has_obj = (`""obj"" != "")
= local has_obj = (`"" != "")
- if (`has_obj' == 0) {
= if (0 == 0) {
- tempname obj
- }
- if ("`rclass'" != "") {
= if (" != ") {
    tempname rhold
    _return hold `rhold'
}
- `.obj' = .__coef_table__header.new, `rclass' `options'
= .__000005 = .__coef_table__header.new,
    -class __coef_table__header {
        - string result = "e"
        - string newline = "display"
        - double opt_dvheader = 0
        - double opt_modeltest = 0
        - double opt_cluster = 0
        - double opt_rules = 0
        - double opt_tvar = 0
        - double opt_septitle = 0
        - double linesize = 0
        - string title = ""
        - string title2 = ""
        - string groupvar = ""
        - string intmethod = ""
        - double intpoints = -1
        - string cmd = ""
        - string cmd2 = ""
        - string prefix = ""
        - double is_prefix = 0
        - double is_svy = 0
        - double is_margins = 0
        - double is_gsem = 0
        - double is_gsem_group = 0
        - double is_sem = 0
        - double is_areg = 0
        - double is_demand = 0
        - double is_demandn = 0
        - double is_bacon = 0
        - double is_htedid = 0
        - double is_xtvar = 0
    }

```

```

-      double  is_cfreg      = 0
-      double  is_sum       = 0
-      double  is_tab       = 0
-      double  is_r2_p      = 1
-      double  is_multclust = 0
-      double  is_stintcox   = 0
-      double  is_stmgintcox = 0
-      double  is_bmareg    = 0
-      double  prop_pushtitle = 0
-      double  prop_groupvar = 0
-      double  prop_censlimits = 0
-      double  prop_censored = 0
-      double  prop_nouncensored = 0
-      double  prop_iselected = 0
-      double  prop_selected  = 0
-      double  prop_groups    = 0
-      double  prop_balance   = 0
-      double  ablen          = 16
-      double  width          = 78
-      double  c1             = 1
-      double  c2             = 16
-      double  c2a            = 16
-      double  c3             = 49
-      double  c4             = 67
-      double  c2wfmt         = 10
-      double  c4wfmt         = 10
-      string  scheme         = "ml"
-      double  lalignr        = 0
-      double  ralignr        = 0
-      double  lalignl        = 0
-      double  ralignl        = 0
-      double  lalignla       = 0
-      double  ralignla       = 0
-      array   left
-      array   right
-}

```

```

> _____ begin _coef_table__header.

```

```

> new _____
- version 16
- syntax [, rclass noDVHeader noMODELtest TTitle(string asis) n
> ocluster noRULES noTVAR SEPTITLE linesize(int 0) ]
- if "`rclass'" != "" {
= if "" != "" {
  .result = "r"
}

```

```

- if "`dvheader'" == "" {
= if "" == "" {
- .opt_dvheader = 1
- }
- if "`modeltest'" == "" {
= if "" == "" {
- .opt_modeltest = 1
- }
- if "`cluster'" == "" {
= if "" == "" {
- .opt_cluster = 1
- }
- if "`rules'" == "" {
= if "" == "" {
- .opt_rules = 1
- }
- if "`tvar'" == "" {
= if "" == "" {
- .opt_tvar = 1
- }
- if "`septitle'" != "" {
= if "" != "" {
    .opt_septitle = 1
  }
- .linesize = `linesize'
= .linesize = 0
- .title = ``title'""
= .title = `""'
- if ``.result'"" == "e" {
= if `e' == "e" {
- .New4e

```

> _____ begin _coef_table__header.Ne

> w4e _____

```

- version 16
- .cmd = ``e(cmd)''
= .cmd = "poisson"
- .cmd2 = ``e(cmd2)''
= .cmd2 = ""
- .prefix = ``e(prefix)''
= .prefix = ""
- if ``.prefix'"" != "" {
= if `""' != "" {
    .is_prefix = 1
  }
- if ``.prefix'" == "svy" {

```

```

= if "" == "svy" {
  .is_svy = 1
}
- if "`cmd'" == "margins" {
= if "poisson" == "margins" {
  .is_margins = 1
}
- if inlist("`cmd'", "contrast", "pwcompare") {
= if inlist("poisson", "contrast", "pwcompare") {
  if "`cmd2'" == "margins" {
    .is_margins = 1
  }
}
- if "`cmd'" == "gsem" | "`cmd2'" == "gsem" {
= if "poisson" == "gsem" | "" == "gsem" {
  .is_gsem = 1
}
- if "`cmd'" == "sem" {
= if "poisson" == "sem" {
  .is_sem = 1
}
- if "`cmd'" == "areg" {
= if "poisson" == "areg" {
  .is_areg = 1
}
- if ("`cmd'" == "demandsys" & "`e(doheader)'"=="yes") {
= if ("poisson" == "demandsys" & `""'=="yes") {
  .is_demand = 1
}
- if ("`cmd'" == "demandsys") {
= if ("poisson" == "demandsys") {
  .is_demandn = 1
}
- if ("`cmd'" == "xthdidregress" & "`e(inestat)'"=="") {
= if ("poisson" == "xthdidregress" & ""=="") {
  .is_htedid = 1
}
- if ("`cmd'" == "xtvar") {
= if ("poisson" == "xtvar") {
  .is_xtvar = 1
}
- if ("`cmd'" == "cfregress") {
= if ("poisson" == "cfregress") {
  .is_cfreg = 1
}
- if "`cmd'" == "stintcox" {

```

```

= if "poisson" == "stintcox" {
    .is_stintcox = 1
}
- if "`cmd'" == "stmgintcox" {
= if "poisson" == "stmgintcox" {
    .is_stmgintcox = 1
}
- if "`cmd'" == "bdecomp" {
= if "poisson" == "bdecomp" {
    .is_bacon = 1
}
- if "`cmd'" == "bmaregress" {
= if "poisson" == "bmaregress" {
    .is_bmareg = 1
}
- is_svysum `cmd'
= is_svysum poisson
}

> ----- begin is_svy
> sum -----
- version 9
- local SvySum mean prop proportion ratio total
- if `"'0'"' != "" & `:list 0 in SvySum' {
= if `"poisson"' != "" & 0 {
    return scalar is_svysum = 1
}
- else return scalar is_svysum = 0
}

> ----- end is_svy
> sum -----
- .is_sum = r(is_svysum)
- if `.is_svy' {
= if 0 {
    if "`cmd'" == "tabulate" {
        .is_tab = 1
    }
}
- if `.is_gsem' {
= if 0 {
    if `"'e(groupvar)'"' != "" & "`cmd2'" == "" {
        .is_gsem_group = 1
    }
}
- local clustvars `e(clustvar)'
= local clustvars
- local kclvar : list sizeof clustvars

```

```

> ))

- .is_multclust = ((`kclvar`>1) & ("`e(kcluster)'"=="matrix"

= .is_multclust = ((0>1) & ("'"=="matrix"))
- if `.is_multclust' {
= if 0 {
  .prop_pushtitle = 1
}
- local c2pfix 20
- if `.is_sem' | `.is_gsem_group' {
= if 0 | 0 {
  local crlen ``e(crittype)''
  local crlen : smcllength local crlen
  if `crlen' >= `c2pfix' {
    local c2pfix = `crlen' + 2
  }
}
- if `.is_sum' {
= if 0 {
  if `.linesize' > 62 {
    local offset = `.linesize' - 62
  }
  else local offset 0
  .width = 62 + `offset'
  .c2 = 18
  .c3 = 35 + `offset'
  .c4 = 51 + `offset'
  .c2wfmt = 7
  .c4wfmt = 10
  .scheme = "compact"
}
- else if `.is_prefix' | `.is_sem' | `.is_gsem_group' {
= else if 0 | 0 | 0 {
  .width = 78
  .c2 = `c2pfix'
  .c3 = 49
  .c4 = 67
  .c2wfmt = 9
  .c4wfmt = 10
  .scheme = "svy"
}
- if `.is_svy' {
= if 0 {
  local maxlen = `.width' - `.c2' - (`c2wfmt'+2) - 2 - (`c4' - `.c3'

> )-2

  if `maxlen' > 19 {
    local maxlen 19

```

```

    }
    local len : display %`maxlen'.0fc e(N_pop)
    local len : list retok len
    local len : length local len
    local ++maxlen
    local ++len
    if `.c4wfmt' <= `len' & `len' <= `maxlen' {
        .c3 = `.c3' + `.c4wfmt' - `len'
        .c4 = `.c4' + `.c4wfmt' - `len'
        .c4wfmt = `len'
    }
}

> _____ end _coef_table__header.Ne
> w4e _____
    - }
    - else {
        .New4r
    }
    - local props ```.Macro _coef_table_props'''

> _____ begin _coef_table__header.Ma
> cro _____
    - version 16
    - class exit `""`.result'(`0')'''
    = class exit `""'

> _____ end _coef_table__header.Ma
> cro _____
    = local props `""'
    - if `.is_sem' | `.is_gsem_group' | `:list posof "pushtitle" i
> n props' {
    = if 0 | 0 | 0 {
        .prop_pushtitle = 1
    }
    - if (`.is_demand' | `.is_htedid' | `.is_xtvar') {
    = if (0 | 0 | 0) {
        .prop_pushtitle = 1
    }
    - if (`.is_bmareg') {
    = if (0) {
        .prop_pushtitle = 1
    }
    - if `.is_sem' | `.is_gsem_group' | `:list posof "groupvar" in
> props' {
    = if 0 | 0 | 0 {

```



```

        .prop_groupvar = 1
    }
    - local list tobit cpoisson ivtobit metobit xttobit
    - local list2 metobit
    - if `:list posof "`cmd'" in list' | `:list posof "`cmd2'" i
> n list2' | `:list posof "censlimits" in props' {
    = if 0 | 0 | 0 {
        .prop_censlimits = !missing(e(N_unc))
    }
    - local list intreg tobit cpoisson ivtobit eintreg xtintreg xt
> tobit
    - local list2 meintreg metobit stintreg
    - if `:list posof "`cmd'" in list' | `:list posof "`cmd2'" i
> n list2' | `:list posof "censored" in props' {
    = if 0 | 0 | 0 {
        .prop_censored = !missing(e(N_unc))
    }
    - if `:list posof "nuncensored" in props' {
    = if 0 {
        .prop_nuncensored = 1
    }
    - local list eintreg
    - if `:list posof "`cmd'" in list' | `:list posof "iselected"
> in props' {
    = if 0 | 0 {
        .prop_iselected = 1
    }
    - local list eregress eprobit eoprobit
    - if `:list posof "`cmd'" in list' | `:list posof "selected"
> in props' {
    = if 0 | 0 {
        .prop_selected = 1
    }
    - if `:list posof "groups" in props' {
    = if 0 {
        .prop_groups = 1
        .groupvar = "`e(repanvar)'"
        .intmethod = "`e(reintmethod)'"
        .intpoints = e(reintpoints)
    }
    - local list xtreg xtprobit xtlogit xtcloglog xtfrontier xtint
> reg xtnbreg
    - local list `list' xtpoisson xttobit xtmlogit xtrc xtvar
    = local list xtreg xtprobit xtlogit xtcloglog xtfrontier xtint
> reg xtnbreg xtpoisson xttobit xtmlogit xtrc xtvar
    - local list2 xtlogit xtprobit xtologit xtmlogit

```

```

- if `:list posof "`cmd'" in list' | `:list posof "`cmd2'" i
> n list2' {
= if 0 | 0 {
    .prop_groups = 1
    .groupvar = "`e(ivar)'"
    .intmethod = "`e(intmethod)'"
    .intpoints = e(n_quad)
  }
- if "`cmd'" == "xtreg" | "`cmd2'" == "xtlogit" {
= if "poisson" == "xtreg" | "" == "xtlogit" {
    .is_r2_p = 0
  }
- if `:list posof "balance" in props' {
= if 0 {
    .prop_balance = 1
  }
- .left = {}
- .right = {}
}

> ----- end _coef_table__header.
> new -----
- if ("`rclass'" != "") {
= if ("'" != "") {
    _return restore `rhold'
    .`obj'.New4r
  }
- if ("`head1left'" != "") {
= if ("'" != "") {
    .`obj'.lalignla = `head1left'
  }
- if ("`head1right'" != "") {
= if ("'" != "") {
    .`obj'.ralignla = `head1right'
  }
- if ("`head2left'" != "") {
= if ("'" != "") {
    .`obj'.lalignr = `head2left'
  }
- if ("`head2right'" != "") {
= if ("'" != "") {
    .`obj'.ralignr = `head2right'
  }
- if ("`width'" != "") {
= if ("'" != "") {
    .`obj'.width = `width'
  }
}

```

```

- .`obj'.build
= .__000005.build

> _____ begin _coef_table__header.bu
> ild _____
- version 16
- if ```.title''' == "" {
= if `''' == "" {
- .title = ```.Macro title'''

> _____ begin _coef_table__header.Ma
> cro _____
- version 16
- class exit `""`.result'(`0')'''
= class exit `Poisson regression''

> _____ end _coef_table__header.Ma
> cro _____
= .title = `Poisson regression''
- .title2 = ```.Macro title2'''

> _____ begin _coef_table__header.Ma
> cro _____
- version 16
- class exit `""`.result'(`0')'''
= class exit `'''

> _____ end _coef_table__header.Ma
> cro _____
= .title2 = `'''
- }
- if `.is_areg' {
= if 0 {
local absvar ``e(absvar)''
if `:list sizeof absvar' > 1 {
.title2 = ""
}
else {
local absvar = abbrev("`absvar'", 22)
.title2 = "Absorbed variable: {res:`absvar'}"
}
}
- if `.prop_pushtitle' {
= if 0 {
if `.is_svy' & (``.cmd'' == "clogit" | ``.cmd'' == "xtmlogit
> " | ``.cmd2'' == "xtmlogit") {

```

```

}
else if `.is_stintcox' | `.is_bmareg' {
  .PushLeft ```.title'''
  .PushLeft ```.title2'''
  .title = ""
  .title2 = ""
}
else if `.is_stmgintcox' {
  if ("`e(strata)'" == "") {
    .PushLeft ```.title'''
    .PushLeft ```.title2'''
    .title = ""
    .title2 = ""
  }
  else {
    .PushLeft ```.title2'''
    .title2 = ""
  }
}
else {
  .PushLeft ```.title'''
  if `.is_areg' {
    .PushLeft ```.title2'''
  }
  .title = ""
  .title2 = ""
}
- if `.prop_groupvar' | `.is_gsem_group' {
= if 0 | 0 {
  local groupvar ```.Macro groupvar'''
  if (```.groupvar''' != "" & `.is_stintcox') {
    local s = cond(`:word count `groupvar''>1, "s", "")
    local grpvar = abbrev("`groupvar'",`.ablen')
    .PushLeft "Strata variable`s': {res}`grpvar'"
  }
  else if ```.groupvar''' != "" {
    local grpvar = abbrev("`groupvar'",`.ablen')
    .PushLeft "Grouping variable: {res}`grpvar'"
  }
}
- if (`.is_stintcox') {
= if (0) {
  .PushLeft ""
  local ndep = e(k_dv)
  if (`ndep'==2) {

```

```

tokenize `e(depvar)'
local ltime `1'
local rtime `2'
.PushLeft "Event-time interval:"
.PushLeft "  Lower endpoint: {res}`ltime'"
.PushLeft "  Upper endpoint: {res}`rtime'"
if "`e(strata)'" != "" {
.PushLeft ""
}
}
else {
.PushLeft "ID variable: {res}`e(id)'"
.PushLeft "Examination time: {res}`e(depvar)'"
.PushLeft "Status indicator: {res}`e(status)'"
}
}
- if (`.is_stmgintcox') {
= if (0) {
.PushLeft ""
.PushLeft "ID variable: {res}`e(id)'"
.PushLeft "Event variable: {res}`e(event)'"
local ndep = e(k_dv)
if (`ndep'==2) {
tokenize `e(depvar)'
local ltime `1'
local rtime `2'
.PushLeft "Event-time interval:"
.PushLeft "  Lower endpoint: {res}`ltime'"
.PushLeft "  Upper endpoint: {res}`rtime'"
if "`e(strata)'" != "" {
.PushLeft ""
}
}
else {
.PushLeft "Examination time: {res}`e(depvar)'"
.PushLeft "Status indicator: {res}`e(status)'"
}
}
- if `.is_svy' {
= if 0 {
.BuildLeft4svy
}
- else if `.is_prefix' {
= else if 0 {
if !`.is_margins' {
.Build4strata
}
}
}
}

```

```

    }
  }
  - if (` .is_tab' | ` .is_sum') & !missing(`.result'(N_stdize)) {
  = if (0 | 0) & !missing(e(N_stdize)) {
    .PushLeft "N. of std strata" " = " "as res" %`.c2wfmt'.0fc `
> .result'(N_stdize)
    }
  - .Build4tvar
    _____
> _____ begin _coef_table__header.Build4t
> var _____
    - version 16
    - if ` .opt_tvar' == 0 {
  = if 1 == 0 {
    exit
  }
  - if "" .Macro tvar'" == "" {
    _____
> _____ begin _coef_table__header.Ma
> cro _____
    - version 16
    - class exit ```.result'(`0')'''
  = class exit `'''
    _____
> _____ end _coef_table__header.Ma
> cro _____
    = if "" == "" {
    - exit
    _____
> _____ end _coef_table__header.Build4t
> var _____
    - if (` .is_stmgintcox') {
  = if (0) {
    .PushRight "Number of events" " = " "as res" %`.c4wfmt'.0fc
> e(N_events)
    .PushRight "Number of subjects" " = " "as res" %`.c4wfmt'.0f
> c e(N_sub)
    }
  - if (!missing(`.Scalar N') & ` .is_demandn'==0 & !`.is_bmareg'
> ) {
    _____
> _____ begin _coef_table__header.Sca
> lar _____
    - version 16
    - class exit ```= `.result'(`0')'''
  = class exit `217'''

```

```

> _____ end _coef_table__header.Sca
> lar _____
      = if (!missing(217) & 0==0 & !0) {
      - .PushRight "Number of obs" " = " "as res" %`.c4wfmt'.0fc `.S
> calar N'
      _____
> _____ begin _coef_table__header.Sca
> lar _____
      - version 16
      - class exit ```= `.result'(`0')''
      = class exit ``217''
      _____
> _____ end _coef_table__header.Sca
> lar _____
      = .PushRight "Number of obs" " = " "as res" %10.0fc 217
      _____
> _____ begin _coef_table__header.PushRi
> ght _____
      - version 16
      - gettoken tok rest : 0
      - gettoken eq rest : rest
      - gettoken dias rest : rest
      - if `:length local rest' {
      = if 12 {
      - local direst = ustrltrim("` : di `rest'")
      = local direst = ustrltrim("      217")
      - .ralignr = max(`.ralignr', udstrlen("`direst'"))
      = .ralignr = max(0, udstrlen("217"))
      - local len : di ``tok''
      = local len : di ``Number of obs''
      - local len : smcllength local len
      - .lalignr = max(`.lalignr', `len')
      = .lalignr = max(0, 13)
      - .right.Arrpush `\.C3' ``{lalign `\.lalignr':`tok}'`` `\.C4
> ' ``eq'' `dias' "{ralign `\.ralignr':`direst'}"
      = .right.Arrpush `\.C3' ``{lalign `\.lalignr':Number of obs}'
> `\.C4' " = " as res "{ralign `\.ralignr':217}"
      - }
      - else if `:length local tok' {
      = else if 13 {
      .right.Arrpush `\.C3' ``tok''
      }
      - else {
      .right.Arrpush
      }

```

```

> _____ end _coef_table__header.PushRi
> ght _____
      - }
      - if `.is_demandn' {
      = if 0 {
        if (e(N_estat_dsys)==.|""e(N_estat_dsys)""==""") {
          .PushRight "Number of obs" " = " "as res" %`.c4wfmt'.0fc `.S
> calar N'
          }
          else {
            .PushRight "Number of obs" " = " "as res" %`.c4wfmt'.0fc e(N
> _estat_dsys)
          }
          }
      - if `.is_demand' {
      = if 0 {
        .PushRight "Number of goods" " = " "as res" %`.c4wfmt'.0fc e
> (n_goods)
        .PushLeft "Expenditure variable: {result:`e(expenditures)}'"
        }
      - if `.is_demand' {
      = if 0 {
        if (""e(piconstant)""!="") {
          .PushRight "Price index constant" " = " "as res" %`.c2wfmt'.
> 4gc e(piconstant)
          .PushLeft ""
          }
          if (e(n_demos)>0) {
            local scaling = strproper("e(demo_type)")
            .PushLeft ""Demographic method: {text:`scaling}""
            .PushRight "Number of demographics" " = " "as res" %`.c2wfmt
> '.0fc e(n_demos)
          }
          .PushLeft ""
          local rsquare = strproper("e(r2_type)")
          .PushLeft ""rsquare' R2 of model for""
          local kdem = e(k_eq_old) + 1
          local labels ""e(labels)""
          forvalues i=1/`kdem' {
            if (""labels""=="") {
              .PushLeft " Good `i'" " = " "as res" %`.c2wfmt'.4f e(r2_`i'
> )
            }
            else {
              local xdm: word `i' of `labels'

```



```

        .PushLeft " `xdm'" " = " "as res" %`.c2wfmt'.4f e(r2_`i')
    }
}
    .PushLeft ""
}
- if `.is_bacon' {
= if 0 {
    .PushLeft "ATET" " = " "as res" %`.c2wfmt'.0g `e(atet)'
    .PushRight "Number of groups" " = " "as res" %`.c4wfmt'.0fc
> `e(N_groups)'
    .PushRight "Number of cohorts" " = " "as res" %`.c4wfmt'.0fc
> `e(N_timing)'
}
- if `.is_bmareg' {
= if 0 {
    local heredlab = proper("`e(heredity)')")
    .PushLeft "`e(sampling_lab)'"
    if "`heredlab'" != "" {
        .PushLeft "Heredity: {txt}`heredlab'"
        if !missing(e(burnin)) {
            .PushLeft ""
        }
    }
    else if !missing(e(burnin)) {
        .PushLeft ""
        .PushLeft ""
    }
    .PushLeft ""
    .PushLeft "Priors:"
    .PushLeft " Models: {txt}`e(mprior_lab)'"
    .PushLeft " Cons.: Noninformative"
    .PushLeft " Coef.: Zellner's g"
    .PushLeft " g: {txt}`e(gprior_lab)'"
    .PushLeft " sigma2: Noninformative"
    if !missing(e(burnin)) {
        .PushLeft
        .PushLeftRalign "{help j_bmaregress_sampcorr:Sampling correl
> ation}" " = " "as res" %`.c4wfmt'.4f e(sampcorr)
    }
    .PushRight "No. of obs" " = " "as res" %`.c4wfmt'.0fc `Scal
> ar N'
    .PushRight "No. of predictors" " = " "as res" %`.c4wfmt'.0fc
> e(p)
    .PushRightRalign "Groups" " = " "as res" %`.c4wfmt'.0fc e(p_
> groups)
    .PushRightRalign "Always" " = " "as res" %`.c4wfmt'.0fc e(p_

```

```

> always)
    .PushRight "No. of models" " = " "as res" %`.c4wfmt'.0fc e(k
> _models)
    .PushRightRalign "For CPMP >= .9" " = " "as res" %`.c4wfmt'.
> 0fc e(k_models_cpmp)
    .PushRight "Mean model size" " = " "as res" %`.c4wfmt'.3f e(
> msize_mean)
    if !missing(e(burnin)) {
    .PushRight "Burn-in" " = " "as res" %`.c4wfmt'.0fc e(burnin)
    .PushRight "MCMC sample size" " = " "as res" %`.c4wfmt'.0fc
> e(mcmcsz)
    .PushRight "Acceptance rate" " = " "as res" %`.c4wfmt'.4f e(
> arate)
    }
    else {
    if "`heredlab'" != "" {
    .PushRight
    }
    .PushRight
    }
    if !missing(e(shrinkage)) {
    .PushRight "Shrinkage, g/(1+g)" " = " "as res" %`.c4wfmt'.4f
> e(shrinkage)
    }
    else {
    .PushRight ""
    }
    if (e(sigma2) < 1e-3) {
    local sigfmt 8.4g
    }
    else {
    local sigfmt `.c4wfmt'.3f
    }
    .PushRight "Mean sigma2" " = " "as res" %`sigfmt' e(sigma2)
    }
    - if `.is_htedid' {
    = if 0 {
    .PushRight "Number of panels" " = " "as res" %`.c4wfmt'.0fc
> e(N_panels)
    }
    - if !missing(`.Scalar N_sub') & `.is_stintcox' {
    _____
> _____ begin _coef_table__header.Sca
> lar _____
    - version 16
    - class exit ```= `.result'(`0')'''

```

```

= class exit `".'"


---


> _____ end _coef_table__header.Sca
> lar _____
      = if !missing(.) & 0 {
        .PushRight "Number of subjects" " = " "as res" %`.c4wfmt'.0f
> c `Scalar N_sub'
      }
      - if `.is_areg' {
      = if 0 {
        local absvar "`e(absvar)'"
        if `:list sizeof absvar' == 1 {
          .PushRight "No. of categories" " = " "as res" %`.c4wfmt'.0fc
> e(k_absorb)
        }
        }
        - if `.is_sem' | `.is_gsem_group' {
      = if 0 | 0 {
        if ```.Macro groupvar''' != "" {
          .PushRight "Number of groups" " = " "as res" %`.c4wfmt'.0fc
> `Scalar N_groups'
        }
        }
        - if `.is_sem' & !`.is_svy' {
      = if 0 & !0 {
        .PushLeft `"Estimation method: {res:`.Macro method'}"'
        }
        - if `.prop_selected' {
      = if 0 {
        .Build4selected
        }
        - if `.is_svy' {
      = if 0 {
        .BuildRight4svy
        if `.prop_censored' {
          .PushRight
          .Build4censobs "header"
          .PushRight
          }
          }
        - else {
        - if `.is_margins' {
      = if 0 {
        .Build4subpop
        }
        - if `.prop_iselected' {

```

```

= if 0 {
  .Build4title
  .Build4iselected
}
- if `.prop_censored' {
= if 0 {
  .Build4title
  .Build4censobs
  if !`.is_prefix' {
    .PushRight
  }
}
- .Build4cluster
}

> _____ begin _coef_table__header.Build4clus
> ter _____
    - version 16
    - if `.is_multclust' {
= if 0 {
  .Build4mclust
  exit
}
- if missing(`.Scalar N_clust') {
}

> _____ begin _coef_table__header.Sca
> lar _____
    - version 16
    - class exit ```= `.result'(`0')'''
    = class exit ``".""
}

> _____ end _coef_table__header.Sca
> lar _____
    = if missing(.) {
    - exit
}

> _____ end _coef_table__header.Build4clus
> ter _____
    - .Build4reps
}

> _____ begin _coef_table__header.Build4r
> eps _____
    - version 16
    - if !missing(`.Scalar N_reps') {
}

> _____ begin _coef_table__header.Sca
> lar _____

```

```

- version 16
- class exit ```= ``.result'(`0')''''
= class exit ``.``'

> _____ end _coef_table__header.Sca
> lar _____
= if !missing(.) {
  .PushRight "Replications" " = " "as res" %`.c4wfmt'.0fc `.`
> Scalar N_reps'
  if `prop_censored' & !`.is_svy' {
    .PushRight
  }
}

> _____ end _coef_table__header.Build4r
> eps _____
- }
- if `prop_groups' {
= if 0 {
  .Build4groups
}
- if `is_stintcox' & ``e(strata)'' != "" {
= if 0 & "" != "" {
  if `ndep' == 2 {
    .PushRight
  }
}
- .Build4modeltest

> _____ begin _coef_table__header.Build4modelt
> est _____
- version 16
- if ``.result'' != "e" {
= if "e" != "e" {
  exit
}
- if `opt_modeltest' == 0 {
= if 1 == 0 {
  exit
}
- if ```.Macro k_eq_model'''' == "0" {

> _____ begin _coef_table__header.Ma
> cro _____
- version 16
- class exit ````.result'(`0')''''

```

```

= class exit `1`
> _____ end _coef_table__header.Ma
> cro _____
= if `1` == "0" {
  exit
}
- if missing(`.Scalar df_m`) {
> _____ begin _coef_table__header.Sca
> lar _____
- version 16
- class exit ``=.result'(`0')``
= class exit `3`
> _____ end _coef_table__header.Sca
> lar _____
= if missing(3) {
  exit
}
- if ``.Macro chi2`` != "" | ``.Macro df_r`` == "" {
> _____ begin _coef_table__header.Ma
> cro _____
- version 16
- class exit ``.result'(`0')``
= class exit `58.21194449752262`
> _____ end _coef_table__header.Ma
> cro _____
> _____ begin _coef_table__header.Ma
> cro _____
- version 16
- class exit ``.result'(`0')``
= class exit `""`
> _____ end _coef_table__header.Ma
> cro _____
= if `58.21194449752262` != "" | `""` == "" {
- .Build4chi2test
> _____ begin _coef_table__header.Build4chi2t
> est _____
- version 16
- local type `e(chi2type)`

```

```

= local type Wald
- if ``type'' == "" {
= if ``Wald'' == "" {
  local type Wald
}
- local didf = strtrim("`: di e(df_m)''")
= local didf = strtrim("3")
- if !missing(e(chi2)) {
- .PushRight ``type' chi2({res:`didf'})" " = " "as res" %`
> .c4wfmt'.2f e(chi2)
= .PushRight "Wald chi2({res:3})" " = " "as res" %10.2f e(
> chi2)

> _____ begin _coef_table__header.PushRi
> ght _____
- version 16
- gettoken tok rest : 0
- gettoken eq rest : rest
- gettoken dias rest : rest
- if `:length local rest' {
= if 15 {
- local direst = ustrltrim("`: di `rest'")
= local direst = ustrltrim("      58.21")
- .ralignr = max(`.ralignr', udstrlen("`direst'"))
= .ralignr = max(3, udstrlen("58.21"))
- local len : di ``tok''
= local len : di ``Wald chi2({res:3})''
- local len : smcllength local len
- .lalignr = max(`.lalignr', `len')
= .lalignr = max(13, 12)
- .right.Arrpush `'.C3' ``{lalign `'.lalignr':`tok}'" \
> `'.C4' ``eq'' `dias' "{ralign `'.ralignr':`direst'"
= .right.Arrpush `'.C3' ``{lalign `'.lalignr':Wald chi2({r
> es:3}})" `'.C4' " = " as res "{ralign `'.ralignr':58.21}"
- }
- else if `:length local tok' {
= else if 18 {
  .right.Arrpush `'.C3' ``tok''
}
- else {
  .right.Arrpush
}

> _____ end _coef_table__header.PushRi
> ght _____
- .PushRight "Prob > chi2" " = " "as res" %`.c4wfmt'.4f ch

```

```

> i2tail(e(df_m),e(chi2))
= .PushRight "Prob > chi2" " = " "as res" %10.4f chi2tail(
> e(df_m),e(chi2))

> _____ begin _coef_table__header.PushRi
> ght _____
- version 16
- gettoken tok rest : 0
- gettoken eq rest : rest
- gettoken dias rest : rest
- if `:length local rest' {
= if 33 {
- local direst = ustrltrim("` : di `rest'")
= local direst = ustrltrim(" 0.0000")
- .ralignr = max(`.ralignr', udstrlen("`direst'"))
= .ralignr = max(5, udstrlen("0.0000"))
- local len : di ``"tok""
= local len : di `"Prob > chi2"
- local len : smcllength local len
- .lalignr = max(`.lalignr', `len')
= .lalignr = max(13, 11)
- .right.Arrpush `\.C3' ``{lalign `\.lalignr':`tok}'" \
> `\.C4' ``eq" `dias' "{ralign `\.ralignr':`direst'"
= .right.Arrpush `\.C3' ``{lalign `\.lalignr':Prob > chi2}
> `` `\.C4' " = " as res "{ralign `\.ralignr':0.0000}"
- }
- else if `:length local tok' {
= else if 11 {
. right.Arrpush `\.C3' ``"tok""
}
- else {
. right.Arrpush
}

> _____ end _coef_table__header.PushRi
> ght _____
- }
- else {
local j_robust "{help j_robustsingular##|_new:`type' chi
> 2(`didf')}"
.PushRight "`j_robust" " = " "as res" %`.c4wfmt's "."
.PushRight "Prob > chi2" " = " "as res" %`.c4wfmt's "."
}

> _____ end _coef_table__header.Build4chi2t
> est _____

```



```

- }
- else {
  .Build4Ftest
}

```

```

> ----- end _coef_table__header.Build4modelt
> est -----
- .Build4r2

```

```

> ----- begin _coef_table__header.Build
> 4r2 -----
- version 16
- if "`result'" != "e" {
= if "e" != "e" {
  exit
}
- if !missing(e(r2)) {
  .PushRight "R-squared" " = " "as res" %`.c4wfmt'.4f e(r2)
}
- if !missing(e(r2_p)) & `.is_r2_p' {
= if !missing(e(r2_p)) & 1 {
- .PushRight "Pseudo R2" " = " "as res" %`.c4wfmt'.4f e(r2_p)
> )
= .PushRight "Pseudo R2" " = " "as res" %10.4f e(r2_p)

```

```

> ----- begin _coef_table__header.PushRi
> ght -----
- version 16
- gettoken tok rest : 0
- gettoken eq rest : rest
- gettoken dias rest : rest
- if `:length local rest' {
= if 15 {
- local direst = ustrltrim("` : di `rest'")
= local direst = ustrltrim(" 0.0893")
- .ralignr = max(`.ralignr', udstrlen("`direst'"))
= .ralignr = max(6, udstrlen("0.0893"))
- local len : di ``tok'""
= local len : di ``Pseudo R2'""
- local len : smcllength local len
- .lalignr = max(`.lalignr', `len')
= .lalignr = max(13, 9)
- .right.Arrpush \.C3' ``{lalign \.lalignr':`tok}'"" \.
> C4' ``eq'"" `dias' "{ralign \.ralignr':`direst'}"
= .right.Arrpush \.C3' ``{lalign \.lalignr':Pseudo R2}'"" \
> .C4' " = " as res "{ralign \.ralignr':0.0893}"

```

```

- }
- else if `:length local tok' {
= else if 9 {
    .right.Arrpush \`.C3' ``tok'''
    }
- else {
    .right.Arrpush
    }
}

> _____ end _coef_table__header.PushRi
> ght _____
- }
- if !missing(e(r2_a)) {
    .PushRight "Adj R-squared" " = " "as res" %`.c4wfmt'.4f e(
> r2_a)
    }
- if !missing(e(rmse)) {
    .PushRight "Root MSE" " = " "as res" %`.c4wfmt'.4f e(rmse)
    }
}

> _____ end _coef_table__header.Build
> 4r2 _____
- .Build4title
}

> _____ begin _coef_table__header.Build4ti
> tle _____
- version 16
- if `.opt_septitle' {
= if 0 {
    exit
    }
- if ``.title''' == "" {
= if `"Poisson regression"' == "" {
    exit
    }
- if `.left.arrnels' {
= if 0 {
    exit
    }
- local title `.title'
= local title Poisson regression
- local title2 `.title2'
= local title2
- local len : smcllength local title
- local len2 : smcllength local title2
- if `len2' > `len' {

```

```

= if 0 > 18 {
    local len = `len2'
}
- if `len' < (`c3' - 2) - (`c1' - 1) {
= if 18 < (49 - 2) - (1 - 1) {
- PushLeft ```.title'''
= PushLeft `"Poisson regression"'
}
}

> _____ begin _coef_table__header.PushL
> eft _____
    - version 16
    - gettoken tok rest : 0
    - gettoken eq rest : rest
    - gettoken dias rest : rest
    - if `:length local rest' {
    = if 0 {
        local direst : di `rest'
        local direst = strtrim("`direst'")
        local len : smcllength local direst
        .ralignl = max(`.ralignl', `len')
        local len : di ``tok'''
        local len : smcllength local len
        .lalignl = max(`.lalignl', `len')
        .left.Arrpush \`.C1' `{lalign \`.lalignl':`tok'}' \`.C
> 2' ``eq' `dias' "{ralign \`.ralignl':`direst'}"
    }
    - else if `:length local tok' {
    = else if 18 {
        - .left.Arrpush \`.C1' ``tok'''
        = .left.Arrpush \`.C1' `"Poisson regression"'
        - }
    - else {
        .left.Arrpush
    }
    }

> _____ end _coef_table__header.PushL
> eft _____
    - .title = ""
    - if `len2' {
    = if 0 {
        PushLeft ```.title2'''
        .title2 = ""
    }
    - }
    - .opt_septitle = 1

```

```

> _____ end _coef_table__header.Build4ti
> tle _____
      - if `.prop_censlimits' {
      = if 0 {
        .Build4censlimits 1
      }
      - .c2 = `.lalignl' + 1
      = .c2 = 0 + 1
      - .c3 = `.width' - `.lalignr' - `.ralignr' - 3 + 1
      = .c3 = 78 - 13 - 6 - 3 + 1
      - .c4 = `.c3' + `.lalignr'
      = .c4 = 57 + 13
      - if `.is_gsem' {
      = if 0 {
        if `.opt_dvheader' {
          gsem_depvar_header, left(`.left.objkey') right(`.right.objke
> y') c3(`.c3') c4(`.c4') c4wfmt(`.c4wfmt')
        }
      }
      - if `.is_xtvar' {
      = if 0 {
        local uno = (`e(rank_W)' < `e(Z_cols)') & (`e(J)' != .j)
        if ("`e(collapse)'"=="") {
          if (`uno'==0) {
          }
          else {
            local extra " {txt}"
          }
          .PushLeft "Number of moment conditions" " = " "as res" %`.c4
> wfmt'.0fc e(Z_cols) "`extra'"
        }
        else {
          if (`uno'==0) {
          }
          .PushLeft "Number of moment conditions" " = " "as res" %`.c4
> wfmt'.0fc e(Z_cols) " {txt}(collapsed)"
        }
        local uno = (`e(rank_W)' < `e(Z_cols)') & (`e(J)' != .j)
        if ("`e(collapse)'"==" & `uno'==0) {
        }
        if ("`e(collapse)'"==" & `uno'==1) {
          .PushLeft "Rank of weight matrix" " = " "as res" %`.c4wfmt'.
> 0fc e(rank_W) "{txt}{helpb j_xtvar_Jdf##lowrank:*)"
        }
        if ("`e(collapse)'"!=" & `uno'==0) {
        }
      }
    }
  }
}

```

```

        if ("`e(collapse)'"!=" & `uno'==1) {
            .PushLeft "Rank of weight matrix" " = " "as res" %`.c4wfmt'.
> 0fc e(rank_W) "{helpb j_xtvar_Jdf##lowrank:*}          {txt}"
        }
    }
- if `.is_cfreg' {
= if 0 {
    local k = e(k_paren)
    local mtypes `e(modeltypes)'
    local looklong: list uniq mtypes
    local kt: list sizeof looklong
    forvalues ei = 1(1) `=wordcount("`e(endog)'"')' {
        local enei : word `ei' of `e(endog)'
        _ms_parse_parts `enei'
        if (`r(omit)' & "`r(type)'"=="factor") {
            continue
        }
        local endog `endog' `enei'
    }
    if (`kt'>1 | `=wordcount("`endog'"')>1) local ess s
    .PushLeft
    .PushLeft
    .PushLeft
    if ("`e(r2)'"!="") if (`e(r2)'<.) .PushLeft
    .PushLeft "Endogenous variable model`ess':"
    local largo = 0
    forvalues i=1/`kt' {
        local x: word `i' of `looklong'
        if ("`x'"=="fprobit") {
            local x "Fractional probit"
        }
        local largo1 = strlen("`x'")
        local largo = max(`largo', `largo1')
        local largo1 = `largo'
    }
    forvalues j = 1/`kt' {
        local endj: word `j' of `looklong'
        forvalues i=1/`k' {
            local typo "`e(type`i)'"
            forvalues ei = 1(1) `=wordcount("`e(endogvars`i)'"')' {
                local eniei : word `ei' of `e(endogvars`i)''
                _ms_parse_parts `eniei'
                if (`r(omit)' & "`r(type)'"=="factor") {
                    continue
                }
                local insts`j'_`i' `insts`j'_`i'' `eniei'
            }
        }
    }
}

```

```

}
if ("`endj`"=="`typo`") {
local print`j` "`print`j` `insts`j`_`i`"
local print`j`= strltrim("`print`j`")
}
}
}
forvalues i=1/`kt` {
local slng = `largo` + 6
local x: word `i` of `looklong`
if ("`x`"=="fprobit") {
local x "Fractional probit"
}
else {
local x = strproper("`x`")
}
local y "`print`i`"
.left.Arrpush %`slng`s "      `x`: " "{res}`y`"
}
if ("`e(vcetype)`" == "HAC") {
local ktyp `e(hac_kernel)`
local fmt -6.0f
local adds "s"
if "`ktyp`" == "quadratic spectral" {
local ktyp "Quadratic spectral"
local fmt -6.3f
}
if `e(hac_lag)`==1 {
local adds
}
local hn : di "{txt}HAC kernel: {res}`ktyp`" "{txt} with {re
> s}" `:di %`fmt` `e(hac_lag)` "{txt} lag`adds`"
.pushLeft
.left.Arrpush %-48s "`hn`"
}
}
- .Build4crit

```

```

> ----- begin _coef_table__header.Build4c
> rit -----
- version 16
- if "`result'" != "e" {
= if "e" != "e" {
exit
}
- local offset 1

```

```

- local hascrit = !missing("`e(ll)'"') & !missing("`e(crit
> type)'"')
= local hascrit = !missing("`-382.7632402098075'"') & !missin
> g("`log pseudolikelihood"')
- if inlist("`e(dispers)'", "mean", "constant") {
= if inlist("", "mean", "constant") {
  if `hascrit' {
    local ++offset
    local crtype "`e(crittype)'"
    local clen : length local crtype
    .c2 = `clen' + 2
  }
  local didisp = strtrim("` : di e(dispers)'"')
  local DISPERS `""Dispersion: {res:`didisp'}""'
}
- .FillLeft `offset'
= .FillLeft 1

> _____ begin _coef_table__header.FillL
> eft _____
- version 16
- args offset
- local kr = `.right.arnels'
= local kr = 4
- local kl = `.left.arnels'
= local kl = 1
- local diff = `kr' - `kl' - 0`offset'
= local diff = 4 - 1 - 01
- forval i = 1/`diff' {
= forval i = 1/2 {
- .left.Arrpush ""
- }
- .left.Arrpush ""
- }

> _____ end _coef_table__header.FillL
> eft _____
- if `""DISPERS'"' != "" {
= if `""' != "" {
  .PushLeft `DISPERS'
}
- local crtype = upper(bsubstr("`e(crittype)'",1,1)) + bsu
> bstr("`e(crittype)'",2,.)
= local crtype = upper(bsubstr("`log pseudolikelihood",1,1)
> ) + bsubstr("`log pseudolikelihood",2,.)
- if `.is_sem' & "`e(critvalue)'" != "" & !`.is_svy' {

```

```

= if 0 & `""' != "" & !0 {
    .PushLeft
    .PushLeftRalign "`crtype'" " = " "as res" %10.0g e(critval
> ue)
    }
- else if `hascrit' {
= else if 1 {
- if `.is_gsem_group' {
= if 0 {
    local dill = strtrim("` : di %10.0g e(ll)'")
    .PushLeft "`crtype' = {res:`dill'}"
    }
- else {
- .PushLeftRalign "`crtype'" " = " "as res" %10.0g e(ll)
= .PushLeftRalign "Log pseudolikelihood" " = " "as res" %10.
> 0g e(ll)
    }
}

> ----- begin _coef_table__header.PushLeftRal
> ign -----
- version 16
- gettoken tok rest : 0
- gettoken eq rest : rest
- gettoken dias rest : rest
- if `:length local rest' {
= if 13 {
- local direst : di `rest'
= local direst : di %10.0g e(ll)
- local direst = strtrim("`direst'")
= local direst = strtrim("-382.76324")
- local len : smcllength local direst
- .ralignla = max(`.ralignla', `len')
= .ralignla = max(0, 10)
- local len : di `""tok'""'
= local len : di `"Log pseudolikelihood"'
- local len : smcllength local len
- .lalignla = max(`.lalignla', `len')
= .lalignla = max(0, 20)
- .left.Arrpush `C1' `{lalign `lalignla':`tok'}" `.`
> C2a' ""eq"" `dias' "{ralign `lalignla':`direst'}"
= .left.Arrpush `C1' `{lalign `lalignla':Log pseudolike
> lihood}" `C2a' " = " as res "{ralign `lalignla':-382.76324}"
- }
- else if `:length local tok' {
= else if 20 {
    .left.Arrpush `C1' `""tok'""'
    }
}

```



```

        - else {
          .left.Arrpush
        }
      }
    }
  }
end _coef_table__header.PushLeftRal
> ign
  - }
  - }
end _coef_table__header.Build4c
> rit
  - .c2 = `.lalignl' + 1
  = .c2 = 0 + 1
  - .c2a = `.lalignla' + 1
  = .c2a = 20 + 1
  - .c3 = `.width'-.lalignr'-.ralignr'-3+1
  = .c3 = 78-13-6-3+1
  - .c4 = `.c3' + `.lalignr'
  = .c4 = 57 + 13
end _coef_table__header.bu
> ild
  - if ("`head2start'" != "") {
  = if ("`head2start'" != "") {
    .`obj'.c3 = `head2start'
    .`obj'.c4 = `head2start' + `.`obj'.lalignr'
    .`obj'.width = `head2start' + `.`obj'.lalignr' + `.`obj'.ralig
  }
  - if (`has_obj' == 0) {
  = if (0 == 0) {
    - .`obj'.display
    = .__000005.display
  }
  - if (`has_obj' == 0) {
  = if (0 == 0) {
    - .`obj'.display
    = .__000005.display
  }
end _coef_table__header.disp
> lay
  - version 16
  - .ShowRules
end _coef_table__header.ShowRu
> les
  - version 16
  - if "`result'" != "e" {
  = if "e" != "e" {
    exit
  }

```

```

- if `.opt_rules' == 0 {
= if 1 == 0 {
    exit
  }
- if !inlist("`cmd'", "logistic", "logit", "probit") {
= if !inlist("poisson", "logistic", "logit", "probit") {
- exit
}

> _____ end _coef_table__header.ShowRu
> les _____
    - local nl = `.left.arnels'
    = local nl = 4
    - local nr = `.right.arnels'
    = local nr = 4
    - local K = max(`nl', `nr')
    = local K = max(4,4)
    - `.newline'
    = display

    - if ``.title''' != "" {
    = if `''' != "" {
      display as txt ``.title'''
      if ``.title2''' != "" {
        display as txt ``.title2'''
      }
      if `K' {
        display
      }
    }

    - forval i = 1/`K' {
    = forval i = 1/4 {
      - display as smcl as txt `.left['i']' as txt `.right['i']'
    }

> _____ begin _coef_table__header
> .C1 _____
    - version 16
    - class exit `"_col(`.c1')"'
    = class exit `"_col(1)"'

> _____ end _coef_table__header
> .C1 _____

> _____ begin _coef_table__header
> .C3 _____
    - version 16
    - class exit `"_col(`.c3')"'

```

```

                = class exit `"_col(57)""


---


> _____ end _coef_table__header
> .C3 _____


---


> _____ begin _coef_table__header
> .C4 _____
        - version 16
        - class exit `"_col(`.c4')""
        = class exit `"_col(70)""


---


> _____ end _coef_table__header
> .C4 _____
        = display as smcl as txt _col(1) `"Poisson regression"' as txt
> _col(57) `{lalign 13:Number of obs}' _col(70) " = " as res "{ralign 6:217
> }"
Poisson regression                                Number of obs =    217
        - }
        - display as smcl as txt `.left['i']' as txt `.right['i']'


---


> _____ begin _coef_table__header
> .C3 _____
        - version 16
        - class exit `"_col(`.c3')""
        = class exit `"_col(57)""


---


> _____ end _coef_table__header
> .C3 _____


---


> _____ begin _coef_table__header
> .C4 _____
        - version 16
        - class exit `"_col(`.c4')""
        = class exit `"_col(70)""


---


> _____ end _coef_table__header
> .C4 _____
        = display as smcl as txt  as txt _col(57) `{lalign 13:Wald ch
> i2({res:3})}' _col(70) " = " as res "{ralign 6:58.21}"
                                                Wald chi2(3) =    58.21
        - }
        - display as smcl as txt `.left['i']' as txt `.right['i']'


---


> _____ begin _coef_table__header
> .C3 _____
        - version 16

```

```

- class exit `"_col(`.c3')"'
= class exit `"_col(57)"'
_____
> _____ end _coef_table__header
> .C3 _____
_____
> _____ begin _coef_table__header
> .C4 _____
- version 16
- class exit `"_col(`.c4')"'
= class exit `"_col(70)"'
_____
> _____ end _coef_table__header
> .C4 _____
= display as smcl as txt as txt _col(57) `{lalign 13:Prob >
> chi2}"" _col(70) " = " as res "{ralign 6:0.0000}"
Prob > chi2 = 0.0000
- }
- display as smcl as txt `.left['i']' as txt `.right['i']'
_____
> _____ begin _coef_table__header
> .C1 _____
- version 16
- class exit `"_col(`.c1')"'
= class exit `"_col(1)"'
_____
> _____ end _coef_table__header
> .C1 _____
_____
> _____ begin _coef_table__header.
> C2a _____
- version 16
- class exit `"_col(`.c2a')"'
= class exit `"_col(21)"'
_____
> _____ end _coef_table__header.
> C2a _____
_____
> _____ begin _coef_table__header
> .C3 _____
- version 16
- class exit `"_col(`.c3')"'
= class exit `"_col(57)"'
_____
> _____ end _coef_table__header
> .C3 _____

```

```

> _____ begin _coef_table__header
> .C4 _____
      - version 16
      - class exit `"_col(`.c4')"'
      = class exit `"_col(70)"'
> _____ end _coef_table__header
> .C4 _____
      = display as smcl as txt _col(1) `{lalign 20:Log pseudolikeli
> hood}"" _col(21) " = " as res "{ralign 10:-382.76324}" as txt _col(57) `{la
> lign 13:Pseudo R2}"" _col(70) " = " as res "{ralign 6:0.0893}"
Log pseudolikelihood = -382.76324 Pseudo R2 = 0.0893
      - }
> _____ end _coef_table__header.disp
> lay _____
      - }
      - sreturn local width_header `.`obj'.width'
      = sreturn local width_header 78
      - sreturn local head2_right `.`obj'.ralignr'
      = sreturn local head2_right 6
      - sreturn local head2_left `.`obj'.lalignr'
      = sreturn local head2_left 13
      - sreturn local head2_start `.`obj'.c3'
      = sreturn local head2_start 57
      - sreturn local head1_right `.`obj'.ralignla'
      = sreturn local head1_right 10
      - sreturn local head1_left `.`obj'.lalignla'
      = sreturn local head1_left 20
      - sreturn local head1_start `.`obj'.c1'
      = sreturn local head1_start 1
> _____ end _coef_table__hea
> der _____
      - di

```

```

- }
- _coef_table, `first' level(`level') `neqopt' `plus' `noskip' `sh
> oweqns' `diopts' `options' `notest'
= _coef_table, level(95)

> ----- begin _coef_ta
> ble -----
- version 11
- local vv : di "version " string(max(11,_caller())) ", missing:
> "
- if (!c(noisily) & c(coeftabresults) == "off") {
  exit
}
- _check_eclass
- syntax [, BMATrix(passthru) VMATrix(passthru) * ]
- if "`e(b)'" == "" & "`e(V)'" == "" & "`bmatrix'`vmatrix'"==""
> {
= if "matrix" == "" & "matrix" == "" & ""=="" {
  exit
}
- local mc_cmds contrast margins pwcompare pwmean
- local cmd "`e(cmd)'"
= local cmd "poisson"
- local keepmc : list cmd in mc_cmds
- if inlist("`cmd'", "pwcompare", "pwmean") {
= if inlist("poisson", "pwcompare", "pwmean") {
  local groups GROUPS
}
- if "`cmd'" == "regress" {
= if "poisson" == "regress" {
  local beta Beta
}
- if "`cmd'" == "gsem" {
= if "poisson" == "gsem" {
  local fvignore fvignore(int 0)
  local flignore flignore
}
- if "`cmd'" == "sem" {
= if "poisson" == "sem" {
  local standardized STANDARDIZED
  local showginvariant SHOWGINvariant
  local nolabel NOLABel LABel NOFVLABel FVLABel
  local nofootnote NOFOOTnote
  local wrap wrap(numlist max=1) fvwrap(passthru)
}
- if "`e(mi)'"=="mi" {

```

```

= if ""=="mi" {
    local dftable DFTable
    local dfonly DFONLY
    local noclustreport NOCLUSTReport
    local pisematrix PISEMATrix(string)
}
- syntax [, cmdextras BMATrix(string) VMATrix(string) EMATrix(st
> ring) DFMATrix(string) EQMATrix(string) ROWMATrix(string) CIMATrix(string) P
> MATrix(string) TSMATrix(string) ROWCFormat(string) ROWPFormat(string) ROWSFo
> rmat(string) NOROWCI MMATrix(string) MVMATrix(string) MEMATrix(string) BSTDM
> ATrix(string) CNSMATrix(string) PCLASSMATrix(string) Level(cilevel) prefix(n
> ame) cnszero(string) suffix(name) OFFSETlist(string asis) `beta' `standardiz
> ed' NOCI NOPValues `dftable' `dfonly' dfci DFPValues dfmissing `groups' COEF
> Legend selegend `fvignore' `flignore' `showginvariant' `nolabel' `nofootnote
> ' `wrap' sort `pisematrix' depname(string) COEFTitle(string) coeftitle2(stri
> ng) ptitle(string) cititle(string) NOMCLEGen noCNSReport FULLCNSReport `noc
> lustreport' cformat(passthru) sformat(passthru) pformat(passthru) NOFirst Fi
> rst SHOWEQns neq(integer -1) NODIPARM NOTEST SEPARATOR(integer 0) NOSKIP OFF
> SETONLY1 PLUS NOEQCHECK EFORMALL CITYPE(string) eqselect(string) cidisjoint
> noEFORMNOTE * ]
= syntax [, cmdextras BMATrix(string) VMATrix(string) EMATrix(st
> ring) DFMATrix(string) EQMATrix(string) ROWMATrix(string) CIMATrix(string) P
> MATrix(string) TSMATrix(string) ROWCFormat(string) ROWPFormat(string) ROWSFo
> rmat(string) NOROWCI MMATrix(string) MVMATrix(string) MEMATrix(string) BSTDM
> ATrix(string) CNSMATrix(string) PCLASSMATrix(string) Level(cilevel) prefix(n
> ame) cnszero(string) suffix(name) OFFSETlist(string asis) NOCI NOPValues
> dfci DFPValues dfmissing COEFLegend selegend sort depname(string) C
> OEFTitle(string) coeftitle2(string) ptitle(string) cititle(string) NOMCLEGen
> d noCNSReport FULLCNSReport cformat(passthru) sformat(passthru) pformat(pas
> sthru) NOFirst First SHOWEQns neq(integer -1) NODIPARM NOTEST SEPARATOR(inte
> ger 0) NOSKIP OFFSETONLY1 PLUS NOEQCHECK EFORMALL CITYPE(string) eqselect(st
> ring) cidisjoint noEFORMNOTE * ]
- if "`wrap'" != "" {
= if "" != "" {
    opts_exclusive `"wrap(`wrap') `fvwrap'"
    local fvwrap fvwrap(`wrap')
}
- if "`nolabel'`label'" != "" {
= if "" != "" {
    opts_exclusive "`nolabel' `label'"
    opts_exclusive "`nofvlabel' `fvlabel'"
    opts_exclusive "`nolabel' `fvlabel'"
    opts_exclusive "`nofvlabel' `label'"
    if "`nolabel'" != "" {
        local fvlabel nofvlabel
    }
}

```

```

        else {
            local fvlabel fvlabel
        }
    }
    - _novce_other_mats, cimatrix("`cimatrix'") pmatrix("`pmatrix'")
> tsmatrix("`tsmatrix'") `noci' `nopvalues' `dfci' `dfpvalues' `cidisjoint'
    = _novce_other_mats, cimatrix("") pmatrix("") tsmatrix("")

> _____ begin _coef_table._novce_other_m
> ats _____
        - syntax [anything], [ CIMATrix(string) PMATrix(string) TSMATr
> ix(string) NOCI NOPValues dfci DFPValues cidisjoint ]
        - if ("`pmatrix'"=="" & "`tsmatrix'"=="" & "`e(V)'"=="" & "`ci
> matrix'"!=" & "`noci'"!=") {
            = if ("==" & "==" & "matrix"==" & "!=" & "!=") {
                sreturn local cimatrix "empt"
            }
            - if ("`pmatrix'"=="" & "`tsmatrix'"!=" & "`e(V)'"=="" & "`ci
> matrix'"==" & ("`noci'"!="|`nopvalues'"!=")) {
                = if ("==" & "!=" & "matrix"==" & "==" & ("!="|!="
> )) {
                    sreturn local noci "empt"
                    sreturn local nopvalues "empt"
                }
            - if ("`pmatrix'"=="" & "`tsmatrix'"=="" & "`e(V)'"=="" & "`ci
> matrix'"!=" & "`noci'"!=") {
                = if ("==" & "==" & "matrix"==" & "!=" & "!=") {
                    sreturn local cimatrix "empt"
                }
            - if ("`pmatrix'"!=" & "`tsmatrix'"=="" & "`e(V)'"=="" & "`ci
> matrix'"==" & "`nopvalues'"!=") {
                = if ("!=" & "==" & "matrix"==" & "==" & "!=") {
                    sreturn local pmatrix "empt"
                }
            - if ("`pmatrix'"!=" & "`tsmatrix'"=="" & "`e(V)'"=="" & "`ci
> matrix'"==" & "`noci'"!=") {
                = if ("!=" & "==" & "matrix"==" & "==" & "!=") {
                    sreturn local noci "empt"
                }
            - if ("`pmatrix'"!=") {
                = if ("!=") {
                    tempname pmat invalid
                    capture matrix `pmat' = `pmatrix'
                    local rc = _rc
                    if (`rc') {
                        display as error "invalid {bf:pmatrix()}"

```



```

exit 198
}
else {
local k: rowsof `pmat'
if (`k'>1 | `k'==0) {
display as error "{bf:pmatix()} should be a row vector"
exit 198
}
}
scalar `isvalid' = 1
mata: _is_in_0_1void("`pmat'", "`isvalid'")
if (`isvalid'==0) {
display as error "invalid {bf:pmatix()}"
di as txt "{p 4 4 2}"
di as smcl as err "{bf:pmatix()}"
di as smcl as err "should contain values inside"
di as smcl as err "the interval [0,1]."
di as smcl as err "{p_end}"
exit 198
}
}
- if ("`tsmatrix'"!="") {
= if ("!=") {
tempname tmat
capture matrix `tmat' = `tsmatrix'
local rc = _rc
if (`rc') {
display as error "invalid {bf:tsmatrix()}"
exit 198
}
else {
local k: rowsof `tmat'
if (`k'>1 | `k'==0) {
display as error "{bf:tsmatrix()} should be a row vector"
exit 198
}
}
}
- if ("`cimatix'"!="") {
= if ("!=") {
tempname cimat isvalid
capture matrix `cimat' = `cimatix'
local rc = _rc
if (`rc') {
display as error "invalid {bf:cimatix()}"
exit 198
}
}
}

```

```

}
if ("`cidisjoint`"==" & "`e(disjoint)`"=="") {
  scalar `isvalid` = 1
  mata: _is_in_ci("`cimat`", "`isvalid`")
  if (`isvalid`==0) {
    display as error "invalid {bf:cimatrx()}"
    di as txt "{p 4 4 2}"
    di as smcl as err "{bf:cimatrx()}"
    di as smcl as err "lower limit should be"
    di as smcl as err "smaller than the upper"
    di as smcl as err "limit."
    di as smcl as err "{p_end}"
    exit 198
  }
}
}
- if ("`e(V)`"==" & "`dfci`"!=" & "`pmatrx`"!=") {
= if ("matrix"==" & ""!=" & ""!=") {
  opts_exclusive "pmatrx() `dfci`"
}
- if ("`e(V)`"==" & "`dfci`"!=" & "`tsmatrx`"!=") {
= if ("matrix"==" & ""!=" & ""!=") {
  opts_exclusive "tsmatrx() `dfci`"
}
- if ("`e(V)`"==" & "`dfci`"!=" & "`cimatrx`"!=") {
= if ("matrix"==" & ""!=" & ""!=") {
  opts_exclusive "cimatrx() `dfci`"
}
- if ("`e(V)`"==" & "`dfpvalues`"!=" & "`pmatrx`"!=") {
= if ("matrix"==" & ""!=" & ""!=") {
  opts_exclusive "pmatrx() `dfci`"
}
- if ("`e(V)`"==" & "`dfpvalues`"!=" & "`tsmatrx`"!=") {
= if ("matrix"==" & ""!=" & ""!=") {
  opts_exclusive "tsmatrx() `dfpvalues`"
}
- if ("`e(V)`"==" & "`dfpvalues`"!=" & "`cimatrx`"!=") {
= if ("matrix"==" & ""!=" & ""!=") {
  opts_exclusive "cimatrx() `dfpvalues`"
}
}

```

```

> _____ end _coef_table._novce_other_m
> ats _____

```

```

- if ("`s(cimatrx)`"=="empty") {
= if ("=="empty") {
  local cimatrx ""

```

```

    }
- if ("`s(pmatrix)'"=="empt") {
= if ("'"=="empt") {
    local pmatrix ""
    }
- if ("`s(noci)'"=="empt") {
= if ("'"=="empt") {
    local noci ""
    }
- if ("`s(nopvalues)'"=="empt") {
= if ("'"=="empt") {
    local nopvalues ""
    }
- if ("`e(V)'"!=" & "`cidisjoint'"!="") {
= if ("matrix"!=" & ""!="") {
    display in red "option {bf:cidisjoint} not allowed when e(V) i
> s posted"
    exit 198
    }
- else local fvlabel `nofvlabel' `fvlabel'
= else local fvlabel
- local type `coeflegend' `selegend'
= local type
- opts_exclusive "`type' `standardized'"
= opts_exclusive " "


---


> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while "`opts'" != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit


---


> ----- end opts_exclus
> ive -----
    - if (``rowmatrix'"==" & "`norowci'"!="") {
    = if (`'"==" & ""!="") {

```

```

        di as err "{bf:norowci} requires {bf:rowmatrix()}"
        exit 198
    }
- if ("`dftable'" != "" & "`norowci'" != "") {
= if ("'" != "" & "'" != "") {
    di as err "{bf:norowci} is not allowed with {bf:`dftable'}"
    exit 198
}
- if ("`dfonly'" != "" & "`norowci'" != "") {
= if ("'" != "" & "'" != "") {
    di as err "{bf:norowci} is not allowed with {bf:`dfonly'}"
    exit 198
}
- if ("`noci'" != "" & "`norowci'" != "") {
= if ("'" != "" & "'" != "") {
    di as err "{bf:norowci} is not allowed with {bf:`noci'}"
    exit 198
}
- if "`standardized'" != "" & "`bstdmatrix'" != "" {
= if "" != "" & "" != "" {
    local beta beta
    local standardized
}
- if `:length local type' == 0 {
= if 0 == 0 {
- local type `beta' `noci' `nopvalues' `dftable' `dfonly' `group
> s' `dfci' `dfpvalues'
    = local type
- }
- opts_exclusive "`type'"
= opts_exclusive ""

> _____ begin opts_exclus
> ive _____
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while "`opts'" != "" {
= while `""' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {

```

```

- exit
- end opts_exclus
>
> ive
- opts_exclusive "`first' `nofirst'"
= opts_exclusive " "
- begin opts_exclus
>
> ive
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
- end opts_exclus
>
> ive
- opts_exclusive "`first' `showeqns'"
= opts_exclusive " "
- begin opts_exclus
>
> ive
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
- end opts_exclus
>
> ive

```

```

- local cnsreport `cnsreport' `fullcnsreport'
= local cnsreport
- opts_exclusive ``cnsreport''
= opts_exclusive ""

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ```opts'`` != "" {
= while `""' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit

> ----- end opts_exclus
> ive -----
- if ```showeqns'`` != "" {
= if `""' != "" {
  local nofirst nofirst
}
- if ```ematrix'`noeqcheck'`` == "" {
= if `""' == "" {
- if ```e(error)'`` == "matrix" {
= if `""' == "matrix" {
  local ematrix e(error)
}
- }
- _get_mcompare, `options'
= _get_mcompare,

> ----- begin _get_mcomp
> are -----
- version 11
- local cmd ```e(cmd)'``
= local cmd ``poisson''
- syntax [name(name=caller)] [, *]
- local is_pwc = inlist("pwcompare", ``cmd'', ``caller'') | in
> list("pwmean", ``cmd'', ``caller'')
= local is_pwc = inlist("pwcompare", "poisson", "") | inlist("

```

```

> pwmean", "poisson", "")
      - local is_marg = inlist("margins", "`cmd'", "`e(cmd2)'", "`ca
> ller'")
      = local is_marg = inlist("margins", "poisson", "", "")
      - local OPTIONS NOADJust BONferroni DUNCAn DUNNett SCHeffe SID
> ak SNK TUKey ADJustall
      - if `is_pwc' {
      = if 0 {
          syntax [name] [, `OPTIONS' MCOMPare(string) *]
        }
      - else {
      - syntax [name] [, MCOMPare(string) *]
      - local suboption mcompare()
      - }
      - sreturn clear
      - sreturn local options ``options'''
      = sreturn local options `'''
      - if `is_pwc' {
      = if 0 {
          local METHOD `noadjust' `bonferroni' `duncan' `dunnett' `sch
> effe' `sidak' `snk' `tukey'
          local METHOD : list uniq METHOD
          opts_exclusive ``METHOD'''
          local ALL `adjustall'
          opts_exclusive ``noadjust' `ALL'''
        }
      - local 0 `", `mcompare'''
      = local 0 `", ""
      - capture syntax [, `OPTIONS']
      = capture syntax [, NOADJust BONferroni DUNCAn DUNNett SCHeffe
> SIDak SNK TUKey ADJustall]
      - if c(rc) {
          di as err "invalid mcompare() option;"
          di as err "method ``mcompare'' not allowed"
          error 198
        }
      - local METHOD `METHOD' `noadjust' `bonferroni' `duncan' `dunn
> ett' `scheffe' `sidak' `snk' `tukey'
      = local METHOD
      - local METHOD : list uniq METHOD
      - local ALL `ALL' `adjustall'
      = local ALL
      - local ALL : list uniq ALL
      - opts_exclusive ``METHOD''' `suboption'
      = opts_exclusive `` mcompare()

```

```

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ```opts'"" != "" {
    = while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
        }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    -----

> ----- end opts_exclus
> ive -----
    - if "`METHOD'" == "" {
    = if "" == "" {
    - if "`ALL'" != "" {
    = if "" != "" {
        di as err "multiple comparison method required with the adju
> stall option"
        exit 198
        }
    - local METHOD noadjust
    - local noadjust noadjust
    - }
    - opts_exclusive "`ALL' `noadjust'" `suboption'
    = opts_exclusive " noadjust" mcompare()
    -----

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts noadjust
    - local n 0
    - while ```opts'"" != "" {
    = while `"noadjust"' != "" {
    - local ++n
    - gettoken item`n' opts : opts, bind
    = gettoken item1 opts : opts, bind
    - }
    - while ```opts'"" != "" {

```



```

= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 1 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
    - local EXCLUDE duncan dunnett snk tukey
    - if `:list METHOD in EXCLUDE' {
= if 0 {
    if `is_pwc' {
        local opt : copy local METHOD
    }
    else {
        local opt "mcompare(`METHOD')"
    }
    local cmdlist anova manova regress mvreg pwmean
    if "`cmd'" == "pwcompare" {
        local cmd ``e(cmd_est)''
    }
    if `is_marg' {
        local cmd margins
    }
    if !`:list cmd in cmdlist' | !`is_pwc' {
        di as err ``method `opt' is not allowed with results from `c
> md'''
        exit 322
    }
    if ``e(prefix)'' == "svy" {
        di as err ``method `opt' is not allowed with results using t
> he svy prefix''
        exit 322
    }
    local vce ``e(vce)''
    if !inlist("`vce'", "", "ols") {
        di as err ``method `opt' is not allowed with results using v
> ce(`vce)''
        exit 322
    }
}
- local EXCLUDE duncan dunnett snk tukey scheffe
- if `:list METHOD in EXCLUDE' {
= if 0 {

```

```

        if "`ALL'" != "" {
        di as err `"option adjustall is not allowed with method `MET
> HOD'"
        exit 198
        }
        }
        - sreturn local method `"'METHOD'"
        = sreturn local method `"noadjust"
        - sreturn local adjustall `"'ALL'"
        = sreturn local adjustall `"''"
    }
}

> ----- end _get_mcomp
> are -----
        - local method `"'s(method)'"
        = local method `"noadjust"
        - local all `"'s(adjustall)'"
        = local all `"''"
        - local options `"'s(options)'"
        = local options `"''"
        - if "`method'" != "noadjust" {
        = if "noadjust" != "noadjust" {
            local keepmc 1
        }
        - opts_exclusive "`all' `groups'"
        = opts_exclusive " "
    }

> ----- begin opts_exclus
> ive -----
        - version 8.2
        - args opts optname errcode optslab
        - local opts `opts'
        = local opts
        - local n 0
        - while `"'opts'" != "" {
        = while `"' != "" {
            local ++n
            gettoken item`n' opts : opts, bind
        }
        - if `n' < 2 {
        = if 0 < 2 {
            - exit
        }
    }

> ----- end opts_exclus
> ive -----
        - if "`method'" == "dunnett" {
        = if "noadjust" == "dunnett" {

```

```

        opts_exclusive "`method' `groups'"
    }
    - _get_diopts diopts options, `options' `fvwrap' `fvlabel'
    = _get_diopts diopts options,
    _____
> _____ begin _get_dio
> pts _____
        - version 11
        - syntax namelist(max=2) [, *]
        - gettoken name1 namelist : namelist
        - gettoken name2 namelist : namelist
        - GetDiopts diopts options, `options'
        = GetDiopts diopts options,
        _____
> _____ begin _get_diopts.GetDio
> pts _____
        - local DIOPTS Level(cilevel) vsquish NOALLBASElevels ALLBAS
> Elevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EMPTY
> cells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFlegend SELEGEND cformat(str
> ing) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru) F
> VWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(passthru) N
> OABBREV ABBREV
        - syntax namelist(max=2) [, `DIOPTS' *]
        = syntax namelist(max=2) [, Level(cilevel) vsquish NOALLBASE
> levels ALLBASElevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMP
> TYcells EMPTYcells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFlegend SELEGEND
> cformat(string) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRA
> P(passthru) FVWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYP
> E(passthru) NOABBREV ABBREV *]
        - opts_exclusive "`allbaselevels' `noallbaselevels'"
        = opts_exclusive " "
        _____
> _____ begin opts_exclus
> ive _____
        - version 8.2
        - args opts optname errcode optslab
        - local opts `opts'
        = local opts
        - local n 0
        - while ``opts' != "" {
        = while `"' != "" {
            local ++n
            gettoken item`n' opts : opts, bind
        }
        - if `n' < 2 {
        = if 0 < 2 {

```

```

- exit
> _____ end opts_exclus
> ive _____
- opts_exclusive "`allbaselevels' `nobaselevels'"
= opts_exclusive " "
> _____ begin opts_exclus
> ive _____
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
> _____ end opts_exclus
> ive _____
- opts_exclusive "`baselevels' `nobaselevels'"
= opts_exclusive " "
> _____ begin opts_exclus
> ive _____
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
> _____ end opts_exclus
> ive _____

```

```

- opts_exclusive "`emptycells' `noemptycells'"
= opts_exclusive " "
_____
> _____ begin opts_exclus
> ive _____
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
_____
> _____ end opts_exclus
> ive _____
- opts_exclusive "`fvlabel' `nofvlabel'"
= opts_exclusive " "
_____
> _____ begin opts_exclus
> ive _____
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
_____
> _____ end opts_exclus
> ive _____
- opts_exclusive "`omitted' `noomitted'"
= opts_exclusive " "
_____
> _____ begin opts_exclus

```

```

> ive
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
      local ++n
      gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

>
> end opts_exclus
> ive
    - opts_exclusive "`lstretch' `nolstretch'"
    = opts_exclusive " "

>
> begin opts_exclus
> ive
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
      local ++n
      gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

>
> end opts_exclus
> ive
    - opts_exclusive "`cnsreport' `fullcnsreport'"
    = opts_exclusive " "

>
> begin opts_exclus
> ive
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'

```

```

= local opts
- local n 0
- while ``opts'' != "" {
= while `'' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`coeflegend' `selegend'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
- local n 0
- while ``opts'' != "" {
= while `'' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`noci' `nopvalues'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
- local n 0
- while ``opts'' != "" {
= while `'' != "" {

```

```

        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}

> ----- end opts_exclus
> ive -----
    - local K : list sizeof namelist
    - gettoken c_diopts c_opts : namelist
    - opts_exclusive "`coding' `compare'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ``opts' != "" {
= while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`versus' `compare'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ``opts' != "" {
= while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }

```



```

        }
        - if `n' < 2 {
        = if 0 < 2 {
        - exit
    }
}
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`abbrev' `noabbrev'"
    = opts_exclusive " "
}
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
}
}
> ----- end opts_exclus
> ive -----
    - local allbaselevels `allbaselevels' `noallbaselevels'
    = local allbaselevels
    - local baselevels `baselevels' `nobaselevels'
    = local baselevels
    - local emptycells `emptycells' `noemptycells'
    = local emptycells
    - local omitted `omitted' `noomitted'
    = local omitted
    - local lstretch `lstretch' `nolstretch'
    = local lstretch
    - local fvlabel `fvlabel' `nofvlabel'
    = local fvlabel
    - local abbrev `abbrev' `noabbrev'
    = local abbrev
    - if "`allbaselevels'`baselevels'" == "" {
    = if "" == "" {
    - if c(showbaselevels) == "all" {
        local allbaselevels allbaselevels
    }
}

```

```

    }
- else if c(showbaselevels) == "on" {
    local baselevels baselevels
  }
- }
- if "`emptycells'" == "" {
= if "" == "" {
- if c(showemptycells) == "off" {
    local emptycells noemptycells
  }
- }
- if "`omitted'" == "" {
= if "" == "" {
- if c(showomitted) == "off" {
    local omitted noomitted
  }
- }
- if "`lstretch'" == "" {
= if "" == "" {
- if c(lstretch) == "off" {
    local lstretch nolstretch
  }
- }
- if `:length local cformat' {
= if 0 {
    confirm numeric format `cformat'
    if fmtwidth("`cformat'") > 9 {
      local cformat "%9.0g"
      di "{txt}note: invalid cformat(), using default"
    }
    sreturn local cformat "`cformat'"
    local cformat `cformat(`cformat')"'
  }
- if `:length local sformat' {
= if 0 {
    confirm numeric format `sformat'
    if fmtwidth("`sformat'") > 8 {
      local sformat "%8.2f"
      di "{txt}note: invalid sformat(), using default"
    }
    sreturn local sformat "`sformat'"
    local sformat `sformat(`sformat')"'
  }
- if `:length local pformat' {
= if 0 {
    confirm numeric format `pformat'

```

```

        if fmtwidth("`pformat'") > 5 {
        local pformat "%5.3f"
        di "{txt}note: invalid pformat(), using default"
        }
        sreturn local pformat "`pformat'"
        local pformat `pformat(pformat)'"
        }
- if `K' == 1 & `:length local options' {
= if 2 == 1 & 0 {
    syntax namelist(max=2) [, `DIOPTS']
    }
- if reldif(`level', c(level)) > 1e-3 {
= if reldif(95, c(level)) > 1e-3 {
    local levelopt level(`level')
    }
- Wraapon , `fvwraapon'
= Wraapon ,

> ----- begin _get_diopts.Wra
> pon -----
- capture syntax [, W0rd WIdth]
- if c(rc) {
    di as err "invalid fvwrapon() option;"
    syntax [, W0rd WIdth]
    exit 198
    }
- opts_exclusive "`word' `width'" fvwrapon
= opts_exclusive " " fvwrapon

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while "`opts'" != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit

> ----- end opts_exclus

```

```
> ive
- local fwrapon `word' `width'
= local fwrapon
- if `:length local fwrapon' {
= if 0 {
    c_local fwrapon fwrapon(`fwrapon')
}

> _____ end _get_diopts.Wra

> pon
- if "`fwrap'" != "" {
= if "" != "" {
    FWrap, `fwrap'
}
- c_local `c_diopts' `levelopt' `vsquish' `allbaselevels' `b
> aselevels' `cnsreport' `fullcnsreport' `emptycells' `omitted' `lstretch' `co
> eflegend' `selegend' `cformat' `sformat' `pformat' `coding' `versus' `compar
> e' `fwrap' `fwrapon' `fvlabel' `nocl' `nopvalues' `markdown' `citype' `abb
> rev'

= c_local diopts
- if `K' == 2 {
= if 2 == 2 {
- c_local `c_opts' ``options'''
= c_local options `'''
- }
- sreturn local coding `coding'
= sreturn local coding
- sreturn local versus `versus'
= sreturn local versus
- sreturn local compare `compare'
= sreturn local compare
- sreturn local level `level'
= sreturn local level 95

> _____ end _get_diopts.GetDio

> pts
- c_local `name1' ``diopts'''
= c_local diopts `'''
- local snames : s(macros)
- foreach sname of local snames {
- local S_`sname' = s(`sname')
= local S_level = s(level)
- }
- local S_`sname' = s(`sname')
= local S_method = s(method)
- }
```

```

- sreturn clear
- GetDiopts DEFAULT

```

```

> _____ begin _get_diopts.GetDio
> pts _____
      - local DIOPTS Level(cilevel) vsquish NOALLBASElevels ALLBAS
> Elevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EMPTY
> cells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cformat(stri
> ng) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru) F
> VWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(passthru) N
> OABBREV ABBREV
      - syntax namelist(max=2) [, `DIOPTS' *]
      = syntax namelist(max=2) [, Level(cilevel) vsquish NOALLBASE
> levels ALLBASElevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMP
> TYcells EMPTYcells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND
> cformat(string) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRA
> P(passthru) FVWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYP
> E(passthru) NOABBREV ABBREV *]
      - opts_exclusive "`allbaselevels' `noallbaselevels'"
      = opts_exclusive " "

```

```

> _____ begin opts_exclus
> ive _____
      - version 8.2
      - args opts optname errcode optslab
      - local opts `opts'
      = local opts
      - local n 0
      - while ``opts' != "" {
      = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
      }
      - if `n' < 2 {
      = if 0 < 2 {
      - exit

```

```

> _____ end opts_exclus
> ive _____
      - opts_exclusive "`allbaselevels' `nobaselevels'"
      = opts_exclusive " "

```

```

> _____ begin opts_exclus
> ive _____
      - version 8.2
      - args opts optname errcode optslab

```

```

- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`baselevels' `nobaselevels'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`emptycells' `noemptycells'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {

```

```

= while `"" != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`fvlabel' `nofvlabel'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while `""opts"" != "" {
= while `"" != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`omitted' `noomitted'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while `""opts"" != "" {
= while `"" != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}

```

```

- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`lstretch' `nolstretch'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while "`opts'" != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`cnsreport' `fullcnsreport'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while "`opts'" != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

```



```

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`coeflegend' `selegend'"
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ```opts'"" != "" {
    = while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`noci' `nopvalues'"
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ```opts'"" != "" {
    = while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - local K : list sizeof namelist
    - gettoken c_diopts c_opts : namelist

```

```

- opts_exclusive "`coding' `compare'"
= opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ```opts'`` != "" {
= while `""' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit

```

```

> ----- end opts_exclus
> ive -----
- opts_exclusive "`versus' `compare'"
= opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ```opts'`` != "" {
= while `""' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit

```

```

> ----- end opts_exclus
> ive -----
- opts_exclusive "`abbrev' `noabbrev'"
= opts_exclusive " "

```

```

> ----- begin opts_exclus

```

```

> ive
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit

> end opts_exclus
> ive
- local allbaselevels `allbaselevels' `noallbaselevels'
= local allbaselevels
- local baselevels `baselevels' `nobaselevels'
= local baselevels
- local emptycells `emptycells' `noemptycells'
= local emptycells
- local omitted `omitted' `noomitted'
= local omitted
- local lstretch `lstretch' `nolstretch'
= local lstretch
- local fvlabel `fvlabel' `nofvlabel'
= local fvlabel
- local abbrev `abbrev' `noabbrev'
= local abbrev
- if "`allbaselevels'`baselevels'" == "" {
= if "" == "" {
- if c(showbaselevels) == "all" {
    local allbaselevels allbaselevels
}
- else if c(showbaselevels) == "on" {
    local baselevels baselevels
}
- }
- if "`emptycells'" == "" {
= if "" == "" {
- if c(showemptycells) == "off" {
    local emptycells noemptycells
}
- }

```

```

- if "`omitted'" == "" {
= if "" == "" {
- if c(showomitted) == "off" {
    local omitted noomitted
  }
- }
- if "`lstretch'" == "" {
= if "" == "" {
- if c(lstretch) == "off" {
    local lstretch nolstretch
  }
- }
- if `:length local cformat' {
= if 0 {
    confirm numeric format `cformat'
    if fmtwidth("`cformat'") > 9 {
      local cformat "%9.0g"
      di "{txt}note: invalid cformat(), using default"
    }
    sreturn local cformat "`cformat'"
    local cformat `cformat(`cformat')"'
  }
- if `:length local sformat' {
= if 0 {
    confirm numeric format `sformat'
    if fmtwidth("`sformat'") > 8 {
      local sformat "%8.2f"
      di "{txt}note: invalid sformat(), using default"
    }
    sreturn local sformat "`sformat'"
    local sformat `sformat(`sformat')"'
  }
- if `:length local pformat' {
= if 0 {
    confirm numeric format `pformat'
    if fmtwidth("`pformat'") > 5 {
      local pformat "%5.3f"
      di "{txt}note: invalid pformat(), using default"
    }
    sreturn local pformat "`pformat'"
    local pformat `pformat(`pformat')"'
  }
- if `K' == 1 & `:length local options' {
= if 1 == 1 & 0 {
    syntax namelist(max=2) [, `DIOPTS' ]
  }

```

```

- if reldif(`level', c(level)) > 1e-3 {
= if reldif(95, c(level)) > 1e-3 {
    local levelopt level(`level')
    }
- Wraapon , `fvwraapon'
= Wraapon ,

> _____ begin _get_diopts.Wra
> pon _____
    - capture syntax [, W0rd WIdth]
    - if c(rc) {
        di as err "invalid fvwraapon() option;"
        syntax [, W0rd WIdth]
        exit 198
    }
    - opts_exclusive "`word' `width'" fvwraapon
= opts_exclusive " " fvwraapon

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ``opts' != "" {
= while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
        - exit

> _____ end opts_exclus
> ive _____
    - local fvwraapon `word' `width'
= local fvwraapon
    - if `:length local fvwraapon' {
= if 0 {
        c_local fvwraapon fvwraapon(`fvwraapon')
    }

> _____ end _get_diopts.Wra
> pon _____
    - if "`fvwrap'" != "" {

```

```

        = if "" != "" {
            FVWrap, `fvwrap'
        }
        - c_local `c_diopts' `levelopt' `vsquish' `allbaselevels' `b
> aselevels' `cnsreport' `fullcnsreport' `emptycells' `omitted' `lstretch' `co
> eflegend' `selegend' `cformat' `sformat' `pformat' `coding' `versus' `compar
> e' `fvwrap' `fvwrapon' `fvlabel' `nocl' `nopvalues' `markdown' `citype' `abb
> rev'

        = c_local DEFAULT
        - if `K' == 2 {
        = if 1 == 2 {
            c_local `c_opts' ``options''
        }
        - sreturn local coding `coding'
        = sreturn local coding
        - sreturn local versus `versus'
        = sreturn local versus
        - sreturn local compare `compare'
        = sreturn local compare
        - sreturn local level `level'
        = sreturn local level 95
    }
}

> ----- end _get_diopts.GetDio
> pts -----

        - if ``name2'' == "" {
        = if ``options'' == "" {
            GetDiopts DUPS, `options'
        }
        - else {
        - GetDiopts DUPS options, `options'
        = GetDiopts DUPS options,
    }
}

> ----- begin _get_diopts.GetDio
> pts -----

        - local DIOPTS Level(cilevel) vsquish NOALLBASElevels ALLBAS
> Elevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EMPTY
> cells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cformat(stri
> ng) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru) F
> VWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(passthru) N
> OABBREV ABBREV

        - syntax namelist(max=2) [, `DIOPTS' *]
        = syntax namelist(max=2) [, Level(cilevel) vsquish NOALLBASE
> levels ALLBASElevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMP
> TYcells EMPTYcells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND
> cformat(string) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRA
> P(passthru) FVWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYP

```

```

> E(passthru) NOABBREV ABBREV *)
    - opts_exclusive "`allbaselevels' `noallbaselevels'"
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `'' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`allbaselevels' `nobaselevels'"
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `'' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`baselevels' `nobaselevels'"
    = opts_exclusive " "
    _____

```

```

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`emptycells' `noemptycells'"
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`fvlabel' `nofvlabel'"
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab

```



```

- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
  }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`omitted' `noomitted'"
= opts_exclusive " "
}

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
  }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`lstretch' `nolstretch'"
= opts_exclusive " "
}

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {

```

```

= while `""` != "" {
    local ++n
    gettoken item`n` opts : opts, bind
}
- if `n` < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`cnsreport` `fullcnsreport`"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts`
= local opts
    - local n 0
    - while `""opts`"" != "" {
= while `""` != "" {
    local ++n
    gettoken item`n` opts : opts, bind
}
    - if `n` < 2 {
= if 0 < 2 {
    - exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`coeflegend` `selegend`"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts`
= local opts
    - local n 0
    - while `""opts`"" != "" {
= while `""` != "" {
    local ++n
    gettoken item`n` opts : opts, bind
}

```

```

- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`noci' `nopvalues'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while "`opts'" != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- local K : list sizeof namelist
- gettoken c_diopts c_opts : namelist
- opts_exclusive "`coding' `compare'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while "`opts'" != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {

```

```

        - exit
    _____
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`versus' `compare'"
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`abbrev' `noabbrev'"
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____
> _____ end opts_exclus
> ive _____

```

```

- local allbaselevels `allbaselevels' `noallbaselevels'
= local allbaselevels
- local baselevels `baselevels' `nobaselevels'
= local baselevels
- local emptycells `emptycells' `noemptycells'
= local emptycells
- local omitted `omitted' `noomitted'
= local omitted
- local lstretch `lstretch' `nolstretch'
= local lstretch
- local fvlabel `fvlabel' `nofvlabel'
= local fvlabel
- local abbrev `abbrev' `noabbrev'
= local abbrev
- if "`allbaselevels'`baselevels'" == "" {
= if "" == "" {
- if c(showbaselevels) == "all" {
    local allbaselevels allbaselevels
  }
- else if c(showbaselevels) == "on" {
    local baselevels baselevels
  }
- }
- if "`emptycells'" == "" {
= if "" == "" {
- if c(showemptycells) == "off" {
    local emptycells noemptycells
  }
- }
- if "`omitted'" == "" {
= if "" == "" {
- if c(showomitted) == "off" {
    local omitted noomitted
  }
- }
- if "`lstretch'" == "" {
= if "" == "" {
- if c(lstretch) == "off" {
    local lstretch nolstretch
  }
- }
- if `:length local cformat' {
= if 0 {
    confirm numeric format `cformat'
    if fmtwidth("`cformat'") > 9 {
      local cformat "%9.0g"
    }
  }
}

```

```

di "{txt}note: invalid cformat(), using default"
}
sreturn local cformat ``cformat''
local cformat `cformat(`cformat')''
}
- if `:length local sformat' {
= if 0 {
confirm numeric format `sformat'
if fmtwidth(`sformat') > 8 {
local sformat "%8.2f"
di "{txt}note: invalid sformat(), using default"
}
sreturn local sformat ``sformat''
local sformat `sformat(`sformat')''
}
- if `:length local pformat' {
= if 0 {
confirm numeric format `pformat'
if fmtwidth(`pformat') > 5 {
local pformat "%5.3f"
di "{txt}note: invalid pformat(), using default"
}
sreturn local pformat ``pformat''
local pformat `pformat(`pformat')''
}
- if `K' == 1 & `:length local options' {
= if 2 == 1 & 0 {
syntax namelist(max=2) [, `DIOPTS']
}
- if reldif(`level', c(level)) > 1e-3 {
= if reldif(95, c(level)) > 1e-3 {
local levelopt level(`level')
}
- Wraupon , `fvwraupon'
= Wraupon ,

```

```

> _____ begin _get_diopts.Wra
> pon _____

```

```

- capture syntax [, W0rd WIdth]
- if c(rc) {
di as err "invalid fvwrapon() option;"
syntax [, W0rd WIdth]
exit 198
}
- opts_exclusive ``word' `width' fvwrapon
= opts_exclusive " " fvwrapon

```

```

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - local fwwrapon `word' `width'
    = local fwwrapon
    - if `:length local fwwrapon' {
    = if 0 {
        c_local fwwrapon fwwrapon(`fwwrapon')
    }
    _____

> _____ end _get_diopts.Wra
> pon _____
    - if "`fwwrap'" != "" {
    = if "" != "" {
        FWWrap, `fwwrap'
    }
    - c_local `c_diopts' `levelopt' `vsquish' `allbaselevels' `b
> aselevels' `cnsreport' `fullcnsreport' `emptycells' `omitted' `lstretch' `co
> eflegend' `selegend' `cformat' `sformat' `pformat' `coding' `versus' `compar
> e' `fwwrap' `fwwrapon' `fvlabel' `nocl' `nopvalues' `markdown' `citype' `abb
> rev'

    = c_local DUPS
    - if `K' == 2 {
    = if 2 == 2 {
    - c_local `c_opts' ``options'
    = c_local options `"'
    - }
    - sreturn local coding `coding'
    = sreturn local coding
    - sreturn local versus `versus'

```

```

= sreturn local versus
- sreturn local compare `compare'
= sreturn local compare
- sreturn local level `level'
= sreturn local level 95

```

```

> _____ end _get_diopts.GetDio
> pts _____
- c_local `name2' ``options''
= c_local options `''
- }
- local DUPS : list DUPS - DEFAULT
- gettoken DUPS : DUPS
- if ``DUPS'' != "" {
= if `'' != "" {
  if (strpos(`DUPS', "(")) {
    gettoken DUPS : DUPS, parse("(")
    local DUPS `DUPS'()'
  }
  di as err "duplicate {bf:`DUPS'} option not allowed"
  exit 198
}
- sreturn clear
- foreach sname of local snames {
- sreturn local `sname' = ``S_`sname''
= sreturn local level = `95'
- }
- sreturn local `sname' = ``S_`sname''
= sreturn local method = `noadjust'
- }

```

```

> _____ end _get_dio
> pts _____
- local legend coeflegend selegend
- local legend : list legend & diopts
- local diopts : list diopts - legend
- local lstretch lstretch nolstretch
- local lstretch : list lstretch & diopts
- local diopts : list diopts - lstretch
- local markdown markdown
- local markdown : list markdown & diopts
- local diopts : list diopts - markdown
- _get_diopts ignore, `diopts' `cformat' `sformat' `pformat'
= _get_diopts ignore,

```

```

> _____ begin _get_dio

```



```

> pts
    - version 11
    - syntax namelist(max=2) [, *]
    - gettoken name1 namelist : namelist
    - gettoken name2 namelist : namelist
    - GetDiopts diopts options, `options'
    = GetDiopts diopts options,
    _____
> _____ begin _get_diopts.GetDio
> pts
    - local DIOPTS Level(cilevel) vsquish NOALLBASElevels ALLBAS
> Elevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EMPTY
> cells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFlegend SELEGEND cformat(stri
> ng) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru) F
> VWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(passthru) N
> OABBREV ABBREV
    - syntax namelist(max=2) [, `DIOPTS' *]
    = syntax namelist(max=2) [, Level(cilevel) vsquish NOALLBASE
> levels ALLBASElevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMP
> TYcells EMPTYcells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFlegend SELEGEND
> cformat(string) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRA
> P(passthru) FVWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYP
> E(passthru) NOABBREV ABBREV *]
    - opts_exclusive "`allbaselevels' `noallbaselevels'"
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____
> _____ end opts_exclus
> ive
    - opts_exclusive "`allbaselevels' `nobaselevels'"
    = opts_exclusive " "

```

```

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `'' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - opts_exclusive ``baselevels' `nobaselevels'
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `'' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - opts_exclusive ``emptycells' `noemptycells'
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2

```

```

- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`fvlabel' `nofvlabel'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`omitted' `noomitted'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0

```

```

- while ``opts'' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`lstretch' `nolstretch'"
    = opts_exclusive " "
}

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts'' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    }

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`cnsreport' `fullcnsreport'"
    = opts_exclusive " "
}

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts'' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }

```

```

        }
        - if `n' < 2 {
        = if 0 < 2 {
        - exit
    }
}
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`coeflegend' `selegend'"
    = opts_exclusive " "
}
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
}
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`noci' `nopvalues'"
    = opts_exclusive " "
}
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
}
}

```

```

> _____ end opts_exclus
> ive _____
    - local K : list sizeof namelist
    - gettoken c_diopts c_opts : namelist
    - opts_exclusive "`coding' `compare'"
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`versus' `compare'"
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus

```

```

> ive -----
      - opts_exclusive "`abbrev' `noabbrev'"
      = opts_exclusive " "
-----

> ----- begin opts_exclus
> ive -----
      - version 8.2
      - args opts optname errcode optslab
      - local opts `opts'
      = local opts
      - local n 0
      - while ``opts' != "" {
      = while `"' != "" {
          local ++n
          gettoken item`n' opts : opts, bind
        }
      - if `n' < 2 {
      = if 0 < 2 {
      - exit
-----

> ----- end opts_exclus
> ive -----
      - local allbaselevels `allbaselevels' `noallbaselevels'
      = local allbaselevels
      - local baselevels `baselevels' `nobaselevels'
      = local baselevels
      - local emptycells `emptycells' `noemptycells'
      = local emptycells
      - local omitted `omitted' `noomitted'
      = local omitted
      - local lstretch `lstretch' `nolstretch'
      = local lstretch
      - local fvlabel `fvlabel' `nofvlabel'
      = local fvlabel
      - local abbrev `abbrev' `noabbrev'
      = local abbrev
      - if "`allbaselevels'`baselevels'" == "" {
      = if "" == "" {
      - if c(showbaselevels) == "all" {
          local allbaselevels allbaselevels
        }
      - else if c(showbaselevels) == "on" {
          local baselevels baselevels
        }
      - }
      - if "`emptycells'" == "" {

```

```

= if "" == "" {
- if c(showemptycells) == "off" {
    local emptycells noemptycells
  }
- }
- if "`omitted'" == "" {
= if "" == "" {
- if c(showomitted) == "off" {
    local omitted noomitted
  }
- }
- if "`lstretch'" == "" {
= if "" == "" {
- if c(lstretch) == "off" {
    local lstretch nolstretch
  }
- }
- if `:length local cformat' {
= if 0 {
    confirm numeric format `cformat'
    if fmtwidth("`cformat'") > 9 {
      local cformat "%9.0g"
      di "{txt}note: invalid cformat(), using default"
    }
    sreturn local cformat "`cformat'"
    local cformat `cformat(`cformat')'
  }
- if `:length local sformat' {
= if 0 {
    confirm numeric format `sformat'
    if fmtwidth("`sformat'") > 8 {
      local sformat "%8.2f"
      di "{txt}note: invalid sformat(), using default"
    }
    sreturn local sformat "`sformat'"
    local sformat `sformat(`sformat')'
  }
- if `:length local pformat' {
= if 0 {
    confirm numeric format `pformat'
    if fmtwidth("`pformat'") > 5 {
      local pformat "%5.3f"
      di "{txt}note: invalid pformat(), using default"
    }
    sreturn local pformat "`pformat'"
    local pformat `pformat(`pformat')'
  }

```



```

    }
    - if `K' == 1 & `:length local options' {
= if 2 == 1 & 0 {
    syntax namelist(max=2) [, `DIOPTS']
    }
    - if reldif(`level', c(level)) > 1e-3 {
= if reldif(95, c(level)) > 1e-3 {
    local levelopt level(`level')
    }
    - Wraapon , `fvwraapon'
= Wraapon ,

> _____ begin _get_diopts.Wra
> pon _____
    - capture syntax [, W0rd WIdth]
    - if c(rc) {
        di as err "invalid fvwraapon() option;"
        syntax [, W0rd WIdth]
        exit 198
    }
    - opts_exclusive "`word' `width'" fvwraapon
= opts_exclusive " " fvwraapon

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ``opts' != "" {
= while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit

> _____ end opts_exclus
> ive _____
    - local fvwraapon `word' `width'
= local fvwraapon
    - if `:length local fvwraapon' {
= if 0 {
        c_local fvwraapon fvwraapon(`fvwraapon')

```

```

        }
    }
end _get_diopts.Wra
pon
    - if "`fvwrap'" != "" {
    = if "" != "" {
        FVWrap, `fvwrap'
    }
    - c_local `c_diopts' `levelopt' `vsquish' `allbaselevels' `b
> aselevels' `cnsreport' `fullcnsreport' `emptycells' `omitted' `lstretch' `co
> eflegend' `selegend' `cformat' `sformat' `pformat' `coding' `versus' `compar
> e' `fvwrap' `fvwrapon' `fvlabel' `nocl' `nopvalues' `markdown' `citype' `abb
> rev'
    = c_local diopts
    - if `K' == 2 {
    = if 2 == 2 {
    - c_local `c_opts' ``options'''
    = c_local options `'''
    - }
    - sreturn local coding `coding'
    = sreturn local coding
    - sreturn local versus `versus'
    = sreturn local versus
    - sreturn local compare `compare'
    = sreturn local compare
    - sreturn local level `level'
    = sreturn local level 95
end _get_diopts.GetDio
pts
    - c_local `name1' ``diopts'''
    = c_local ignore `'''
    - local snames : s(macros)
    - foreach sname of local snames {
    - local S_`sname' = s(`sname')
    = local S_level = s(level)
    - }
    - local S_`sname' = s(`sname')
    = local S_method = s(method)
    - }
    - sreturn clear
    - GetDiopts DEFAULT
end _get_diopts.GetDio
pts
    - local DIOPTS Level(cilevel) vsquish NOALLBASElevels ALLBAS

```

```

> Elevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EMPTY
> cells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cformat(stri
> ng) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru) F
> VWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(passthru) N
> OABBREV ABBREV
      - syntax namelist(max=2) [, `DIOPTS' *]
      = syntax namelist(max=2) [, Level(cilevel) vsquish NOALLBASE
> levels ALLBASElevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMP
> TYcells EMPTYcells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND
> cformat(string) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRA
> P(passthru) FVWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYP
> E(passthru) NOABBREV ABBREV *]
      - opts_exclusive "`allbaselevels' `noallbaselevels'"
      = opts_exclusive " "

> _____ begin opts_exclus
> ive _____
      - version 8.2
      - args opts optname errcode optslab
      - local opts `opts'
      = local opts
      - local n 0
      - while ``opts' != "" {
      = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
      }
      - if `n' < 2 {
      = if 0 < 2 {
      - exit

> _____ end opts_exclus
> ive _____
      - opts_exclusive "`allbaselevels' `nobaselevels'"
      = opts_exclusive " "

> _____ begin opts_exclus
> ive _____
      - version 8.2
      - args opts optname errcode optslab
      - local opts `opts'
      = local opts
      - local n 0
      - while ``opts' != "" {
      = while `"' != "" {
        local ++n

```

```

        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`baselevels' `nobaselevels'"
= opts_exclusive " "
}
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ``opts' != "" {
= while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`emptycells' `noemptycells'"
= opts_exclusive " "
}
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ``opts' != "" {
= while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {

```

```

- exit
> _____ end opts_exclus
> ive _____
- opts_exclusive "`fvlabel' `nofvlabel'"
= opts_exclusive " "
> _____ begin opts_exclus
> ive _____
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
> _____ end opts_exclus
> ive _____
- opts_exclusive "`omitted' `noomitted'"
= opts_exclusive " "
> _____ begin opts_exclus
> ive _____
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
> _____ end opts_exclus
> ive _____

```

```

- opts_exclusive "`lstretch' `nolstretch'"
= opts_exclusive " "


---


> 

---

 begin opts_exclus
> ive 

---


- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while "`opts'" != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit


---


> 

---

 end opts_exclus
> ive 

---


- opts_exclusive "`cnsreport' `fullcnsreport'"
= opts_exclusive " "


---


> 

---

 begin opts_exclus
> ive 

---


- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while "`opts'" != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit


---


> 

---

 end opts_exclus
> ive 

---


- opts_exclusive "`coeflegend' `selegend'"
= opts_exclusive " "


---


> 

---

 begin opts_exclus

```

```

> ive
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit

> ----- end opts_exclus
> ive
- opts_exclusive "`nocl' `nopvalues'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit

> ----- end opts_exclus
> ive
- local K : list sizeof namelist
- gettoken c_diopts c_opts : namelist
- opts_exclusive "`coding' `compare'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive
- version 8.2

```

```

- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`versus' `compare'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`abbrev' `noabbrev'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0

```



```

- while ``opts'' != "" {
= while `'' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> _____ end opts_exclus
> ive _____
- local allbaselevels `allbaselevels' `noallbaselevels'
= local allbaselevels
- local baselevels `baselevels' `nobaselevels'
= local baselevels
- local emptycells `emptycells' `noemptycells'
= local emptycells
- local omitted `omitted' `noomitted'
= local omitted
- local lstretch `lstretch' `nolstretch'
= local lstretch
- local fvlabel `fvlabel' `nofvlabel'
= local fvlabel
- local abbrev `abbrev' `noabbrev'
= local abbrev
- if "`allbaselevels'`baselevels'" == "" {
= if "" == "" {
- if c(showbaselevels) == "all" {
    local allbaselevels allbaselevels
}
- else if c(showbaselevels) == "on" {
    local baselevels baselevels
}
- }
- if "`emptycells'" == "" {
= if "" == "" {
- if c(showemptycells) == "off" {
    local emptycells noemptycells
}
- }
- if "`omitted'" == "" {
= if "" == "" {
- if c(showomitted) == "off" {
    local omitted noomitted
}
- }

```

```

- if "`lstretch'" == "" {
= if "" == "" {
- if c(lstretch) == "off" {
    local lstretch nolstretch
  }
- }
- if `:length local cformat' {
= if 0 {
    confirm numeric format `cformat'
    if fmtwidth("`cformat'") > 9 {
      local cformat "%9.0g"
      di "{txt}note: invalid cformat(), using default"
    }
    sreturn local cformat "`cformat'"
    local cformat `cformat(`cformat')"'
  }
- if `:length local sformat' {
= if 0 {
    confirm numeric format `sformat'
    if fmtwidth("`sformat'") > 8 {
      local sformat "%8.2f"
      di "{txt}note: invalid sformat(), using default"
    }
    sreturn local sformat "`sformat'"
    local sformat `sformat(`sformat')"'
  }
- if `:length local pformat' {
= if 0 {
    confirm numeric format `pformat'
    if fmtwidth("`pformat'") > 5 {
      local pformat "%5.3f"
      di "{txt}note: invalid pformat(), using default"
    }
    sreturn local pformat "`pformat'"
    local pformat `pformat(`pformat')"'
  }
- if `K' == 1 & `:length local options' {
= if 1 == 1 & 0 {
    syntax namelist(max=2) [, `DIOPTS']
  }
- if reldif(`level', c(level)) > 1e-3 {
= if reldif(95, c(level)) > 1e-3 {
    local levelopt level(`level')
  }
- Wraon , `fvwraon'
= Wraon ,

```

```

> _____ begin _get_diopts.Wra
> pon _____
    - capture syntax [, W0rd WIdth]
    - if c(rc) {
      di as err "invalid fwwrapon() option;"
      syntax [, W0rd WIdth]
      exit 198
    }
    - opts_exclusive "`word' `width'" fwwrapon
= opts_exclusive " " fwwrapon
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ``opts' != "" {
= while `"' != "" {
      local ++n
      gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - local fwwrapon `word' `width'
= local fwwrapon
    - if `:length local fwwrapon' {
= if 0 {
      c_local fwwrapon fwwrapon(`fwwrapon')
    }
    _____

> _____ end _get_diopts.Wra
> pon _____
    - if "`fwwrap'" != "" {
= if "" != "" {
      FWWrap, `fwwrap'
    }
    - c_local `c_diopts' `levelopt' `vsquish' `allbaselevels' `b
> aselevels' `cnsreport' `fullcnsreport' `emptycells' `omitted' `lstretch' `co
> eflegend' `selegend' `cformat' `sformat' `pformat' `coding' `versus' `compar

```

```

> e' `fvwrap' `fvwrapon' `fvlabel' `nocl' `nopvalues' `markdown' `citype' `abb
> rev'
    = c_local DEFAULT
    - if `K' == 2 {
    = if 1 == 2 {
        c_local `c_opts' ``options''
    }
    - sreturn local coding `coding'
    = sreturn local coding
    - sreturn local versus `versus'
    = sreturn local versus
    - sreturn local compare `compare'
    = sreturn local compare
    - sreturn local level `level'
    = sreturn local level 95
    _____
> _____ end _get_diopts.GetDio
> pts _____
    - if ``name2'' == "" {
    = if ``' == "" {
    - GetDiopts DUPS, `options'
    = GetDiopts DUPS,
    _____

> _____ begin _get_diopts.GetDio
> pts _____
    - local DIOPTS Level(cilevel) vsquish NOALLBASElevels ALLBAS
> Elevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EMPTY
> cells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFlegend SELEGEND cformat(stri
> ng) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru) F
> VWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(passthru) N
> OABBREV ABBREV
    - syntax namelist(max=2) [, `DIOPTS' *]
    = syntax namelist(max=2) [, Level(cilevel) vsquish NOALLBASE
> levels ALLBASElevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMP
> TYcells EMPTYcells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFlegend SELEGEND
> cformat(string) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRA
> P(passthru) FVWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYP
> E(passthru) NOABBREV ABBREV *]
    - opts_exclusive ``allbaselevels' `noallbaselevels''
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'

```

```

= local opts
- local n 0
- while ``opts'' != "" {
= while `'' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`allbaselevels' `nobaselevels'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
- local n 0
- while ``opts'' != "" {
= while `'' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
    }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`baselevels' `nobaselevels'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
- local n 0
- while ``opts'' != "" {
= while `'' != "" {

```

```

        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}
}
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`emptycells' `noemptycells'"
= opts_exclusive " "
}
}
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ```opts'`" != "" {
= while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}
}
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`fvlabel' `nofvlabel'"
= opts_exclusive " "
}
}
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ```opts'`" != "" {
= while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {

```

```

        = if 0 < 2 {
        - exit
    }
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`omitted' `noomitted'"
    = opts_exclusive " "
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    }
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`lstretch' `nolstretch'"
    = opts_exclusive " "
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    }
> ----- end opts_exclus

```

```

> ive -----
      - opts_exclusive "`cnsreport' `fullcnsreport'"
      = opts_exclusive " "
-----

> ----- begin opts_exclus
> ive -----
      - version 8.2
      - args opts optname errcode optslab
      - local opts `opts'
      = local opts
      - local n 0
      - while ``opts' != "" {
      = while `"' != "" {
          local ++n
          gettoken item`n' opts : opts, bind
        }
      - if `n' < 2 {
      = if 0 < 2 {
      - exit
-----

> ----- end opts_exclus
> ive -----
      - opts_exclusive "`coeflegend' `selegend'"
      = opts_exclusive " "
-----

> ----- begin opts_exclus
> ive -----
      - version 8.2
      - args opts optname errcode optslab
      - local opts `opts'
      = local opts
      - local n 0
      - while ``opts' != "" {
      = while `"' != "" {
          local ++n
          gettoken item`n' opts : opts, bind
        }
      - if `n' < 2 {
      = if 0 < 2 {
      - exit
-----

> ----- end opts_exclus
> ive -----
      - opts_exclusive "`noci' `nopvalues'"
      = opts_exclusive " "
-----

```



```

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    -----

> ----- end opts_exclus
> ive -----
    - local K : list sizeof namelist
    - gettoken c_diopts c_opts : namelist
    - opts_exclusive "`coding' `compare'"
    = opts_exclusive " "
    -----

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    -----

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`versus' `compare'"
    = opts_exclusive " "
    -----

> ----- begin opts_exclus
> ive -----

```

```

- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----

- opts_exclusive "`abbrev' `noabbrev'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----

- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----

- local allbaselevels `allbaselevels' `noallbaselevels'
= local allbaselevels
- local baselevels `baselevels' `nobaselevels'
= local baselevels
- local emptycells `emptycells' `noemptycells'
= local emptycells
- local omitted `omitted' `noomitted'
= local omitted
- local lstretch `lstretch' `nolstretch'

```

```

= local lstretch
- local fvlabel `fvlabel' `nofvlabel'
= local fvlabel
- local abbrev `abbrev' `noabbrev'
= local abbrev
- if "`allbaselevels'`baselevels'" == "" {
= if "" == "" {
- if c(showbaselevels) == "all" {
    local allbaselevels allbaselevels
  }
- else if c(showbaselevels) == "on" {
    local baselevels baselevels
  }
- }
- if "`emptycells'" == "" {
= if "" == "" {
- if c(showemptycells) == "off" {
    local emptycells noemptycells
  }
- }
- if "`omitted'" == "" {
= if "" == "" {
- if c(showomitted) == "off" {
    local omitted noomitted
  }
- }
- if "`lstretch'" == "" {
= if "" == "" {
- if c(lstretch) == "off" {
    local lstretch nolstretch
  }
- }
- if `:length local cformat' {
= if 0 {
    confirm numeric format `cformat'
    if fmtwidth("`cformat'") > 9 {
      local cformat "%9.0g"
      di "{txt}note: invalid cformat(), using default"
    }
    sreturn local cformat "`cformat'"
    local cformat `cformat(`cformat')'
  }
- if `:length local sformat' {
= if 0 {
    confirm numeric format `sformat'
    if fmtwidth("`sformat'") > 8 {

```

```

    local sformat "%8.2f"
    di "{txt}note: invalid sformat(), using default"
    }
    sreturn local sformat ``sformat''
    local sformat `sformat(`sformat')`
    }
- if `:length local pformat' {
= if 0 {
    confirm numeric format `pformat'
    if fmtwidth(`pformat') > 5 {
        local pformat "%5.3f"
        di "{txt}note: invalid pformat(), using default"
        }
    sreturn local pformat ``pformat''
    local pformat `pformat(`pformat')`
    }
- if `K' == 1 & `:length local options' {
= if 1 == 1 & 0 {
    syntax namelist(max=2) [, `DIOPTS']
    }
- if reldif(`level', c(level)) > 1e-3 {
= if reldif(95, c(level)) > 1e-3 {
    local levelopt level(`level')
    }
- Wraupon , `fvwraupon'
= Wraupon ,

```

> _____ begin _get_diopts.Wra

> pon _____

```

- capture syntax [, W0rd WIdth]
- if c(rc) {
    di as err "invalid fvwraupon() option;"
    syntax [, W0rd WIdth]
    exit 198
    }
- opts_exclusive ``word' `width' fvwraupon
= opts_exclusive " " fvwraupon

```

> _____ begin opts_exclus

> ive _____

```

- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts'' != "" {

```

```

        = while `""` != "" {
            local ++n
            gettoken item`n' opts : opts, bind
        }
        - if `n' < 2 {
        = if 0 < 2 {
        - exit
    }
}

> _____ end opts_exclus
> ive _____
    - local fvwrapon `word' `width'
    = local fvwrapon
    - if `:length local fvwrapon' {
    = if 0 {
        c_local fvwrapon fvwrapon(`fvwrapon')
    }
}

> _____ end _get_diopts.Wra
> pon _____
    - if "`fvwrap'" != "" {
    = if "" != "" {
        FVWrap, `fvwrap'
    }
    - c_local `c_diopts' `levelopt' `vsquish' `allbaselevels' `b
> aselevels' `cnsreport' `fullcnsreport' `emptycells' `omitted' `lstretch' `co
> eflegend' `selegend' `cformat' `sformat' `pformat' `coding' `versus' `compar
> e' `fvwrap' `fvwrapon' `fvlabel' `nocl' `nopvalues' `markdown' `citype' `abb
> rev'

    = c_local DUPS
    - if `K' == 2 {
    = if 1 == 2 {
        c_local `c_opts' ``options'
    }
    - sreturn local coding `coding'
    = sreturn local coding
    - sreturn local versus `versus'
    = sreturn local versus
    - sreturn local compare `compare'
    = sreturn local compare
    - sreturn local level `level'
    = sreturn local level 95
}

> _____ end _get_diopts.GetDio
> pts _____
    - }
    - else {

```

```

        GetDiopts DUPS options, `options'
        c_local `name2' ``options'
    }
    - local DUPS : list DUPS - DEFAULT
    - gettoken DUPS : DUPS
    - if ``DUPS' != "" {
= if `'' != "" {
        if (strpos(`DUPS', "(")) {
            gettoken DUPS : DUPS, parse("(")
            local DUPS `DUPS'()'
        }
        di as err "duplicate {bf:`DUPS'} option not allowed"
        exit 198
    }
    - sreturn clear
    - foreach sname of local snames {
    - sreturn local `sname' = ``S_`sname'
= sreturn local level = `95'
    - }
    - sreturn local `sname' = ``S_`sname'
= sreturn local method = `noadjust'
    - }
}

> _____ end _get_dio
> pts _____
    - local cformat ``s(cformat)'
= local cformat `''
    - local sformat ``s(sformat)'
= local sformat `''
    - local pformat ``s(pformat)'
= local pformat `''
    - _get_eformopts , eformopts(`options') allowed(__all__) soption
> s
= _get_eformopts , eformopts() allowed(__all__) soptions
}

> _____ begin _get_eformo
> pts _____
    - version 8.0
    - syntax [, eformopts(string asis) soptions ALLOWed(string) ]
    - local 0 , `eformopts'
= local 0 ,
    - local EFALL NOHR hr NOSHR shr or IRr RRr tr TRatio
    - if ``soptions' != "" {
= if "soptions" != "" {
    - syntax [, EForm1(passthru) EForm `EFALL' * ]
= syntax [, EForm1(passthru) EForm NOHR hr NOSHR shr or IRr RR

```

```

> r tr TRatio * ]
    - local opts ``options'''
    = local opts `'''
    - local 0 , `eform1' `eform' `nohr' `hr' `noshr' `shr' `or' `i
> rr' `rrr' `tr' `tratio'
    = local 0 ,
    - }
    - if ``allowed'' == "__all__" {
    = if "__all__" == "__all__" {
    - local allowed `EFALL'
    = local allowed NOHR hr NOSHR shr or IRr RRr tr TRatio
    - }
    - foreach ef of local allowed {
    - capture confirm name `ef'
    = capture confirm name NOHR
    - if _rc {
      di as err ``ef' is not a valid name"
      exit 198
    }
    - local efopts `efopts' `=lower("`ef'")'
    = local efopts nohr
    - }
    - capture confirm name `ef'
    = capture confirm name hr
    - if _rc {
      di as err ``ef' is not a valid name"
      exit 198
    }
    - local efopts `efopts' `=lower("`ef'")'
    = local efopts nohr hr
    - }
    - capture confirm name `ef'
    = capture confirm name NOSHR
    - if _rc {
      di as err ``ef' is not a valid name"
      exit 198
    }
    - local efopts `efopts' `=lower("`ef'")'
    = local efopts nohr hr noshr
    - }
    - capture confirm name `ef'
    = capture confirm name shr
    - if _rc {
      di as err ``ef' is not a valid name"
      exit 198
    }
    }

```

```

- local efopts `efopts' `=lower("`ef'")'
= local efopts nohr hr noshr shr
- }
- capture confirm name `ef'
= capture confirm name or
- if _rc {
  di as err "`ef' is not a valid name"
  exit 198
}
- local efopts `efopts' `=lower("`ef'")'
= local efopts nohr hr noshr shr or
- }
- capture confirm name `ef'
= capture confirm name IRr
- if _rc {
  di as err "`ef' is not a valid name"
  exit 198
}
- local efopts `efopts' `=lower("`ef'")'
= local efopts nohr hr noshr shr or irr
- }
- capture confirm name `ef'
= capture confirm name RRr
- if _rc {
  di as err "`ef' is not a valid name"
  exit 198
}
- local efopts `efopts' `=lower("`ef'")'
= local efopts nohr hr noshr shr or irr rrr
- }
- capture confirm name `ef'
= capture confirm name tr
- if _rc {
  di as err "`ef' is not a valid name"
  exit 198
}
- local efopts `efopts' `=lower("`ef'")'
= local efopts nohr hr noshr shr or irr rrr tr
- }
- capture confirm name `ef'
= capture confirm name TRatio
- if _rc {
  di as err "`ef' is not a valid name"
  exit 198
}
- local efopts `efopts' `=lower("`ef'")'

```



```

    local eform_cons_ti = "Time"
    local eform_cons_note = "time ratios"
  }
- else if ``eform1'""=="IRR" {
= else if `""'=="IRR" {
    local eform_cons_ti = "Inc. rate"
    local eform_cons_note = "incidence-rate ratios"
    local eform_cons_ti2 = "incidence rate"
  }
- else if ``eform1'""=="Risk ratio" {
= else if `""'=="Risk ratio" {
    local eform_cons_ti = "Risk"
    local eform_cons_note = "risk ratios"
  }
- else if ``eform1'""=="Hlth ratio" {
= else if `""'=="Hlth ratio" {
    local eform_cons_ti = "Health"
    local eform_cons_note = "health ratios"
  }
- local k : list sizeof eform
- if `k' {
= if 0 {
    opts_exclusive ``eform'
    if `:length local eform1' {
      opts_exclusive "eform() `eform'"
    }
  }
- if `k' {
= if 0 {
    if (``eform'=="eform") local eform1 = "exp(b)"
    else if (``eform'=="hr") {
      local eform1 = "Haz. ratio"
      local eform_cons_ti = "Hazard"
      local eform_cons_note = "hazard ratios"
    }
    else if (``eform'=="shr") {
      local eform1 = "SHR"
      local eform_cons_ti = "Subhazard"
      local eform_cons_note = "subhazard ratios"
    }
    else if (``eform'=="tr") {
      local eform1 = "Time ratio"
      local eform_cons_ti = "Time"
      local eform_cons_note = "time ratios"
    }
    else if (``eform'=="tratio") {

```

```

        local eform1 = "Time ratio"
        local eform_cons_ti = "Time"
        local eform_cons_note = "time ratios"
    }
    else if ("`eform'"=="or") {
        local eform1 = "Odds ratio"
        if ("`e(cmd)'"=="asclogit" | "`e(cmd)'"=="cmclogit" | "`e(cm
> d)'"=="cmmixlogit" | "`e(cmd)'"=="cmxtmixlogit" ) {
            local eform_cons_ti = "Rel. risk"
            local eform_cons_note = "relative-risk ratios"
            local eform_cons_ti2 = "relative risk"
        }
        else {
            local eform_cons_ti = "Odds"
            local eform_cons_note = "odds ratios"
        }
    }
    else if ("`eform'"=="irr") {
        local eform1 = "IRR"
        local eform_cons_ti = "Inc. rate"
        local eform_cons_note = "incidence-rate ratios"
        local eform_cons_ti2 = "incidence rate"
    }
    else if ("`eform'"=="rrr") {
        local eform1 = "RRR"
        local eform_cons_ti = "Rel. risk"
        local eform_cons_note = "relative-risk ratios"
        local eform_cons_ti2 = "relative risk"
    }
    else if ("`eform'"!="nohr") & ("`eform'"!="noshr") {
        local eform1 = upper("`eform'")
    }
}

- sreturn clear
- sreturn local options ```opts'``
= sreturn local options `'''
- sreturn local opt `eform'
= sreturn local opt
- sreturn local str `eform1'
= sreturn local str
- if ```eform1'`` != "" {
= if `''' != "" {
    sreturn local eform eform("`eform1'")
}
- else sreturn local eform ""
- sreturn local eform_cons_ti `eform_cons_ti'

```

```

= sreturn local eform_cons_ti
- sreturn local eform_cons_note `eform_cons_note'
= sreturn local eform_cons_note
- sreturn local eform_cons_ti2 `eform_cons_ti2'
= sreturn local eform_cons_ti2

```

```

> _____ end _get_eformo
> pts _____
- local tr_item = ``s(eform_cons_note)''
= local tr_item = ``''
- if inlist("`bmatrix'", "", "e(b)") & "`e(k_eform)'" == "0" {
= if inlist("", "", "e(b)") & "" == "0" {
  local eform
  }
- else local eform ``s(str)''
= else local eform ``''
- local eform_cons_ti ``s(eform_cons_ti)''
= local eform_cons_ti ``''
- local eform_cons_ti2 ``s(eform_cons_ti2)''
= local eform_cons_ti2 ``''
- if (`e(consonly)'"!="1" | ``eform_cons_ti'"=="") {
= if ("0"!="1" | ``'"=="") {
- local eformdi ``s(str)''
= local eformdi ``''
- }
- else {
  local eformdi ``eform_cons_ti''
  local tr_item = cond(missing("`eform_cons_ti2'"), strlower(``
> eform_cons_ti''), ``eform_cons_ti2'')
  }
- local coefttl = cond(``eform'"=="", ``coeftitle'', ``ef
> ormdi'')
= local coefttl = cond(`""=="", `'', `')
- local options ``s(options)''
= local options ``''
- _get_diparmopts, diparmopts(`options') level(`level')
= _get_diparmopts, diparmopts() level(95)

```

```

> _____ begin _get_diparmo
> pts _____
- if _caller() < 8.2 {
  _get_diparmopts_8 `0'
  exit
  }
- version 9
- local version : di "version " string(_caller()) ":"

```

```

        - syntax [, diparmopts(string asis) EXECute soptions bottom pl
> us SYNTAXonly * ]
        - local goptions `options'
        = local goptions level(95)
        - SpliceGlobals junk , `goptions'
        = SpliceGlobals junk , level(95)


---


> _____ begin _get_diparmopts.SpliceGlob
> als _____
        - syntax name(id="macro name" name=c_diparm) [, diparm(strin
> g asis) Level(cilevel) dof(passthru) syntaxonly ]
        - if ``dof''' == "" & ``e(df_r)''' != "" {
        = if `''' == "" & `''' != "" {
            capture confirm integer number `e(df_r)'
            if !c(rc) {
                local gdof dof(`e(df_r)')
            }
            capture
        }
        - else local gdof ``dof'''
        = else local gdof `'''
        - local glevel `level'
        = local glevel 95
        - local lopt level(`glevel')
        = local lopt level(95)
        - if (``diparm''' == "") exit
        = if (``''' == "") exit


---


> _____ end _get_diparmopts.SpliceGlob
> als _____
        - local 0 `", `diparmopts'''
        = local 0 `", ""
        - local diparmopts
        - local k 0
        - syntax [, diparm(string asis) * ]
        - while ``diparm''' != "" {
        = while `''' != "" {
            local ++k
            local single 1
            local after
            capture _on_colon_parse `diparm'
            if !c(rc) {
                local single 0
                local diparm ``s(before)'''
                local after ``s(after)'''
            }

```

```

capture
SpliceGlobals diparm , diparm(`diparm') `syntaxonly' `goptio

> ns'

local diparm`k' ```diparm'''
local diparmopts ```diparmopts' : `diparm'''
if `single' | ```:list retok after''' == "" {
local 0 `", `options'''
syntax [, diparm(string asis) * ]
}
else {
local diparm ```after'''
}
}
- if ```soptions''' == "" {
= if `''' == "" {
- syntax [, diparm(string asis) ]
- }
- if ("`execute'" == "") {
= if ("" == "") {
- sreturn clear
- sreturn local options ```options'''
= sreturn local options `'''
- sreturn local diparm ```diparmopts'''
= sreturn local diparm `'''
- forval i = 1/`k' {
= forval i = 1/0 {
sreturn local diparm`i' ```diparm`i''''
}
- sreturn local k `k'
= sreturn local k 0
- exit

> _____ end _get_diparmo
> pts _____
- local NODIPARM : length local nodiparm
- if `NODIPARM' {
= if 0 {
local options
}
- local GTOPTS parse(":") bind quotes
- local k 0
- if !`NODIPARM' {
= if !0 {
- if ```e(diparm)''' != "" {
= if `''' != "" {
local i 0

```

```

    local diparm ``e(diparm)''
  }
- else if ``e(diparm1)'' != "" {
= else if ``'' != "" {
    local i 1
    local diparm ``e(diparm1)''
  }
- while `:length local diparm' {
= while 0 {
    gettoken diparm rest : diparm, `GTOPTS'
    while `:length local rest' {
      local ++k
      local diparm`k' : copy local diparm
      gettoken COLON rest : rest, `GTOPTS'
      gettoken diparm rest : rest, `GTOPTS'
    }
    local ++k
    local diparm`k' : copy local diparm
    local ++i
    local diparm ``e(diparm`i)''
  }
- }
- if `:length local options' {
= if 0 {
    local 0 `", `options''
    syntax [, diparm(string asis) *]
    if `k' & `:length local diparm' {
      local ++k
      local diparm`k' __sep__
    }
    while `:length local diparm' {
      gettoken diparm rest : diparm, `GTOPTS'
      while `:length local rest' {
        local ++k
        local diparm`k' : copy local diparm
        gettoken COLON rest : rest, `GTOPTS'
        gettoken diparm rest : rest, `GTOPTS'
      }
      local ++k
      local diparm`k' : copy local diparm
      local 0 `", `options''
      syntax [, diparm(string asis) *]
    }
  }
- if ``markdown'' != "" {
= if "" != "" {

```

```

        local lsize = c(linesize)
        set linesize 255
    }
    - `vv' mata: _coef_table()
    = version 12, missing: mata: _coef_table()


---


> _____ begin _get_dio
> pts _____
        - version 11
        - syntax namelist(max=2) [, *]
        - gettoken name1 namelist : namelist
        - gettoken name2 namelist : namelist
        - GetDiopts diopts options, `options'
        = GetDiopts diopts options,


---


> _____ begin _get_diopts.GetDio
> pts _____
        - local DIOPTS Level(cilevel) vsquish NOALLBASElevels ALLBAS
> Elevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EMPTY
> cells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFlegend SELEGEND cformat(stri
> ng) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru) F
> VWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(passthru) N
> OABBREV ABBREV
        - syntax namelist(max=2) [, `DIOPTS' *]
        = syntax namelist(max=2) [, Level(cilevel) vsquish NOALLBASE
> levels ALLBASElevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMP
> TYcells EMPTYcells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFlegend SELEGEND
> cformat(string) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRA
> P(passthru) FVWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYP
> E(passthru) NOABBREV ABBREV *]
        - opts_exclusive "`allbaselevels' `noallbaselevels'"
        = opts_exclusive " "


---


> _____ begin opts_exclus
> ive _____
        - version 8.2
        - args opts optname errcode optslab
        - local opts `opts'
        = local opts
        - local n 0
        - while ``opts' != "" {
        = while `"' != "" {
            local ++n
            gettoken item`n' opts : opts, bind
        }
        - if `n' < 2 {

```



```

        = if 0 < 2 {
        - exit
    }
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`allbaselevels' `nobaselevels'"
    = opts_exclusive " "
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    }
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`baselevels' `nobaselevels'"
    = opts_exclusive " "
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    }
> ----- end opts_exclus

```

```

> ive -----
      - opts_exclusive "`emptycells' `noemptycells'"
      = opts_exclusive " "
      -----

> ----- begin opts_exclus
> ive -----
      - version 8.2
      - args opts optname errcode optslab
      - local opts `opts'
      = local opts
      - local n 0
      - while ``opts' != "" {
      = while `"' != "" {
          local ++n
          gettoken item`n' opts : opts, bind
        }
      - if `n' < 2 {
      = if 0 < 2 {
      - exit
      -----

> ----- end opts_exclus
> ive -----
      - opts_exclusive "`fvlabel' `nofvlabel'"
      = opts_exclusive " "
      -----

> ----- begin opts_exclus
> ive -----
      - version 8.2
      - args opts optname errcode optslab
      - local opts `opts'
      = local opts
      - local n 0
      - while ``opts' != "" {
      = while `"' != "" {
          local ++n
          gettoken item`n' opts : opts, bind
        }
      - if `n' < 2 {
      = if 0 < 2 {
      - exit
      -----

> ----- end opts_exclus
> ive -----
      - opts_exclusive "`omitted' `noomitted'"
      = opts_exclusive " "
      -----

```

```

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`lstretch' `nolstretch'"
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`cnsreport' `fullcnsreport'"
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab

```

```

- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`coeflegend' `selegend'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`noci' `nopvalues'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {

```

```

= while `""` != "" {
    local ++n
    gettoken item`n` opts : opts, bind
}
- if `n` < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
    - local K : list sizeof namelist
    - gettoken c_diopts c_opts : namelist
    - opts_exclusive "`coding` `compare`"
= opts_exclusive " "
}

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts`
= local opts
    - local n 0
    - while `""`opts`"" != "" {
= while `""` != "" {
    local ++n
    gettoken item`n` opts : opts, bind
}
    - if `n` < 2 {
= if 0 < 2 {
    - exit
}

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`versus` `compare`"
= opts_exclusive " "
}

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts`
= local opts
    - local n 0
    - while `""`opts`"" != "" {
= while `""` != "" {
    local ++n

```

```

        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`abbrev' `noabbrev'"
= opts_exclusive " "
}
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ``opts' != "" {
= while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}
> _____ end opts_exclus
> ive _____
    - local allbaselevels `allbaselevels' `noallbaselevels'
= local allbaselevels
    - local baselevels `baselevels' `nobaselevels'
= local baselevels
    - local emptycells `emptycells' `noemptycells'
= local emptycells
    - local omitted `omitted' `noomitted'
= local omitted
    - local lstretch `lstretch' `nolstretch'
= local lstretch
    - local fvlabel `fvlabel' `nofvlabel'
= local fvlabel
    - local abbrev `abbrev' `noabbrev'
= local abbrev
    - if "`allbaselevels'`baselevels'" == "" {
= if "" == "" {
    - if c(showbaselevels) == "all" {

```

```

    local allbaselevels allbaselevels
  }
- else if c(showbaselevels) == "on" {
  local baselevels baselevels
  }
- }
- if "`emptycells'" == "" {
= if "" == "" {
- if c(showemptycells) == "off" {
  local emptycells noemptycells
  }
- }
- if "`omitted'" == "" {
= if "" == "" {
- if c(showomitted) == "off" {
  local omitted noomitted
  }
- }
- if "`lstretch'" == "" {
= if "" == "" {
- if c(lstretch) == "off" {
  local lstretch nolstretch
  }
- }
- if `:length local cformat' {
= if 0 {
  confirm numeric format `cformat'
  if fmtwidth("`cformat'") > 9 {
    local cformat "%9.0g"
    di "{txt}note: invalid cformat(), using default"
  }
  sreturn local cformat "`cformat'"
  local cformat `"cformat(`cformat')"'
}
- if `:length local sformat' {
= if 0 {
  confirm numeric format `sformat'
  if fmtwidth("`sformat'") > 8 {
    local sformat "%8.2f"
    di "{txt}note: invalid sformat(), using default"
  }
  sreturn local sformat "`sformat'"
  local sformat `"sformat(`sformat')"'
}
- if `:length local pformat' {
= if 0 {

```

```

confirm numeric format `pformat'
if fmtwidth("`pformat'") > 5 {
local pformat "%5.3f"
di "{txt}note: invalid pformat(), using default"
}
sreturn local pformat "`pformat'"
local pformat `pformat(`pformat')'
}
- if `K' == 1 & `:length local options' {
= if 2 == 1 & 0 {
syntax namelist(max=2) [, `DIOPTS']
}
- if reldif(`level', c(level)) > 1e-3 {
= if reldif(95, c(level)) > 1e-3 {
local levelopt level(`level')
}
- Wraon , `fvwraon'
= Wraon ,

> ----- begin _get_diopts.Wra
> pon -----
- capture syntax [, W0rd WIdth]
- if c(rc) {
di as err "invalid fvwrapon() option;"
syntax [, W0rd WIdth]
exit 198
}
- opts_exclusive "`word' `width'" fvwrapon
= opts_exclusive " " fvwrapon

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while "`opts'" != "" {
= while `"' != "" {
local ++n
gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit

```



```

> _____ end opts_exclus
> ive _____
      - local fvwrapon `word' `width'
      = local fvwrapon
      - if `:length local fvwrapon' {
      = if 0 {
        c_local fvwrapon fvwrapon(`fvwrapon')
      }
      _____

> _____ end _get_diopts.Wra
> pon _____
      - if "`fvwrap'" != "" {
      = if "" != "" {
        FVWrap, `fvwrap'
      }
      - c_local `c_diopts' `levelopt' `vsquish' `allbaselevels' `b
> aselevels' `cnsreport' `fullcnsreport' `emptycells' `omitted' `lstretch' `co
> eflegend' `selegend' `cformat' `sformat' `pformat' `coding' `versus' `compar
> e' `fvwrap' `fvwrapon' `fvlabel' `nocl' `nopvalues' `markdown' `citype' `abb
> rev'

      = c_local diopts
      - if `K' == 2 {
      = if 2 == 2 {
        - c_local `c_opts' ``options'
        = c_local options `''
        - }
        - sreturn local coding `coding'
        = sreturn local coding
        - sreturn local versus `versus'
        = sreturn local versus
        - sreturn local compare `compare'
        = sreturn local compare
        - sreturn local level `level'
        = sreturn local level 95
      _____

> _____ end _get_diopts.GetDio
> pts _____
      - c_local `name1' ``diopts'
      = c_local __000005 `''
      - local snames : s(macros)
      - foreach sname of local snames {
      - local S_`sname' = s(`sname')
      = local S_level = s(level)
      - }
      - local S_`sname' = s(`sname')
      = local S_k = s(k)

```

```

- }
- sreturn clear
- GetDiopts DEFAULT

```

```

> _____ begin _get_diopts.GetDio
> pts _____
    - local DIOPTS Level(cilevel) vsquish NOALLBASElevels ALLBAS
> Elevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EMPTY
> cells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cformat(stri
> ng) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru) F
> VWRAPON(string) NOFVLABel FVLABel NOCI NOPValues MARKDOWN CITYPE(passthru) N
> OABBREV ABBREV
    - syntax namelist(max=2) [, `DIOPTS' *]
    = syntax namelist(max=2) [, Level(cilevel) vsquish NOALLBASE
> levels ALLBASElevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMP
> TYcells EMPTYcells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND
> cformat(string) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRA
> P(passthru) FVWRAPON(string) NOFVLABel FVLABel NOCI NOPValues MARKDOWN CITYP
> E(passthru) NOABBREV ABBREV *]
    - opts_exclusive "`allbaselevels' `noallbaselevels'"
    = opts_exclusive " "

```

```

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

```

```

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`allbaselevels' `nobaselevels'"
    = opts_exclusive " "

```

```

> _____ begin opts_exclus
> ive _____
    - version 8.2

```

```

- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
  }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`baselevels' `nobaselevels'"
= opts_exclusive " "
}

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
  }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`emptycells' `noemptycells'"
= opts_exclusive " "
}

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0

```

```

- while ``opts'' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`fvlabel' `nofvlabel'"
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts'' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    }

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`omitted' `noomitted'"
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts'' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }

```

```

        }
        - if `n' < 2 {
        = if 0 < 2 {
        - exit
    }
}
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`lstretch' `nolstretch'"
    = opts_exclusive " "
}
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
}
> ----- end opts_exclus
> ive -----
    - opts_exclusive "`cnsreport' `fullcnsreport'"
    = opts_exclusive " "
}
> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
}

```

```

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`coeflegend' `selegend'"
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``"opts"' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`noci' `nopvalues'"
    = opts_exclusive " "
    _____
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``"opts"' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____
> _____ end opts_exclus
> ive _____
    - local K : list sizeof namelist

```

```

- gettoken c_diopts c_opts : namelist
- opts_exclusive "`coding' `compare'"
= opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit

```

```

> ----- end opts_exclus
> ive -----
- opts_exclusive "`versus' `compare'"
= opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit

```

```

> ----- end opts_exclus
> ive -----
- opts_exclusive "`abbrev' `noabbrev'"
= opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    -----

> ----- end opts_exclus
> ive -----
    - local allbaselevels `allbaselevels' `noallbaselevels'
    = local allbaselevels
    - local baselevels `baselevels' `nobaselevels'
    = local baselevels
    - local emptycells `emptycells' `noemptycells'
    = local emptycells
    - local omitted `omitted' `noomitted'
    = local omitted
    - local lstretch `lstretch' `nolstretch'
    = local lstretch
    - local fvlabel `fvlabel' `nofvlabel'
    = local fvlabel
    - local abbrev `abbrev' `noabbrev'
    = local abbrev
    - if "`allbaselevels'`baselevels'" == "" {
    = if "" == "" {
    - if c(showbaselevels) == "all" {
        local allbaselevels allbaselevels
    }
    - else if c(showbaselevels) == "on" {
        local baselevels baselevels
    }
    - }
    - if "`emptycells'" == "" {
    = if "" == "" {
    - if c(showemptycells) == "off" {
        local emptycells noemptycells
    }

```



```

- }
- if "`omitted'" == "" {
= if "" == "" {
- if c(showomitted) == "off" {
    local omitted noomitted
  }
- }
- if "`lstretch'" == "" {
= if "" == "" {
- if c(lstretch) == "off" {
    local lstretch nolstretch
  }
- }
- if `:length local cformat' {
= if 0 {
    confirm numeric format `cformat'
    if fmtwidth("`cformat'") > 9 {
      local cformat "%9.0g"
      di "{txt}note: invalid cformat(), using default"
    }
    sreturn local cformat "`cformat'"
    local cformat `cformat(`cformat')'
  }
- if `:length local sformat' {
= if 0 {
    confirm numeric format `sformat'
    if fmtwidth("`sformat'") > 8 {
      local sformat "%8.2f"
      di "{txt}note: invalid sformat(), using default"
    }
    sreturn local sformat "`sformat'"
    local sformat `sformat(`sformat')'
  }
- if `:length local pformat' {
= if 0 {
    confirm numeric format `pformat'
    if fmtwidth("`pformat'") > 5 {
      local pformat "%5.3f"
      di "{txt}note: invalid pformat(), using default"
    }
    sreturn local pformat "`pformat'"
    local pformat `pformat(`pformat')'
  }
- if `K' == 1 & `:length local options' {
= if 1 == 1 & 0 {
    syntax namelist(max=2) [, `DIOPTS']

```

```

    }
    - if reldif(`level', c(level)) > 1e-3 {
= if reldif(95, c(level)) > 1e-3 {
    local levelopt level(`level')
    }
    - Wrapon , `fvwrapon'
= Wrapon ,

```

```

> ----- begin _get_diopts.Wra
> pon -----
    - capture syntax [, W0rd WIdth]
    - if c(rc) {
        di as err "invalid fvwrapon() option;"
        syntax [, W0rd WIdth]
        exit 198
    }
    - opts_exclusive "`word' `width'" fvwrapon
= opts_exclusive " " fvwrapon

```

```

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ``opts' != "" {
= while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit

```

```

> ----- end opts_exclus
> ive -----
    - local fvwrapon `word' `width'
= local fvwrapon
    - if `:length local fvwrapon' {
= if 0 {
        c_local fvwrapon fvwrapon(`fvwrapon')
    }

```

```

> ----- end _get_diopts.Wra
> pon -----

```

```

- if "`fvwrap'" != "" {
= if "" != "" {
    FVWrap, `fvwrap'
}
- c_local `c_diopts' `levelopt' `vsquish' `allbaselevels' `b
> aselevels' `cnsreport' `fullcnsreport' `emptycells' `omitted' `lstretch' `co
> eflegend' `selegend' `cformat' `sformat' `pformat' `coding' `versus' `compar
> e' `fvwrap' `fvwrapon' `fvlabel' `nocl' `nopvalues' `markdown' `citype' `abb
> rev'

= c_local DEFAULT
- if `K' == 2 {
= if 1 == 2 {
    c_local `c_opts' ``options''
}
- sreturn local coding `coding'
= sreturn local coding
- sreturn local versus `versus'
= sreturn local versus
- sreturn local compare `compare'
= sreturn local compare
- sreturn local level `level'
= sreturn local level 95

_____
> _____ end _get_diopts.GetDio
> pts _____

- if ``name2'' == "" {
= if ``' == "" {
- GetDiopts DUPS, `options'
= GetDiopts DUPS,

_____
> _____ begin _get_diopts.GetDio
> pts _____

- local DIOPTS Level(cilevel) vsquish NOALLBASElevels ALLBAS
> Elevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMPTYcells EMPTY
> cells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND cformat(stri
> ng) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRAP(passthru) F
> VWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYPE(passthru) N
> OABBREV ABBREV

- syntax namelist(max=2) [, `DIOPTS' *]
= syntax namelist(max=2) [, Level(cilevel) vsquish NOALLBASE
> levels ALLBASElevels NOBASElevels BASElevels noCNSReport FULLCNSReport NOEMP
> TYcells EMPTYcells NOOMITted OMITted NOLSTRETCH LSTRETCH COEFLegend SELEGEND
> cformat(string) sformat(string) pformat(string) CODING VERSUS COMPARE FVWRA
> P(passthru) FVWRAPON(string) NOFVLABEL FVLABEL NOCI NOPValues MARKDOWN CITYP
> E(passthru) NOABBREV ABBREV *]

- opts_exclusive ``allbaselevels' `noallbaselevels''

```

```

= opts_exclusive " "
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`allbaselevels' `nbaselevels'"
    = opts_exclusive " "
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`baselevels' `nbaselevels'"
    = opts_exclusive " "
> _____ begin opts_exclus
> ive _____

```

```

- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit

```

```

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`emptycells' `noemptycells'"
    = opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while ``opts' != "" {
    = while `"' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit

```

```

> ----- end opts_exclus
> ive -----
    - opts_exclusive "`fvlabel' `nofvlabel'"
    = opts_exclusive " "

```

```

> ----- begin opts_exclus
> ive -----
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts

```

```

- local n 0
- while ``opts'' != "" {
= while `'' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`omitted' `noomitted'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts'' != "" {
= while `'' != "" {
  local ++n
  gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus
> ive -----
- opts_exclusive "`lstretch' `nolstretch'"
= opts_exclusive " "

> ----- begin opts_exclus
> ive -----
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts'' != "" {
= while `'' != "" {
  local ++n

```

```

        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`cnsreport' `fullcnsreport'"
= opts_exclusive " "
}
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ```opts'` != "" {
= while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {
    - exit
}
> _____ end opts_exclus
> ive _____
    - opts_exclusive "`coeflegend' `selegend'"
= opts_exclusive " "
}
> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
= local opts
    - local n 0
    - while ```opts'` != "" {
= while `""' != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
= if 0 < 2 {

```

```

- exit


---


> 

---

 end opts_exclus
> ive 

---


- opts_exclusive "`noci' `nopvalues'"
= opts_exclusive " "


---


> 

---

 begin opts_exclus
> ive 

---


- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
local ++n
gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit


---


> 

---

 end opts_exclus
> ive 

---


- local K : list sizeof namelist
- gettoken c_diopts c_opts : namelist
- opts_exclusive "`coding' `compare'"
= opts_exclusive " "


---


> 

---

 begin opts_exclus
> ive 

---


- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts' != "" {
= while `"' != "" {
local ++n
gettoken item`n' opts : opts, bind
}
- if `n' < 2 {
= if 0 < 2 {
- exit


---



```



```

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`versus' `compare'"
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while `""opts'" != "" {
    = while `"" != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - opts_exclusive "`abbrev' `noabbrev'"
    = opts_exclusive " "
    _____

> _____ begin opts_exclus
> ive _____
    - version 8.2
    - args opts optname errcode optslab
    - local opts `opts'
    = local opts
    - local n 0
    - while `""opts'" != "" {
    = while `"" != "" {
        local ++n
        gettoken item`n' opts : opts, bind
    }
    - if `n' < 2 {
    = if 0 < 2 {
    - exit
    _____

> _____ end opts_exclus
> ive _____
    - local allbaselevels `allbaselevels' `noallbaselevels'
    = local allbaselevels

```

```

- local baselevels `baselevels' `nobaselevels'
= local baselevels
- local emptycells `emptycells' `noemptycells'
= local emptycells
- local omitted `omitted' `noomitted'
= local omitted
- local lstretch `lstretch' `nolstretch'
= local lstretch
- local fvlabel `fvlabel' `nofvlabel'
= local fvlabel
- local abbrev `abbrev' `noabbrev'
= local abbrev
- if "`allbaselevels'`baselevels'" == "" {
= if "" == "" {
- if c(showbaselevels) == "all" {
    local allbaselevels allbaselevels
  }
- else if c(showbaselevels) == "on" {
    local baselevels baselevels
  }
- }
- if "`emptycells'" == "" {
= if "" == "" {
- if c(showemptycells) == "off" {
    local emptycells noemptycells
  }
- }
- if "`omitted'" == "" {
= if "" == "" {
- if c(showomitted) == "off" {
    local omitted noomitted
  }
- }
- if "`lstretch'" == "" {
= if "" == "" {
- if c(lstretch) == "off" {
    local lstretch nolstretch
  }
- }
- if `:length local cformat' {
= if 0 {
    confirm numeric format `cformat'
    if fmtwidth("`cformat'") > 9 {
      local cformat "%9.0g"
    }
    di "{txt}note: invalid cformat(), using default"
  }
}

```

```

        sreturn local cformat ``cformat'''
        local cformat `cformat(`cformat')''
    }
- if `:length local sformat' {
= if 0 {
    confirm numeric format `sformat'
    if fmtwidth(`sformat') > 8 {
        local sformat "%8.2f"
        di "{txt}note: invalid sformat(), using default"
    }
    sreturn local sformat ``sformat'''
    local sformat `sformat(`sformat')''
}
- if `:length local pformat' {
= if 0 {
    confirm numeric format `pformat'
    if fmtwidth(`pformat') > 5 {
        local pformat "%5.3f"
        di "{txt}note: invalid pformat(), using default"
    }
    sreturn local pformat ``pformat'''
    local pformat `pformat(`pformat')''
}
- if `K' == 1 & `:length local options' {
= if 1 == 1 & 0 {
    syntax namelist(max=2) [, `DIOPTS']
}
- if reldif(`level', c(level)) > 1e-3 {
= if reldif(95, c(level)) > 1e-3 {
    local levelopt level(`level')
}
- Wraon , `fvwraon'
= Wraon ,

```

> _____ begin _get_diopts.Wra

> pon _____

```

- capture syntax [, W0rd WIdth]
- if c(rc) {
    di as err "invalid fvwraon() option;"
    syntax [, W0rd WIdth]
    exit 198
}
- opts_exclusive ``word' `width'" fvwraon
= opts_exclusive " " fvwraon

```

> _____ begin opts_exclus

```

> ive
- version 8.2
- args opts optname errcode optslab
- local opts `opts'
= local opts
- local n 0
- while ``opts'' != "" {
= while `'' != "" {
    local ++n
    gettoken item`n' opts : opts, bind
  }
- if `n' < 2 {
= if 0 < 2 {
- exit
}

> ----- end opts_exclus

> ive
- local fwraupon `word' `width'
= local fwraupon
- if `:length local fwraupon' {
= if 0 {
    c_local fwraupon fwraupon(`fwraupon')
  }
}

> ----- end _get_diopts.Wra

> pon
- if "`fwwrap'" != "" {
= if "" != "" {
    FWWrap, `fwwrap'
  }
- c_local `c_diopts' `levelopt' `vsquish' `allbaselevels' `b
> aselevels' `cnsreport' `fullcnsreport' `emptycells' `omitted' `lstretch' `co
> eflegend' `selegend' `cformat' `sformat' `pformat' `coding' `versus' `compar
> e' `fwwrap' `fwraupon' `fvlabel' `nocl' `nopvalues' `markdown' `citype' `abb
> rev'

= c_local DUPS
- if `K' == 2 {
= if 1 == 2 {
    c_local `c_opts' ``options''
  }
- sreturn local coding `coding'
= sreturn local coding
- sreturn local versus `versus'
= sreturn local versus
- sreturn local compare `compare'
= sreturn local compare

```

```

- sreturn local level `level'
= sreturn local level 95

```

```

> _____ end _get_diopts.GetDio
> pts _____
- }
- else {
  GetDiopts DUPS options, `options'
  c_local `name2' ``options'
}
- local DUPS : list DUPS - DEFAULT
- gettoken DUPS : DUPS
- if ``DUPS' != "" {
= if ``' != "" {
  if (strpos(`DUPS', "(")) {
    gettoken DUPS : DUPS, parse("(")
    local DUPS ``DUPS'()'
  }
  di as err "duplicate {bf:`DUPS'} option not allowed"
  exit 198
}
- sreturn clear
- foreach sname of local snames {
- sreturn local `sname' = ``S_`sname'
= sreturn local level = `95'
- }
- sreturn local `sname' = ``S_`sname'
= sreturn local k = `0'
- }

```

```

> _____ end _get_dio
> pts _____

```

y_timing_max	Robust		z	P> z	[95% conf. interval]	
	Coefficient	std. err.				
rule_g	.5161489	.167503	3.08	0.002	.1878492	.8444487
rule_itr	.3195246	.1355019	2.36	0.018	.0539459	.5851034
estimated	.7236507	.1034902	6.99	0.000	.5208136	.9264878
_cons	.0221755	.1256523	0.18	0.860	-.2240985	.2684495

```

- if ``markdown' != "" {
= if "" != "" {
  set linesize `lsize'
}
- if ``eqselect' == "" & ``eformnote' != "noeformnote" {

```

```

= if "" == "" & "" != "noeformnote" {
- if ``eformdi''!= "" & (``e(cmd)''!="gnbreg" | ``e(prefix)''==
> "svy") {
= if ``''!= "" & ("poisson"!="gnbreg" | ""=="svy") {
  local k_eform `r(k_eform)'
  if (``k_eform'')== "") {
    local k_eform = 1
  }
  local k_eq `e(k_eq)'
  if (``k_eq'')== "") {
    local k_eq = 1
  }
  if (`k_eform'<`k_eq' & `k_eform') {
    if (``e(cmd2)'' == "stintreg" | ``e(cmd2)'' == "streg") & (``e
> (cmd)'' == "weibull" | ``e(cmd)'' == "gompertz") {
    }
    else {
      _eform_multeq_note efnote : `k_eform' ``tr_item''
      di as txt ``efnote''
    }
  }
}
- if (``eformdi''!= "" & ``e(noconstant)''=="0" & ``eform_cons
> _ti''!= "" & ``e(consonly)''!="1") {
= if (``''!= "" & "0"=="0" & ``''!= "" & "0"!="1") {
  if (``e(cmd)''=="asclogit" | ``e(cmd)''=="cmclogit" | ``e(cmd)
> ""=="cmmixlogit" | ``e(cmd)''=="cmxtmixlogit" ) {
    local asvar = ``e(ranvars)''e(fixvars)''e(indvars)'' != ""
    if ``e(casevars)'' != "" & `asvar' {
      local note1 "Exponentiated coefficients represent odds ratios
> for "
      local note2 "alternative-specific variables (first equation) a
> nd "
      local note3 "{help j_cmrisk##|_new:relative-risk ratios} "
      local note4 "for case-specific variables."
      di as txt "{p 0 6 2}Note: `note1'`note2'`note3'`note4'{p_end}"
    }
  }
  if ``eform_cons_ti'' == "Inc. rate" {
    local eform_cons_note "incidence rate"
  }
  else if ``eform_cons_ti'' == "Rel. risk" {
    local eform_cons_note "relative risk"
  }
  else if ``eform_cons_ti'' == "Health" {
    local eform_cons_note "health (probability of no disease)"

```

```

    }
    else {
        local eform_cons_note = strlower("`eform_cons_ti'")
    }
    local eform_cons_note "baseline `eform_cons_note'"
    if ("`e(cmd2)'"=="") {
        local cmd `e(cmd)'
    }
    else {
        local cmd `e(cmd2)'
    }
    local f2 = udsustr("`cmd'",1,2)
    local is_re = ("`f2'"=="xt" | "`f2'"=="me")
    if `is_re' {
        local extranote " (conditional on zero random effects)"
    }
    di as txt "{p 0 6 2}Note: {bf:_cons} estimates " "`eform_cons_
> note`extranote'" _c
    if ("`e(cmd)'"=="mlogit" | "`e(cmd)'"=="asclogit" | "`e(cmd)'"
> == "cmclogit" | "`e(cmd)'"=="cmmixlogit" | "`e(cmd)'"=="cmxtmixlogit" ) {
        di as txt " for each outcome" _c
    }
    di as txt ".{p_end}"
    }
- }
- return add
- if !`keepmc' {
= if !0 {
- return local mcmethod
- return local mctitle
- }

_____  

> _____ end _coef_ta  

> ble _____  

    - if "`footnote'" == "" {  

= if "nofootnote" == "" {  

    ml_footnote  

    }  

    _____  

> _____ end mopt.Disp  

> lay _____  

    - exit  

    _____  

> _____ end m  

> opt _____  

    - exit

```

```

> _____ end
> ml _____
  - _prefix_footnote
  _____
> _____ begin _prefix_footn
> ote _____
  - version 9
  - local is_st = "`e(cmd2)'" == "streg"
  = local is_st = "" == "streg"
  - if `is_st' {
  = if 0 {
    local tropt TR
  }
  - syntax [, deff `tropt' linesize(int 79) * ]
  = syntax [, deff linesize(int 79) * ]
  - if `is_st' & "`e(noeform)'" != "" & "`tr'" != "" {
  = if 0 & `""' != "" & `""' != "" {
    di as smcl as txt "{p 0 6 2}" "Note: Option {res:tr} ignored; " "not
> appropriate with option {res:strata()} or {res:ancillary()}." "{p_end}"
  }
  - local footnote "`e(footnote)'"
  = local footnote `""'
  - gettoken cmd args : footnote, parse(" ,")
  - capture which `cmd'
  = capture which
  - if !c(rc) {
    if `:length local options' {
      `footnote' , `options'
    }
    else {
      `footnote'
    }
  }
  - capture
  - if "`e(prefix)'" == "svy" {
  = if "" == "svy" {
    _svy_fpc_note "`deff'" `linesize'
    _svy_subpop_note, linesize(`linesize')
    _svy_singleton_note, linesize(`linesize')
  }
  - if inlist("`e(cmd)'", "logit", "logistic", "probit") {
  = if inlist("`poisson'", "logit", "logistic", "probit") {
    CompleteLogit
  }
  - if inlist("`e(cmd)'", "mlogit", "ologit", "oprobit") {

```



```

= if inlist("`poisson'", "mlogit", "ologit", "oprobit") {
  CompleteOlogit
}
- if "`e(missing)'" == "missing" & inlist("`e(vce)'", "brr", "bootstra
> p", "jackknife") {
  = if "" == "missing" & inlist("robust", "brr", "bootstrap", "jackknife
> ") {
    if "`e(vce)'" == "brr" {
      local vcetype BRR
    }
    else local vcetype `e(vce)'
    if e(N_misreps) == 1 {
      local reps replicate
    }
    else {
      local reps replicates
    }
    if "`e(N_misreps)'" != "" {
      local the `e(N_misreps)'
    }
    else local the "some of the"
    di as txt "{p 0 6 0 `linesize'}" "Note: One or more parameters could
> not be estimated in " "`the' `vcetype' `reps'; " "standard-error estimates
> include only complete replications.{p_end}"
  }
  - if inlist("`e(opt)'", "ml", "moptimize") | !missing(e(converged))
> {
    = if inlist("`moptimize'", "ml", "moptimize") | !missing(e(converged))
> {
      - ml_footnote
    }
  }
}

> ----- begin ml_footn
> ote -----
  - version 9
  - syntax
  - _check_e_rc
}

> ----- begin _check_e
> _rc -----
  - version 11
  - syntax [, ignorerc]
  - if e(rc) == 504 & inlist("`e(opt)'", "ml", "moptimize") {
    = if e(rc) == 504 & inlist("moptimize", "ml", "moptimize") {
      di as err "{p 0 0 2}variance matrix missing because `e(user)' fa
> iled" "to compute scores or computed scores with missing values{p_end}"
      exit 504
    }
  }
}

```

```

        }
        - if (`""ignorerc""=="" & !missing(e(rc)) & e(rc) != 0) error e(r
> c)
        = if (`""=="" & !missing(e(rc)) & e(rc) != 0) error e(rc)
        _____
> _____ end _check_e
> _rc _____
        - if ``e(converged)`` == "0" {
        = if ``1`` == "0" {
            di as txt "Warning: Convergence not achieved."
        }
        _____
> _____ end ml_footn
> ote _____
        - }
        - _check_e_rc
        _____
> _____ begin _check_e
> _rc _____
        - version 11
        - syntax [, ignorerc]
        - if e(rc) == 504 & inlist("`e(opt)\"", "ml", "moptimize") {
        = if e(rc) == 504 & inlist("moptimize", "ml", "moptimize") {
            di as err "{p 0 0 2}variance matrix missing because `e(user)' fail
> ed" "to compute scores or computed scores with missing values{p_end}"
            exit 504
        }
        - if (`""ignorerc""=="" & !missing(e(rc)) & e(rc) != 0) error e(rc)
        = if (`""=="" & !missing(e(rc)) & e(rc) != 0) error e(rc)
        _____
> _____ end _check_e
> _rc _____
        _____
> _____ end _prefix_footn
> ote _____
        _____
> _____ end poisson.Disp
> lay _____
        - }
        - error `e(rc)'
        = error 0
        _____
> _____ end poisson.Estim
> ate _____
        - version 10: ereturn local cmdline ``poisson `0'""
        = version 10: ereturn local cmdline ``poisson y_timing_max rule_g rule_itr e

```

```
> stimated if y_timing_max < 99 , vce(robust) nolog''  
_____  
> _____ end pois  
> son _____  
- log close  
    name: <unnamed>  
    log: /Users/connorbrennan/Library/CloudStorage/OneDrive-TheUniversityo  
> fChicago/mmb/output/stepwise_regressions/y_timing_max_nomrig.smcl  
    log type: smcl  
closed on: 12 Sep 2025, 19:25:17  
_____
```