STaTa

Statistics/Data analysis

_____

```
     name:  <unnamed>
      log:  /msu/scratch4/m1cmb07/Connor_bob/mmb/output/stepwise_regressions/infl_per
> _rr_wlth.smcl
  log type:  smcl
 opened on:  18 Jul 2024, 15:09:43
```
****
Interaction effects of wlth and rules on infl_per_rr at various horizons
****
note: **1.rule_g** omitted because of collinearity.
note: **1.wlth#1.rule_g** omitted because of collinearity.
obtaining LAD starting values ... done
iterating RLS .... done
fitting empty model ... done
computing standard errors ... done

M regression (95% efficiency)   Number of obs   =   **228**
                                                 Wald chi2(**5**)   =   **68.03**
                                                 Prob > chi2   =   **0.0000**
                                                 Pseudo R2   =   **0.1379**
                                                 Biweight k   =   **4.685**
                                                 Scale   = **.26163977**

infl_per_rr20	Coefficient	Robust std. err.	t	P>|t|	[95% conf. interval]	
wlth						
0	**0**	(empty)				
1	**-.1947856**	**.162413**	**-1.20**	**0.232**	**-.5148541**	**.1252829**
rule_tr						
0	**0**	(empty)				
1	**.4121311**	**.0556714**	**7.40**	**0.000**	**.302419**	**.5218432**
rule_itr						
0	**0**	(empty)				
1	**.2442134**	**.0658124**	**3.71**	**0.000**	**.1145164**	**.3739105**
rule_g						
0	**0**	(empty)				
1	**0**	(empty)				
wlth#rule_tr						
0 0	**0**	(empty)				
0 1	**0**	(empty)				
1 0	**0**	(empty)				
1 1	**.1601589**	**.1672278**	**0.96**	**0.339**	**-.1693982**	**.489716**
wlth#rule_itr						
0 0	**0**	(empty)				
0 1	**0**	(empty)				
1 0	**0**	(empty)				
1 1	**.1283443**	**.1813393**	**0.71**	**0.480**	**-.2290224**	**.4857111**
wlth#rule_g						
0 0	**0**	(empty)				
0 1	**0**	(empty)				
1 0	**0**	(empty)				
1 1	**0**	(empty)				
_cons	**-.4628368**	**.0525801**	**-8.80**	**0.000**	**-.5664568**	**-.3592168**

```
*******************************************************************************
Interaction effects of wlth and rules on infl_per_rr at various horizons
*******************************************************************************
```
note: **1.rule_g** omitted because of collinearity.
note: **1.wlth#1.rule_g** omitted because of collinearity.
obtaining LAD starting values ... done
iterating RLS .... done
fitting empty model ... done
computing standard errors ... done

M regression (95% efficiency)

Number of obs =	**228**
Wald chi2(**5**) =	**73.59**
Prob > chi2 =	**0.0000**
Pseudo R2 =	**0.1189**
Biweight k =	**4.685**
Scale =	**.31228173**

infl_per_rr40	Coefficient	Robust std. err.	t	P>|t|	[95% conf. interval]	
wlth						
0	**0**	(empty)				
1	**-.1514072**	.1419365	**-1.07**	**0.287**	-.4311224	.128308
rule_tr						
0	**0**	(empty)				
1	**.4540582**	.0601432	**7.55**	**0.000**	.3355336	.5725829
rule_itr						
0	**0**	(empty)				
1	**.2704311**	.0723528	**3.74**	**0.000**	.1278448	.4130173
rule_g						
0	**0**	(empty)				
1	**0**	(empty)				
wlth#rule_tr						
0 0	**0**	(empty)				
0 1	**0**	(empty)				
1 0	**0**	(empty)				
1 1	**.1501798**	.1511237	**0.99**	**0.321**	-.1476408	.4480004
wlth#rule_itr						
0 0	**0**	(empty)				
0 1	**0**	(empty)				
1 0	**0**	(empty)				
1 1	**.1399454**	.1853091	**0.76**	**0.451**	-.2252446	.5051353
wlth#rule_g						
0 0	**0**	(empty)				
0 1	**0**	(empty)				
1 0	**0**	(empty)				
1 1	**0**	(empty)				
_cons	**-.5061868**	.0555678	**-9.11**	**0.000**	-.6156947	-.3966789

```
****************************************************************************
Interaction effects of wlth and rules on infl_per_rr at various horizons
****************************************************************************
```

note: **1.rule_g** omitted because of collinearity.
note: **1.wlth#1.rule_g** omitted because of collinearity.
obtaining LAD starting values ... done
iterating RLS .... done
fitting empty model ... done
computing standard errors ... done

M regression (95% efficiency)

Number of obs	= **228**
Wald chi2(**5**)	= **66.68**
Prob > chi2	= **0.0000**
Pseudo R2	= **0.1121**
Biweight k	= **4.685**
Scale	= **.32259097**

infl_per_rr60	Coefficient	Robust std. err.	t	P>|t|	[95% conf. interval]	
wlth						
0	**0**	(empty)				
1	**-.1306403**	**.1435879**	**-0.91**	**0.364**	**-.41361**	**.1523294**
rule_tr						
0	**0**	(empty)				
1	**.470082**	**.0665692**	**7.06**	**0.000**	**.3388937**	**.6012703**
rule_itr						
0	**0**	(empty)				
1	**.2710384**	**.0786714**	**3.45**	**0.001**	**.116**	**.4260767**
rule_g						
0	**0**	(empty)				
1	**0**	(empty)				
wlth#rule_tr						
0 0	**0**	(empty)				
0 1	**0**	(empty)				
1 0	**0**	(empty)				
1 1	**.1422923**	**.1539162**	**0.92**	**0.356**	**-.1610315**	**.4456161**
wlth#rule_itr						
0 0	**0**	(empty)				
0 1	**0**	(empty)				
1 0	**0**	(empty)				
1 1	**.1556446**	**.2007824**	**0.78**	**0.439**	**-.2400387**	**.551328**
wlth#rule_g						
0 0	**0**	(empty)				
0 1	**0**	(empty)				
1 0	**0**	(empty)				
1 1	**0**	(empty)				
_cons	**-.5261869**	**.0620411**	**-8.48**	**0.000**	**-.6484518**	**-.403922**

```
      name:  <unnamed>
       log:  /msu/scratch4/m1cmb07/Connor_bob/mmb/output/stepwise_regressions/infl_per
> _rr_wlth.smcl
  log type:  smcl
 closed on:  18 Jul 2024, 15:09:43
```
───