HPE Smart Choice Purchase Program – Supplemental QuickSpecs



Overview

HPE Smart Choice Purchase Program – Supplemental QuickSpecs

What is the HPE Smart Choice purchase program?

The HPE Smart Choice purchase program features popular fully configured products that can be quoted in minutes and shipped quickly through HPE Authorized Partners. Products are configured and tested in an HPE factory and stocked at HPE Authorized Distributors and Partners. The products arrive in a single box, making onsite integration easier and more efficient for partners and customers. Additionally, there are aggressively priced HPE Tech Care Services available only through the HPE Smart Choice program when you purchase an HPE Smart Choice product.

Country Code Key

- -005 = HPE Smart Choice for US and Canada
- -035 = HPE Smart Choice for United Kingdom
- -205 = HPE Smart Choice for Brazil
- -425 = HPE Smart Choice for Europe, the Middle East and Africa (EMEA)
- -D65 = HPE Smart Choice for India
- -DM5 = HPE Smart Choice for LATAM



Smart Choice Services

HPE Services

Don't forget to add HPE Services – Standard Tech Care Basic and Essential Fixed support services in unique packages specific to Smart Choice purchase server configurations.

Fixed Families	Fixed SS	Long Description
Smart Choice DL320	H44YQE	HPE 3Year Tech Care Basic DL320 Gen11 Smart Choice Service
Gen11	H44YSE	HPE 5Year Tech Care Basic DL320 Gen11 Smart Choice Service
	H44YRE	HPE 3Year Tech Care Essential DL320 Gen11 Smart Choice Service
	H44YTE	HPE 5Year Tech Care Essential DL320 Gen11 Smart Choice Service
Smart Choice DL360	H44YVE	HPE 3Year Tech Care Basic DL360 Gen10/Gen10+ Smart Choice Service
G10/+	H44YXE	HPE 5Year Tech Care Basic DL360 Gen10/Gen10+ Smart Choice Service
	H44YWE	HPE 3Year Tech Care Essential DL360 Gen10/Gen10+ Smart Choice Service
	H44YYE	HPE 5Year Tech Care Essential DL360 Gen10/Gen10+ Smart Choice Service
Smart Choice DL360	H44YZE	HPE 3Year Tech Care Basic DL360 Gen11 Smart Choice Service
G11	H44ZCE	HPE 5Year Tech Care Basic DL360 Gen11 Smart Choice Service
	H44ZBE	HPE 3Year Tech Care Essential DL360 Gen11 Smart Choice Service
	H44ZDE	HPE 5Year Tech Care Essential DL360 Gen11 Smart Choice Service
Smart Choice DL380	H44ZFE	HPE 3Year Tech Care Basic DL380 Gen10/Gen10+ Smart Choice Service
G10/+	H44ZHE	HPE 5Year Tech Care Basic DL380 Gen10/Gen10+ Smart Choice Service
	H44ZGE	HPE 3Year Tech Care Essential DL380 Gen10/Gen10+ Smart Choice Service
	H44ZJE	HPE 5Year Tech Care Essential DL380 Gen10/Gen10+ Smart Choice Service
Smart Choice DL38x	H44ZKE	HPE 3Year Tech Care Basic DL38x Gen11 Smart Choice Service
G11	H44ZME	HPE 5Year Tech Care Basic DL38x Gen11 Smart Choice Service
	H44ZLE	HPE 3Year Tech Care Essential DL38x Gen11 Smart Choice Service
	H44ZNE	HPE 5Year Tech Care Essential DL38x Gen11 Smart Choice Service
Smart Choice	H44ZQE	HPE 3Year Tech Care Basic DL325/DL345 Gen11 Smart Choice Service
DL325/DL345 G11	H44ZSE	HPE 5Year Tech Care Basic DL325/DL345 Gen11 Smart Choice Service
	H44ZRE	HPE 3Year Tech Care Essential DL325/DL345 Gen11 Smart Choice Service
	H44ZTE	HPE 5Year Tech Care Essential DL325/DL345 Gen11 Smart Choice Service
Smart Choice ML350	H44ZVE	HPE 3Year Tech Care Basic ML350 Gen11 Smart Choice Service
G11	H44ZXE	HPE 5Year Tech Care Basic ML350 Gen11 Smart Choice Service
	H44ZWE	HPE 3Year Tech Care Essential ML350 Gen11 Smart Choice Service
	H44ZYE	HPE 5Year Tech Care Essential ML350 Gen11 Smart Choice Service
Smart Choice ML110	H44ZZE	HPE 3Year Tech Care Basic ML110 Server Smart Choice Service
	H45BBE	HPE 5Year Tech Care Basic ML110 Server Smart Choice Service
Smart Choice Low-end	H45BCE	HPE 3Year Tech Care Basic Low-end Server (ML30 and DL20) Smart Choice Service
Servers	H45BDE	HPE 5Year Tech Care Basic Low-end Server (ML30 and DL20) Smart Choice Service
Smart Choice	H45BFE	HPE 3Year Tech Care Basic MicroServer Smart Choice Service
MicroServers	H45BGE	HPE 5Year Tech Care Basic MicroServer Smart Choice Service



HPE ProLiant	DL20 Gen11 - Smart Choice Models		
SKU Number	P71375-425	P71682-005	
Model Name	HPE ProLiant DL20 Gen11 E-2436 2.9GHz 6c 1P 32GB-DR 4SFF VROC 2x480GB SATA SSD 800W RPS EU Server	HPE ProLiant DL20 Gen11 E-2436 2.9GHz 6-core 1P 32GB-DR MR408i-o 4SFF 2x500W RPS NA Server	
Chassis	HPE ProLiant DL20 Gen11 4SFF Hot Plug Configure-to-	order Server	
Processor	E-2436 (6 core, 2.9 GHz, 65W)		
Number of Processors	One		
Memory	32 GB (1x32 GB UDIMM, 4800 MT/s)		
Network Controller	HPE embedded 1GB 4-port BCM5719 Network Adapter		
Storage Controller	Embedded Intel VROC SATA software RAID Notes: SATA only	HPE MR408i-o Gen11 x8 Lanes 4GB Cache OCP SPDM Storage Controller	
Included Hard Drives	2x 480GB SATA SSD	2x 960GB SATA SSD	
Internal Storage	4 SFF HDD Bays (Hot Plug)		
Optical Drive	Optional: DVD-ROM, DVD-RW		
Expansion Slots	1x PCIe 5.0 CEM slot, 1 Internal OCP Storage Controller s	slot, 1 External OCP 3.0 Network Controller slot	
Power Supply	1x HPE 800W Flex Slot Titanium Hot Plug Low Halogen Power Supply Kit	2x HPE 500W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit	
Fans	3x high performance non-hot plug and non-redundant fa	ans	
Management	iLO Management (standard), Intelligent Provisioning (standard) iLO Advanced (optional)		
Rail Kit	HPE Easy Install Rail 12 Kit		
Security	TPM (Trusted Platform Module)		

HPE ProLiant	DL20 Gen11 - Smart Choice Models		
SKU Number	P74296-205	P75333-D65	
Model Name	HPE ProLiant DL20 Gen11 E-2436 2.9GHz 6c 1P 32GB-R 4SFF 2x480GB SSD 500W PS BR Server	HPE ProLiant DL20 Gen11 E-2436 2.9GHz 6c 1P 32GB-DR 4SFF 960GB SSD 500W PS IN Server	
Chassis	HPE ProLiant DL20 Gen11 4SFF Hot Plug Configure-to-	order Server	
Processor	E-2436 (6 core, 2.9 GHz, 65W)		
Number of Processors	One		
Memory	32 GB (2x16 GB UDIMM, 4800 MT/s)	32 GB (1x32 GB UDIMM, 4800 MT/s)	
Network Controller	HPE embedded 1GB 4-port BCM5719 Network Adapter		
Storage Controller	Embedded Intel VROC SATA software RAID Notes: SATA only		
Included Hard Drives	2x 480GB SATA SSD	960GB SATA SSD	
Optical Drive	Optional: DVD-ROM, DVD-RW		
Expansion Slots	1x PCIe 5.0 CEM slot, 1 Internal OCP Storage Controller slot, 1 External OCP 3.0 Network Controller slot		
Power Supply	1x HPE 500W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit		
Fans	3x high performance non-hot plug and non-redundant fans		
Management	iLO Management (standard), Intelligent Provisioning (standard) iLO Advanced (optional)		
Rail Kit	HPE Easy Install Rail 12 Kit		
Security	TPM (Trusted Platform Module)		

HPE ProLiant	PE ProLiant DL320 Gen11 - Smart Choice Models			
SKU Number	P69302-005	P77243-425		
Model Name	HPE ProLiant DL320 Gen11 5416S 2.0GHz 16-core 1P 64GB-R 8SFF 800W PS AMS Server	HPE ProLiant DL320 Gen11 4514Y 2.0GHz 16c 64GB-R 8SFF MR408i-o 2x480GB SATA SSD 2x1000W PS EU Server		
Chassis	HPE ProLiant DL320 Gen11 8SFF Configure-to-order Se	erver		
Processor	5416S (16 core, 2.0 GHz, 150W)	4514Y (16 core, 2.0 GHz, 150W)		
Number of Processors	One with standard heatsink			
Memory	64 GB (2x32 GB, 4800 MT/s) Notes: Runs at 4400 MT/s due to processor limitation.	64 GB (2x32 GB, 5600 MT/s) Notes: Runs at 4400 MT/s due to processor limitation.		
Network Controller	Broadcom BCM5720 Ethernet 1Gb 2-port BASE-T Adap	CM5720 Ethernet 1Gb 2-port BASE-T Adapter		
Storage Controller	HPE NS204i-u Gen11 NVMe Hot Plug Boot Optimized Storage Device	HPE MR408i-o Gen11 x8 Lanes 4GB Cache OCP SPDM Storage Controller Notes: Smart Storage battery included		
Included Hard Drives	None ship standard, 8 SFF supported	2x 480GB SATA SSD		
Optical Drive	None included (Optical Drive options available)	None included, optional HPE 9.5mm SATA DVD-RW Optical Drive or HPE Mobile USB DVD-RW Drive		
Expansion Slots	1 x16 FHHL PCle Gen5; 1 OCP 3.0 Slot as default. 1 x16	FHHL PCIe Gen5 optional.		
Power Supply	2x HPE 800W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit	2x HPE 1000W Flex Slot Titanium Hot Plug Power Supply Kit		
Fans	7x High Performance Fans	7x Standard Fans		
Management	HPE iLO 6			
Rail Kit	HPE Easy Install Rail 1 Kit			
Security	TPM (Trusted Platform Module)			

Model Name HPE ProLiant DL325 Gen11 9354P 3.25GHz 32c 1P 256GB-R 8SFF MR408i-o 800W PS Server Chassis HPE ProLiant DL325 Gen11 9354P MR408i-o 800W PS Server Chassis HPE ProLiant DL325 Gen11 8SFF Configure-to-order Server Backplane Processor 9354P (32 core, 3.25 GHz, 280W) Number of Processors Memory 256 GB (4x64 GB, 4800 MT/s) Broadcom BCM57414 Ethernet 20/25GB-2-port SP28 OCP3 Adapter for HPE Storage Controller HPE MR408i-o Gen11 x8 Lanes 4GB Cache OCP SPDM Storage Controller Included Hard Drives 8 SFF Cache 2x480GB SATA SSD 2x 480GB SATA SSD 2x 480GB SATA SSD Adapter for HPE With standard heatsink One with standard heatsink Processors Memory 256 GB (4x64 GB, 4800 MT/s) Broadcom BCM57414 Ethernet 20/25Gb 2-port SFP28 OCP3 Adapter for HPE Broadcom BCM57416 Ethernet 1Gb 4-port BASE-T OCP3 Adapter for HPE Storage Controller Included Hard Drives 2x 1.92TB NVMe SSD 2x 480GB SATA SSD 2x 480GB SATA SSD 2x 480GB SATA SSD 2x 480GB SATA SSD Doptional, None ship standard Expansion Stors 1 PCIe x16 Primary Riser Power Supply Are Formance Fans 7x Standard Fans 7x Standard Fans As Per Formance Fans 7x Standard Fans As Per Formance Fans 7x Standard Fans Management Default: HPE iLO Standard with Intelligent Provisioning, HPE OneView Standard (requires download) Rail Kit HPE ProLiant DL32X Sep11 asy Install Rail 2 Kit Socurity TPM (Trusted Platform Module)	HPE ProLiant	DL325 Gen11 - Smart Choice Models	5	
Model Name HPE Prollant D235 Gen.11 934P AST Security 3.0GHz 16c 1P 32GB-R 8SFF MR408I-0 2x480GB SATA 2x800W RPS 2x480GB SATA SSD 2x1000W RPS LA Server 2.5GHz 24c 64GB-R 8SFF MR408I-0 2x480GB SATA 2x800W RPS EU Server Chassis HPE ProLiant DL325 Gen.11 8SFF Configure-to-order Server HPE ProLiant DL325 Gen.11 8SFF Configure-to-order Server Backplane 8 SFF Processor Processor 9354P (32 core, 3.25 GHz, 280W) 9124 (16 core, 3.0 GHz, 200W) 9224 (24 core, 2.5 GHz, 200W) Number of Processors One with performance heatsink One with standard heatsink One with standard heatsink Memory 256 GB (4x64 GB, 4800 MT/s) 32 GB (1x32 GB, 4800 MT/s) 64 GB (2x32 GB, 4800 MT/s) 8 Foradocom BCM5719 Ethernet 1Gb L9/25Gb 2-port SFP28 OCP3 Adapter for HPE 8 Foradocom BCM5719 Ethernet 1Gb L9-port BASE-T OCP3 Adapter for HPE 9 Foradocom BCM5714 Ethernet 1Gb L9-port BASE-T OCP3 Adapter for HPE 9 Foradocom BCM5714 Ethernet 1Gb L9-port BASE-T OCP3 Adapter for HPE 9 Foradocom BCM5714 Ethernet 1Gb L9-port BASE-T OCP3 Adapter for HPE 9 Foradocom BCM5714 Ethernet 1Gb L9-port BASE-T OCP3 Adapter for HPE 9 Foradocom BCM5714 Ethernet 1Gb L9-port BASE-T OCP3 Adapter for HPE 9 Foradocom BCM5714 Ethernet 1Gb L9-port BASE-T OCP3 Adapter for HPE 9 Foradocom BCM5714 Ethernet 1Gb L9-port BASE-T OCP3 Adapter for HPE 9 Foradocom BCM5714 Ethernet 1Gb L9-port BASE-T OCP3 Adapter for HPE 9 Foradocom BCM5714 Ethern	SKU Number	P72990-005	P75342-DM5	P77239-425
Backplane 8 SFF 9354P (32 core, 3.25 GHz, 280W) 9124 (16 core, 3.0 GHz, 200W) 9224 (24 core, 2.5 GHz, 200W) Number of Processors One with performance heatsink One with standard for Hore To Procesors OPT BASE-T OCP3 Adapter for Adapter for HPE Ord BASE-T OCP3 Adapter for HPE Ord Procesors OPT BASE-T OCP3 Adapter for HPE Ord Proc	Model Name	3.25GHz 32c 1P 256GB-R 8SFF	3.0GHz 16c 1P 32GB-R 8SFF MR408i-o 2x480GB SATA 2x800W	2.5GHz 24c 64GB-R 8SFF MR408i- o 2x480GB SATA SSD 2x1000W
Processor 9354P (32 core, 3.25 GHz, 280W) 9124 (16 core, 3.0 GHz, 200W) 9224 (24 core, 2.5 GHz, 200W) Number of Processors One with performance heatsink One with standard Broadcom BCM5719 Ethernet 1Gb drows DCM57416 Ethernet 10/25Gb 2-port SF28 OCP3 Adapter for HPE Storage Controller HPE MR408i-o Gen11 x8 Lanes 4GB Cache OCP SPDM Storage Controller Included Large Power Standard Storage Ontroller Storage Ontroller SF front) Optical Drive Optional, None ship standard Optional, None ship standard Optional, None ship standard Drows Slots Platinum Hor Plug Low Halogen Power Supply Kit Slot Platinum Hor Plug Low Halogen Power Supply Kit Standard Fans Optional HPE ILO Standard with Intelligent Provisioning, HPE OneView Standard (requires download) Rail Kit HPE ProLiant DL3XX Gen11 Easy Install Rail 2 Kit Security TPM (Trusted Platform Module)	Chassis	HPE ProLiant DL325 Gen11 8SFF Co	onfigure-to-order Server	
Number of Processors One with performance heatsink One with standard should hall on the standard one scale and with standard one by Sea Boo WENSON DATA SED Broadcom BCM57416 Ethernet 106 Broadcom BCM57416 Ethernet 106 Broadcom BCM57416 Ethernet 106b 4-port BASE-T OCP3 Adapter for HPE OCATION BROADCH BEXSET OCP3 Adapter for HPE One View Standard New Sept Broadcom BCM5719 Ethernet 106b 4-pour Book DATA SED One with standard Heatson MT/s) Broadcom BCM5719 Ethernet 106b 4-pour Book BCM5719 Ethernet 106b 4-pour BASE-T OCP3 Adapter for HPE One Valoue Broadcam BCM5719 Ethernet 106b 4-pour Book	Backplane		8 SFF	
Processors One with performance heatsink One with standard heatsink Of 4 GB (2x32 GB, 4800 MT/s) Broadcom BCM57416 Ethernet 10Gb 2-port BASE-T OCP3 Adapter for HPE OCP3 Adapter for HPE Storage Controller HPE MR408i-o Gen11 x8 Lanes 4GB Cache OCP SPDM Storage Controller 2x 480GB SATA SSD 2x 480GB SATA SSD 2x 480GB SATA SSD Optional, None ship standard Optional, None ship standard 1 PCle x16 Primary Riser 2x HPE 800W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit Hot Plug Low Halogen Power Supply Kit Fans 7x Standard Fans 7x Standard Fans Management Default: HPE iLO Standard with Intelligent Provisioning, HPE OneView Standard (requires download) HPE ProLiant DL3XX Gen11 Easy Install Rail 2 Kit TPM (Trusted Platform Module)	Processor	9354P (32 core, 3.25 GHz, 280W)	9124 (16 core, 3.0 GHz, 200W)	9224 (24 core, 2.5 GHz, 200W)
Network Controller Broadcom BCM57414 Ethernet 10/25Gb 2-port SFP28 OCP3 Adapter for HPE Storage Controller Included Hard Drives Breadcom BCM57416 Ethernet 10/25Gb 2-port BASE-T OCP3 Adapter for HPE Storage Controller Included Hard Drives Breadcom BCM57416 Ethernet 10/25Gb 2-port BASE-T OCP3 Adapter for HPE Storage Controller Included Hard Drives Breadcom BCM57416 Ethernet 10/25Gb 2-port BASE-T OCP3 Adapter for HPE Storage Controller Included Hard Drives Breadcom BCM57416 Ethernet 10/25Gb 2-port BASE-T OCP3 Adapter for HPE Storage Controller Included Hard Drives Breadcom BCM57416 Ethernet 10/25Gb 2-port BASE-T OCP3 Adapter for HPE Storage Controller Included Hard Drives Breadcom BCM57416 Ethernet 10/25Gb 2-port BASE-T OCP3 Adapter for HPE Storage Controller Included Hard Drives 2x 480GB SATA SSD Internal Storage SFF Chassis (upgradeable to 10 SFF front) Optional, None ship standard Optional, None ship standard Expansion 1 PCle x16 Primary Riser Power Supply Hot Plug Low Halogen Power Supply Kit Fans 7x Performance Fans 7x Standard Fans 7x Standard Fans Management Default: HPE iLO Standard with Intelligent Provisioning, HPE OneView Standard (requires download) Rail Kit HPE ProLiant DL3XX Gen11 Easy Install Rail 2 Kit TPM (Trusted Platform Module)	Number of Processors	One with performance heatsink	One with standard heatsink	One with standard heatsink
Controller 10/25Gb 2-port SFP28 OCP3 Adapter for HPE 10/25Gb 2-port BASE-T OCP3 2x 480GB SATA SSD 2x 480	Memory	256 GB (4x64 GB, 4800 MT/s)	32 GB (1x32 GB, 4800 MT/s)	64 GB (2x32 GB, 4800 MT/s)
Controller HPE MR408I-0 Gen11 x8 Lanes 4GB Cacne OCP SPDM Storage Controller Included Hard Drives Internal Storage SFF Chassis (upgradeable to 10 SFF front) Optical Drive Optional, None ship standard Expansion Slots Power Supply Cx HPE 800W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit Fans 7x Performance Fans 7x Standard Fans Default: HPE iLO Standard with Intelligent Provisioning, HPE OneView Standard (requires download) Rail Kit HPE ProLiant DL3XX Gen11 Easy Install Rail 2 Kit Security 2x 480GB SATA SSD 2x 480G	Network Controller	10/25Gb 2-port SFP28 OCP3	4-port BASE-T OCP3 Adapter for	10Gb 2-port BASE-T OCP3 Adapter
Hard Drives Internal 2x 1.92 IB NVMe SSD 2x 480GB SATA SSD 2x 480	Storage Controller	HPE MR408i-o Gen11 x8 Lanes 4GB	Cache OCP SPDM Storage Controller	
Storage SFF front) Optical Drive Optional, None ship standard Optional, None ship standard Expansion Slots Power Supply Can HPE 800W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit Fans 7x Performance Fans 7x Standard Fans Default: HPE iLO Standard with Intelligent Provisioning, HPE OneView Standard (requires download) Rail Kit HPE ProLiant DL3XX Gen11 Easy Install Rail 2 Kit TPM (Trusted Platform Module)	Included Hard Drives	2x 1.92TB NVMe SSD	2x 480GB SATA SSD	2x 480GB SATA SSD
Expansion Slots 1 PCle x16 Primary Riser 2x HPE 800W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit 7x Performance Fans 7x Standard Fans Default: HPE iLO Standard with Intelligent Provisioning, HPE OneView Standard (requires download) Rail Kit TPM (Trusted Platform Module)	Internal Storage			
Power Supply 2x HPE 800W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit 7x Performance Fans 7x Standard Fans Default: HPE iLO Standard with Intelligent Provisioning, HPE OneView Standard (requires download) Rail Kit TPM (Trusted Platform Module) 2x HPE 800W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit 7x HPE 1000W Flex Slot Titanium Hot Plug Power Supply Kit 7x Standard Fans 7x Standard Fans 7x Standard Fans 7x Standard (requires download)	Optical Drive	Optional, None ship standard		Optional, None ship standard
Hot Plug Low Halogen Power Supply Kit Hot Plug Low Halogen Power Supply Kit Fans 7x Performance Fans 7x Standard Fans Default: HPE iLO Standard with Intelligent Provisioning, HPE OneView Standard (requires download) Rail Kit Hot Plug Low Halogen Power Supply Kit 7x Standard Fans 7x Standard Fans Power Supply Kit TPM (Trusted Platform Module)	Expansion Slots	1 PCle x16 Primary Riser		
Management Default: HPE iLO Standard with Intelligent Provisioning, HPE OneView Standard (requires download) Rail Kit HPE ProLiant DL3XX Gen11 Easy Install Rail 2 Kit Security TPM (Trusted Platform Module)	Power Supply	Hot Plug Low Halogen Power Supply	Hot Plug Low Halogen Power Supply	
Rail Kit HPE ProLiant DL3XX Gen11 Easy Install Rail 2 Kit Security TPM (Trusted Platform Module)	Fans	7x Performance Fans	7x Standard Fans	7x Standard Fans
Security TPM (Trusted Platform Module)	Management	Default: HPE iLO Standard with Intelli	gent Provisioning, HPE OneView Stand	lard (requires download)
	Rail Kit	HPE ProLiant DL3XX Gen11 Easy Ins	itall Rail 2 Kit	
Energy Star 4.0 certified	Security	TPM (Trusted Platform Module)		
	Energy Star	4.0 certified		

HPE ProLiant	DL325 Gen11 - Smart Choice Models			
SKU Number	P77246-005	P77252-425		
Model Name	HPE ProLiant DL325 Gen11 9124 3.0GHz 16c 64GB-R 8SFF MR408i-o 2x480GB SATA SSD 2x500W RPS NA Server	HPE ProLiant DL325 Gen11 9124 3.0GHz 16c 64GB-R 8SFF MR408i-o 2x480GB SATA SSD 2x1000W RPS EU Server		
Chassis	HPE ProLiant DL325 Gen11 8SFF Configure-to-order Se	erver		
Processor	9124 (16 core, 3.0 GHz, 200W)			
Number of Processors	One with standard heatsink			
Memory	64 GB (2x32 GB, 4800 MT/s)			
Network Controller	Broadcom BCM57416 Ethernet 10Gb 2-port BASE-T OCP3 Adapter for HPE	Broadcom BCM5719 Ethernet 1Gb 4-port BASE-T OCP3 Adapter for HPE		
Storage Controller	HPE MR408i-o Gen11 x8 Lanes 4GB Cache OCP SPDM Storage Controller			
Included Hard Drives	2x 480GB SATA SSD	2x 480GB SATA SSD		
Optical Drive	Optional, None ship standard			
Expansion Slots	1 PCle x16 Primary Riser			
Power Supply	2x HPE 500W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit	2x HPE 1000W Flex Slot Titanium Hot Plug Power Supply Kit		
Fans	7x Standard Fans			
Management	Default: HPE iLO Standard with Intelligent Provisioning, HPE OneView Standard (requires download)			
Rail Kit	HPE ProLiant DL3XX Gen11 Easy Install Rail 2 Kit	HPE ProLiant DL3XX Gen11 Easy Install Rail 2 Kit		
Security	TPM (Trusted Platform Module)			

HPE ProLiant	IPE ProLiant DL345 Gen11 - Smart Choice Models				
SKU Number	P75332-005	P77238-425	P77248-425		
Model Name	HPE ProLiant DL345 Gen11 9354P 3.25GHz 32c 1P 256GB-R 8SFF MR416i-p 2x1.92TB SSD 2x800W PS NA Server	HPE ProLiant DL345 Gen11 9124 3.0GHz 16c 64GB-R 8SFF MR416i- p 2x480GB SATA SSD 2x1000W RPS EU Server	HPE ProLiant DL345 Gen11 9124 3.0GHz 16c 64GB-R 8LFF MR416i- p 2x960GB SATA SSD 2x1000W RPS EU Server		
Chassis	HPE ProLiant DL345 Gen11 8SFF Configure-to-order Server	HPE ProLiant DL345 Gen11 8SFF Configure-to-order Server	HPE ProLiant DL345 Gen11 8LFF Configure-to-order Server		
Backplane	2x 8SFF				
Processor	9354P (32 core, 3.25 GHz, 280W)	9124 (16 core, 3.0 GHz, 200W)	9124 (16 core, 3.0 GHz, 200W)		
Number of Processors	One with performance heatsink	One with standard heatsink	One with standard heatsink		
Memory	256 GB (4x64 GB, 4800 MT/s)	64 GB (2x32 GB, 4800 MT/s)	64 GB (2x32 GB, 4800 MT/s)		
Network Controller	1x Broadcom BCM57414 Ethernet 10/25Gb 2-port SFP28 OCP3 Adapter for HPE 1x Broadcom BCM5719 Ethernet 1Gb 4-port BASE-T OCP3 Adapter for HPE	Broadcom BCM5719 Ethernet 1Gb 4-port BASE-T OCP3 Adapter for HPE	Broadcom BCM5719 Ethernet 1Gb 4-port BASE-T OCP3 Adapter for HPE		
Storage Controller	HPE MR416i-p Gen11 x16 Lanes 8G	B Cache PCI SPDM Plug-in Storage Co	ontroller		
Included Hard Drives	2x 1.92TB NVMe SSD	2x 480GB SATA SSD	2x 960GB SATA SSD		
Expansion Slots	2 PCle x16 Riser (Primary slot 3 and S	Secondary slot 6)			
Power Supply	2x HPE 800W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit	2x HPE 1000W Flex Slot Titanium Hot Plug Power Supply Kit	2x HPE 1000W Flex Slot Titanium Hot Plug Power Supply Kit		
Fans	6x Standard Fans				
Management	Default: HPE iLO Standard with Intelli	gent Provisioning, HPE OneView Stand	dard (requires download)		
Rail Kit	HPE ProLiant DL3XX Gen11 Easy Ins	tall Rail 2 Kit			
Security	TPM (Trusted Platform Module)				

HPE ProLiant	DL360 Gen11 - Smart Choice Model	s	
SKU Number	P71673-425	P71676-005	P71678-005
Model Name	HPE ProLiant DL360 Gen11 4510 2.4GHz 12c 1P 64GB-R 8SFF MR408i-o 2x960GB SSD 2x1000W PS EMEA Server	HPE ProLiant DL360 Gen11 4509Y 2.6GHz 8-core 1P 64GB-R MR408i- o NC 8SFF 1000W RPS AMS Server	HPE ProLiant DL360 Gen11 6526Y 2.8GHz 16-core 1P 128GB-R NS204i-u NC 8SFF 1000W RPS AMS Server
Chassis	HPE ProLiant DL360 Gen11 8SFF N	C Configure-to-order Server	
Processor	4510 (12 core, 2.4 GHz, 150W)	4509Y (8 core, 2.6 GHz, 125W)	6526Y (16 core, 2.8 GHz, 195W)
Number of Processors	One with standard heatsink	One with standard heatsink	One with high performance heatsink
Memory	64 GB (2x32 GB, 5600 MT/s) Notes: Runs at 4400 MT/s due to processor limitation.	64 GB (2x32 GB, 5600 MT/s) Notes: Runs at 4400 MT/s due to processor limitation.	128 GB (4x32 GB, 5600 MT/s) Notes: Runs at 5200 MT/s due to processor limitation.
Network Controller	Broadcom BCM5719 Ethernet 1Gb 4-port BASE-T OCP3 Adapter for HPE Notes: No embedded networking		
Storage Controller	HPE MR408i-o Gen11 x8 Lanes 4GB Cache OCP SPDM Storage Controller	HPE MR408i-o Gen11 x8 Lanes 4GB Cache OCP SPDM Storage Controller	HPE NS204i-u Gen11 NVMe Hot Plug Boot Optimized Storage Device
Included Hard Drives	2x 960GB SATA SSD	2x 480GB SATA SSD	None ship standard, 8 SFF supported
Optical Drive	Optional - HPE 9.5mm SATA DVD-R	W Optical Drive, HPE Mobile USB DVD-	-RW Drive.
Expansion Slots		d. Upgradeable to 3rd slot in HH (or re All PCIe Slots are in design with up to 9.	
Power Supply	2x HPE 1000W Flex Slot Titanium Hot Plug Power Supply Kit		
Fans	5x Standard Fans	5x Standard Fans	7x High Performance Fans
Management	HPE iLO 6		
Rail Kit	HPE ProLiant DL3XX Gen11 Easy Install Rail 3 Kit Notes: Server does not support shelf mounted rail kits ("L" brackets).		
Security	TPM (Trusted Platform Module)		

HPE ProLiant	PE ProLiant DL360 Gen11 - Smart Choice Models			
SKU Number	P71686-005	P72985-005	P72987-005	
Model Name	HPE ProLiant DL360 Gen11 4510 2.4GHz 12-core 1P 64GB-R MR408i-o NC 8SFF 1000W RPS AMS Server	HPE ProLiant DL360 Gen11 4514Y 2.0GHz 16c 128GB-R 8SFF MR408i-o 2x1.2TB HDD NC 2x1000W RPS NA Server	HPE ProLiant DL360 Gen11 4510 2.4GHz 12c 64GB-R 8SFF MR408i- o 2x1.2TB HDD NC 2x1000W RPS NA Server	
Chassis	HPE ProLiant DL360 Gen11 8SFF N	C Configure-to-order Server		
Processor	4510 (12 core, 2.4 GHz, 150W)	4514Y (16 core, 2.0 GHz, 150W)	4510 (12 core, 2.4 GHz, 150W)	
Number of Processors	One with standard heatsink			
Memory	64 GB (2x32 GB, 5600 MT/s) Notes: Runs at 4400 MT/s due to processor limitation.	128 GB (4x32 GB, 5600 MT/s) Notes: Runs at 4400 MT/s due to processor limitation.	64 GB (2x32 GB, 5600 MT/s) Notes: Runs at 4400 MT/s due to processor limitation.	
Network Controller	Broadcom BCM5719 Ethernet 1Gb 4-port BASE-T OCP3 Adapter for HPE Notes: No embedded networking			
Storage Controller	HPE MR408i-o Gen11 x8 Lanes 4GE	8 Cache OCP SPDM Storage Controller		
Included Hard Drives	2x 480GB SATA SSD	2x 1.2TB SAS HDD	2x 1.2TB SAS HDD	
Optical Drive	Optional - HPE 9.5mm SATA DVD-R	W Optical Drive, HPE Mobile USB DVD-	-RW Drive.	
Expansion Slots		d. Upgradeable to 3rd slot in HH (or re All PCle Slots are in design with up to 9.		
Power Supply	2x HPE 1000W Flex Slot Titanium Hot Plug Power Supply Kit			
Fans	5x Standard Fans			
Management	HPE iLO 6			
Rail Kit	HPE ProLiant DL3XX Gen11 Easy Install Rail 3 Kit Notes: Server does not support shelf mounted rail kits ("L" brackets).			
Security	TPM (Trusted Platform Module)			

HPE ProLiant	DL360 Gen11 - Smart Choice Models	5		
SKU Number	P72992-005	P72993-005	P72994-005	
Model Name	HPE ProLiant DL360 Gen11 4514Y 2.0GHz 16c 128GB-R 8SFF MR408i-o 2x960GB SSD NC 2x1000W RPS NA Server	HPE ProLiant DL360 Gen11 4516Y+ 2.2GHz 24c 1P 128GB-R 8SFF NS204i-u NC 2x1000W RPS NA Server	HPE ProLiant DL360 Gen11 6530 2.1GHz 32c 1P 128GB-R 8SFF NS204i-u NC 2x1000W RPS NA Server	
Chassis	HPE ProLiant DL360 Gen11 8SFF No	C Configure-to-order Server		
Processor	4514Y (16 core, 2.0 GHz, 150W)	4516Y+ (24 core, 2.2 GHz, 185W)	6530 (32 core, 2.1 GHz, 270W)	
Number of Processors	One with standard heatsink	One with high performance heatsink	One with high performance heatsink	
Memory	128 GB (4x32 GB, 5600 MT/s) Notes: Runs at 4400 MT/s due to processor limitation.	128 GB (2x64 GB, 5600 MT/s) Notes: Runs at 4400 MT/s due to processor limitation.	128 GB (2x64 GB, 5600 MT/s) Notes: Runs at 4800 MT/s due to processor limitation.	
Network Controller	Broadcom BCM5719 Ethernet 1Gb 4-port BASE-T OCP3 Adapter for HPE Notes: No embedded networking			
Storage Controller	HPE MR408i-o Gen11 x8 Lanes 4GB Cache OCP SPDM Storage Controller	HPE NS204i-u Gen11 NVMe Hot Plug Boot Optimized Storage Device	HPE NS204i-u Gen11 NVMe Hot Plug Boot Optimized Storage Device	
Included Hard Drives	2x 960GB SATA SSD	None ship standard, 8 SFF supported	None ship standard, 8 SFF supported	
Optical Drive	Optional - HPE 9.5mm SATA DVD-RV	W Optical Drive, HPE Mobile USB DVD-	-RW Drive.	
Expansion Slots		d. Upgradeable to 3rd slot in HH (or re Ill PCIe Slots are in design with up to 9.		
Power Supply	2x HPE 1000W Flex Slot Titanium Hot Plug Power Supply Kit			
Fans	5x Standard Fans	7x High Performance Fans	7x High Performance Fans	
Management	HPE iLO 6	HPE iLO 6		
Rail Kit	HPE ProLiant DL3XX Gen11 Easy Install Rail 3 Kit Notes: Server does not support shelf mounted rail kits ("L" brackets).			
Security	TPM (Trusted Platform Module)			

SKU Number P7			
	74291-205	P74292-205	P74651-D65
Model Name 2.0	IPE ProLiant DL360 Gen11 4410Y .0GHz 12c 1P 32GB-R 8SFF IR408i-o 2x1.2TB HDD 2x800W PS BR Server	HPE ProLiant DL360 Gen11 4410Y 2.0GHz 12c 2P 64GB-R 8SFF MR408i-o 2x480GB SSD 2x800W RPS BR Server	HPE ProLiant DL360 Gen11 4510 2.4GHz 12c 1P 64GB-R 8SFF MR408i-o 2x960GB SSD 2x1000W RPS IN Server
Chassis H	IPE ProLiant DL360 Gen11 8SFF NC	Configure-to-order Server	
Processor 44	410Y (12 core, 2.0 GHz, 150W)	4410Y (12 core, 2.0 GHz, 150W)	4510 (12 core, 2.4 GHz, 150W)
Number of Processors	ne with standard heatsink	Two with standard heatsink	One with standard heatsink
Memory No	2 GB (1x32 GB, 4800 MT/s) lotes: Runs at 4000 MT/s due to rocessor limitation.	64 GB (2x32 GB, 4800 MT/s) Notes: Runs at 4000 MT/s due to processor limitation.	64 GB (1x64 GB, 5600 MT/s) Notes: Runs at 4400 MT/s due to processor limitation.
	Broadcom BCM5719 Ethernet 1Gb 4-port BASE-T OCP3 Adapter for HPE Notes: No embedded networking		
Storage Controller	IPE MR408i-o Gen11 x8 Lanes 4GB	Cache OCP SPDM Storage Controller	
Included Hard Drives	x 1.2TB SAS HDD	2x 480GB SATA SSD	2x 960GB SATA SSD
Optical Drive Op	Optional - HPE 9.5mm SATA DVD-RW Optical Drive, HPE Mobile USB DVD-RW Drive.		
		. Upgradeable to 3rd slot in HH (or re Il PCle Slots are in design with up to 9.!	
Dowar		2x HPE 800W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit	2x HPE 1000W Flex Slot Titanium Hot Plug Power Supply Kit
Fans 5×	x Standard Fans	7x Standard Fans	5x Standard Fans
Management H	IPE iLO 6		
Dail Kit	HPE ProLiant DL3XX Gen11 Easy Install Rail 3 Kit Notes: Server does not support shelf mounted rail kits ("L" brackets).		
Security TF	PM (Trusted Platform Module)		

SKU Number	P74653-D65	P75343-DM5	P77236-425
Model Name	HPE ProLiant DL360 Gen11 4514Y 2.0GHz 16c 1P 128GB-R 8SFF MR408i-o 2x960GB SSD NC 1000W PS IN Server	HPE ProLiant DL360 Gen11 4410Y 2.0GHz 12c 1P 64GB-R 8SFF	HPE ProLiant DL360 Gen11 4514Y 2.0GHz 16c 1P 128GB-R 8SFF NS204i-u NC BCM57416 2x1000W PS EU Server
Chassis	HPE ProLiant DL360 Gen11 8SFF NO	Configure-to-order Server	
Processor	4514Y (16 core, 2.0 GHz, 150W)	4410Y (12 core, 2.0 GHz, 150W)	4514Y (16 core, 2.0 GHz, 150W)
Number of Processors	One with high performance heatsink	One with standard heatsink	One with high performance heatsink
Memory	128 GB (2x64 GB, 5600 MT/s) Notes: Runs at 4400 MT/s due to processor limitation.	64 GB (2x32 GB, 4800 MT/s) Notes: Runs at 4000 MT/s due to processor limitation.	128 GB (4x32 GB, 5600 MT/s) Notes: Runs at 4400 MT/s due to processor limitation.
Network Controller	Broadcom BCM5719 Ethernet 1Gb 4-port BASE-T OCP3 Adapter for HPE Notes: No embedded networking	Broadcom BCM5719 Ethernet 1Gb 4-port BASE-T OCP3 Adapter for HPE Notes: No embedded networking	Broadcom BCM57416 Ethernet 10Gb 2-port BASE-T Adapter for HPE Notes: No embedded networking
Storage Controller	HPE MR408i-o Gen11 x8 Lanes 4GB Cache OCP SPDM Storage Controller	HPE MR408i-o Gen11 x8 Lanes 4GB Cache OCP SPDM Storage Controller	HPE NS204i-u Gen11 NVMe Hot Plug Boot Optimized Storage Device
Included Hard Drives	2x 960GB SATA SSD	2x 960GB SATA SSD	None ship standard, 8 SFF supported
Optical Drive	Optional - HPE 9.5mm SATA DVD-RV	N Optical Drive, HPE Mobile USB DVD-	-RW Drive.
Expansion Slots	2-slots (x16 FH, x16 HH) as standard. Upgradeable to 3rd slot in HH (or remove Slot 2 bracket to be FH at Slot 3) in a 2nd processor configuration. All PCle Slots are in design with up to 9.5" length.	2-slots (x16 FH, x16 HH) as standard. Upgradeable to 3rd slot in HH (or remove Slot 2 bracket to be FH at Slot 3) in a 2nd processor configuration. All PCle Slots are in design with up to 9.5" length.	
Power Supply	1x HPE 1000W Flex Slot Titanium Hot Plug Power Supply Kit	2x HPE 1000W Flex Slot Titanium Hot Plug Power Supply Kit	2x HPE 1000W Flex Slot Titanium Hot Plug Power Supply Kit
Fans	7x High Performance Fans	5x Standard Fans	7x High Performance Fans
Management	HPE iLO 6		
Rail Kit	HPE ProLiant DL3XX Gen11 Easy Ins Notes: Server does not support shelf		
Security	TPM (Trusted Platform Module)		

HPE ProLiant	DL360 Gen11 - Smart Choice Models		
SKU Number	P77237-425	P77247-425	
Model Name	HPE ProLiant DL360 Gen11 4514Y 2.0GHz 16c 64GB-R 8SFF MR408i-o 2x480GB SATA SSD 2x1000W PS EU Server	HPE ProLiant DL360 Gen11 4510 2.4GHz 12c 1P 64GB-R 8SFF MR408i-o 2x2.4TB HDD 2x1000W PS EU Server	
Chassis	HPE ProLiant DL360 Gen11 8SFF NC Configure-to-orde	er Server	
Processor	4514Y (16 core, 2.0 GHz, 150W)	4510 (12 core, 2.4 GHz, 150W)	
Number of Processors	One with standard heatsink		
Memory	64 GB (2x32 GB, 5600 MT/s) Notes: Runs at 4400 MT/s due to processor limitation.		
Network Controller	Broadcom BCM57416 Ethernet 10Gb 2-port BASE-T Adapter for HPE Notes: No embedded networking	Broadcom BCM5719 Ethernet 1Gb 4-port BASE-T OCP3 Adapter for HPE Notes: No embedded networking	
Storage Controller	HPE MR408i-o Gen11 x8 Lanes 4GB Cache OCP SPDM	Storage Controller	
Included Hard Drives	2x 480GB SATA SSD	2x 2.4TB SAS HDD	
Optical Drive	Optional - HPE 9.5mm SATA DVD-RW Optical Drive, HPI	E Mobile USB DVD-RW Drive.	
Power Supply	2x HPE 1000W Flex Slot Titanium Hot Plug Power Supply Kit		
Fans	5x Standard Fans		
Management	HPE iLO 6		
Rail Kit	HPE ProLiant DL3XX Gen11 Easy Install Rail 3 Kit Notes: Server does not support shelf mounted rail kits ("L" brackets).		
Security	TPM (Trusted Platform Module)		

HPE ProLiant	DL365 Gen11 - Smart Choice Models		
SKU Number	P77249-005		
Model Name	HPE ProLiant DL365 Gen11 9354 3.25GHz 32c 2P 384GB-R 8SFF NS204i-u NC BCM57414 2x1000W PS NA Server		
Chassis	HPE ProLiant DL365 Gen11 8SFF Configure-to-order Server		
Processor	9354 (32 core, 3.25 GHz, 280W)		
Number of Processors	Two with performance heatsink		
Memory	384 GB (24x16 GB, 4800 MT/s)		
Network Controller	1x Broadcom BCM57414 Ethernet 10/25Gb 2-port SFP28 OCP3 Adapter for HPE 1x Broadcom BCM5719 Ethernet 1Gb 4-port BASE-T OCP3 Adapter for HPE		
Storage Controller	HPE NS204i-u Gen11 NVMe Hot Plug Boot Optimized Storage Device		
Included Hard Drives	None ship standard, 8 SFF supported		
Optical Drive	Optional: 9.5mm SATA DVD-ROM/RW Optical Drive		
Power Supply	2x HPE 1000W Flex Slot Titanium Hot Plug Power Supply Kit		
Fans	7x Performance Fans		
Rail Kit	HPE ProLiant DL3XX Gen11 Easy Install Rail 2 Kit		
Security	TPM (Trusted Platform Module)		

HPE ProLiant	PE ProLiant DL380 Gen11 - Smart Choice Models			
SKU Number	P71674-425	P71675-425	P71679-005	
Model Name	HPE ProLiant DL380 Gen11 4510 2.4GHz 12c 1P 64GB-R 8SFF MR408i-o 2x960GB SSD 2x1000W PS EMEA Server	HPE ProLiant DL380 Gen11 4510 2.4GHz 12c 64GB-R 12LFF MR416i-p 2x8TB SATA HDD 2x1000W PS EMEA Server	HPE ProLiant DL380 Gen11 4510 12-core 1P 64GB-R MR408i-o NC BCM5719 8SFF 2x1000W RPS NA Server	
Chassis	HPE ProLiant DL380 Gen11 8SFF NC Configure-to-order Server	HPE ProLiant DL380 Gen11 12LFF NC Configure-to-order Server	HPE ProLiant DL380 Gen11 8SFF NC Configure-to-order Server	
Processor	4510 (12 core, 2.4 GHz, 150W)			
Number of Processors	One			
Memory	64 GB (2x32 GB, 5600 MT/s) Notes: Runs at 4400 MT/s due to processor limitation.			
Network Controller	Broadcom BCM5719 Ethernet 1Gb 4-port BASE-T OCP3 Adapter for HPE			
Storage Controller	HPE MR408i-o Gen11 x8 Lanes 4GB Cache OCP SPDM Storage Controller	HPE MR416i-p Gen11 x16 Lanes 8GB Cache PCI SPDM Plug-in Storage Controller	HPE MR408i-o Gen11 x8 Lanes 4GB Cache OCP SPDM Storage Controller	
Included Hard Drives	2x 960GB SATA SSD	2x 8TB SATA HDD	2x 480GB SATA SSD	
Optical Drive	Optional DVD-ROM Optional via Univ	versal Media Bay External support only		
Expansion Slots	3-slots (x8, x16, x8) as standard; upg	radeable to 8-slots in a 2 processor co	nfiguration	
Power Supply	2x HPE 1000W Flex Slot Titanium Hot Plug Power Supply Kit			
Fans	4x Standard Fans	4x Standard Fan	4x Standard Fans	
Management	HPE iLO 6			
Rail Kit	HPE ProLiant DL3XX Gen11 Easy Install Rail 3 Kit			
Security	TPM (Trusted Platform Module)			

HPE ProLiant	HPE ProLiant DL380 Gen11 - Smart Choice Models			
SKU Number	P71680-005	P71681-005	P72981-005	
Model Name	HPE ProLiant DL380 Gen11 4509Y 8-core 1P 64GB-R MR408i-o NC BCM5719 8SFF 2x1000W RPS NA Server	HPE ProLiant DL380 Gen11 6526Y 16-core 1P 128GB-R NS204i-u NC BCM5719 8SFF 2x1000W RPS NA Server	HPE ProLiant DL380 Gen11 4510 2.4GHz 12c 1P 64GB-R 12LFF MR416i-o 2x8TB HDD 2x1000W PS NA Server	
Chassis	HPE ProLiant DL380 Gen11 8SFF NC Configure-to-order Server	HPE ProLiant DL380 Gen11 8SFF NC Configure-to-order Server	HPE ProLiant DL380 Gen11 12LFF NC Configure-to-order Server	
Processor	4509Y (8 core, 2.6 GHz, 125W)	6526Y (16 core, 2.8 GHz, 195W)	4510 (12 core, 2.4 GHz, 150W)	
Number of Processors	One	One with high performance heatsink	One	
Memory	64 GB (2x32 GB, 5600 MT/s) Notes: Runs at 4400 MT/s due to processor limitation.	128 GB (4x32 GB, 5600 MT/s) Notes: Runs at 5200 MT/s due to processor limitation.	64 GB (2x32 GB, 5600 MT/s) Notes: Runs at 4400 MT/s due to processor limitation.	
Network Controller	Broadcom BCM5719 Ethernet 1Gb 4-port BASE-T OCP3 Adapter for HPE			
Storage Controller	HPE MR408i-o Gen11 x8 Lanes 4GB Cache OCP SPDM Storage Controller	HPE NS204i-u Gen11 NVMe Hot Plug Boot Optimized Storage Device	HPE MR416i-o Gen11 x16 Lanes 8GB Cache OCP SPDM Storage Controller	
Included Hard Drives	2x 480GB SATA SSD	None ship standard, 8 SFF supported	2x 8TB SATA HDD	
Optical Drive	Optional DVD-ROM Optional via Univ	rersal Media Bay External support only		
Expansion Slots	3-slots (x8, x16, x8) as standard; upgradeable to 8-slots in a 2 processor configuration			
Power Supply	2x HPE 1000W Flex Slot Titanium Hot Plug Power Supply Kit			
Fans	4x Standard Fans	6x High Performance Fan	4x Standard Fans	
Management	HPE iLO 6			
Rail Kit	HPE ProLiant DL3XX Gen11 Easy Install Rail 3 Kit			
Security	TPM (Trusted Platform Module)			

HPE ProLiant	HPE ProLiant DL380 Gen11 - Smart Choice Models			
SKU Number	P72982-005	P72983-005	P72984-005	
Model Name	HPE ProLiant DL380 Gen11 4514Y 2.0GHz 16c 1P 128GB-R 8SFF MR408i-o 2x480GB SSD 2x1000W PS NA Server	HPE ProLiant DL380 Gen11 4510 2.4GHz 12c 1P 64GB-R 8SFF MR408i-o 2x2.4TB HDD 2x1000W PS NA Server	HPE ProLiant DL380 Gen11 4514Y 2.0GHz 16c 1P 128GB-R 8SFF MR408i-o 2x2.4TB HDD 2x1000W PS NA Server	
Chassis	HPE ProLiant DL380 Gen11 8SFF No	C Configure-to-order Server		
Processor	4514Y (16 core, 2.0 GHz, 150W)	4510 (12 core, 2.4 GHz, 150W)	4514Y (16 core, 2.0 GHz, 150W)	
Number of Processors	One			
Memory	128 GB (4x32 GB, 5600 MT/s) Notes: Runs at 4400 MT/s due to processor limitation.	64 GB (2x32 GB, 5600 MT/s) Notes: Runs at 4400 MT/s due to processor limitation.	128 GB (4x32 GB, 5600 MT/s) Notes: Runs at 4400 MT/s due to processor limitation.	
Network Controller	Broadcom BCM5719 Ethernet 1Gb 4-port BASE-T OCP3 Adapter for HPE			
Storage Controller	HPE MR408i-o Gen11 x8 Lanes 4GB Cache OCP SPDM Storage Controller			
Included Hard Drives	2x 480GB SATA SSD	2x 2.4TB SAS HDD	2x 2.4TB SAS HDD	
Optical Drive	Optional DVD-ROM Optional via Univ	ersal Media Bay External support only		
Expansion Slots	3-slots (x8, x16, x8) as standard; upgradeable to 8-slots in a 2 processor configuration			
Power Supply	2x HPE 1000W Flex Slot Titanium Hot Plug Power Supply Kit			
Fans	4x Standard Fans			
Management	HPE iLO 6			
Rail Kit	HPE ProLiant DL3XX Gen11 Easy Install Rail 3 Kit			
Security	TPM (Trusted Platform Module)			

HPE ProLiant	DL380 Gen11 - Smart Choice Models	s		
SKU Number	P74293-205	P74294-205	P74295-205	
Model Name	HPE ProLiant DL380 Gen11 4410Y 2.0GHz 12c 1P 32GB-DR 8SFF MR408i-o 2x1.2TB HDD 2x800W RPS BR Server	HPE ProLiant DL380 Gen11 4416+ 2.0GHz 20c 1P 32GB-DR 8SFF MR408i-o 2x480GB SSD 2x800W RPS BR Server	HPE ProLiant DL380 Gen11 4410Y 2.0GHz 12c 1P 32GB-DR 12LFF MR416i-o 2x4TB HDD 2x800W RPS BR Server	
Chassis	HPE ProLiant DL380 Gen11 8SFF NC Configure-to-order Server	HPE ProLiant DL380 Gen11 8SFF NC Configure-to-order Server	HPE ProLiant DL380 Gen11 12LFF NC Configure-to-order Server	
Processor	4410Y (12 core, 2.0 GHz, 150W)	4416+ (20 core, 2.0 GHz, 165W)	4410Y (12 core, 2.0 GHz, 150W)	
Number of Processors	One	One with high performance heatsink	One	
Memory	32 GB (1x32 GB, 4800 MT/s) Notes: Runs at 4000 MT/s due to processor limitation.			
Network Controller	Broadcom BCM5719 Ethernet 1Gb 4-port BASE-T OCP3 Adapter for HPE			
Storage Controller	HPE MR408i-o Gen11 x8 Lanes 4GB Cache OCP SPDM Storage Controller	HPE MR408i-o Gen11 x8 Lanes 4GB Cache OCP SPDM Storage Controller	HPE MR416i-o Gen11 x16 Lanes 8GB Cache OCP SPDM Storage Controller	
Included Hard Drives	2x 1.2TB SAS HDD	2x 480GB SATA SSD	2x 4TB SATA HDD	
Optical Drive	Optional DVD-ROM Optional via Univ	ersal Media Bay External support only		
Expansion Slots	3-slots (x8, x16, x8) as standard; upg	3-slots (x8, x16, x8) as standard; upgradeable to 8-slots in a 2 processor configuration		
Power Supply	2x HPE 800W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit			
Fans	4x Standard Fan			
Management	HPE iLO 6			
Rail Kit	HPE ProLiant DL3XX Gen11 Easy Install Rail 3 Kit			
Security	TPM (Trusted Platform Module)			

HPE ProLiant	HPE ProLiant DL380 Gen11 - Smart Choice Models			
SKU Number	P74648-D65	P74649-D65	P75344-DM5	
Model Name	HPE ProLiant DL380 Gen11 4510 2.4GHz 12c 1P 64GB-R 8SFF MR416i-o 2x960GB SSD 2x1000W RPS IN Server	HPE ProLiant DL380 Gen11 4514Y 2.0GHz 16c 1P 64GB-R 8SFF MR416i-o 2x960GB SSD 2x1000W RPS IN Server	HPE ProLiant DL380 Gen11 4410Y 2.0GHz 12c 1P 32GB-R 12LFF MR416i-o 2x4TB HDD 2x1000W RPS LA Server	
Chassis	HPE ProLiant DL380 Gen11 8SFF NC Configure-to-order Server	HPE ProLiant DL380 Gen11 8SFF NC Configure-to-order Server	HPE ProLiant DL380 Gen11 12LFF NC Configure-to-order Server	
Processor	4510 (12 core, 2.4 GHz, 150W)	4514Y (16 core, 2.0 GHz, 150W)	4410Y (12 core, 2.0 GHz, 150W)	
Number of Processors	One			
Memory	64 GB (1x64 GB, 5600 MT/s) Notes: Runs at 4400 MT/s due to processor limitation.	64 GB (1x64 GB, 5600 MT/s) Notes: Runs at 4400 MT/s due to processor limitation.	32 GB (1x32 GB, 4800 MT/s) Notes: Runs at 4000 MT/s due to processor limitation.	
Network Controller	Broadcom BCM5719 Ethernet 1Gb 4-port BASE-T OCP3 Adapter for HPE			
Storage Controller	HPE MR416i-o Gen11 x16 Lanes 8G	B Cache OCP SPDM Storage Controlle	r	
Included Hard Drives	2x 960GB SATA SSD	2x 960GB SATA SSD	2x 4TB SATA HDD	
Optical Drive	Optional DVD-ROM Optional via Univ	versal Media Bay External support only		
Expansion Slots	3-slots (x8, x16, x8) as standard; upg	radeable to 8-slots in a 2 processor co	nfiguration	
Power Supply	2x HPE 1000W Flex Slot Titanium Hot Plug Power Supply Kit			
Fans	4x Standard Fans			
Management	HPE iLO 6			
Rail Kit	HPE ProLiant DL3XX Gen11 Easy Install Rail 3 Kit			
Security	TPM (Trusted Platform Module)			

HPE ProLiant	HPE ProLiant DL380 Gen11 - Smart Choice Models			
SKU Number	P75345-DM5	P77235-425	P77241-425	
Model Name	HPE ProLiant DL380 Gen11 5418Y 2.0GHz 24c 1P 64GB-R 8SFF NS204i-u 2x1000W RPS LA Server	HPE ProLiant DL380 Gen11 4514Y 2.0GHz 16c 1P 64GB-R 8SFF MR416i-o 2x2.4TB HDD 2x1000W PS EU Server	HPE ProLiant DL380 Gen11 6526Y 2.8GHz 16c 1P 128GB-R 8SFF NS204i-u NC BCM57416 2x1000W PS EU Server	
Chassis	HPE ProLiant DL380 Gen11 8SFF No	C Configure-to-order Server		
Processor	5418Y (24 core, 2.0 GHz, 185W)	4514Y (16 core, 2.0 GHz, 150W)	6526Y (16 core, 2.80 GHz, 195W)	
Number of Processors	One with high performance heatsink	One	One with high performance heatsink	
Memory	64 GB (2x32 GB, 4800 MT/s) Notes: Runs at 4400 MT/s due to processor limitation.	64 GB (2x32 GB, 5600 MT/s) Notes: Runs at 4400 MT/s due to processor limitation.	128 GB (4x32 GB, 5600 MT/s) Notes: Runs at 5200 MT/s due to processor limitation.	
Network Controller	Broadcom BCM57416 Ethernet 10Gb	2-port BASE-T Adapter for HPE		
Storage Controller	HPE NS204i-u Gen11 NVMe Hot Plug Boot Optimized Storage Device	HPE MR416i-o Gen11 x16 Lanes 8GB Cache OCP SPDM Storage Controller	HPE NS204i-u Gen11 NVMe Hot Plug Boot Optimized Storage Device	
Included Hard Drives	None ship standard, 8 SFF supported	2x 2.4TB SAS HDD	None ship standard, 8 SFF supported	
Optical Drive	Optional DVD-ROM Optional via Univ	ersal Media Bay External support only		
Expansion Slots	3-slots (x8, x16, x8) as standard; upg	radeable to 8-slots in a 2 processor co	nfiguration	
Power Supply	2x HPE 1000W Flex Slot Titanium Hot Plug Power Supply Kit			
Fans	6x High Performance Fan	4x Standard Fans	6x High Performance Fan	
Management	HPE iLO 6			
Rail Kit	HPE ProLiant DL3XX Gen11 Easy Install Rail 3 Kit			
Security	TPM (Trusted Platform Module)			

HPE ProLiant	DL380 Gen11 - Smart Choice Models	
SKU Number	P77242-425	
Model Name	HPE ProLiant DL380 Gen11 4514Y 2.0GHz 16c 1P 128GB-R 8SFF NS204i-u NC BCM57416 2x1000W PS EU Server	
Chassis	HPE ProLiant DL380 Gen11 8SFF NC Configure-to-order Server	
Processor	4514Y (16 core, 2.0 GHz, 150W)	
Number of Processors	One	
Memory	128 GB (4x32 GB, 5600 MT/s) Notes: Runs at 4400 MT/s due to processor limitation.	
Network Controller	Broadcom BCM57416 Ethernet 10Gb 2-port BASE-T Adapter for HPE	
Storage Controller	HPE NS204i-u Gen11 NVMe Hot Plug Boot Optimized Storage Device	
Included Hard Drives	None ship standard, 8 SFF supported	
Optical Drive	Optional DVD-ROM Optional via Universal Media Bay External support only	
Expansion Slots	3-slots (x8, x16, x8) as standard; upgradeable to 8-slots in a 2 processor configuration	
Power Supply	2x HPE 1000W Flex Slot Titanium Hot Plug Power Supply Kit	
Fans	6x High Performance Fan	
Management	HPE iLO 6	
Rail Kit	HPE ProLiant DL3XX Gen11 Easy Install Rail 3 Kit	
Security	TPM (Trusted Platform Module)	

HPE ProLiant	DL385 Gen11 - Smart Choice Models	1	
SKU Number	P75340-D65	P75346-DM5	P77244-425
Model Name	HPE ProLiant DL385 Gen11 9124 3.0GHz 16c 1P 64GB-R 8SFF MR408i-o 2x480GB SATA 2x800W RPS IN Server	HPE ProLiant DL385 Gen11 9124 3.0GHz 16c 1P 64GB-R 8SFF MR408i-o 2x960GB SSD 2x800W RPS LA Server	HPE ProLiant DL385 Gen11 9124 3.0GHz 16c 1P 64GB-R 8LFF NS204i-u NC BCM57416 2x1000W PS EU Server
Chassis	HPE ProLiant DL385 Gen11 8SFF Configure-to-order Server	HPE ProLiant DL385 Gen11 8SFF Configure-to-order Server	HPE ProLiant DL385 Gen11 8LFF Configure-to-order Server
Processor	9124 (16 core, 3.0 GHz, 200W)		
Number of Processors	One with standard heatsink		
Memory	64 GB (2x32 GB, 4800 MT/s)		
Network Controller	Broadcom BCM57416 Ethernet 10Gb 2-port BASE-T OCP3 Adapter for HPE		
Storage Controller	HPE MR408i-o Gen11 x8 Lanes 4GB Cache OCP SPDM Storage Controller	HPE MR408i-o Gen11 x8 Lanes 4GB Cache OCP SPDM Storage Controller	HPE NS204i-u Gen11 NVMe Hot Plug Boot Optimized Storage Device
Included Hard Drives	2x 480GB SATA SSD	2x 960GB SATA SSD	None ship standard, 8 LFF supported
Power Supply	2x HPE 800W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit	2x HPE 800W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit	2x HPE 1000W Flex Slot Titanium Hot Plug Power Supply Kit
Fans	6x Standard Fans	6x Standard Fans	6x Performance Fans
Rail Kit	HPE ProLiant DL3XX Gen11 Easy Install Rail 2 Kit		
Security	TPM (Trusted Platform Module)		

HPE ProLiant	DL385 Gen11 - Smart Choice Models		
SKU Number	P77245-425	P77251-005	
Model Name	HPE ProLiant DL385 Gen11 9124 3.0GHz 16c 64GB-R 8SFF MR408i-o 2x480GB SATA SSD 2x1000W PS EU Server	HPE ProLiant DL385 Gen11 9354 3.25GHz 32c 2P 384GB-R 8SFF NS204i-u NC BCM57414 2x1000W PS NA Server	
Chassis	HPE ProLiant DL385 Gen11 8SFF Configure-to-order Se	erver	
Processor	9124 (16 core, 3.0 GHz, 200W)	9354 (32 core, 3.25 GHz, 280W)	
Number of Processors	One with standard heatsink	Two with performance heatsink	
Memory	64 GB (2x32 GB, 4800 MT/s)	384 GB (24x16 GB, 4800 MT/s)	
Network Controller	Broadcom BCM57416 Ethernet 10Gb 2-port BASE-T OCP3 Adapter for HPE	1x Broadcom BCM57414 Ethernet 10/25Gb 2-port SFP28 OCP3 Adapter for HPE 1x Broadcom BCM5719 Ethernet 1Gb 4-port BASE-T OCP3 Adapter for HPE	
Storage Controller	HPE MR408i-o Gen11 x8 Lanes 4GB Cache OCP SPDM Storage Controller	HPE NS204i-u Gen11 NVMe Hot Plug Boot Optimized Storage Device	
Included Hard Drives	2x 480GB SATA SSD	None ship standard, 8 SFF supported	
Power Supply	2x HPE 1000W Flex Slot Titanium Hot Plug Power Supply Kit		
Fans	6x Standard Fans 6x Performance Fans		
Rail Kit	HPE ProLiant DL3XX Gen11 Easy Install Rail 2 Kit		
Security	TPM (Trusted Platform Module)		

HPE ProLiant	MicroServer Gen11 - Smart Choice M	1odels	
SKU Number	P74439-005 P74439-425	P74440-005	P74441-DM5
	P74439-005: HPE ProLiant MicroServer Gen11 G7400 2c 16GB-U 4LFF-NHP 1TB HDD 180W Ext PS NA Cmp Module Server	2434 4c 32GB-U 4LFF-NHP 4TB HDD 180W External PS NA Cmp	HPE ProLiant MicroServer Gen11 E- 2434 4c 16GB-U 4LFF-NHP 2x1TB HDD 180W External PS LA Cmp Mod Svr
Model Name	P74439-425: HPE ProLiant MicroServer Gen11 G7400 2c 16GB-U 4LFF-NHP 1TB HDD 180W Ext PS EMEA Cmp Module Server		
Processor	Intel® Pentium® Gold G7400	Intel® Xeon® E-2434	Intel® Xeon® E-2434
Number of Processors	One		
Memory	16 GB (1x 16 GB, 4400 MT/s)	32 GB (1x 32 GB, 4400 MT/s)	16 GB (1x 16 GB, 4400 MT/s)
Network Controller	4x1Gbe embedded Notes: Embedded 1Gb 4-port		
Storage Controller	Embedded Intel VROC SATA SW RAI	D	
Included	P74439-005: 1TB HDD	4 TB HDD	2x1TB HDD
Hard Drives	P74439-425: 1 TB HDD		
Optical Drive Bay	Optional ODD Bay Kit, none included		
Optical Drive	Optional ODD Bay Kit, none included		
Expansion Slots	(1) PCIe 5.0 slots, (1) PCIe 4.0 slots		
Power Supply	1x 180W External Power Adapter, Non-Redundant Power Supply		
Management	HPE iLO 6		
Security	TPM (Trusted Platform Module)		

HPE ProLiant	MicroServer Gen11 - Smart Choice Models		
SKU Number	P75207-425	P75215-D65	
Model Name	HPE ProLiant MicroServer Gen11 E-2434 4c 32GB-U 4LFF-NHP 2x4TB HDD 180W External PS EMEA Cmp Mod Svr	HPE ProLiant MicroServer Gen11 E-2434 4c 32GB-U 4LFF-NHP 1TB HDD 180W External PS IN Cmp Module Svr	
Processor	Intel® Xeon® E-2434		
Number of Processors	One		
Memory	32 GB (1x 32 GB, 4400 MT/s)		
Network Controller	4x1Gbe embedded Notes: Embedded 1Gb 4-port		
Storage Controller	Embedded Intel VROC SATA SW RAID		
Included Hard Drives	2x4TB HDD 1 TB HDD		
Optical Drive Bay	Optional ODD Bay Kit, none included		
Optical Drive	Optional ODD Bay Kit, none included		
Expansion Slots	(1) PCIe 5.0 slots, (1) PCIe 4.0 slots		
Power Supply	1x 180W External Power Adapter, Non-Redundant Power Supply		
Management	HPE iLO 6		
Security	TPM (Trusted Platform Module)		

HPE ProLiant	ML30 Gen11 - Smart Choice Models		
SKU Number	P71385-425	P71387-425	P71388-035
Model Name	HPE ProLiant ML30 Gen11 E-2414 2.6GHz 4c 1P 32GB-DR 4LFF-NHP VROC 2x1TB SATA HDD 350W PS EU Server	HPE ProLiant ML30 Gen11 E-2434 3.4GHz 4c 1P 32GB-DR 8SFF VROC 2x480GB SATA SSD 800W RPS EU Server	HPE ProLiant ML30 Gen11 E-2434 3.4GHz 4c 1P 32GB-DR 8SFF VROC 2x480GB SATA SSD 800W RPS UK/IE Server
Chassis	HPE ProLiant ML30 Gen11 4LFF Non-hot Plug Configure-to-order Server	HPE ProLiant ML30 Gen11 8SFF Hot Plug Configure-to-order Server	HPE ProLiant ML30 Gen11 8SFF Hot Plug Configure-to-order Server
Processor	E-2414 (4 core, 2.6 GHz, 55W)	E-2434 (4 core, 3.4 GHz, 55W)	E-2434 (4 core, 3.4 GHz, 55W)
Number of Processors	One		
Memory	32 GB (1x32 GB UDIMM, 4800 MT/s	5)	
Network Controller	Embedded 1Gb 4-Port Ethernet Adapter		
Storage Controller	Embedded Intel VROC SATA software RAID Notes: - SATA Only - NHP models do not support internal Smart Array controllers		
Included Hard Drives	2x 1TB SATA HDD	2x 480GB SATA SSD	2x 480GB SATA SSD
Optical Drive Bay	Optional Slimline ODD Bay Kit (P65102-B21) consumes 1 media bay Notes: Up to 1 optical drive bay		
Optical Drive	None ship standard; ODD Optional		
Power Supply	1x HPE ML30 Gen10 Plus 350W FIO Power Supply Kit	1x HPE 800W Flex Slot Titanium Hot Plug Low Halogen Power Supply Kit Notes: - Add a second 800W Flex Slot Power Supply to get 1+1 power redundancy feature. - 800W power supply only in	1x HPE 800W Flex Slot Titanium Hot Plug Low Halogen Power Supply Kit Notes: - Add a second 800W Flex Slot Power Supply to get 1+1 power redundancy feature. - 800W power supply only in
		EMEA for EU Lot 9 Compliance.	EMEA for EU Lot 9 Compliance.
Fans	1x Non-hot plug non-redundant system fan		
Security	TPM (Trusted Platform Module)		

HPE ProLiant ML30 Gen11 - Smart Choice Models				
SKU Number	P71389-035	P72995-005	P72996-005	
Model Name	HPE ProLiant ML30 Gen11 E-2414 2.6GHz 4c 1P 32GB-DR 4LFF-NHP VROC 2x1TB SATA HDD 350W PS UK Server	HPE ProLiant ML30 Gen11 E-2434 3.4GHz 4-core 1P 32GB-R 8SFF 2x960GB SSD 2x500W RPS NA Server	HPE ProLiant ML30 Gen11 E-2434 3.4GHz 4-core 1P 32GB-R 4LFF 2x2TB HDD 500W RPS NA Server	
Chassis	HPE ProLiant ML30 Gen11 4LFF Non-hot Plug Configure-to-order Server	HPE ProLiant ML30 Gen11 8SFF Hot Plug Configure-to-order Server	HPE ProLiant ML30 Gen11 4LFF Hot Plug Configure-to-order Server	
Processor	E-2414 (4 core, 2.6 GHz, 55W)	E-2434 (4 core, 3.4 GHz, 55W)	E-2434 (4 core, 3.4 GHz, 55W)	
Number of Processors	One			
Memory	32 GB (1x32 GB UDIMM, 4800 MT/s)			
Network Controller	Embedded 1Gb 4-Port Ethernet Adapter			
Storage Controller	Embedded Intel VROC SATA software RAID Notes: - SATA Only - NHP models do not support internal Smart Array controllers	HPE MR216i-p Gen11 x16 Lanes without Cache PCI SPDM Plug-in Storage Controller	HPE MR216i-p Gen11 x16 Lanes without Cache PCI SPDM Plug-in Storage Controller	
Included Hard Drives	2x 1TB SATA HDD	2x 960GB SATA SSD	2x 2TB SATA HDD	
Optical Drive Bay	Optional Slimline ODD Bay Kit (P65102-B21) consumes 1 media bay Notes: Up to 1 optical drive bay			
Optical Drive	None ship standard; ODD Optional			
Power Supply	1x HPE ML30 Gen10 Plus 350W FIO Power Supply Kit	2x HPE 500W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit	1x HPE 500W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit	
Fans	1x Non-hot plug non-redundant system fan			
Security	TPM (Trusted Platform Module)			

HPE ProLiant	HPE ProLiant ML30 Gen11 - Smart Choice Models			
SKU Number	P75337-D65	P75338-D65	P77232-425	
Model Name	HPE ProLiant ML30 Gen11 E-2434 3.4GHz 4c 1P 32GB-DR 8SFF 480GB SSD 2x500W RPS IN Server	HPE ProLiant ML30 Gen11 E-2414 2.6GHz 4c 1P 32GB-DR 4LFF 1TB HDD 350W PS IN Server	HPE ProLiant ML30 Gen11 E-2434 3.4GHz 4c 1P 32GB-U 4LFF 2x960GB SSD 800W RPS EU Server	
Chassis	HPE ProLiant ML30 Gen11 8SFF Hot Plug Configure-to-order Server	HPE ProLiant ML30 Gen11 4LFF Non-hot Plug Configure-to-order Server	HPE ProLiant ML30 Gen11 4LFF Hot Plug Configure-to-order Server	
Processor	E-2434 (4 core, 3.4 GHz, 55W)	E-2414 (4 core, 2.6 GHz, 55W)		
Number of Processors	One			
Memory	32 GB (1x32 GB UDIMM, 4800 MT/s)			
Network Controller	Embedded 1Gb 4-Port Ethernet Adapter			
Storage Controller	Embedded Intel VROC SATA software RAID			
Included Hard Drives	480GB SATA SSD	1TB SATA HDD	2x 960GB SATA SSD	
Optical Drive Bay	Optional Slimline ODD Bay Kit (P65102-B21) consumes 1 media bay Notes: Up to 1 optical drive bay			
Optical Drive	None ship standard; ODD Optional	None ship standard; ODD Optional	None ship standard. Optional: SATA 9.5mm DVD-RW/DVD-ROM Optical Drive	
Power Supply	2x HPE 500W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit	1x HPE ML30 Gen10 Plus 350W FIO Power Supply Kit	1x HPE 800W Flex Slot Titanium Hot Plug Low Halogen Power Supply Kit	
Fans	1x Non-hot plug non-redundant system fan			
Security	TPM (Trusted Platform Module)			

HPE ProLiant ML110 Gen11 - Smart Choice Models				
SKU Number	P69303-005	P71647-425	P71648-035	
Model Name	HPE ProLiant ML110 Gen11 4410Y 12-core 1P 32GB-R MR408i-o 8SFF 2x480GB SSD 2x800W RPS AMS Server	HPE ProLiant ML110 Gen11 3508U 2.1GHz 8-core 1P 32GB-R VROC 4LFF 2x2TB HDD 2x1000W RPS EU Server	HPE ProLiant ML110 Gen11 3508U 2.1GHz 8-core 1P 32GB-R VROC 4LFF 2x2TB HDD 2x1000W RPS UK/IE Server	
Chassis	HPE ProLiant ML110 Gen11 SFF Configure-to-order Server	HPE ProLiant ML110 Gen11 LFF Configure-to-order Server	HPE ProLiant ML110 Gen11 LFF Configure-to-order Server	
Processor	4410Y (12 core, 2.0 GHz, 150W)	3508U (8 core, 2.1 GHz, 125W)	3508U (8 core, 2.1 GHz, 125W)	
Number of Processors	One			
Memory	32 GB (1x32 GB, 4800 MT/s) Notes: Runs at 4000 MT/s due to processor limitation.	32 GB (1x32 GB, 5600 MT/s) Notes: Runs at 4400 MT/s due to processor limitation.	32 GB (1x32 GB, 5600 MT/s) Notes: Runs at 4400 MT/s due to processor limitation.	
Network Controller	Embedded 2-Port 1GbE BCM5720 networking ports			
Storage Controller	HPE MR408i-o Gen11 x8 Lanes 4GB Cache OCP SPDM Storage Controller	Embedded 8 SATA ports controller with Intel® VROC Software RAID. Notes: Embedded controller can only support SATA drive, additional storage controller is required to support SAS drive.	Embedded 8 SATA ports controller with Intel® VROC Software RAID. Notes: Embedded controller can only support SATA drive, additional storage controller is required to support SAS drive.	
Included Hard Drives	2x 480GB SATA SSD	2x 2TB SATA HDD	2x 2TB SATA HDD	
Optical Drive	Optional. None ship standard.			
Expansion Slots	PCIe Gen5: 2 slots (x16), upgradable	to 4 slots (x16); OCP3 with PCle Gen5.	: 1 slot (x16)	
Power Supply	2x HPE 800W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit	2x HPE 1000W Flex Slot Titanium Hot Plug Power Supply Kit	2x HPE 1000W Flex Slot Titanium Hot Plug Power Supply Kit	
Fans	Default with 2 standard fans, non-hot-plug. Optional Redundant Fan Kit (P49984-B21) provides advanced cooling in heavier configurations and redundancy functionality. Notes: Configurations that require fan kits are provided in later sections.			
Management	HPE iLO Standard with Intelligent Provisioning (embedded), HPE OneView Standard (requires download); HPE iLO Advanced and HPE OneView Advanced (require licenses)			
Security	TPM (Trusted Platform Module)			

HPE ProLiant	HPE ProLiant ML110 Gen11 - Smart Choice Models			
SKU Number	P71659-425	P71670-035	P71683-005	
Model Name	HPE ProLiant ML110 Gen11 4510 12-core 1P 64GB-R MR408i-o 8SFF 2x480GB SSD 2x1000W RPS EU Server	HPE ProLiant ML110 Gen11 4510 12-core 1P 64GB-R MR408i-o 8SFF 2x480GB SSD 2x1000W RPS UK/IE Server	HPE ProLiant ML110 Gen11 3508U 2.1GHz 8-core 1P 32GB-R MR408i- o 4LFF 2x2TB HDD 2x500W RPS AMS Server	
Chassis	HPE ProLiant ML110 Gen11 SFF Configure-to-order Server	HPE ProLiant ML110 Gen11 SFF Configure-to-order Server	HPE ProLiant ML110 Gen11 LFF Configure-to-order Server	
Processor	4510 (12 core, 2.4 GHz, 150W)	4510 (12 core, 2.4 GHz, 150W)	3508U (8 core, 2.1 GHz, 125W)	
Number of Processors	One			
Memory	64 GB (2x32 GB, 5600 MT/s) Notes: Runs at 4400 MT/s due to processor limitation.	64 GB (2x32 GB, 5600 MT/s) Notes: Runs at 4400 MT/s due to processor limitation.	32 GB (1x32 GB, 5600 MT/s) Notes: Runs at 4400 MT/s due to processor limitation.	
Network Controller	Embedded 2-Port 1GbE BCM5720 networking ports			
Storage Controller	HPE MR408i-o Gen11 x8 Lanes 4GB	Cache OCP SPDM Storage Controller		
Included Hard Drives	2x 480GB SATA SSD	2x 480GB SATA SSD	2x 2TB SATA HDD	
Optical Drive	Optional. None ship standard.			
Expansion Slots	PCIe Gen5: 2 slots (x16), upgradable to 4 slots (x16); OCP3 with PCIe Gen5: 1 slot (x16)			
Power Supply	2x HPE 1000W Flex Slot Titanium Hot Plug Power Supply Kit	2x HPE 1000W Flex Slot Titanium Hot Plug Power Supply Kit	2x HPE 500W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit	
Fans	Default with 2 standard fans, non-hot-plug. Optional Redundant Fan Kit (P49984-B21) provides advanced cooling in heavier configurations and redundancy functionality. Notes: Configurations that require fan kits are provided in later sections.			
Management	HPE iLO Standard with Intelligent Provisioning (embedded), HPE OneView Standard (requires download); HPE iLO Advanced and HPE OneView Advanced (require licenses)			
Security	TPM (Trusted Platform Module)			

HPE ProLiant	ML110 Gen11 - Smart Choice Models	S	
SKU Number	P71687-005	P75329-005	P75330-D65
Model Name	HPE ProLiant ML110 Gen11 4514Y 2.0GHz 16-core 1P 64GB-R MR408i-o 8SFF 2x960GB 2x800W RPS AMS Server	HPE ProLiant ML110 Gen11 4510 2.4GHz 12c 1P 32GB-R 4LFF VROC 4TB HDD 2x500W RPS NA Server	HPE ProLiant ML110 Gen11 3508U 2.1GHz 8c 1P 32GB-R 4LFF VROC 2TB HDD 1x500W RPS IN Server
Chassis	HPE ProLiant ML110 Gen11 SFF Configure-to-order Server	HPE ProLiant ML110 Gen11 LFF Configure-to-order Server	HPE ProLiant ML110 Gen11 LFF Configure-to-order Server
Processor	4514Y (16 core, 2.0 GHz, 150W)	4510 (12 core, 2.4 GHz, 150W)	3508U (8 core, 2.1 GHz, 125W)
Number of Processors	One		
Memory	64 GB (2x32 GB, 5600 MT/s) Notes: Runs at 4400 MT/s due to processor limitation.	32 GB (1x32 GB, 5600 MT/s) Notes: Runs at 4400 MT/s due to processor limitation.	32 GB (1x32 GB, 5600 MT/s) Notes: Runs at 4400 MT/s due to processor limitation.
Network Controller	Embedded 2-Port 1GbE BCM5720 ne	etworking ports	
Storage Controller	HPE MR408i-o Gen11 x8 Lanes 4GB Cache OCP SPDM Storage Controller	Embedded 8 SATA ports controller with Intel® VROC Software RAID. Notes: Embedded controller can only support SATA drive, additional storage controller is required to support SAS drive.	Embedded 8 SATA ports controller with Intel® VROC Software RAID. Notes: Embedded controller can only support SATA drive, additional storage controller is required to support SAS drive.
Included Hard Drives	2x 960GB SATA SSD	4TB SATA HDD	2TB SATA HDD
Optical Drive	Optional. None ship standard.		
Expansion Slots	PCle Gen5: 2 slots (x16), upgradable to 4 slots (x16); OCP3 with PCle Gen5: 1 slot (x16)		
Power Supply	2x HPE 800W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit	2x HPE 500W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit	1x HPE 500W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit Notes: Additional HPE 500W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit (865408-B21) provides 1+1 power redundancy feature.
Fans	Default with 2 standard fans, non-hot-plug. Optional Redundant Fan Kit (P49984-B21) provides advanced cooling in heavier configurations and redundancy functionality. Notes: Configurations that require fan kits are provided in later sections.		
Management	HPE iLO Standard with Intelligent Provisioning (embedded), HPE OneView Standard (requires download); HPE iLO Advanced and HPE OneView Advanced (require licenses)		
Security	TPM (Trusted Platform Module)		

HPE ProLiant	ML110 Gen11 - Smart Choice Models
SKU Number	P77234-425
Model Name	HPE ProLiant ML110 Gen11 4510 2.4GHz 12c 1P 32GB-R 4LFF 2x4TB HDD 2x1000W PS EU Server
Chassis	HPE ProLiant ML110 Gen11 LFF Configure-to-order Server
Processor	4510 (12 core, 2.4 GHz, 150W)
Number of Processors	One
Memory	32 GB (1x32 GB, 5600 MT/s) Notes: Runs at 4400 MT/s due to processor limitation.
Network Controller	Embedded 2-Port 1GbE BCM5720 networking ports
Storage Controller	Embedded Intel VROC SATA/NVMe Notes: Embedded controller can only support SATA drive, additional storage controller is required to support SAS drive.
Included Hard Drives	2x 4TB SATA HDD
Optical Drive	Optional DVD-ROM or DVD-RW. Optional via ODD cable Kit. Optional Half-Height RDX, up to 1. Refer to the QuickSpecs for more detail.
Expansion Slots	PCIe Gen5: 2 slots (x16), upgradable to 4 slots (x16); OCP3 with PCIe Gen5: 1 slot (x16)
Power Supply	2x HPE 1000W Flex Slot Titanium Hot Plug Power Supply Kit
Fans	Default with 2 standard fans, non-hot-plug. Optional Redundant Fan Kit (P49984-B21) provides advanced cooling in heavier configurations and redundancy functionality. Notes: Configurations that require fan kits are provided in later sections.
Management	HPE iLO Standard with Intelligent Provisioning (embedded), HPE OneView Standard (requires download); HPE iLO Advanced and HPE OneView Advanced (require licenses)
Security	TPM (Trusted Platform Module)

HPE ProLiant	ML350 Gen11 - Smart Choice Models	s	
SKU Number	P69310-005	P69313-005	P71671-425
Model Name	HPE ProLiant ML350 Gen11 4410Y 12-core 1P 64GB-R MR408i-o 8SFF 2x480GB SSD 2x800W RPS AMS Server	HPE ProLiant ML350 Gen11 5416S 16-core 1P 64GB-R MR408i-o 8SFF 2x480GB SSD 2x800W RPS AMS Server	HPE ProLiant ML350 Gen11 4510 12-core 64GB-R MR408i-o 8SFF 2x960GB SSD 2x1000W RPS EU Server
Chassis	HPE ProLiant ML350 Gen11 SFF Cor	nfigure-to-order Server	
Backplane	8 SFF		
Processor	4410Y (12 core, 2.0 GHz, 150W)	5416S (16 core, 2.0 GHz, 150W)	4510 (12 core, 2.4 GHz, 150W)
Number of Processors	One with standard heatsink		
Memory	64 GB (2x32 GB, 4800 MT/s) Notes: Runs at 4000 MT/s due to processor limitation.	64 GB (2x32 GB, 4800 MT/s) Notes: Runs at 4400 MT/s due to processor limitation.	64 GB (2x32 GB, 5600 MT/s) Notes: Runs at 4400 MT/s due to processor limitation.
Network Controller	Notes: Slot 15 OCP will be occupied a		
Storage Controller	HPE MR408i-o Gen11 x8 Lanes 4GB Cache OCP SPDM Storage Controller Notes: - Slot 14 OCP will be occupied, PCIe expansion slot is not required. - This controller supports up to 8 SAS/SATA/NVMe Drives with performance RAID. - Smart Storage battery included.		
Included Hard Drives	2x 480GB SATA SSD	2x 480GB SATA SSD	2x 960GB SATA SSD
Internal Storage	Default with 8 SFF SAS/SATA/NVMe x1 U.3 Drive Cage Kit (P47217-B21), up to two additional drive cages. Notes: Controller/cable kit is required for additional drive cage.		
Optical Drive	Optional. None ship standard.		
Expansion Slots		orimary riser cage. Upgradable with add to support expansion card on PCIe slo	
Power Supply	2x HPE 800W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit	2x HPE 800W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit	2x HPE 1000W Flex Slot Titanium Hot Plug Power Supply Kit
Fans	Default with 3 standard fans, none-hot-plug. Optional Second CPU Fan Kit (P47902-B21) and Redundant Fan Kit (P47219-B21) provide advanced cooling and redundancy functionality in heavier configurations. Notes: Configurations that require fan kits are provided in later sections	8x Standard Fans Notes: Configurations that require fan kits are provided in later sections	Default with 3 standard fans, none-hot-plug. Optional Second CPU Fan Kit (P47902-B21) and Redundant Fan Kit (P47219-B21) provide advanced cooling and redundancy functionality in heavier configurations. Notes: Configurations that require fan kits are provided in later sections
Management	HPE iLO Standard with Intelligent Provisioning (embedded), HPE OneView Standard (requires download); HPE iLO Advanced and HPE OneView Advanced (require licenses)		



Security	TPM (Trusted Platform Module)
----------	-------------------------------

HPE ProLiant	HPE ProLiant ML350 Gen11 - Smart Choice Models			
SKU Number	P71672-035	P71688-005	P74650-D65	
Model Name	HPE ProLiant ML350 Gen11 4510 12-core 64GB-R MR408i-o 8SFF 2x960GB SSD 2x1000W RPS UK/IE Server	HPE ProLiant ML350 Gen11 4514Y 16-core 64GB-R MR408i-o 8SFF 2x480GB SSD 2x800W RPS AMS Server	HPE ProLiant ML350 Gen11 4510 2.4GHz 12c 1P 32GB-R 8SFF MR408i-o 2x2.4TB HDD 2x800W RPS IN Server	
Chassis	HPE ProLiant ML350 Gen11 SFF Cor	nfigure-to-order Server		
Backplane	8 SFF			
Processor	4510 (12 core, 2.4 GHz, 150W)	4514Y (16 core, 2.0 GHz, 150W)	4510 (12 core, 2.4 GHz, 150W)	
Number of Processors	One with standard heatsink			
Memory	64 GB (2x32 GB, 5600 MT/s) Notes: Runs at 4400 MT/s due to processor limitation.	64 GB (2x32 GB, 5600 MT/s) Notes: Runs at 4400 MT/s due to processor limitation.	32 GB (1x32 GB, 5600 MT/s) Notes: Runs at 4400 MT/s due to processor limitation.	
Network Controller	Broadcom BCM5719 Ethernet 1Gb 4 Notes: Slot 15 OCP will be occupied a	·		
Storage Controller	HPE MR408i-o Gen11 x8 Lanes 4GB Cache OCP SPDM Storage Controller Notes: - Slot 14 OCP will be occupied, PCIe expansion slot is not required. - This controller supports up to 8 SAS/SATA/NVMe Drives with performance RAID. - Smart Storage battery included.			
Included Hard Drives	2x 960GB SATA SSD	2x 480GB SATA SSD	2x 2.4TB SAS HDD	
Internal Storage	Default with 8 SFF SAS/SATA/NVMe x1 U.3 Drive Cage Kit (P47217-B21), up to two additional drive cages. Notes: Controller/cable kit is required for additional drive cage.			
Optical Drive	Optional. None ship standard.			
Expansion Slots		orimary riser cage. Upgradable with add to support expansion card on PCIe slo		
Power Supply	2x HPE 1000W Flex Slot Titanium Hot Plug Power Supply Kit	2x HPE 800W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit	2x HPE 800W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit	
Fans	Default with 3 standard fans, none-hot-plug. Optional Second CPU Fan Kit (P47902-B21) and Redundant Fan Kit (P47219-B21) provide advanced cooling and redundancy functionality in heavier configurations. Notes: Configurations that require fan kits are provided in later sections	8x Standard Fans Notes: Configurations that require fan kits are provided in later sections	Default with 3 standard fans, none-hot-plug. Optional Second CPU Fan Kit (P47902-B21) and Redundant Fan Kit (P47219-B21) provide advanced cooling and redundancy functionality in heavier configurations. Notes: Configurations that require fan kits are provided in later sections	
Management	HPE iLO Standard with Intelligent Provisioning (embedded), HPE OneView Standard (requires download); HPE iLO Advanced and HPE OneView Advanced (require licenses)			



Security	TPM (Trusted Platform Module)
----------	-------------------------------

HPE ProLiant	HPE ProLiant ML350 Gen11 - Smart Choice Models				
SKU Number	P75339-D65	P75341-DM5	P77233-425		
Model Name	HPE ProLiant ML350 Gen11 4509Y 2.6GHz 8c 1P 32GB-R 4LFF MR408i-o 2x4TB HDD 2x800W RPS IN Server	HPE ProLiant ML350 Gen11 4410Y 2.0GHz 12c 1P 64GB-R 8SFF MR408i-o 2x960GB SSD 2x800W RPS LA Server	HPE ProLiant ML350 Gen11 4514Y 2.0GHz 16c 1P 64GB-R 8SFF MR408i-o 2x2.4TB HDD 2x1000W PS EU Server		
Chassis	HPE ProLiant ML350 Gen11 LFF Configure-to-order Server	HPE ProLiant ML350 Gen11 SFF Configure-to-order Server	HPE ProLiant ML350 Gen11 SFF Configure-to-order Server		
Backplane	4 LFF	8 SFF			
Processor	4509Y (8 core, 2.6 GHz, 125W)	4410Y (12 core, 2.0 GHz, 150W)	4514Y (16 core, 2.0 GHz, 150W)		
Number of Processors	One with standard heatsink				
Memory	32 GB (1x32 GB, 5600 MT/s) Notes: Runs at 4400 MT/s due to processor limitation.	64 GB (2x32 GB, 4800 MT/s) Notes: Runs at 4000 MT/s due to processor limitation.	64 GB (2x32 GB, 5600 MT/s) Notes: Runs at 4400 MT/s due to processor limitation.		
Network Controller	Broadcom BCM5719 Ethernet 1Gb 4-port BASE-T OCP3 Adapter for HPE Notes: Slot 15 OCP will be occupied along with CPU 1 MCIO port 1.				
Storage Controller	HPE MR408i-o Gen11 x8 Lanes 4GB Cache OCP SPDM Storage Controller Notes: - Slot 14 OCP will be occupied, PCIe expansion slot is not required. - This controller supports up to 8 SAS/SATA/NVMe Drives with performance RAID. - Smart Storage battery included.				
Included Hard Drives	2x 4TB SATA HDD	2x 960GB SATA SSD	2x 2.4TB SAS HDD		
Internal Storage	Default with 4LFF SAS/SATA Drive Cage Kit (P47216- B21), up to two additional drive cages. Notes: Controller/cable kit is required for additional drive cage.	Default with 8 SFF SAS/SATA/NVMe x1 U.3 Drive Cage Kit (P47217-B21), up to two additional drive cages. Notes: Controller/cable kit is required for additional drive cage.			
Optical Drive	Optional. None ship standard.				
Expansion Slots	Default with 4 x8 PCle 5.0 slots with primary riser cage. Upgradable with additional riser kit. Notes: Dual processors are required to support expansion card on PCle slots 5-10.				
Power Supply	2x HPE 800W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit	2x HPE 800W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit	2x HPE 1000W Flex Slot Titanium Hot Plug Power Supply Kit		

Fans	Default with 3 standard fans, none-hot-plug. Optional Second CPU Fan Kit (P47902-B21) and Redundant Fan Kit (P47219-B21) provide advanced cooling and redundancy functionality in heavier configurations. Notes: Configurations that require fan kits are provided in later sections	Default with 3 standard fans, none-hot-plug. Optional Second CPU Fan Kit (P47902-B21) and Redundant Fan Kit (P47219-B21) provide advanced cooling and redundancy functionality in heavier configurations. Notes: Configurations that require fan kits are provided in later sections	Default with 3 standard fans, none-hot-plug. Optional Second CPU Fan Kit (P47902-B21) and Redundant Fan Kit (P47219-B21) provide advanced cooling and redundancy functionality in heavier configurations. Notes: Configurations that require fan kits are provided in later sections
Management	HPE iLO Standard with Intelligent Provisioning (embedded), HPE OneView Standard (requires download); HPE iLO Advanced and HPE OneView Advanced (require licenses)		
Security	TPM (Trusted Platform Module)		

HPE ProLiant	MicroServer Gen10 Plus v2 - Smart Choice Models		
SKU Number	P69101-005	P69102-005	
Model Name	HPE ProLiant MicroServer Gen10 Plus v2 E-2314 4- core 1P 16GB-U VROC 4LFF-NHP 180W External PS Server	HPE ProLiant MicroServer Gen10 Plus v2 G6405 2- core 1P 16GB-U VROC 4LFF-NHP 180W External PS Server	
Number of Processors	One		
Memory	16 GB (1x 16 GB UDIMM DDR4 3200 MT/s) Notes: Total of 2 DIMM slots. With E-2314 processor, memory speed supports up to 3200 MT/s.	16 GB (1x 16 GB UDIMM DDR4 3200 MT/s) Notes: Total of 2 DIMM slots. With G6405 processor, memory speed supports up to 2666 MT/s.	
Network Controller	Embedded 1Gb 4-Port Intel i350-AM4 Controller		
Storage Controller	Embedded Intel VROC SATA SW RAID		
Included Hard Drives	None included, four LFF non-hot plug drives supported		
Internal Storage	4 LFF NHP SATA HDD cage		
Optical Drive	N/A		
Expansion Slots	1x standard (Low Profile) PCle 4.0		
Power Supply	1x 180W External Power Adapter		
Fans	1x non-redundant system fan ships standard		
Security	TPM (Trusted Platform Module)		

HPE ProLiant	MicroServer Gen10 Plus v2 - Smart Choice Models			
SKU Number	P69103-005 P70335-425			
Model Name	HPE ProLiant MicroServer Gen10 Plus v2 E-2314 4-core VROC 4LFF-NHP 1TB 180W External PS Server			
Number of Processors	One			
Memory	16 GB (1x 16 GB UDIMM DDR4 3200 MT/s) Notes: Total of 2 DIMM slots. With E-2314 processor, memory speed supports up to 3200 MT/s. 32 GB (2x 16 GB UDIMM DDR4 3200 MT/s) Notes: Total of 2 DIMM slots. With E-2314 processor, memory speed supports up to 3200 MT/s.			
Network Controller	Embedded 1Gb 4-Port Intel i350-AM4 Controller			
Storage Controller	Embedded Intel VROC SATA SW RAID			
Included Hard Drives	1x 1TB SATA HHD 2x 1TB SATA HHD			
Internal Storage	4 LFF NHP SATA HDD cage			
Optical Drive	N/A			
Expansion Slots	1x standard (Low Profile) PCle 4.0			
Power Supply	1x 180W External Power Adapter			
Fans	1x non-redundant system fan ships standard			
Security	TPM (Trusted Platform Module)			

HPE ProLiant	HPE ProLiant DL20 Gen10 Plus - Smart Choice Models			
SKU Number	P69301-005			
Model Name	HPE ProLiant DL20 Gen10 Plus E-2336 2.9GHz 6-core 1P 32GB-R 4SFF 500W RPS Server			
Chassis	HPE ProLiant DL20 Gen10 Plus 4SFF Configure-to-order Server			
Processor	E-2336 (6 core, 2.9 GHz, 65W)			
Number of Processors	One			
Memory	32 GB (2x16 GB UDIMM, 3200 MT/s)			
Network Controller	HPE embedded 1Gb 2-port BCM5720 network Adapter			
Storage Controller	Embedded Intel VROC SATA SW RAID Notes: SATA only			
Included Hard Drives	2x 480GB SATA SSD			
Expansion Slots	2 PCle 4.0 slots			
Power Supply	2x HPE 500W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit			
Fans	3 non hot plug, non-redundant			
Management	iLO Management (standard), Intelligent Provisioning (standard), iLO Advanced (optional)			
Rail Kit	HPE 1U Short Friction Rail Kit			
Security	TPM (Trusted Platform Module)			

HPE ProLiant	HPE ProLiant DL360 Gen10 Plus - Smart Choice Models				
SKU Number	P69298-005	P69299-005	P69749-005		
Model Name	HPE ProLiant DL360 Gen10 Plus 4310 2.1GHz 12-core 1P 32GB-R S100i NC 8SFF 800W PS Server	HPE ProLiant DL360 Gen10 Plus 4310 2.1GHz 12-core 1P 32GB-R P408i-a NC 8SFF 800W PS Server	HPE ProLiant DL360 Gen10 Plus 4314 2.4GHz 16-core 1P 128GB-R MR416i-a NC 8SFF 800W PS Server		
Chassis	HPE ProLiant DL360 Gen10 Plus 8S	FF NC Configure-to-order Server			
Processor	4310 (12 core, 2.1 GHz, 120W)	4310 (12 core, 2.1 GHz, 120W)	4314 (16 core, 2.4 GHz, 135W)		
Number of Processors	One with standard heatsink				
Memory	32 GB (1x32 GB, 3200 MT/s) Notes: Runs at 2667 MT/s due to processor limitation.	32 GB (1x32 GB, 3200 MT/s) Notes: Runs at 2667 MT/s due to processor limitation.	128 GB (4x32 GB, 3200 MT/s) Notes: Runs at 2667 MT/s due to processor limitation.		
Network Controller	Broadcom BCM5719 Ethernet 1Gb 4-port BASE-T OCP3 Adapter for HPE Notes: No embedded networking	Broadcom BCM5719 Ethernet 1Gb 4-port BASE-T OCP3 Adapter for HPE Notes: No embedded networking	Broadcom BCM57416 Ethernet 10Gb 2-port BASE-T OCP3 Adapter for HPE Notes: No embedded networking		
Storage Controller	HPE NS204i-p x2 Lanes NVMe PCle3 x8 OS Boot Device	HPE Smart Array P408i-a SR Gen10 x8 Lanes 2GB Cache SAS 12G Modular Controller	HPE MR416i-a Gen10 Plus x16 Lanes 4GB Cache NVMe/SAS 12G Controller		
Included Hard Drives	None ship standard, 8 SFF supported	2x 480GB SATA SSD	2x 480GB SATA SSD		
Optical Drive	Not included (Optical Drive options a	vailable)			
Expansion Slots	2 PCle: 1 x16 FH, 1 x16 LP				
Power Supply	2x HPE 800W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit				
Fans	7x High Performance fans	7x High Performance fans	5x Standard fans		
Management	HPE iLO 5				
Rail Kit	HPE ProLiant DL300 Gen10 Plus 1U SFF Easy Install Rail Kit Notes: Server does not support shelf mounted rail kits ("L" brackets).				
Security	TPM (Trusted Platform Module)				

SKU Number P74645-D65 P77128-425 P77171-425 Model Name HPE ProLiant DL360 Gen10 Plus 4310 2.1GHz 12c 64GB-R 8SFF MR416i-a 2x1.2TB HDD 2x800W RPS IN Server HPE ProLiant DL360 Gen10 Plus 4309Y 8c 64GB-R 8SFF SR416i-a 2x2.4TB HDD 2x800W PS EU Server HPE ProLiant DL360 Gen10 Plus 8SFF NC Configure-to-order Server Chassis HPE ProLiant DL360 Gen10 Plus 8SFF NC Configure-to-order Server Processor 4310 (12 core, 2.1 GHz, 120W) 4309Y (8 core, 2.8 GHz, 105W) Notes: 8/8/8 cores would result in 2.8/2.6/2.3 GHz operating points at 105W/95W/85W TDPs. 4309Y (8 core, 2.8 GHz, 105W) Notes: 8/8/8 cores would result in 2.8/2.6/2.3 GHz operating points at 105W/95W/85W TDPs. Number of Processors One with standard heatsink Broadcom BCM5719 Ethernet 1Gb 4-port BASE-T OCP3 Adapter for HPE Notes: No embedded networking Broadcom BCM5719 Ethernet 1Gb 4-port BASE-T OCP3 Adapter for HPE Notes: No embedded networking. Broadcom BCM5719 Ethernet 1Gb 4-port BASE-T OCP3 Adapter for HPE Notes: No embedded networking. Notes: No embedded networking. Notes: No embedded networking. HPE SR416i-a Gen10 Plus x16 Lanes 4GB Cache NVMe/SAS 24G Controller HPE SR416i-a Gen10 Plus x16 Lanes 4GB Cache NVMe/SAS 24G Controller HPE SR416i-a Gen10 Plus x16 Lanes 4GB Cache NVMe/SAS 24G Controller HPE SR416i-a Gen10 Plus x16 Lanes 4GB Cache NVMe/SAS 24G Controller HPE SR416i-a Gen10 Plus x16 Lanes 4GB Cache NVMe/SAS 24G Controller HPE SR416i-a Gen10 Plus x16 Lanes 4GB Cache NVMe/SAS 24G Controller
Model Name4310 2.1GHz 12c 64GB-R 8SFF MR416i-a 2x1.2TB HDD 2x800W RPS IN Server4309Y 8c 64GB-R 8SFF SR416i-a 2x480GB SATA SSD 2x800W PS EU Server4309Y 2.8GHz 8c 64GB-R 8SFF SR416i-a 2x2.4TB HDD 2x800W PS EU ServerChassisHPE ProLiant DL360 Gen10 Plus 8SFF NC Configure-to-order ServerProcessor4310 (12 core, 2.1 GHz, 120W)4309Y (8 core, 2.8 GHz, 105W) Notes: 8/8/8 cores would result in 2.8/2.6/2.3 GHz operating points at 105W/95W/85W TDPs.4309Y (8 core, 2.8 GHz, 105W) Notes: 8/8/8 cores would result in 2.8/2.6/2.3 GHz operating points at 105W/95W/85W TDPs.Number of ProcessorsOne with standard heatsink64 GB (2x32 GB, 3200 MT/s) Notes: Runs at 2667 MT/s due to processor limitation.Broadcom BCM5719 Ethernet 1Gb 4-port BASE-T OCP3 Adapter for HPE Notes: No embedded networkingBroadcom BCM5719 Ethernet 1Gb 4-port BASE-T OCP3 Adapter for HPE Notes: No embedded networking.Broadcom BCM5719 Ethernet 1Gb 4-port BASE-T OCP3 Adapter for HPE Notes: No embedded networking.HPE SR416i-a Gen10 Plus x16 Lanes 4GB Cache NVMe/SAS 24G ControllerHPE SR416i-a Gen10 Plus x16 Lanes 4GB Cache NVMe/SAS 24G ControllerHPE SR416i-a Gen10 Plus x16 Lanes 4GB Cache NVMe/SAS 24G ControllerIncluded2x 1 2TB SAS HDD2x 480GB SATA SSD2x 2 4TB SAS HDD
Processor 4310 (12 core, 2.1 GHz, 120W) Notes: 8/8/8 cores would result in 2.8/2.6/2.3 GHz operating points at 105W/95W/85W TDPs. Number of Processors One with standard heatsink Memory 64 GB (2x32 GB, 3200 MT/s) Notes: Runs at 2667 MT/s due to processor limitation. Broadcom BCM5719 Ethernet 1Gb 4-port BASE-T OCP3 Adapter for HPE Notes: No embedded networking Notes: No embedded networking Storage Controller Notes: No embedded networking A309Y (8 core, 2.8 GHz, 105W) Notes: 8/8/8 cores would result in 2.8/2.6/2.3 GHz operating points at 105W/95W/85W TDPs. Notes: 8/8/8 cores vould result in 2.8/2.6/2.3 GHz operating points at 105W/95W/85W TDPs. Notes: Runs at 2667 MT/s due to processor limitation. Broadcom BCM5719 Ethernet 1Gb 4-port BASE-T OCP3 Adapter for HPE Notes: No embedded networking. Notes: No embedded networking. Notes: No embedded networking. HPE MR416i-a Gen10 Plus x16 Lanes 4GB Cache NVMe/SAS 24G Controller Included 2x 1 2TB SAS HDD 2x 480GB SATA SSD 2x 2 4TB SAS HDD
Processor 4310 (12 core, 2.1 GHz, 120W) Notes: 8/8/8 cores would result in 2.8/2.6/2.3 GHz operating points at 105W/95W/85W TDPs. Number of Processors One with standard heatsink 64 GB (2x32 GB, 3200 MT/s) Notes: Runs at 2667 MT/s due to processor limitation. Broadcom BCM5719 Ethernet 1Gb 4-port BASE-T OCP3 Adapter for HPE Notes: No embedded networking Notes: No embedded networking Notes: No embedded networking. HPE MR416i-a Gen10 Plus x16 Lanes 4GB Cache NVMe/SAS 12G Controller Notes: No embedded Networking 2x 480GB SATA SSD. Notes: Note
Processors Memory 64 GB (2x32 GB, 3200 MT/s) Notes: Runs at 2667 MT/s due to processor limitation. Broadcom BCM5719 Ethernet 1Gb 4-port BASE-T OCP3 Adapter for HPE Notes: No embedded networking Notes: No embedded networking HPE MR416i-a Gen10 Plus x16 Lanes 4GB Cache NVMe/SAS 12G Controller Notes: No embedded networking HPE MR416i-a Gen10 Plus x16 Lanes 4GB Cache NVMe/SAS 12G Controller Notes: No embedded networking HPE SR416i-a Gen10 Plus x16 Lanes 4GB Cache NVMe/SAS 24G Controller Notes: No embedded networking HPE SR416i-a Gen10 Plus x16 Lanes 4GB Cache NVMe/SAS 24G Controller Notes: No embedded networking HPE SR416i-a Gen10 Plus x16 Lanes 4GB Cache NVMe/SAS 24G Controller Notes: No embedded networking
Notes: Runs at 2667 MT/s due to processor limitation. Broadcom BCM5719 Ethernet 1Gb 4-port BASE-T OCP3 Adapter for HPE Notes: No embedded networking Storage Controller HPE MR416i-a Gen10 Plus x16 Lanes 4GB Cache NVMe/SAS 12G Controller Notes: No embedded networking HPE SR416i-a Gen10 Plus x16 Lanes 4GB Cache NVMe/SAS 24G Controller Notes: No embedded networking. HPE SR416i-a Gen10 Plus x16 Lanes 4GB Cache NVMe/SAS 24G Controller Notes: No embedded networking. HPE SR416i-a Gen10 Plus x16 Lanes 4GB Cache NVMe/SAS 24G Controller Notes: No embedded networking. HPE SR416i-a Gen10 Plus x16 Lanes 4GB Cache NVMe/SAS 24G Controller Notes: No embedded networking. HPE SR416i-a Gen10 Plus x16 Lanes 4GB Cache NVMe/SAS 24G Controller Notes: No embedded networking.
Network Controller 4-port BASE-T OCP3 Adapter for HPE Notes: No embedded networking HPE Notes: No embedded networking HPE MR416i-a Gen10 Plus x16 Lanes 4GB Cache NVMe/SAS 12G Controller HPE SR416i-a Gen10 Plus x16 Lanes 4GB Cache NVMe/SAS 24G Controller HPE SR416i-a Gen10 Plus x16 Lanes 4GB Cache NVMe/SAS 24G Controller 2x 480GB SATA SSD 2x 2 4TB SAS HDD 2x 4 80GB SATA SSD 2x 2 4TB SAS HDD
Controller Lanes 4GB Cache NVMe/SAS 12G Controller Lanes 4GB Cache NVMe/SAS 24G Controller Lanes 4GB Cache NVMe/SAS 24G Controller 2x 480GB SATA SSD 2x 2 4TB SAS HDD 2x 2 4TB SAS HDD
2 × 1 2TR SAS HDD 2 × 480GR SATA SSD 2 × 2 4TR SAS HDD
Hard Drives ZX 2.410 3/13 1100
Optical DriveNot included (Optical Drive options available)Optional DVD via Universal Media Bay or USB connectivityOptional DVD via Universal Media Bay or USB connectivity
Expansion Slots 2 PCle: 1 x16 FH, 1 x16 LP
Power Supply 2x HPE 800W Flex Slot Platinum 2x HPE 800W Flex Slot Titanium 4x HPE 800W Flex Sl
Fans 5x Standard fans
Management HPE iLO 5
Rail Kit HPE ProLiant DL300 Gen10 Plus 1U SFF Easy Install Rail Kit Notes: Server does not support shelf mounted rail kits ("L" brackets).
Security TPM (Trusted Platform Module)

HPE ProLiant	DL380 Gen10 Plus - Smart Choice M	odels		
SKU Number	P69320-005 P69754-005 P69755-005			
Model Name	HPE ProLiant DL380 Gen10 Plus 6326 2.9GHz 16-core 1P 32GB-R MR416i-a NC 8SFF 800W PS Server	HPE ProLiant DL380 Gen10 Plus 4310 2.1GHz 12-core 1P 64GB-R MR416i-a NC 8SFF 800W PS Server	HPE ProLiant DL380 Gen10 Plus 4314 2.4GHz 16-core 1P 128GB-R MR416i-a NC 8SFF 800W PS Server	
Chassis	HPE ProLiant DL380 Gen10 Plus 8SI	F NC Configure-to-order Server		
Processor	6326 (16 core, 2.9 GHz, 185W)	4310 (12 core, 2.1 GHz, 120W)	4314 (16 core, 2.4 GHz, 135W) Notes: Supports Intel Optane Persistent Memory 200 Series, enabling up to 6TB memory per socket (does not work with SGX).	
Number of Processors	One with high performance heatsink One with standard heatsink One with standard heatsink			
Memory	32 GB (1x32 GB, 3200 MT/s)	64 GB (2x32 GB, 3200 MT/s) Notes: Runs at 2667 MT/s due to processor limitation.	128 GB (4x32 GB, 3200 MT/s) Notes: Runs at 2667 MT/s due to processor limitation.	
Network Controller	Broadcom BCM5719 Ethernet 1Gb 4-port BASE-T OCP3 Adapter for HPE Notes: No embedded networking	Broadcom BCM5719 Ethernet 1Gb 4-port BASE-T OCP3 Adapter for HPE Notes: No embedded networking	Broadcom BCM57416 Ethernet 10Gb 2-port BASE-T OCP3 Adapter for HPE Notes: No embedded networking	
Storage Controller	HPE MR416i-a Gen10 Plus x16 Lanes 4GB Cache NVMe/SAS 12G Controller			
Included Hard Drives	2x 480GB SATA SSD			
Optical Drive	Optional DVD-ROM Optional via Universal Media Bay External support only			
Power Supply	2x HPE 800W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit			
Fans	6x Maximum Performance Fans	4x Standard Fans	4x Standard Fans	
Management	HPE iLO 5			
Rail Kit	HPE DL38X Gen10 Plus 2U SFF Easy Install Rail Kit Notes: Easy Install w/ CMA			
Security	TPM (Trusted Platform Module)			

HPE ProLiant	HPE ProLiant DL380 Gen10 Plus - Smart Choice Models				
SKU Number	P74646-D65	P74647-D65	P77170-425		
Model Name	HPE ProLiant DL380 Gen10 Plus 4310 2.1GHz 12c 64GB-R 12LFF MR416i-a 2x4TB HDD 2x800W RPS IN Server	HPE ProLiant DL380 Gen10 Plus 4310 2.1GHz 12c 64GB-R 8SFF MR416i-a 2x1.2TB HDD 2x800W RPS IN Server	HPE ProLiant DL380 Gen10 Plus 4309Y 8c 64GB-R 8SFF SR416i-a 2x480GB SATA SSD 2x800W PS EU Server		
Chassis	HPE ProLiant DL380 Gen10 Plus 12LFF NC Configure-to-order Server	HPE ProLiant DL380 Gen10 Plus 8SFF NC Configure-to-order Server	HPE ProLiant DL380 Gen10 Plus 8SFF NC Configure-to-order Server		
Processor	4310 (12 core, 2.1 GHz, 120W)	4310 (12 core, 2.1 GHz, 120W)	4309Y (8 core, 2.8 GHz, 105W) Notes: 8/8/8 cores would result in 2.8/2.6/2.3 GHz operating points at 105W/95W/85W TDPs.		
Number of Processors	One with standard heatsink				
Memory	64 GB (2x32 GB, 3200 MT/s) Notes: Runs at 2667 MT/s due to processor limitation.				
Network Controller	Broadcom BCM5719 Ethernet 1Gb 4-port BASE-T OCP3 Adapter for HPE				
Storage Controller	HPE MR416i-a Gen10 Plus x16 Lanes 4GB Cache NVMe/SAS 12G Controller	HPE MR416i-a Gen10 Plus x16 Lanes 4GB Cache NVMe/SAS 12G Controller	HPE SR416i-a Gen10 Plus x16 Lanes 4GB Cache NVMe/SAS 24G Controller		
Included Hard Drives	2x 4TB SATA HDD	2x 1.2TB SAS HDD	2x 480GB SATA SSD		
Optical Drive	Optional DVD-ROM Optional via Univ	ersal Media Bay External support only			
Power Supply	2x HPE 800W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit	2x HPE 800W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit	2x HPE 800W Flex Slot Titanium Hot Plug Low Halogen Power Supply Kit		
Fans	6x Maximum Performance Fans	4x Standard Fans	6x Maximum Performance Fans		
Management	HPE iLO 5				
Rail Kit	HPE DL38X Gen10 Plus 2U LFF Easy Install Rail Kit Notes: Easy Install w/ CMA	HPE DL38X Gen10 Plus 2U SFF Easy Install Rail Kit Notes: Easy Install w/ CMA	HPE DL38X Gen10 Plus 2U SFF Easy Install Rail Kit Notes: Easy Install w/ CMA		
Security	TPM (Trusted Platform Module)				

HPE ProLiant	HPE ProLiant DL360 Gen10 - Smart Choice Models				
SKU Number	P69746-005	P69748-005	P71373-425		
Model Name	HPE ProLiant DL360 Gen10 4208 2.1GHz 8-core 1P 64GB-R P408i-a 8SFF 800W PS Server	HPE ProLiant DL360 Gen10 4210R 2.4GHz 10-core 1P 64GB-R P408i-a 8SFF 800W PS Server	HPE ProLiant DL360 Gen10 4208 2.1GHz 8c 1P 64GB-R 8SFF P408i- a 2x960GB SSD 2x800W RPS EMEA Server		
Chassis	HPE ProLiant DL360 Gen10 8SFF Co	onfigure-to-order Server			
Processor	4208 (8 core, 2.1 GHz, 85W)	4210R (10 core, 2.4 GHz, 100W)	4208 (8 core, 2.1 GHz, 85W)		
Number of Processors	One				
Memory	64 GB (2x32 GB, 2933 MT/s) Notes: Runs at 2400 MT/s due to processor limitation.	64 GB (2x32 GB, 2933 MT/s) Notes: Runs at 2400 MT/s due to processor limitation.	64 GB (2x32 GB, 2933 MT/s) Notes: Runs at 2400 MT/s due to processor limitation.		
Network Controller	Embedded 4 x 1GbE Ethernet Adapter				
Storage Controller	HPE Smart Array P408i-a SR Gen10 x8 Lanes 2GB Cache SAS 12G Modular Controller				
Included Hard Drives	2x 480GB SATA SSD	2x 480GB SATA SSD	2x 960GB SATA SSD		
Optical Drive	Not included (Optical Drive options available)	Not included (Optical Drive options available)	Not included		
Power Supply	2x HPE 800W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit	2x HPE 800W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit	2x HPE 800W Flex Slot Titanium Hot Plug Low Halogen Power Supply Kit		
Fans	5 single rotor hot plug fans				
Rail Kit	HPE Gen10 1U SFF Easy Install Rail Kit				
Security	TPM (Trusted Platform Module)				

Model Name HPE ProLiant DL380 Gen10 4210R 2.1GHz 8-core 1P 64GB-R P408i-a 85FF 800W PS Server Chassis HPE ProLiant DL380 Gen10 4210R 2.4GHz 10-core 1P 64GB-R P408i-a 85FF 800W PS Server RPS EMEA Server Chassis HPE ProLiant DL380 Gen10 85FF Configure-to-order Server Processor 4208 (8 core, 2.1 GHz, 85W) Valor (10 core, 2.4 GHz, 100W) Number of Processors One 64 GB (2x32 GB, 2933 MT/s) Notes: Runs at 2400 MT/s due to processor limitation. Network Controller 1x Embedded 4 x 1GbE Ethernet Adapter Storage Controller HPE Smart Array P408i-a SR Gen10 x8 Lanes 2GB Cache SAS 12G Modular Controller Included Hard Drives Internal Storage Optical Drive Optional Expansion Slots 2x HPE 800W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit Fans 4x Standard Management HPE ILO Standard with Intelligent Provisioning (embedded), HPE OneView Standard (requires download); HPE ILO Advanced, HPE iLO Advanced Premium Security Edition and HPE OneView Advanced (require licenses)	HPE ProLiant	DL380 Gen10 - Smart Choice Models	3	
Model NameHFE Prollaint DL380 Gen10 4208 a SFF B00W PS Server2.4GHz 10c 1P 64GB-R P408i-a 8FF 800W PS Server2.4GHz 10c 1P 64GB-R 8FF P408i-a 2x1.921B SSD 2x800W RPS EMEA ServerChassisHPE Prolaint DL380 Gen10 48FF Configure-to-order ServerProcessor4208 (8 core, 2.1 GHz, 85W)4210R (10 core, 2.4 GHz, 100W)4210R (10 core, 2.4 GHz, 100W)Number of ProcessorsMemory64 GB (2x32 GB, 2933 MT/s) Notes: Runs at 2400 MT/s due to processor limitation.64 GB (2x32 GB, 2933 MT/s) Notes: Runs at 2400 MT/s due to processor limitation.Network Controller1x Embedded 4 x 1GbE Ethernet AdapterNotes: Runs at 2400 MT/s due to processor limitation.Storage ControllerHPE Smart Array P408i-a SR Gen10 x8 Lanes 2GB Cache SAS 12G Modular ControllerIncluded Hard Drives2x 480GB SATA SSD2x 480GB SATA SSD2x 1.92TB SAS SSDInternal Storage8 SFF (upgradeable to 24 SFF front + 6 SFF rear)2x 480GB SATA SSD2x 1.92TB SAS SSDOptical DriveOptional2x 4PE 800W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit2x HPE 800W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit2x HPE 800W Flex Slot Titanium Hot Plug Low Halogen Power Supply KitFans4x Standard4x Standard4x Standard4x Standard With Intelligent Provisioning (embedded), HPE OneView Advanced (r	SKU Number	P69751-005	P69753-005	P71383-425
Number of Processors One 4210R (10 core, 2.4 GHz, 100W) 4210R (10 core, 2.4 GHz, 100W) Number of Processors One 64 GB (2x32 GB, 2933 MT/s) Notes: Runs at 2400 MT/s due to processor limitation. Network Controller Storage Controller Included Hard Drives By SFF (upgradeable to 24 SFF front + 6 SFF rear) Optical Drive Optional Expansion Stors Supply Ax Standard Management Management One 64 GB (2x32 GB, 2933 MT/s) Notes: Runs at 2400 MT/s due to processor limitation. 64 GB (2x32 GB, 2933 MT/s) Notes: Runs at 2400 MT/s due to processor limitation. 64 GB (2x32 GB, 2933 MT/s) Notes: Runs at 2400 MT/s due to processor limitation. 64 GB (2x32 GB, 2933 MT/s) Notes: Runs at 2400 MT/s due to processor limitation. 64 GB (2x32 GB, 2933 MT/s) Notes: Runs at 2400 MT/s due to processor limitation. 64 GB (2x32 GB, 2933 MT/s) Notes: Runs at 2400 MT/s due to processor limitation. 8 CHORD Report Supply Associated to processor limitation. 8 SFF (upgradeable to x8 Lanes 2GB Cache SAS 12G Modular Controller 2x 480GB SATA SSD 2x 480GB SATA SSD 2x 490GB SATA SSD 2x 4.92TB SAS SSD 2x 1.92TB SAS SSD Determine Sample S	Model Name	2.1GHz 8-core 1P 64GB-R P408i-a	2.4GHz 10-core 1P 64GB-R P408i-a	P408i-a 2x1.92TB SSD 2x800W
Number of Processors Memory	Chassis	HPE ProLiant DL380 Gen10 8SFF Co	onfigure-to-order Server	
Processors Memory 64 GB (2x32 GB, 2933 MT/s) Notes: Runs at 2400 MT/s due to processor limitation. Network Controller Storage Controller Included Hard Drives 8 SFF (upgradeable to 24 SFF front + 6 SFF rear) Optical Drive Coptional Expansion Slots 2x HPE 800W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit Fans 4x Standard Management 64 GB (2x32 GB, 2933 MT/s) Notes: Runs at 2400 MT/s due to processor limitation. 64 GB (2x32 GB, 2933 MT/s) Notes: Runs at 2400 MT/s due to processor limitation. 64 GB (2x32 GB, 2933 MT/s) Notes: Runs at 2400 MT/s due to processor limitation. 64 GB (2x32 GB, 2933 MT/s) Notes: Runs at 2400 MT/s due to processor limitation. 64 GB (2x32 GB, 2933 MT/s) Notes: Runs at 2400 MT/s due to processor limitation. 64 GB (2x32 GB, 2933 MT/s) Notes: Runs at 2400 MT/s due to processor limitation. 64 GB (2x32 GB, 2933 MT/s) Notes: Runs at 2400 MT/s due to processor limitation. 64 GB (2x32 GB, 2933 MT/s) Notes: Runs at 2400 MT/s due to processor limitation. 64 GB (2x32 GB, 2933 MT/s) Notes: Runs at 2400 MT/s due to processor limitation. 64 GB (2x32 GB, 2933 MT/s) Notes: Runs at 2400 MT/s due to processor limitation. 64 GB (2x32 GB, 2933 MT/s) Notes: Runs at 2400 MT/s due to processor limitation. 64 GB (2x32 GB, 2933 MT/s) Notes: Runs at 2400 MT/s due to processor limitation. 64 GB (2x32 GB, 2933 MT/s) Notes: Runs at 2400 MT/s due to processor limitation. 64 GB (2x32 GB, 293 MT/s) Notes: Runs at 2400 MT/s due to processor limitation. 64 GB (2x32 GB, 293 MT/s) Notes: Runs at 2400 MT/s due to processor limitation. 64 GB (2x32 GB, 293 MT/s) Notes: Runs at 2400 MT/s due to processor limitation. 64 GB (2x32 GB, 293 MT/s) Notes: Runs at 2400 MT/s due to processor limitation. 64 GB (2x32 GB, 293 MT/s) Notes: Runs at 2400 MT/s due to processor limitation. 64 GB (2x32 GB, 293 MT/s) Notes: Runs at 2400 MT/s due to processor limitation. 64 GB (2x32 GB (24 SFF front + 6 SFF rear) 64 GB (2x32 GB (24 SFF front + 6 SFF rear) 64 GB (2x 24 SGB SATA SD 2x 1.92TB SAS SD 2x 1	Processor	4208 (8 core, 2.1 GHz, 85W)	4210R (10 core, 2.4 GHz, 100W)	4210R (10 core, 2.4 GHz, 100W)
MemoryNotes: Runs at 2400 MT/s due to processor limitation.Notes: Runs at 2400 MT/s due to processor limitation.Notes: Runs at 2400 MT/s due to processor limitation.Network Controller1x Embedded 4 x 1GbE Ethernet AdapterStorage ControllerHPE Smart Array P408i-a SR Gen10 x8 Lanes 2GB Cache SAS 12G Modular ControllerIncluded Hard Drives2x 480GB SATA SSD2x 480GB SATA SSDInternal Storage8 SFF (upgradeable to 24 SFF front + 6 SFF rear)Optical DriveOptionalExpansion Slots3-slots (x8, x16, x8 with dual m.2) as standard; upgradeable to 8-slots in a 2 processor configurationPower Supply2x HPE 800W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit2x HPE 800W Flex Slot Titanium Hot Plug Low Halogen Power Supply KitFans4x StandardManagementHPE iLO Standard with Intelligent Provisioning (embedded), HPE OneView Advanced (requires download); HPE iLO Advanced, HPE iLO Advanced Premium Security Edition and HPE OneView Advanced (require licenses)	Number of Processors	One		
Controller Storage Controller HPE Smart Array P408i-a SR Gen10 x8 Lanes 2GB Cache SAS 12G Modular Controller Included Hard Drives Internal Storage Optical Drive Optional Expansion Slots 2x HPE 800W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit Fans 4x Standard Management HPE Smart Array P408i-a SR Gen10 x8 Lanes 2GB Cache SAS 12G Modular Controller 2x 1.92TB SAS SSD 4x 1.92TB SAS SSD 2x 1.92TB SAS SSD 2x 1.92TB SAS SSD 4x 1.92TB SAS SSD 2x 1.92TB SAS SSD 4x 1.92TB SAS SSD 2x 1.92TB SAS SSD 4x 1.92TB SAS SSD 4x 1.92TB SAS SSD 2x 1.92TB SAS SSD 4x 1.92TB SAS SSD 2x 1.92TB SAS SSD 4x 1.92TB SAS SSD	Memory	Notes: Runs at 2400 MT/s due to	Notes: Runs at 2400 MT/s due to	Notes: Runs at 2400 MT/s due to
Controller	Network Controller	1x Embedded 4 x 1GbE Ethernet Adapter		
Hard Drives Internal Storage 8 SFF (upgradeable to 24 SFF front + 6 SFF rear) Optical Drive Expansion Slots 3-slots (x8, x16, x8 with dual m.2) as standard; upgradeable to 8-slots in a 2 processor configuration Power Supply Cit Los Standard HPE iLO Standard with Intelligent Provisioning (embedded), HPE OneView Standard (requires download); HPE iLO Advanced, HPE iLO Advanced Premium Security Edition and HPE OneView Advanced (require licenses)	Storage Controller	HPE Smart Array P408i-a SR Gen10 x8 Lanes 2GB Cache SAS 12G Modular Controller		
Storage Optical Drive Optical Drive Expansion Slots	Included Hard Drives	2x 480GB SATA SSD	2x 480GB SATA SSD	2x 1.92TB SAS SSD
Expansion Slots 3-slots (x8, x16, x8 with dual m.2) as standard; upgradeable to 8-slots in a 2 processor configuration Power Supply 2x HPE 800W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit 4x Standard HPE iLO Standard with Intelligent Provisioning (embedded), HPE OneView Standard (requires download); HPE iLO Advanced, HPE iLO Advanced Premium Security Edition and HPE OneView Advanced (require licenses)	Internal Storage	8 SFF (upgradeable to 24 SFF front + 6 SFF rear)		
Slots 2x HPE 800W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit 4x Standard HPE iLO Standard with Intelligent Provisioning (embedded), HPE OneView Standard (requires download); HPE iLO Advanced, HPE iLO Advanced Premium Security Edition and HPE OneView Advanced (require licenses)	Optical Drive	Optional		
Hot Plug Low Halogen Power Supply Kit Av Standard HPE iLO Standard with Intelligent Provisioning (embedded), HPE OneView Standard (requires download); HPE iLO Advanced, HPE iLO Advanced Premium Security Edition and HPE OneView Advanced (require licenses)	Expansion Slots	3-slots (x8, x16, x8 with dual m.2) as standard; upgradeable to 8-slots in a 2 processor configuration		
Management HPE iLO Standard with Intelligent Provisioning (embedded), HPE OneView Standard (requires download); HPE iLO Advanced, HPE iLO Advanced Premium Security Edition and HPE OneView Advanced (require licenses)	Power Supply	Hot Plug Low Halogen Power Supply	Hot Plug Low Halogen Power Supply	Hot Plug Low Halogen Power Supply
iLO Advanced, HPE iLO Advanced Premium Security Edition and HPE OneView Advanced (require licenses)	Fans	4x Standard		
Security TPM (Trusted Platform Module)	Management			
	Security	TPM (Trusted Platform Module)		

Country Code Key

- -005 = HPE Smart Choice for US and Canada
- -035 = HPE Smart Choice for United Kingdom
- -205 = HPE Smart Choice for Brazil
- -425 = HPE Smart Choice for Europe, the Middle East and Africa (EMEA)
- -D65 = HPE Smart Choice for India
- -DM5 = HPE Smart Choice for LATAM

Full ProLiant Server QuickSpecs

HPE Smart Choice products are fully configured and ready-to-ship. Core options within the integrated server may not be changed, but in some cases additional options for expansion and upgrade of the product may be possible. To understand potential option choices, please view the Additional Options section of the base product's QuickSpecs.

Full ProLiant Server QuickSpecs

- HPE ProLiant DL20 Gen11: https://www.hpe.com/psnow/doc/a50007009enw
- HPE ProLiant DL320 Gen11: https://www.hpe.com/psnow/doc/a50004315enw
- HPE ProLiant DL325 Gen11: https://www.hpe.com/psnow/doc/a50004297enw
- HPE ProLiant DL360 Gen11: https://www.hpe.com/psnow/doc/a50004306enw
- HPE ProLiant DL380 Gen11: https://www.hpe.com/psnow/doc/a50004307enw
- HPE ProLiant ML30 Gen11: https://www.hpe.com/psnow/doc/a50007008enw
- HPE ProLiant ML110 Gen11: https://www.hpe.com/psnow/doc/a00054055enw
- HPE ProLiant ML350 Gen11: https://www.hpe.com/psnow/doc/a50004308enw
- HPE ProLiant MicroServer Gen10 Plus v2: https://www.hpe.com/psnow/doc/a50004293enw
- HPE ProLiant DL20 Gen10 Plus Server: https://www.hpe.com/psnow/doc/a50002583enw
- HPE ProLiant DL360 Gen10 Plus Server: https://www.hpe.com/psnow/doc/a50002559enw
- HPE ProLiant DL380 Gen10 Plus Server: https://www.hpe.com/psnow/doc/a50002553enw
- HPE ProLiant DL360 Gen10 Server: https://www.hpe.com/psnow/doc/a00008159enw
- HPE ProLiant DL380 Gen10 Server: https://www.hpe.com/psnow/doc/a00008180enw

Summary of Changes

Date	Version History	Action	Description of Change
03-Sep-2024	Version 1	New	New QuickSpecs.

Copyright

Make the right purchase decision. Contact our presales specialists.







© Copyright 2024 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

Intel® and Xeon® are registered trademarks of Intel Corporation in the U.S. and other countries. Microsoft®, Windows®, and Windows Server® are U.S. registered trademarks of the Microsoft group of companies.

For hard drives, 1GB = 1 billion bytes. Actual formatted capacity is less

a50009219enw - 17251 - Worldwide - V1 - 03-September-2024