EDS Stored Procedures Documentation

Stored Procedures Reference

EDS Universal Requisition System

Generated: January 22, 2026

Generated: 2026-01-09 11:41:42

Summary

Metric	Count
Total Stored Procedures	395
Total Parameters	1308
Documented Procedures	395 (100.0%)
Documented Parameters	1308 (100.0%)

Table of Contents

Schema: dbo

- [spFA_UpdateRequisitionStatus](#sp-dbo--sp-fa-updaterequisitionstatus)
- [bid2xls](#sp-dbo-bid2xls)
- [bid2xlsTest](#sp-dbo-bid2xlstest)
- [dt_addtosourcecontrol](#sp-dbo-dt-addtosourcecontrol)
- [dtaddtosourcecontrolu](#sp-dbo-dt-addtosourcecontrol-u)
- [dt_adduserobject](#sp-dbo-dt-adduserobject)
- [dtadduserobjectvcs](#sp-dbo-dt-adduserobject-vcs)
- [dt_checkinobject](#sp-dbo-dt-checkinobject)
- [dtcheckinobjectu](#sp-dbo-dt-checkinobject-u)
- [dt_checkoutobject](#sp-dbo-dt-checkoutobject)
- [dtcheckoutobjectu](#sp-dbo-dt-checkoutobject-u)
- [dt_displayoaerror](#sp-dbo-dt-displayoaerror)
- [dtdisplayoaerroru](#sp-dbo-dt-displayoaerror-u)
- [dt_droppropertiesbyid](#sp-dbo-dt-droppropertiesbyid)
- [dt_dropuserobjectbyid](#sp-dbo-dt-dropuserobjectbyid)
- [dt_generateansiname](#sp-dbo-dt-generateansiname)
- [dt_getobjwithprop](#sp-dbo-dt-getobjwithprop)

- [dtgetobjwithpropu](#sp-dbo-dt-getobjwithprop-u)
- [dt_getpropertiesbyid](#sp-dbo-dt-getpropertiesbyid)
- [dtgetpropertiesbyidu](#sp-dbo-dt-getpropertiesbyid-u)
- [dtgetpropertiesbyidvcs](#sp-dbo-dt-getpropertiesbyid-vcs)
- [dtgetpropertiesbyidvcs_u](#sp-dbo-dt-getpropertiesbyid-vcs-u)
- [dt_isundersourcecontrol](#sp-dbo-dt-isundersourcecontrol)
- [dtisundersourcecontrolu](#sp-dbo-dt-isundersourcecontrol-u)
- [dt_removefromsourcecontrol](#sp-dbo-dt-removefromsourcecontrol)
- [dt_setpropertybyid](#sp-dbo-dt-setpropertybyid)
- [dtsetpropertybyidu](#sp-dbo-dt-setpropertybyid-u)
- [dt_validateloginparams](#sp-dbo-dt-validateloginparams)
- [dtvalidateloginparamsu](#sp-dbo-dt-validateloginparams-u)
- [dt_vcsenabled](#sp-dbo-dt-vcsenabled)
- [dt_verstamp006](#sp-dbo-dt-verstamp006)
- [dt_verstamp007](#sp-dbo-dt-verstamp007)
- [dt_whocheckedout](#sp-dbo-dt-whocheckedout)
- [dtwhocheckedoutu](#sp-dbo-dt-whocheckedout-u)
- [sp_AddDistrict](#sp-dbo-sp-adddistrict)
- [sp_AddISBN](#sp-dbo-sp-addisbn)
- [sp_AddMSRPItem](#sp-dbo-sp-addmsrpitem)
- [sp_AddPPCatalog](#sp-dbo-sp-addppcatalog)
- [sp_AddPricePlan](#sp-dbo-sp-addpriceplan)
- [sp_AddSchool](#sp-dbo-sp-addschool)
- [sp_alterdiagram](#sp-dbo-sp-alterdiagram)
- [sp_ApproveReq](#sp-dbo-sp-approvereq)
- [sp_AttemptLogin](#sp-dbo-sp-attemptlogin)
- [sp_AwardBid](#sp-dbo-sp-awardbid)
- [sp_AwardBidHeader](#sp-dbo-sp-awardbidheader)
- [sp_AwardBidHeaderSingleItem](#sp-dbo-sp-awardbidheadersingleitem)
- [sp_BAList](#sp-dbo-sp-balist)
- [sp_BatchChanges](#sp-dbo-sp-batchchanges)
- [sp_BatchConvert](#sp-dbo-sp-batchconvert)
- [sp_BatchConvertNew](#sp-dbo-sp-batchconvertnew)
- [sp_BatchLoad](#sp-dbo-sp-batchload)
- [sp_BatchProcess](#sp-dbo-sp-batchprocess)
- [sp_BatchQueue](#sp-dbo-sp-batchqueue)
- [sp_BatchVerify](#sp-dbo-sp-batchverify)
- [sp_BatchVerifyBook](#sp-dbo-sp-batchverifybook)

- [sp_BatchVerifyForce](#sp-dbo-sp-batchverifyforce)
- [sp_BidCompare](#sp-dbo-sp-bidcompare)
- [sp_BidCompareDiscount](#sp-dbo-sp-bidcomparediscount)
- [sp_BidCompareSame](#sp-dbo-sp-bidcomparesame)
- [sp_BidCompareSummary](#sp-dbo-sp-bidcomparesummary)
- [sp_BidCopy](#sp-dbo-sp-bidcopy)
- [sp_BidCopyChangePP](#sp-dbo-sp-bidcopychangepp)
- [sp_BidCopyWithIncrease](#sp-dbo-sp-bidcopywithincrease)
- [sp_BringBillingForward](#sp-dbo-sp-bringbillingforward)
- [sp_BringBillingForwardState](#sp-dbo-sp-bringbillingforwardstate)
- [sp_BuildTopOrdered](#sp-dbo-sp-buildtopordered)
- [sp_CanDeleteRequisition](#sp-dbo-sp-candeleterequisition)
- [sp_CatalogDataCheck](#sp-dbo-sp-catalogdatacheck)
- [sp_CatalogDataPriceCheck](#sp-dbo-sp-catalogdatapricecheck)
- [sp_CatalogImport](#sp-dbo-sp-catalogimport)
- [sp_CatalogImporter](#sp-dbo-sp-catalogimporter)
- [sp_CatalogImporterXML](#sp-dbo-sp-catalogimporterxml)
- [sp_CCAccountMaint](#sp-dbo-sp-ccaccountmaint)
- [sp_CCAddAddendaItem](#sp-dbo-sp-ccaddaddendaitem)
- [sp_CCAddAddendaMaint](#sp-dbo-sp-ccaddaddendamaint)
- [sp_CCAnalysisReturn](#sp-dbo-sp-ccanalysisreturn)
- [sp_CCItemMaint](#sp-dbo-sp-ccitemmaint)
- [sp_CCSchoolMaint](#sp-dbo-sp-ccschoolmaint)
- [sp_CCUpdateAddendaItem](#sp-dbo-sp-ccupdateaddendaitem)
- [sp_CCUpdateAddendaItemSizesOnly](#sp-dbo-sp-ccupdateaddendaitemsizesonly)
- [sp_CCUpdateAddendaMaint](#sp-dbo-sp-ccupdateaddendamaint)
- [sp_CCUpdateResults](#sp-dbo-sp-ccupdateresults)
- [sp_CCUpdateUserAccounts](#sp-dbo-sp-ccupdateuseraccounts)
- [spCCUpdateUserAccounts2](#sp-dbo-sp-ccupdateuseraccounts-2)
- [sp_CCUpdateUserAccountsBulk](#sp-dbo-sp-ccupdateuseraccountsbulk)
- [sp_CCUserAccountMaint](#sp-dbo-sp-ccuseraccountmaint)
- [sp_CCUserGridMaint](#sp-dbo-sp-ccusergridmaint)
- [sp_CombineReqs](#sp-dbo-sp-combinereqs)
- [sp_CombineReqsByVendorNoDelete](#sp-dbo-sp-combinereqsbyvendornodelete)
- [sp_CometLoad](#sp-dbo-sp-cometload)
- [sp_ConvertReqs](#sp-dbo-sp-convertreqs)
- [sp_ConvertTextbookReqs](#sp-dbo-sp-converttextbookreqs)
- [sp_CopyBidImport](#sp-dbo-sp-copybidimport)

- [sp_CopyBudgetAmounts](#sp-dbo-sp-copybudgetamounts)
- [sp_CopyCalendar](#sp-dbo-sp-copycalendar)
- [sp_CopyItems](#sp-dbo-sp-copyitems)
- [sp_CopyMSRPVers2Bid](#sp-dbo-sp-copymsrpvers2bid)
- [sp_CopyMSRPVers2BidBackup](#sp-dbo-sp-copymsrpvers2bidbackup)
- [sp_CopyMSRPVers2BidBackup-2014-10-29](#sp-dbo-sp-copymsrpvers2bidbackup-2014-10-29)
- [sp_CopyMSRPVers2BidUsingCursorSave](#sp-dbo-sp-copymsrpvers2bidusingcursorsave)
- [sp_CopyMSRPVers2BidUsingCursorSave2](#sp-dbo-sp-copymsrpvers2bidusingcursorsave2)
- [sp_CopyMSRPVers3Bid](#sp-dbo-sp-copymsrpvers3bid)
- [sp_CopyMSRPVers4Bid](#sp-dbo-sp-copymsrpvers4bid)
- [sp_CopyReqBulk](#sp-dbo-sp-copyreqbulk)
- [sp_CopyReqs](#sp-dbo-sp-copyreqs)
- [sp_CopyReqsBulk](#sp-dbo-sp-copyreqsbulk)
- [sp_CopyToBudgetBook](#sp-dbo-sp-copytobudgetbook)
- [sp_CreateBidFromRequest](#sp-dbo-sp-createbidfromrequest)
- [sp_CreateBidHeaderDetail](#sp-dbo-sp-createbidheaderdetail)
- [sp_CreateBidHeaderItems](#sp-dbo-sp-createbidheaderitems)
- [sp_creatediagram](#sp-dbo-sp-creatediagram)
- [sp_CreateNewBidHeader](#sp-dbo-sp-createnewbidheader)
- [sp_CreateNewDistrictReqNumber](#sp-dbo-sp-createnewdistrictreqnumber)
- [sp_CreateNewPO](#sp-dbo-sp-createnewpo)
- [sp_CreateNewRequisition](#sp-dbo-sp-createnewrequisition)
- [sp_CreateNewRequisitionV](#sp-dbo-sp-createnewrequisitionv)
- [sp_CreateNewRequisitionVendor](#sp-dbo-sp-createnewrequisitionvendor)
- [spCreateNewRequisitionVendorbk20250416](#sp-dbo-sp-createnewrequisitionvendor-bk20250416)
- [sp_CreateOrderBook](#sp-dbo-sp-createorderbook)
- [sp_CreateOrderBook03](#sp-dbo-sp-createorderbook03)
- [sp_CreateOrderBookTest](#sp-dbo-sp-createorderbooktest)
- [sp_CreatePO](#sp-dbo-sp-createpo)
- [spCreatePOSaved062724](#sp-dbo-sp-createpo-saved062724)
- [sp_CreatePOTest](#sp-dbo-sp-createpotest)
- [sp_CreateQuoteRequest](#sp-dbo-sp-createquoterequest)
- [sp_CreateQuoteRequestPrebid](#sp-dbo-sp-createquoterequestprebid)
- [sp_CreateTextBookBidRequest](#sp-dbo-sp-createtextbookbidrequest)

- [sp_CreateVendorSession](#sp-dbo-sp-createvendorsession)
- [sp_CXmlLogin](#sp-dbo-sp-cxmllogin)
- [sp_DBCheck](#sp-dbo-sp-dbcheck)
- [sp_DefragAll](#sp-dbo-sp-defragall)
- [sp_DeleteBatch](#sp-dbo-sp-deletebatch)
- [sp_DeleteBook](#sp-dbo-sp-deletebook)
- [sp_DeleteDistrictPOs](#sp-dbo-sp-deletedistrictpos)
- [sp_DeleteNoBids](#sp-dbo-sp-deletenobids)
- [sp_DeletePO](#sp-dbo-sp-deletepo)
- [sp_DeleteRequisition](#sp-dbo-sp-deleterequisition)
- [sp_DeleteRequisitionRestricted](#sp-dbo-sp-deleterequisitionrestricted)
- [sp_DeleteRequisitionWithDetail](#sp-dbo-sp-deleterequisitionwithdetail)
- [sp_DeleteZeros](#sp-dbo-sp-deletezeros)
- [sp_DistrictRequisitionDetail](#sp-dbo-sp-districtrequisitiondetail)
- [sp_dropdiagram](#sp-dbo-sp-dropdiagram)
- [sp_DSHeadings](#sp-dbo-sp-dsheadings)
- [sp_easyadd](#sp-dbo-sp-easyadd)
- [sp_EDSItems](#sp-dbo-sp-edsitems)
- [sp_EnhancedSearchItem](#sp-dbo-sp-enhancedsearchitem)
- [sp_ExportMSRPBid](#sp-dbo-sp-exportmsrpbid)
- [spFAAddUpdateAccountCode](#sp-dbo-sp-fa-addupdateaccountcode)
- [spFAApproveReq](#sp-dbo-sp-fa-approvereq)
- [spFAAttemptLogin](#sp-dbo-sp-fa-attemptlogin)
- [spFAAttemptLoginBK20241018BeforeEncryptedPassword](#sp-dbo-sp-fa-attemptlogin-bk-20241018-before-encryptedpassword)
- [spFAAvailableAccounts](#sp-dbo-sp-fa-availableaccounts)
- [spFACCAddAddendaItem](#sp-dbo-sp-fa-ccaddaddendaitem)
- [spFACCUpdateAddendaItem](#sp-dbo-sp-fa-ccupdateaddendaitem)
- [spFACreatePO](#sp-dbo-sp-fa-createpo)
- [spFACreateReportSession](#sp-dbo-sp-fa-createreportsession)
- [spFACreateReportSessionLinks](#sp-dbo-sp-fa-createreportsessionlinks)
- [spFADeleteAccount](#sp-dbo-sp-fa-deleteaccount)
- [spFADeleteRequisition](#sp-dbo-sp-fa-deleterequisition)
- [spFADeleteRequisition_bk20250416](#sp-dbo-sp-fa-deleterequisition-bk20250416)
- [spFADeleteUser](#sp-dbo-sp-fa-deleteuser)
- [spFAGetAlert](#sp-dbo-sp-fa-getalert)
- [spFAgetUserKeys](#sp-dbo-sp-fa-getuserkeys)
- [spFANewPONumbers](#sp-dbo-sp-fa-newponumbers)

- [spFANextPONumber](#sp-dbo-sp-fa-nextponumber)
- [spFARequisitionsForPurchaseOrderModal](#sp-dbo-sp-fa-requisitionsforpurchaseordermodal)
- [spFARequisitionsTotals](#sp-dbo-sp-fa-requisitionstotals)
- [spFASaveHeading](#sp-dbo-sp-fa-saveheading)
- [spFASaveKeyword](#sp-dbo-sp-fa-savekeyword)
- [spFASavePOs](#sp-dbo-sp-fa-savepos)
- [spFASaveRequisitionNote](#sp-dbo-sp-fa-saverequisitionnote)
- [spFASaveRequisitionNoteEmails](#sp-dbo-sp-fa-saverequisitionnoteemails)
- [spFASaveUser](#sp-dbo-sp-fa-saveuser)
- [spFASetBudgetAccount](#sp-dbo-sp-fa-setbudgetaccount)
- [spFASetUserAccount](#sp-dbo-sp-fa-setuseraccount)
- [spFAUpdatePOStatus](#sp-dbo-sp-fa-updatepostatus)
- [spFAUpdateRequisitionStatus](#sp-dbo-sp-fa-updaterequisitionstatus)
- [sp_FixVendorItemCode](#sp-dbo-sp-fixvendoritemcode)
- [sp_getCurrentPrices](#sp-dbo-sp-getcurrentprices)
- [sp_GetPODetailByIds](#sp-dbo-sp-getpodetailbyids)
- [sp_GetRequisitionShipping](#sp-dbo-sp-getrequisitionshipping)
- [sp_GetUserRequisitions](#sp-dbo-sp-getuserrequisitions)
- [sp_helpdiagramdefinition](#sp-dbo-sp-helpdiagramdefinition)
- [sp_helpdiagrams](#sp-dbo-sp-helpdiagrams)
- [sp_HoldRequisition](#sp-dbo-sp-holdrequisition)
- [sp_ImportVendorsBid](#sp-dbo-sp-importvendorsbid)
- [sp_IPQueueStart](#sp-dbo-sp-ipqueuestart)
- [sp_ISBNAdd](#sp-dbo-sp-isbnadd)
- [sp_Logout](#sp-dbo-sp-logout)
- [sp_MakeReq](#sp-dbo-sp-makereq)
- [sp_MasterBudgetBook](#sp-dbo-sp-masterbudgetbook)
- [sp_MergeAccounts](#sp-dbo-sp-mergeaccounts)
- [sp_MergeAwards](#sp-dbo-sp-mergeawards)
- [sp_MergeBidImports](#sp-dbo-sp-mergebidimports)
- [sp_MergeBids](#sp-dbo-sp-mergebids)
- [sp_MoveIndexes](#sp-dbo-sp-moveindexes)
- [sp_MoveReqs](#sp-dbo-sp-movereqs)
- [sp_MPIHeadings](#sp-dbo-sp-mpiheadings)
- [sp_MSRPExporter](#sp-dbo-sp-msrpexporter)
- [sp_MSRPImporter](#sp-dbo-sp-msrpimporter)
- [sp_NewReportSession](#sp-dbo-sp-newreportsession)

- [sp_NewRequisitionId](#sp-dbo-sp-newrequisitionid)
- [spNewRequisitionIdBK20250416](#sp-dbo-sp-newrequisitionid-bk20250416)
- [sp_NewUpload](#sp-dbo-sp-newupload)
- [sp_OrderBookMaint](#sp-dbo-sp-orderbookmaint)
- [sp_PAAccounts](#sp-dbo-sp-paaccounts)
- [sp_PABudgets](#sp-dbo-sp-pabudgets)
- [sp_PACategories](#sp-dbo-sp-pacategories)
- [sp_PAComet](#sp-dbo-sp-pacomet)
- [sp_PARequisitions](#sp-dbo-sp-parequisitions)
- [sp_PARequisitionsTest](#sp-dbo-sp-parequisitionstest)
- [sp_PARequisitionsTotal](#sp-dbo-sp-parequisitionstotal)
- [sp_PASchools](#sp-dbo-sp-paschools)
- [sp_PAStatus](#sp-dbo-sp-pastatus)
- [sp_PAStatusTest](#sp-dbo-sp-pastatustest)
- [sp_PAStatusTest1](#sp-dbo-sp-pastatustest1)
- [sp_PAUsers](#sp-dbo-sp-pausers)
- [sp_PODetail](#sp-dbo-sp-podetail)
- [sp_PODetailLastItemOnly](#sp-dbo-sp-podetaillastitemonly)
- [sp_PrepareNextYear](#sp-dbo-sp-preparenextyear)
- [sp_PrepTMSurvey](#sp-dbo-sp-preptmsurvey)
- [sp_ProcessCopyRequests](#sp-dbo-sp-processcopyrequests)
- [sp_processKill](#sp-dbo-sp-processkill)
- [sp_processMonitor](#sp-dbo-sp-processmonitor)
- [sp_processMonitorOrig](#sp-dbo-sp-processmonitororig)
- [sp_processStatus](#sp-dbo-sp-processstatus)
- [sp_QueueIPs](#sp-dbo-sp-queueips)
- [sp_QueueReqs](#sp-dbo-sp-queuereqs)
- [spReawardscript](#sp-dbo-sp-reaward-script)
- [sp_RefreshAccounts](#sp-dbo-sp-refreshaccounts)
- [sp_RefreshDistrictVendors](#sp-dbo-sp-refreshdistrictvendors)
- [sp_RefreshPendingApprovals](#sp-dbo-sp-refreshpendingapprovals)
- [sp_ReindexAll](#sp-dbo-sp-reindexall)
- [sp_renamediagram](#sp-dbo-sp-renamediagram)
- [sp_ReportReqData](#sp-dbo-sp-reportreqdata)
- [sp_ReqAdd](#sp-dbo-sp-reqadd)
- [sp_ResetDistrictAccountingYear](#sp-dbo-sp-resetdistrictaccountingyear)
- [sp_retrieveTagset](#sp-dbo-sp-retrievetagset)
- [sp_retrieveTagsetDMS](#sp-dbo-sp-retrievetagsetdms)

- [sp_ReturnUserReqs](#sp-dbo-sp-returnuserreqs)
- [spRTKAddReportItems](#sp-dbo-sp-rtk-addreportitems)
- [spRTKBuildMSDSand_MSDSDetail](#sp-dbo-sp-rtk-build-msds-and-msdsdetail)
- [sp_RTKExport](#sp-dbo-sp-rtkexport)
- [sp_SaveTags](#sp-dbo-sp-savetags)
- [sp_SchoolMerge](#sp-dbo-sp-schoolmerge)
- [sp_search](#sp-dbo-sp-search)
- [sp_SearchItems](#sp-dbo-sp-searchitems)
- [sp_SearchItemsByReqHK](#sp-dbo-sp-searchitemsbyreqhk)
- [sp_SessionTableUpdate](#sp-dbo-sp-sessiontableupdate)
- [sp_SetBudgetYear](#sp-dbo-sp-setbudgetyear)
- [sp_SetDistrictAndBudgetYear](#sp-dbo-sp-setdistrictandbudgetyear)
- [sp_ShowAllDefrag](#sp-dbo-sp-showalldefrag)
- [sp_ShowDistribution](#sp-dbo-sp-showdistribution)
- [sp_ShowTextbookSavings](#sp-dbo-sp-showtextbooksavings)
- [sp_SmallPOCheck](#sp-dbo-sp-smallpocheck)
- [sp_SubmitRequisition](#sp-dbo-sp-submitrequisition)
- [sp_SubmitRequisitionNew](#sp-dbo-sp-submitrequisitionnew)
- [sp_UAAccounts](#sp-dbo-sp-uaaccounts)
- [sp_UAList](#sp-dbo-sp-ualist)
- [sp_UAListTotals](#sp-dbo-sp-ualisttotals)
- [sp_UAUsers](#sp-dbo-sp-uausers)
- [sp_UnawardBidHeader](#sp-dbo-sp-unawardbidheader)
- [sp_UnpostCatalog](#sp-dbo-sp-unpostcatalog)
- [sp_UpdateAllListPrices](#sp-dbo-sp-updatealllistprices)
- [sp_UpdateAllReqs](#sp-dbo-sp-updateallreqs)
- [sp_UpdateCatalogText](#sp-dbo-sp-updatecatalogtext)
- [sp_UpdateCatalogTextPart](#sp-dbo-sp-updatecatalogtextpart)
- [sp_UpdateDetails](#sp-dbo-sp-updatedetails)
- [sp_UpdateHeading](#sp-dbo-sp-updateheading)
- [sp_UpdateISBN](#sp-dbo-sp-updateisbn)
- [sp_UpdateListPrices](#sp-dbo-sp-updatelistprices)
- [sp_UpdateMSRPItem](#sp-dbo-sp-updatemsrpitem)
- [sp_UpdateNextNumber](#sp-dbo-sp-updatenextnumber)
- [sp_UpdatePOAmounts](#sp-dbo-sp-updatepoamounts)
- [sp_UpdatePricePlan](#sp-dbo-sp-updatepriceplan)
- [sp_UpdateReq](#sp-dbo-sp-updatereq)
- [sp_UpdateReqDetail](#sp-dbo-sp-updatereqdetail)

- [sp_UpdateReqDetailItem](#sp-dbo-sp-updatereqdetailitem)
- [sp_UpdateReqDetailList](#sp-dbo-sp-updatereqdetaillist)
- [sp_UpdateReqDetailPricePlan](#sp-dbo-sp-updatereqdetailpriceplan)
- [sp_UpdateReqHeader](#sp-dbo-sp-updatereqheader)
- [sp_UpdateShippingCode](#sp-dbo-sp-updateshippingcode)
- [sp_UpdateVIC](#sp-dbo-sp-updatevic)
- [sp_upgraddiagrams](#sp-dbo-sp-upgraddiagrams)
- [sp_ValidateBidImport](#sp-dbo-sp-validatebidimport)
- [sp_ValidateForPO](#sp-dbo-sp-validateforpo)
- [sp_VendorOverride](#sp-dbo-sp-vendoroverride)
- [sp_VendorOverrideLine](#sp-dbo-sp-vendoroverrideline)
- [sp_VendorOverrideOld](#sp-dbo-sp-vendoroverrideold)
- [sp_VerifyForPO](#sp-dbo-sp-verifyforpo)
- [sp_WarningsForPO](#sp-dbo-sp-warningsforpo)
- [usp_BidMatchRefs](#sp-dbo-usp-bidmatchrefs)
- [usp_BidPageNumberUpdate](#sp-dbo-usp-bidpagenumberupdate)
- [usp_BidRanking](#sp-dbo-usp-bidranking)
- [uspBidRequestItemMergeDetailnotused](#sp-dbo-usp-bidrequestitemmergedetail-notused)
- [usp_BidRequestItemMergeDetailDavid](#sp-dbo-usp-bidrequestitemmergedetaildavid)
- [uspBidRequestItemMergeDetailDavidTestnotused](#sp-dbo-usp-bidrequestitemmergedetaildavidtest-notused)
- [uspBidRequestItemMergeDetailTempKevinnotused](#sp-dbo-usp-bidrequestitemmergedetailtempkevin-notused)
- [usp_BidRequestMergeActions](#sp-dbo-usp-bidrequestmergeactions)
- [usp_BidRequestMergeActionsUNDO-wait](#sp-dbo-usp-bidrequestmergeactionsundo-wait)
- [usp_BringAccountsForward](#sp-dbo-usp-bringaccountsforward)
- [usp_ChangeBidHeaderNumber](#sp-dbo-usp-changebidheadernumber)
- [usp_ContinuanceAcceptance](#sp-dbo-usp-continuanceacceptance)
- [usp_CopyRequisition](#sp-dbo-usp-copyrequisition)
- [usp_CreateFreightRequest](#sp-dbo-usp-createfreightrequest)
- [usp_DetailedIdentityColumnsReport](#sp-dbo-usp-detailedidentitycolumnsreport)
- [usp_EmailBlastProcessOrderDetailChangeNotifications](#sp-dbo-usp-emailblastprocessorderdetailchangenotifications)
- [usp_EmailBlastSetNotificationBlastHTMLApprover](#sp-dbo-usp-emailblastsetnotificationblasthtmlapprover)

- [usp_EmailBlastSetNotificationBlastHTMLRequisitioner](#sp-dbo-usp-emailblastsetnotificationblasthtmlrequisitioner)
- [uspEmailBlastVarsOrderDetailChangeApproverNotUsed](#sp-dbo-usp-emailblastvarsorderdetailchangeapprover-notused)
- [uspEmailBlastVarsOrderDetailChangeRequistionerNotUsed](#sp-dbo-usp-emailblastvarsorderdetailchangerequistioner-notused)
- [usp_EndPOSend](#sp-dbo-usp-endposend)
- [usp_FindEmail](#sp-dbo-usp-findemail)
- [uspFindEmailBK](#sp-dbo-usp-findemail-bk)
- [usp_GeneratePassword](#sp-dbo-usp-generatepassword)
- [uspGeneratePasswordPrint](#sp-dbo-usp-generatepassword-print)
- [usp_GetBidItemAIData](#sp-dbo-usp-getbiditemaidata)
- [usp_GetBidItemsNeedingAIUpdate](#sp-dbo-usp-getbiditemsneedingaiupdate)
- [usp_GetImageList](#sp-dbo-usp-getimagelist)
- [usp_GetItemAIData](#sp-dbo-usp-getitemaidata)
- [usp_GetItemsNeedingAIUpdate](#sp-dbo-usp-getitemsneedingaiupdate)
- [usp_GetMSDSSheets](#sp-dbo-usp-getmsdssheets)
- [usp_getMyLastYearsReqs](#sp-dbo-usp-getmylastyearsreqs)
- [usp_GetNextPONumber](#sp-dbo-usp-getnextponumber)
- [usp_GetPODetail](#sp-dbo-usp-getpodetail)
- [uspGetPODetailTest](#sp-dbo-usp-getpodetail-test)
- [usp_GetPOs](#sp-dbo-usp-getpos)
- [uspGetPOsTest](#sp-dbo-usp-getpos-test)
- [usp_getSDSDocsAll](#sp-dbo-usp-getsdsdocsall)
- [usp_getSDSDocsDistrict](#sp-dbo-usp-getsdsdocsdistrict)
- [usp_getSDSDocsSchool](#sp-dbo-usp-getsdsdocsschool)
- [usp_getSDSDocsUser](#sp-dbo-usp-getsdsdocsuser)
- [usp_getSDSheets](#sp-dbo-usp-getsdsheets)
- [usp_getSDSItems](#sp-dbo-usp-getsdsitems)
- [usp_GetSDSURLs](#sp-dbo-usp-getsdsurls)
- [usp_GetVendorPricing](#sp-dbo-usp-getvendorpricing)
- [usp_ImportUser](#sp-dbo-usp-importuser)
- [usp_MakeZ$](#sp-dbo-usp-makez$)
- [usp_MakeZC](#sp-dbo-usp-makezc)
- [usp_MissingHeaders](#sp-dbo-usp-missingheaders)
- [usp_mySDS](#sp-dbo-usp-mysds)
- [usp_OrderEZVendors](#sp-dbo-usp-orderezvendors)
- [usp_POPrintExport](#sp-dbo-usp-poprintexport)

- [usp_POStatusByRep](#sp-dbo-usp-postatusbyrep)
- [usp_POStatusByState](#sp-dbo-usp-postatusbystate)
- [usp_POStatusUpdates](#sp-dbo-usp-postatusupdates)
- [usp_QueuePOsToSend](#sp-dbo-usp-queuepostosend)
- [usp_RestoreBidHeaderNumber](#sp-dbo-usp-restorebidheadernumber)
- [usp_SavePositionData](#sp-dbo-usp-savepositiondata)
- [usp_SDSDocs](#sp-dbo-usp-sdsdocs)
- [uspSearchItemsSearchDataDB](#sp-dbo-usp-searchitems-searchdatadb)
- [usp_SearchItemsByReqHKDS](#sp-dbo-usp-searchitemsbyreqhkds)
- [uspSearchItemsByReqHKDSDavid](#sp-dbo-usp-searchitemsbyreqhkds-david)
- [usp_SearchItemsByReqHKDSDavid](#sp-dbo-usp-searchitemsbyreqhkdsdavid)
- [usp_SearchItemsByReqHKDSError](#sp-dbo-usp-searchitemsbyreqhkdserror)
- [usp_SearchItemsByReqHKDSTest](#sp-dbo-usp-searchitemsbyreqhkdstest)
- [usp_SearchVendors](#sp-dbo-usp-searchvendors)
- [usp_SetBidItemAIData](#sp-dbo-usp-setbiditemaidata)
- [usp_SetItemAIData](#sp-dbo-usp-setitemaidata)
- [usp_SetPricing](#sp-dbo-usp-setpricing)
- [uspSetPricingSearchDataDB](#sp-dbo-usp-setpricing-searchdatadb)
- [usp_ShowItemURLs](#sp-dbo-usp-showitemurls)
- [usp_StartPOSend](#sp-dbo-usp-startposend)
- [usp_StoreImage](#sp-dbo-usp-storeimage)
- [usp_StoreImageDone](#sp-dbo-usp-storeimagedone)
- [usp_StoreImageError](#sp-dbo-usp-storeimageerror)
- [usp_StoreVendorOrder](#sp-dbo-usp-storevendororder)
- [usp_TransactionLogMover](#sp-dbo-usp-transactionlogmover)
- [usp_UpdateBudgets](#sp-dbo-usp-updatebudgets)
- [usp_UpdatePONextNumber](#sp-dbo-usp-updateponextnumber)
- [usp_UpdatePONumbers](#sp-dbo-usp-updateponumbers)
- [usp_validateRequisitionStatuses](#sp-dbo-usp-validaterequisitionstatuses)
- [usp_VendorStatsCYvsLY](#sp-dbo-usp-vendorstatscyvsly)
- [usp_WaitingTasks](#sp-dbo-usp-waitingtasks)
- [x_TestErrorHandling](#sp-dbo-x-testerrorhandling)

Schema: EDSIQWebUser

- [spCCAddAddendaItemEDSIQWebuser](#sp-edsiqwebuser-sp-ccaddaddendaitem-edsiqwebuser)
- [sp_CCAddAddendaMaint](#sp-edsiqwebuser-sp-ccaddaddendamaint)

- [spCCUpdateAddendaItemEDSIQWEBUSER](#sp-edsiqwebuser-sp-ccupdateaddendaitem-edsiqwebuser)
- [sp_CCUpdateAddendaMaint](#sp-edsiqwebuser-sp-ccupdateaddendamaint)
- [sp_CombineReqs](#sp-edsiqwebuser-sp-combinereqs)
- [sp_CombineReqsNoDelete](#sp-edsiqwebuser-sp-combinereqsnodelete)
- [sp_ConvertReadyBatches](#sp-edsiqwebuser-sp-convertreadybatches)
- [sp_CopyReq](#sp-edsiqwebuser-sp-copyreq)
- [sp_CopyReqs](#sp-edsiqwebuser-sp-copyreqs)
- [sp_CoverView](#sp-edsiqwebuser-sp-coverview)
- [sp_DeleteDistrictBudgetPOs](#sp-edsiqwebuser-sp-deletedistrictbudgetpos)
- [sp_DeleteEmptyReqs](#sp-edsiqwebuser-sp-deleteemptyreqs)
- [sp_DeletePOList](#sp-edsiqwebuser-sp-deletepolist)
- [sp_DeleteRequisitionWithItems](#sp-edsiqwebuser-sp-deleterequisitionwithitems)
- [sp_MultiBatchLoad](#sp-edsiqwebuser-sp-multibatchload)
- [sp_NightlyGarbageCollection](#sp-edsiqwebuser-sp-nightlygarbagecollection)
- [sp_OrderBookCopy](#sp-edsiqwebuser-sp-orderbookcopy)
- [sp_SavingsLetter](#sp-edsiqwebuser-sp-savingsletter)
- [sp_Sys3000ToWinCap](#sp-edsiqwebuser-sp-sys3000towincap)

Schema: utility

- [Log_ProcedureCall](#sp-utility-log-procedurecall)

Stored Procedure Definitions

Schema: dbo

_sp_FA_UpdateRequisitionStatus {sp-dbo--sp-fa-updaterequisitionstatus}

> Requisition procedure for FA_UpdateStatus

Property	Value
Schema	dbo
Created	2012-06-14 00:03:50.520000
Modified	2012-06-14 00:03:50.520000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@requisitionID	int	INPUT	requisition identifier
2	@statusID	int	INPUT	status identifier

Definition

```
CREATE PROCEDURE [dbo].[_sp_FA_UpdateRequisitionStatus] @requisitionID int, @statusID int

AS

UPDATERequisitions

SETStatusID = @statusID

WHERERequisitionID = @requisitionID
```

bid2xls {sp-dbo-bid2xls}

> Stored procedure: bid2xls

Property	Value
Schema	dbo
Created	2008-08-26 14:13:13.550000
Modified	2022-07-22 13:38:02.837000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pBidHeaderId	int	INPUT	p Bid Header identifier

Definition

```
--exec bid2xls 9708

CREATE   procedure [dbo].[bid2xls] @pBidHeaderId int

as

declare @DynSql varchar(max),

@Part1 varchar(max),

@Part2 varchar(max),

@Part3 varchar(max),

--@CatalogId int,

@VendorId int,

@CatalogName varchar(50),

@VendorName varchar(50),

@BidHeaderId int,

@BHold int,

@IncludeManufacturer tinyint



select @BidHeaderId = isnull(@pBidHeaderId,0)



select @IncludeManufacturer = case when BidHeaders.CategoryId in (2,4) then 1 else 0 end

  from BidHeaders

 where BidHeaderId = @BidHeaderId
```

```
declare CatCur cursor read_only fast_forward for

select Vendors.VendorId, Vendors.Name, isnull((select top 1 bh.BidHeaderId
```

```
        from BidHeaders bh

        join BidImports on BidImports.BidHeaderId = bh.BidHeaderId

  ... (truncated)
```

bid2xlsTest {sp-dbo-bid2xlstest}

> Stored procedure: bid2xlsTest

Property	Value
Schema	dbo
Created	2014-06-26 19:37:54.140000
Modified	2018-07-23 12:40:35.540000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pBidHeaderId	int	INPUT	p Bid Header identifier

Definition

```
CREATE   procedure [dbo].[bid2xlsTest] @pBidHeaderId int

as

declare @DynSql varchar(max),

@Part1 varchar(max),

@Part2 varchar(max),

@Part3 varchar(max),

--@CatalogId int,

@VendorId int,

@CatalogName varchar(50),

@VendorName varchar(50),

@BidHeaderId int,

@BHold int,

@IncludeManufacturer tinyint



select @BidHeaderId = isnull(@pBidHeaderId,0)



select @IncludeManufacturer = case when BidHeaders.CategoryId in (2,4) then 1 else 0 end

  from BidHeaders

 where BidHeaderId = @BidHeaderId
```

```
declare CatCur cursor read_only fast_forward for

select Vendors.VendorId, Vendors.Name, isnull((select top 1 bh.BidHeaderId

      from BidHeaders bh
```

```
        join BidImports on BidImports.BidHeaderId = bh.BidHeaderId

                        and BidImports.VendorId = Vendors.VendorId

... (truncated)
```

dt_addtosourcecontrol {sp-dbo-dt-addtosourcecontrol}

> Stored procedure: dt addtosourcecontrol

Property	Value
Schema	dbo
Created	2006-08-29 12:12:36.380000
Modified	2006-08-29 12:12:36.380000
Parameters	5

Parameters

#	Parameter	Type	Direction	Description
1	@vchSourceSafeINI	varchar(255)	INPUT	vch Source Safe INI parameter
2	@vchProjectName	varchar(255)	INPUT	vch Project name
3	@vchComment	varchar(255)	INPUT	vch Comment parameter
4	@vchLoginName	varchar(255)	INPUT	vch Login name
5	@vchPassword	varchar(255)	INPUT	vch Password parameter

Definition

```
create proc dbo.dt_addtosourcecontrol

    @vchSourceSafeINI varchar(255) = '',

    @vchProjectName   varchar(255) ='',

    @vchComment       varchar(255) ='',

    @vchLoginName     varchar(255) ='',

    @vchPassword      varchar(255) =''



as



set nocount on



declare @iReturn int

declare @iObjectId int

select @iObjectId = 0



declare @iStreamObjectId int

select @iStreamObjectId = 0



declare @VSSGUID varchar(100)

select @VSSGUID = 'SQLVersionControl.VCS_SQL'



declare @vchDatabaseName varchar(255)

select @vchDatabaseName = db_name()
```

```
declare @iReturnValue int

... (truncated)
```

dt_addtosourcecontrol_u {sp-dbo-dt-addtosourcecontrol-u}

> Stored procedure: dt addtosourcecontrol u

Property	Value
Schema	dbo
Created	2006-08-29 12:12:36.473000
Modified	2006-08-29 12:12:36.473000
Parameters	5

Parameters

#	Parameter	Type	Direction	Description
1	@vchSourceSafeINI	nvarchar(255)	INPUT	vch Source Safe INI parameter
2	@vchProjectName	nvarchar(255)	INPUT	vch Project name
3	@vchComment	nvarchar(255)	INPUT	vch Comment parameter
4	@vchLoginName	nvarchar(255)	INPUT	vch Login name
5	@vchPassword	nvarchar(255)	INPUT	vch Password parameter

Definition

```
create proc dbo.dt_addtosourcecontrol_u

    @vchSourceSafeINI nvarchar(255) = '',

    @vchProjectName   nvarchar(255) ='',

    @vchComment       nvarchar(255) ='',

    @vchLoginName     nvarchar(255) ='',

    @vchPassword      nvarchar(255) =''



as

-- This procedure should no longer be called;  dt_addtosourcecontrol should be called ...

-- Calls are forwarded to dt_addtosourcecontrol to maintain backward compatibility

set nocount on

exec dbo.dt_addtosourcecontrol

@vchSourceSafeINI,

@vchProjectName,

@vchComment,

@vchLoginName,

@vchPassword
```

dt_adduserobject {sp-dbo-dt-adduserobject}

> User management procedure for dt_adduserobject

Property	Value
Schema	dbo
Created	2006-08-29 12:12:36.020000

Modified	2006-08-29 12:12:36.020000
Parameters	0

Definition

```
/*

**Add an object to the dtproperties table

*/

create procedure dbo.dt_adduserobject

as

set nocount on

/*

** Create the user object if it does not exist already

*/

begin transaction

insert dbo.dtproperties (property) VALUES ('DtgSchemaOBJECT')

update dbo.dtproperties set objectid=@@identity

where id=@@identity and property='DtgSchemaOBJECT'

commit

return @@identity
```

dt_adduserobject_vcs {sp-dbo-dt-adduserobject-vcs}

> User management procedure for dtadduserobjectvcs

Property	Value

Schema	dbo
Created	2006-08-29 12:12:36.350000
Modified	2006-08-29 12:12:36.350000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@vchProperty	varchar(64)	INPUT	vch Property parameter

Definition

```
create procedure dbo.dt_adduserobject_vcs

    @vchProperty varchar(64)



as



set nocount on



declare @iReturn int

    /*

    ** Create the user object if it does not exist already

    */

    begin transaction

        select @iReturn = objectid from dbo.dtproperties where property = @vchProperty

        if @iReturn IS NULL

        begin

            insert dbo.dtproperties (property) VALUES (@vchProperty)

            update dbo.dtproperties set objectid=@@identity

                    where id=@@identity and property=@vchProperty

            select @iReturn = @@identity

        end

    commit

    return @iReturn
```

dt_checkinobject {sp-dbo-dt-checkinobject}

> Check/verify procedure for dt_checkinobject

Property	Value
Schema	dbo
Created	2006-08-29 12:12:36.397000
Modified	2006-08-29 12:12:36.397000
Parameters	10

Parameters

#	Parameter	Type	Direction	Description
1	@chObjectType	char(4)	INPUT	ch Object type
2	@vchObjectName	varchar(255)	INPUT	vch Object name
3	@vchComment	varchar(255)	INPUT	vch Comment parameter
4	@vchLoginName	varchar(255)	INPUT	vch Login name
5	@vchPassword	varchar(255)	INPUT	vch Password parameter
6	@iVCSFlags	int	INPUT	i VCSFlags parameter
7	@iActionFlag	int	INPUT	i Action flag
8	@txStream1	text	INPUT	tx Stream1 parameter
9	@txStream2	text	INPUT	tx Stream2 parameter
10	@txStream3	text	INPUT	tx Stream3 parameter

Definition

```
create proc dbo.dt_checkinobject

    @chObjectType  char(4),

    @vchObjectName varchar(255),

    @vchComment    varchar(255)='',

    @vchLoginName  varchar(255),

    @vchPassword   varchar(255)='',

    @iVCSFlags     int = 0,

    @iActionFlag   int = 0,   /* 0 => AddFile, 1 => CheckIn */

    @txStream1     Text = '', /* drop stream   */ /* There is a bug that if items are N...

    @txStream2     Text = '', /* create stream */

    @txStream3     Text = ''  /* grant stream  */




as



set nocount on



declare @iReturn int

declare @iObjectId int

select @iObjectId = 0

declare @iStreamObjectId int



declare @VSSGUID varchar(100)
```

```
select @VSSGUID = 'SQLVersionControl.VCS_SQL'


... (truncated)
```

dt_checkinobject_u {sp-dbo-dt-checkinobject-u}

> Check/verify procedure for dtcheckinobjectu

Property	Value
Schema	dbo
Created	2006-08-29 12:12:36.490000
Modified	2006-08-29 12:12:36.490000
Parameters	10

Parameters

#	Parameter	Type	Direction	Description
1	@chObjectType	char(4)	INPUT	ch Object type
2	@vchObjectName	nvarchar(255)	INPUT	vch Object name
3	@vchComment	nvarchar(255)	INPUT	vch Comment parameter
4	@vchLoginName	nvarchar(255)	INPUT	vch Login name
5	@vchPassword	nvarchar(255)	INPUT	vch Password parameter
6	@iVCSFlags	int	INPUT	i VCSFlags parameter
7	@iActionFlag	int	INPUT	i Action flag
8	@txStream1	text	INPUT	tx Stream1 parameter
9	@txStream2	text	INPUT	tx Stream2 parameter
10	@txStream3	text	INPUT	tx Stream3 parameter

Definition

```
create proc dbo.dt_checkinobject_u

    @chObjectType  char(4),

    @vchObjectName nvarchar(255),

    @vchComment    nvarchar(255)='',

    @vchLoginName  nvarchar(255),

    @vchPassword   nvarchar(255)='',

    @iVCSFlags     int = 0,

    @iActionFlag   int = 0,   /* 0 => AddFile, 1 => CheckIn */

    @txStream1     text = '',  /* drop stream   */ /* There is a bug that if items are ...

    @txStream2     text = '',  /* create stream */

    @txStream3     text = ''   /* grant stream  */



as

-- This procedure should no longer be called;  dt_checkinobject should be called instead.

-- Calls are forwarded to dt_checkinobject to maintain backward compatibility.

set nocount on

exec dbo.dt_checkinobject

@chObjectType,

@vchObjectName,

@vchComment,

@vchLoginName,

@vchPassword,

@iVCSFlags,
```

```
@iActionFlag,

@txStream1,

... (truncated)
```

dt_checkoutobject {sp-dbo-dt-checkoutobject}

> Check/verify procedure for dt_checkoutobject

Property	Value
Schema	dbo
Created	2006-08-29 12:12:36.427000
Modified	2006-08-29 12:12:36.427000
Parameters	7

Parameters

#	Parameter	Type	Direction	Description
1	@chObjectType	char(4)	INPUT	ch Object type
2	@vchObjectName	varchar(255)	INPUT	vch Object name
3	@vchComment	varchar(255)	INPUT	vch Comment parameter
4	@vchLoginName	varchar(255)	INPUT	vch Login name
5	@vchPassword	varchar(255)	INPUT	vch Password parameter
6	@iVCSFlags	int	INPUT	i VCSFlags parameter
7	@iActionFlag	int	INPUT	i Action flag

Definition

```
create proc dbo.dt_checkoutobject

    @chObjectType  char(4),

    @vchObjectName varchar(255),

    @vchComment    varchar(255),

    @vchLoginName  varchar(255),

    @vchPassword   varchar(255),

    @iVCSFlags     int = 0,

    @iActionFlag   int = 0/* 0 => Checkout, 1 => GetLatest, 2 => UndoCheckOut */



as



set nocount on



declare @iReturn int

declare @iObjectId int

select @iObjectId =0



declare @VSSGUID varchar(100)

select @VSSGUID = 'SQLVersionControl.VCS_SQL'
```

```
declare @iReturnValue int

select @iReturnValue = 0
```

```
declare @vchTempText varchar(255)
```

```
... (truncated)
```

dt_checkoutobject_u {sp-dbo-dt-checkoutobject-u}

> Check/verify procedure for dtcheckoutobjectu

Property	Value
Schema	dbo
Created	2006-08-29 12:12:36.507000
Modified	2006-08-29 12:12:36.507000
Parameters	7

Parameters

#	Parameter	Type	Direction	Description
1	@chObjectType	char(4)	INPUT	ch Object type
2	@vchObjectName	nvarchar(255)	INPUT	vch Object name
3	@vchComment	nvarchar(255)	INPUT	vch Comment parameter
4	@vchLoginName	nvarchar(255)	INPUT	vch Login name
5	@vchPassword	nvarchar(255)	INPUT	vch Password parameter
6	@iVCSFlags	int	INPUT	i VCSFlags parameter
7	@iActionFlag	int	INPUT	i Action flag

Definition

```
create proc dbo.dt_checkoutobject_u

    @chObjectType  char(4),

    @vchObjectName nvarchar(255),

    @vchComment    nvarchar(255),

    @vchLoginName  nvarchar(255),

    @vchPassword   nvarchar(255),

    @iVCSFlags     int = 0,

    @iActionFlag   int = 0/* 0 => Checkout, 1 => GetLatest, 2 => UndoCheckOut */



as



-- This procedure should no longer be called;  dt_checkoutobject should be called inst...

-- Calls are forwarded to dt_checkoutobject to maintain backward compatibility.

set nocount on

exec dbo.dt_checkoutobject

@chObjectType,

@vchObjectName,

@vchComment,

@vchLoginName,

@vchPassword,

@iVCSFlags,

@iActionFlag
```

dt_displayoaerror {sp-dbo-dt-displayoaerror}

> Stored procedure: dt displayoaerror

Property	Value
Schema	dbo
Created	2006-08-29 12:12:36.333000
Modified	2006-08-29 12:12:36.333000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@iObject	int	INPUT	i Object parameter
2	@iresult	int	INPUT	iresult parameter

Definition

```
CREATE PROCEDURE dbo.dt_displayoaerror

    @iObject int,

    @iresult int

as



set nocount on



declare @vchOutput      varchar(255)

declare @hr             int

declare @vchSource      varchar(255)

declare @vchDescription varchar(255)



    exec @hr = master.dbo.sp_OAGetErrorInfo @iObject, @vchSource OUT, @vchDescription OUT



    select @vchOutput = @vchSource + ': ' + @vchDescription

    raiserror (@vchOutput,16,-1)



    return
```

dt_displayoaerror_u {sp-dbo-dt-displayoaerror-u}

> Stored procedure: dt displayoaerror u

Property	Value
Schema	dbo

Created	2006-08-29 12:12:36.473000
Modified	2006-08-29 12:12:36.473000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@iObject	int	INPUT	i Object parameter
2	@iresult	int	INPUT	iresult parameter

Definition

```
CREATE PROCEDURE dbo.dt_displayoaerror_u

    @iObject int,

    @iresult int

as

-- This procedure should no longer be called;  dt_displayoaerror should be called inst...

-- Calls are forwarded to dt_displayoaerror to maintain backward compatibility.

set nocount on

exec dbo.dt_displayoaerror

@iObject,

@iresult
```

dt_droppropertiesbyid {sp-dbo-dt-droppropertiesbyid}

> Stored procedure: dt droppropertiesbyid

Property	Value
Schema	dbo

Created	2006-08-29 12:12:36.303000
Modified	2006-08-29 12:12:36.303000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@id	int	INPUT	id parameter
2	@property	varchar(64)	INPUT	property parameter

Definition

```
/*

**Drop one or all the associated properties of an object or an attribute

**

**dt_dropproperties objid, null or '' -- drop all properties of the object itself

**dt_dropproperties objid, property -- drop the property

*/

create procedure dbo.dt_droppropertiesbyid

@id int,

@property varchar(64)

as

set nocount on



if (@property is null) or (@property = '')

delete from dbo.dtproperties where objectid=@id

else

delete from dbo.dtproperties

where objectid=@id and property=@property
```

dt_dropuserobjectbyid {sp-dbo-dt-dropuserobjectbyid}

> User management procedure for dt_dropuserobjectbyid

Property	Value
Schema	dbo
Created	2006-08-29 12:12:36.287000

Modified	2006-08-29 12:12:36.287000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@id	int	INPUT	id parameter

Definition

```
/*

**Drop an object from the dbo.dtproperties table

*/

create procedure dbo.dt_dropuserobjectbyid

@id int

as

set nocount on

delete from dbo.dtproperties where objectid=@id
```

dt_generateansiname {sp-dbo-dt-generateansiname}

> Stored procedure: dt generateansiname

Property	Value
Schema	dbo
Created	2006-08-29 12:12:35.927000
Modified	2006-08-29 12:12:35.927000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@name	varchar(255)	OUTPUT	name parameter

Definition

```
/*
**Generate an ansi name that is unique in the dtproperties.value column
*/
create procedure dbo.dt_generateansiname(@name varchar(255) output)
as
declare @prologue varchar(20)
declare @indexstring varchar(20)
declare @index integer


set @prologue = 'MSDT-A-'
set @index = 1


while 1 = 1
begin
set @indexstring = cast(@index as varchar(20))
set @name = @prologue + @indexstring
if not exists (select value from dtproperties where value = @name)
break


set @index = @index + 1


if (@index = 10000)
goto TooMany
```

```
end


... (truncated)
```

dt_getobjwithprop {sp-dbo-dt-getobjwithprop}

> Stored procedure: dt getobjwithprop

Property	Value
Schema	dbo
Created	2006-08-29 12:12:36.113000
Modified	2006-08-29 12:12:36.113000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@property	varchar(30)	INPUT	property parameter
2	@value	varchar(255)	INPUT	value parameter

Definition

```
/*
**Retrieve the owner object(s) of a given property
*/
create procedure dbo.dt_getobjwithprop
@property varchar(30),
@value varchar(255)
as
set nocount on


if (@property is null) or (@property = '')
begin
raiserror('Must specify a property name.',-1,-1)
return (1)
end


if (@value is null)
select objectid id from dbo.dtproperties
where property=@property


else
select objectid id from dbo.dtproperties
where property=@property and value=@value
```

dt_getobjwithprop_u {sp-dbo-dt-getobjwithprop-u}

> Stored procedure: dt getobjwithprop u

Property	Value
Schema	dbo
Created	2006-08-29 12:12:36.240000
Modified	2006-08-29 12:12:36.240000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@property	varchar(30)	INPUT	property parameter
2	@uvalue	nvarchar(255)	INPUT	uvalue parameter

Definition

```
/*
**Retrieve the owner object(s) of a given property
*/
create procedure dbo.dt_getobjwithprop_u
@property varchar(30),
@uvalue nvarchar(255)
as
set nocount on


if (@property is null) or (@property = '')
begin
raiserror('Must specify a property name.',-1,-1)
return (1)
end


if (@uvalue is null)
select objectid id from dbo.dtproperties
where property=@property


else
select objectid id from dbo.dtproperties
where property=@property and uvalue=@uvalue
```

dt_getpropertiesbyid {sp-dbo-dt-getpropertiesbyid}

> Stored procedure: dt getpropertiesbyid

Property	Value
Schema	dbo
Created	2006-08-29 12:12:36.160000
Modified	2006-08-29 12:12:36.160000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@id	int	INPUT	id parameter
2	@property	varchar(64)	INPUT	property parameter

Definition

```
/*

**Retrieve properties by id's

**

**dt_getproperties objid, null or '' -- retrieve all properties of the object itself

**dt_getproperties objid, property -- retrieve the property specified

*/

create procedure dbo.dt_getpropertiesbyid

@id int,

@property varchar(64)

as

set nocount on



if (@property is null) or (@property = '')

select property, version, value, lvalue

from dbo.dtproperties

where  @id=objectid

else

select property, version, value, lvalue

from dbo.dtproperties

where  @id=objectid and @property=property
```

dt_getpropertiesbyid_u {sp-dbo-dt-getpropertiesbyid-u}

> Stored procedure: dt getpropertiesbyid u

Property	Value
Schema	dbo
Created	2006-08-29 12:12:36.270000
Modified	2006-08-29 12:12:36.270000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@id	int	INPUT	id parameter
2	@property	varchar(64)	INPUT	property parameter

Definition

```
/*

**Retrieve properties by id's

**

**dt_getproperties objid, null or '' -- retrieve all properties of the object itself

**dt_getproperties objid, property -- retrieve the property specified

*/

create procedure dbo.dt_getpropertiesbyid_u

@id int,

@property varchar(64)

as

set nocount on



if (@property is null) or (@property = '')

select property, version, uvalue, lvalue

from dbo.dtproperties

where  @id=objectid

else

select property, version, uvalue, lvalue

from dbo.dtproperties

where  @id=objectid and @property=property
```

dt_getpropertiesbyid_vcs {sp-dbo-dt-getpropertiesbyid-vcs}

> Stored procedure: dt getpropertiesbyid vcs

Property	Value
Schema	dbo
Created	2006-08-29 12:12:36.333000
Modified	2006-08-29 12:12:36.333000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@id	int	INPUT	id parameter
2	@property	varchar(64)	INPUT	property parameter
3	@value	varchar(255)	OUTPUT	value parameter

Definition

```
create procedure dbo.dt_getpropertiesbyid_vcs

    @id       int,

    @property varchar(64),

    @value    varchar(255) = NULL OUT



as



    set nocount on



    select @value = (

        select value

                from dbo.dtproperties

                where @id=objectid and @property=property

                )
```

dt_getpropertiesbyid_vcs_u {sp-dbo-dt-getpropertiesbyid-vcs-u}

> Stored procedure: dt getpropertiesbyid vcs u

Property	Value
Schema	dbo
Created	2006-08-29 12:12:36.473000
Modified	2006-08-29 12:12:36.473000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@id	int	INPUT	id parameter
2	@property	varchar(64)	INPUT	property parameter
3	@value	nvarchar(255)	OUTPUT	value parameter

Definition

```
create procedure dbo.dt_getpropertiesbyid_vcs_u

    @id       int,

    @property varchar(64),

    @value    nvarchar(255) = NULL OUT



as



    -- This procedure should no longer be called;  dt_getpropertiesbyid_vcsshould be ca...

-- Calls are forwarded to dt_getpropertiesbyid_vcs to maintain backward compatibility.

set nocount on

    exec dbo.dt_getpropertiesbyid_vcs

@id,

@property,

@value output
```

dt_isundersourcecontrol {sp-dbo-dt-isundersourcecontrol}

> Stored procedure: dt isundersourcecontrol

Property	Value
Schema	dbo
Created	2006-08-29 12:12:36.443000
Modified	2006-08-29 12:12:36.443000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@vchLoginName	varchar(255)	INPUT	vch Login name
2	@vchPassword	varchar(255)	INPUT	vch Password parameter
3	@iWhoToo	int	INPUT	i Who Too parameter

Definition

```
create proc dbo.dt_isundersourcecontrol

    @vchLoginName varchar(255) = '',

    @vchPassword  varchar(255) = '',

    @iWhoToo      int = 0 /* 0 => Just check project; 1 => get list of objs */



as



set nocount on



declare @iReturn int

declare @iObjectId int

select @iObjectId = 0



declare @VSSGUID varchar(100)

select @VSSGUID = 'SQLVersionControl.VCS_SQL'



declare @iReturnValue int

select @iReturnValue = 0



declare @iStreamObjectId int

select @iStreamObjectId   = 0



declare @vchTempText varchar(255)
```

```
    declare @iPropertyObjectId int

... (truncated)
```

dt_isundersourcecontrol_u {sp-dbo-dt-isundersourcecontrol-u}

> Stored procedure: dt isundersourcecontrol u

Property	Value
Schema	dbo
Created	2006-08-29 12:12:36.507000
Modified	2006-08-29 12:12:36.507000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@vchLoginName	nvarchar(255)	INPUT	vch Login name
2	@vchPassword	nvarchar(255)	INPUT	vch Password parameter
3	@iWhoToo	int	INPUT	i Who Too parameter

Definition

```
create proc dbo.dt_isundersourcecontrol_u

    @vchLoginName nvarchar(255) = '',

    @vchPassword  nvarchar(255) = '',

    @iWhoToo      int = 0 /* 0 => Just check project; 1 => get list of objs */



as

-- This procedure should no longer be called;  dt_isundersourcecontrol should be calle...

-- Calls are forwarded to dt_isundersourcecontrol to maintain backward compatibility.

set nocount on

exec dbo.dt_isundersourcecontrol

@vchLoginName,

@vchPassword,

@iWhoToo
```

dt_removefromsourcecontrol {sp-dbo-dt-removefromsourcecontrol}

> Move procedure for dt_removefromsourcecontrol

Property	Value
Schema	dbo
Created	2006-08-29 12:12:36.460000
Modified	2006-08-29 12:12:36.460000
Parameters	0

Definition

```
create procedure dbo.dt_removefromsourcecontrol



as



    set nocount on



    declare @iPropertyObjectId int

    select @iPropertyObjectId = (select objectid from dbo.dtproperties where property =...



    exec dbo.dt_droppropertiesbyid @iPropertyObjectId, null



    /* -1 is returned by dt_droppopertiesbyid */

    if @@error <> 0 and @@error <> -1 return 1



    return 0
```

dt_setpropertybyid {sp-dbo-dt-setpropertybyid}

> Stored procedure: dt setpropertybyid

Property	Value
Schema	dbo
Created	2006-08-29 12:12:36.083000
Modified	2006-08-29 12:12:36.083000
Parameters	4

Parameters

#	Parameter	Type	Direction	Description
1	@id	int	INPUT	id parameter
2	@property	varchar(64)	INPUT	property parameter
3	@value	varchar(255)	INPUT	value parameter
4	@lvalue	image	INPUT	lvalue parameter

Definition

```
/*

**If the property already exists, reset the value; otherwise add property

**id -- the id in sysobjects of the object

**property -- the name of the property

**value -- the text value of the property

**lvalue -- the binary value of the property (image)

*/

create procedure dbo.dt_setpropertybyid

@id int,

@property varchar(64),

@value varchar(255),

@lvalue image

as

set nocount on

declare @uvalue nvarchar(255)

set @uvalue = convert(nvarchar(255), @value)

if exists (select * from dbo.dtproperties

where objectid=@id and property=@property)

begin

--

-- bump the version count for this row as we update it

--

update dbo.dtproperties set value=@value, uvalue=@uvalue, lvalue=@lvalue, version=ver...
```

```
where objectid=@id and property=@property

end

... (truncated)
```

dt_setpropertybyid_u {sp-dbo-dt-setpropertybyid-u}

> Stored procedure: dt setpropertybyid u

Property	Value
Schema	dbo
Created	2006-08-29 12:12:36.210000
Modified	2006-08-29 12:12:36.210000
Parameters	4

Parameters

#	Parameter	Type	Direction	Description
1	@id	int	INPUT	id parameter
2	@property	varchar(64)	INPUT	property parameter
3	@uvalue	nvarchar(255)	INPUT	uvalue parameter
4	@lvalue	image	INPUT	lvalue parameter

Definition

```
/*

**If the property already exists, reset the value; otherwise add property

**id -- the id in sysobjects of the object

**property -- the name of the property

**uvalue -- the text value of the property

**lvalue -- the binary value of the property (image)

*/

create procedure dbo.dt_setpropertybyid_u

@id int,

@property varchar(64),

@uvalue nvarchar(255),

@lvalue image

as

set nocount on

--

-- If we are writing the name property, find the ansi equivalent.

-- If there is no lossless translation, generate an ansi name.

--

declare @avalue varchar(255)

set @avalue = null
```

```
if (@uvalue is not null)

begin

if (convert(nvarchar(255), convert(varchar(255), @uvalue)) = @uvalue)
```

```
begin

set @avalue = convert(varchar(255), @uvalue)

... (truncated)
```

dt_validateloginparams {sp-dbo-dt-validateloginparams}

> Login/authentication procedure for dt_validateloginparams

Property	Value
Schema	dbo
Created	2006-08-29 12:12:36.460000
Modified	2006-08-29 12:12:36.460000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@vchLoginName	varchar(255)	INPUT	vch Login name
2	@vchPassword	varchar(255)	INPUT	vch Password parameter

Definition

```
create proc dbo.dt_validateloginparams

    @vchLoginName  varchar(255),

    @vchPassword   varchar(255)

as



set nocount on



declare @iReturn int

declare @iObjectId int

select @iObjectId =0



declare @VSSGUID varchar(100)

select @VSSGUID = 'SQLVersionControl.VCS_SQL'



    declare @iPropertyObjectId int

    select @iPropertyObjectId = (select objectid from dbo.dtproperties where property =...



    declare @vchSourceSafeINI varchar(255)

    exec dbo.dt_getpropertiesbyid_vcs @iPropertyObjectId, 'VCSSourceSafeINI', @vchSourc...
```

```
    exec @iReturn = master.dbo.sp_OACreate @VSSGUID, @iObjectId OUT

    if @iReturn <> 0 GOTO E_OAError
```

```
    exec @iReturn = master.dbo.sp_OAMethod @iObjectId,

'ValidateLoginParams',

... (truncated)
```

dt_validateloginparams_u {sp-dbo-dt-validateloginparams-u}

> Login/authentication procedure for dtvalidateloginparamsu

Property	Value
Schema	dbo
Created	2006-08-29 12:12:36.507000
Modified	2006-08-29 12:12:36.507000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@vchLoginName	nvarchar(255)	INPUT	vch Login name
2	@vchPassword	nvarchar(255)	INPUT	vch Password parameter

Definition

```
create proc dbo.dt_validateloginparams_u

    @vchLoginName  nvarchar(255),

    @vchPassword   nvarchar(255)

as



-- This procedure should no longer be called;  dt_validateloginparams should be called...

-- Calls are forwarded to dt_validateloginparams to maintain backward compatibility.

set nocount on

exec dbo.dt_validateloginparams

@vchLoginName,

@vchPassword
```

dt_vcsenabled {sp-dbo-dt-vcsenabled}

> Stored procedure: dt vcsenabled

Property	Value
Schema	dbo
Created	2006-08-29 12:12:36.460000
Modified	2006-08-29 12:12:36.460000
Parameters	0

Definition

```
create proc dbo.dt_vcsenabled



as



set nocount on



declare @iObjectId int

select @iObjectId = 0



declare @VSSGUID varchar(100)

select @VSSGUID = 'SQLVersionControl.VCS_SQL'



    declare @iReturn int

    exec @iReturn = master.dbo.sp_OACreate @VSSGUID, @iObjectId OUT

    if @iReturn <> 0 raiserror('', 16, -1) /* Can't Load Helper DLLC */
```

dt_verstamp006 {sp-dbo-dt-verstamp006}

> Stored procedure: dt verstamp006

Property	Value
Schema	dbo
Created	2006-08-29 12:12:36.317000
Modified	2006-08-29 12:12:36.317000
Parameters	0

Definition

```
/*

**This procedure returns the version number of the stored

**    procedures used by legacy versions of the Microsoft

**Visual Database Tools.  Version is 7.0.00.

*/

create procedure dbo.dt_verstamp006

as

select 7000
```

dt_verstamp007 {sp-dbo-dt-verstamp007}

> Stored procedure: dt verstamp007

Property	Value
Schema	dbo
Created	2006-08-29 12:12:36.317000
Modified	2006-08-29 12:12:36.317000
Parameters	0

Definition

```
/*

**This procedure returns the version number of the stored

**    procedures used by the the Microsoft Visual Database Tools.

**Version is 7.0.05.

*/

create procedure dbo.dt_verstamp007

as

select 7005
```

dt_whocheckedout {sp-dbo-dt-whocheckedout}

> Check/verify procedure for dt_whocheckedout

Property	Value
Schema	dbo
Created	2006-08-29 12:12:36.473000
Modified	2006-08-29 12:12:36.473000
Parameters	4

Parameters

#	Parameter	Type	Direction	Description
1	@chObjectType	char(4)	INPUT	ch Object type
2	@vchObjectName	varchar(255)	INPUT	vch Object name
3	@vchLoginName	varchar(255)	INPUT	vch Login name
4	@vchPassword	varchar(255)	INPUT	vch Password parameter

Definition

```
create proc dbo.dt_whocheckedout

        @chObjectType  char(4),

        @vchObjectName varchar(255),

        @vchLoginName  varchar(255),

        @vchPassword   varchar(255)



as



set nocount on



declare @iReturn int

declare @iObjectId int

select @iObjectId =0



declare @VSSGUID varchar(100)

select @VSSGUID = 'SQLVersionControl.VCS_SQL'



    declare @iPropertyObjectId int



    select @iPropertyObjectId = (select objectid from dbo.dtproperties where property =...
```

```
    declare @vchProjectName   varchar(255)

    declare @vchSourceSafeINI varchar(255)
```

```
    declare @vchServerName    varchar(255)

    declare @vchDatabaseName  varchar(255)

... (truncated)
```

dt_whocheckedout_u {sp-dbo-dt-whocheckedout-u}

> Check/verify procedure for dtwhocheckedoutu

Property	Value
Schema	dbo
Created	2006-08-29 12:12:36.520000
Modified	2006-08-29 12:12:36.520000
Parameters	4

Parameters

#	Parameter	Type	Direction	Description
1	@chObjectType	char(4)	INPUT	ch Object type
2	@vchObjectName	nvarchar(255)	INPUT	vch Object name
3	@vchLoginName	nvarchar(255)	INPUT	vch Login name
4	@vchPassword	nvarchar(255)	INPUT	vch Password parameter

Definition

```
create proc dbo.dt_whocheckedout_u

        @chObjectType  char(4),

        @vchObjectName nvarchar(255),

        @vchLoginName  nvarchar(255),

        @vchPassword   nvarchar(255)



as



-- This procedure should no longer be called;  dt_whocheckedout should be called instead.

-- Calls are forwarded to dt_whocheckedout to maintain backward compatibility.

set nocount on

exec dbo.dt_whocheckedout

@chObjectType,

@vchObjectName,

@vchLoginName,

@vchPassword
```

sp_AddDistrict {sp-dbo-sp-adddistrict}

> Add new record to AddDistrict

Property	Value
Schema	dbo
Created	2001-10-08 22:30:33.253000
Modified	2022-07-21 13:12:26.847000
Parameters	21

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pDistrictId	int	INPUT	p District identifier
3	@pDistrictCode	varchar(255)	INPUT	p District code
4	@pDistrictName	varchar(50)	INPUT	p District name
5	@pDistrictAddr1	varchar(255)	INPUT	p District Addr1 parameter
6	@pDistrictAddr2	varchar(255)	INPUT	p District Addr2 parameter
7	@pDistrictAddr3	varchar(255)	INPUT	p District Addr3 parameter
8	@pDistrictCity	varchar(255)	INPUT	p District City parameter
9	@pDistrictState	varchar(255)	INPUT	p District State parameter
10	@pDistrictZip	varchar(255)	INPUT	p District Zip parameter
11	@pPhoneNumber	varchar(255)	INPUT	p Phone number
12	@pFax	varchar(255)	INPUT	p Fax parameter
13	@pEMail	varchar(255)	INPUT	p EMail parameter
14	@pNextCometId	int	INPUT	p Next Comet identifier
15	@pApprovalLevel	int	INPUT	p Approval Level parameter
16	@pBAName	varchar(255)	INPUT	p BA name
17	@pUseGrossPrices	tinyint	INPUT	p Use Gross Prices parameter
18	@pPOLayoutId	int	INPUT	p POLayout identifier
19	@pAccountingForm	int	INPUT	p Accounting Format identifier
20	@pTextbookPercen	varchar(255)	INPUT	p Textbook Percentage parameter
21	@rDistrictId	int	OUTPUT	r District identifier

Definition

```
CREATE procedure [dbo].[sp_AddDistrict] @pSessionId int, @pDistrictId int, @pDistrictCo...



declare @DistrictId int,

@ShippingId int,

@UserId int,

@CSRepId int,

@BudgetId int,

@NextCometId int,

@StartDate datetime,

@EndDate datetime,

@TextbookPercentage decimal(9,5)



if rtrim(@pTextbookPercentage) = ''

begin

  select @pTextbookPercentage = '0.0'

end



select @TextbookPercentage = convert(decimal(9,5),@pTextbookPercentage)



select @DistrictId = ISNULL(SessionTable.DistrictId,0),

       @UserId = ISNULL(SessionTable.UserId,0),

       @CSRepId = ISNULL(CSRep.CSRepId,0)

  from SessionTable
```

```
    full join CSRep on CSRep.UserId = SessionTable.UserId

   where SessionTable.SessionId = @pSessionId

  ... (truncated)
```

sp_AddISBN {sp-dbo-sp-addisbn}

> Add new record to AddISBN

Property	Value
Schema	dbo
Created	2002-04-30 23:32:40.577000
Modified	2013-01-28 22:25:07.427000
Parameters	10

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pISBN	varchar(255)	INPUT	p ISBN parameter
3	@pTitle	varchar(255)	INPUT	p Title parameter
4	@pCopyrightYear	int	INPUT	p Copyright Year parameter
5	@pEditionId	int	INPUT	p Edition identifier
6	@pPublisherId	int	INPUT	p Publisher identifier
7	@pPublisherCost	varchar(255)	INPUT	p Publisher Cost parameter
8	@pRequisitionId	int	INPUT	p Requisition identifier
9	@pQuantity	int	INPUT	p quantity
10	@rItemId	int	OUTPUT	r Item identifier

Definition

```
CREATE           procedure [dbo].[sp_AddISBN] @pSessionId int, @pISBN varchar(255), @pT...



declare @ItemId int,

@CategoryId int,

@UnitId int,

@CrossRefId int,

@Active tinyint,

@PublisherCost money,

@UserLevel int



select @UserLevel = ApprovalLevel

  from SessionTable

 where SessionId = @pSessionId



select @CategoryId = Category.CategoryId

  from Category

  join Requisitions on Requisitions.CategoryId = Category.CategoryId

 where Requisitions.RequisitionId = @pRequisitionId

   and Category.Type = 2
```

```
select @UnitId = UnitId

  from Units

 where Code = 'BOOK'
```

```
    and Active = 1


... (truncated)
```

sp_AddMSRPItem {sp-dbo-sp-addmsrpitem}

> Add new record to AddMSRP

Property	Value
Schema	dbo
Created	2013-05-30 13:26:57.150000
Modified	2015-11-24 23:37:40.343000
Parameters	13

Parameters

#	Parameter	Type	Direction	Description
1	@pDescription	varchar(1024)	INPUT	p description
2	@pUnitId	int	INPUT	p Unit identifier
3	@pManufacturerId	int	INPUT	p Manufacturer identifier
4	@pManufacturerNu	varchar(50)	INPUT	p Manufacturer number
5	@pVendorId	int	INPUT	p Vendor identifier
6	@pVendorPartNuml	varchar(50)	INPUT	p Vendor Part number
7	@pItemsPerUnit	varchar(50)	INPUT	p Items Per Unit parameter
8	@pListPrice	money	INPUT	p List price
9	@pRequisitionId	int	INPUT	p Requisition identifier
10	@pQuantity	int	INPUT	p quantity
11	@sessionID	int	INPUT	session identifier
12	@pBidderToSupply\	tinyint	INPUT	p Bidder To Supply Vendor Part Nbr
13	@pExtraDescriptior	varchar(1024)	INPUT	p Extra description

Definition

```
CREATE procedure [dbo].[sp_AddMSRPItem] @pDescription varchar(1024),

                                        @pUnitId int, @pManufacturerId int, @pManufacture...

                                        @pVendorPartNumber varchar(50), @pItemsPerUnit va...

                                        @pRequisitionId int, @pQuantity int, @sessionID i...

, @pExtraDescription varchar(1024)

as



declare @NextNumber varchar(50),

@DistrictCode varchar(16),

@DistrictId int,

@CategoryId int,

@ItemId int,

@UnitCode varchar(16),

@PricePlanId int,

@CatalogId int



  select @DistrictCode = isnull(District.DistrictCode,''),

         @DistrictId = isnull(District.DistrictId,0),

         @CategoryId = isnull(Requisitions.CategoryId,0),

         @CatalogId = isnull(Catalog.CatalogId,0)

    from dbo.Requisitions

    join dbo.Users on Users.UserId = Requisitions.UserId
```

```
        join dbo.District on District.DistrictId = Users.DistrictId

        left outer join Catalog on Catalog.CategoryId = Requisitions.CategoryId

                                and Catalog.Active = 1

    ... (truncated)
```

sp_AddPPCatalog {sp-dbo-sp-addppcatalog}

> Add new record to AddPP

Property	Value
Schema	dbo
Created	2001-10-15 02:26:56.630000
Modified	2009-03-25 06:55:28.380000
Parameters	6

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pPPCatalogId	int	INPUT	p PPCatalog identifier
3	@pPricePlanId	int	INPUT	p Price Plan identifier
4	@pCategoryId	int	INPUT	p Category identifier
5	@pCatalogId	int	INPUT	p Catalog identifier
6	@pDiscountRate	varchar(255)	INPUT	p Discount Rate parameter

Definition

```
CREATE      procedure sp_AddPPCatalog @pSessionId int, @pPPCatalogId int, @pPricePlanId...



declare @DiscountRate money



select @DiscountRate = convert(money,@pDiscountRate)



if @pPPCatalogId = 0

begin

  insert PPCatalogs (PricePlanId, CatalogId, CategoryId, DiscountRate)

    values (@pPricePlanId, @pCatalogId, @pCategoryId, @DiscountRate)

end

else

begin

  if @pCatalogId = 0

  begin

    delete PPCatalogs

     where PPCatalogId = @pPPCatalogId

  end

  else

  begin

    Update PPCatalogs

       set DiscountRate = @DiscountRate

     where PPCatalogId = @pPPCatalogId
```

```
    end

  end

  ... (truncated)
```

sp_AddPricePlan {sp-dbo-sp-addpriceplan}

> Add new record to AddPlan

Property	Value
Schema	dbo
Created	2001-10-16 16:00:17.980000
Modified	2009-03-25 06:55:28.410000
Parameters	4

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pPricePlanId	int	INPUT	p Price Plan identifier
3	@pCode	varchar(2)	INPUT	p code
4	@pDescription	varchar(255)	INPUT	p description

Definition

```
CREATE  procedure sp_AddPricePlan @pSessionId int, @pPricePlanId int, @pCode varchar(2)...



if @pPricePlanId = 0

begin

  if rtrim(@pCode) != ''

  begin

    insert PricePlans (Active, Code, [Description])

      values (1, @pCode, @pDescription)

  end

end

else

begin

  if rtrim(@pCode) = ''

  begin

    Update PricePlans

       set Active = 0

     where PricePlanId = @pPricePlanId

  end

  else

  begin

    Update PricePlans

       set Code = rtrim(@pCode),

           [Description] = rtrim(@pDescription),
```

```
    Active = 1

      where PricePlanId = @pPricePlanId

... (truncated)
```

sp_AddSchool {sp-dbo-sp-addschool}

> Add new record to AddSchool

Property	Value
Schema	dbo
Created	2001-10-05 08:09:34.880000
Modified	2015-11-24 23:37:30.070000
Parameters	14

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pSchoolId	int	INPUT	p School identifier
3	@pSchoolName	varchar(50)	INPUT	p School name
4	@pSchoolAddr1	varchar(255)	INPUT	p School Addr1 parameter
5	@pSchoolAddr2	varchar(255)	INPUT	p School Addr2 parameter
6	@pSchoolAddr3	varchar(255)	INPUT	p School Addr3 parameter
7	@pSchoolCity	varchar(255)	INPUT	p School City parameter
8	@pSchoolState	varchar(255)	INPUT	p School State parameter
9	@pSchoolZip	varchar(255)	INPUT	p School Zip parameter
10	@pPhoneNumber	varchar(255)	INPUT	p Phone number
11	@pFax	varchar(255)	INPUT	p Fax parameter
12	@pEMail	varchar(255)	INPUT	p EMail parameter
13	@pLocationCode	varchar(255)	INPUT	p Location code
14	@rSchoolId	int	OUTPUT	r School identifier

Definition

```
CREATE procedure [dbo].[sp_AddSchool] @pSessionId int, @pSchoolId int, @pSchoolName var...



declare @DistrictId int,

@SchoolId int,

@ShippingId int



select @DistrictId = ISNULL(DistrictId,0)

  from SessionTable

 where SessionId = @pSessionId



if ISNULL(@pSchoolId,0) = 0

begin

  insert ShipLocations (DistrictId, Active, Name, Address1, Address2, Address3, City, S...

    values (@DistrictId, 1, rtrim(@pSchoolName), rtrim(@pSchoolAddr1), rtrim(@pSchoolAd...



  select @ShippingId = Scope_Identity() --DCH 11/24/2015 @@IDENTITY



  insert School (DistrictId, Active, Name, Address1, Address2, Address3, City, State, Z...

    values (@DistrictId, 1, rtrim(@pSchoolName), rtrim(@pSchoolAddr1), rtrim(@pSchoolAd...
```

```
  select @SchoolId = Scope_Identity() --DCH 11/24/2015 @@IDENTITY

end
```

```
else

begin

  -- Set Return School Id

... (truncated)
```

sp_alterdiagram {sp-dbo-sp-alterdiagram}

> Stored procedure: alterdiagram

Property	Value
Schema	dbo
Created	2009-03-26 16:18:10.600000
Modified	2009-03-26 16:18:10.600000
Parameters	4

Parameters

#	Parameter	Type	Direction	Description
1	@diagramname	sysname	INPUT	diagramname parameter
2	@owner_id	int	INPUT	owner id parameter
3	@version	int	INPUT	version parameter
4	@definition	varbinary(MAX)	INPUT	definition parameter

Definition

```
CREATE PROCEDURE dbo.sp_alterdiagram

(

@diagramname sysname,

@owner_idint= null,

@version int,

@definition varbinary(max)

)

WITH EXECUTE AS 'dbo'

AS

BEGIN

set nocount on



declare @theId int

declare @retval int

declare @IsDbo int



declare @UIDFound int

declare @DiagIdint

declare @ShouldChangeUIDint
```

```
if(@diagramname is null)

begin

RAISERROR ('Invalid ARG', 16, 1)
```

```
return -1

end

... (truncated)
```

sp_ApproveReq {sp-dbo-sp-approvereq}

> Approve req

Property	Value
Schema	dbo
Created	2001-08-24 14:40:44.703000
Modified	2016-04-28 17:01:27.233000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	varchar(255)	INPUT	p Session identifier
2	@pRequisitionId	varchar(255)	INPUT	p Requisition identifier
3	@pStatusCode	varchar(255)	INPUT	p Status code

Definition

```
CREATE          procedure [dbo].[sp_ApproveReq] @pSessionId varchar(255), @pRequisition...



declare @UserApprovalLevel int,

@RequiredApprovalLevel int,

@UserId int,

@DistrictId int,

@RequisitionId int,

@RequisitionNumber varchar(255),

@CurrentApprovalLevel int,

@StatusId int,

@StatusCode char(1),

@PendingId int,

@HoldId int,

@ChangesId int,

@ApprovedId int,

@AtEDSId int,

@POPrintedId int,

@pStatusId int,

@CurrentStatus int,

@ApproverId int,

@POCount int,

@OnlineDistrict int,

@Amount money
```

```
-- Validate Session

... (truncated)
```

sp_AttemptLogin {sp-dbo-sp-attemptlogin}

> Login/authentication procedure for Attempt

Property	Value
Schema	dbo
Created	2001-08-24 14:40:44.753000
Modified	2025-03-26 09:00:48.497000
Parameters	6

Parameters

#	Parameter	Type	Direction	Description
1	@rtDistrictCode	char(2)	INPUT	rt District code
2	@rtCometId	varchar(50)	INPUT	rt Comet identifier
3	@rtUserName	varchar(50)	INPUT	rt User name
4	@rtPassword	varchar(100)	INPUT	rt Password parameter
5	@rtResolutionX	int	INPUT	rt Resolution X parameter
6	@rtResolutionY	int	INPUT	rt Resolution Y parameter

Definition

```
CREATE   PROCEDURE [dbo].[sp_AttemptLogin] @rtDistrictCode char(2), @rtCometId varchar(...

declare @tempSessionId int,

        @tempBudgetId int,

@StartDate varchar(32)

set nocount on

/*

select @tempBudgetId = BudgetId

  from SessionTable

 where SessionId = (select max(SessionId)

                      from SessionTable

                      JOIN dbo.Users on dbo.Users.UserId = SessionTable.UserId

                      JOIN dbo.School on dbo.School.SchoolId = dbo.Users.SchoolId

                      JOIN dbo.District on dbo.District.DistrictId = dbo.School.DistrictId

                     WHERE dbo.District.DistrictCode = @rtDistrictCode

                       AND dbo.Users.CometId = convert(int,@rtCometId)

                       AND dbo.Users.UserName = @rtUserName

                       AND dbo.Users.Password = @rtPassword)



if @@rowcount = 0

begin

  select @tempBudgetId = MAX(Budgets.BudgetId)

    FROM Budgets

    JOIN dbo.District on dbo.District.DistrictId = Budgets.DistrictId
```

```
    WHERE dbo.District.DistrictCode = @rtDistrictCode

end

... (truncated)
```

sp_AwardBid {sp-dbo-sp-awardbid}

> Award processing procedure for Bid

Property	Value
Schema	dbo
Created	2002-06-13 17:37:16.590000
Modified	2015-11-24 23:37:27.310000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pBidId	int	INPUT	p Bid identifier

Definition

```
CREATE procedure [dbo].[sp_AwardBid] @pBidId int as



declare @AwardId int,

@ItemsBid int,

@AmountBid money



select @ItemsBid = count(*),

       @AmountBid = sum(isnull(BidQuantity,0) * isnull(Price,0))

  from BidItems

 where BidId = @pBidId



-- Check for Existing Award

select @AwardId = AwardId

  from Awards

 where BidId = @pBidId

   and Active = 1



if @@rowcount = 0

begin

  -- Create Award
```

```
  insert Awards (Active, BidId, VendorId, PricePlanId, CategoryId, VendorBidNumber, Des...

    select 1, BidId, VendorId, PricePlanId, CategoryId, VendorBidNumber, Name, CatalogI...

      from Bids
```

```
        where BidId = @pBidId



... (truncated)
```

sp_AwardBidHeader {sp-dbo-sp-awardbidheader}

> Award processing procedure for data

Property	Value
Schema	dbo
Created	2004-06-09 02:02:01.263000
Modified	2025-06-26 12:00:23.160000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pBidHeaderId	int	INPUT	p Bid Header identifier

Definition

```
--sp_AwardBidHeader 9981

--select * from Awardings

--select * from DetailNotifications

/* exec sp_AwardBidHeader 600 rollback */



CREATE procedure [dbo].[sp_AwardBidHeader] @pBidHeaderId int as



/********  test error handler

--SEt @pBidHeaderId = 2200

Begin Try

Insert Into Awards (AwardId) Values (83)

End Try

Begin Catch

Goto ErrorHandler;

End Catch

--*/



declare @BidType int,

@Type int,

@MarkAsOriginal int



Begin Try

select @Type = Type,
```

```
    @BidType = BidHeaders.BidType,

        @MarkAsOriginal = MarkAsOriginal

... (truncated)
```

sp_AwardBidHeaderSingleItem {sp-dbo-sp-awardbidheadersingleitem}

> Award processing procedure for Single

Property	Value
Schema	dbo
Created	2015-08-05 15:03:27.490000
Modified	2015-08-05 15:03:27.490000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pBidHeaderId	int	INPUT	p Bid Header identifier
2	@pItemId	int	INPUT	p Item identifier

Definition

```
--sp_AwardBidHeader 2200



/* exec sp_AwardBidHeader 600 rollback */



Create procedure [dbo].[sp_AwardBidHeaderSingleItem] @pBidHeaderId int, @pItemId int as



declare @BidType int,

@Type int,

@MarkAsOriginal int



select @Type = Type,

       @BidType = BidHeaders.BidType,

       @MarkAsOriginal = MarkAsOriginal

  from BidHeaders

  join Category on Category.CategoryId = BidHeaders.CategoryId

 where BidHeaders.BidHeaderId = @pBidHeaderId



if @Type in (1,4)

begin

  select *

into #BidSummary

from dbo.uf_BidAnalysisDetail(@pBidHeaderId)

   where ItemId = @pItemId
```

```
end


... (truncated)
```

sp_BAList {sp-dbo-sp-balist}

> List procedure for BA

Property	Value
Schema	dbo
Created	2001-08-24 14:40:44.783000
Modified	2010-05-25 14:11:18.380000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	varchar(255)	INPUT	p Session identifier

Definition

```
CREATE     procedure [dbo].[sp_BAList] @pSessionId varchar(255) AS



declare @SessionId int,

@ApprovalLevel int,

@UserId int



select @SessionId = convert(int,@pSessionId)



select @ApprovalLevel = ISNULL(ApprovalLevel,0),

       @UserId = ISNULL(UserId,0)

  from SessionTable

--  join Users on Users.UserId = SessionTable.UserId

 where SessionTable.SessionId = @SessionId



if @ApprovalLevel > 1

begin

  select Accounts.Code AccountCode, isnull(rt.RequisitionsTotal,0) RequisitionsTotal,

          isnull(BudgetAccounts.BudgetAmount,0) BudgetAmount,

          isnull(BudgetAccounts.AmountAvailable,0) AmountAvailable,

          isnull(ua.AllocationUsed,0) AllocationTotal,

          isnull(ua.AllocationTotal,0) AllocatedAmount,

          isnull(BudgetAccounts.UseAllocations,0) UseBudgetAllocations,

          0 UseUserAllocations
```

```
    from BudgetAccounts

    join Accounts on Accounts.AccountId = BudgetAccounts.AccountId

... (truncated)
```

sp_BatchChanges {sp-dbo-sp-batchchanges}

> Batch processing procedure for Changes

Property	Value
Schema	dbo
Created	2001-12-05 23:22:59.497000
Modified	2009-03-25 06:55:28.550000
Parameters	0

Definition

```
CREATE  procedure sp_BatchChanges AS



create table #TempChanges (

ChangeId int identity(1,1) not null,

BatchIdint null,

BatchBookId int null,

BatchDetailId int null,

RecordNumber int null,

Fieldvarchar(16) null,

OrigValue varchar(16) null,

CorrectedValue varchar(16) null )



-- Insert District Code Changes

insert #TempChanges (BatchId, BatchBookId, BatchDetailId, RecordNumber, Field, OrigValu...

  select BatchDetail.BatchId, BatchDetail.BatchBookId, BatchDetail.BatchDetailId, Batch...

    from Batches

    join BatchBook on BatchBook.BatchId = Batches.BatchId

    join BatchDetail on BatchDetail.BatchBookId = BatchBook.BatchBookId

   where isnull(OrigDistrictCode,'') != isnull(BatchDetail.DistrictCode,'')

     and BatchDetail.Active = 1



-- Insert Category Code Changes

insert #TempChanges (BatchId, BatchBookId, BatchDetailId, RecordNumber, Field, OrigValu...
```

```
    select BatchDetail.BatchId, BatchDetail.BatchBookId, BatchDetail.BatchDetailId, Batch...

      from Batches

  ... (truncated)
```

sp_BatchConvert {sp-dbo-sp-batchconvert}

> Batch processing procedure for Convert

Property	Value
Schema	dbo
Created	2003-06-30 12:55:47.200000
Modified	2009-03-25 06:55:28.397000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pBatchId	int	INPUT	p Batch identifier

Definition

```
CREATE         procedure dbo.sp_BatchConvert @pSessionId int, @pBatchId int AS



-- Declare Local Variables

declare@BatchId int,

@BatchBookId int,

@RequisitionId int,

@DistrictId int,

@CategoryId int,

@SchoolId int,

@UserId int,

@BudgetId int,

@AccountId int,

@BudgetAccountId int,

@UserAccountId int,

@Errors int,

@AccountCode varchar(30),

@Total money,

@TodaysDate datetime,

@BatchDetailId int,

@Qty int,
```

```
@SourceId int,

@ItemId int,

@ConvertedId int,
```

```
@BidHeaderId int
```

```
... (truncated)
```

sp_BatchConvertNew {sp-dbo-sp-batchconvertnew}

> Batch processing procedure for ConvertNew

Property	Value
Schema	dbo
Created	2009-02-26 10:25:33.367000
Modified	2009-03-25 06:55:28.350000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pBatchId	int	INPUT	p Batch identifier

Definition

```
create procedure dbo.sp_BatchConvertNew @pSessionId int, @pBatchId int AS



-- Declare Local Variables

declare@BatchId int,

@BatchBookId int,

@RequisitionId int,

@DistrictId int,

@CategoryId int,

@SchoolId int,

@UserId int,

@BudgetId int,

@AccountId int,

@BudgetAccountId int,

@UserAccountId int,

@Errors int,

@AccountCode varchar(30),

@Total money,

@TodaysDate datetime,

@BatchDetailId int,

@Qty int,

@SourceId int,

@ItemId int,

@ConvertedId int,
```

```
@BidHeaderId int



... (truncated)
```

sp_BatchLoad {sp-dbo-sp-batchload}

> Batch processing procedure for Load

Property	Value
Schema	dbo
Created	2001-08-28 15:08:57.787000
Modified	2015-11-24 23:37:34.710000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pSourceFile	varchar(255)	INPUT	p Source File parameter

Definition

```
CREATE procedure [dbo].[sp_BatchLoad] @pSourceFile varchar(255) AS



-- Create Temp Table

create table #ImportBatch (

DataRowvarchar(256),

RowIdint identity(1,1)

)



-- Declare Local Varaiables

declare @Records int,

@BatchId int,

@SQLStmt varchar(1024)



-- Build Load Ascii File into TempDB statement

select @SQLStmt = 'BULK INSERT #ImportBatch FROM ''' + @pSourceFile + ''' WITH (FORMATF...



execute(@SQLStmt)



-- Get Import Count

select @Records = count(RowId) from #ImportBatch



-- Create New Batch Entry

insert Batches (Active, BatchDate,Records,Type,ImportedRecords,SourceId, InputRecords, ...
```

```
    values (1, getdate(),@Records,'Q',@Records,2, 0, getdate())



  ... (truncated)
```

sp_BatchProcess {sp-dbo-sp-batchprocess}

> Batch processing procedure for data

Property	Value
Schema	dbo
Created	2002-11-21 14:58:45.920000
Modified	2009-03-25 06:55:28.660000
Parameters	0

Definition

```
create procedure sp_BatchProcess AS

declare @BatchId int



declare BatchCur cursor fast_forward read_only for

select BatchId

  from Batches

 where Scheduled is not null

   and Started is null

   and Completed is null



open BatchCur



fetch next from BatchCur into @BatchId



while @@fetch_status = 0

begin

  execute sp_BatchVerify @BatchId



  fetch next from BatchCur into @BatchId

end



close BatchCur

deallocate BatchCur
```

sp_BatchQueue {sp-dbo-sp-batchqueue}

> Batch processing procedure for data

Property	Value
Schema	dbo
Created	2002-11-21 14:53:58.873000
Modified	2015-11-24 23:37:40.680000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pSourceFile	varchar(255)	INPUT	p Source File parameter

Definition

```
CREATE procedure [dbo].[sp_BatchQueue] @pSourceFile varchar(255) AS



-- Create Temp Table

create table #ImportBatch (

DataRowvarchar(256),

RowIdint identity(1,1)

)



-- Declare Local Varaiables

declare @Records int,

@BatchId int,

@DistrictCode char(2),

@CategoryCode char(1),

@BatchAmount money,

@SQLStmt varchar(1024)



-- Build Load Ascii File into TempDB statement

select @SQLStmt = 'BULK INSERT #ImportBatch FROM ''' + @pSourceFile + ''' WITH (FORMATF...



execute(@SQLStmt)
```

```
declare BICur cursor fast_forward read_only for

select substring(DataRow,3,2), substring(DataRow,5,1), count(*) Counter
```

```
 from #ImportBatch

group by substring(DataRow,3,2), substring(DataRow,5,1)

... (truncated)
```

sp_BatchVerify {sp-dbo-sp-batchverify}

> Batch processing procedure for data

Property	Value
Schema	dbo
Created	2001-08-28 15:09:14.380000
Modified	2014-10-07 17:53:27.777000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pBatchId	int	INPUT	p Batch identifier

Definition

```
CREATE procedure [dbo].[sp_BatchVerify] @pBatchId int AS



-- Declare Local Variables

declare @BatchId int,

@ErrorCount int,

@TotalAmount decimal(11,2),

@BatchBookId int,

@Records int,

@EnteredRecords int,

@BudgetId int,

@AccountId int,

@BudgetAccountId int,

@UserAccountId int,

@DistrictId int,

@UserId int,

@CatalogId int,

@ItemId int,

@BatchDetailId int,

@BidPrice money,

@ItemCode varchar(50),

@Location char(1),

@StartDate varchar(32),

@AccountCode varchar(32),
```

```
@DuplicateDetected tinyint,

@CategoryId int,

... (truncated)
```

sp_BatchVerifyBook {sp-dbo-sp-batchverifybook}

> Batch processing procedure for Book

Property	Value
Schema	dbo
Created	2002-12-03 14:12:18.403000
Modified	2014-10-07 17:53:27.227000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pBatchId	int	INPUT	p Batch identifier
2	@pBatchBookId	int	INPUT	p Batch Book identifier

Definition

```
CREATE procedure [dbo].[sp_BatchVerifyBook] @pBatchId int, @pBatchBookId int AS



-- Declare Local Variables

declare @BatchId int,

@ErrorCount int,

@TotalAmount decimal(11,2),

@BatchBookId int,

@Records int,

@EnteredRecords int,

@BudgetId int,

@AccountId int,

@BudgetAccountId int,

@UserAccountId int,

@DistrictId int,

@UserId int,

@CatalogId int,

@ItemId int,

@BatchDetailId int,

@BidPrice money,

@ItemCode varchar(50),

@Location char(1),

@StartDate varchar(32),

@AccountCode varchar(32),
```

```
@DuplicateDetected tinyint,

@CategoryId int,

... (truncated)
```

sp_BatchVerifyForce {sp-dbo-sp-batchverifyforce}

> Batch processing procedure for Force

Property	Value
Schema	dbo
Created	2004-01-14 15:43:19.077000
Modified	2014-10-07 17:53:25.853000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pBatchId	int	INPUT	p Batch identifier

Definition

```
CREATE procedure [dbo].[sp_BatchVerifyForce] @pBatchId int AS



-- Declare Local Variables

declare @BatchId int,

@ErrorCount int,

@TotalAmount decimal(11,2),

@BatchBookId int,

@Records int,

@EnteredRecords int,

@BudgetId int,

@AccountId int,

@BudgetAccountId int,

@UserAccountId int,

@DistrictId int,

@UserId int,

@CatalogId int,

@ItemId int,

@BatchDetailId int,

@BidPrice money,

@ItemCode varchar(50),

@Location char(1),

@StartDate varchar(32),

@AccountCode varchar(32),
```

```
@DuplicateDetected tinyint,

@CategoryId int,

... (truncated)
```

sp_BidCompare {sp-dbo-sp-bidcompare}

> Stored procedure: BidCompare

Property	Value
Schema	dbo
Created	2004-09-02 15:06:28.553000
Modified	2025-10-24 11:26:54.980000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pBidOld	int	INPUT	p Bid Old parameter
2	@pBidNew	int	INPUT	p Bid New parameter

Definition

```
/*

Z2 This vs Last Year Cascade vs SS Catalog less 20% this year



Order Book Z2



select * from PricePlans



select *

  from BidHeaders

  join BidImports on BidImports.BidHeaderId = BidHeaders.BidHeaderId

 where PricePlanId = 9

 order by BidHeaders.BidHeaderId



sp_BidCompare 366, 921

sp_BidCompare 371, 961



Update BidImports

   set Active = 1

 where BidImportId in (4003, 4004)
```

```
select * from Vendors where VendorId = 21



*/
```

```
CREATE procedure [dbo].[sp_BidCompare] @pBidOld int, @pBidNew int as

declare @BidComp table (

... (truncated)
```

sp_BidCompareDiscount {sp-dbo-sp-bidcomparediscount}

> Stored procedure: BidCompareDiscount

Property	Value
Schema	dbo
Created	2004-09-07 14:40:30.950000
Modified	2009-03-25 06:55:28.537000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@pBidOld	int	INPUT	p Bid Old parameter
2	@pBidNew	int	INPUT	p Bid New parameter
3	@pDiscountRate	varchar(255)	INPUT	p Discount Rate parameter

Definition

```
/*

Z2 This vs Last Year Cascade vs SS Catalog less 20% this year



Order Book Z2



select * from PricePlans



select *

  from BidHeaders

  join BidImports on BidImports.BidHeaderId = BidHeaders.BidHeaderId

 where PricePlanId = 9

 order by BidHeaders.BidHeaderId



sp_BidCompareDiscount 366, 921, '20'

sp_BidCompareDiscount 371, 961, '0'



Update BidImports

   set Active = 1

 where BidImportId in (4003, 4004)
```

```
select * from Vendors where VendorId = 21



*/
```

```
CREATE procedure dbo.sp_BidCompareDiscount @pBidOld int, @pBidNew int, @pDiscountRate v...
```

```
... (truncated)
```

sp_BidCompareSame {sp-dbo-sp-bidcomparesame}

> Stored procedure: BidCompareSame

Property	Value
Schema	dbo
Created	2019-11-20 17:16:32.010000
Modified	2019-11-20 17:18:43.243000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pBidOld	int	INPUT	p Bid Old parameter
2	@pBidNew	int	INPUT	p Bid New parameter

Definition

```
/*

Z2 This vs Last Year Cascade vs SS Catalog less 20% this year



Order Book Z2



select * from PricePlans



select *

  from BidHeaders

  join BidImports on BidImports.BidHeaderId = BidHeaders.BidHeaderId

 where PricePlanId = 9

 order by BidHeaders.BidHeaderId



sp_BidCompare 366, 921

sp_BidCompare 371, 961



Update BidImports

   set Active = 1

 where BidImportId in (4003, 4004)
```

```
select * from Vendors where VendorId = 21



*/
```

```
CREATE procedure [dbo].[sp_BidCompareSame] @pBidOld int, @pBidNew int as



... (truncated)
```

sp_BidCompareSummary {sp-dbo-sp-bidcomparesummary}

> Summation procedure for BidComparemary

Property	Value
Schema	dbo
Created	2022-10-14 16:28:56.557000
Modified	2022-10-14 16:48:05.437000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pBidOld	int	INPUT	p Bid Old parameter
2	@pBidNew	int	INPUT	p Bid New parameter

Definition

```
/*

exec [sp_BidCompareSummary] 11384, 11721

*/

create   procedure [dbo].[sp_BidCompareSummary] @pBidOld int, @pBidNew int as

declare @PP varchar(10),

@Category varchar(50)



select @PP = PricePlans.Code,

   @Category = Category.Name

  from BidHeaders

  join PricePlans on PricePlans.PricePlanId = BidHeaders.PricePlanId

  join Category on Category.CategoryId = BidHeaders.CategoryId

 where BidHeaders.BidHeaderId = @pBidOld



select bh1.BidHeaderId,

       i1.ItemId,

       i1.ItemCode,

       dbo.uf_ItemDescription(i1.ItemId) Description,

   lo.BidPrice,

   lo.CatalogPrice,

   lo.GrossPrice,

   lo.DiscountRate,

   lo.VendorItemCode,
```

```
    lo.Alternate,

    lo.BidItemId,

... (truncated)
```

sp_BidCopy {sp-dbo-sp-bidcopy}

> Copy procedure for Bid

Property	Value
Schema	dbo
Created	2010-09-15 23:00:35.250000
Modified	2022-12-08 11:43:22.960000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pSourceBidId	int	INPUT	p Source Bid identifier
2	@pCopies	int	INPUT	p Copies parameter

Definition

```
CREATE   procedure [dbo].[sp_BidCopy] @pSourceBidId int, @pCopies int as

set transaction isolation level read uncommitted

declare @BidHeaderId int, @BidImportId int, @NewBidImportId int, @LoopCounter int, @Sou...



select @SourceBidHeaderId = @pSourceBidId

select @LoopCounter = 0

while @LoopCounter < @pCopies

begin

  select @LoopCounter = @LoopCounter + 1



insert BidHeaders (Active, CategoryId, PricePlanId, BidDate, BidAwardDate, BidMessage, ...

  select Active, CategoryId, PricePlanId, BidDate, BidAwardDate, BidMessage, BidType, P...

    from BidHeaders

   where BidHeaderId = @SourceBidHeaderId



select @BidHeaderKey = Scope_Identity() --DCH 11/24/2015 @@identity



select @BidHeaderId = BidHeaderId

  from BidHeaders

 where BidHeaderKey = @BidHeaderKey



/* replaced 4/2/2018 kjm - new code part A

insert BidRequestItems (BidHeaderKey, BidHeaderId, ItemId, BidRequest, Active, Requisit...
```

```
    select @BidheaderKey, @BidHeaderId, ItemId, BidRequest, Active, RequisitionCount, Sta...

      from BidRequestItems

  ... (truncated)
```

sp_BidCopyChangePP {sp-dbo-sp-bidcopychangepp}

> Copy procedure for BidChangePP

Property	Value
Schema	dbo
Created	2010-09-15 23:02:40.573000
Modified	2025-12-04 15:15:56.470000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@pSourceBidId	int	INPUT	p Source Bid identifier
2	@pNewPPId	int	INPUT	p New PP identifier
3	@pCopies	int	INPUT	p Copies parameter

Definition

```
CREATE   procedure [dbo].[sp_BidCopyChangePP] @pSourceBidId int, @pNewPPId int, @pCopie...

set transaction isolation level read uncommitted

declare @BidHeaderId int, @BidImportId int, @NewBidImportId int, @LoopCounter int, @Sou...



begin Transaction

set nocount on

select @TargetPricePlanId = @pNewPPId

select @SourceBidHeaderId = @pSourceBidId

select @LoopCounter = 0

while @LoopCounter < @pCopies

begin

  select @LoopCounter = @LoopCounter + 1



insert BidHeaders (Active, CategoryId, PricePlanId, BidDate, BidAwardDate, BidMessage, ...

  select Active, CategoryId, @TargetPricePlanId, BidDate, BidAwardDate, BidMessage, Bid...

    from BidHeaders

   where BidHeaderId = @SourceBidHeaderId



select @BidHeaderKey = Scope_Identity() --DCH 11/24/2015 @@identity
```

```
select @BidHeaderId = BidHeaderId

  from BidHeaders

 where BidHeaderKey = @BidHeaderKey
```

```
/* replaced 4/2/2018 kjm - new code part A

... (truncated)
```

sp_BidCopyWithIncrease {sp-dbo-sp-bidcopywithincrease}

> Copy procedure for BidWithIncrease

Property	Value
Schema	dbo
Created	2024-11-12 16:08:11.497000
Modified	2025-11-12 14:11:43.953000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pSourceBidId	int	INPUT	p Source Bid identifier
2	@pIncrease	decimal(11,5)	INPUT	p Increase parameter

Definition

```
--exec sp_BidCopyWithIncrease 13002, 1.8



CREATE     procedure [dbo].[sp_BidCopyWithIncrease] @pSourceBidId int, @pIncrease decim...

set transaction isolation level read uncommitted

declare @BidHeaderId int, @BidImportId int, @NewBidImportId int, @LoopCounter int, @Sou...



select @SourceBidHeaderId = @pSourceBidId

select @LoopCounter = 0

while @LoopCounter < 1

begin

  select @LoopCounter = @LoopCounter + 1



insert BidHeaders (Active, CategoryId, PricePlanId, BidDate, BidAwardDate, BidMessage, ...

  select Active, CategoryId, PricePlanId, BidDate, BidAwardDate, BidMessage, BidType, P...

    from BidHeaders

   where BidHeaderId = @SourceBidHeaderId



select @BidHeaderKey = Scope_Identity() --DCH 11/24/2015 @@identity



select @BidHeaderId = BidHeaderId

  from BidHeaders

 where BidHeaderKey = @BidHeaderKey
```

```
/* replaced 4/2/2018 kjm - new code part A

insert BidRequestItems (BidHeaderKey, BidHeaderId, ItemId, BidRequest, Active, Requisit...

... (truncated)
```

sp_BringBillingForward {sp-dbo-sp-bringbillingforward}

> Stored procedure: BringBillingForward

Property	Value
Schema	dbo
Created	2015-02-04 12:01:19.373000
Modified	2025-12-08 11:57:53.300000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@increasePercenta	decimal(11,5)	INPUT	increase Percentage parameter

Definition

```
--exec sp_BringBillingForward 0.0

CREATE   procedure [dbo].[sp_BringBillingForward] @increasePercentage decimal(11,5) as

insert Budgets (Active, DistrictId, EndDate, Name, StartDate, VisibleFrom, VisibleUntil...

select 1, District.DistrictId,

       DATEADD(year,1,bc.EndDate),

       cast(CAST(substring(bc.Name,1,4) as int) + 1 as varchar) + ' - ' + cast(CAST(sub...

       DATEADD(year,1,bc.StartDate), DATEADD(year,1,bc.VisibleFrom), DATEADD(year,1,bc....

       DATEADD(year,1,bc.EditFrom), DATEADD(YEAR,1,bc.EditUntil), DATEADD(year,1,bc.Ann...

  from District

  join Budgets bc on bc.DistrictId = District.DistrictId

                  and cast(substring(bc.Name,1,4) as int) = case when month(getdate()) ...

  left outer join Budgets bn on bn.DistrictId = District.DistrictId

                             and cast(substring(bn.Name,1,4) as int) = cast(substring(b...

 where District.Active = 1

   and bn.BudgetId is null



insert DistrictProposedCharges (Amount, BudgetId, ChargeTypeId, DateUpdated, DistrictId...

select dc.Amount + round(dc.Amount * 0 / 100,-1),

       bn.BudgetId, dc.ChargeTypeId, GETDATE(), District.DistrictId,

       dc.Frequency, dc.FrequencyData, case when isnull(dc.Amount,0) = 0 then 0 else ro...

  from District

  join Budgets bc on bc.DistrictId = District.DistrictId

                 and cast(substring(bc.Name,1,4) as int) = case when month(getdate()) b...
```

```
    join DistrictCharges dc on dc.BudgetId = bc.BudgetId

    join ChargeTypes on ChargeTypes.ChargeTypeId = dc.ChargeTypeId

  ... (truncated)
```

sp_BringBillingForwardState {sp-dbo-sp-bringbillingforwardstate}

> Stored procedure: BringBillingForwardState

Property	Value
Schema	dbo
Created	2024-10-31 15:01:02.693000
Modified	2024-11-11 11:57:58.070000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@State	char(2)	INPUT	State parameter
2	@increasePercenta	decimal(11,5)	INPUT	increase Percentage parameter

Definition

```
--exec sp_BringBillingForwardState 'NY', 0--1.9

CREATE   procedure [dbo].[sp_BringBillingForwardState] @State char(2), @increasePercent...

insert Budgets (Active, DistrictId, EndDate, Name, StartDate, VisibleFrom, VisibleUntil...

select 1, District.DistrictId,

       DATEADD(year,1,bc.EndDate),

       cast(CAST(substring(bc.Name,1,4) as int) + 1 as varchar) + ' - ' + cast(CAST(sub...

       DATEADD(year,1,bc.StartDate), DATEADD(year,1,bc.VisibleFrom), DATEADD(year,1,bc....

       DATEADD(year,1,bc.EditFrom), DATEADD(YEAR,1,bc.EditUntil), DATEADD(year,1,bc.Ann...

  from District

  join Budgets bc on bc.DistrictId = District.DistrictId

                  and cast(substring(bc.Name,1,4) as int) = case when month(getdate()) ...

  left outer join Budgets bn on bn.DistrictId = District.DistrictId

                             and cast(substring(bn.Name,1,4) as int) = cast(substring(b...

 where District.Active = 1

   and isnull(District.State,'') = @State

   and bn.BudgetId is null



insert DistrictProposedCharges (Amount, BudgetId, ChargeTypeId, DateUpdated, DistrictId...

select case when (isnull(ChargeTypes.LM,0) = 1 /*or isnull(ChargeTypes.RTK,0) = 1*/) th...

       bn.BudgetId, dc.ChargeTypeId, GETDATE(), District.DistrictId,

       dc.Frequency, dc.FrequencyData, case when isnull(dc.Amount,0) = 0 then 0 else ro...

  from District

  join Budgets bc on bc.DistrictId = District.DistrictId
```

```
                    and cast(substring(bc.Name,1,4) as int) = case when month(getdate()) b...

     join DistrictProposedCharges dc on dc.BudgetId = bc.BudgetId

   ... (truncated)
```

sp_BuildTopOrdered {sp-dbo-sp-buildtopordered}

> Purchase order procedure for BuildToped

Property	Value
Schema	dbo
Created	2003-06-30 12:55:47.747000
Modified	2014-10-07 17:53:23.593000
Parameters	0

Definition

```
CREATE procedure [dbo].[sp_BuildTopOrdered] as


declare @CategoryId int,
@BudgetId int


declare cbcur cursor fast_forward read_only for
select Requisitions.CategoryId, Budgets.BudgetId
  from Requisitions
  join Budgets on Budgets.BudgetId = Requisitions.BudgetId
              and Budgets.VisibleFrom <= getdate()
              and Budgets.VisibleUntil >= getdate()
 group by Requisitions.CategoryId, Budgets.BudgetId


truncate table TopOrderedItems


open cbcur


fetch next from cbcur into @CategoryId, @BudgetId


while @@fetch_status = 0
begin
  insert TopOrderedItems (CategoryId, BudgetId, ItemId, Quantity, ReqCount, Weight)
    select top 200 Requisitions.CategoryId, Requisitions.BudgetId, Detail.ItemId, sum(D...
```

```
        from Detail

        join Requisitions on Requisitions.RequisitionId = Detail.RequisitionId

  ... (truncated)
```

sp_CanDeleteRequisition {sp-dbo-sp-candeleterequisition}

> Requisition procedure for CanDelete

Property	Value
Schema	dbo
Created	2001-08-24 14:40:45.053000
Modified	2009-03-25 06:55:28.583000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pRequisitionId	varchar(255)	INPUT	p Requisition identifier

Definition

```
CREATE procedure dbo.sp_CanDeleteRequisition @pRequisitionId varchar(255) AS



declare @CanDelete int



select @CanDelete = count(ApprovalId)

  from Approvals

 where RequisitionId = CONVERT(int,@pRequisitionId)



select @CanDelete
```

sp_CatalogDataCheck {sp-dbo-sp-catalogdatacheck}

> Catalog management procedure for Data

Property	Value
Schema	dbo
Created	2002-02-18 17:23:40.513000
Modified	2009-03-25 06:55:28.770000
Parameters	0

Definition

```
CREATE    procedure sp_CatalogDataCheck AS



create table #ImportBatch (

DataRowvarchar(512),

RowIdint identity(1,1)

)



BULK INSERT #ImportBatch

 FROM 'A:TEST.DAT'

 WITH (FORMATFILE = 'C:\INETPUB\EDSIQ\ImportQty1.fmt')



select case right('        ' + dbo.uf_RemoveLeadingZeros(substring(#ImportBatch.DataRow...

    right('        ' + dbo.uf_RemoveLeadingZeros(substring(#ImportBatch.DataRow,305,8))...

    NewFF.ItemCode DBItemCode,

    case convert(money,substring(#ImportBatch.DataRow,328,7)) when NewFF.GrossPrice the...

    convert(money,substring(#ImportBatch.DataRow,328,7)) ImportPrice,

    NewFF.GrossPrice DBGrossPrice,

    case NewFF.Code

      when substring(#ImportBatch.DataRow,323,5) then 'OK'

      else case len(rtrim(substring(#ImportBatch.DataRow,323,5)))

              when 2 then

                case substring(NewFF.Code,1,2)

                  when substring(#ImportBatch.DataRow,323,2) then 'OK'
```

```
                    else case substring(#ImportBatch.DataRow,323,2)

                           when substring(NewFF.Code,1,1) + substring(NewFF.Code,len(rtrim...

... (truncated)
```

sp_CatalogDataPriceCheck {sp-dbo-sp-catalogdatapricecheck}

> Catalog management procedure for Data

Property	Value
Schema	dbo
Created	2002-02-21 18:44:53.670000
Modified	2009-03-25 06:55:28.270000
Parameters	0

Definition

```
CREATE       procedure sp_CatalogDataPriceCheck AS



create table #ImportBatch (

DataRowvarchar(512),

RowIdint identity(1,1)

)



BULK INSERT #ImportBatch

 FROM 'A:TEST.DAT'

 WITH (FORMATFILE = 'C:\INETPUB\EDSIQ\ImportQty1.fmt')



select case right('        ' + dbo.uf_RemoveLeadingZeros(rtrim(substring(#ImportBatch.D...

    right('        ' + dbo.uf_RemoveLeadingZeros(rtrim(substring(#ImportBatch.DataRow,3...

    NewFF.ItemCode DBItemCode,

    case convert(money,substring(#ImportBatch.DataRow,15,7)) when NewFF.GrossPrice then...

    convert(money,substring(#ImportBatch.DataRow,15,7)) ImportPrice,

    NewFF.GrossPrice DBGrossPrice,

    case substring(#ImportBatch.DataRow,11,4) when Vendors.Code then 'OK' else 'BAD' en...

    substring(#ImportBatch.DataRow,11,4) ImportVendor,

    Vendors.Code DBVendor

into #LineStatus

from #ImportBatch

join PricePlans on PricePlans.Code = substring(#ImportBatch.DataRow,1,2)
```

```
join Vendors on Vendors.Code = substring(#ImportBatch.DataRow,11,4)

left outer join NewFF on NewFF.ItemCode = right('        ' + dbo.uf_RemoveLeadingZeros(...

... (truncated)
```

sp_CatalogImport {sp-dbo-sp-catalogimport}

> Catalog management procedure for data

Property	Value
Schema	dbo
Created	2011-10-27 12:48:14.723000
Modified	2011-12-07 13:46:23.033000
Parameters	4

Parameters

#	Parameter	Type	Direction	Description
1	@pFileName	varchar(255)	INPUT	p File name
2	@pCatalogId	int	INPUT	p Catalog identifier
3	@pXmlFieldMap	varchar(MAX)	INPUT	p Xml Field Map parameter
4	@pXML	varchar(MAX)	INPUT	p XML data

Definition

```
CREATE procedure [dbo].[sp_CatalogImport] @pFileName varchar(255), @pCatalogId int, @pX...

as

insert Catalogs.dbo.CatalogXML (FileName, CatalogId, XMLData, XMLFieldMap)

  values (@pFileName, @pCatalogId, @pXML, @pXmlFieldMap)
```

sp_CatalogImporter {sp-dbo-sp-catalogimporter}

> Catalog management procedure for er

Property	Value
Schema	dbo
Created	2012-11-14 19:57:29.560000
Modified	2012-11-14 20:04:32.920000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@xmlMap	xml	INPUT	xml Map parameter
2	@xmlFile	xml	INPUT	xml File parameter

Definition

```
--declare @xml xml,@map xml select @map = '<Map></Map>', @xml = '<Catalog id="1234"><Ro...

CREATE procedure sp_CatalogImporter @xmlMap xml, @xmlFile xml as

/*

Things the catalog importer should do.

1.Check for # Records being within 10%

2.Check for Prices being within 20%, report exceptions

3.Check for # of Matches on existing items vs New Items

4.Strip Special Characters

5.Check for Missing Data in Required Fields

6.Validate Data types (money, Page Numbers

7.Check for Duplicate Entries

8.Post File once Acceptable

*/

declare @hMap int, @hFile int

declare @FileMap varchar(max)



exec sp_xml_prepareDocument @hFile output, @xmlFile



select @FileMap = ''

select *
```

```
  from OPENXML(@hFile, '/Catalog')
```

sp_CatalogImporterXML

{sp-dbo-sp-catalogimporterxml}

> Catalog management procedure for erXML

Property	Value
Schema	dbo
Created	2013-11-25 16:41:26.817000
Modified	2014-06-03 15:39:58.940000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pXML	varchar(MAX)	INPUT	p XML data
2	@Mode	int	INPUT	Mode parameter

Definition

```
CREATE procedure [dbo].[sp_CatalogImporterXML] @pXML varchar(max), @Mode int = 0

as

begin

declare @hDoc int,

@catalogId int,

@ExistingEntries int



-- Prepare Document

exec sp_xml_preparedocument @hDoc output, @pXML



-- Get CatalogId

select @catalogId = cast(CatalogId as int)

   from OPENXML(@hDoc, '/Catalog') with ([CatalogId] varchar(50) '@id')



--get existing row count

select @ExistingEntries = COUNT(*)

  from Catalogs.dbo.[Master Catalog] mc

 where mc.CatalogId = @catalogId



--Store Import Data

insert Catalogs.dbo.CatalogImports(CatalogId, Mode, ExistingCount, XmlDoc)

  values (@catalogId, @Mode, @ExistingEntries, @pXML)
```

```
--Check Mode

if @Mode = 0 and @ExistingEntries > 0

... (truncated)
```

sp_CCAccountMaint {sp-dbo-sp-ccaccountmaint}

> Stored procedure: CCAccountMaint

Property	Value
Schema	dbo
Created	2019-06-04 16:45:14.587000
Modified	2019-06-13 08:40:40.213000
Parameters	7

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pAccountId	int	INPUT	p Account identifier
3	@pActive	int	INPUT	p Active parameter
4	@pSchoolId	int	INPUT	p School identifier
5	@pAccountEntry	varchar(50)	INPUT	p Account Entry parameter
6	@pDescription	varchar(512)	INPUT	p description
7	@pAction	tinyint	INPUT	p Action parameter

Definition

```
CREATE   procedure [dbo].[sp_CCAccountMaint] @pSessionId int, @pAccountId int, @pActive...

declare @AccountId int,

@UserAccountId int,

@BudgetAccountId int,

@DistrictId int,

@BudgetId int,

@SchoolId int,

@Account_SchoolId int,

@Account_Active int,

@BA_Active int,

@UA_Active int,

@UA_AllocationAmount decimal(11,2),

@UA_UseAllocations int,

@UA_BudgetAccountId int,

@UA_Count int,

@BA_Count int



set nocount on



-- Get District id

select @DistrictId = DistrictId, @BudgetId = BudgetId

  from SessionTable

 where SessionId = @pSessionId
```

```
if @@ROWCOUNT = 0

... (truncated)
```

sp_CCAddAddendaItem {sp-dbo-sp-ccaddaddendaitem}

> Item management procedure for CCAddAddenda

Property	Value
Schema	dbo
Created	2009-12-08 09:35:43.490000
Modified	2019-01-28 16:18:33.703000
Parameters	15

Parameters

#	Parameter	Type	Direction	Description
1	@pHeadingId	int	INPUT	p Heading identifier
2	@pKeywordId	int	INPUT	p Keyword identifier
3	@pDescription	varchar(1024)	INPUT	p description
4	@pUnitId	int	INPUT	p Unit identifier
5	@pBrandName	varchar(255)	INPUT	p Brand name
6	@pManufacturorNu	varchar(50)	INPUT	p Manufacturor number
7	@pVendorId	int	INPUT	p Vendor identifier
8	@pVendorPartNum	varchar(50)	INPUT	p Vendor Part number
9	@pItemsPerUnit	varchar(50)	INPUT	p Items Per Unit parameter
10	@pListPrice	money	INPUT	p List price
11	@pExtraDetail	varchar(1024)	INPUT	p Extra Detail parameter
12	@pRequisitionId	int	INPUT	p Requisition identifier
13	@pQuantity	int	INPUT	p quantity
14	@sessionID	int	INPUT	session identifier

15	@pVendorToSupply	tinyint	INPUT	p Vendor To Supply Manufacturer p

Definition

```
CREATE procedure [dbo].[sp_CCAddAddendaItem] @pHeadingId int, @pKeywordId int, @pDescri...

                                        @pUnitId int, @pBrandName varchar(255), @pManufac...

                                        @pVendorPartNumber varchar(50), @pItemsPerUnit va...

                                        @pRequisitionId int, @pQuantity int, @sessionID i...

as





/*

declare @pHeadingId int, @pKeywordId int, @pDescription varchar(1024),

                                        @pUnitId int, @pBrandName varchar(255), @pManufac...

                                        @pVendorPartNumber varchar(50), @pItemsPerUnit va...

                                        @pRequisitionId int, @pQuantity int



set @pHeadingId = 59722

set @pKeywordId = 3771

set @pDescription = 'This is an addednda test'

set @pUnitId =1374

set @pBrandName = 'BobManu'

set @pManufacturorNumber = NULL

set @pVendorId = 984
```

```
set @pVendorPartNumber = '1234'

set @pItemsPerUnit = '21'

set @pListPrice = 12.00

set @pExtraDetail = NULL

set @pRequisitionId = 1242664

... (truncated)
```

sp_CCAddAddendaMaint {sp-dbo-sp-ccaddaddendamaint}

> Stored procedure: CCAddAddendaMaint

Property	Value
Schema	dbo
Created	2009-12-07 16:06:02.030000
Modified	2015-11-24 23:37:29.380000
Parameters	13

Parameters

#	Parameter	Type	Direction	Description
1	@pHeadingId	int	INPUT	p Heading identifier
2	@pKeywordId	int	INPUT	p Keyword identifier
3	@pDescription	varchar(1024)	INPUT	p description
4	@pUnitId	int	INPUT	p Unit identifier
5	@pBrandName	varchar(255)	INPUT	p Brand name
6	@pManufacturorNu	varchar(50)	INPUT	p Manufacturor number
7	@pVendorId	int	INPUT	p Vendor identifier
8	@pVendorPartNum	varchar(50)	INPUT	p Vendor Part number
9	@pItemsPerUnit	varchar(50)	INPUT	p Items Per Unit parameter
10	@pListPrice	money	INPUT	p List price

11	@pExtraDetail	varchar(1024)	INPUT	p Extra Detail parameter
12	@pDistrictId	int	INPUT	p District identifier
13	@pCategoryId	int	INPUT	p Category identifier

Definition

```
CREATE procedure [dbo].[sp_CCAddAddendaMaint] @pHeadingId int, @pKeywordId int, @pDescr...

                                        @pUnitId int, @pBrandName varchar(255), @pManufac...

                                        @pVendorPartNumber varchar(50), @pItemsPerUnit va...

                                        @pDistrictId int, @pCategoryId int

as

declare @NextNumber varchar(50),

@DistrictCode varchar(16),

@DistrictId int,

@CategoryId int,

@ItemId int,

@UnitCode varchar(16),

@PricePlanId int,

@CatalogId int



  select @DistrictCode = District.DistrictCode,

         @DistrictId = District.DistrictId

    from dbo.District

   where District.DistrictId = @pDistrictId



  if isnull(@DistrictCode,'') = ''

  begin

    select @DistrictCode = ''

  end
```

```
    select @CategoryId = Category.CategoryId,

  ... (truncated)
```

sp_CCAnalysisReturn {sp-dbo-sp-ccanalysisreturn}

> Stored procedure: CCAnalysisReturn

Property	Value
Schema	dbo
Created	2007-06-26 13:59:48.983000
Modified	2009-03-25 06:55:28.223000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pRSId	int	INPUT	p RS identifier
3	@pAction	int	INPUT	p Action parameter

Definition

```
CREATE  procedure dbo.sp_CCAnalysisReturn @pSessionId int, @pRSId int, @pAction int as



if @pAction = 1 -- Keep 'Pending Analysis' Status

begin

  insert Approvals (ApprovalById, Level, StatusId, RequisitionId, ApprovalDate, Approve...

    select SessionTable.UserId, SessionTable.ApprovalLevel, 28, Requisitions.Requisitio...

      from SessionTable

      join ReportSession on ReportSession.RSId = @pRSId

      join ReportSessionLinks rsl on rsl.RSId = ReportSession.RSId

      join Requisitions on Requisitions.RequisitionId = rsl.IntId

      left outer join Approvals on Approvals.ApprovalId =

          (select top 1 ap.ApprovalId

             from Approvals ap

            where ap.RequisitionId = Requisitions.RequisitionId

            order by ap.ApprovalDate desc)

     where Sessiontable.SessionId = @pSessionId

       and isnull(Approvals.StatusId,0) != 28

end

else

if @pAction = 2 -- Change to On-Hold

begin

  insert Approvals (ApprovalById, Level, StatusId, RequisitionId, ApprovalDate, Approve...

    select SessionTable.UserId, SessionTable.ApprovalLevel, 1, Requisitions.Requisition...
```

```
        from SessionTable

        join ReportSession on ReportSession.RSId = @pRSId

  ... (truncated)
```

sp_CCItemMaint {sp-dbo-sp-ccitemmaint}

> Item management procedure for CCMaint

Property	Value
Schema	dbo
Created	2003-05-21 23:16:51.090000
Modified	2019-08-01 07:59:19.477000
Parameters	22

Parameters

#	Parameter	Type	Direction	Description
1	@pItemId	int	INPUT	p Item identifier
2	@pActive	tinyint	INPUT	p Active parameter
3	@pCategoryId	int	INPUT	p Category identifier
4	@pItemCode	varchar(50)	INPUT	p Item code
5	@pDescription	varchar(512)	INPUT	p description
6	@pUnitId	int	INPUT	p Unit identifier
7	@pParentCatalogId	int	INPUT	p Parent Catalog identifier
8	@pHeadingId	int	INPUT	p Heading identifier
9	@pRTK	tinyint	INPUT	p RTK parameter
10	@pEditionId	int	INPUT	p Edition identifier
11	@pCopyrightYear	int	INPUT	p Copyright Year parameter
12	@pDistrictId	int	INPUT	p District identifier
13	@pBrandName	varchar(50)	INPUT	p Brand name
14	@pManufacturorNu	varchar(50)	INPUT	p Manufacturor number

15	@pVendorId	int	INPUT	p Vendor identifier
16	@pVendorPartNum	varchar(50)	INPUT	p Vendor Part number
17	@pItemsPerUnit	varchar(50)	INPUT	p Items Per Unit parameter
18	@pListPrice	money	INPUT	p List price
19	@pExtraDetail	varchar(1024)	INPUT	p Extra Detail parameter
20	@pShortDescriptior	varchar(60)	INPUT	p Short description
21	@pKeywordId	int	INPUT	p Keyword identifier
22	@pAlternateItemCo	varchar(50)	INPUT	p Alternate Item code

Definition

```
CREATE procedure [dbo].[sp_CCItemMaint]

@pItemId int,

@pActive tinyint,

@pCategoryId int,

@pItemCode varchar(50),

@pDescription varchar(512),

@pUnitId int,

@pParentCatalogId int,

@pHeadingId int,

@pRTK tinyint,

@pEditionId int,

@pCopyrightYear int,

@pDistrictId int,

@pBrandName varchar(50),

@pManufacturorNumber varchar(50),

@pVendorId int,

@pVendorPartNumber varchar(50),

@pItemsPerUnit varchar(50),

@pListPrice money,

@pExtraDetail varchar(1024),
```

```
@pShortDescription varchar(60),

@pKeywordId int,

@pAlternateItemCode varchar(50) as
```

```
declare @ItemId int,

... (truncated)
```

sp_CCSchoolMaint {sp-dbo-sp-ccschoolmaint}

> Stored procedure: CCSchoolMaint

Property	Value
Schema	dbo
Created	2004-09-30 20:37:39.607000
Modified	2015-11-24 23:37:29.730000
Parameters	16

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pSchoolId	int	INPUT	p School identifier
3	@pSchoolName	varchar(50)	INPUT	p School name
4	@pSchoolAddr1	varchar(255)	INPUT	p School Addr1 parameter
5	@pSchoolAddr2	varchar(255)	INPUT	p School Addr2 parameter
6	@pSchoolAddr3	varchar(255)	INPUT	p School Addr3 parameter
7	@pSchoolCity	varchar(255)	INPUT	p School City parameter
8	@pSchoolState	varchar(255)	INPUT	p School State parameter
9	@pSchoolZip	varchar(255)	INPUT	p School Zip parameter
10	@pPhoneNumber	varchar(255)	INPUT	p Phone number
11	@pFax	varchar(255)	INPUT	p Fax parameter
12	@pEMail	varchar(255)	INPUT	p EMail parameter
13	@pLocationCode	varchar(255)	INPUT	p Location code
14	@pAction	tinyint	INPUT	p Action parameter

15	@pShippingId	int	INPUT	p Shipping identifier
16	@pActive	int	INPUT	p Active parameter

Definition

```
CREATE procedure [dbo].[sp_CCSchoolMaint] @pSessionId int, @pSchoolId int, @pSchoolName...



declare @DistrictId int,

@SchoolId int,

@ShippingId int,

@References int,

@AddressId int



select @DistrictId = ISNULL(DistrictId,0)

  from SessionTable

 where SessionId = @pSessionId



if @pAction = 1

begin

  insert ShipLocations (DistrictId, Active, Name, Address1, Address2, Address3, City, S...

    values (@DistrictId, 1, rtrim(@pSchoolName), rtrim(@pSchoolAddr1), rtrim(@pSchoolAd...



  select @ShippingId = Scope_Identity() --DCH 11/24/2015 @@IDENTITY



  insert School (DistrictId, Active, Name, Address1, Address2, Address3, City, State, Z...

    values (@DistrictId, 1, rtrim(@pSchoolName), rtrim(@pSchoolAddr1), rtrim(@pSchoolAd...



  select @SchoolId = Scope_Identity() --DCH 11/24/2015 @@IDENTITY
```

```
end

else

... (truncated)
```

sp_CCUpdateAddendaItem {sp-dbo-sp-ccupdateaddendaitem}

> Item management procedure for CCUpdateAddenda

Property	Value
Schema	dbo
Created	2009-12-04 14:59:29.790000
Modified	2014-10-07 17:53:22.107000
Parameters	16

Parameters

#	Parameter	Type	Direction	Description
1	@pHeadingId	int	INPUT	p Heading identifier
2	@pKeywordId	int	INPUT	p Keyword identifier
3	@pDescription	varchar(1024)	INPUT	p description
4	@pUnitId	int	INPUT	p Unit identifier
5	@pBrandName	varchar(255)	INPUT	p Brand name
6	@pManufacturorNu	varchar(50)	INPUT	p Manufacturor number
7	@pVendorId	int	INPUT	p Vendor identifier
8	@pVendorPartNum	varchar(50)	INPUT	p Vendor Part number
9	@pItemsPerUnit	varchar(50)	INPUT	p Items Per Unit parameter
10	@pListPrice	money	INPUT	p List price
11	@pExtraDetail	varchar(1024)	INPUT	p Extra Detail parameter
12	@pRequisitionId	int	INPUT	p Requisition identifier
13	@pQuantity	int	INPUT	p quantity

14	@pDetailId	int	INPUT	p Detail identifier
15	@sessionID	int	INPUT	session identifier
16	@pVendorToSupply	tinyint	INPUT	p Vendor To Supply Manufacturer p

Definition

```
CREATE procedure [dbo].[sp_CCUpdateAddendaItem] @pHeadingId int, @pKeywordId int, @pDes...

                                        @pUnitId int, @pBrandName varchar(255), @pManufac...

                                        @pVendorPartNumber varchar(50), @pItemsPerUnit va...

                                        @pRequisitionId int, @pQuantity int, @pDetailId i...

as

declare @ItemId int,

@BidItemId int,

@UnitCode varchar(16),

@PricePlanId int



  -- Get Detail Record Info

  select @ItemId = ItemId,

         @BidItemId = BidItemId

    from Detail with (nolock)

   where DetailId = @pDetailId



  -- Get Unit Code Description

  select @UnitCode = Code

    from Units with (nolock)

   where UnitId = @pUnitId



  if @@rowcount = 0

  begin
```

```
      select @UnitCode = ''

    end

  ... (truncated)
```

sp_CCUpdateAddendaItemSizesOnly {sp-dbo-sp-ccupdateaddendaitemsizesonly}

> Item management procedure for CCUpdateAddendaSizesOnly

Property	Value
Schema	dbo
Created	2005-01-27 12:36:27.827000
Modified	2013-09-24 09:31:33.277000
Parameters	5

Parameters

#	Parameter	Type	Direction	Description
1	@pListPrice	money	INPUT	p List price
2	@pExtraDetail	varchar(1024)	INPUT	p Extra Detail parameter
3	@pRequisitionId	int	INPUT	p Requisition identifier
4	@pQuantity	int	INPUT	p quantity
5	@pDetailId	int	INPUT	p Detail identifier

Definition

```
CREATE   procedure [dbo].[sp_CCUpdateAddendaItemSizesOnly] @pListPrice money, @pExtraDe...

                                        @pRequisitionId int, @pQuantity int, @pDetailId int

as

declare @ItemId int,

@BidItemId int,

@PricePlanId int



  -- Get Detail Record Info

  select @ItemId = ItemId,

         @BidItemId = BidItemId

    from Detail

   where DetailId = @pDetailId



  if isnull(@BidItemId,0) = 0

  begin

    -- Update Item

    Update Items

       set   ListPrice = convert(money,@pListPrice)

--           ExtraDetail = @pExtraDetail

     where ItemId = @ItemId



    -- Update Detail

    Update Detail
```

```
        set Quantity = @pQuantity,

            ExtraDescription = @pExtraDetail

... (truncated)
```

sp_CCUpdateAddendaMaint {sp-dbo-sp-ccupdateaddendamaint}

> Stored procedure: CCUpdateAddendaMaint

Property	Value
Schema	dbo
Created	2009-12-04 15:10:22.757000
Modified	2013-09-24 09:31:16.537000
Parameters	12

Parameters

#	Parameter	Type	Direction	Description
1	@pHeadingId	int	INPUT	p Heading identifier
2	@pKeywordId	int	INPUT	p Keyword identifier
3	@pDescription	varchar(1024)	INPUT	p description
4	@pUnitId	int	INPUT	p Unit identifier
5	@pBrandName	varchar(255)	INPUT	p Brand name
6	@pManufacturorNu	varchar(50)	INPUT	p Manufacturor number
7	@pVendorId	int	INPUT	p Vendor identifier
8	@pVendorPartNuml	varchar(50)	INPUT	p Vendor Part number
9	@pItemsPerUnit	varchar(50)	INPUT	p Items Per Unit parameter
10	@pListPrice	money	INPUT	p List price
11	@pExtraDetail	varchar(1024)	INPUT	p Extra Detail parameter
12	@pItemId	int	INPUT	p Item identifier

Definition

```
CREATE procedure [dbo].[sp_CCUpdateAddendaMaint] @pHeadingId int, @pKeywordId int, @pDe...

                                        @pUnitId int, @pBrandName varchar(255), @pManufac...

                                        @pVendorPartNumber varchar(50), @pItemsPerUnit va...

                                        @pItemId int

as

declare @ItemId int,

@BidItemId int,

@UnitCode varchar(16),

@PricePlanId int



  -- Get Detail Record Info

  select @ItemId = ItemId

    from Items

   where ItemId = @pItemId



  -- Update Item

  Update Items

     set HeadingId = @pHeadingId,

         KeywordId = @pKeywordId,

         [Description] = @pDescription,

         UnitId = @pUnitId,

         BrandName = @pBrandName,
```

```
            ManufacturorNumber = @pManufacturorNumber,

            VendorId = @pVendorId,

            VendorPartNumber = @pVendorPartNumber,

   ... (truncated)
```

sp_CCUpdateResults {sp-dbo-sp-ccupdateresults}

> Stored procedure: CCUpdateResults

Property	Value
Schema	dbo
Created	2004-11-09 13:14:10.540000
Modified	2009-03-25 06:55:28.660000
Parameters	5

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pRequisitionId	int	INPUT	p Requisition identifier
3	@pDetailId	varchar(20)	INPUT	p Detail identifier
4	@pItemId	int	INPUT	p Item identifier
5	@pQuantity	varchar(20)	INPUT	p quantity

Definition

```
CREATE procedure dbo.sp_CCUpdateResults @pSessionId int, @pRequisitionId int, @pDetailI...

declare @Sessionid int,

@RequisitionId int,

@DetailId int,

@ItemId int,

@Quantity int



-- Validate Session

select @SessionId = SessionId

  from SessionTable

 where SessionId = @pSessionId



if @@rowcount = 0

begin

  raiserror('Invalid SessionId',16,1)

  return

end



-- Validate Requisition

select @RequisitionId = RequisitionId

  from Requisitions

 where RequisitionId = @pRequisitionId
```

```
if @@rowcount = 0

begin

... (truncated)
```

sp_CCUpdateUserAccounts {sp-dbo-sp-ccupdateuseraccounts}

> User management procedure for CCUpdateAccounts

Property	Value
Schema	dbo
Created	2004-02-16 12:12:16.543000
Modified	2015-11-24 23:37:28
Parameters	8

Parameters

#	Parameter	Type	Direction	Description
1	@pCode	varchar(255)	INPUT	p code
2	@pAllocationAmour	money	INPUT	p Allocation amount
3	@pBudgetAmount	money	INPUT	p Budget amount
4	@pDistrictId	int	INPUT	p District identifier
5	@pUserId	int	INPUT	p User identifier
6	@pUserAccountId	int	INPUT	p User Account identifier
7	@pSchoolId	int	INPUT	p School identifier
8	@pDelete	int	INPUT	p Delete parameter

Definition

```
CREATE procedure [dbo].[sp_CCUpdateUserAccounts] @pCode varchar(255), @pAllocationAmoun...

declare @AccountId int,

@BudgetAccountId int,

@SchoolId int,

@UserAccountId int,

@BudgetId int



if @pDelete = 1

begin

  delete UserAccounts

   where UserAccountId = @pUserAccountId

end

else

if rtrim(@pCode) != ''

begin

select top 1 @BudgetId = Budgets.BudgetId

  from Budgets

  join Users on Users.DistrictId = Budgets.DistrictId

and Users.UserId = @pUserId

 where GETDATE() between case when isnull(Users.AllowEarlyAccess,0) = 1 or Users.Appro...

 and Budgets.VisibleUntil

/* DCH 10/6/14 Code above replaces this code for Early Access

   Budgets.VisibleFrom <= getdate()
```

```
    and Budgets.VisibleUntil >= getdate()*/

    and Budgets.DistrictId = @pDistrictId

  ... (truncated)
```

sp_CCUpdateUserAccounts_2 {sp-dbo-sp-ccupdateuseraccounts-2}

> User management procedure for CCUpdateAccounts_2

Property	Value
Schema	dbo
Created	2008-05-19 16:30:36.327000
Modified	2014-10-07 17:53:25.150000
Parameters	5

Parameters

#	Parameter	Type	Direction	Description
1	@pOldCode	varchar(255)	INPUT	p Old code
2	@pNewCode	varchar(255)	INPUT	p New code
3	@pUserId	int	INPUT	p User identifier
4	@pDistrictId	int	INPUT	p District identifier
5	@pBudgetId	int	INPUT	p Budget identifier

Definition

```
CREATE procedure [dbo].[sp_CCUpdateUserAccounts_2]

                  @pOldCode varchar(255),                              -- Users accou...

                  @pNewCode varchar(255),                              -- New account...

                  @pUserId int,                                        -- required

                  @pDistrictId int,                                    -- required

                  @pBudgetId int = null                                -- required if...

as

declare @OldAccountId int,

@BudgetAccountId int,

@UserSchoolId int,

@NewAccountId int,

@NewAccountSchoolId int,

@UserAccountId int,

@BudgetId int,

@RowCount int

--@UserId int




-- sample use: Execute sp_CCUpdateUserAccounts_2  '151901000610000336036600 0', '1500022...

-- different school: 150002220600000314014000  (15898)

--      same school: 150002400600000336036666 2 (15894)

--                   151901000610000336036600 0 (15894)
```

```
-- If BudgetId not specified (e.g. null), determine budgetid to use  (Note: if more tha...

if @pBudgetId = null

... (truncated)
```

sp_CCUpdateUserAccountsBulk {sp-dbo-sp-ccupdateuseraccountsbulk}

> User management procedure for CCUpdateAccountsBulk

Property	Value
Schema	dbo
Created	2004-02-19 00:44:20.607000
Modified	2015-11-24 23:37:27.653000
Parameters	14

Parameters

#	Parameter	Type	Direction	Description
1	@pActive	int	INPUT	p Active parameter
2	@pCometId	varchar(255)	INPUT	p Comet identifier
3	@pUserName	varchar(255)	INPUT	p User name
4	@pPassword	varchar(255)	INPUT	p Password parameter
5	@pAttention	varchar(255)	INPUT	p Attention parameter
6	@pUseAllocations	int	INPUT	p Use Allocations parameter
7	@pCode	varchar(255)	INPUT	p code
8	@pAllocationAmour	money	INPUT	p Allocation amount
9	@pDistrictId	int	INPUT	p District identifier
10	@pUserId	int	INPUT	p User identifier
11	@pUserAccountId	int	INPUT	p User Account identifier
12	@pSchoolId	int	INPUT	p School identifier
13	@pDelete	int	INPUT	p Delete parameter

14	@pDistrictAccounti	varchar(255)	INPUT	p District Accounting code

Definition

```
CREATE procedure [dbo].[sp_CCUpdateUserAccountsBulk] @pActive int, @pCometId varchar(25...

declare @AccountId int,

@BudgetAccountId int,

@SchoolId int,

@UserAccountId int,

@BudgetId int



if @pDelete = 1

begin

  delete UserAccounts

   where UserAccountId = @pUserAccountId

end

else

if rtrim(@pCode) != ''

begin

select top 1 @BudgetId = Budgets.BudgetId

  from Budgets

  join Users on Users.DistrictId = Budgets.DistrictId

             and Users.UserId = @pUserId

 where GETDATE() between case when isnull(Users.AllowEarlyAccess,0) = 1 or Users.Approv...
```

```
                        and Budgets.VisibleUntil

  /* DCH 10/6/14 Code above replaces this code for Early Access

          Budgets.VisibleFrom <= getdate()

     and Budgets.VisibleUntil >= getdate()*/

     and Budgets.DistrictId = @pDistrictId

  ... (truncated)
```

sp_CCUserAccountMaint {sp-dbo-sp-ccuseraccountmaint}

> User management procedure for CCAccountMaint

Property	Value
Schema	dbo
Created	2004-10-02 16:43:28.573000
Modified	2009-03-25 06:55:28.270000
Parameters	9

Parameters

#	Parameter	Type	Direction	Description
1	@pUserAccountId	int	INPUT	p User Account identifier
2	@pBudgetAccountI	int	INPUT	p Budget Account identifier
3	@pAllocationAmour	decimal(11,2)	INPUT	p Allocation amount
4	@pUseAllocations	int	INPUT	p Use Allocations parameter
5	@pBudgetId	int	INPUT	p Budget identifier
6	@pUserId	int	INPUT	p User identifier
7	@pActive	int	INPUT	p Active parameter
8	@pAccountEntry	varchar(50)	INPUT	p Account Entry parameter
9	@pAction	tinyint	INPUT	p Action parameter

Definition

```
CREATE    procedure dbo.sp_CCUserAccountMaint @pUserAccountId int, @pBudgetAccountId in...

declare @AccountId int,

@UserAccountId int,

@BudgetAccountId int,

@DistrictId int,

@SchoolId int,

@Account_SchoolId int,

@Account_Active int,

@BA_Active int,

@UA_Active int,

@UA_AllocationAmount decimal(11,2),

@UA_UseAllocations int,

@UA_BudgetAccountId int,

@LinkCount int



set nocount on



-- Get District id

select @DistrictId = DistrictId

  from Budgets

 where BudgetId = @pBudgetId
```

```
-- Get School Id

select @SchoolId = SchoolId

  from Users

... (truncated)
```

sp_CCUserGridMaint {sp-dbo-sp-ccusergridmaint}

> User management procedure for CCGridMaint

Property	Value
Schema	dbo
Created	2004-10-03 16:24:21.550000
Modified	2025-01-31 20:46:50.710000
Parameters	34

Parameters

#	Parameter	Type	Direction	Description
1	@pUserId	int	INPUT	p User identifier
2	@pActive	int	INPUT	p Active parameter
3	@pCometId	int	INPUT	p Comet identifier
4	@pUserName	varchar(50)	INPUT	p User name
5	@pPassword	varchar(100)	INPUT	p Password parameter
6	@pAttention	varchar(50)	INPUT	p Attention parameter
7	@pApproverId	int	INPUT	p Approver identifier
8	@pApprovalLevel	int	INPUT	p Approval Level parameter
9	@pNewRequisitionE	int	INPUT	p New Requisition Button paramete
10	@pDistrictAcctgCod	varchar(50)	INPUT	p District Acctg code
11	@pShippingId	int	INPUT	p Shipping identifier
12	@pSchoolId	int	INPUT	p School identifier
13	@pDistrictId	int	INPUT	p District identifier

14	@pBudgetAccountI	int	INPUT	p Budget Account identifier
15	@pAllocationAmour	varchar(50)	INPUT	p Allocation amount
16	@pUseAllocations	int	INPUT	p Use Allocations parameter
17	@pUserAccountId	int	INPUT	p User Account identifier
18	@pBudgetId	int	INPUT	p Budget identifier
19	@pAction	int	INPUT	p Action parameter
20	@pAllowIncidentals	tinyint	INPUT	p Allow Incidentals parameter
21	@pAllowVendorCha	tinyint	INPUT	p Allow Vendor Changes parameter
22	@pAllowShipToCha	tinyint	INPUT	p Allow Ship To Changes paramete
23	@pAllowTM	tinyint	INPUT	p Allow TM parameter
24	@pAllowMSRP	tinyint	INPUT	p Allow MSRP parameter
25	@pEMail	varchar(255)	INPUT	p EMail parameter
26	@pUseNewSys	int	INPUT	p Use New Sys parameter
27	@pAllowAddenda	int	INPUT	p Allow Addenda parameter
28	@pIBTypeId	int	INPUT	p IBType identifier
29	@pHasAdminAcces	tinyint	INPUT	p Has Admin Access parameter
30	@pAllowAccountCo	int	INPUT	p Allow Account Code Mgmt param
31	@pAllowEarlyAcces	int	INPUT	p Allow Early Access parameter
32	@pAllowPOAccess	int	INPUT	p Allow POAccess parameter
33	@pAllowVendorCod	tinyint	INPUT	p Allow Vendor Code Maint parame
34	@pNotificationType	int	INPUT	p Notification type

Definition

```
CREATE        procedure [dbo].[sp_CCUserGridMaint] @pUserId int, @pActive int, @pCometI...

                                                   @pPassword varchar(100), @pAttention ...

                                                   @pApprovalLevel int, @pNewRequisition...

                                                   @pShippingId int, @pSchoolId int, @pD...

                                                   @pAllocationAmount varchar(50), @pUse...

                                                   @pBudgetId int, @pAction int, @pAllow...

                                                   @pAllowVendorChanges tinyint, @pAllow...

                                                   @pAllowMSRP tinyint, @pEMail varchar(...

                                                   @pAllowAddenda int, @pIBTypeId int, @...

                                                   @pAllowAccountCodeMgmt int, @pAllowEa...

declare @UserAccountId int,

@AccountId int,

@UserId int,

@AllocationAmount money,

@LinkCount int,

@ExistingCometId int



set nocount on

insert DebugMsgs (Msg)

  values(left('@UserId=' + isnull(CAST(@pUserId as varchar(50)),'<null>') +

          ' Active=' + isnull(CAST(@pActive as varchar(50)),'<null>') +

          ' CometId=' + isnull(CAST(@pCometId as varchar(50)),'<null>') +

          ' UserName=' + isnull(CAST(@pUserName as varchar(50)),'<null>') +
```

```
            ' Password=' + isnull(CAST(@pPassword as varchar(100)),'<null>') +

            ' Attention=' + isnull(CAST(@pAttention as varchar(50)),'<null>') +

... (truncated)
```

sp_CombineReqs {sp-dbo-sp-combinereqs}

> Stored procedure: CombineReqs

Property	Value
Schema	dbo
Created	2007-06-04 10:46:17.263000
Modified	2015-07-10 13:36:30.773000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@pRSId	int	INPUT	p RS identifier
2	@pDelete	tinyint	INPUT	p Delete parameter
3	@rRequisitionId	int	OUTPUT	r Requisition identifier

Definition

```
CREATE    procedure [dbo].[sp_CombineReqs] @pRSId int, @pDelete tinyint, @rRequisitionI...



-- Declare Local Variables

declare@RequisitionId int,

@DistrictId int,

@CategoryId int,

@SchoolId int,

@UserId int,

@BudgetId int,

@AccountId int,

@BudgetAccountId int,

@UserAccountId int,

@AccountCode varchar(30),

@Total money,

@TodaysDate datetime,

@Qty int,

@ItemId int,

@DetailId int,

@DelReqId int,

@rStatus int,

@SourceId int,

@StatusId int
```

```
set transaction isolation level read uncommitted

insert DebugMsgs(Msg) values ('Start dbo.sp_CombineReqs RSId=' + cast(@pRSId as varchar...

... (truncated)
```

sp_CombineReqsByVendorNoDelete {sp-dbo-sp-combinereqsbyvendornodelete}

> Vendor management procedure for CombineReqsByNoDelete

Property	Value
Schema	dbo
Created	2008-06-16 09:52:45.997000
Modified	2015-03-24 14:59:07.783000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pRSId	int	INPUT	p RS identifier
3	@rRequisitionId	int	OUTPUT	r Requisition identifier

Definition

```
CREATE  procedure [dbo].[sp_CombineReqsByVendorNoDelete] @pSessionId int, @pRSId int, @...



-- Declare Local Variables

declare@RequisitionId int,

@DistrictId int,

@CategoryId int,

@SchoolId int,

@UserId int,

@BudgetId int,

@AccountId int,

@BudgetAccountId int,

@UserAccountId int,

@AccountCode varchar(30),

@Total money,

@TodaysDate datetime,

@Qty int,

@ItemId int,

@DetailId int,

@DelReqId int,

@rStatus int,

@SourceId int,

@StatusId int,

@VendorId int
```

```
insert DebugMsgs(Msg) values ('Start dbo.sp_CombineReqsByVendorNoDelete RSId=' + cast(@...

... (truncated)
```

sp_CometLoad {sp-dbo-sp-cometload}

> Stored procedure: CometLoad

Property	Value
Schema	dbo
Created	2002-02-19 08:08:40.577000
Modified	2015-11-24 23:37:34.373000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@pSourceFile	varchar(255)	INPUT	p Source File parameter
2	@pDistrictCode	varchar(2)	INPUT	p District code
3	@pCategoryCode	varchar(1)	INPUT	p Category code

Definition

```
CREATE procedure [dbo].[sp_CometLoad] @pSourceFile varchar(255), @pDistrictCode varchar...



-- Create Temp Table

create table #ImportBatch (

DataRowvarchar(256),

RowIdint identity(1,1)

)



-- Declare Local Varaiables

declare @Records int,

@BatchId int,

@SQLStmt varchar(1024)



print 'Ready to Import DataFile'



-- Build Load Ascii File into TempDB statement

select @SQLStmt = 'BULK INSERT #ImportBatch FROM ''' + @pSourceFile + ''' WITH (FORMATF...



execute(@SQLStmt)
```

```
print 'Data File Loaded'



-- Get Import Count
```

```
select @Records = count(RowId) from #ImportBatch



... (truncated)
```

sp_ConvertReqs {sp-dbo-sp-convertreqs}

> Stored procedure: ConvertReqs

Property	Value
Schema	dbo
Created	2002-03-20 22:18:07.060000
Modified	2022-04-01 08:49:58.957000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pRSId	int	INPUT	p RS identifier

Definition

```
CREATE          procedure [dbo].[sp_ConvertReqs] @pSessionId int, @pRSId int AS



declare @ReqId int,

@DistrictId int,

@ReqList varchar(max) = '',

@ErrorMsg varchar(max) = ''



set transaction isolation level read uncommitted



select @ReqList = STRING_AGG(cast(Requisitions.RequisitionNumber as varchar(max)),', ')

  from ReportSessionLinks

  join Requisitions on Requisitions.RequisitionId = ReportSessionLinks.IntId

  outer apply (Select sum(rsc.Extended + rsc.ShippingCost + rsc.TotalShippingCost) Tota...

 where ReportSessionLinks.RSId = @pRSId

   and coalesce(Requisitions.TotalRequisitionCost,0) != coalesce(ReqTotal.Total,0)



if isnull(@ReqList,'') = ''

begin

declare ReqCur cursor fast_forward read_only for

select RequisitionId

  from ReportSessionLinks

  join Requisitions on Requisitions.RequisitionId = ReportSessionLinks.IntId

  join Users on Users.UserId = Requisitions.UserId
```

```
    where ReportSessionLinks.RSId = @pRSId

    order by Requisitions.CategoryId, Requisitions.SchoolId, Users.CometId, Requisitions....

   ... (truncated)
```

sp_ConvertTextbookReqs {sp-dbo-sp-converttextbookreqs}

> Stored procedure: ConvertTextbookReqs

Property	Value
Schema	dbo
Created	2002-06-12 15:13:07.530000
Modified	2009-07-16 13:30:14.573000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pRSId	int	INPUT	p RS identifier
3	@pBidHeaderId	int	INPUT	p Bid Header identifier

Definition

```
CREATE      procedure [dbo].[sp_ConvertTextbookReqs] @pSessionId int, @pRSId int, @pBid...



declare @RequisitionId int,

@VendorId int,

@POId int,

@DistrictId int,

@AwardId int,

@StatusId int,

@AtEDSId int,

@HoldDistrictId int



select @StatusId = StatusId

  from StatusTable

 where StatusCode = 'O'



select @AtEDSId = StatusId

  from StatusTable

 where StatusCode = 'I'



Delete ReportSessionLinks
```

```
  from ReportSessionLinks

  join Requisitions on Requisitions.RequisitionId = ReportSessionLinks.IntId

  join Detail on Detail.RequisitionId = Requisitions.RequisitionId
```

```
 join PODetailItems on PODetailItems.DetailId = Detail.DetailId

where ReportSessionLinks.RSId = @pRSId

... (truncated)
```

sp_CopyBidImport {sp-dbo-sp-copybidimport}

> Purchase order procedure for Bid

Property	Value
Schema	dbo
Created	2004-04-14 00:27:38.690000
Modified	2009-03-25 06:55:28.457000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pBidImportId	int	INPUT	p Bid Import identifier
2	@pNewImportId	int	OUTPUT	p New Import identifier

Definition

```
CREATE procedure sp_CopyBidImport @pBidImportId int, @pNewImportId int output as

declare @BidImportId int



select @BidImportId = max(BidImportId) + 1 from BidImports



INSERT INTO [EDS].[dbo].[BidImports]([BidImportId], [BidHeaderId], [Active], [VendorId]...

  SELECT @BidImportId, [BidHeaderId], [Active], [VendorId], [BidItemDiscountRate], [Cat...

    FROM [EDS].[dbo].[BidImports]

   WHERE BidImports.BidImportId = @pBidImportId



INSERT INTO [EDS].[dbo].[BidResults]([BidImportId], [BidHeaderId], [BidRequestItemId], ...

  SELECT @BidImportId, [BidHeaderId], [BidRequestItemId], [CategoryId], [DistrictId], [...

    FROM [EDS].[dbo].[BidResults]

   WHERE BidResults.BidImportId = @pBidImportId



select @pNewImportId = @BidImportId
```

sp_CopyBudgetAmounts {sp-dbo-sp-copybudgetamounts}

> Copy procedure for BudgetAmounts

Property	Value
Schema	dbo
Created	2013-12-05 07:37:52.613000
Modified	2013-12-05 09:17:04.373000

Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@sourceBudgetId	int	INPUT	source Budget identifier
2	@destBudgetId	int	INPUT	dest Budget identifier

Definition

```
--exec sp_CopyBudgetAmounts  6477,7144

CREATE procedure dbo.sp_CopyBudgetAmounts @sourceBudgetId int, @destBudgetId int as

begin transaction

declare @sourceDistrictId int,

@destDistrictId int



--get Source District

select @sourceDistrictId = DistrictId

  from Budgets

 where Budgets.BudgetId = @sourceBudgetId



--get Destination District

select @destDistrictId = DistrictId

  from Budgets

 where Budgets.BudgetId = @destBudgetId



--check for match

if ISNULL(@sourceDistrictId,0) != ISNULL(@destDistrictId,0)

begin

raiserror('Districts do not match!',16,1)

rollback

return

end
```

```
--unlink requisitions tied to BudgetAccounts/UserAccounts that will be deleted

... (truncated)
```

sp_CopyCalendar {sp-dbo-sp-copycalendar}

> Copy procedure for Calendar

Property	Value
Schema	dbo
Created	2012-09-25 16:38:41.657000
Modified	2017-11-27 13:28:21.340000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pOldYear	int	INPUT	p Old Year parameter
2	@pNewYear	int	INPUT	p New Year parameter

Definition

```
CREATE procedure [dbo].[sp_CopyCalendar] @pOldYear int, @pNewYear int as

/****** Script for SelectTopNRows command from SSMS  ******/

INSERT INTO [EDS].[dbo].[Calendars]

           ([Active]

           ,[BudgetYear]

           ,[ScheduleId]

           ,[CalendarTypeId]

           ,[Description]

           ,[HeaderText]

           ,[FooterText])

SELECT [Active]

      ,@pNewYear

      ,[ScheduleId]

      ,[CalendarTypeId]

      ,[Description]

      ,[HeaderText]

      ,[FooterText]

  FROM [EDS].[dbo].[Calendars]

 where BudgetYear = @pOldYear
```

```
INSERT INTO [EDS].[dbo].[CalendarIB]

           ([CalendarId]

           ,[IBTypeId]
```

```
            ,[ScheduleId]

            ,[CalendarTypeId])

  ... (truncated)
```

sp_CopyItems {sp-dbo-sp-copyitems}

> Item management procedure for s

Property	Value
Schema	dbo
Created	2012-11-12 14:15:58.197000
Modified	2012-11-14 09:33:45.473000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@pSourceDistrictId	int	INPUT	p Source District identifier
2	@pTargetDistrictId	int	INPUT	p Target District identifier
3	@pCategoryId	int	INPUT	p Category identifier

Definition

```
CREATE procedure [dbo].[sp_CopyItems] @pSourceDistrictId int, @pTargetDistrictId int, @...

as

INSERT INTO [EDS].[dbo].[Headings]

           ([Active]

           ,[CategoryId]

           ,[Code]

           ,[ExpandAll]

           ,[Title]

           ,[Description]

           ,[DistrictId])

SELECT Headings.[Active]

      ,Headings.[CategoryId]

      ,Headings.[Code]

      ,Headings.[ExpandAll]

      ,Headings.[Title]

      ,Headings.[Description]

      ,@pTargetDistrictId

  FROM [EDS].[dbo].[Headings]

  join Items on Items.HeadingId = Headings.HeadingId

            and Items.Active = 1

            and Items.DistrictId = @pSourceDistrictId

  left outer join Headings hnew on hnew.Active = 1

                                   and hnew.CategoryId = Headings.CategoryId
```

```
                                and hnew.DistrictId = @pTargetDistrictId

                                and hnew.Title = Headings.Title

... (truncated)
```

sp_CopyMSRPVers2Bid {sp-dbo-sp-copymsrpvers2bid}

> Copy procedure for MSRPVers2Bid

Property	Value
Schema	dbo
Created	2014-01-17 17:00:00.313000
Modified	2020-08-07 14:39:44.657000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@pOldBidHeaderId	varchar(50)	INPUT	p Old Bid Header identifier
2	@pNewBidHeaderId	varchar(50)	INPUT	p New Bid Header identifier
3	@ExcludeManufWit	tinyint	INPUT	Exclude Manuf With Bids paramete

Definition

```
-- ============================================

-- Author:Kevin

-- Create date: 1-17-2014

-- Description:Copy MSRP (Version 2) Bid

-- ============================================

CREATE procedure [dbo].[sp_CopyMSRPVers2Bid] @pOldBidHeaderId  varchar(50), @pNewBidHea...

AS

BEGIN



set nocount on



declare @CopyFromBidHeaderId int, @CopyToBidHeaderId int, @IncludeWriteInManuf int



Select @CopyFromBidHeaderId=CAST(@pOldBidHeaderId as int)

Select @CopyToBidHeaderId=CAST(@pNewBidHeaderId as int)



Select @IncludeWriteInManuf = 1  -- for now hardcode this to 1 - add as parameter as so...



IF @ExcludeManufWithBids = 1

BEGIN

  INSERT INTO BidRequestManufacturer

    (Active, BidHeaderId, ManufacturerId, SequenceNumber, AllowAdditionalProductLines, ...

  SELECT Active, @CopyToBidHeaderId, ManufacturerId, SequenceNumber, AllowAdditionalPro...
```

```
    FROM BidRequestManufacturer

    WHERE BidHeaderId=@CopyFromBidHeaderId

  ... (truncated)
```

sp_CopyMSRPVers2BidBackup {sp-dbo-sp-copymsrpvers2bidbackup}

> Copy procedure for MSRPVers2BidBackup

Property	Value
Schema	dbo
Created	2014-02-11 16:46:56.187000
Modified	2014-02-11 16:46:56.187000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pOldBidHeaderId	varchar(50)	INPUT	p Old Bid Header identifier
2	@pNewBidHeaderId	varchar(50)	INPUT	p New Bid Header identifier

Definition

```
-- ============================================

-- Author:Kevin

-- Create date: 1-17-2014

-- Description:Copy MSRP (Version 2) Bid

-- ============================================

CREATE procedure [dbo].[sp_CopyMSRPVers2BidBackup] @pOldBidHeaderId  varchar(50), @pNew...

AS

BEGIN



set nocount on



declare @CopyFromBidHeaderId int, @CopyToBidHeaderId int



Select @CopyFromBidHeaderId=CAST(@pOldBidHeaderId as int)

Select @CopyToBidHeaderId=CAST(@pNewBidHeaderId as int)





INSERT INTO BidRequestManufacturer

  (Active, BidHeaderId, ManufacturerId, SequenceNumber, AllowAdditionalProductLines, Us...

SELECT Active, @CopyToBidHeaderId, ManufacturerId, SequenceNumber, AllowAdditionalProdu...

FROM BidRequestManufacturer

WHERE BidHeaderId=@CopyFromBidHeaderId

      and BidRequestManufacturerId NOT IN
```

```
        (SELECT BidRequestManufacturerId FROM BidMSRPResults WHERE BidHeaderId = @CopyFro...
```

```
... (truncated)
```

sp_CopyMSRPVers2BidBackup-2014-10-29 {sp-dbo-sp-copymsrpvers2bidbackup-2014-10-29}

> Copy procedure for MSRPVers2BidBackup-2014-10-29

Property	Value
Schema	dbo
Created	2014-10-29 14:45:36.190000
Modified	2014-10-29 14:45:36.190000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@pOldBidHeaderId	varchar(50)	INPUT	p Old Bid Header identifier
2	@pNewBidHeaderIc	varchar(50)	INPUT	p New Bid Header identifier
3	@ExcludeManufWit	tinyint	INPUT	Exclude Manuf With Bids paramete

Definition

```
-- ============================================

-- Author:Kevin

-- Create date: 1-17-2014

-- Description:Copy MSRP (Version 2) Bid

-- ============================================

CREATE procedure [dbo].[sp_CopyMSRPVers2BidBackup-2014-10-29] @pOldBidHeaderId  varchar...

AS

BEGIN



set nocount on



declare @CopyFromBidHeaderId int, @CopyToBidHeaderId int



Select @CopyFromBidHeaderId=CAST(@pOldBidHeaderId as int)

Select @CopyToBidHeaderId=CAST(@pNewBidHeaderId as int)



IF @ExcludeManufWithBids = 1

BEGIN

  INSERT INTO BidRequestManufacturer

    (Active, BidHeaderId, ManufacturerId, SequenceNumber, AllowAdditionalProductLines, ...

  SELECT Active, @CopyToBidHeaderId, ManufacturerId, SequenceNumber, AllowAdditionalPro...

  FROM BidRequestManufacturer

  WHERE BidHeaderId=@CopyFromBidHeaderId
```

```
        and BidRequestManufacturerId NOT IN

            ( SELECT BidRequestManufacturerId FROM BidMSRPResults WHERE BidHeaderId = @...

... (truncated)
```

sp_CopyMSRPVers2BidUsingCursorSave {sp-dbo-sp-copymsrpvers2bidusingcursorsave}

> Copy procedure for MSRPVers2BidUsingCursorSave

Property	Value
Schema	dbo
Created	2014-01-17 16:57:13.840000
Modified	2015-11-24 23:37:42.357000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pOldBidHeaderId	varchar(50)	INPUT	p Old Bid Header identifier
2	@pNewBidHeaderId	varchar(50)	INPUT	p New Bid Header identifier

Definition

```
-- ============================================

-- Author:Kevin

-- Create date: 1-16-2014

-- Description:Copy MSRP (Version 2) Bid

-- ============================================

CREATE procedure [dbo].[sp_CopyMSRPVers2BidUsingCursorSave] @pOldBidHeaderId  varchar(5...

AS

BEGIN



set nocount on



declare @LoopCount int    -- THIS WAS USED TO LIMIT THE COUNT FOR INITIAL TESTING

declare @CopyFromBidHeaderId int, @CopyToBidHeaderId int



Select @CopyFromBidHeaderId=CAST(@pOldBidHeaderId as int)

Select @CopyToBidHeaderId=CAST(@pNewBidHeaderId as int)



declare @BidRequestManufacturerId int, @NewBidRequestManufacturerId int

declare @BidRequestProductLineId int, @NewBidRequestProductLineId int

declare @BidRequestPriceRangeId int, @NewBidRequestPriceRangeId int

declare @BidRequestOptionId int, @NewBidRequestOptionId int



-- Copy BidRequestManufacturer records
```

```
declare BRMCur cursor fast_forward read_only for

  select BidRequestManufacturerId

... (truncated)
```

sp_CopyMSRPVers2BidUsingCursorSave2 {sp-dbo-sp-copymsrpvers2bidusingcursorsave2}

> Copy procedure for MSRPVers2BidUsingCursorSave2

Property	Value
Schema	dbo
Created	2014-01-16 19:33:41.157000
Modified	2015-11-24 23:37:42.013000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pOldBidHeaderId	varchar(50)	INPUT	p Old Bid Header identifier
2	@pNewBidHeaderId	varchar(50)	INPUT	p New Bid Header identifier

Definition

```
-- ============================================

-- Author:Kevin

-- Create date: 1-16-2014

-- Description:Copy MSRP (Version 2) Bid

-- ============================================

CREATE procedure [dbo].[sp_CopyMSRPVers2BidUsingCursorSave2] @pOldBidHeaderId  varchar(...

AS

BEGIN



set nocount on



declare @LoopCount int    -- THIS WAS USED TO LIMIT THE COUNT FOR INITIAL TESTING

declare @CopyFromBidHeaderId int, @CopyToBidHeaderId int



Select @CopyFromBidHeaderId=CAST(@pOldBidHeaderId as int)

Select @CopyToBidHeaderId=CAST(@pNewBidHeaderId as int)



declare @BidRequestManufacturerId int, @NewBidRequestManufacturerId int

declare @BidRequestProductLineId int, @NewBidRequestProductLineId int

declare @BidRequestPriceRangeId int, @NewBidRequestPriceRangeId int

declare @BidRequestOptionId int, @NewBidRequestOptionId int



-- Copy BidRequestManufacturer records
```

```
declare BRMCur cursor fast_forward read_only for

  select BidRequestManufacturerId

... (truncated)
```

sp_CopyMSRPVers3Bid {sp-dbo-sp-copymsrpvers3bid}

> Copy procedure for MSRPVers3Bid

Property	Value
Schema	dbo
Created	2020-08-07 14:35:27.750000
Modified	2022-09-01 11:46:30.337000
Parameters	4

Parameters

#	Parameter	Type	Direction	Description
1	@pOldBidHeaderId	varchar(50)	INPUT	p Old Bid Header identifier
2	@pNewBidHeaderIc	varchar(50)	INPUT	p New Bid Header identifier
3	@ExcludeManufWit	tinyint	INPUT	Exclude Manuf With Bids paramete
4	@IncludeWriteInMa	tinyint	INPUT	Include Write In Manuf parameter

Definition

```
-- ============================================

-- Author:Kevin / David

-- Create date: 1-17-2014, updated 8/7/2020

-- Description:Copy MSRP (Version 3) Bid

-- ============================================

CREATE procedure [dbo].[sp_CopyMSRPVers3Bid] @pOldBidHeaderId  varchar(50), @pNewBidHea...

AS

BEGIN



set nocount on



declare @CopyFromBidHeaderId int, @CopyToBidHeaderId int



Select @CopyFromBidHeaderId=CAST(@pOldBidHeaderId as int)

Select @CopyToBidHeaderId=CAST(@pNewBidHeaderId as int)



IF @ExcludeManufWithBids = 1

BEGIN

  INSERT INTO BidRequestManufacturer

    (Active, BidHeaderId, ManufacturerId, SequenceNumber, AllowAdditionalProductLines, ...

  SELECT BidRequestManufacturer.Active, @CopyToBidHeaderId, BidRequestManufacturer.Manu...

  FROM BidRequestManufacturer

  left outer join BidRequestManufacturer brm on brm.BidHeaderId = @CopyToBidHeaderId --...
```

```
                                                and brm.ManufacturerId = BidRequestManufact...

    WHERE BidRequestManufacturer.BidHeaderId=@CopyFromBidHeaderId

  ... (truncated)
```

sp_CopyMSRPVers4Bid {sp-dbo-sp-copymsrpvers4bid}

> Copy procedure for MSRPVers4Bid

Property	Value
Schema	dbo
Created	2022-10-21 16:10:30.167000
Modified	2022-10-21 16:10:30.167000
Parameters	4

Parameters

#	Parameter	Type	Direction	Description
1	@pOldBidHeaderId	varchar(50)	INPUT	p Old Bid Header identifier
2	@pNewBidHeaderId	varchar(50)	INPUT	p New Bid Header identifier
3	@ExcludeManufWit	tinyint	INPUT	Exclude Manuf With Bids paramete
4	@IncludeWriteInMa	tinyint	INPUT	Include Write In Manuf parameter

Definition

```
-- ============================================

-- Author:Kevin / David

-- Create date: 1-17-2014, updated 10/21/2022

-- Description:Copy MSRP Bid (Version 4)

-- ============================================

CREATE procedure [dbo].[sp_CopyMSRPVers4Bid] @pOldBidHeaderId  varchar(50), @pNewBidHea...

AS

BEGIN



set nocount on



declare @CopyFromBidHeaderId int, @CopyToBidHeaderId int



Select @CopyFromBidHeaderId=CAST(@pOldBidHeaderId as int)

Select @CopyToBidHeaderId=CAST(@pNewBidHeaderId as int)



IF @ExcludeManufWithBids = 1

BEGIN

  INSERT INTO BidRequestManufacturer

    (Active, BidHeaderId, ManufacturerId, SequenceNumber, AllowAdditionalProductLines, ...

  SELECT BidRequestManufacturer.Active, @CopyToBidHeaderId, BidRequestManufacturer.Manu...

  FROM BidRequestManufacturer

  left outer join BidRequestManufacturer brm on brm.BidHeaderId = @CopyToBidHeaderId --...
```

```
                                                and brm.ManufacturerId = BidRequestManufact...

    WHERE BidRequestManufacturer.BidHeaderId=@CopyFromBidHeaderId

  ... (truncated)
```

sp_CopyReqBulk {sp-dbo-sp-copyreqbulk}

> Copy procedure for ReqBulk

Property	Value
Schema	dbo
Created	2008-10-30 22:42:08.763000
Modified	2025-06-26 11:44:19.290000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pRSLId	int	INPUT	p RSL identifier
2	@pRequisitionId	int	INPUT	p Requisition identifier

Definition

```
CREATE  procedure [dbo].[sp_CopyReqBulk] @pRSLId int, @pRequisitionId int as



declare @NewReqId int,

@BudgetId int,

@DistrictId int,

@SchoolId int,

@UserId int,

@UserAccountId int,

@BudgetAccountId int,

@AccountCode varchar(50),

@CategoryId int,

@Attention varchar(50),

@TodaysDate datetime,

@AccountCount int,

@DontDeleteNoBids int,

@NewUserId int,

@NewSchoolId int,

@ShippingId int,

        @NewAttention varchar(50)


set transaction isolation level read uncommitted

--begin transaction
```

```
-- Get Current Date

select @TodaysDate = getdate()

... (truncated)
```

sp_CopyReqs {sp-dbo-sp-copyreqs}

> Copy procedure for Reqs

Property	Value
Schema	dbo
Created	2013-10-16 12:57:21.310000
Modified	2013-10-16 12:57:21.310000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@SessionId	int	INPUT	Session identifier
2	@RSId	int	INPUT	RS identifier

Definition

```
create procedure dbo.sp_CopyReqs @SessionId int, @RSId int

as

  declare @ReqList varchar(255)

  insert DebugMsgs (Msg) values ('Copying Requisitions from RSId=' + CAST(@RSId as varc...

  select @ReqList = cast(@RSId as varchar(255))

  exec dbo.sp_CopyReqsBulk @ReqList
```

sp_CopyReqsBulk {sp-dbo-sp-copyreqsbulk}

> Copy procedure for ReqsBulk

Property	Value
Schema	dbo
Created	2008-11-01 19:02:23.847000
Modified	2018-05-02 08:47:23.363000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pReqList	varchar(255)	INPUT	p Req list/array

Definition

```
CREATE  procedure [dbo].[sp_CopyReqsBulk] @pReqList varchar(255) as



declare @ReqId int,

@ReqCount int,

@ReqList int,

@RSLId int,

@DontDeleteNoBids int



--set nocount on

set transaction isolation level read uncommitted

select @ReqList = convert(int,@pReqList)

select @ReqCount = count(*) from ReportSessionLinks where RSId = @ReqList

insert DebugMsgs (Msg) values ('ReqList=' + convert(varchar(16),@ReqList) + ',' + @pReq...

select @DontDeleteNoBids = 1



declare ReqListCur cursor read_only for

/*select IntId from ReportSessionLinks where RSId = @ReqList*/

select RSLId, IntId

  from ReportSessionLinks

  join Requisitions on Requisitions.RequisitionId = ReportSessionLinks.IntId

  outer apply (select Users.UserId from Users where Users.UserId = Requisitions.UserId ...

 where RSId = @ReqList

   and Users.UserId is not null
```

```
    order by RSLId


  ... (truncated)
```

sp_CopyToBudgetBook {sp-dbo-sp-copytobudgetbook}

> Copy procedure for ToBudgetBook

Property	Value
Schema	dbo
Created	2003-10-31 10:42:20.593000
Modified	2009-03-25 06:55:28.457000
Parameters	8

Parameters

#	Parameter	Type	Direction	Description
1	@pOrderBookId	int	INPUT	p Order Book identifier
2	@pCategoryId	int	INPUT	p Category identifier
3	@pPricePlanId	int	INPUT	p Price Plan identifier
4	@pDistrictId	int	INPUT	p District identifier
5	@pAwardId	int	INPUT	p Award identifier
6	@pCategoryDescrip	varchar(255)	INPUT	p Category description
7	@pPricePlanDescrip	varchar(255)	INPUT	p Price Plan description
8	@pMarkup	decimal(9,5)	INPUT	p Markup parameter

Definition

```
CREATE      procedure dbo.sp_CopyToBudgetBook @pOrderBookId int, @pCategoryId int, @pPr...



set nocount on

declare @OrderBookId int



INSERT INTO [EDS].[dbo].[OrderBooks]([PricePlanDescription], [Category], [CategoryId], ...

  values (@pPricePlanDescription, @pCategoryDescription, @pCategoryId, @pPricePlanId, @...



select @OrderBookId = SCOPE_identity()



INSERT INTO [EDS].[dbo].[OrderBookDetail]([OrderBookId], [Active], [ItemId], [BidItemId...

SELECT @OrderBookId, OrderBookDetail.[Active], OrderBookDetail.[ItemId], null, OrderBoo...

  FROM [EDS].[dbo].[OrderBookDetail]

  join Items on Items.ItemId = OrderBookdetail.ItemId

--  join uf_OrderBook (@pOrderBookId, 0, 0) ob on ob.ItemId = OrderBookDetail.ItemId

 where OrderBookDetail.OrderBookId = @pOrderBookId



set nocount off



select @OrderBookId OrderBookId

return
```

sp_CreateBidFromRequest

{sp-dbo-sp-createbidfromrequest}

> Create new CreateBidFromRequest

Property	Value
Schema	dbo
Created	2002-06-08 20:40:58.123000
Modified	2009-03-25 06:55:28.300000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pBidHeaderId	int	INPUT	p Bid Header identifier

Definition

```
CREATE  procedure sp_CreateBidFromRequest @pBidHeaderId int AS



declare @BidId int



select @BidId = max(BidId)

  from Bids with (nolock)

 where BidHeaderId = @pBidHeaderId



insert BidItems (BidId, ItemId)

  select @BidId, ItemId from BidRequestItems with (nolock)

   where BidHeaderId = @pBidHeaderId
```

sp_CreateBidHeaderDetail {sp-dbo-sp-createbidheaderdetail}

> Create new Create

Property	Value
Schema	dbo
Created	2003-05-08 09:09:37.360000
Modified	2022-12-08 10:20:19.013000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@pRSId	int	INPUT	p RS identifier
2	@pRSId2	int	INPUT	p RSId2 parameter
3	@pBidHeaderId	int	INPUT	p Bid Header identifier

Definition

```
CREATE       procedure [dbo].[sp_CreateBidHeaderDetail] @pRSId int, @pRSId2 int, @pBidH...



SET NOCOUNT ON

set transaction isolation level read uncommitted

declare @RecCount int,

@BidType int



-- Get Bid Type

select @BidType = isnull(BidType,2)

  from BidHeaders

 where BidHeaderId = @pBidHeaderId



-- Attach Requested Items to Bid Request

--insert BidRequestItems (BidHeaderId, ItemId, BidRequest, RequisitionCount, Active)

--  select @pBidHeaderId, Detail.ItemId, sum(Detail.Quantity), count(*), 1)

--Changed 2 lines below dch 1/16/2012 to Fixed Same Item with differenct extraInformation

insert BidRequestItems (BidHeaderId, ItemId, BidRequest, RequisitionCount, Active, [Che...

  select @pBidHeaderId, Detail.ItemId, sum(Detail.Quantity), count(*), 1, CHECKSUM(case...

    from ReportSessionLinks rsl with (nolock)

--    join Requisitions on Requisitions.RequisitionId = rsl.IntId

    join Detail on Detail.RequisitionId = rsl.IntId --Requisitions.RequisitionId

    join vw_DetailDescription dd on dd.DetailId = Detail.DetailId

    join vw_ItemDescription id on id.ItemId = Detail.ItemId
```

```
--    join Items on Items.ItemId = Detail.ItemId

    join ReportSessionLinks RS2 on RS2.IntId = Detail.ItemId

... (truncated)
```

sp_CreateBidHeaderItems {sp-dbo-sp-createbidheaderitems}

> Create new Creates

Property	Value
Schema	dbo
Created	2003-05-08 11:52:12.513000
Modified	2015-11-24 23:37:33.323000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pRSId	int	INPUT	p RS identifier
2	@pBidHeaderId	int	INPUT	p Bid Header identifier

Definition

```
CREATE procedure [dbo].[sp_CreateBidHeaderItems] @pRSId int, @pBidHeaderId int as



declare @RSId int,

@BidType int



set NOCOUNT ON

set transaction isolation level read uncommitted

select @BidType = isnull(BidType,2)

  from BidHeaders with (nolock)

 where BidHeaderId = @pBidHeaderId



-- Create Report Session

insert ReportSession (ReportStarted) values (getdate())



select @RSId = Scope_Identity() --DCH 11/24/2015 @@IDENTITY



if @BidType = 1

begin

  -- Attach Requested Items to Bid Request

  insert ReportSessionLinks (RSId, IntId)

    select @RSId, Detail.ItemId

      from Detail with (nolock)

      join Items on Items.ItemId = Detail.ItemId
```

```
        join Requisitions on Requisitions.RequisitionId = Detail.RequisitionId

        join ReportSessionLinks on ReportSessionLinks.IntId = Requisitions.RequisitionId

  ... (truncated)
```

sp_creatediagram {sp-dbo-sp-creatediagram}

> Create new creatediagram

Property	Value
Schema	dbo
Created	2009-03-26 16:18:10.600000
Modified	2009-03-26 16:18:10.600000
Parameters	4

Parameters

#	Parameter	Type	Direction	Description
1	@diagramname	sysname	INPUT	diagramname parameter
2	@owner_id	int	INPUT	owner id parameter
3	@version	int	INPUT	version parameter
4	@definition	varbinary(MAX)	INPUT	definition parameter

Definition

```
CREATE PROCEDURE dbo.sp_creatediagram

(

@diagramname sysname,

@owner_idint= null,

@version int,

@definition varbinary(max)

)

WITH EXECUTE AS 'dbo'

AS

BEGIN

set nocount on



declare @theId int

declare @retval int

declare @IsDboint

declare @userName sysname

if(@version is null or @diagramname is null)

begin

RAISERROR (N'E_INVALIDARG', 16, 1);

return -1

end



execute as caller;
```

```
select @theId = DATABASE_PRINCIPAL_ID();

select @IsDbo = IS_MEMBER(N'db_owner');

... (truncated)
```

sp_CreateNewBidHeader {sp-dbo-sp-createnewbidheader}

> Create new CreateNew

Property	Value
Schema	dbo
Created	2003-06-30 12:55:48.857000
Modified	2015-11-24 23:37:38.880000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pBidHeaderId	int	INPUT	p Bid Header identifier
2	@pDistrictList	varchar(4096)	INPUT	p District list/array

Definition

```
CREATE procedure [dbo].[sp_CreateNewBidHeader] @pBidHeaderId int, @pDistrictList varcha...



declare @AllowAddenda int,

@RSId int,

@ValidCombo int,

@ReqCount int,

@BidType int,

@DLRSId int,

@DynSql varchar(4096)



set NOCOUNT ON

set transaction isolation level read uncommitted



select @ValidCombo = isnull(count(*),0)

  from BidHeaders with (nolock)

  join PPCategory on PPCategory.PricePlanId = BidHeaders.PricePlanId

                 and PPCategory.CategoryId = BidHeaders.CategoryId

 where BidHeaders.BidHeaderId = @pBidHeaderId



if @@rowcount = 0 or @ValidCombo = 0

begin

  RAISERROR('Category is not a part of this Price Plan',16,1)

  return
```

```
end


... (truncated)
```

sp_CreateNewDistrictReqNumber {sp-dbo-sp-createnewdistrictreqnumber}

> Create new CreateNewDistrictReqNumber

Property	Value
Schema	dbo
Created	2003-12-11 16:25:56.280000
Modified	2012-09-06 12:37:20.903000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pRequisitionId	int	INPUT	p Requisition identifier
2	@DRNumber	varchar(255)	OUTPUT	DR number

Definition

```
CREATE   procedure [dbo].[sp_CreateNewDistrictReqNumber] @pRequisitionId int, @DRNumber...



declare @DRPrefix varchar(10),

@DRSuffix varchar(10),

@UseSchool int,

@SchoolId int,

@BudgetId int,

@DistrictId int



Begin Transaction



set transaction isolation level repeatable read



  select @SchoolId = Requisitions.SchoolId,

         @BudgetId = Requisitions.BudgetId,

         @DistrictId = Budgets.DistrictId

    from Requisitions

    join Budgets on Budgets.BudgetId = Requisitions.BudgetId

   where RequisitionId = @pRequisitionId


  select @UseSchool = DRsbySchool

    from District

   where DistrictId = @DistrictId
```

```
    if @@rowcount > 0

  ... (truncated)
```

sp_CreateNewPO {sp-dbo-sp-createnewpo}

> Create new CreateNew

Property	Value
Schema	dbo
Created	2002-03-14 08:16:16.937000
Modified	2025-06-26 11:53:09.733000
Parameters	5

Parameters

#	Parameter	Type	Direction	Description
1	@pDistrictId	int	INPUT	p District identifier
2	@pVendorId	int	INPUT	p Vendor identifier
3	@pAwardId	int	INPUT	p Award identifier
4	@pRequisitionId	int	INPUT	p Requisition identifier
5	@POId	int	OUTPUT	Purchase order identifier

Definition

```
CREATE procedure [dbo].[sp_CreateNewPO] @pDistrictId int, @pVendorId int, @pAwardId int...



declare @PONumber varchar(20),

@POPrefix varchar(10),

@POSuffix varchar(10),

@UseSchool int,

@SchoolId int,

@BudgetId int,

@PODate datetime



set transaction isolation level repeatable read



Begin Transaction



/******************** Deleted ***************************

Select @PONumber = case UsePOLeadingZeros when 1 then right('00000000000000000000' + co...

       @POPrefix = isnull(POPrefix,''),

       @POSuffix = isnull(POSuffix,'')

  from District

 where DdistrictId = @pDistrictId



Update District

   Set PONextNumber = PONextNumber + 1
```

```
    where DistrictId = @pDistrictId



  ... (truncated)
```

sp_CreateNewRequisition {sp-dbo-sp-createnewrequisition}

> Create new CreateNew

Property	Value
Schema	dbo
Created	2001-08-24 14:40:45.073000
Modified	2014-10-07 17:53:21.727000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pCatalogId	int	INPUT	p Catalog identifier
3	@ReqId	int	OUTPUT	Req identifier

Definition

```
CREATE PROCEDURE [dbo].[sp_CreateNewRequisition] @pSessionId int, @pCatalogId int, @Req...



declare@DistrictId int,

@SchoolId int,

@BudgetId int,

@UserId int,

@UseSchool tinyint,

@ReqNumber varchar(50),

@StartDate varchar(32),

@CurrentBudgetId int,

@NextBudgetId int,

@IncidentalCategories int,

@CategoryId int,

@CXmlSessionId int



if month(getdate()) >= 11

begin

  select @StartDate = '07/01/' + convert(char(4),year(getdate()) + 1)

end

else

begin

  select @StartDate = '07/01/' + convert(char(4),year(getdate()))

end
```

```
Update SessionTable

... (truncated)
```

sp_CreateNewRequisitionV {sp-dbo-sp-createnewrequisitionv}

> Create new CreateNewV

Property	Value
Schema	dbo
Created	2013-02-06 22:02:01.173000
Modified	2014-10-07 17:53:24.200000
Parameters	4

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pCategoryId	int	INPUT	p Category identifier
3	@pVendorId	int	INPUT	p Vendor identifier
4	@ReqId	int	OUTPUT	Req identifier

Definition

```
CREATE PROCEDURE [dbo].[sp_CreateNewRequisitionV] @pSessionId int, @pCategoryId int, @p...



declare@DistrictId int,

@SchoolId int,

@BudgetId int,

@UserId int,

@UseSchool tinyint,

@ReqNumber varchar(50),

@StartDate varchar(32),

@CurrentBudgetId int,

@NextBudgetId int,

@IncidentalCategories int,

@CategoryId int,

@CXmlSessionId int,

@BidHeaderId int



if month(getdate()) >= 11

begin

  select @StartDate = '07/01/' + convert(char(4),year(getdate()) + 1)

end

else

begin

  select @StartDate = '07/01/' + convert(char(4),year(getdate()))
```

```
end


... (truncated)
```

sp_CreateNewRequisitionVendor {sp-dbo-sp-createnewrequisitionvendor}

> Create new CreateNew

Property	Value
Schema	dbo
Created	2012-04-11 21:23:14.273000
Modified	2025-04-16 03:31:15.297000
Parameters	5

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pCategoryId	int	INPUT	p Category identifier
3	@pVendorId	int	INPUT	p Vendor identifier
4	@pBudgetId	int	INPUT	p Budget identifier
5	@ReqId	int	OUTPUT	Req identifier

Definition

```
CREATE PROCEDURE dbo.sp_CreateNewRequisitionVendor

    @pSessionId INT, @pCategoryId INT, @pVendorId INT, @pBudgetId INT, @ReqId INT OUTPUT

AS

BEGIN

    SET NOCOUNT ON;



    DECLARE @DistrictId INT,

            @SchoolId INT,

            @BudgetId INT,

            @UserId INT,

            @UseSchool TINYINT,

            @ReqNumber VARCHAR(50),

            @StartDate VARCHAR(32),

            @CurrentBudgetId INT,

            @NextBudgetId INT,

            @IncidentalCategories INT,

            @CategoryId INT,

            @CXmlSessionId INT;



    BEGIN TRY

        BEGIN TRANSACTION;



        UPDATE SessionTable WITH (ROWLOCK, UPDLOCK)
```

```
            SET VendorId = ISNULL(@pVendorId, 0)

          WHERE SessionId = @pSessionId;

... (truncated)
```

sp_CreateNewRequisitionVendor_bk20250416 {sp-dbo-sp-createnewrequisitionvendor-bk20250416}

> Create new CreateNew_bk20250416

Property	Value
Schema	dbo
Created	2025-04-15 22:37:30.350000
Modified	2025-04-15 22:37:30.350000
Parameters	5

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pCategoryId	int	INPUT	p Category identifier
3	@pVendorId	int	INPUT	p Vendor identifier
4	@pBudgetId	int	INPUT	p Budget identifier
5	@ReqId	int	OUTPUT	Req identifier

Definition

```
CREATE PROCEDURE dbo.sp_CreateNewRequisitionVendor_bk20250416 @pSessionId int, @pCatego...



declare@DistrictId int,

@SchoolId int,

@BudgetId int,

@UserId int,

@UseSchool tinyint,

@ReqNumber varchar(50),

@StartDate varchar(32),

@CurrentBudgetId int,

@NextBudgetId int,

@IncidentalCategories int,

@CategoryId int,

@CXmlSessionId int



Update SessionTable

   set VendorId = ISNULL(@pVendorId,0)

 where SessionId = @pSessionId



select @DistrictId = DistrictId,

@SchoolId = SchoolId,

@UserId = UserId,

@CategoryId = isnull(@pCategoryId,0),
```

```
        @BudgetId = coalesce(@pBudgetId,SessionTable.BudgetId,0),

@CurrentBudgetId = isnull(CurrentBudgetId,0),

... (truncated)
```

sp_CreateOrderBook {sp-dbo-sp-createorderbook}

> Create new CreateBook

Property	Value
Schema	dbo
Created	2004-08-04 11:19:28.240000
Modified	2021-06-01 16:01:37.540000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pBidHeaderId	int	INPUT	p Bid Header identifier
2	@pAwardId	int	INPUT	p Award identifier

Definition

```
--exec [sp_CreateOrderBookTest] 10885, 0

create   procedure [dbo].[sp_CreateOrderBook] @pBidHeaderId int, @pAwardId int as

declare @OrderBookId int,

@ControlYear int,

@OrderBookType char(1),

@CategoryType int



--set NOCOUNT ON



select top 1 @ControlYear = isnull(ControlYear,year(getdate()))

  from dbo.Control



select @CategoryType = isnull(Category.Type,1)

  from BidHeaders with (nolock)

  join Category on Category.CategoryId = BidHeaders.CategoryId

 where BidHeaders.BidHeaderId = @pBidHeaderId



if @CategoryType in (3)

begin

  select CAST(null as int) [@OrderBookId]

  return

end
```

```
Update BidItems

set ItemBidType = case BidResults.ItemBidType when 'S' then 'As Specified' when 'C' the...

... (truncated)
```

sp_CreateOrderBook03 {sp-dbo-sp-createorderbook03}

> Create new CreateBook03

Property	Value
Schema	dbo
Created	2003-08-24 14:30:09.390000
Modified	2015-11-24 23:37:38.077000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pBidHeaderId	int	INPUT	p Bid Header identifier
2	@pAwardId	int	INPUT	p Award identifier

Definition

```
CREATE procedure [dbo].[sp_CreateOrderBook03] @pBidHeaderId int, @pAwardId int as

declare @OrderBookId int



set NOCOUNT ON



exec dbo.sp_CreateOrderBook @pBidHeaderId, @pAwardId



set NOCOUNT OFF

return



Update BidItems

set ItemBidType = case BidResults.ItemBidType when 'S' then 'As Specified' when 'C' the...

  from BidResults

  join BidImports on BidImports.BidImportId = BidResults.BidImportId

  join Bids on Bids.BidHeaderId = BidImports.BidHeaderId

            and Bids.VendorId = BidImports.VendorId

  join BidItems on BidItems.BidId = Bids.BidId

                and BidItems.ItemId = BidResults.ItemId

 where BidItems.ItemBidType is null

   and Bids.BidHeaderId = @pBidHeaderId



Update BidItems

   set CrossRefId = CrossRefs.CrossRefId
```

```
    from BidItems

    join Bids on Bids.BidId = BidItems.BidId

  ... (truncated)
```

sp_CreateOrderBookTest {sp-dbo-sp-createorderbooktest}

> Create new CreateBookTest

Property	Value
Schema	dbo
Created	2021-06-01 13:11:48.993000
Modified	2021-06-01 13:11:48.993000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pBidHeaderId	int	INPUT	p Bid Header identifier
2	@pAwardId	int	INPUT	p Award identifier

Definition

```
create   procedure [dbo].[sp_CreateOrderBookTest] @pBidHeaderId int, @pAwardId int as

declare @OrderBookId int,

@ControlYear int,

@OrderBookType char(1),

@CategoryType int



--set NOCOUNT ON



select top 1 @ControlYear = isnull(ControlYear,year(getdate()))

  from dbo.Control



select @CategoryType = isnull(Category.Type,1)

  from BidHeaders with (nolock)

  join Category on Category.CategoryId = BidHeaders.CategoryId

 where BidHeaders.BidHeaderId = @pBidHeaderId



if @CategoryType in (3)

begin

  select CAST(null as int) [@OrderBookId]

  return

end



Update BidItems
```

```
set ItemBidType = case BidResults.ItemBidType when 'S' then 'As Specified' when 'C' the...

  from BidResults

... (truncated)
```

sp_CreatePO {sp-dbo-sp-createpo}

> Create new Create

Property	Value
Schema	dbo
Created	2002-03-14 08:17:09.590000
Modified	2025-06-26 11:52:27.627000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pRequisitionId	int	INPUT	p Requisition identifier

Definition

```
CREATE   procedure [dbo].[sp_CreatePO] @pSessionId int, @pRequisitionId int AS



declare @POId int,

@VendorId int,

@DistrictId int,

@AwardId int,

@BidHeaderId int,

@TotalItems int,

@tempItemCount int,

@MaxPODetailItems int,

@MaxDetailId int,

@TotalBidCost money,

@TotalGrossCost money,

@TotalItemsCost money,

@tempTotalGrossCost money,

@TotalCalcAmount money,

@TotalDiscountAmount money,

@DiscountRate decimal(9,5),

@StatusId int,

@StatusCode char(1),
```

```
@ErrorMsg varchar(2048),

@ReqNbr varchar(50),

@DistrictApprovalLevel int,
```

```
@POCount int,

@WrongCategoryItems int,

... (truncated)
```

sp_CreatePO_Saved062724 {sp-dbo-sp-createpo-saved062724}

> Create new Create_Saved062724

Property	Value
Schema	dbo
Created	2024-06-27 18:44:50.310000
Modified	2024-06-27 18:44:50.310000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pRequisitionId	int	INPUT	p Requisition identifier

Definition

```
create procedure [dbo].[sp_CreatePO_Saved062724] @pSessionId int, @pRequisitionId int AS



declare @POId int,

@VendorId int,

@DistrictId int,

@AwardId int,

@BidHeaderId int,

@TotalItems int,

@tempItemCount int,

@MaxPODetailItems int,

@MaxDetailId int,

@TotalBidCost money,

@TotalGrossCost money,

@TotalItemsCost money,

@tempTotalGrossCost money,

@TotalCalcAmount money,

@TotalDiscountAmount money,

@DiscountRate decimal(9,5),

@StatusId int,

@StatusCode char(1),

@ErrorMsg varchar(2048),

@ReqNbr varchar(50),

@DistrictApprovalLevel int,
```

```
@POCount int,

@WrongCategoryItems int,

... (truncated)
```

sp_CreatePOTest {sp-dbo-sp-createpotest}

> Create new CreateTest

Property	Value
Schema	dbo
Created	2024-06-27 18:20:41.237000
Modified	2024-06-27 18:20:41.237000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pRequisitionId	int	INPUT	p Requisition identifier

Definition

```
create   procedure [dbo].[sp_CreatePOTest] @pSessionId int, @pRequisitionId int AS



declare @POId int,

@VendorId int,

@DistrictId int,

@AwardId int,

@BidHeaderId int,

@TotalItems int,

@tempItemCount int,

@MaxPODetailItems int,

@MaxDetailId int,

@TotalBidCost money,

@TotalGrossCost money,

@TotalItemsCost money,

@tempTotalGrossCost money,

@TotalCalcAmount money,

@TotalDiscountAmount money,

@DiscountRate decimal(9,5),

@StatusId int,

@StatusCode char(1),

@ErrorMsg varchar(2048),

@ReqNbr varchar(50),

@DistrictApprovalLevel int,
```

```
@POCount int,

@WrongCategoryItems int,

... (truncated)
```

sp_CreateQuoteRequest {sp-dbo-sp-createquoterequest}

> Create new CreateQuoteRequest

Property	Value
Schema	dbo
Created	2004-05-07 17:37:37.090000
Modified	2022-12-08 10:21:10.700000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pBidHeaderId	int	INPUT	p Bid Header identifier

Definition

```
CREATE procedure [dbo].[sp_CreateQuoteRequest] @pBidHeaderId int as



declare @NewBidHeaderId int, @NewBidHeaderKey int



INSERT INTO dbo.BidHeaders([Active], [CategoryId], [PricePlanId], [DistrictId], [BidDat...

SELECT [Active], [CategoryId], [PricePlanId], [DistrictId], [BidDate], [BidAwardDate], ...

  FROM [dbo].[BidHeaders] with (nolock)

 where BidHeaderId = @pBidHeaderId



select @NewBidHeaderKey = Scope_Identity() --DCH 11/24/2015 @@identity

select @NewBidHeaderId = BidHeaderId

  from BidHeaders

 where BidHeaderKey = @NewBidHeaderKey



if @@rowcount > 0

begin

  insert BidRequestItems (BidHeaderId, ItemId, BidRequest, Active, RequisitionCount, Bi...

    select @NewBidHeaderId, Detail.ItemId, sum(Detail.Quantity), 1, count(Detail.ItemId...

      from BidHeaderDetail with (nolock)

      join BidRequestItems on BidRequestItems.BidRequestItemId = BidHeaderDetail.BidReq...

                           and BidRequestItems.Active = 1    -- added 10/26/2010 kjm

      join Detail on Detail.DetailId = BidHeaderDetail.DetailId

      join Requisitions on Requisitions.RequisitionId = Detail.RequisitionId
```

```
        join Budgets on Budgets.BudgetId = Requisitions.BudgetId

        left outer join PO on PO.RequisitionId = Requisitions.RequisitionId

  ... (truncated)
```

sp_CreateQuoteRequestPrebid {sp-dbo-sp-createquoterequestprebid}

> Create new CreateQuoteRequestPrebid

Property	Value
Schema	dbo
Created	2010-10-26 16:14:34.787000
Modified	2022-12-08 10:21:58.463000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pBidHeaderId	int	INPUT	p Bid Header identifier

Definition

```
CREATE   procedure [dbo].[sp_CreateQuoteRequestPrebid] @pBidHeaderId int as



declare @NewBidHeaderId int,

@NewBidHeaderKey int



INSERT INTO dbo.BidHeaders([Active], [CategoryId], [PricePlanId], [DistrictId], [BidDat...

SELECT [Active], [CategoryId], [PricePlanId], [DistrictId], [BidDate], [BidAwardDate], ...

  FROM [dbo].[BidHeaders] with (nolock)

 where BidHeaderId = @pBidHeaderId

select @NewBidHeaderKey = Scope_Identity() --DCH 11/24/2015 @@identity



select @NewBidHeaderId = BidHeaderId

  from BidHeaders

 where BidHeaderKey = @NewBidHeaderKey



if @@rowcount > 0

begin



  insert BidRequestItems (BidHeaderId, ItemId, BidRequest, Active, RequisitionCount, Bi...

    select @NewBidHeaderId, OldBRI.ItemId, OldBRI.BidRequest, 1, OldBRI.RequisitionCoun...

      from BidRequestItems OldBRI  with (nolock)

     where OldBRI.BidHeaderId = @pBidHeaderId and OldBRI.Active = 1

       and (select top 1 BidResults.BidResultsId from BidResults join BidImports on Bid...
```

```
    insert BidHeaderDetail (BidHeaderId, DetailId, BidRequestItemId, Quantity, BidHeaderK...

  ... (truncated)
```

sp_CreateTextBookBidRequest {sp-dbo-sp-createtextbookbidrequest}

> Create new CreateTextBook

Property	Value
Schema	dbo
Created	2002-06-08 15:19:01.577000
Modified	2015-11-24 23:37:32.297000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pRSId	int	INPUT	p RS identifier

Definition

```
CREATE procedure [dbo].[sp_CreateTextBookBidRequest] @pRSId int AS



declare @BidHeaderId int



insert BidHeaders (Active, CategoryId, PricePlanId, DistrictId, BidMessage)

  select 1, Requisitions.CategoryId, Detail.PricePlanId,

         District.DistrictId, 'Textbook Bid Request for ' + rtrim(District.Name)

    from ReportSessionLinks

    join Requisitions on Requisitions.RequisitionId = ReportSessionLinks.IntId

    join Detail on Detail.RequisitionId = Requisitions.RequisitionId

    join School on School.SchoolId = Requisitions.SchoolId

    join District on District.DistrictId = School.DistrictId

    join Category on Category.CategoryId = Requisitions.CategoryId

   where ReportSessionLinks.RSId = @pRSId and Category.Type = 2

   group by Requisitions.CategoryId, Detail.PricePlanId, District.DistrictId, District....



select @BidHeaderId = Scope_Identity() --DCH 11/24/2015 @@IDENTITY



insert BidRequestItems (BidHeaderId, ItemId, BidRequest)

  select @BidHeaderId, Detail.ItemId, sum(Detail.Quantity)

    from ReportSessionLinks

    join Requisitions on Requisitions.RequisitionId = ReportSessionLinks.IntId

    join Detail on Detail.RequisitionId = Requisitions.RequisitionId
```

```
    join School on School.SchoolId = Requisitions.SchoolId

    join District on District.DistrictId = School.DistrictId

... (truncated)
```

sp_CreateVendorSession {sp-dbo-sp-createvendorsession}

> Create new Create

Property	Value
Schema	dbo
Created	2009-03-11 17:12:27.067000
Modified	2009-03-25 06:55:28.397000
Parameters	4

Parameters

#	Parameter	Type	Direction	Description
1	@pUser	varchar(255)	INPUT	p User parameter
2	@pUserName	varchar(255)	INPUT	p User name
3	@pIPAddress	varchar(255)	INPUT	p IPAddress parameter
4	@pjSession	varchar(128)	INPUT	pj Session parameter

Definition

```
CREATE  procedure [dbo].[sp_CreateVendorSession] @pUser varchar(255), @pUserName varcha...

as

declare @SessionId int

set nocount on

insert vendorsessions (vendorid, UserName, starttime, ipaddress, jsession)

  select top 1 VendorId, @pUserName, getdate(), @pIPAddress, @pjSession

    from vendors

   where code = @pUser

     and active = 1



if @@rowcount = 0

begin

  insert DebugMsgs (Msg) values ('Unable to Locate User')

  raiserror('Unable to Locate User',16,1)

  return 0

end



select @SessionId = scope_identity()

if isnull(@SessionId,0) = 0

begin

  insert DebugMsgs (Msg) values ('Unable to Locate Session')

  raiserror('Unable to Locate Session',16,1)

  return 0
```

```
end

set nocount off

... (truncated)
```

sp_CXmlLogin {sp-dbo-sp-cxmllogin}

> Login/authentication procedure for CXml

Property	Value
Schema	dbo
Created	2008-01-23 12:43:15.687000
Modified	2024-10-18 06:40:48.047000
Parameters	23

Parameters

#	Parameter	Type	Direction	Description
1	@pDistrict	varchar(50)	INPUT	p District parameter
2	@pUserNumber	varchar(50)	INPUT	p User number
3	@pUserName	varchar(50)	INPUT	p User name
4	@pPassword	varchar(50)	INPUT	p Password parameter
5	@pBuyerReqCode	varchar(50)	INPUT	p Buyer Req code
6	@pBuyerUserName	varchar(50)	INPUT	p Buyer User name
7	@pBuyerUserNumb	varchar(50)	INPUT	p Buyer User number
8	@pBuyerPassword	varchar(50)	INPUT	p Buyer Password parameter
9	@pBuyerAccountCo	varchar(50)	INPUT	p Buyer Account code
10	@pBuyerBudgetYea	varchar(50)	INPUT	p Buyer Budget Year parameter
11	@pOrigReqId	varchar(50)	INPUT	p Orig Req identifier
12	@pPayloadId	varchar(255)	INPUT	p Payload identifier
13	@pFromDomain	varchar(255)	INPUT	p From Domain parameter
14	@pFromIdentity	varchar(255)	INPUT	p From Identity parameter

15	@pToDomain	varchar(255)	INPUT	p To Domain parameter
16	@pToIdentity	varchar(255)	INPUT	p To Identity parameter
17	@pSenderDomain	varchar(255)	INPUT	p Sender Domain parameter
18	@pSenderIdentity	varchar(255)	INPUT	p Sender Identity parameter
19	@pBuyerCookie	varchar(255)	INPUT	p Buyer Cookie parameter
20	@pBrowserFormPos	varchar(255)	INPUT	p Browser Form Post parameter
21	@pFromUserAgent	varchar(255)	INPUT	p From User Agent parameter
22	@pCategoryId	varchar(50)	INPUT	p Category identifier
23	@pMode	int	INPUT	p Mode parameter

Definition

```
--exec sp_CXmlLogin '!~','91825','91825','91825','JBARTH','John A. Barth','','','A','20...



CREATE           procedure [dbo].[sp_CXmlLogin]

@pDistrict varchar(50),

@pUserNumber varchar(50),

@pUserName varchar(50),

@pPassword varchar(50),

@pBuyerReqCode varchar(50),

@pBuyerUserName varchar(50),

@pBuyerUserNumber varchar(50),

@pBuyerPassword varchar(50),

@pBuyerAccountCode varchar(50),

@pBuyerBudgetYear varchar(50),

@pOrigReqId varchar(50),

@pPayloadId varchar(255),

@pFromDomain varchar(255),

@pFromIdentity varchar(255),

@pToDomain varchar(255),

@pToIdentity varchar(255),

@pSenderDomain varchar(255),

@pSenderIdentity varchar(255),

@pBuyerCookie varchar(255),

@pBrowserFormPost varchar(255),
```

```
@pFromUserAgent varchar(255),

@pCategoryId varchar(50),

... (truncated)
```

sp_DBCheck {sp-dbo-sp-dbcheck}

> Check/verify procedure for DB

Property	Value
Schema	dbo
Created	2002-02-13 01:12:41.873000
Modified	2009-03-25 06:55:28.770000
Parameters	0

Definition

```
CREATE   procedure sp_DBCheck AS




print 'Checking for Catalogs Not Matching Awarded Vendor'



select *

  from Awards

  join AwardsCatalogList on AwardsCatalogList.AwardId = Awards.AwardId

  join Catalog on Catalog.CatalogId = AwardsCatalogList.CatalogId

  join Category on Category.CategoryId = Awards.CategoryId

               and Category.Type != 2

 where Awards.BidStartDate <= getdate()

   and Awards.BidEndDate >= getdate()

   and Awards.VendorId != Catalog.VendorId
```

sp_DefragAll {sp-dbo-sp-defragall}

> Stored procedure: DefragAll

Property	Value
Schema	dbo
Created	2001-11-28 11:09:20.327000
Modified	2001-11-28 11:09:20.327000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pDBName	varchar(255)	INPUT	p DB name

Definition

```
CREATE   procedure sp_DefragAll @pDBName varchar(255) as



declare @TableName varchar(255),

@IndexName varchar(255),

@Id int,

@DynStr varchar(255)



print 'Beginning to Defrag Database ' + @pDBName



create table #TempTables (

sysidint identity(1,1) not null,

[Name]varchar(255) not null,

[Id]int not null

)



select @DynStr = 'insert #TempTables ([Name], [Id]) select name, id from ' + @pDBName +...

exec(@DynStr)



declare TableCursor CURSOR FORWARD_ONLY READ_ONLY FOR

select [Name], [Id] from #TempTables
```

```
open TableCursor
```

```
fetch next from TableCursor into @TableName, @Id



... (truncated)
```

sp_DeleteBatch {sp-dbo-sp-deletebatch}

> Delete record from Delete

Property	Value
Schema	dbo
Created	2002-02-27 11:15:00.217000
Modified	2009-03-25 06:55:28.350000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pBatchId	int	INPUT	p Batch identifier

Definition

```
create procedure sp_DeleteBatch @pSessionId int, @pBatchId int as



begin transaction



delete BatchDetail

 where BatchId = @pBatchId



delete BatchBook

 where BatchId = @pBatchId



delete Batches

 where BatchId = @pBatchId



commit transaction
```

sp_DeleteBook {sp-dbo-sp-deletebook}

> Delete record from DeleteBook

Property	Value
Schema	dbo
Created	2002-02-27 11:19:20.060000
Modified	2009-03-25 06:55:28.350000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pBatchId	int	INPUT	p Batch identifier
3	@pBookId	int	INPUT	p Book identifier

Definition

```
CREATE  procedure sp_DeleteBook @pSessionId int, @pBatchId int, @pBookId int as



begin transaction



Delete BatchDetail

 where BatchId = @pBatchId and BatchBookId = @pBookId



Delete BatchBook

 where BatchBookId = @pBookId



commit transaction
```

sp_DeleteDistrictPOs {sp-dbo-sp-deletedistrictpos}

> Delete record from DeleteDistricts

Property	Value
Schema	dbo
Created	2002-04-16 16:01:15.840000
Modified	2009-03-25 06:55:28.550000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@pDistrictId	int	INPUT	p District identifier
2	@pBudgetId	int	INPUT	p Budget identifier
3	@pCategoryId	int	INPUT	p Category identifier

Definition

```
CREATE    procedure sp_DeleteDistrictPOs @pDistrictId int, @pBudgetId int, @pCategoryId...



declare @POIdint



declare POCur cursor fast_forward read_only for

select POId

  from PO

  join Requisitions on Requisitions.RequisitionId = PO.RequisitionId

                    and Requisitions.CategoryId = isnull(@pCategoryId,Requisitions.Categ...

  join Budgets on Budgets.BudgetId = Requisitions.BudgetId

               and Budgets.BudgetId = @pBudgetId

               and Budgets.DistrictId = @pDistrictId

 group by POId



open POCur



fetch next from POCur into @POId



while @@fetch_status = 0

begin

  exec sp_DeletePO @POId



  fetch next from POCur into @POId
```

```
end


... (truncated)
```

sp_DeleteNoBids {sp-dbo-sp-deletenobids}

> Delete record from DeleteNoBids

Property	Value
Schema	dbo
Created	2002-02-24 21:15:37.123000
Modified	2009-03-25 06:55:28.270000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	varchar(255)	INPUT	p Session identifier
2	@pRequisitionId	varchar(255)	INPUT	p Requisition identifier

Definition

```
create  procedure sp_DeleteNoBids @pSessionId varchar(255),@pRequisitionId varchar(255) AS



delete detail

  from Detail

  join Vendors on Vendors.VendorId = detail.VendorId

 where RequisitionId = convert(int,@pRequisitionId)

   and Vendors.Code = '0000'
```

sp_DeletePO {sp-dbo-sp-deletepo}

> Delete record from Delete

Property	Value
Schema	dbo
Created	2002-04-16 15:56:44.890000
Modified	2014-05-20 13:29:00.750000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pPOId	int	INPUT	p PO identifier

Definition

```
CREATE    procedure [dbo].[sp_DeletePO] @pPOId int AS



delete Approvals

  from Approvals

  join Requisitions on Requisitions.RequisitionId = Approvals.RequisitionId

  join Detail on Detail.RequisitionId = Requisitions.RequisitionId

  join podetailItems on PODetailItems.DetailId = Detail.DetailId

  join PO on PO.POId = PODetailItems.POId

  join School on School.SchoolId = Requisitions.SchoolId

  join StatusTable on StatusTable.StatusId = Approvals.StatusId

 where PO.POId = @pPOId

   and StatusTable.StatusCode = 'O'



Delete PODetailItems

  from podetailItems

  join PO on PO.POId = PODetailItems.POId

  join Requisitions on Requisitions.RequisitionId = PO.RequisitionId

  join School on School.SchoolId = Requisitions.SchoolId

 where PO.POId = @pPOId


/*

Update Detail

   set POId = null
```

```
 where POId = @pPOId

*/

... (truncated)
```

sp_DeleteRequisition {sp-dbo-sp-deleterequisition}

> Delete record from Delete

Property	Value
Schema	dbo
Created	2001-12-13 12:59:39.103000
Modified	2012-08-31 09:33:51.697000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pRequisitionId	int	INPUT	p Requisition identifier
3	@rStatus	int	OUTPUT	r status

Definition

```
CREATE      procedure [dbo].[sp_DeleteRequisition] @pSessionId int, @pRequisitionId int...



declare @ReqNumber varchar(255),

@POCount int,

@DetailCount int,

@ApprovalCount int,

@CSRepId int



select Requisitions.RequisitionId

  from Requisitions

 where Requisitions.RequisitionId = @pRequisitionId



if @@rowcount = 0

begin

  RETURN

end



select @ApprovalCount = COUNT(*)

  from Approvals

 where Approvals.RequisitionId = @pRequisitionId



if @ApprovalCount != 0

begin
```

```
    RETURN

  end

  ... (truncated)
```

sp_DeleteRequisitionRestricted {sp-dbo-sp-deleterequisitionrestricted}

> Delete record from DeleteRestricted

Property	Value
Schema	dbo
Created	2002-05-28 13:09:15.107000
Modified	2017-05-11 15:15:45.783000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pReportSessionId	int	INPUT	p Report Session identifier
3	@rStatus	int	OUTPUT	r status

Definition

```
CREATE    procedure [dbo].[sp_DeleteRequisitionRestricted] @pSessionId int, @pReportSes...



declare @ReqNumber varchar(255),

@MaxLevel int,

@RequisitionId int



declare ReqCur cursor fast_forward read_only for

select IntId from ReportSessionLinks where RSId = @pReportSessionId



open ReqCur



fetch next from ReqCur into @RequisitionId



while @@fetch_status = 0

begin

  select Requisitions.RequisitionId

    from Requisitions

    left outer join PO on PO.RequisitionId = Requisitions.RequisitionId

   where Requisitions.RequisitionId = @RequisitionId

     and PO.POId is null



  if @@rowcount != 0

  begin
```

```
      select @MaxLevel = max(Level)

        from Approvals

  ... (truncated)
```

sp_DeleteRequisitionWithDetail {sp-dbo-sp-deleterequisitionwithdetail}

> Delete record from DeleteWith

Property	Value
Schema	dbo
Created	2003-03-26 20:53:25.750000
Modified	2009-03-25 06:55:28.287000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pRequisitionId	int	INPUT	p Requisition identifier
3	@rStatus	int	OUTPUT	r status

Definition

```
create procedure dbo.sp_DeleteRequisitionWithDetail @pSessionId int, @pRequisitionId in...



declare @ReqNumber varchar(255),

@POCount int,

@DetailCount int



select Requisitions.RequisitionId

  from Requisitions

 where Requisitions.RequisitionId = @pRequisitionId



if @@rowcount = 0

begin

  RETURN

end



select @POCount = count(*)

  from Requisitions

  join PO on PO.RequisitionId = Requisitions.RequisitionId

 where Requisitions.RequisitionId = @pRequisitionId
```

```
if @POCount != 0

begin

  RETURN
```

```
end


... (truncated)
```

sp_DeleteZeros {sp-dbo-sp-deletezeros}

> Delete record from DeleteZeros

Property	Value
Schema	dbo
Created	2001-08-24 14:40:45.083000
Modified	2009-03-25 06:55:28.600000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	varchar(255)	INPUT	p Session identifier
2	@pRequisitionId	varchar(255)	INPUT	p Requisition identifier

Definition

```
CREATE   procedure sp_DeleteZeros @pSessionId varchar(255),@pRequisitionId varchar(255) AS



delete detail

 where RequisitionId = convert(int,@pRequisitionId)

   and Quantity = 0
```

sp_DistrictRequisitionDetail {sp-dbo-sp-districtrequisitiondetail}

> Requisition procedure for District

Property	Value
Schema	dbo
Created	2003-12-11 16:55:27.730000
Modified	2025-03-03 18:46:38.420000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pRSId	int	INPUT	p RS identifier

Definition

```
CREATE          procedure [dbo].[sp_DistrictRequisitionDetail] (@pRSId int)

as

declare @DistrictRequisitionNumber varchar(50),

        @VendorId int,

@RequisitionId int



set nocount on



declare VenCur cursor fast_forward read_only for

select Detail.RequisitionId, Detail.VendorId

  from Detail

  join Requisitions on Requisitions.RequisitionId = Detail.RequisitionId

  join Users on Users.UserId = Requisitions.UserId

  join ReportSessionLinks on ReportSessionLinks.IntId = Detail.RequisitionId

 where ReportSessionLinks.RSId = @pRSId

   and Detail.DistrictRequisitionNumber is null

   and case isnull(Detail.VendorId,0) when 0 then 7691 else Detail.VendorId end != 7691

 group by Detail.RequisitionId, Detail.VendorId, Users.CometId

 order by Users.CometId, Detail.RequisitionId, Detail.VendorId


open VenCur



fetch next from VenCur into @RequisitionId, @VendorId
```

```
while @@fetch_status = 0

... (truncated)
```

sp_dropdiagram {sp-dbo-sp-dropdiagram}

> Stored procedure: dropdiagram

Property	Value
Schema	dbo
Created	2009-03-26 16:18:10.600000
Modified	2009-03-26 16:18:10.600000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@diagramname	sysname	INPUT	diagramname parameter
2	@owner_id	int	INPUT	owner id parameter

Definition

```
CREATE PROCEDURE dbo.sp_dropdiagram

(

@diagramname sysname,

@owner_idint= null

)

WITH EXECUTE AS 'dbo'

AS

BEGIN

set nocount on

declare @theId int

declare @IsDbo int



declare @UIDFound int

declare @DiagIdint



if(@diagramname is null)

begin

RAISERROR ('Invalid value', 16, 1);

return -1

end
```

```
EXECUTE AS CALLER;

select @theId = DATABASE_PRINCIPAL_ID();
```

```
select @IsDbo = IS_MEMBER(N'db_owner');

if(@owner_id is null)

... (truncated)
```

sp_DSHeadings {sp-dbo-sp-dsheadings}

> Stored procedure: DSHeadings

Property	Value
Schema	dbo
Created	2017-10-23 16:29:03.927000
Modified	2022-12-20 11:46:23.393000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@RequisitionId	int	INPUT	Requisition identifier

Definition

```
--exec sp_DSHeadings 51652881



CREATE procedure [dbo].[sp_DSHeadings] @RequisitionId int as

set nocount on

declare @DistrictId int, @CategoryId int, @AllowAddenda int

declare @Headings table (HeadingId bigint, HeadingTitle varchar(255))



select @DistrictId = isnull(Budgets.DistrictId,0),

   @CategoryId = isnull(Requisitions.CategoryId,0),

   @AllowAddenda = isnull(AllowAddenda.AllowAddenda,0)

  from Requisitions with (nolock)

  join Budgets on Budgets.BudgetId = Requisitions.BudgetId

  outer apply (select DistrictCategories.AllowAddenda

                 from DistrictCategories

where DistrictCategories.DistrictId = Budgets.DistrictId

                  and DistrictCategories.CategoryId = Requisitions.CategoryId) AllowAdd...

 where RequisitionId = @RequisitionId



if @AllowAddenda = 1

begin

insert @Headings (HeadingId, HeadingTitle)

select min(cast(Headings.HeadingId as bigint)) HeadingId, Headings.Title

  from PricingAddenda
```

```
    join Headings on Headings.HeadingId = PricingAddenda.HeadingId

                 and Headings.Active = 1

  ... (truncated)
```

sp_easyadd {sp-dbo-sp-easyadd}

> Stored procedure: easyadd

Property	Value
Schema	dbo
Created	2001-08-24 14:40:45.713000
Modified	2013-05-22 14:41:19.023000
Parameters	5

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pRequisitionId	int	INPUT	p Requisition identifier
3	@pItemCode	varchar(25)	INPUT	p Item code
4	@pCatalogId	varchar(255)	INPUT	p Catalog identifier
5	@pQuantity	int	INPUT	p quantity

Definition

```
CREATE            PROCEDURE [dbo].[sp_easyadd] @pSessionId int, @pRequisitionId int, @p...



declare @ReturnValue int,

@ItemId int,

@DistrictId int,

@DetailId int,

@CategoryId int,

@CatalogId int,

        @BudgetAccountId int,

@BidHeaderId int,

@TotalCost money,

@TodaysDate datetime,

@paddedItemCode varchar(16),

@ItemCount int,

@VendorId int,

@DistrictVendorCode varchar(50),

@BrowserFormPost varchar(255),

@ReturnMsg varchar(1024),

@CatalogName varchar(50),

@VendorName varchar(50),
```

```
@UseEDSVendorCodes tinyint



--BEGIN TRANSACTION
```

```
set transaction isolation level read uncommitted



... (truncated)
```

sp_EDSItems {sp-dbo-sp-edsitems}

> Item management procedure for EDSs

Property	Value
Schema	dbo
Created	2001-10-18 09:07:39.403000
Modified	2009-03-25 06:55:28.490000
Parameters	5

Parameters

#	Parameter	Type	Direction	Description
1	@pItemCode	varchar(255)	INPUT	p Item code
2	@CategoryId	int	INPUT	Category identifier
3	@DistrictId	int	INPUT	District identifier
4	@ReturnValue	int	OUTPUT	Output return value
5	@ItemId	int	OUTPUT	Item identifier

Definition

```
CREATE          procedure sp_EDSItems @pItemCode varchar(255), @CategoryId int, @Distri...

declare @TodaysDate datetime



      select @TodaysDate = getdate()



      select @ItemId = ItemId

        from EDSIQWebUser.uf_LookupItemCode(@pItemCode, @CategoryId, 0, @TodaysDate, 0,...



      if @@rowcount = 0

      begin

      --  RAISERROR('Bad Item Code Specified',16,1)

        select @ReturnValue = 4

      end
```

sp_EnhancedSearchItem {sp-dbo-sp-enhancedsearchitem}

> Item management procedure for Enhanced

Property	Value
Schema	dbo
Created	2020-06-08 14:39:41.710000
Modified	2024-07-12 09:40:43.500000
Parameters	7

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pCategoryId	int	INPUT	p Category identifier
3	@pCatalogId	int	INPUT	p Catalog identifier
4	@pSearchBy	int	INPUT	p Search By parameter
5	@pSearchStart	varchar(255)	INPUT	p Search Start parameter
6	@pSearchEnd	varchar(255)	INPUT	p Search End parameter
7	@pSearchPrev	tinyint	INPUT	p Search Prev parameter

Definition

```
-- sp_EnhancedSearchItem 1785380869, 91, 999999, 4, 'BN-PDSWNG-GRYBLU-BT', '', 0

--exec sp_SearchItems 1785380869, 91, 'BN-PDSWNG-GRYBLU-BT', 999999, 4



CREATE   procedure [dbo].[sp_EnhancedSearchItem] @pSessionId int, @pCategoryId int, @pC...



declare @SessionId int,

@DistrictId int,

@CategoryId int,

@CatalogId int,

@SearchBy int,

@SearchSessionId int,

@DynSql varchar(max),

@Select varchar(max),

@From varchar(max),

        @Join varchar(max),

@Where1 varchar(max),

@Where varchar(max),

@Declare varchar(max),

@VariLoad varchar(max),

@Order varchar(max),
```

```
@Group varchar(max),

@SSId varchar(16),

@SearchStart varchar(64),
```

```
@SearchEnd varchar(64),

@CrossRefNeeded tinyint,

... (truncated)
```

sp_ExportMSRPBid {sp-dbo-sp-exportmsrpbid}

> Purchase order procedure for MSRPBid

Property	Value
Schema	dbo
Created	2014-07-16 14:14:15.220000
Modified	2014-07-16 14:55:37.890000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@BidHeaderId	int	INPUT	Bid Header identifier

Definition

```
CREATE procedure [dbo].[sp_ExportMSRPBid] @BidHeaderId int

as

create table #ExportSet (ManufacturerName varchar(50), ProductLine varchar(50), OptionN...



insert #ExportSet(ManufacturerName, ProductLine, OptionName, RangeBase1, RangeWeight1, ...

select 'MANUFACTURER' ManufacturerName,'PRODUCT LINE/GROUP' ProductLine, 'DELIVERY OPT...

/*

insert #ExportSet(ManufacturerName, ProductLine, OptionName, RangeBase1, RangeWeight1, ...

select '(WRITEINS)' ManufacturerName, 'ALL' ProductLine, 'ALL' OptionName,

       '' RangeBase1,

       '' RangeWeight1,

       '' RangeBase2,

       '' RangeWeight2,

       '' RangeBase3,

       '' RangeWeight3,

       '' RangeBase4,

       '' RangeWeight4,

       '' RangeBase5,

       '' RangeWeight5,

       '' RangeBase6,

       '' RangeWeight6

  from BidHeaders

  join Category on Category.CategoryId = BidHeaders.CategoryId
```

```
 where BidHeaders.BidHeaderId = @BidHeaderId

   and BidHeaders.AllowAdditionalManufacturers = 1

... (truncated)
```

sp_FA_AddUpdateAccountCode {sp-dbo-sp-fa-addupdateaccountcode}

> Stored procedure: FA AddUpdateAccountCode

Property	Value
Schema	dbo
Created	2012-06-14 00:06:04.013000
Modified	2023-02-21 16:01:42.727000
Parameters	4

Parameters

#	Parameter	Type	Direction	Description
1	@sessionID	varchar(40)	INPUT	session identifier
2	@accountID	int	INPUT	account identifier
3	@schoolID	int	INPUT	school identifier
4	@code	varchar(50)	INPUT	code parameter

Definition

```
CREATE PROCEDURE [dbo].[sp_FA_AddUpdateAccountCode] @sessionID varchar(40), @accountID ...



AS



DECLARE @error int, @errorMessage varchar(255), @districtID int, @selectAccountID int,...

SET @error = 0;

SET@errorMessage = '';

SET @selectAccountID = 0;

DECLARE @previousSchoolID int = 0;



SELECT @budgetID = BudgetID, @districtID = DistrictId FROM SessionTable where SessionI...



-- VALIDATION

IF @accountID > 0

BEGIN



-- edit code: this code already exists

IF (SELECT COUNT(*) FROM Accounts WHERECode = @code AND AccountId <> @accountID AND...

BEGIN

SET @error = 1;

SET @errorMessage = 'The new code is a duplicate of an existing code; you may not ...

END
```

```
ELSE IF (SELECT COUNT(*) FROM Accounts WHERE Code = @code AND DistrictId = @district...

BEGIN

... (truncated)
```

sp_FA_ApproveReq {sp-dbo-sp-fa-approvereq}

> Stored procedure: FA ApproveReq

Property	Value
Schema	dbo
Created	2012-06-14 00:04:23.280000
Modified	2022-07-07 21:41:51.943000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pRequisitionId	int	INPUT	p Requisition identifier
3	@pStatusCode	varchar(1)	INPUT	p Status code

Definition

```
CREATE PROCEDURE [dbo].[sp_FA_ApproveReq] @pSessionId int, @pRequisitionId int, @pStatu...



declare @UserApprovalLevel int,

@RequiredApprovalLevel int,

@UserId int,

@DistrictId int,

@RequisitionId int,

@RequisitionNumber varchar(255),

@CurrentApprovalLevel int,

@CurrentApprovalById int,

@CurrentApprovalId int,

@StatusId int,

@StatusCode char(1),

@PendingId int,

@HoldId int,

@ChangesId int,

@ApprovedId int,

@AtEDSId int,

@POPrintedId int,

@pStatusId int,

@CurrentStatus int,

@ApproverId int,

@POCount int,
```

```
@OnlineDistrict int,

@Amount money,

... (truncated)
```

sp_FA_AttemptLogin {sp-dbo-sp-fa-attemptlogin}

> Login/authentication procedure for FA_Attempt

Property	Value
Schema	dbo
Created	2012-06-14 00:06:32.173000
Modified	2024-10-18 03:57:04.120000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@rtDistrictCode	varchar(4)	INPUT	rt District code
2	@rtCometId	varchar(50)	INPUT	rt Comet identifier
3	@rtPassword	varchar(100)	INPUT	rt Password parameter

Definition

```
CREATE PROCEDURE dbo.sp_FA_AttemptLogin @rtDistrictCode varchar(4), @rtCometId varchar(...



DECLARE@tempSessionId int



set nocount on

insert DebugMsgs(Msg) values('DistrictCode=>' + isnull(@rtDistrictCode,'<null>') + '< C...




INSERTSessionTable (UserId, SchoolId, DistrictId, CSRepId, RepUserId, ApprovalLevel, A...

SELECTdbo.Users.UserId, dbo.School.SchoolId, dbo.District.DistrictId, CSRep.CSRepId, C...

  FROMdbo.Users

  JOINdbo.School on dbo.School.SchoolId = dbo.Users.SchoolId

ANDdbo.School.Active = 1

  JOINdbo.District on dbo.District.DistrictId = dbo.School.DistrictId

AND dbo.District.Active = 1

AND isnull(dbo.District.DisableLogins,0) = 0

  LEFT OUTER JOIN CSRep on CSRep.UserId = Users.UserId

WHEREdbo.District.DistrictCode = @rtDistrictCode

   ANDdbo.Users.CometId = convert(int,@rtCometId)

   AND(dbo.Users.Password = dbo.uf_EncryptPassword(@rtPassword) OR dbo.Users.Password ...

   ANDdbo.Users.Active = 1



if @@RowCount != 0
```

```
begin

  select @tempSessionId = scope_identity()

... (truncated)
```

sp_FA_AttemptLogin_BK_20241018_Before_EncryptedPassword {sp-dbo-sp-fa-attemptlogin-bk-20241018-befor

> Login/authentication procedure for FAAttemptBK20241018Before_Encrypted

Property	Value
Schema	dbo
Created	2024-10-18 03:17:08.343000
Modified	2024-10-18 03:17:39.573000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@rtDistrictCode	varchar(4)	INPUT	rt District code
2	@rtCometId	varchar(50)	INPUT	rt Comet identifier
3	@rtPassword	varchar(50)	INPUT	rt Password parameter

Definition

```
CREATE PROCEDURE [dbo].[sp_FA_AttemptLogin_copy1] @rtDistrictCode varchar(4), @rtCometI...



DECLARE@tempSessionId int



set nocount on

insert DebugMsgs(Msg) values('DistrictCode=>' + isnull(@rtDistrictCode,'<null>') + '< C...




INSERTSessionTable (UserId, SchoolId, DistrictId, CSRepId, RepUserId, ApprovalLevel, A...

SELECTdbo.Users.UserId, dbo.School.SchoolId, dbo.District.DistrictId, CSRep.CSRepId, C...

  FROMdbo.Users

  JOINdbo.School on dbo.School.SchoolId = dbo.Users.SchoolId

ANDdbo.School.Active = 1

  JOINdbo.District on dbo.District.DistrictId = dbo.School.DistrictId

AND dbo.District.Active = 1

AND isnull(dbo.District.DisableLogins,0) = 0

  LEFT OUTER JOIN CSRep on CSRep.UserId = Users.UserId

WHEREdbo.District.DistrictCode = @rtDistrictCode

   ANDdbo.Users.CometId = convert(int,@rtCometId)

   ANDdbo.Users.Password = @rtPassword

   ANDdbo.Users.Active = 1



if @@RowCount != 0
```

```
begin

  select @tempSessionId = scope_identity()

... (truncated)
```

sp_FA_AvailableAccounts {sp-dbo-sp-fa-availableaccounts}

> Stored procedure: FA AvailableAccounts

Property	Value
Schema	dbo
Created	2012-06-14 00:06:19.817000
Modified	2012-06-14 00:06:19.817000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@sessionID	varchar(40)	INPUT	session identifier
2	@schoolID	int	INPUT	school identifier
3	@budgetID	int	INPUT	budget identifier

Definition

```
CREATE PROCEDURE [dbo].[sp_FA_AvailableAccounts] @sessionID varchar(40), @schoolID int,...



AS



DECLARE @availableAccounts TABLE (

AccountId int

, Active tinyint

, DistrictId int

, SchoolId int

, Code varchar(50)

, [Description] varchar(512)

, [Type] varchar(255)

, Allocated money

, Spent money

)



INSERTINTO @availableAccounts

SELECTA.AccountId, A.Active, A.DistrictId, ISNULL(A.SchoolId,0) AS SchoolId, A.Code, ...

, CASE

WHEN ISNULL(A.SchoolId,0) > 0 THEN S.Name

ELSE 'All Schools'

END AS [Type]

, ISNULL((SELECT Allocated FROM vw_FA_BudgetAccounts WHERE AccountId = A.AccountId A...
```

```
, ISNULL((SELECT Spent FROM vw_FA_BudgetAccounts WHERE AccountId = A.AccountId AND B...

FROMSessionTable ST, Accounts A

... (truncated)
```

sp_FA_CCAddAddendaItem {sp-dbo-sp-fa-ccaddaddendaitem}

> Item management procedure for FA_CCAddAddenda

Property	Value
Schema	dbo
Created	2012-07-11 11:08:17.740000
Modified	2015-11-24 23:37:43.310000
Parameters	14

Parameters

#	Parameter	Type	Direction	Description
1	@pHeadingId	int	INPUT	p Heading identifier
2	@pKeywordId	int	INPUT	p Keyword identifier
3	@pDescription	varchar(1024)	INPUT	p description
4	@pUnitId	int	INPUT	p Unit identifier
5	@pBrandName	varchar(255)	INPUT	p Brand name
6	@pManufacturorNu	varchar(50)	INPUT	p Manufacturor number
7	@pVendorId	int	INPUT	p Vendor identifier
8	@pVendorPartNuml	varchar(50)	INPUT	p Vendor Part number
9	@pItemsPerUnit	varchar(50)	INPUT	p Items Per Unit parameter
10	@pListPrice	money	INPUT	p List price
11	@pExtraDetail	varchar(1024)	INPUT	p Extra Detail parameter
12	@pRequisitionId	int	INPUT	p Requisition identifier
13	@pQuantity	int	INPUT	p quantity

14	@sessionID	int	INPUT	session identifier

Definition

```
CREATE  procedure [dbo].[sp_FA_CCAddAddendaItem] @pHeadingId int, @pKeywordId int, @pDe...

                                        @pUnitId int, @pBrandName varchar(255), @pManufac...

                                        @pVendorPartNumber varchar(50), @pItemsPerUnit va...

                                        @pRequisitionId int, @pQuantity int, @sessionID int

as



declare @NextNumber varchar(50),

@DistrictCode varchar(16),

@DistrictId int,

@CategoryId int,

@ItemId int,

@UnitCode varchar(16),

@PricePlanId int,

@CatalogId int



  select @DistrictCode = District.DistrictCode,

         @DistrictId = District.DistrictId,

         @CategoryId = Requisitions.CategoryId,

         @CatalogId = Catalog.CatalogId

    from dbo.Requisitions
```

```
        join dbo.Users on Users.UserId = Requisitions.UserId

        join dbo.District on District.DistrictId = Users.DistrictId

        left outer join Catalog on Catalog.CategoryId = Requisitions.CategoryId

                                and Catalog.Active = 1

                                and Catalog.Name = 'EDS'

    ... (truncated)
```

sp_FA_CCUpdateAddendaItem {sp-dbo-sp-fa-ccupdateaddendaitem}

> Item management procedure for FA_CCUpdateAddenda

Property	Value
Schema	dbo
Created	2012-06-14 00:00:46.850000
Modified	2015-11-24 23:37:31.473000
Parameters	15

Parameters

#	Parameter	Type	Direction	Description
1	@pHeadingId	int	INPUT	p Heading identifier
2	@pKeywordId	int	INPUT	p Keyword identifier
3	@pDescription	varchar(1024)	INPUT	p description
4	@pUnitId	int	INPUT	p Unit identifier
5	@pBrandName	varchar(255)	INPUT	p Brand name
6	@pManufacturorNu	varchar(50)	INPUT	p Manufacturor number
7	@pVendorId	int	INPUT	p Vendor identifier
8	@pVendorPartNum	varchar(50)	INPUT	p Vendor Part number
9	@pItemsPerUnit	varchar(50)	INPUT	p Items Per Unit parameter
10	@pListPrice	money	INPUT	p List price

11	@pExtraDetail	varchar(1024)	INPUT	p Extra Detail parameter
12	@pRequisitionId	int	INPUT	p Requisition identifier
13	@pQuantity	int	INPUT	p quantity
14	@pDetailId	int	INPUT	p Detail identifier
15	@sessionID	int	INPUT	session identifier

Definition

```
CREATE procedure [dbo].[sp_FA_CCUpdateAddendaItem] @pHeadingId int, @pKeywordId int, @p...

                                        @pUnitId int, @pBrandName varchar(255), @pManufac...

                                        @pVendorPartNumber varchar(50), @pItemsPerUnit va...

                                        @pRequisitionId int, @pQuantity int, @pDetailId i...

as

declare @ItemId int,

@BidItemId int,

@UnitCode varchar(16),

@PricePlanId int



  -- Get Detail Record Info

  select @ItemId = ItemId,

         @BidItemId = BidItemId

    from Detail with (nolock)

   where DetailId = @pDetailId



  -- Get Unit Code Description

  select @UnitCode = Code

    from Units with (nolock)

   where UnitId = @pUnitId



  if @@rowcount = 0

  begin
```

```
      select @UnitCode = ''

    end

  ... (truncated)
```

sp_FA_CreatePO {sp-dbo-sp-fa-createpo}

> Purchase order procedure for FA_Create

Property	Value
Schema	dbo
Created	2012-06-13 23:58:41.520000
Modified	2012-06-13 23:58:41.520000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@poTempID	int	INPUT	po Temp identifier
3	@pRequisitionId	int	INPUT	p Requisition identifier

Definition

```
CREATE procedure [dbo].[sp_FA_CreatePO] @pSessionId int, @poTempID int, @pRequisitionId...



declare @POId int,

@VendorId int,

@DistrictId int,

@AwardId int,

@BidHeaderId int,

@PONumber int,

@Prefix varchar(20),

@Suffix varchar(20),

@BudgetID int,

@PODate datetime,

@tempItemCount int,

@MaxPODetailItems int,

@MaxDetailId int,

@StatusId int,

@CreatedPOStatusID int



/* we are doing a check before we pop open the PO modal now

select Requisitions.RequisitionId
```

```
  from Requisitions

  join StatusTable on StatusTable.StatusId = Requisitions.StatusId

  join School on School.SchoolId = Requisitions.SchoolId
```

```
    join District on District.DistrictId = School.DistrictId

    join Category on Category.CategoryId = Requisitions.CategoryId

  ... (truncated)
```

sp_FA_CreateReportSession {sp-dbo-sp-fa-createreportsession}

> Purchase order procedure for FA_Create

Property	Value
Schema	dbo
Created	2012-06-13 23:50:28.747000
Modified	2012-06-13 23:50:28.747000
Parameters	0

Definition

```
CREATE PROCEDURE [dbo].[sp_FA_CreateReportSession]

AS

INSERT INTO ReportSession (RSData)

VALUES('')



SELECT SCOPE_IDENTITY() AS ReportSessionID
```

sp_FA_CreateReportSessionLinks {sp-dbo-sp-fa-createreportsessionlinks}

> Purchase order procedure for FA_CreateLinks

Property	Value
Schema	dbo
Created	2012-06-13 23:50:35.653000
Modified	2012-06-13 23:50:35.653000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@reportSessionID	int	INPUT	report Session identifier
2	@intID	int	INPUT	int identifier

Definition

```
CREATE PROCEDURE [dbo].[sp_FA_CreateReportSessionLinks] @reportSessionID int, @intID int

AS

INSERT INTO ReportSessionLinks (RSId, IntId)

VALUES(@reportSessionID, @intID)
```

sp_FA_DeleteAccount {sp-dbo-sp-fa-deleteaccount}

> Stored procedure: FA DeleteAccount

Property	Value
Schema	dbo
Created	2012-06-13 23:50:56.307000
Modified	2012-06-13 23:50:56.307000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@accountID	int	INPUT	account identifier

Definition

```
CREATE PROCEDURE [dbo].[sp_FA_DeleteAccount] @accountID int



AS



DECLARE @userAssigned int, @schoolAssigned int, @error int, @errorMessage varchar(255);



/*

SET@userAssigned = (SELECT ISNULL(COUNT(UserAccountID),0) FROM UserAccounts WHERE Acc...

SET@schoolAssigned = (SELECT ISNULL(COUNT(BudgetAccountID),0) FROM BudgetAccounts WHE...

*/

SET @error = 0;

SET @errorMessage = 'Account deleted.';

 /*

IF @userAssigned != 0 OR @schoolAssigned != 0

BEGIN

SET @error = 1;

SET @errorMessage = 'You may not delete a code that is currently in use.';

END

*/

IF @error = 0

BEGIN



UPDATEAccounts
```

```
SETActive = 0

WHEREAccountId = @accountID

... (truncated)
```

sp_FA_DeleteRequisition {sp-dbo-sp-fa-deleterequisition}

> Requisition procedure for FA_Delete

Property	Value
Schema	dbo
Created	2013-03-13 10:41:06.793000
Modified	2025-04-16 03:31:13.683000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pRequisitionId	int	INPUT	p Requisition identifier
3	@rStatus	int	OUTPUT	r status

Definition

```
CREATE PROCEDURE dbo.sp_FA_DeleteRequisition

    @pSessionId INT,

    @pRequisitionId INT,

    @rStatus INT OUTPUT

AS

BEGIN

    SET NOCOUNT ON;



    DECLARE @CSRepId INT;



    -- Check existence

    IF NOT EXISTS (SELECT 1 FROM Requisitions WITH (ROWLOCK, UPDLOCK) WHERE Requisition...

    BEGIN

        -- Not found

        RETURN;

    END;



    -- Check POs

    IF EXISTS (SELECT 1 FROM PO WITH (NOLOCK) WHERE RequisitionId = @pRequisitionId)

    BEGIN

        -- POs exist

        RETURN;

    END;
```

```
    -- Check CSRepId

... (truncated)
```

sp_FA_DeleteRequisition_bk20250416 {sp-dbo-sp-fa-deleterequisition-bk20250416}

> Requisition procedure for FADeletebk20250416

Property	Value
Schema	dbo
Created	2025-04-15 22:25:26.927000
Modified	2025-04-15 22:25:26.927000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pRequisitionId	int	INPUT	p Requisition identifier
3	@rStatus	int	OUTPUT	r status

Definition

```
CREATE procedure dbo.sp_FA_DeleteRequisition_bk20250416 @pSessionId int, @pRequisitionI...



declare @ReqNumber varchar(255),

@POCount int,

@DetailCount int,

@ApprovalCount int,

@CSRepId int



select Requisitions.RequisitionId

  from Requisitions

 where Requisitions.RequisitionId = @pRequisitionId



if @@rowcount = 0

begin

  RETURN

end



select @POCount = count(*)

  from Requisitions

  join PO on PO.RequisitionId = Requisitions.RequisitionId

 where Requisitions.RequisitionId = @pRequisitionId



if @POCount != 0
```

```
begin

  RETURN

... (truncated)
```

sp_FA_DeleteUser {sp-dbo-sp-fa-deleteuser}

> User management procedure for FA_Delete

Property	Value
Schema	dbo
Created	2012-06-13 23:51:17.787000
Modified	2012-06-13 23:51:17.787000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@sessionID	int	INPUT	session identifier
2	@userID	int	INPUT	user identifier

Definition

```
CREATE PROCEDURE [dbo].[sp_FA_DeleteUser] @sessionID int, @userID int



AS

BEGIN



UPDATEUserAccounts

SETActive = 0

WHEREUserId = @userID



UPDATEUsers

SETActive = 0

WHEREUserId = @userID



SELECT0 AS Error, 'User Deleted.' AS ErrorMessage



END
```

sp_FA_GetAlert {sp-dbo-sp-fa-getalert}

> Alert procedure for FA_Get

Property	Value
Schema	dbo
Created	2012-06-14 00:03:35.783000
Modified	2012-06-14 00:03:35.783000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@sessionID	int	INPUT	session identifier

Definition

```
CREATE PROCEDURE [dbo].[sp_FA_GetAlert] @sessionID int



AS



SELECTA.[Message]

FROMSessionTable ST, Alerts A

WHEREGETDATE() BETWEEN A.DisplayStart AND A.DisplayEnd

AND(A.DistrictID = ST.DistrictId OR A.DistrictID IS NULL)

AND ST.SessionId=@sessionID

ORDERBY A.DistrictId DESC, A.AlertID DESC
```

sp_FA_getUserKeys {sp-dbo-sp-fa-getuserkeys}

> User management procedure for FA_getKeys

Property	Value
Schema	dbo
Created	2012-06-14 00:05:35.370000
Modified	2025-03-20 14:07:38.853000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@userID	varchar(50)	INPUT	user identifier

Definition

```
CREATE PROCEDURE [dbo].[sp_FA_getUserKeys] @userID varchar(50) AS



SELECTSK.KeyName AS [Key]

FROMSecurityRoleUsers SRU, SecurityRoles SR, SecurityRoleKeys SRK, SecurityKeys SK

WHERESK.SecurityKeyID = SRK.SecurityKeyID

ANDSRK.SecurityRoleID = SR.SecurityRoleID

ANDSR.SecurityRoleID = SRU.SecurityRoleID

ANDSRU.UserID = @userID

 group by SK.KeyName
```

sp_FA_NewPONumbers {sp-dbo-sp-fa-newponumbers}

> Purchase order procedure for FA_NewNumbers

Property	Value
Schema	dbo
Created	2012-06-14 00:08:08.827000
Modified	2012-06-14 00:08:08.827000
Parameters	4

Parameters

#	Parameter	Type	Direction	Description
1	@sessionID	int	INPUT	session identifier

2	@RSID	int	INPUT	RS identifier
3	@budgetID	int	INPUT	budget identifier
4	@nextNumber	int	INPUT	next number

Definition

```
CREATE procedure [dbo].[sp_FA_NewPONumbers] @sessionID int, @RSID int, @budgetID int, @...



AS



DECLARE @temp table ([counter] int identity(1,1), firstNumber int)

DECLARE @rTemp table (ID int identity(1,1) , RequisitionID int, RequisitionNumber varch...



-- get all the PO line items

insert into @rTemp exec sp_FA_RequisitionsForPurchaseOrderModal @sessionID,@budgetID,@R...



-- put the next number into a table with ID's to use for adding later

INSERTINTO @temp

SELECTISNULL(@nextNumber,1)

FROM@rTemp



SELECTCAST((firstNumber+[counter]-1) AS varchar) AS poNumber

FROM@temp
```

sp_FA_NextPONumber {sp-dbo-sp-fa-nextponumber}

> Purchase order procedure for FA_NextNumber

Property	Value
Schema	dbo
Created	2012-06-13 23:57:58.450000
Modified	2014-01-10 17:09:24.863000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@sessionID	int	INPUT	session identifier
2	@RSID	int	INPUT	RS identifier
3	@budgetID	int	INPUT	budget identifier

Definition

```
CREATE procedure [dbo].[sp_FA_NextPONumber] @sessionID int, @RSID int, @budgetID int



AS



DECLARE@districtID int

, @UseSchool bit

, @schoolID int

, @allowLZ bit

, @prefix varchar(20)

, @nextNumber int

, @endNumber int

, @suffix varchar(20)



SET@schoolID = NULL;

SET @allowLZ = 1;

SET @prefix = '';

SET @nextNumber = NULL;

SET @endNumber = NULL;

SET @suffix = '';
```

```
-- find out if we are going to use school specific PO numbers

SELECT@districtID = D.DistrictId

, @UseSchool = D.POsbySchool
```

```
FROMDistrict D, SessionTable ST

WHERED.DistrictId = ST.DistrictID

... (truncated)
```

sp_FA_RequisitionsForPurchaseOrderModal {sp-dbo-sp-fa-requisitionsforpurchaseordermodal}

> Order processing procedure for FA_sForPurchaseModal

Property	Value
Schema	dbo
Created	2012-06-14 00:07:52.177000
Modified	2025-09-18 15:12:45.383000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@sessionID	int	INPUT	session identifier
2	@budgetID	int	INPUT	budget identifier
3	@RSID	int	INPUT	RS identifier

Definition

```
CREATE PROCEDURE [dbo].[sp_FA_RequisitionsForPurchaseOrderModal] @sessionID int, @budge...



AS

/*

SELECTR.RequisitionID, R.RequisitionNumber, u.StatusName, u.CategoryName, u.CometID, u...

, D.VendorID, SUM(D.Quantity*D.BidPrice) AS VendorTotal, (SELECT CASE WHEN COUNT(POId...

, ISNULL(PO.PONumber,'') AS PONumber

, CASE ISNULL(D.BidHeaderId,0)

WHEN 0 THEN R.BidHeaderID

ELSE ISNULL(D.BidHeaderId,0)

END AS BidHeaderID

, ISNULL(POST.StatusName,'') AS POStatus

, NN.Prefix, NN.Suffix

, COUNT(D.DetailID) AS NumberOfItems

--INTO#TempRequisitions

FROMReportSession RS, ReportSessionLinks RSL, uf_FA_Requisitions (@sessionID,@budgetID...

LEFT OUTER JOIN PO ON PO.RequisitionId = D.RequisitionId AND PO.VendorId = D.VendorI...

LEFT OUTER JOIN POStatusTable POST ON POST.POStatusID = PO.POStatusID

LEFT OUTER JOIN NextNumber NN ON NN.BudgetId=@budgetID AND NN.IdType='P'

, Vendors V

WHEREV.VendorId = D.VendorID

ANDV.VendorId <> 7691

ANDISNULL(V.Code,'0000') != '0000'
```

```
AND D.RequisitionID = R.RequisitionID

AND R.RequisitionId = u.RequisitionID

... (truncated)
```

sp_FA_RequisitionsTotals {sp-dbo-sp-fa-requisitionstotals}

> Requisition procedure for FA_ss

Property	Value
Schema	dbo
Created	2012-06-14 00:05:52.733000
Modified	2022-05-19 15:15:12.133000
Parameters	10

Parameters

#	Parameter	Type	Direction	Description
1	@sessionID	int	INPUT	session identifier
2	@budgetID	int	INPUT	budget identifier
3	@categoryID	int	INPUT	category identifier
4	@accountID	int	INPUT	account identifier
5	@userID	int	INPUT	user identifier
6	@schoolID	int	INPUT	school identifier
7	@statusID	int	INPUT	status identifier
8	@RSID	int	INPUT	RS identifier
9	@type	varchar(20)	INPUT	type parameter
10	@statusDesc	varchar(255)	INPUT	status description

Definition

```
--exec sp_FA_RequisitionsTotals 3500803,7183,null,null,null,null,null,null,'ApproveRequ...

CREATE PROCEDURE [dbo].[sp_FA_RequisitionsTotals] @sessionID int, @budgetID int,@catego...



AS



/*

DECLARE@sessionID int = 3282747

, @budgetID int = 6531

,@categoryID int = NULL

, @accountID int = 21317

, @userID int = 211072

, @schoolID int = 14612

, @statusID int = NULL

, @RSID int = NULL

, @type varchar(20) = 'ApproveRequisitions'

*/





CREATE TABLE #ReqTotals (

SchoolID int NOT NULL

, AccountID int null

, AccountCode varchar(50) NULL

, UserAccountID int NULL
```

```
, Annual money NOT NULL

, Incidental money NOT NULL

... (truncated)
```

sp_FA_SaveHeading {sp-dbo-sp-fa-saveheading}

> Stored procedure: FA SaveHeading

Property	Value
Schema	dbo
Created	2012-06-13 23:48:40.363000
Modified	2012-06-13 23:48:40.363000
Parameters	5

Parameters

#	Parameter	Type	Direction	Description
1	@sessionID	int	INPUT	session identifier
2	@districtID	int	INPUT	district identifier
3	@categoryID	int	INPUT	category identifier
4	@title	varchar(255)	INPUT	title parameter
5	@headingID	int	OUTPUT	heading identifier

Definition

```
CREATE PROCEDURE [dbo].[sp_FA_SaveHeading] @sessionID int, @districtID int, @categoryID...



AS



INSERT INTO [EDS].[dbo].[Headings]

            ([Active]

            ,[CategoryId]

            ,[Code]

            ,[ExpandAll]

            ,[Title]

            ,[Description]

            ,[DistrictId])

      VALUES

            (1

            ,@categoryID

            ,NULL

            ,0

            ,@title

            ,NULL

            ,@districtID)
```

```
SELECT@headingID = SCOPE_IDENTITY()
```

sp_FA_SaveKeyword {sp-dbo-sp-fa-savekeyword}

> Stored procedure: FA SaveKeyword

Property	Value
Schema	dbo
Created	2012-06-13 23:48:22.890000
Modified	2012-06-13 23:48:22.890000
Parameters	6

Parameters

#	Parameter	Type	Direction	Description
1	@sessionID	int	INPUT	session identifier
2	@categoryID	int	INPUT	category identifier
3	@districtID	int	INPUT	district identifier
4	@headingID	int	INPUT	heading identifier
5	@keyword	varchar(50)	INPUT	keyword parameter
6	@keywordID	int	OUTPUT	keyword identifier

Definition

```
CREATE PROCEDURE [dbo].[sp_FA_SaveKeyword] @sessionID int, @categoryID int, @districtID...



AS



INSERT INTO [EDS].[dbo].[Keywords]

            ([Active]

            ,[CategoryId]

            ,[HeadingId]

            ,[DistrictId]

            ,[Keyword])

      VALUES

            (1

            ,@categoryId

            ,@headingId

            ,@districtId

            ,@keyword)



SET @keywordID = (SELECT SCOPE_IDENTITY())
```

sp_FA_SavePOs {sp-dbo-sp-fa-savepos}

> Purchase order procedure for FA_Saves

Property	Value
Schema	dbo

Created	2012-06-13 23:59:03.643000
Modified	2014-01-10 17:09:15.490000
Parameters	6

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@poTempID	int	INPUT	po Temp identifier
3	@pRequisitionId	int	INPUT	p Requisition identifier
4	@poGenerationMet	varchar(10)	INPUT	po Generation Method parameter
5	@poEnd	int	INPUT	po End parameter
6	@created	int	OUTPUT	created parameter

Definition

```
CREATE PROCEDURE [dbo].[sp_FA_SavePOs] @pSessionId int, @poTempID int, @pRequisitionId ...



/*

declare

@pSessionId int = 2926562

, @poTempID int = 220

, @pRequisitionId int = 1471345

, @poGenerationMethod varchar(10) = 'Automatic'

, @poEnd int = 24

, @created int;

*/



AS



DECLARE @PONumber int

, @districtID int

, @schoolID int

, @budgetID int

, @nextNumberID int

, @nextNumber int
```

```
, @useSchool bit

, @lastPONumber int

, @prefix varchar(20)
```

```
, @suffix varchar(20)

, @endNumber int

... (truncated)
```

sp_FA_SaveRequisitionNote {sp-dbo-sp-fa-saverequisitionnote}

> Requisition procedure for FA_SaveNote

Property	Value
Schema	dbo
Created	2012-06-13 23:49:10.810000
Modified	2025-04-16 16:45:52.687000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@requisitionID	int	INPUT	requisition identifier
2	@note	varchar(MAX)	INPUT	note parameter
3	@userID	int	INPUT	user identifier

Definition

```
CREATE PROCEDURE [dbo].[sp_FA_SaveRequisitionNote] @requisitionID int, @note varchar(ma...



AS



INSERT INTO [dbo].[RequisitionNotes]

            ([RequisitionID]

            ,[Note]

            ,[CreateDate]

            ,[CreatedByUserID])

      VALUES

            (@requisitionID

            ,@note

            ,GETDATE()

            ,@userID)



     SELECT SCOPE_IDENTITY() AS RequisitionNoteID
```

sp_FA_SaveRequisitionNoteEmails {sp-dbo-sp-fa-saverequisitionnoteemails}

> Requisition procedure for FA_SaveNotes

Property	Value
Schema	dbo
Created	2012-06-13 23:49:30.307000
Modified	2025-04-16 16:48:52.423000

Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@requisitionNoteID	int	INPUT	requisition Note identifier
2	@userID	int	INPUT	user identifier

Definition

```
CREATE PROCEDURE [dbo].[sp_FA_SaveRequisitionNoteEmails] @requisitionNoteID int, @userI...



AS



INSERT INTO [dbo].[RequisitionNoteEmails]

            ([RequisitionNoteID]

            ,[UserID])

      VALUES

            (@requisitionNoteID

            ,@userID)
```

sp_FA_SaveUser {sp-dbo-sp-fa-saveuser}

> User management procedure for FA_Save

Property	Value
Schema	dbo
Created	2012-06-13 23:51:30.840000
Modified	2024-12-01 08:26:37.090000

Parameters	12

Parameters

#	Parameter	Type	Direction	Description
1	@UserID	int	INPUT	User identifier
2	@FirstName	varchar(100)	INPUT	First name
3	@LastName	varchar(100)	INPUT	Last name
4	@Email	varchar(255)	INPUT	Email address
5	@Password	varchar(50)	INPUT	Password (should be hashed)
6	@DistrictID	int	INPUT	District identifier
7	@SchoolID	int	INPUT	School identifier
8	@ApproverID	int	INPUT	Approver identifier
9	@Attention	varchar(50)	INPUT	Attention parameter
10	@ApprovalLevel	tinyint	INPUT	Approval Level parameter
11	@DistrictAcctgCode	varchar(20)	INPUT	District Acctg code
12	@NotificationOption	int	INPUT	Notification Option identifier

Definition

```
CREATE     PROCEDURE [dbo].[sp_FA_SaveUser] @UserID int, @FirstName varchar(100), @Last...



AS



DECLARE @ShippingId int ,@Active tinyint ,@UserName varchar (10),@DisableNewRequisitio...



SET @ShippingId = null;

SET @Active = 1;

SET @UserName = NULL;

SET @DisableNewRequisition = NULL;

--SET @DistrictAcctgCode = NULL;

SET @NewRequisitionButton = 1;

SET @AllowIncidentals = 1;

SET @AllowVendorChanges = NULL;

SET @AllowShipToChanges = NULL;

SET @AllowTM = 0;

SET @SecurityRoleId = NULL;

SET @Use20 = NULL;

SET @EmailByPassDate = NULL;
```

```
IF @UserID = 0



BEGIN
```

```
INSERT INTO Users

... (truncated)
```

sp_FA_SetBudgetAccount {sp-dbo-sp-fa-setbudgetaccount}

> Stored procedure: FA SetBudgetAccount

Property	Value
Schema	dbo
Created	2012-06-13 23:51:05.293000
Modified	2013-02-04 00:10:19.300000
Parameters	6

Parameters

#	Parameter	Type	Direction	Description
1	@sessionID	varchar(40)	INPUT	session identifier
2	@budgetID	int	INPUT	budget identifier
3	@accountID	int	INPUT	account identifier
4	@setBudget	tinyint	INPUT	set Budget parameter
5	@budget	money	INPUT	budget parameter
6	@active	tinyint	INPUT	active parameter

Definition

```
CREATE PROCEDURE [dbo].[sp_FA_SetBudgetAccount] @sessionID varchar(40), @budgetID int, ...



AS



DECLARE @budgetAccountID integer;



SET @budgetAccountID =(

SELECTBudgetAccountID

FROMBudgetAccounts

WHEREBudgetId = @budgetID

ANDAccountId = @accountID

--ANDActive = 1

)



IF @setBudget = 0

SET @budget = NULL



IF @budgetAccountID > 0



UPDATEBudgetAccounts

SETUseAllocations = @setBudget

, BudgetAmount = @budget

, Active = @active
```

```
WHEREBudgetAccountId = @budgetAccountID



... (truncated)
```

sp_FA_SetUserAccount {sp-dbo-sp-fa-setuseraccount}

> User management procedure for FA_SetAccount

Property	Value
Schema	dbo
Created	2012-06-13 23:51:12.660000
Modified	2019-05-01 13:54:48.217000
Parameters	6

Parameters

#	Parameter	Type	Direction	Description
1	@sessionID	varchar(40)	INPUT	session identifier
2	@userID	int	INPUT	user identifier
3	@budgetAccountID	int	INPUT	budget Account identifier
4	@useAllocations	tinyint	INPUT	use Allocations parameter
5	@allocationAmount	money	INPUT	allocation amount
6	@active	tinyint	INPUT	active parameter

Definition

```
CREATE PROCEDURE [dbo].[sp_FA_SetUserAccount] @sessionID varchar(40), @userID int, @bud...



AS



DECLARE @userAccountID integer;



SET @userAccountID =(

SELECTtop 1 UserAccountID

FROMUserAccounts

WHEREUserID = @userID

ANDBudgetAccountId = @budgetAccountID

--ANDActive = 1

order by isnull(Active,0) desc, UserAccountId

)



IF @useAllocations = 0

SET @allocationAmount = NULL



IF @userAccountID > 0
```

```
UPDATEUserAccounts

SETUseAllocations = @useAllocations

, AllocationAmount = @allocationAmount
```

```
, Active = @active

WHEREUserAccountId = @userAccountID

... (truncated)
```

sp_FA_UpdatePOStatus {sp-dbo-sp-fa-updatepostatus}

> Purchase order procedure for FA_UpdateStatus

Property	Value
Schema	dbo
Created	2012-06-13 23:48:34.287000
Modified	2012-06-13 23:48:34.287000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@sessionID	int	INPUT	session identifier
2	@poTempID	int	INPUT	po Temp identifier
3	@action	varchar(25)	INPUT	action parameter

Definition

```
CREATE PROCEDURE [dbo].[sp_FA_UpdatePOStatus] @sessionID int, @poTempID int, @action va...



DECLARE @createdStatusID int

, @downloadedStatusID int

, @sentStatusID int



SELECT @createdStatusID = POStatusID FROM POStatusTable WHERE StatusName = 'Created'

SELECT @downloadedStatusID = POStatusID FROM POStatusTable WHERE StatusName = 'Downloaded'

SELECT @sentStatusID = POStatusID FROM POStatusTable WHERE StatusName = 'Electronically...



UPDATEPO

SETPOStatusID = CASE @action

WHEN 'Save' THEN @createdStatusID

WHEN 'Download' THEN @downloadedStatusID

WHEN 'Send' THEN @sentStatusID

ELSE ISNULL(POStatusID,0)

END

FROMPOTemp, POTempDetails

WHEREPO.RequisitionId = POTempDetails.RequisitionID

ANDPO.VendorId = POTempDetails.VendorID

ANDPOTempDetails.POTempID = POTemp.POTempID

ANDPOTemp.POTempID = @poTempID

ANDPOTemp.SessionID = @sessionID
```

```
-- don't update rows if a lower level action is performed

ANDPO.POStatusID < CASE @action

... (truncated)
```

sp_FA_UpdateRequisitionStatus {sp-dbo-sp-fa-updaterequisitionstatus}

> Requisition procedure for FA_UpdateStatus

Property	Value
Schema	dbo
Created	2012-06-14 00:04:56.720000
Modified	2020-03-03 11:30:26.047000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pRequisitionId	int	INPUT	p Requisition identifier
3	@pStatusCode	varchar(1)	INPUT	p Status code

Definition

```
CREATE PROCEDURE [dbo].[sp_FA_UpdateRequisitionStatus] @pSessionId int, @pRequisitionId...



declare @UserApprovalLevel int,

@RequiredApprovalLevel int,

@UserId int,

@DistrictId int,

@RequisitionId int,

@RequisitionNumber varchar(255),

@CurrentApprovalLevel int,

@StatusId int,

@StatusCode char(1),

@PendingId int,

@HoldId int,

@ChangesId int,

@ApprovedId int,

@AtEDSId int,

@POPrintedId int,

@POPrintedForReqId int,

@pStatusId int,

@CurrentStatus int,

@ApproverId int,

@POCount int,

@OnlineDistrict int,
```

```
@Amount money



... (truncated)
```

sp_FixVendorItemCode {sp-dbo-sp-fixvendoritemcode}

> Item management procedure for FixCode

Property	Value
Schema	dbo
Created	2009-07-23 13:29:04.400000
Modified	2009-07-23 13:51:07.340000
Parameters	5

Parameters

#	Parameter	Type	Direction	Description
1	@oldVendorItemCo	varchar(50)	INPUT	old Vendor Item code
2	@newVendorItemC	varchar(50)	INPUT	new Vendor Item code
3	@newPackedVendo	varchar(50)	INPUT	new Packed Vendor Item code
4	@VendorId	int	INPUT	Vendor identifier
5	@BidHeaderId	int	INPUT	Bid Header identifier

Definition

```
CREATE procedure sp_FixVendorItemCode

@oldVendorItemCode varchar(50),

@newVendorItemCode varchar(50),

@newPackedVendorItemCode varchar(50),

@VendorId int,

@BidHeaderId int

as



--2707, 2708, 2958 Sax

--2782, 2800, 2805, 2807 EE



update BidResults

   set VendorItemCode = @newVendorItemCode,

       PackedVendorItemCode = @newPackedVendorItemCode

--select *

  from BidResults

  join BidImports on BidImports.BidImportId = BidResults.BidImportId

                 and BidImports.VendorId = @VendorId

                 and BidImports.BidHeaderId = @BidHeaderId

 where BidResults.VendorItemCode = @oldVendorItemCode



update BidItems

   set VendorItemCode = @newVendorItemCode,
```

```
        PackedVendorItemCode = @newPackedVendorItemCode

--select *

... (truncated)
```

sp_getCurrentPrices {sp-dbo-sp-getcurrentprices}

> Retrieve record(s) from getCurrents

Property	Value
Schema	dbo
Created	2012-10-10 13:49:38.757000
Modified	2012-10-10 13:49:38.757000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pItemId	int	INPUT	p Item identifier

Definition

```
create procedure sp_getCurrentPrices @pItemId int

as

declare @TodaysDate datetime

select @TodaysDate = getdate()

select lp.*, PricePlans.Code PricePlanCode from dbo.uf_LookupPricesAlt(@pItemId,@Todays...
```

sp_GetPODetailByIds {sp-dbo-sp-getpodetailbyids}

> Retrieve record(s) from GetByIds

Property	Value
Schema	dbo
Created	2025-04-24 22:18:22.730000
Modified	2025-04-24 22:25:22.800000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@POIds	nvarchar(MAX)	INPUT	POIds parameter

Definition

```
CREATE PROCEDURE dbo.sp_GetPODetailByIds

    @POIds NVARCHAR(MAX)

AS

BEGIN

/*

    SELECT pd.*

    FROM PODetail pd

    WHERE pd.POId IN (

        SELECT CAST(value AS INT)

        FROM STRING_SPLIT(@POIds, ',')

    )

    ORDER BY

        pd.SortSeq;

*/

    -- Create a temp table to store POIds

    CREATE TABLE #POIds (POId INT);

    INSERT INTO #POIds (POId)

    SELECT CAST(value AS INT)

    FROM STRING_SPLIT(@POIds, ',');
```

```
    SELECT pd.*

    FROM PODetail pd WITH(NOLOCK)

    JOIN #POIds p ON pd.POId = p.POId
```

```
    --ORDER BY pd.SortSeq;


... (truncated)
```

sp_GetRequisitionShipping {sp-dbo-sp-getrequisitionshipping}

> Retrieve record(s) from GetShipping

Property	Value
Schema	dbo
Created	2025-04-15 22:38:13.350000
Modified	2025-04-15 22:38:13.350000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@RequisitionId	int	INPUT	Requisition identifier

Definition

```
CREATE PROCEDURE dbo.sp_GetRequisitionShipping

    @RequisitionId INT

AS

BEGIN

    SET NOCOUNT ON;



    SELECT  RequisitionID, TotalRequisitionCost, UserAccountID,

            COALESCE(AdditionalShippingCost, 0) AdditionalShippingCost,

            COALESCE(AdditionalFreight, 0) AdditionalFreight,

            COALESCE(det.UpdateRequired, 0) UpdateRequired

    FROM    Requisitions WITH (NOLOCK)

    OUTER APPLY (SELECT SUM(Detail.ShippingCost) ShippingCost,

                        MAX(CASE WHEN Detail.Quantity != COALESCE(Detail.ShippingQuanti...

                                 OR Detail.ShippingUpdated IS NULL

                                 OR COALESCE(Detail.ShippingCost, 0) = 0 THEN 1 ELSE 0 ...

                  FROM   Detail WITH (NOLOCK)

                  WHERE  Detail.RequisitionId = Requisitions.RequisitionId

                  AND    Detail.AdditionalShipping = 1) det

    WHERE   RequisitionID = @RequisitionId;

END;
```

sp_GetUserRequisitions {sp-dbo-sp-getuserrequisitions}

> Retrieve record(s) from Gets

Property	Value
Schema	dbo
Created	2025-04-16 00:23:39.447000
Modified	2025-04-16 00:23:39.447000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@SessionID	int	INPUT	Session identifier
2	@BudgetID	int	INPUT	Budget identifier
3	@UserID	int	INPUT	User identifier

Definition

```
CREATE PROCEDURE dbo.sp_GetUserRequisitions

    @SessionID INT,

    @BudgetID INT,

    @UserID INT

AS

BEGIN

    SET NOCOUNT ON;



    WITH StatusHistoryCount AS (

        SELECT RequisitionId, COUNT(*) AS HistoryCount

        FROM vw_StatusHistory WITH (NOLOCK)

        GROUP BY RequisitionId

    )

    SELECT  R.*,

            ISNULL(shc.HistoryCount, 0) AS HistoryCount,

            UA.UseAllocations | ISNULL(UA.UseBudgetAccountAllocations, 0) AS UseAllocat...

            CASE

                WHEN ISNULL(UA.UseBudgetAccountAllocations, 0) = 1 AND UA.UseAllocation...

                WHEN ISNULL(UA.UseBudgetAccountAllocations, 0) = 1 AND UA.UseAllocation...

                WHEN ISNULL(UA.UseBudgetAccountAllocations, 0) = 1 AND UA.UseAllocation...

                WHEN ISNULL(UA.UseBudgetAccountAllocations, 0) = 0 AND UA.UseAllocation...

                ELSE ISNULL(UA.AmountAvailable, 0)

            END AS AllocationAvailable,
```

```
            CASE

                WHEN ISNULL(UA.UseBudgetAccountAllocations, 0) = 1 AND UA.UseAllocation...

... (truncated)
```

sp_helpdiagramdefinition {sp-dbo-sp-helpdiagramdefinition}

> Initialization procedure for helpdiagramdefinition

Property	Value
Schema	dbo
Created	2009-03-26 16:18:10.600000
Modified	2009-03-26 16:18:10.600000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@diagramname	sysname	INPUT	diagramname parameter
2	@owner_id	int	INPUT	owner id parameter

Definition

```
CREATE PROCEDURE dbo.sp_helpdiagramdefinition

(

@diagramname sysname,

@owner_idint= null

)

WITH EXECUTE AS N'dbo'

AS

BEGIN

set nocount on



declare @theId int

declare @IsDbo int

declare @DiagIdint

declare @UIDFoundint



if(@diagramname is null)

begin

RAISERROR (N'E_INVALIDARG', 16, 1);

return -1

end



execute as caller;

select @theId = DATABASE_PRINCIPAL_ID();
```

```
select @IsDbo = IS_MEMBER(N'db_owner');

if(@owner_id is null)

... (truncated)
```

sp_helpdiagrams {sp-dbo-sp-helpdiagrams}

> Stored procedure: helpdiagrams

Property	Value
Schema	dbo
Created	2009-03-26 16:18:10.600000
Modified	2009-03-26 16:18:10.600000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@diagramname	sysname	INPUT	diagramname parameter
2	@owner_id	int	INPUT	owner id parameter

Definition

```
CREATE PROCEDURE dbo.sp_helpdiagrams

(

@diagramname sysname = NULL,

@owner_id int = NULL

)

WITH EXECUTE AS N'dbo'

AS

BEGIN

DECLARE @user sysname

DECLARE @dboLogin bit

EXECUTE AS CALLER;

SET @user = USER_NAME();

SET @dboLogin = CONVERT(bit,IS_MEMBER('db_owner'));

REVERT;

SELECT

[Database] = DB_NAME(),

[Name] = name,

[ID] = diagram_id,

[Owner] = USER_NAME(principal_id),

[OwnerID] = principal_id

FROM

sysdiagrams

WHERE
```

```
(@dboLogin = 1 OR USER_NAME(principal_id) = @user) AND

(@diagramname IS NULL OR name = @diagramname) AND

... (truncated)
```

sp_HoldRequisition {sp-dbo-sp-holdrequisition}

> Requisition procedure for Hold

Property	Value
Schema	dbo
Created	2002-03-06 16:39:54.483000
Modified	2013-07-02 16:11:06.803000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	varchar(255)	INPUT	p Session identifier
2	@pRequisitionId	varchar(255)	INPUT	p Requisition identifier

Definition

```
CREATE         procedure [dbo].[sp_HoldRequisition] @pSessionId varchar(255),@pRequisit...



declare @SessionId int,

@RequisitionId int,

@ApprovalLevel tinyint,

@CurrentApprovalLevel tinyint,

@UserApprovalLevel tinyint,

@UserId int,

@StatusId int



-- Convert Passed Data

select @SessionId = convert(int,@pSessionId),

       @RequisitionId = convert(int,@pRequisitionId)



exec sp_DeleteZeros 0, @pRequisitionId



-- Get User

select @UserId = ISNULL(Users.UserId,0)

  from SessionTable

  join Users on Users.UserId = case isnull(SessionTable.RepUserId,0) when 0 then Sessio...

 where SessionId = @SessionId



if @@rowcount < 1
```

```
begin

  RAISERROR('Invalid Session Id or Session has timed-out',16,1)

... (truncated)
```

sp_ImportVendorsBid {sp-dbo-sp-importvendorsbid}

> Purchase order procedure for sBid

Property	Value
Schema	dbo
Created	2011-08-15 21:46:11.503000
Modified	2022-08-12 11:04:50.830000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pPassPhrase	varchar(255)	INPUT	p Pass Phrase parameter
2	@pVendorBidId	varchar(50)	INPUT	p Vendor Bid identifier

Definition

```
CREATE procedure [dbo].[sp_ImportVendorsBid] @pPassPhrase varchar(255), @pVendorBidId v...

as

declare @VendorBidId int,

@BidImportId int,

@ReturnCode varchar(50),

@CategoryType int,

@DecryptedPW varchar(1024)



select @VendorBidId = CAST(@pVendorBidId as int)

select @DecryptedPW = null

select @CategoryType = isnull(Category.Type,1)

  from Category with (nolock)

  join BidHeaders on BidHeaders.CategoryId = Category.CategoryId

  join VendorBids.dbo.VendorBids VendorBids on VendorBids.calendarid = BidHeaders.BidHe...

                                              and VendorBids.vendorbidid = @VendorBidId



select @DecryptedPW = isnull(cast(DECRYPTBYPASSPHRASE(@pPassPhrase,VendorBids.bidpwd,1,...

  from VendorBids.dbo.VendorBids VendorBids with (nolock)

 where VendorBids.VendorBidId = @VendorBidId


if isnull(@pPassPhrase,'') = ''

begin

  select @ReturnCode = 'A Valid Entryption Code MUST be entered.'
```

```
end

else

... (truncated)
```

sp_IPQueueStart {sp-dbo-sp-ipqueuestart}

> Queue management procedure for IPStart

Property	Value
Schema	dbo
Created	2012-12-18 16:26:38.293000
Modified	2012-12-18 17:51:55.580000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pDevice	varchar(50)	INPUT	p Device parameter

Definition

```
create procedure sp_QueueStart @pDevice varchar(50)

as

declare @IPQueueId int

begin transaction

select @IPQueueId = null

select top 1 @IPQueueId = IPQueueId

  from IPQueue

 where IPQueue.Queue = @pDevice

   and Started is null

 order by IPQueueId



 if @@ROWCOUNT = 1

 begin

update IPQueue

   set Started = GETDATE(),

   Status = 'Generating Instruction Packets'

     where IPQueue.IPQueueId = @IPQueueId

 end

 commit Transaction

 select @IPQueueId IPQueueId
```

sp_ISBNAdd {sp-dbo-sp-isbnadd}

> Stored procedure: ISBNAdd

Property	Value
Schema	dbo
Created	2002-05-02 13:31:27.187000
Modified	2013-07-15 11:39:16.240000
Parameters	4

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pRequisitionId	int	INPUT	p Requisition identifier
3	@pItemCode	varchar(25)	INPUT	p Item code
4	@pQuantity	int	INPUT	p quantity

Definition

```
CREATE      PROCEDURE [dbo].[sp_ISBNAdd] @pSessionId int, @pRequisitionId int, @pItemCo...



declare @ReturnValue int,

@ItemId int,

@DistrictId int,

@DetailId int,

@CategoryId int,

@CatalogId int,

        @BudgetAccountId int,

@TotalCost money,

@paddedItemCode varchar(16),

@EffectiveDate datetime



--BEGIN TRANSACTION



select @ReturnValue = 0

select @EffectiveDate = getdate()



select @DistrictId = DistrictId

  from SessionTable

 where SessionId = @pSessionId



if @@rowcount = 0
```

```
begin

--  RAISERROR('Bad Session Identifier',16,1)

... (truncated)
```

sp_Logout {sp-dbo-sp-logout}

> Logging procedure for out

Property	Value
Schema	dbo
Created	2001-08-24 14:40:45.093000
Modified	2009-03-25 06:55:28.600000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier

Definition

```
CREATE procedure sp_Logout @pSessionId int AS



update SessionTable

   SET SessionEnd = getdate()

 WHERE SessionId = @pSessionId

   AND SessionEnd is null
```

sp_MakeReq {sp-dbo-sp-makereq}

> Stored procedure: MakeReq

Property	Value
Schema	dbo
Created	2002-07-30 19:17:59.950000
Modified	2015-11-24 23:37:35.827000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pImportId	int	INPUT	p Import identifier

Definition

```
CREATE procedure [dbo].[sp_MakeReq] @pImportId int as



-- Declare Local Variables

declare @BatchId int,

        @Records int



-- Get Record Count

select @Records = count(*)

  from ImportDetail

 where ImportId = @pImportId



-- Create New Batch Entry

insert Batches (BatchDate,Records,Type,ImportedRecords,SourceId, InputRecords)

  values (getdate(), @Records, 'Q', @Records, 2, @Records)



-- Get Batch Id

select @BatchId = Scope_Identity() --DCH 11/24/2015 @@identity



-- Load Batch Detail

insert BatchDetail (Active, BatchId, RecordNumber, Type, DistrictCode, Category, CometI...

 select 1, @BatchId, min(ImportDetailId), 'Q', substring(ImportData,1,2), substring(Imp...

        '00000', right('0000000000000000' + rtrim(substring(ImportData,305,8)),15), rig...

        'Q', substring(ImportData,1,2), substring(ImportData,3,1),
```

```
        '00000', right('0000000000000000' + rtrim(substring(ImportData,305,8)),15), rig...

    from ImportDetail

... (truncated)
```

sp_MasterBudgetBook {sp-dbo-sp-masterbudgetbook}

> Stored procedure: MasterBudgetBook

Property	Value
Schema	dbo
Created	2004-10-01 14:05:29.050000
Modified	2016-11-04 15:55:21.777000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pCategoryId	int	INPUT	p Category identifier

Definition

```
CREATE procedure [dbo].[sp_MasterBudgetBook] @pCategoryId int as

declare @DistrictLetter char(1),

@OrderBookId int



set nocount on



declare CodeCur cursor fast_forward read_only for

select substring(District.Name,1,1)

  from District

  join DistrictCategories on DistrictCategories.DistrictId = District.DistrictId

                          and DistrictCategories.CategoryId = @pCategoryId

 where District.Active = 1

 group by substring(District.Name,1,1)

 order by substring(District.Name,1,1)



open CodeCur



fetch next from CodeCur into @DistrictLetter



while @@fetch_status = 0

begin

    insert OrderBooks (PricePlanDescription, Category, CategoryId, PricePlanId, Type, D...

      select 'Budget Book for Districts Starting with the Letter ' + @DistrictLetter, C...
```

```
          from Category

         where Category.CategoryId = @pCategoryId

  ... (truncated)
```

sp_MergeAccounts {sp-dbo-sp-mergeaccounts}

> Merge accounts

Property	Value
Schema	dbo
Created	2016-06-27 13:39:30.133000
Modified	2016-06-27 13:39:30.133000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@pBudgetId	int	INPUT	p Budget identifier
2	@pSourceAccountI	int	INPUT	p Source Account identifier
3	@pDestinationAcco	int	INPUT	p Destination Account identifier

Definition

```
create procedure sp_MergeAccounts @pBudgetId int, @pSourceAccountId int, @pDestinationA...

as

begin



-- Move User Accounts

Update UserAccounts

   set BudgetAccountId = BudgetAccounts.BudgetAccountId

  from UserAccounts

  join BudgetAccounts on BudgetAccounts.BudgetId = UserAccounts.BudgetAccountId

                      and BudgetAccounts.AccountId = @pDestinationAccountId

                      and BudgetAccounts.Active = 1

                      and BudgetAccounts.BudgetId = @pBudgetId

 where UserAccounts.AccountId = @pSourceAccountId

   and UserAccounts.Active = 1

   and UserAccounts.BudgetId = @pBudgetId

   and (select top 1 ua.UserAccountId

          from UserAccounts ua

         where ua.BudgetId = UserAccounts.BudgetId

           and ua.AccountId = @pDestinationAccountId

           and ua.UserId = UserAccounts.UserId

           and ua.Active = 1) is null



-- Move Requisitions to New Accounts
```

```
Update Requisitions

   set AccountCode = Accounts.Code,

... (truncated)
```

sp_MergeAwards {sp-dbo-sp-mergeawards}

> Award processing procedure for Merges

Property	Value
Schema	dbo
Created	2002-05-28 11:12:44.250000
Modified	2009-03-25 06:55:28.690000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pSourceAwardId	int	INPUT	p Source Award identifier
2	@pDestAwardId	int	INPUT	p Dest Award identifier

Definition

```
CREATE  procedure sp_MergeAwards @pSourceAwardId int, @pDestAwardId int AS



declare @SourceBidId int,

@DestBidId int,

@SourcePricePlanId int,

@DestPricePlanId int,

@SourceCategoryId int,

@DestCategoryId int,

@SourceVendorId int,

@DestVendorId int



select @SourceCategoryId = CategoryId,

       @SourceVendorId = VendorId,

       @SourcePricePlanId = PricePlanId,

       @SourceBidId = BidId

  from Awards

 where AwardId = @pSourceAwardId



if @@rowcount = 0

begin

  RAISERROR('Invalid Source Award Specified',16,1)

  return

end
```

```
select @DestCategoryId = CategoryId,

... (truncated)
```

sp_MergeBidImports {sp-dbo-sp-mergebidimports}

> Purchase order procedure for MergeBids

Property	Value
Schema	dbo
Created	2004-04-14 00:29:47.387000
Modified	2009-03-25 06:55:28.457000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pSourceBidImpor	int	INPUT	p Source Bid Import identifier
2	@pTargetBidImport	int	INPUT	p Target Bid Import identifier

Definition

```
create procedure sp_MergeBidImports @pSourceBidImportId int, @pTargetBidImportId int as



INSERT INTO [EDS].[dbo].[BidResults]([BidImportId], [BidHeaderId], [BidRequestItemId], ...

  SELECT @pTargetBidImportId, BidResults.[BidHeaderId], BidResults.[BidRequestItemId], ...

    FROM [EDS].[dbo].[BidResults]

    left outer join BidResults br0 on br0.BidImportId = @pTargetBidImportId

                                   and br0.BidRequestItemId = BidResults.BidRequestItemId

   WHERE BidResults.BidImportId = @pSourceBidImportId

     AND br0.BidResultsId is null



UPDATE [EDS].[dbo].[BidResults]

   SET [CategoryId]=ss.CategoryId,

       [DistrictId]=ss.DistrictId,

       [ItemId]=ss.ItemId,

       [ItemCode]=ss.ItemCode,

       [Units]=ss.Units,

       [Alternate]=ss.Alternate,

       [Quantity]=ss.Quantity,

       [ItemBidType]=ss.ItemBidType,

       [UnitPrice]=ss.UnitPrice,

       [Cost]=ss.Cost,

       [VendorItemCode]=ss.VendorItemCode,

       [QuantityBid]=ss.QuantityBid,
```

```
        [ItemsPerUnit]=ss.ItemsPerUnit,

        [UnitId]=ss.UnitId,

  ... (truncated)
```

sp_MergeBids {sp-dbo-sp-mergebids}

> Merge bids

Property	Value
Schema	dbo
Created	2002-05-28 10:32:49
Modified	2009-03-25 06:55:28.690000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pSourceBidId	int	INPUT	p Source Bid identifier
2	@pDestBidId	int	INPUT	p Dest Bid identifier

Definition

```
CREATE  procedure sp_MergeBids @pSourceBidId int, @pDestBidId int AS



declare @SourceBidId int,

@DestBidId int,

@SourcePricePlanId int,

@DestPricePlanId int,

@SourceCategoryId int,

@DestCategoryId int,

@SourceVendorId int,

@DestVendorId int



select @SourceCategoryId = CategoryId,

       @SourceVendorId = VendorId,

       @SourcePricePlanId = PricePlanId

  from Bids

 where BidId = @pSourceBidId



if @@rowcount = 0

begin

  RAISERROR('Invalid Source Bid Specified',16,1)

  return

end
```

```
select @DestCategoryId = CategoryId,

       @DestVendorId = VendorId,

... (truncated)
```

sp_MoveIndexes {sp-dbo-sp-moveindexes}

> Move procedure for Indexes

Property	Value
Schema	dbo
Created	2004-01-30 19:54:57.577000
Modified	2004-01-30 19:54:57.577000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pDBName	varchar(255)	INPUT	p DB name
2	@pNewFileGroup	varchar(255)	INPUT	p New File Group parameter

Definition

```
CREATE procedure dbo.sp_MoveIndexes @pDBName varchar(255), @pNewFileGroup varchar(255) as



declare @IndexName varchar(255),

@TableName varchar(255),

@ColumnName varchar(255),

@SQLCommand varchar(1024),

@id int,

@indid int,

@Keyno int



declare ci cursor fast_forward read_only for

select su.name + '.[' + so.name + ']' TableName, si.Name IndexName, so.id, si.indid

  from eds..sysindexkeys sik

  join eds..sysobjects so on so.id = sik.id

  join eds..sysusers su on su.uid = so.uid

  join eds..sysindexes si on si.id = sik.id

                         and si.indid = sik.indid

where so.xtype = 'U'

  and si.status in ( 2097152 , 18450)

group by su.Name, so.Name, si.Name, so.id, si.indid

order by TableName, IndexName



open ci
```

```
fetch next from ci into @TableName, @IndexName, @id, @indid

... (truncated)
```

sp_MoveReqs {sp-dbo-sp-movereqs}

> Move procedure for Reqs

Property	Value
Schema	dbo
Created	2014-04-07 11:35:31.287000
Modified	2014-04-07 20:44:09.850000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@SourceBudget	int	INPUT	Source Budget parameter
2	@TargetBudget	int	INPUT	Target Budget parameter
3	@ReqNumbers	varchar(MAX)	INPUT	Req Numbers parameter

Definition

```
CREATE procedure dbo.sp_MoveReqs  @SourceBudget int, @TargetBudget int, @ReqNumbers var...



-- Create Budget Accounts as needed

insert BudgetAccounts (AccountId, Active, BudgetAmount, BudgetId, UseAllocations)

select a.AccountId, 1, bas.BudgetAmount, bt.BudgetId, bas.UseAllocations

  from BudgetAccounts bas

  join Accounts a on a.AccountId = bas.AccountId

  join Budgets bs on bs.BudgetId = bas.BudgetId

                 and bs.BudgetId = @SourceBudget

  join Budgets bt on bt.BudgetId = @TargetBudget

                 and bt.DistrictId = bs.DistrictId

  left outer join BudgetAccounts bat on bat.BudgetId = bt.BudgetId

                                     and bat.AccountId = a.AccountId

                                     and bat.Active = 1

 where bat.BudgetAccountId is null



-- Create Budget Accounts as needed

insert UserAccounts (AccountId, Active, BudgetId, UseAllocations, AllocationAmount, Bud...

select a.AccountId, 1, bt.BudgetId, uas.UseAllocations, uas.AllocationAmount, bat.Budge...

  from UserAccounts uas

  join BudgetAccounts bas on bas.BudgetAccountId = uas.BudgetAccountId

  join Accounts a on a.AccountId = uas.AccountId

  join Budgets bs on bs.BudgetId = uas.BudgetId
```

```
                    and bs.BudgetId = @SourceBudget

     join Budgets bt on bt.BudgetId = @TargetBudget

   ... (truncated)
```

sp_MPIHeadings {sp-dbo-sp-mpiheadings}

> Stored procedure: MPIHeadings

Property	Value
Schema	dbo
Created	2015-02-25 16:39:25.313000
Modified	2021-03-23 10:22:14.050000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@RequisitionId	int	INPUT	Requisition identifier

Definition

```
CREATE procedure [dbo].[sp_MPIHeadings] @RequisitionId int as

set nocount on

declare @BidHeaderId int, @DistrictId int, @CategoryId int

declare @BidsList table (RequisitionId int, BidHeaderId int)

declare @Headings table (HeadingId bigint, HeadingTitle varchar(255))



select @BidHeaderId = isnull(Requisitions.BidHeaderId,0),

   @DistrictId = isnull(Budgets.DistrictId,0),

   @CategoryId = isnull(Requisitions.CategoryId,0)

  from Requisitions with (nolock)

  left outer join Budgets on Budgets.BudgetId = Requisitions.BudgetId

 where RequisitionId = @RequisitionId



-- Build Base List of Bids for each Requisition

  if @BidHeaderId is not null and @BidHeaderId != 0

  begin

  insert @BidsList (RequisitionId, BidHeaderId)

values (@RequisitionId, @BidHeaderId)

  end
```

```
  -- Add All other bids needed to list

  while @@rowcount != 0

  begin
```

```
-- Add Parent PreBids

insert @BidsList (RequisitionId, BidHeaderId)

... (truncated)
```

sp_MSRPExporter {sp-dbo-sp-msrpexporter}

> Purchase order procedure for MSRPer

Property	Value
Schema	dbo
Created	2014-09-08 19:29:31.947000
Modified	2014-09-16 16:59:56.290000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@BidHeaderId	int	INPUT	Bid Header identifier

Definition

```
CREATE procedure [dbo].[sp_MSRPExporter] @BidHeaderId int

as



Truncate Table eds.dbo.MSRPExcelExport



insert eds.dbo.MSRPExcelExport(ManufacturerName, ProductLine, OptionName, ManufWebsite,...

select 'MANUFACTURER' ManufacturerName,'PRODUCT LINE/GROUP' ProductLine, 'DELIVERY OPT...



insert eds.dbo.MSRPExcelExport(ManufacturerName, ProductLine, OptionName, ManufWebsite,...

select Manufacturers.Name ManufacturerName, isnull(ManufacturerProductLines.Name,'') Pr...

       isnull(cast((select RangeBase from (select row_Number() over(order by RangeBase)...

       isnull(cast((select RangeWeight from (select row_Number() over(order by RangeBas...

       isnull(cast((select RangeBase from (select row_Number() over(order by RangeBase)...

       isnull(cast((select RangeWeight from (select row_Number() over(order by RangeBas...

       isnull(cast((select RangeBase from (select row_Number() over(order by RangeBase)...

       isnull(cast((select RangeWeight from (select row_Number() over(order by RangeBas...

-- [Definition truncated...]
```

sp_MSRPImporter {sp-dbo-sp-msrpimporter}

> Purchase order procedure for MSRPer

Property	Value
Schema	dbo
Created	2013-11-05 12:32:23.790000

Modified	2014-09-11 18:38:30.243000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@BidHeaderId	int	INPUT	Bid Header identifier

Definition

```
CREATE procedure [dbo].[sp_MSRPImporter] @BidHeaderId int

as

declare @CategoryId int/*,

@Columns int*/



select @CategoryId = BidHeaders.CategoryId

  from BidHeaders

 where BidHeaders.BidHeaderId = @BidHeaderId



/*

select @Columns = case

                    when max(ei.Base2) = 0 then 1

                    when max(ei.Base3) = 0 then 2

                    when max(ei.Base4) = 0 then 3

                    when max(ei.Base5) = 0 then 4

                    when max(ei.Base6) = 0 then 5

                    when max(ei.Base7) = 0 then 6

                    when max(ei.Base8) = 0 then 7

                    when max(ei.Base9) = 0 then 8

                    when max(ei.Base10) = 0 then 9

                    else

                      10

                  end
```

```
 from MSRPExcelImport ei

where ei.BidNumber = @BidHeaderId

... (truncated)
```

sp_NewReportSession {sp-dbo-sp-newreportsession}

> Purchase order procedure for New

Property	Value
Schema	dbo
Created	2002-05-13 23:42:21.043000
Modified	2015-11-24 23:37:41.333000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pReportRequest	varchar(4096)	INPUT	p Report Request parameter
2	@rRSId	int	OUTPUT	r RS identifier

Definition

```
CREATE procedure [dbo].[sp_NewReportSession] @pReportRequest varchar(4096), @rRSId int ...



insert ReportSession (RSData) values (@pReportRequest)



select @rRSId = Scope_Identity() --DCH 11/24/2015 @@IDENTITY



return
```

sp_NewRequisitionId {sp-dbo-sp-newrequisitionid}

> Requisition procedure for NewId

Property	Value
Schema	dbo
Created	2001-09-06 23:26:02.420000
Modified	2025-06-26 11:50:16.557000
Parameters	5

Parameters

#	Parameter	Type	Direction	Description
1	@pDistrictId	int	INPUT	p District identifier
2	@pSchoolId	int	INPUT	p School identifier
3	@pBudgetId	int	INPUT	p Budget identifier
4	@pUserId	int	INPUT	p User identifier
5	@ReqId	int	OUTPUT	Req identifier

Definition

```
CREATE procedure [dbo].[sp_NewRequisitionId] @pDistrictId int, @pSchoolId int, @pBudget...



declare

@DistrictId int,

@SchoolId int,

@BudgetId int,

@UserId int,

@UseSchool tinyint,

@ReqNumber varchar(50),

@UserAccountId int,

@BudgetAccountId int,

@AccountCode varchar(50)



  select @DistrictId = @pDistrictId,

 @SchoolId = @pSchoolId,

 @BudgetId = @pBudgetId,

 @UserId = @pUserId,

 @BudgetAccountId = null,

 @UserAccountId = null,

 @AccountCode = null
```

```
if ISNULL(@BudgetId,0) = 0

begin
```

```
        RAISERROR('Invalid BudgetId passed.',16,1)

        return

    ... (truncated)
```

sp_NewRequisitionId_BK20250416 {sp-dbo-sp-newrequisitionid-bk20250416}

> Requisition procedure for NewId_BK20250416

Property	Value
Schema	dbo
Created	2025-04-15 22:01:31.827000
Modified	2025-04-15 22:10:13.223000
Parameters	5

Parameters

#	Parameter	Type	Direction	Description
1	@pDistrictId	int	INPUT	p District identifier
2	@pSchoolId	int	INPUT	p School identifier
3	@pBudgetId	int	INPUT	p Budget identifier
4	@pUserId	int	INPUT	p User identifier
5	@ReqId	int	OUTPUT	Req identifier

Definition

```
CREATE procedure dbo.sp_NewRequisitionId_BK20250416 @pDistrictId int, @pSchoolId int, @...



declare

@DistrictId int,

@SchoolId int,

@BudgetId int,

@UserId int,

@UseSchool tinyint,

@ReqNumber varchar(50),

@UserAccountId int,

@BudgetAccountId int,

@AccountCode varchar(50)



  select @DistrictId = @pDistrictId,

 @SchoolId = @pSchoolId,

 @BudgetId = @pBudgetId,

 @UserId = @pUserId,

 @BudgetAccountId = null,

 @UserAccountId = null,

 @AccountCode = null
```

```
if ISNULL(@BudgetId,0) = 0

begin
```

```
        RAISERROR('Invalid BudgetId passed.',16,1)

        return

    ... (truncated)
```

sp_NewUpload {sp-dbo-sp-newupload}

> Stored procedure: NewUpload

Property	Value
Schema	dbo
Created	2005-04-19 17:24:29.160000
Modified	2009-03-25 06:55:28.503000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pVendorId	int	INPUT	p Vendor identifier

Definition

```
CREATE    procedure dbo.sp_NewUpload @pVendorId int as



declare @FileName varchar(255),

@HexBase char(16),

        @UploadId int,

@UploadType int



set nocount on



select @UploadType = UploadType

  from Vendors

 where VendorId = @pVendorId



if @UploadType = 2

begin

  insert VendorUploads (DateCreated) values (getdate())

  select @UploadId = Scope_Identity()



  select @HexBase = '0123456789ABCDEF'


  select @FileName = 'POC' + substring(@HexBase,((@UploadId / 0x010000) & 0x0F) + 1,1) ...



  update VendorUploads
```

```
        set FileName = @FileName

      where UploadId = @UploadId

  ... (truncated)
```

sp_OrderBookMaint {sp-dbo-sp-orderbookmaint}

> Order processing procedure for BookMaint

Property	Value
Schema	dbo
Created	2003-10-08 21:02:13.577000
Modified	2015-11-24 23:37:31.960000
Parameters	15

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pOrderBookId	int	INPUT	p Order Book identifier
3	@pCategoryId	int	INPUT	p Category identifier
4	@pPricePlanId	int	INPUT	p Price Plan identifier
5	@pDistrictId	int	INPUT	p District identifier
6	@pAwardId	int	INPUT	p Award identifier
7	@pCategoryDescrip	varchar(255)	INPUT	p Category description
8	@pPricePlanDescrip	varchar(255)	INPUT	p Price Plan description
9	@pMarkup	varchar(255)	INPUT	p Markup parameter
10	@pAction	tinyint	INPUT	p Action parameter
11	@pCopyMode	varchar(255)	INPUT	p Copy Mode parameter
12	@pActive	int	INPUT	p Active parameter
13	@pUseParentCatalo	int	INPUT	p Use Parent Catalog parameter
14	@pKeepZeroPages	int	INPUT	p Keep Zero Pages parameter

15	@pOrderBookYear	int	INPUT	p Order Book Year parameter

Definition

```
CREATE procedure [dbo].[sp_OrderBookMaint] @pSessionId int, @pOrderBookId int, @pCatego...

declare @ApprovalLevel int,

@OrderBookId int,

@OrderBookType char(1),

@Markup decimal(9,5)



set nocount on

set transaction isolation level serializable

begin transaction



if isnumeric(@pMarkup) = 1

begin

  select @Markup = convert(decimal(9,5),@pMarkup)

end

else

begin

  select @Markup = null

end



select @ApprovalLevel = ApprovalLevel
```

```
    from SessionTable

   where SessionId = @pSessionId



  if @@rowcount = 0

  begin

  ... (truncated)
```

sp_PAAccounts {sp-dbo-sp-paaccounts}

> Stored procedure: PAAccounts

Property	Value
Schema	dbo
Created	2003-06-30 12:55:49.390000
Modified	2003-06-30 12:55:49.390000
Parameters	7

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	varchar(255)	INPUT	p Session identifier
2	@pCategoryId	varchar(255)	INPUT	p Category identifier
3	@pBudgetId	varchar(255)	INPUT	p Budget identifier
4	@pAccountId	varchar(255)	INPUT	p Account identifier
5	@pSchoolId	varchar(255)	INPUT	p School identifier
6	@pUserId	varchar(255)	INPUT	p User identifier
7	@pStatusId	varchar(255)	INPUT	p Status identifier

Definition

```
CREATE                 procedure dbo.sp_PAAccounts @pSessionId varchar(255), @pCategory...

declare @DynamicSelect varchar(4096)



set transaction isolation level read uncommitted

select @DynamicSelect = 'set transaction isolation level read uncommitted' +

                        ' SELECT PendingApprovals.AccountId, isnull(Accounts.Code,'''')...

                        '  FROM dbo.PendingApprovals with (nolock)' +

                        '  JOIN SessionTable on SessionTable.SessionId = PendingApprova...

--                        '                   and (SessionTable.ApprovalLevel <= Pendin...

--                        '                     or SessionTable.ApprovalLevel >= 5)' +

                        '  LEFT OUTER JOIN dbo.Accounts on dbo.Accounts.AccountId = Pen...

--                        '  LEFT OUTER JOIN Users LastApprover on LastApprover.UserId ...

--                        '  LEFT OUTER JOIN Users NextApprover on NextApprover.UserId ...

--                        '  left outer join BidHeaders bh on bh.BidHeaderId = (select ...

                        ' WHERE SessionTable.SessionId = ' + @pSessionId

--                        '   and dbo.uf_RequisitionIsVisible(' + @pSessionId + ',Pendi...



if CONVERT(int,@pCategoryId) <> 0

begin

  select @DynamicSelect = @DynamicSelect + ' AND PendingApprovals.CategoryId = ' + @pCa...

end



if CONVERT(int,@pBudgetId) <> 0
```

```
begin

  select @DynamicSelect = @DynamicSelect + ' AND PendingApprovals.BudgetId = ' + @pBudg...

... (truncated)
```

sp_PABudgets {sp-dbo-sp-pabudgets}

> Stored procedure: PABudgets

Property	Value
Schema	dbo
Created	2003-06-30 12:55:49.903000
Modified	2014-10-07 17:53:20.323000
Parameters	7

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	varchar(255)	INPUT	p Session identifier
2	@pCategoryId	varchar(255)	INPUT	p Category identifier
3	@pBudgetId	varchar(255)	INPUT	p Budget identifier
4	@pAccountId	varchar(255)	INPUT	p Account identifier
5	@pSchoolId	varchar(255)	INPUT	p School identifier
6	@pUserId	varchar(255)	INPUT	p User identifier
7	@pStatusId	varchar(255)	INPUT	p Status identifier

Definition

```
CREATE PROCEDURE [dbo].[sp_PABudgets] @pSessionId varchar(255), @pCategoryId varchar(25...



declare @DynamicSelect varchar(4096)



set transaction isolation level read uncommitted

select @DynamicSelect = 'set transaction isolation level read uncommitted' +

                        ' select Budgets.BudgetId, Budgets.Name' +

'  from (' +

'    select SessionTable.BudgetId, SessionTable.ApprovalLevel' +

'      from SessionTable with (nolock)' +

'     where SessionTable.SessionId = ' + @pSessionId +

'    union ' +

'      SELECT distinct PendingApprovals.BudgetId, SessionTable.ApprovalLevel' +

'        FROM dbo.PendingApprovals with (nolock)' +

'        JOIN SessionTable on SessionTable.SessionId = PendingApprovals.SessionId' +

'WHERE SessionTable.SessionId = ' + @pSessionId +

'   ) ss ' +

'  join Budgets b1 on b1.BudgetId = ss.BudgetId' +

                        '  join Budgets Budgets on Budgets.DistrictId = b1.DistrictId' +

                        ' where Budgets.VisibleFrom <= case ss.ApprovalLevel when 9 the...

                        '   and Budgets.VisibleUntil >= case ss.ApprovalLevel when 9 th...

                        '   and Budgets.Active = 1' +

                        ' ORDER BY Budgets.Name'
```

```
execute(@DynamicSelect)

... (truncated)
```

sp_PACategories {sp-dbo-sp-pacategories}

> Stored procedure: PACategories

Property	Value
Schema	dbo
Created	2003-06-30 12:55:50.437000
Modified	2003-06-30 12:55:50.437000
Parameters	7

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	varchar(255)	INPUT	p Session identifier
2	@pCategoryId	varchar(255)	INPUT	p Category identifier
3	@pBudgetId	varchar(255)	INPUT	p Budget identifier
4	@pAccountId	varchar(255)	INPUT	p Account identifier
5	@pSchoolId	varchar(255)	INPUT	p School identifier
6	@pUserId	varchar(255)	INPUT	p User identifier
7	@pStatusId	varchar(255)	INPUT	p Status identifier

Definition

```
CREATE              PROCEDURE dbo.sp_PACategories @pSessionId varchar(255), @pCategoryI...

declare @DynamicSelect varchar(4096)



set transaction isolation level read uncommitted

select @DynamicSelect = 'set transaction isolation level read uncommitted' +

                        ' SELECT distinct PendingApprovals.CategoryId, Category.Name' +

                        '  FROM dbo.PendingApprovals with (nolock)' +

                        '  JOIN dbo.Category on dbo.Category.CategoryId = dbo.PendingAp...

                        '  JOIN SessionTable on SessionTable.SessionId = PendingApprova...

                        '  LEFT OUTER JOIN Users LastApprover on LastApprover.UserId = ...

                        '  LEFT OUTER JOIN Users NextApprover on NextApprover.UserId = ...

                        '  left outer join BidHeaders bh on bh.BidHeaderId = (select to...

--                        '  JOIN District on District.DistrictId = SessionTable.Distri...

--                        '  JOIN Budgets on Budgets.DistrictId = District.DistrictId' +

                        ' WHERE PendingApprovals.SessionId = ' + @pSessionId

--                        '   and Budgets.VisibleFrom <= getdate()' +

--                        '   and Budgets.VisibleUntil >= getdate()' +

--                        '   and dbo.uf_RequisitionIsVisible(' + @pSessionId + ',Pendi...



if CONVERT(int,@pCategoryId) <> 0

begin

  select @DynamicSelect = @DynamicSelect + ' AND PendingApprovals.CategoryId = ' + @pCa...

end
```

```
if CONVERT(int,@pBudgetId) <> 0

... (truncated)
```

sp_PAComet {sp-dbo-sp-pacomet}

> Stored procedure: PAComet

Property	Value
Schema	dbo
Created	2003-06-30 12:55:50.920000
Modified	2010-02-01 01:06:45.233000
Parameters	7

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	varchar(255)	INPUT	p Session identifier
2	@pCategoryId	varchar(255)	INPUT	p Category identifier
3	@pBudgetId	varchar(255)	INPUT	p Budget identifier
4	@pAccountId	varchar(255)	INPUT	p Account identifier
5	@pSchoolId	varchar(255)	INPUT	p School identifier
6	@pUserId	varchar(255)	INPUT	p User identifier
7	@pStatusId	varchar(255)	INPUT	p Status identifier

Definition

```
CREATE           procedure [dbo].[sp_PAComet] @pSessionId varchar(255), @pCategoryId va...

declare @DynamicSelect varchar(4096)



set transaction isolation level read uncommitted

select @DynamicSelect = 'set transaction isolation level read uncommitted' +

                        ' SELECT dbo.PendingApprovals.UserId, right(''00000'' + convert...

                        '  FROM dbo.PendingApprovals with (nolock)' +

                        '  JOIN dbo.Users on dbo.Users.UserId = dbo.PendingApprovals.Us...

                        '  JOIN SessionTable on SessionTable.SessionId = PendingApprova...

--                        '                   and (SessionTable.ApprovalLevel <= Pendin...

--                        '                     or SessionTable.ApprovalLevel >= 5)' +

                        ' WHERE SessionTable.SessionId = ' + @pSessionId



if CONVERT(int,@pCategoryId) <> 0

begin

  select @DynamicSelect = @DynamicSelect + ' AND PendingApprovals.CategoryId = ' + @pCa...

end



if CONVERT(int,@pBudgetId) <> 0

begin

  select @DynamicSelect = @DynamicSelect + ' AND PendingApprovals.BudgetId = ' + @pBudg...

end

/*
```

```
if CONVERT(int,@pAccountId) <> 0

begin

... (truncated)
```

sp_PARequisitions {sp-dbo-sp-parequisitions}

> Requisition procedure for PAs

Property	Value
Schema	dbo
Created	2003-06-30 12:55:51.500000
Modified	2003-06-30 12:55:51.500000
Parameters	7

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	varchar(255)	INPUT	p Session identifier
2	@pCategoryId	varchar(255)	INPUT	p Category identifier
3	@pBudgetId	varchar(255)	INPUT	p Budget identifier
4	@pAccountId	varchar(255)	INPUT	p Account identifier
5	@pSchoolId	varchar(255)	INPUT	p School identifier
6	@pUserId	varchar(255)	INPUT	p User identifier
7	@pStatusId	varchar(255)	INPUT	p Status identifier

Definition

```
--sp_PARequisitionsTest '1264774', '', '4351', '', '', '', ''


CREATE  PROCEDURE dbo.sp_PARequisitions @pSessionId varchar(255), @pCategoryId varchar(...


declare @DynamicSelect varchar(4096)


set transaction isolation level read uncommitted

select @DynamicSelect = 'set transaction isolation level read uncommitted' +

                        ' SELECT PendingApprovals.SysId, PendingApprovals.RequisitionId...

                        ' case isnull(PendingApprovals.StatusId,0) ' +

                        '   when 29 then StatusTable.Name + '' on Bid '' + convert(varc...

                        '   else isnull(StatusTable.Name,''On Hold'') + isnull(case Pen...

                        ' end Status, isnull(PendingApprovals.ApprovalLevel,0) Approval...

                        'isnull((dbo.PendingApprovals.StatusId * 16777216) + case isnul...

                        '   when 29 then isnull(bh.BidHeaderId,0) ' +

                        '   else isnull(case PendingApprovals.StatusId when 2 then Next...

                        ' end,0) Stat, case isnull(UserAccounts.UseAllocations,0) when ...

                        ' JOIN SessionTable on SessionTable.SessionId = PendingApproval...

--                        '                   and (SessionTable.ApprovalLevel <= Pendin...

--                        '                     or SessionTable.ApprovalLevel >= 5)' +

                        ' JOIN dbo.Requisitions on dbo.Requisitions.RequisitionId = dbo...

                        ' JOIN StatusTable on StatusTable.StatusId = PendingApprovals.S...

                        ' LEFT OUTER JOIN School on School.SchoolId = Requisitions.Scho...
```

```
                            ' LEFT OUTER JOIN Category on Category.CategoryId = Requisition...

                            ' LEFT OUTER JOIN Users on Users.UserId = Requisitions.UserId ' +

... (truncated)
```

sp_PARequisitionsTest {sp-dbo-sp-parequisitionstest}

> Requisition procedure for PAsTest

Property	Value
Schema	dbo
Created	2006-06-26 15:02:06.543000
Modified	2006-06-26 15:02:06.543000
Parameters	7

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	varchar(255)	INPUT	p Session identifier
2	@pCategoryId	varchar(255)	INPUT	p Category identifier
3	@pBudgetId	varchar(255)	INPUT	p Budget identifier
4	@pAccountId	varchar(255)	INPUT	p Account identifier
5	@pSchoolId	varchar(255)	INPUT	p School identifier
6	@pUserId	varchar(255)	INPUT	p User identifier
7	@pStatusId	varchar(255)	INPUT	p Status identifier

Definition

```
--sp_PARequisitionsTest '618919', '', '3055', '', '', '', '33792673'


CREATE  PROCEDURE dbo.sp_PARequisitionsTest @pSessionId varchar(255), @pCategoryId varc...


declare @DynamicSelect varchar(4096)


set transaction isolation level read uncommitted

select @DynamicSelect = 'set transaction isolation level read uncommitted' +

                        ' SELECT PendingApprovals.SysId, PendingApprovals.RequisitionId...

                        ' case isnull(PendingApprovals.StatusId,0) ' +

                        '   when 29 then StatusTable.Name + '' on Bid '' + convert(varc...

                        '   else isnull(StatusTable.Name,''On Hold'') + isnull(case Pen...

                        ' end Status, isnull(PendingApprovals.ApprovalLevel,0) Approval...

                        'isnull((dbo.PendingApprovals.StatusId * 16777216) + case isnul...

                        '   when 29 then isnull(bh.BidHeaderId,0) ' +

                        '   else isnull(case PendingApprovals.StatusId when 2 then Next...

                        ' end,0) Stat, case isnull(UserAccounts.UseAllocations,0) when ...

                        ' JOIN SessionTable on SessionTable.SessionId = PendingApproval...

--                        '                   and (SessionTable.ApprovalLevel <= Pendin...

--                        '                     or SessionTable.ApprovalLevel >= 5)' +

                        ' JOIN dbo.Requisitions on dbo.Requisitions.RequisitionId = dbo...

                        ' JOIN StatusTable on StatusTable.StatusId = PendingApprovals.S...

                        ' LEFT OUTER JOIN School on School.SchoolId = Requisitions.Scho...
```

```
                            ' LEFT OUTER JOIN Category on Category.CategoryId = Requisition...

                            ' LEFT OUTER JOIN Users on Users.UserId = Requisitions.UserId ' +

  ... (truncated)
```

sp_PARequisitionsTotal {sp-dbo-sp-parequisitionstotal}

> Requisition procedure for PAs

Property	Value
Schema	dbo
Created	2003-06-30 12:55:52.107000
Modified	2003-06-30 12:55:52.107000
Parameters	7

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	varchar(255)	INPUT	p Session identifier
2	@pCategoryId	varchar(255)	INPUT	p Category identifier
3	@pBudgetId	varchar(255)	INPUT	p Budget identifier
4	@pAccountId	varchar(255)	INPUT	p Account identifier
5	@pSchoolId	varchar(255)	INPUT	p School identifier
6	@pUserId	varchar(255)	INPUT	p User identifier
7	@pStatusId	varchar(255)	INPUT	p Status identifier

Definition

```
CREATE                PROCEDURE dbo.sp_PARequisitionsTotal @pSessionId varchar(255), @p...



declare @DynamicSelect varchar(4096)



set transaction isolation level read uncommitted

select @DynamicSelect = 'set transaction isolation level read uncommitted' +

                        ' SELECT ISNULL(sum(PendingApprovals.Amount),0) as TotalAmount' +

                        ' FROM dbo.PendingApprovals with (nolock)' +

                        ' JOIN SessionTable on SessionTable.SessionId = PendingApproval...

--                        '                   and (SessionTable.ApprovalLevel <= Pendin...

--                        '                     or SessionTable.ApprovalLevel >= 5)' +

                        ' JOIN dbo.Requisitions on dbo.Requisitions.RequisitionId = dbo...

                        ' JOIN StatusTable on StatusTable.StatusId = PendingApprovals.S...

--                        ' LEFT OUTER JOIN School on School.SchoolId = Requisitions.Sc...

--                        ' LEFT OUTER JOIN Category on Category.CategoryId = Requisiti...

--                        ' LEFT OUTER JOIN Users on Users.UserId = Requisitions.UserId...

--                        ' LEFT OUTER JOIN BudgetAccounts on BudgetAccounts.BudgetAcco...

--                        ' LEFT OUTER JOIN Accounts on Accounts.AccountId = BudgetAcco...

                        ' LEFT OUTER JOIN Users LastApprover on LastApprover.UserId = P...

                        ' LEFT OUTER JOIN Users NextApprover on NextApprover.UserId = P...

                        '  left outer join BidHeaders bh on bh.BidHeaderId = (select to...

                        ' WHERE SessionTable.SessionId = ' + @pSessionId

--                        '   and dbo.uf_RequisitionIsVisible(' + @pSessionId + ',Requi...
```

```
if CONVERT(int,@pCategoryId) <> 0

... (truncated)
```

sp_PASchools {sp-dbo-sp-paschools}

> Stored procedure: PASchools

Property	Value
Schema	dbo
Created	2003-06-30 12:55:52.590000
Modified	2003-06-30 12:55:52.590000
Parameters	7

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	varchar(255)	INPUT	p Session identifier
2	@pCategoryId	varchar(255)	INPUT	p Category identifier
3	@pBudgetId	varchar(255)	INPUT	p Budget identifier
4	@pAccountId	varchar(255)	INPUT	p Account identifier
5	@pSchoolId	varchar(255)	INPUT	p School identifier
6	@pUserId	varchar(255)	INPUT	p User identifier
7	@pStatusId	varchar(255)	INPUT	p Status identifier

Definition

```
CREATE            PROCEDURE dbo.sp_PASchools @pSessionId varchar(255), @pCategoryId var...

declare @DynamicSelect varchar(4096)



set transaction isolation level read uncommitted

select @DynamicSelect = 'set transaction isolation level read uncommitted' +

                        ' SELECT distinct PendingApprovals.SchoolId, School.Name' +

                        '  FROM dbo.PendingApprovals with (nolock)' +

                        '  JOIN dbo.School on dbo.School.SchoolId = dbo.PendingApproval...

                        '  JOIN SessionTable on SessionTable.SessionId = PendingApprova...

--                        '                   and (SessionTable.ApprovalLevel <= Pendin...

--                        '                     or SessionTable.ApprovalLevel >= 5)' +

                        ' WHERE SessionTable.SessionId = ' + @pSessionId

--                        '   and dbo.uf_RequisitionIsVisible(' + @pSessionId + ',Pendi...



if CONVERT(int,@pCategoryId) <> 0

begin

  select @DynamicSelect = @DynamicSelect + ' AND PendingApprovals.CategoryId = ' + @pCa...

end



if CONVERT(int,@pBudgetId) <> 0

begin

  select @DynamicSelect = @DynamicSelect + ' AND PendingApprovals.BudgetId = ' + @pBudg...

end
```

```
/*

... (truncated)
```

sp_PAStatus {sp-dbo-sp-pastatus}

> Stored procedure: PAStatus

Property	Value
Schema	dbo
Created	2003-06-30 12:55:53.107000
Modified	2003-06-30 12:55:53.107000
Parameters	7

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	varchar(255)	INPUT	p Session identifier
2	@pCategoryId	varchar(255)	INPUT	p Category identifier
3	@pBudgetId	varchar(255)	INPUT	p Budget identifier
4	@pAccountId	varchar(255)	INPUT	p Account identifier
5	@pSchoolId	varchar(255)	INPUT	p School identifier
6	@pUserId	varchar(255)	INPUT	p User identifier
7	@pStatusId	varchar(255)	INPUT	p Status identifier

Definition

```
--sp_PAStatus '618919', '', '3055', '', '', '', '33792673'


CREATE    procedure dbo.sp_PAStatus @pSessionId varchar(255), @pCategoryId varchar(255)...

declare @DynamicSelect varchar(4096)


set transaction isolation level read uncommitted

--select @DynamicSelect = 'SELECT distinct dbo.PendingApprovals.StatusId, dbo.StatusTab...

select @DynamicSelect = 'set transaction isolation level read uncommitted' +

                        ' SELECT distinct (dbo.PendingApprovals.StatusId * 16777216) + ...

                        '   when 29 then isnull(bh.BidHeaderId,0) ' +

                        '   else isnull(case PendingApprovals.StatusId when 2 then Next...

                        ' end StatusId, ' +

                        ' case isnull(PendingApprovals.StatusId,0) ' +

                        '   when 29 then StatusTable.Name + '' on Bid '' + convert(varc...

                        '   else isnull(StatusTable.Name,''On Hold'') + isnull(case Pen...

                        ' end Name, sum(dbo.PendingApprovals.Amount) as StatusTotal' +

                        '  FROM dbo.PendingApprovals with (nolock)' +

                        '  JOIN dbo.StatusTable on dbo.StatusTable.StatusId = dbo.Pendi...

                        '  JOIN SessionTable on SessionTable.SessionId = PendingApprova...

                        '  LEFT OUTER JOIN Users LastApprover on LastApprover.UserId = ...

                        '  LEFT OUTER JOIN Users NextApprover on NextApprover.UserId = ...

                        '  left outer join BidHeaders bh on bh.BidHeaderId = (select to...

                        ' WHERE SessionTable.SessionId = ' + @pSessionId
```

```
--                        '   and dbo.uf_RequisitionIsVisible(' + @pSessionId + ',Pendi...
```

```
... (truncated)
```

sp_PAStatusTest {sp-dbo-sp-pastatustest}

> Stored procedure: PAStatusTest

Property	Value
Schema	dbo
Created	2006-06-26 14:25:39.303000
Modified	2006-06-26 14:25:39.303000
Parameters	7

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	varchar(255)	INPUT	p Session identifier
2	@pCategoryId	varchar(255)	INPUT	p Category identifier
3	@pBudgetId	varchar(255)	INPUT	p Budget identifier
4	@pAccountId	varchar(255)	INPUT	p Account identifier
5	@pSchoolId	varchar(255)	INPUT	p School identifier
6	@pUserId	varchar(255)	INPUT	p User identifier
7	@pStatusId	varchar(255)	INPUT	p Status identifier

Definition

```
--sp_PAStatusTest '618919', '', '3055', '', '', '', ''



CREATE  procedure dbo.sp_PAStatusTest @pSessionId varchar(255), @pCategoryId varchar(25...

declare @DynamicSelect varchar(4096)



--select @DynamicSelect = 'SELECT distinct dbo.PendingApprovals.StatusId, dbo.StatusTab...

select @DynamicSelect = 'SELECT distinct (dbo.PendingApprovals.StatusId * 16777216) + c...

                        '   when 29 then isnull(bh.BidHeaderId,0) ' +

                        '   else isnull(case PendingApprovals.StatusId when 2 then Next...

                        ' end StatusId, ' +

                        ' case isnull(PendingApprovals.StatusId,0) ' +

                        '   when 29 then StatusTable.Name + '' on Bid '' + convert(varc...

                        '   else isnull(StatusTable.Name,''On Hold'') + isnull(case Pen...

                        ' end Name, sum(dbo.PendingApprovals.Amount) as StatusTotal' +

                        '  FROM dbo.PendingApprovals with (nolock)' +

                        '  JOIN dbo.StatusTable on dbo.StatusTable.StatusId = dbo.Pendi...

                        '  JOIN SessionTable on SessionTable.SessionId = PendingApprova...

--                        '                   and (SessionTable.ApprovalLevel <= Pendin...

--                        '                     or SessionTable.ApprovalLevel >= 5)' +

                        '  LEFT OUTER JOIN Users LastApprover on LastApprover.UserId = ...

                        '  LEFT OUTER JOIN Users NextApprover on NextApprover.UserId = ...

                        '  left outer join BidHeaders bh on bh.BidHeaderId = (select to...

                        ' WHERE SessionTable.SessionId = ' + @pSessionId
```

```
--                        '   and dbo.uf_RequisitionIsVisible(' + @pSessionId + ',Pendi...
```

```
... (truncated)
```

sp_PAStatusTest1 {sp-dbo-sp-pastatustest1}

> Stored procedure: PAStatusTest1

Property	Value
Schema	dbo
Created	2008-07-02 10:49:47.623000
Modified	2008-07-02 10:49:47.623000
Parameters	7

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	varchar(255)	INPUT	p Session identifier
2	@pCategoryId	varchar(255)	INPUT	p Category identifier
3	@pBudgetId	varchar(255)	INPUT	p Budget identifier
4	@pAccountId	varchar(255)	INPUT	p Account identifier
5	@pSchoolId	varchar(255)	INPUT	p School identifier
6	@pUserId	varchar(255)	INPUT	p User identifier
7	@pStatusId	varchar(255)	INPUT	p Status identifier

Definition

```
--sp_PAStatus '618919', '', '3055', '', '', '', '33792673'


CREATE procedure dbo.sp_PAStatusTest1 @pSessionId varchar(255), @pCategoryId varchar(25...

declare @DynamicSelect varchar(4096)


set transaction isolation level read uncommitted

--select @DynamicSelect = 'SELECT distinct dbo.PendingApprovals.StatusId, dbo.StatusTab...

select @DynamicSelect = 'set transaction isolation level read uncommitted' +

                        ' SELECT distinct (dbo.PendingApprovals.StatusId * 16777216) + ...

                        '   when 29 then isnull(bh.BidHeaderId,0) ' +

                        '   else isnull(case PendingApprovals.StatusId when 2 then Next...

                        ' end StatusId, ' +

                        ' case isnull(PendingApprovals.StatusId,0) ' +

                        '   when 29 then StatusTable.Name + '' on Bid '' + convert(varc...

                        '   else isnull(StatusTable.Name,''On Hold'') + isnull(case Pen...

                        ' end Name, sum(dbo.PendingApprovals.Amount) as StatusTotal' +

                        '  FROM dbo.PendingApprovals with (nolock)' +

                        '  JOIN dbo.StatusTable on dbo.StatusTable.StatusId = dbo.Pendi...

                        '  JOIN SessionTable on SessionTable.SessionId = PendingApprova...

                        '  LEFT OUTER JOIN Users LastApprover on LastApprover.UserId = ...

                        '  LEFT OUTER JOIN Users NextApprover on NextApprover.UserId = ...

                        '  left outer join BidHeaders bh on bh.BidHeaderId = (select to...

                        ' WHERE SessionTable.SessionId = ' + @pSessionId
```

```
--                        '   and dbo.uf_RequisitionIsVisible(' + @pSessionId + ',Pendi...
```

```
... (truncated)
```

sp_PAUsers {sp-dbo-sp-pausers}

> User management procedure for PAs

Property	Value
Schema	dbo
Created	2003-06-30 12:55:53.623000
Modified	2010-02-01 01:04:41.243000
Parameters	7

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	varchar(255)	INPUT	p Session identifier
2	@pCategoryId	varchar(255)	INPUT	p Category identifier
3	@pBudgetId	varchar(255)	INPUT	p Budget identifier
4	@pAccountId	varchar(255)	INPUT	p Account identifier
5	@pSchoolId	varchar(255)	INPUT	p School identifier
6	@pUserId	varchar(255)	INPUT	p User identifier
7	@pStatusId	varchar(255)	INPUT	p Status identifier

Definition

```
CREATE            PROCEDURE [dbo].[sp_PAUsers] @pSessionId varchar(255), @pCategoryId v...

declare @DynamicSelect varchar(4096)



set transaction isolation level read uncommitted



select @DynamicSelect = 'set transaction isolation level read uncommitted' +

                        ' SELECT dbo.PendingApprovals.UserId, left(dbo.Users.Attention,...

                        '  FROM dbo.PendingApprovals with (nolock)' +

                        '  JOIN dbo.Users on dbo.Users.UserId = dbo.PendingApprovals.Us...

                        '  JOIN SessionTable on SessionTable.SessionId = PendingApprova...

--                        '                   and (SessionTable.ApprovalLevel <= Pendin...

--                        '                     or SessionTable.ApprovalLevel >= 5)' +

                        ' WHERE SessionTable.SessionId = ' + @pSessionId

--                        '   and dbo.uf_RequisitionIsVisible(' + @pSessionId + ',Pendi...



if CONVERT(int,@pCategoryId) <> 0

begin

  select @DynamicSelect = @DynamicSelect + ' AND PendingApprovals.CategoryId = ' + @pCa...

end


if CONVERT(int,@pBudgetId) <> 0

begin

  select @DynamicSelect = @DynamicSelect + ' AND PendingApprovals.BudgetId = ' + @pBudg...
```

```
end

/*

... (truncated)
```

sp_PODetail {sp-dbo-sp-podetail}

> Purchase order procedure for data

Property	Value
Schema	dbo
Created	2010-07-15 21:58:32.837000
Modified	2010-07-15 22:25:11.653000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@POId	int	INPUT	Purchase order identifier

Definition

```
CREATE procedure [dbo].[sp_PODetail] @POId int

as

select * from PODetail with (nolock) where POId = @POId order by SortSeq
```

sp_PODetailLastItemOnly {sp-dbo-sp-podetaillastitemonly}

> Item management procedure for LastOnly

Property	Value
Schema	dbo
Created	2025-05-20 11:07:07.317000
Modified	2025-05-20 11:07:07.317000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@POId	int	INPUT	Purchase order identifier

Definition

```
create procedure [dbo].[sp_PODetailLastItemOnly] @POId int

as

select top 1 * from PODetail with (nolock) where POId = @POId order by SortSeq desc
```

sp_PrepareNextYear {sp-dbo-sp-preparenextyear}

> Stored procedure: PrepareNextYear

Property	Value
Schema	dbo
Created	2003-08-23 01:05:38.700000
Modified	2015-01-28 13:38:11.153000
Parameters	0

Definition

```
CREATE procedure [dbo].[sp_PrepareNextYear] as

declare@StartDate datetime,

@EndDate datetime



-- Build Start Date

if month(getdate()) >= 7

begin

  select @StartDate = convert(datetime,'07/01/' + convert(char(4),year(getdate()) + 1))

end

else

begin

  select @StartDate = convert(datetime,'07/01/' + convert(char(4),year(getdate())))

end



-- Build End Date

select @EndDate = convert(datetime,'06/30/' + convert(char(4),year(@Startdate) + 1) + '...



-- Create New Budgets as Needed

insert Budgets (DistrictId, Active, Name, StartDate, EndDate, VisibleFrom, VisibleUntil...

  select District.DistrictId, 1, convert(char(4),year(@StartDate)) + ' - ' + convert(ch...

    from District

    left outer join Budgets on Budgets.DistrictId = District.DistrictId

                            and Budgets.Name like cast(year(@StartDate) as char(4)) + '%'
```

```
                                and Budgets.Active = 1

--                                and Budgets.StartDate = @StartDate

... (truncated)
```

sp_PrepTMSurvey {sp-dbo-sp-preptmsurvey}

> Stored procedure: PrepTMSurvey

Property	Value
Schema	dbo
Created	2012-11-15 15:03:40.693000
Modified	2013-10-06 23:15:25.487000
Parameters	0

Definition

```
CREATE procedure [dbo].[sp_PrepTMSurvey] as

insert TMVendors (TMYear, VendorId, VendorName, TradeId, CountyId, Sequence)

select YEAR(getdate()), TMAwards.VendorId, Vendors.Name, Trades.TradeId, Counties.Count...

  from TMAwards

  join BidHeaders on BidHeaders.BidHeaderId = TMAwards.BidHeaderId

                 and GETDATE() between BidHeaders.EffectiveFrom and BidHeaders.Effectiv...

  join BidTradeCounties on BidTradeCounties.BidTradeCountyId = TMAwards.BidTradeCountyId

  join BidTrades on BidTrades.BidTradeId = BidTradeCounties.BidTradeId

                and BidTrades.BidHeaderId = TMAwards.BidHeaderId

  join Trades on Trades.TradeId = BidTrades.TradeId

  join Vendors on Vendors.VendorId = TMAwards.VendorId

  join Counties on Counties.CountyId = BidTradeCounties.CountyId

 where TMAwards.VendorId != 7691

   and TMAwards.Active = 1

 order by BidTradeCounties.BidTradeId, CountyId, AwardType
```

sp_ProcessCopyRequests {sp-dbo-sp-processcopyrequests}

> Processing procedure for Requests

Property	Value
Schema	dbo
Created	2004-10-26 19:36:05.830000
Modified	2009-03-25 06:55:28.537000
Parameters	0

Definition

```
CREATE    procedure dbo.sp_ProcessCopyRequests

as

declare @CopyRequestId int,

@RSId int



delete ReportSessionLinks

  from CopyRequests

  join ReportSessionLinks rsl on rsl.RSId = CopyRequests.RSId

 where CopyRequests.StartTime is null

   and CopyRequests.CopyRequestId != (select top 1 cr1.CopyRequestId

                                       from CopyRequests cr1

                                       join ReportSessionLinks rsl1 on rsl1.RSId = cr1...

                                                                  and rsl1.IntId = rs...

                                      where CR1.StartTime is null

                                      order by cr1.CopyRequestId)



declare QCC cursor  read_only for

select CopyRequestId, RSId

  from CopyRequests

 where StartTime is null
```

```
open QCC
```

```
fetch next from QCC into @CopyRequestId, @RSId
```

```
... (truncated)
```

sp_processKill {sp-dbo-sp-processkill}

> Processing procedure for processKill

Property	Value
Schema	dbo
Created	2008-02-21 00:47:38.153000
Modified	2009-03-25 06:55:28.537000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pSpid	int	INPUT	p Spid parameter
3	@pRIP	varchar(32)	INPUT	p RIP parameter

Definition

```
create procedure sp_processKill @pSessionId int, @pSpid int, @pRIP varchar(32) as

declare @Cmd varchar(255),

@AuditMsg varchar(1024),

@ApprovalLevel int



select @Cmd = 'KILL ' + cast(@pSpid as varchar(16)),

       @AuditMsg = 'Process ' + cast(@pSpid as varchar(16)) + ' killed per ' + isnull(C...

       @ApprovalLevel = isnull(Sessiontable.ApprovalLevel,0)

  from SessionTable

  join CSRep on CSRep.CSRepId = SessionTable.CSRepId

 where SessionTable.SessionId = @pSessionId



if isnull(@ApprovalLevel,0) = 9 and isnull(@pSpid,0) > 50

begin

  exec(@Cmd)

  insert DebugMsgs (Msg) values (@AuditMsg)

end

else

if isnull(@pSpid,0) <= 50

begin

  select @AuditMsg = 'Process ' + cast(@pSpid as varchar(16)) + ' was not killed due to...

  insert DebugMsgs (Msg) values (@AuditMsg)

end
```

```
else

begin

... (truncated)
```

sp_processMonitor {sp-dbo-sp-processmonitor}

> Processing procedure for processMonitor

Property	Value
Schema	dbo
Created	2008-02-19 12:25:04.590000
Modified	2012-12-27 17:33:21.380000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pType	char(1)	INPUT	p type

Definition

```
--sp_ProcessMonitor ''

CREATE  procedure [dbo].[sp_processMonitor] @pType char(1) as



select es.session_id spid,

       isnull(er.blocking_session_id,0) Blocked,

       isnull(er.wait_type,'') WaitType,

       isnull(er.wait_time,0) WaitTime,

       isnull(er.wait_resource,'') WaitResource,

       es.cpu_time cpu,

       es.logical_reads physical_io,

       isnull(er.granted_query_memory,0) memusage,

       es.last_request_start_time Last_Batch,

       isnull(er.open_transaction_count,0) open_tran,

       es.[status] [Status],

       ISNULL(er.command,'') Cmd,

       es.host_name hostname,

       0 LockCount,

       '' WaitingLock,

       isnull(est.text,'') LastCmd,

       cast((select COUNT(*) from sys.dm_exec_requests er1 where er1.blocking_session_i...

       cast(case

                 when isnull(cast((select COUNT(*) from sys.dm_exec_requests er1 where ...

                 when isnull(er.blocking_session_id,0) > 0 then 'Blocked'
```

```
                    when substring(es.[status],1,3) = 'run' then 'Active'

                    else 'Idle'

  ... (truncated)
```

sp_processMonitorOrig {sp-dbo-sp-processmonitororig}

> Processing procedure for processMonitorOrig

Property	Value
Schema	dbo
Created	2012-12-27 16:43:35.007000
Modified	2012-12-27 16:43:35.007000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pType	char(1)	INPUT	p type

Definition

```
--sp_ProcessMonitor ''

create  procedure [dbo].[sp_processMonitorOrig] @pType char(1) as



declare @spid int,

@Cmd varchar(1024),

        @EventInfo varchar(255)



set nocount on

set transaction isolation level read uncommitted



select sp.spid, sp.blocked, sp.waittype, sp.waittime, sp.waitresource, sp.cpu, sp.physi...

       (select count(*) from master.dbo.syslockinfo sli where sli.req_spid = sp.spid) L...

       (select top 1 sli.rsc_text from master.dbo.syslockinfo sli where sli.req_spid = ...

       cast('' as varchar(4096)) as LastCmd,

       cast(0 as int) as BlockingCount,

       cast('' as varchar(64)) as State,

       cast('' as varchar(32)) as BGColor,

       cast('' as varchar(32)) as TextColor,

       cast('' as varchar(128)) as SortKey

  into #ProcessTable

  from master.dbo.sysprocesses sp



if isnull(rtrim(@pType),'') <> ''
```

```
begin

  if @pType = 'B'

... (truncated)
```

sp_processStatus {sp-dbo-sp-processstatus}

> Processing procedure for processStatus

Property	Value
Schema	dbo
Created	2008-02-20 12:16:42.263000
Modified	2009-06-15 10:16:41.807000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pSpid	int	INPUT	p Spid parameter

Definition

```
--sp_ProcessStatus 65

CREATE procedure [dbo].[sp_processStatus] @pSpid int

as

declare @spid int,

@Cmd varchar(1024),

        @EventInfo varchar(255),

@pType char(1)



set nocount on

set transaction isolation level read uncommitted



select sp.spid, sp.blocked, sp.waittype, sp.waittime, sp.waitresource, sp.cpu, sp.physi...

       (select count(*) from master.dbo.syslockinfo sli where sli.req_spid = sp.spid) L...

       (select top 1 sli.rsc_text from master.dbo.syslockinfo sli where sli.req_spid = ...

       cast('' as varchar(4096)) as LastCmd,

       cast(0 as int) as BlockingCount,

       cast('' as varchar(64)) as State,

       cast('' as varchar(32)) as BGColor,

       cast('' as varchar(32)) as TextColor,

       cast('' as varchar(128)) as SortKey

  into #ProcessTable

  from master.dbo.sysprocesses sp
```

```
if isnull(rtrim(@pType),'') <> ''

begin

... (truncated)
```

sp_QueueIPs {sp-dbo-sp-queueips}

> Queue management procedure for IPs

Property	Value
Schema	dbo
Created	2012-12-18 13:04:05.547000
Modified	2012-12-18 14:51:36.523000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pXml	varchar(MAX)	INPUT	p Xml parameter

Definition

```
CREATE procedure [dbo].[sp_QueueIPs] @pXml varchar(max)

as

declare @hXml int,

@IPQueueId int



--Prepare XML Document

exec sp_xml_preparedocument @hXml output, @pXML



--Build Queue Header

insert IPQueue (Queue, Email, SingleFile, ToUser)

  select Device, Email, SingleFile, ToUser

    from OPENXML(@hXml, '/InstructionPackets')

    with (Device varchar(50) '@device',

      EMail varchar(255) '@Email',

          SingleFile tinyint '@SingleFile',

          ToUser tinyint '@ToUser')



--Get IPQueueId

select @IPQueueId = SCOPE_IDENTITY()
```

```
--Add Users Requested

insert IPQueueUsers (IPQueueId, UserId)

  select @IPQueueId, UserId
```

```
    from OPENXML(@hXml, '/InstructionPackets/User',1)

    with (UserId int 'text()')

... (truncated)
```

sp_QueueReqs {sp-dbo-sp-queuereqs}

> Queue management procedure for Reqs

Property	Value
Schema	dbo
Created	2015-03-24 15:58:54.337000
Modified	2015-03-24 15:58:54.337000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pRSId	int	INPUT	p RS identifier

Definition

```
create procedure dbo.sp_QueueReqs @pSessionId int, @pRSId int

as

insert CopyRequests (RSId, SessionId)

 values (@pRSId, @pSessionId)



select Category.Name CategoryName, Users.CometId, Requisitions.RequisitionNumber, Requi...

  from ReportSessionLinks rsl

  join Requisitions on Requisitions.RequisitionId = rsl.IntId

  join Category on Category.CategoryId = Requisitions.CategoryId

  join Users on Users.UserId = Requisitions.UserId

 where rsl.RSId = @pRSId

 order by Category.Name, Users.CometId, Requisitions.Attention
```

sp_Reaward_script {sp-dbo-sp-reaward-script}

> Award processing procedure for Reaward_script

Property	Value
Schema	dbo
Created	2005-04-06 12:04:01.433000
Modified	2009-03-25 06:55:28.503000
Parameters	0

Definition

```
create procedure sp_Reaward_script as


declare @BidHeaderId int


declare bhcur cursor read_only fast_forward for

select BidHeaderId

  from BidHeaders

 where BidHeaderId between 1169 and 1190


open bhcur


fetch next from bhcur into @BidHeaderId


while @@fetch_status = 0

begin

  exec sp_AwardBidHeader @BidHeaderId


  exec sp_CreateOrderBook @BidHeaderId, 0


  fetch next from bhcur into @BidHeaderId

end


close bhcur
```

```
deallocate bhcur
```

sp_RefreshAccounts {sp-dbo-sp-refreshaccounts}

> Stored procedure: RefreshAccounts

Property	Value
Schema	dbo
Created	2001-12-12 13:22:13.233000
Modified	2009-03-25 06:55:28.643000
Parameters	0

Definition

```
CREATE procedure sp_RefreshAccounts AS



set transaction isolation level serializable



begin transaction



Update UserAccounts

   set AllocationAvailable = AllocationAmount

 where UseAllocations = 1



update UserAccounts

   set AllocationAvailable = AllocationAvailable - Requisitions.TotalRequisitionCost

  from UserAccounts

  join Requisitions on Requisitions.UserAccountId = UserAccounts.UserAccountId

 where UserAccounts.UseAllocations = 1



Update BudgetAccounts

   set AmountAvailable = BudgetAmount

 where UseAllocations = 1
```

```
Update BudgetAccounts

   set AmountAvailable = AmountAvailable - Requisitions.TotalRequisitionCost

  from BudgetAccounts
```

```
 join Requisitions on Requisitions.BudgetAccountId = BudgetAccounts.BudgetAccountId

where UseAllocations = 1

... (truncated)
```

sp_RefreshDistrictVendors {sp-dbo-sp-refreshdistrictvendors}

> Vendor management procedure for RefreshDistricts

Property	Value
Schema	dbo
Created	2003-06-30 12:55:54.060000
Modified	2014-05-20 12:12:32.403000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pDistrictId	int	INPUT	p District identifier

Definition

```
CREATE      procedure [dbo].[sp_RefreshDistrictVendors] @pDistrictId int as



insert DistrictVendor (Active, DistrictId, VendorId)

  select ss.*

    from (

  select 1 Active, DistrictPP.DistrictId, Vendors.VendorId

from Requisitions

join BidHeaders on BidHeaders.BidHeaderId = Requisitions.BidHeaderId

               and GETDATE() between BidHeaders.EffectiveFrom and BidHeaders.Effectiv...

               and BidHeaders.Active = 1

join Bids on Bids.BidHeaderId = BidHeaders.BidHeaderId

         and Bids.Active = 1

join Budgets on Budgets.BudgetId = Requisitions.BudgetId

--and dateadd(month,8,getdate()) between Budgets.StartDate and Budgets.EndDate

join DistrictPP on DistrictPP.DistrictId = Budgets.DistrictId

               and DistrictPP.PricePlanId = BidHeaders.PricePlanId

--join PricePlans on PricePlans.PricePlanId = DistrictPP.PricePlanId

--join Awards on Awards.PricePlanId = DistrictPP.PricePlanId

join Vendors on Vendors.VendorId = Bids.VendorId

join Category on Category.CategoryId = Requisitions.CategoryId

left outer join PO on PO.RequisitionId = Requisitions.RequisitionId

  and PO.VendorId = Vendors.VendorId

left outer join DistrictVendor on DistrictVendor.DistrictId = DistrictPP.DistrictId
```

```
    and DistrictVendor.VendorId = Vendors.VendorId

    and DistrictVendor.Active = 1

  ... (truncated)
```

sp_RefreshPendingApprovals {sp-dbo-sp-refreshpendingapprovals}

> Approval workflow procedure for RefreshPendings

Property	Value
Schema	dbo
Created	2003-06-30 12:55:55.390000
Modified	2009-03-25 06:55:28.473000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	varchar(255)	INPUT	p Session identifier

Definition

```
CREATE     procedure [dbo].[sp_RefreshPendingApprovals] @pSessionId varchar(255) AS

declare @SessionId int,

@SchoolId int,

@DistrictId int,

@UserId int,

@UserApprovalLevel int,

@DistrictApprovalLevel int,

@ApprovalStatusId int,

@PendingStatusId int,

@OnHoldStatusId int,

@BudgetId int



set transaction isolation level read uncommitted



select  @SessionId = ISNULL(SessionId,0),

@SchoolId = ISNULL(SchoolId,0),

@DistrictId = ISNULL(DistrictId,0),

@UserId = ISNULL(UserId,0),

@BudgetId = isnull(BudgetId,0),

        @UserApprovalLevel = ISNULL(ApprovalLevel,0)

  from SessionTable with (nolock)

 where SessionId = convert(int,@pSessionId)

   and SessionEnd is null
```

```
if @@rowcount = 0

... (truncated)
```

sp_ReindexAll {sp-dbo-sp-reindexall}

> Stored procedure: ReindexAll

Property	Value
Schema	dbo
Created	2003-07-07 02:12:00.717000
Modified	2003-07-07 02:12:00.717000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pDBName	varchar(255)	INPUT	p DB name

Definition

```
CREATE  procedure dbo.sp_ReindexAll @pDBName varchar(255) as


declare @TableName varchar(255),

@IndexName varchar(255),

@Id int,

@DynStr varchar(255)


print 'Beginning to Reindex Database ' + @pDBName


create table #TempTables (

sysidint identity(1,1) not null,

[Name]varchar(255) not null,

[Id]int not null

)


select @DynStr = 'insert #TempTables ([Name], [Id]) select su.Name + ''.['' + so.name +...


exec(@DynStr)


declare TableCursor CURSOR FORWARD_ONLY READ_ONLY FOR

select [Name], [Id] from #TempTables


open TableCursor
```

```
fetch next from TableCursor into @TableName, @Id

... (truncated)
```

sp_renamediagram {sp-dbo-sp-renamediagram}

> Stored procedure: renamediagram

Property	Value
Schema	dbo
Created	2009-03-26 16:18:10.600000
Modified	2009-03-26 16:18:10.600000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@diagramname	sysname	INPUT	diagramname parameter
2	@owner_id	int	INPUT	owner id parameter
3	@new_diagramnam	sysname	INPUT	new diagramname parameter

Definition

```
CREATE PROCEDURE dbo.sp_renamediagram

(

@diagramname sysname,

@owner_idint= null,

@new_diagramnamesysname



)

WITH EXECUTE AS 'dbo'

AS

BEGIN

set nocount on

declare @theId int

declare @IsDbo int



declare @UIDFound int

declare @DiagIdint

declare @DiagIdTargint

declare @u_namesysname

if((@diagramname is null) or (@new_diagramname is null))

begin

RAISERROR ('Invalid value', 16, 1);

return -1

end
```

```
EXECUTE AS CALLER;

... (truncated)
```

sp_ReportReqData {sp-dbo-sp-reportreqdata}

> Purchase order procedure for ReqData

Property	Value
Schema	dbo
Created	2002-01-24 00:55:08.483000
Modified	2009-03-25 06:55:28.677000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pRequisitionId	int	INPUT	p Requisition identifier

Definition

```
CREATE procedure sp_ReportReqData @pRequisitionId int AS



SelectRequisitions.RequisitionId, Requisitions.RequisitionNumber,

Requisitions.Attention, convert(varchar(32),Requisitions.DateEntered,101) as DateEnter...

Requisitions.ShippingCost, Requisitions.TotalItemsCost,

Requisitions.TotalRequisitionCost, Requisitions.Comments,

Detail.ItemCode, Detail.AddendumItem, Detail.Quantity,

Detail.[Description] ItemDescription, Detail.UnitCode,

Detail.BidPrice, Detail.CatalogPrice,

Vendors.VendorId, Vendors.[Name] VendorName,

Detail.VendorItemCode,

District.[Name] DistrictName, District.Address1 DistrictAddress1,

District.Address2 DistrictAddress2, District.Address3 DistrictAddress3,

ISNULL(District.City,'') + ', ' + ISNULL(District.State,'') + '  ' + ISNULL(District.Z...

Budgets.[Name] BudgetName,

isnull(Accounts.Code,'') AccountCode, isnull(Accounts.[Description],'') AccountDescrip...

Category.[Name] CategoryName,

ShipLocations.[Name] ShippingName,

ShipLocations.Address1 ShippingAddress1,

ShipLocations.Address2 ShippingAddress2,
```

```
ShipLocations.Address3 ShippingAddress3,

ISNULL(ShipLocations.City,'') + ', ' + ISNULL(ShipLocations.State,'') + '  ' + ISNULL(...

ShipLocations.Phone ShippingPhone, ShipLocations.Fax ShippingFax,
```

```
case rtrim(isnull(Detail.Alternate,''))

when '' then

... (truncated)
```

sp_ReqAdd {sp-dbo-sp-reqadd}

> Stored procedure: ReqAdd

Property	Value
Schema	dbo
Created	2001-10-18 09:08:34.050000
Modified	2009-03-25 06:55:28.490000
Parameters	7

Parameters

#	Parameter	Type	Direction	Description
1	@pRequisitionId	int	INPUT	p Requisition identifier
2	@pQuantity	int	INPUT	p quantity
3	@ItemId	int	INPUT	Item identifier
4	@DistrictId	int	INPUT	District identifier
5	@BudgetAccountId	int	INPUT	Budget Account identifier
6	@CatalogId	int	INPUT	Catalog identifier
7	@pSessionId	int	INPUT	p Session identifier

Definition

```
CREATE    procedure dbo.sp_ReqAdd @pRequisitionId int, @pQuantity int, @ItemId int, @Di...



declare @DetailId int,

@BidHeaderId int,

@TotalCost money,

@TodaysDate datetime



      select @TodaysDate = getdate()



      select @BidHeaderId = isnull(BidHeaderId,0)

        from Requisitions with (nolock)

       where RequisitionId = @pRequisitionId



      select @DetailId = DetailId

        from detail with (nolock)

       where RequisitionId = @pRequisitionId

 and ItemId = @ItemId



      if @@rowcount > 0

      begin
```

```
update Detail

   set Quantity = Quantity + @pQuantity

 where DetailId = @DetailId
```

```
        end

        else

  ... (truncated)
```

sp_ResetDistrictAccountingYear {sp-dbo-sp-resetdistrictaccountingyear}

> Reset district accounting year

Property	Value
Schema	dbo
Created	2016-11-15 14:49:45.650000
Modified	2016-11-15 14:53:26.043000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@DistrictId	int	INPUT	District identifier
2	@SourceBudgetId	int	INPUT	Source Budget identifier
3	@DestBudgetId	int	INPUT	Dest Budget identifier

Definition

```
CREATE procedure [dbo].[sp_ResetDistrictAccountingYear] @DistrictId int, @SourceBudgetI...

declare@StartDate datetime,

@EndDate datetime



-- Build Start Date

if month(getdate()) >= 7

begin

  select @StartDate = convert(datetime,'07/01/' + convert(char(4),year(getdate()) + 1))

end

else

begin

  select @StartDate = convert(datetime,'07/01/' + convert(char(4),year(getdate())))

end



-- Build End Date

select @EndDate = convert(datetime,'06/30/' + convert(char(4),year(@Startdate) + 1) + '...



delete UserAccounts

  from UserAccounts

  join Budgets on Budgets.BudgetId = UserAccounts.BudgetId

 where Budgets.BudgetId = @DestBudgetId

   and Budgets.DistrictId = @DistrictId
```

```
delete BudgetAccounts

  from BudgetAccounts

... (truncated)
```

sp_retrieveTagset {sp-dbo-sp-retrievetagset}

> Stored procedure: retrieveTagset

Property	Value
Schema	dbo
Created	2012-04-02 17:32:17.107000
Modified	2012-05-18 16:20:23.677000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@tagSet	varchar(MAX)	INPUT	tag Set parameter

Definition

```
CREATE procedure [dbo].[sp_retrieveTagset] @tagSet varchar(max)

as

declare @hDoc int



set nocount on



--insert debugmsgs (Msg) values (@tagSet)



exec sp_xml_preparedocument @hDoc output, @tagSet



select sd.DocType, sd.DocId, sd.DocFolder, sd.DocName, sd.BaseName

  from OPENXML(@hDoc, '/tagset/tag')

  with (Id uniqueidentifier '@Id') x

  join ContentCentral.dbo.vw_ScannedDocumentDataAll sd on sd.DocId = x.Id



exec sp_xml_removedocument @hDoc



--select top 10 * from debugmsgs order by sysid desc
```

sp_retrieveTagsetDMS {sp-dbo-sp-retrievetagsetdms}

> Stored procedure: retrieveTagsetDMS

Property	Value
Schema	dbo

Created	2015-01-05 16:46:30.760000
Modified	2015-01-05 16:46:30.760000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@tagSet	varchar(MAX)	INPUT	tag Set parameter

Definition

```
create procedure [dbo].[sp_retrieveTagsetDMS] @tagSet varchar(max)

as

declare @hDoc int



set nocount on



--insert debugmsgs (Msg) values (@tagSet)



exec sp_xml_preparedocument @hDoc output, @tagSet



select sd.DocumentType, sd.DocId, sd.DocName

  from OPENXML(@hDoc, '/tagset/tag')

  with (Id uniqueidentifier '@Id') x

  join vw_DMSAllDocuments sd on sd.DocId = x.Id



exec sp_xml_removedocument @hDoc



--select top 10 * from debugmsgs order by sysid desc
```

sp_ReturnUserReqs {sp-dbo-sp-returnuserreqs}

> User management procedure for ReturnReqs

Property	Value
Schema	dbo

Created	2001-08-24 14:40:45.267000
Modified	2013-02-22 16:16:21.727000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier

Definition

```
CREATE           PROCEDURE [dbo].[sp_ReturnUserReqs] @pSessionId int AS



declare @HoldId int



set Transaction isolation level read uncommitted



-- Validate Session

UPDATE SessionTable

   SET SessionLast = GetDate()

 WHERE SessionId = @pSessionId

   AND SessionEnd is null



-- Get On Hold Id

select @HoldId = ISNULL(StatusId,0)

  from StatusTable with (nolock)

 where StatusCode = 'H'



-- Mark Uninitialized as On Hold

update Requisitions

   set StatusId = @HoldId
```

```
  from SessionTable

  inner join Requisitions on Requisitions.SchoolId = SessionTable.SchoolId

 where SessionTable.SessionId = @pSessionId
```

```
    and (StatusId = 0 or StatusId is null)


... (truncated)
```

sp_RTK_AddReportItems {sp-dbo-sp-rtk-addreportitems}

> Item management procedure for RTK_Adds

Property	Value
Schema	dbo
Created	2005-03-21 15:18:19.100000
Modified	2009-03-25 06:55:28.490000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pDistrictId	int	INPUT	p District identifier
2	@pYear	int	INPUT	p Year parameter

Definition

```
CREATE procedure sp_RTK_AddReportItems @pDistrictId int, @pYear int

as

set nocount on

insert RTK_ReportItems ([Year], DistrictId, RTK_SitesId, CategoryId, ItemId, Quantity, ...

select Year(Budgets.StartDate), Budgets.DistrictId, RTK_Sites.RTK_SitesId, Requisitions...

  from Items

  join Detail on Detail.ItemId = Items.ItemId

             and isnull(Detail.VendorId,7691) != 7691

  join Requisitions on Requisitions.RequisitionId = Detail.RequisitionId

                   and Requisitions.Requisitionid = (select top 1 Approvals.Requisition...

  join Budgets on Budgets.BudgetId = Requisitions.BudgetId

              and Budgets.StartDate <= convert(datetime,'11/01/' + convert(varchar(16),...

              and Budgets.EndDate >= convert(datetime,'11/01/' + convert(varchar(16),@p...

  join District on District.DistrictId = Budgets.DistrictId

               and District.RTK = 1

               and District.DistrictId = @pDistrictId

  join ShipLocations on ShipLocations.ShippingId = Requisitions.ShippingId

  join RTK_Sites on RTK_Sites.RTK_SitesId = ShipLocations.RTK_SitesId

  left outer join RTK_ReportItems on RTK_ReportItems.ItemId = Detail.ItemId

                                  and RTK_ReportItems.[Year] = Year(Budgets.StartDate)

                                  and RTK_ReportItems.DistrictId = Budgets.DistrictId

                                  and RTK_ReportItems.DetailId = Detail.DetailId

 where Items.RTK = 1
```

```
    and RTK_ReportItems.RTK_ReportItemsId is null



... (truncated)
```

sp_RTK_Build_MSDS_and_MSDSDetail {sp-dbo-sp-rtk-build-msds-and-msdsdetail}

> Detail record procedure for RTKBuildMSDSandMSDS

Property	Value
Schema	dbo
Created	2013-08-13 14:53:24.330000
Modified	2015-11-24 23:37:38.500000
Parameters	0

Definition

```
CREATE procedure [dbo].[sp_RTK_Build_MSDS_and_MSDSDetail] as



declare @vRTK_ItemsId int,

        @vAlternateDesc varchar(60),

        @NewMSDSId int



-- ************ remember to build/rebuild Duplicate_RTK_Items_Temp table FIRST ********...

-- to build Duplicate_RTK_Items_Temp table use

-- sql script:

-- ScriptToCreateDuplicateRTK_ItemsMappingTable.sql

--

-- if rebuilding, then use following script:

-- use sql script:

-- ScriptToClearAndRebuildMSDSandMSDSDetail.sql





-- FIRST: process all non-duplicate RTK_Items

declare cursorRTK cursor fast_forward read_only for

SELECT RTK_ItemsId, Isnull(AlternateDesc,'') AlternateDesc

FROM RTK_Items with (nolock)

Where RTK_ItemsId Not In (Select Dupe_RTK_ItemsId From Duplicate_RTK_Items_Temp)



set nocount on
```

```
set transaction isolation level read uncommitted

... (truncated)
```

sp_RTKExport {sp-dbo-sp-rtkexport}

> Purchase order procedure for RTK

Property	Value
Schema	dbo
Created	2004-03-04 12:57:23.717000
Modified	2009-03-25 06:55:28.270000
Parameters	0

Definition

```
CREATE  procedure dbo.sp_RTKExport as



select 'Q' + case Category.CategoryId when 7 then '5' else '1' end + District.DistrictC...

  from Detail

  join Requisitions on Requisitions.RequisitionId = Detail.RequisitionId

  join Budgets on Budgets.BudgetId = Requisitions.BudgetId

               and Budgets.StartDate <= getdate()

               and Budgets.EndDate >= getdate()

  join District on District.DistrictId = Budgets.DistrictId

                and District.RTK = 1

  join Users on Users.UserId = Requisitions.UserId

  join Category on Category.CategoryId = Requisitions.CategoryId

                and substring(Category.Code,1,1) in ('J','E','7','R','H')

 order by DataRow
```

sp_SaveTags {sp-dbo-sp-savetags}

> Save (insert or update) record in SaveTags

Property	Value
Schema	dbo
Created	2012-03-06 12:43:45.850000
Modified	2012-03-06 18:39:00.540000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@xmlTagList	varchar(MAX)	INPUT	xml Tag list/array

Definition

```
CREATE procedure sp_SaveTags @xmlTagList varchar(max)

as

declare @hDoc int,

@RSId int



SET NOCOUNT ON;



exec sp_xml_preparedocument @hDoc output, @xmlTagList



insert ReportSession (RSData) values ('')



select @RSId = SCOPE_IDENTITY()



insert ReportSessionLinks (RSId, IntId)

  select @RSId, TagId

    from OPENXML(@hDoc, '/tagset/tag')

    with (TagId int '@Id') tagset



exec sp_xml_removedocument @hDoc


select @RSId as RSId
```

sp_SchoolMerge {sp-dbo-sp-schoolmerge}

> Stored procedure: SchoolMerge

Property	Value
Schema	dbo
Created	2016-09-26 11:45:44.717000
Modified	2016-09-26 11:49:48.483000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pSourceSchoolId	int	INPUT	p Source School identifier
2	@pDestSchoolId	int	INPUT	p Dest School identifier

Definition

```
CREATE procedure sp_SchoolMerge @pSourceSchoolId int, @pDestSchoolId int

as

begin

declare @SourceDistrictId int,

@DestDistrictId int,

@StatusMsg varchar(4096)



select @SourceDistrictId = DistrictId

  from School

 where SchoolId = @pSourceSchoolId



select @DestDistrictId = DistrictId

  from School

 where SchoolId = @pDestSchoolId



-- Check for Districts being the same

if isnull(@SourceDistrictId,0) = isnull(@DestDistrictId,0)

begin

-- Move Source Users to Dest School

Update Users

   set SchoolId = @pDestSchoolId

 where Users.DistrictId = @SourceDistrictId

   and Users.SchoolId = @pSourceSchoolId
```

```
    and Users.Active = 1


... (truncated)
```

sp_search {sp-dbo-sp-search}

> Search procedure for search

Property	Value
Schema	dbo
Created	2001-08-24 14:40:45.443000
Modified	2009-03-25 06:55:28.660000
Parameters	5

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	varchar(255)	INPUT	p Session identifier
2	@pRequisitionId	varchar(255)	INPUT	p Requisition identifier
3	@pSearchData	varchar(255)	INPUT	p Search Data parameter
4	@pCatalogId	varchar(255)	INPUT	p Catalog identifier
5	@pOrderBy	varchar(255)	INPUT	p Order By parameter

Definition

```
CREATE                    PROCEDURE sp_search @pSessionId varchar(255), @pRequisitionId...



declare @CatalogId int



select @CatalogId = convert(int,isnull(@pCatalogId,'0'))



UPDATE SessionTable

   SET SessionLast = GetDate()

 WHERE SessionId = CONVERT(int,@pSessionId)

   AND SessionEnd is null

if @@rowcount = 0

begin

  RAISERROR('Invalid Session or Session has Timed Out',16,1)

end



if @pSearchData = ''

begin

  if @CatalogId = 999999 -- All Items

  begin

    if CONVERT(int,@pOrderBy) = 1

    begin

      SELECT top 20 dbo.NewFF.ItemId, dbo.NewFF.ItemCode, dbo.NewFF.Description, dbo.Ne...

        FROM dbo.NewFF
```

```
        JOIN dbo.SessionTable on dbo.SessionTable.DistrictId = dbo.NewFF.DistrictId

        JOIN dbo.Requisitions on dbo.Requisitions.CategoryId = dbo.NewFF.CategoryId

... (truncated)
```

sp_SearchItems {sp-dbo-sp-searchitems}

> Item management procedure for s

Property	Value
Schema	dbo
Created	2001-11-12 21:58:36.220000
Modified	2009-03-25 06:55:28.770000
Parameters	5

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	varchar(255)	INPUT	p Session identifier
2	@pCategoryId	varchar(255)	INPUT	p Category identifier
3	@pSearchData	varchar(255)	INPUT	p Search Data parameter
4	@pCatalogId	varchar(255)	INPUT	p Catalog identifier
5	@pOrderBy	varchar(255)	INPUT	p Order By parameter

Definition

```
CREATE                 PROCEDURE sp_SearchItems @pSessionId varchar(255), @pCategoryId ...



declare @CatalogId int



select @CatalogId = convert(int,isnull(@pCatalogId,'0'))



UPDATE SessionTable

   SET SessionLast = GetDate()

 WHERE SessionId = CONVERT(int,@pSessionId)

   AND SessionEnd is null



if @@rowcount = 0

begin

  RAISERROR('Invalid Session or Session has Timed Out',16,1)

end



if @pSearchData = ''

begin

  if CONVERT(int,@pCatalogId) = 999999 -- All Items

  begin

    if CONVERT(int,@pOrderBy) = 1

    begin

      SELECT dbo.NewFF.ItemId, dbo.NewFF.ItemCode, dbo.NewFF.Description, dbo.NewFF.Cod...
```

```
        FROM dbo.NewFF

        JOIN dbo.SessionTable on dbo.SessionTable.DistrictId = dbo.NewFF.DistrictId

... (truncated)
```

sp_SearchItemsByReqHK {sp-dbo-sp-searchitemsbyreqhk}

> Item management procedure for sByReqHK

Property	Value
Schema	dbo
Created	2015-03-02 22:18:49.587000
Modified	2018-08-07 23:49:16.470000
Parameters	4

Parameters

#	Parameter	Type	Direction	Description
1	@pRequisitionId	int	INPUT	p Requisition identifier
2	@pVendorId	int	INPUT	p Vendor identifier
3	@pHeadingId	bigint	INPUT	p Heading identifier
4	@pFilter	varchar(4096)	INPUT	p Filter parameter

Definition

```
--select * from dbo.uf_SearchItemsByReq(1726368, 0, 0, 'crayons') order by Ranking desc...

--select * from Requisitions where RequisitionId = 1715646



CREATE procedure [dbo].[sp_SearchItemsByReqHK] @pRequisitionId int, @pVendorId int, @pH...

as

declare @ItemTable table (

BidHeaderId int null,

ItemIdint null,

CrossRefIdint null,

CrossRefIdBidint null,

BidPricemoney null,

GrossPricemoney null,

CatalogPricemoney null,

AwardIdint null,

VendorIdint null,

PricePlanIdint null,

CatalogIdint null,

VendorItemCodevarchar(50) null,

Alternate       varchar(1024) null,

BidItemIdint null,

ParentCatalogId int null,

ItemCodevarchar(50) null,

Descriptionvarchar(1024) null,
```

```
UnitIdint null,

UnitCodevarchar(16) null,

... (truncated)
```

sp_SessionTableUpdate {sp-dbo-sp-sessiontableupdate}

> Session management procedure for TableUpdate

Property	Value
Schema	dbo
Created	2004-09-29 09:31:25.103000
Modified	2014-10-07 17:53:26.357000
Parameters	4

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pDistrictId	int	INPUT	p District identifier
3	@pBudgetId	int	INPUT	p Budget identifier
4	@pTabSelected	varchar(32)	INPUT	p Tab Selected parameter

Definition

```
CREATE procedure [dbo].[sp_SessionTableUpdate] @pSessionId int, @pDistrictId int, @pBud...



declare @DistrictId int,

@BudgetId int,

@UserId int

set nocount on



  select @BudgetId = null, @DistrictId = null



  select @UserId = UserId

    from SessionTable

   where SessionTable.SessionId = @pSessionId



  if isnull(@pDistrictId,0) = 0 and isnull(@pBudgetId,0) = 0

  begin

    Update SessionTable

       set DistrictId = null,

           BudgetId = null,

           SchoolId = null,

           TempUserId = null,

           TabSelected = @pTabSelected

      where SessionId = @pSessionId

  end
```

```
    else

    begin

  ... (truncated)
```

sp_SetBudgetYear {sp-dbo-sp-setbudgetyear}

> Set/update budget year

Property	Value
Schema	dbo
Created	2002-01-23 11:54:33.153000
Modified	2014-10-07 17:53:26.180000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier

Definition

```
CREATE procedure [dbo].[sp_SetBudgetYear] @pSessionId int AS



declare @DistrictId int,

@tempBudgetId int,

@CurrentBudget int,

@NextBudget int,

@StartDate varchar(32),

@UserId int



select @DistrictId = DistrictId,

@UserId = UserId

  from SessionTable

 where SessionId = @pSessionId



/*

if month(getdate()) > 10

begin

  select @StartDate = '07/01/' + convert(char(4),year(getdate()) + 1)

end

else

begin

  select @StartDate = '07/01/' + convert(char(4),year(getdate()))

end
```

```
*/


... (truncated)
```

sp_SetDistrictAndBudgetYear {sp-dbo-sp-setdistrictandbudgetyear}

> Set/update district and budget year

Property	Value
Schema	dbo
Created	2004-11-30 17:13:19.460000
Modified	2014-10-07 17:53:26.013000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pDistrictId	int	INPUT	p District identifier
3	@pBudgetId	int	INPUT	p Budget identifier

Definition

```
CREATE procedure [dbo].[sp_SetDistrictAndBudgetYear] @pSessionId int, @pDistrictId int,...



declare @DistrictId int,

@tempBudgetId int,

@CurrentBudget int,

@NextBudget int,

@StartDate varchar(32),

@AllowIncidentals tinyint,

@VerifyDistrictId int,

@UserId int



select @AllowIncidentals = isnull(AllowIncidentals,0),

   @UserId = SessionTable.UserId

  from SessionTable

 where SessionId = @pSessionId



if isnull(@pDistrictId,0) = 0

begin

  select @DistrictId = DistrictId

    from SessionTable

   where SessionId = @pSessionId

end

else
```

```
begin

  select @DistrictId = @pDistrictId

... (truncated)
```

sp_ShowAllDefrag {sp-dbo-sp-showalldefrag}

> Stored procedure: ShowAllDefrag

Property	Value
Schema	dbo
Created	2001-11-28 11:07:51.240000
Modified	2001-11-28 11:07:51.240000
Parameters	0

Definition

```
CREATE  procedure sp_ShowAllDefrag as


declare @TableName varchar(255)


declare TableCursor CURSOR FORWARD_ONLY READ_ONLY FOR

select name from sysobjects where xtype = 'U'


open TableCursor


fetch next from TableCursor into @TableName


while @@fetch_status = 0

begin

  DBCC SHOWCONTIG (@TableName) WITH ALL_INDEXES, ALL_LEVELS


  fetch next from TableCursor into @TableName

end


close TableCursor

deallocate TableCursor
```

sp_ShowDistribution {sp-dbo-sp-showdistribution}

> Stored procedure: ShowDistribution

Property	Value
Schema	dbo
Created	2002-06-11 12:44:17.513000
Modified	2009-03-25 06:55:28.317000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pRSId	int	INPUT	p RS identifier

Definition

```
CREATE  procedure sp_ShowDistribution @pRSId int AS



/* Allocate Items to Vendor(s)

   Sort Items by Quantity in Descending Order

   Deduct Items from those available by cost in Ascending Order */

declare @QuantityNeeded int,

@QuantityAvailable int,

@QuantityUsed int,

@ReqId int,

@DetailId int,

@BidItemId int,

@ItemId int,

@ItemCode varchar(16)



CREATE TABLE #PODetailItems (

[PODetailItemId] [int] IDENTITY (1, 1) NOT NULL ,

[POId] [int] NULL ,

[DetailId] [int] NULL ,

[ItemId] [int] NULL ,

[Quantity] [int] NULL ,
```

```
[BidItemId] [int] NULL ,

[BidPrice] [money] NULL ,

[GrossPrice] [money] NULL ,
```

```
[DiscountRate] [decimal](9, 5) NULL ,

[AwardId] [int] NULL ,

... (truncated)
```

sp_ShowTextbookSavings {sp-dbo-sp-showtextbooksavings}

> Stored procedure: ShowTextbookSavings

Property	Value
Schema	dbo
Created	2002-06-11 13:45:33.310000
Modified	2009-03-25 06:55:28.317000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pRSId	int	INPUT	p RS identifier

Definition

```
CREATE procedure sp_ShowTextbookSavings @pRSId int AS



/* Allocate Items to Vendor(s)

   Sort Items by Quantity in Descending Order

   Deduct Items from those available by cost in Ascending Order */

declare @QuantityNeeded int,

@QuantityAvailable int,

@QuantityUsed int,

@ReqId int,

@DetailId int,

@BidItemId int,

@ItemId int,

@ItemCode varchar(16),

@VendorCode char(4),

@VendorName varchar(50)



CREATE TABLE #PODetailItems (

[PODetailItemId] [int] IDENTITY (1, 1) NOT NULL ,

[POId] [int] NULL ,

[DetailId] [int] NULL ,

[ItemId] [int] NULL ,

[Quantity] [int] NULL ,

[BidItemId] [int] NULL ,
```

```
[BidPrice] [money] NULL ,

[GrossPrice] [money] NULL ,

... (truncated)
```

sp_SmallPOCheck {sp-dbo-sp-smallpocheck}

> Purchase order procedure for Small

Property	Value
Schema	dbo
Created	2015-03-19 16:25:51.410000
Modified	2015-03-23 13:11:00.510000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@SessionId	int	INPUT	Session identifier
2	@RSId	int	INPUT	RS identifier

Definition

```
CREATE procedure [dbo].[sp_SmallPOCheck] @SessionId int, @RSId int

as

select ar.RequisitionNumber,ar.StatusDesc Status,ar.CategoryName,ar.SchoolName,ar.Accou...

  from ReportSessionLinks rsl

  join vw_ApproveRequisitionsBySession ar on ar.RequisitionId = rsl.IntId

                                          and ar.SessionId = @SessionId

                                          and ar.LowPOCount != 0

 where rsl.RSId = @RSId
```

sp_SubmitRequisition {sp-dbo-sp-submitrequisition}

> Requisition procedure for Submit

Property	Value
Schema	dbo
Created	2001-08-24 14:40:45.503000
Modified	2019-11-13 07:27:40.527000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	varchar(255)	INPUT	p Session identifier
2	@pRequisitionId	varchar(255)	INPUT	p Requisition identifier

Definition

```
CREATE procedure [dbo].[sp_SubmitRequisition] @pSessionId varchar(255),@pRequisitionId ...



declare @SessionId int,

@CXmlSessionId int,

@RequisitionId int,

@ApprovalLevel tinyint,

@UserId int,

@StatusId int,

@NotBidCount int,

@ApproverId int,

@Balance money



-- Convert Passed Data

select @SessionId = convert(int,@pSessionId),

       @RequisitionId = convert(int,@pRequisitionId)



exec sp_DeleteZeros 0, @pRequisitionId



-- Get User

select @UserId = ISNULL(Users.UserId,0),

       @ApproverId = isnull(Users.ApproverId,0),

       @CXmlSessionId = isnull(CXmlSession.SessionId,0)

  from SessionTable with (nolock)
```

```
    left outer join CXmlSession on CXmlSession.SessionId = SessionTable.SessionId

  --  join Users on Users.UserId = SessionTable.UserId

  ... (truncated)
```

sp_SubmitRequisitionNew {sp-dbo-sp-submitrequisitionnew}

> Requisition procedure for SubmitNew

Property	Value
Schema	dbo
Created	2004-12-30 12:37:11.473000
Modified	2009-03-25 06:55:28.270000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pRequisitionId	int	INPUT	p Requisition identifier
3	@rStatus	int	INPUT	r status

Definition

```
CREATE procedure sp_SubmitRequisitionNew @pSessionId int,@pRequisitionId int, @rStatus ...



declare @SessionId int,

@RequisitionId int,

@ApprovalLevel tinyint,

@UserId int,

@StatusId int,

@NotBidCount int,

@ApproverId int,

@ReturnValue int,

@AmountAvailable money



-- Convert Passed Data

select @SessionId = @pSessionId,

       @RequisitionId = @pRequisitionId,

       @ReturnValue = 0



-- Get User

select @UserId = ISNULL(Users.UserId,0),

       @ApproverId = isnull(Users.ApproverId,0)
```

```
  from SessionTable with (nolock)

--  join Users on Users.UserId = SessionTable.UserId

  join Users on Users.UserId = case isnull(SessionTable.RepUserId,0) when 0 then Sessio...
```

```
    where SessionId = @SessionId


  ... (truncated)
```

sp_UAAccounts {sp-dbo-sp-uaaccounts}

> Stored procedure: UAAccounts

Property	Value
Schema	dbo
Created	2001-08-24 14:40:45.533000
Modified	2009-03-25 06:55:28.677000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	varchar(255)	INPUT	p Session identifier

Definition

```
CREATE  procedure sp_UAAccounts @pSessionId varchar(255) AS



declare @SessionId int,

@ApprovalLevel int,

@PriorUsers varchar(4096)



select @SessionId = convert(int,@pSessionId)



select @ApprovalLevel = ISNULL(Users.ApprovalLevel,0)

  from SessionTable

  join Users on Users.UserId = SessionTable.UserId

 where SessionTable.SessionId = @SessionId



if @ApprovalLevel > 0

begin

  SELECT distinct Accounts.AccountId, Accounts.Code

    FROM dbo.UserAccounts

    JOIN Users on Users.UserId = UserAccounts.UserId

    JOIN School on School.SchoolId = Users.SchoolId

    JOIN dbo.Accounts on Accounts.AccountId = UserAccounts.AccountId

    JOIN SessionTable on SessionTable.BudgetId = UserAccounts.BudgetId

     and dbo.uf_UserInApprovalChain(SessionTable.UserId, Users.UserId, @PriorUsers) = 1

   WHERE SessionTable.SessionId = convert(int,@pSessionId)
```

```
    GROUP BY Accounts.AccountId, Accounts.Code

    ORDER BY Accounts.Code

... (truncated)
```

sp_UAList {sp-dbo-sp-ualist}

> List procedure for UA

Property	Value
Schema	dbo
Created	2001-08-24 14:40:45.553000
Modified	2009-03-25 06:55:28.677000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	varchar(255)	INPUT	p Session identifier
2	@pUserId	varchar(255)	INPUT	p User identifier
3	@pAccountId	varchar(255)	INPUT	p Account identifier

Definition

```
CREATE   procedure sp_UAList @pSessionId varchar(255), @pUserId varchar(255), @pAccount...



declare @SessionId int,

@ApprovalLevel int,

@DynamicSelect varchar(4096)



select  @SessionId = convert(int,@pSessionId)



select @ApprovalLevel = ISNULL(Users.ApprovalLevel,0)

  from SessionTable

  join Users on Users.UserId = SessionTable.UserId

 where SessionTable.SessionId = @SessionId



select @DynamicSelect = 'declare @PriorUsers varchar(4096)  SELECT distinct Users.UserI...

         max(ISNULL(UserAccounts.AllocationAmount,0)) as AllocationAmount,

         max(ISNULL(UserAccounts.AllocationAvailable,0)) as AllocationAvailable,

         Accounts.Code as AccountCode

    FROM dbo.UserAccounts

    JOIN Users on Users.UserId = UserAccounts.UserId

    JOIN School on School.SchoolId = Users.SchoolId

    JOIN dbo.Accounts on Accounts.AccountId = UserAccounts.AccountId

    JOIN SessionTable on SessionTable.BudgetId = UserAccounts.BudgetId

     and dbo.uf_UserInApprovalChain(SessionTable.UserId, Users.UserId, @PriorUsers) = 1
```

```
    WHERE SessionTable.SessionId = ' + @pSessionId


... (truncated)
```

sp_UAListTotals {sp-dbo-sp-ualisttotals}

> List procedure for UAs

Property	Value
Schema	dbo
Created	2001-08-24 14:40:45.563000
Modified	2009-03-25 06:55:28.677000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	varchar(255)	INPUT	p Session identifier
2	@pUserId	varchar(255)	INPUT	p User identifier
3	@pAccountId	varchar(255)	INPUT	p Account identifier

Definition

```
CREATE     procedure sp_UAListTotals @pSessionId varchar(255), @pUserId varchar(255), @...



declare @SessionId int,

@ApprovalLevel int,

@DynamicSelect varchar(4096)



select  @SessionId = convert(int,@pSessionId)



select @ApprovalLevel = ISNULL(Users.ApprovalLevel,0)

  from SessionTable

  join Users on Users.UserId = SessionTable.UserId

 where SessionTable.SessionId = @SessionId



select @DynamicSelect = 'declare @PriorUsers varchar(4096)  SELECT ISNULL(sum(UserAccou...

         ISNULL(sum(UserAccounts.AllocationAvailable),0) as AllocationAvailable,

         ISNULL(sum(Requisitions.TotalRequisitionCost),0) as AllocationsUsed

    FROM dbo.UserAccounts

    JOIN Users on Users.UserId = UserAccounts.UserId

    JOIN School on School.SchoolId = Users.SchoolId

    JOIN dbo.Accounts on Accounts.AccountId = UserAccounts.AccountId

    JOIN SessionTable on SessionTable.BudgetId = UserAccounts.BudgetId

                     and dbo.uf_UserInApprovalChain(SessionTable.UserId, Users.UserId, ...

    FULL JOIN Requisitions on Requisitions.UserAccountId = UserAccounts.UserAccountId
```

```
    WHERE SessionTable.SessionId = ' + @pSessionId


... (truncated)
```

sp_UAUsers {sp-dbo-sp-uausers}

> User management procedure for UAs

Property	Value
Schema	dbo
Created	2001-08-24 14:40:45.593000
Modified	2009-03-25 06:55:28.690000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	varchar(255)	INPUT	p Session identifier

Definition

```
CREATE procedure sp_UAUsers @pSessionId varchar(255) AS



declare @SessionId int,

@ApprovalLevel int



select @SessionId = convert(int,@pSessionId)



select @ApprovalLevel = ISNULL(Users.ApprovalLevel,0)

  from SessionTable

  join Users on Users.UserId = SessionTable.UserId

 where SessionTable.SessionId = @SessionId



if @ApprovalLevel > 0

begin

  SELECT distinct Users.UserId, Users.Attention

    FROM dbo.UserAccounts

    JOIN Users on Users.UserId = UserAccounts.UserId

    JOIN School on School.SchoolId = Users.SchoolId

    JOIN dbo.Accounts on Accounts.AccountId = UserAccounts.AccountId

    JOIN SessionTable on SessionTable.BudgetId = UserAccounts.BudgetId

     AND                 SessionTable.SchoolId = School.SchoolId

   WHERE SessionTable.SessionId = convert(int,@pSessionId)

   GROUP BY Users.UserId, Users.Attention
```

```
    ORDER BY Users.Attention

end

... (truncated)
```

sp_UnawardBidHeader {sp-dbo-sp-unawardbidheader}

> Award processing procedure for Unaward

Property	Value
Schema	dbo
Created	2004-02-24 00:24:39.967000
Modified	2009-03-25 06:55:28.240000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pBidHeaderId	int	INPUT	p Bid Header identifier

Definition

```
CREATE   Procedure dbo.sp_UnawardBidHeader @pBidHeaderId int as



/*      select BidItems.AwardId, Bids.BidHeaderId, Bids.BidId

        into #DeleteItems

        from BidItems

        join Bids on Bids.BidId = BidItems.BidId

       where Bids.BidHeaderId = @pBidHeaderId

       group by BidItems.AwardId, Bids.BidHeaderId, Bids.BidId



      insert #DeleteItems (AwardId, BidHeaderId, BidId)

        select Awards.AwardId, Bids.BidHeaderId, Bids.BidId

          from BidHeaders

          join Bids on Bids.BidHeaderId = BidHeaders.BidHeaderId

          join #DeleteItems dih on dih.BidHeaderId = BidHeaders.BidHeaderId

          left outer join Awards on Awards.BidId = Bids.BidId

          left outer join #DeleteItems di on di.BidId = Bids.BidId

         where di.BidId is null

         group by Awards.AwardId, Bids.BidHeaderId, Bids.BidId



      Update Detail

         set BidItemId = null,

             BidPrice = Items.ListPrice,

             GrossPrice = Items.ListPrice,
```

```
                DiscountRate = 0,

                AwardId = null,

  ... (truncated)
```

sp_UnpostCatalog {sp-dbo-sp-unpostcatalog}

> Catalog management procedure for Unpost

Property	Value
Schema	dbo
Created	2012-01-03 22:11:08.063000
Modified	2025-04-09 15:57:20.873000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@CatalogId	int	INPUT	Catalog identifier

Definition

```
CREATE procedure [dbo].[sp_UnpostCatalog] @CatalogId int

as

--Delete CrossRefs

Delete CrossRefs

  from CrossRefs with (rowlock, updlock)

--  join Catalogs.dbo.[Master Catalog] mc on mc.CrossRefId = CrossRefs.CrossRefId

 where CrossRefs.CatalogId = @CatalogId

   and not exists (select DetailId

                     from Detail with (nolock)

                    where Detail.ItemId = CrossRefs.ItemId)

   and not exists (select BidItems.BidItemId

                     from BidItems with (nolock)

                    where BidItems.ItemId = CrossRefs.ItemId

                      and BidItems.CrossRefId = CrossRefs.CrossRefId)



--Check for item having no other references and no ordering info

Delete CrossRefs

  from Catalogs.dbo.[Master Catalog] mc with (rowlock, updlock)

  join Items on Items.ItemId = mc.ItemId

  join CrossRefs on CrossRefs.ItemId = Items.ItemId

 where mc.CatalogId = @CatalogId

   and not exists (select CrossRefId

                     from CrossRefs xr with (nolock)
```

```
                    join Catalog cat on Cat.CatalogId = xr.CatalogId

                                and Cat.Name != 'EDS'

... (truncated)
```

sp_UpdateAllListPrices {sp-dbo-sp-updatealllistprices}

> Update existing record in UpdateAlls

Property	Value
Schema	dbo
Created	2012-10-12 13:06:31.580000
Modified	2012-10-12 13:06:31.580000
Parameters	0

Definition

```
create procedure dbo.sp_UpdateAllListPrices as

set transaction isolation level read uncommitted

declare @CategoryId int, @CategoryName varchar(50)

declare CatCur cursor for

select category.CategoryId, Category.Name

  from BidHeaders

  join Category on Category.CategoryId = BidHeaders.CategoryId

               and Category.Type = 1

 where getdate() between BidHeaders.EffectiveFrom and BidHeaders.EffectiveUntil

   and BidHeaders.BidType in (1,2)

   and BidHeaders.Active = 1

 group by category.CategoryId, Category.Name



open CatCur



fetch Next From catCur into @CategoryId, @CategoryName



while @@FETCH_STATUS = 0

begin

  print 'Updating ' + @CategoryName


  exec sp_UpdateListPrices @CategoryId
```

```
    fetch Next From catCur into @CategoryId, @CategoryName

  end

  ... (truncated)
```

sp_UpdateAllReqs {sp-dbo-sp-updateallreqs}

> Update existing record in UpdateAllReqs

Property	Value
Schema	dbo
Created	2002-02-25 16:53:50.763000
Modified	2009-03-25 06:55:28.270000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pDistrictId	int	INPUT	p District identifier

Definition

```
create procedure sp_UpdateAllReqs @pDistrictId int as



declare @ReqId int



declare reqcur cursor fast_forward for

select RequisitionId

  from requisitions

  join school on school.schoolid = requisitions.schoolid

  join district on district.districtid = school.districtid

 where district.DistrictId = @pDistrictId



open reqcur



fetch next from reqcur into @ReqId

while @@fetch_status = 0

begin

exec sp_UpdateReq @ReqId,0,1

fetch next from reqcur into @ReqId

end


close reqcur

deallocate reqcur
```

sp_UpdateCatalogText {sp-dbo-sp-updatecatalogtext}

> Update existing record in UpdateText

Property	Value
Schema	dbo
Created	2012-02-21 00:22:39.133000
Modified	2012-08-02 18:49:56.190000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@pCatalogId	int	INPUT	p Catalog identifier
2	@pPageNbr	int	INPUT	p Page Nbr parameter
3	@pXML	varchar(MAX)	INPUT	p XML data

Definition

```
CREATE procedure [dbo].[sp_UpdateCatalogText] @pCatalogId int, @pPageNbr int, @pXML var...

as

declare @CatalogTextId int,

@hDoc int



select @CatalogTextId = CatalogTextId

  from CatalogText with (nolock)

 where CatalogId = @pCatalogId

   and PageNbr = @pPageNbr



if @@ROWCOUNT = 0

begin

  insert CatalogText (CatalogId, PageNbr, BaseFileName, TextData)

    values (@pCatalogId, @pPageNbr, 'Page', @pXML)

  select @CatalogTextId = SCOPE_IDENTITY()

end

else

begin

  update CatalogText

     set TextData = @pXML

   where CatalogTextId = @CatalogTextId

end
```

```
delete CatalogTextParts

 where CatalogTextId = @CatalogTextId

... (truncated)
```

sp_UpdateCatalogTextPart {sp-dbo-sp-updatecatalogtextpart}

> Update existing record in UpdateTextPart

Property	Value
Schema	dbo
Created	2012-07-31 22:48:04.270000
Modified	2012-08-01 22:43:06.207000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pCatalogTextId	int	INPUT	p Catalog Text identifier
2	@pPartText	varchar(MAX)	INPUT	p Part text

Definition

```
CREATE procedure [dbo].[sp_UpdateCatalogTextPart] @pCatalogTextId int, @pPartText varch...

as



  insert CatalogTextParts (CatalogTextId, TextPart)

    values (@pCatalogTextId, @pPartText)
```

sp_UpdateDetails {sp-dbo-sp-updatedetails}

> Update existing record in Updates

Property	Value
Schema	dbo
Created	2001-08-24 14:40:45.623000
Modified	2009-03-25 06:55:28.707000
Parameters	5

Parameters

#	Parameter	Type	Direction	Description
1	@pRequisitionId	varchar(255)	INPUT	p Requisition identifier
2	@pItemId	varchar(255)	INPUT	p Item identifier
3	@pDetailId	varchar(255)	INPUT	p Detail identifier
4	@pQuantity	varchar(255)	INPUT	p quantity
5	@pSessionId	varchar(255)	INPUT	p Session identifier

Definition

```
CREATE  PROCEDURE sp_UpdateDetails @pRequisitionId varchar(255), @pItemId varchar(255),...



declare @NextDetailId int,

@DistrictId int,

@ItemId int,

@UserId int,

@OrigQuantity int,

@OrigBidPrice money,

@OrigBidItemId int,

@OrigVendorId int,

@TodaysDate datetime,

@BidHeaderId int,

@ApprovalId int



select @ItemId = convert(int,@pItemId),

       @TodaysDate = getdate()



select @DistrictId = DistrictId,

       @UserId = case isnull(SessionTable.CSRepId,0) when 0 then SessionTable.UserId el...

  from SessionTable with (nolock)

  left outer join CSRep on CSRep.CSRepId = SessionTable.CSRepId

 where SessionId = CONVERT(int,@pSessionId)
```

```
if @@rowcount < 1

begin

... (truncated)
```

sp_UpdateHeading {sp-dbo-sp-updateheading}

> Update existing record in UpdateHeading

Property	Value
Schema	dbo
Created	2001-12-07 15:52:21.040000
Modified	2015-11-24 23:37:41.660000
Parameters	6

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pHeadingId	int	INPUT	p Heading identifier
3	@pActive	tinyint	INPUT	p Active parameter
4	@pCode	varchar(255)	INPUT	p code
5	@pDescription	varchar(255)	INPUT	p description
6	@rHeadingId	int	OUTPUT	r Heading identifier

Definition

```
CREATE procedure [dbo].[sp_UpdateHeading] @pSessionId int, @pHeadingId int, @pActive ti...



declare @HeadingId int



select @HeadingId = @pHeadingId



if @pHeadingId = 0

begin

  -- Insert New Item

  insert Headings (Active, Code, [Description])

    values (1, @pCode, @pDescription)



  select @HeadingId = Scope_Identity() --DCH 11/24/2015 @@IDENTITY

end

else

begin

  -- Update Existing Item

  Update Headings

     set Active = @pActive,

         Code = @pCode,

         [Description] = @pDescription

   where HeadingId = @HeadingId

end
```

```
select @rHeadingId = @HeadingId
```

sp_UpdateISBN {sp-dbo-sp-updateisbn}

> Update existing record in UpdateISBN

Property	Value
Schema	dbo
Created	2004-03-18 23:02:49.633000
Modified	2015-11-24 23:37:28.707000
Parameters	9

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pDetailId	int	INPUT	p Detail identifier
3	@pTitle	varchar(255)	INPUT	p Title parameter
4	@pCopyrightYear	int	INPUT	p Copyright Year parameter
5	@pEditionId	int	INPUT	p Edition identifier
6	@pPublisherId	int	INPUT	p Publisher identifier
7	@pPublisherCost	varchar(255)	INPUT	p Publisher Cost parameter
8	@pRequisitionId	int	INPUT	p Requisition identifier
9	@rItemId	int	OUTPUT	r Item identifier

Definition

```
CREATE procedure [dbo].[sp_UpdateISBN] @pSessionId int, @pDetailId int, @pTitle varchar...



declare @ItemId int,

@CategoryId int,

@UnitId int,

@CrossRefId int,

@Active tinyint,

@PublisherCost money



if @pDetailId = 0

begin

  return

end



select @CategoryId = Category.CategoryId

  from Category

  join Items on Items.CategoryId = Category.CategoryId

  join Detail on Detail.ItemId = Items.ItemId

             and Detail.DetailId = @pDetailId

 where Category.Type = 2



select @UnitId = UnitId

  from Units
```

```
 where Code = 'BOOK'

   and Active = 1

... (truncated)
```

sp_UpdateListPrices {sp-dbo-sp-updatelistprices}

> Update existing record in Updates

Property	Value
Schema	dbo
Created	2009-09-16 16:26:16.577000
Modified	2012-10-11 11:22:32.313000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pCategoryId	int	INPUT	p Category identifier

Definition

```
CREATE procedure [dbo].[sp_UpdateListPrices] @pCategoryId int

as

declare @IncreasePct float



select @IncreasePct = .1



Update CrossRefs

   set GrossPrice = case isnull(xr1.DoNotDiscount,0) when 0 then round(xr1.GrossPrice -...

       CatalogPrice = xr1.CatalogPrice + round(xr1.CatalogPrice * @IncreasePct,2),

       DateUpdated = GETDATE()

  from CrossRefs

  join CrossRefs xr1 on xr1.CrossRefId =

    (select Top 1 CrossRefId

       from CrossRefs xr2 with (nolock)

       join BidsCatalogList bcl on bcl.CatalogId = xr2.CatalogId

       join Bids b on b.BidId = bcl.BidId

                  and b.Active = 1

                  and isnull(b.VendorId,0) not IN (0, 7691)

       join BidHeaders bh on bh.BidHeaderId = b.BidHeaderId

                         and bh.EffectiveFrom between DATEADD(year,-1,getdate()) and GE...

                         and bh.EffectiveUntil between DATEADD(month,-6,getdate()) and ...

                         and bh.Active = 1

        where xr2.ItemId = CrossRefs.ItemId
```

```
          and xr2.GrossPrice not between 9999 and 9999.99

        order by case isnull(xr2.DoNotDiscount,0) when 0 then xr2.GrossPrice - round(xr2....

  ... (truncated)
```

sp_UpdateMSRPItem {sp-dbo-sp-updatemsrpitem}

> Update existing record in UpdateMSRP

Property	Value
Schema	dbo
Created	2013-05-30 13:32:56.317000
Modified	2014-10-07 17:53:20.393000
Parameters	14

Parameters

#	Parameter	Type	Direction	Description
1	@pDescription	varchar(1024)	INPUT	p description
2	@pUnitId	int	INPUT	p Unit identifier
3	@pManufacturerId	int	INPUT	p Manufacturer identifier
4	@pManufacturerNu	varchar(50)	INPUT	p Manufacturer number
5	@pVendorId	int	INPUT	p Vendor identifier
6	@pVendorPartNuml	varchar(50)	INPUT	p Vendor Part number
7	@pItemsPerUnit	varchar(50)	INPUT	p Items Per Unit parameter
8	@pListPrice	money	INPUT	p List price
9	@pRequisitionId	int	INPUT	p Requisition identifier
10	@pQuantity	int	INPUT	p quantity
11	@pDetailId	int	INPUT	p Detail identifier
12	@sessionID	int	INPUT	session identifier
13	@pBidderToSupply\	tinyint	INPUT	p Bidder To Supply Vendor Part Nbr
14	@pExtraDescriptior	varchar(1024)	INPUT	p Extra description

Definition

```
CREATE procedure [dbo].[sp_UpdateMSRPItem] @pDescription varchar(1024),

                                        @pUnitId int, @pManufacturerId int, @pManufacture...

                                        @pVendorPartNumber varchar(50), @pItemsPerUnit va...

                                        @pRequisitionId int, @pQuantity int, @pDetailId i...

, @pExtraDescription varchar(1024)

as

declare @ItemId int,

@BidItemId int,

@UnitCode varchar(16),

@PricePlanId int



  -- Get Detail Record Info

  select @ItemId = ItemId,

         @BidItemId = BidItemId

    from Detail with (nolock)

   where DetailId = @pDetailId



  -- Get Unit Code Description

  select @UnitCode = Code

    from Units with (nolock)

   where UnitId = @pUnitId
```

```
    if @@rowcount = 0

    begin

      select @UnitCode = ''

  ... (truncated)
```

sp_UpdateNextNumber {sp-dbo-sp-updatenextnumber}

> Update existing record in UpdateNextNumber

Property	Value
Schema	dbo
Created	2002-04-04 15:19:08.873000
Modified	2009-03-25 06:55:28.537000
Parameters	11

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pNextNumberId	int	INPUT	p Next Number identifier
3	@pIdType	varchar(255)	INPUT	p Id type
4	@pDistrictId	int	INPUT	p District identifier
5	@pSchoolId	int	INPUT	p School identifier
6	@pBudgetId	int	INPUT	p Budget identifier
7	@pPrefix	varchar(255)	INPUT	p Prefix parameter
8	@pSuffix	varchar(255)	INPUT	p Suffix parameter
9	@pNextNumber	int	INPUT	p Next number
10	@pSuppressLZ	tinyint	INPUT	p Suppress LZ parameter
11	@pNumberLength	tinyint	INPUT	p Number Length parameter

Definition

```
create procedure sp_UpdateNextNumber @pSessionId int, @pNextNumberId int, @pIdType varc...



if @pNextNumberId = 0

begin

  insert NextNumber (DistrictId, BudgetId, IdType, Prefix, Suffix, NextNumber, Suppress...

    values (@pDistrictId, @pBudgetId, @pIDType, @pPrefix, @pSuffix, @pNextNumber, @pSup...

end

else

begin

  Update NextNumber

     set Prefix = @pPrefix,

 Suffix = @pSuffix,

 NextNumber = @pNextNumber,

 SuppressLZ = @pSuppressLZ,

 NumberLength = @pNumberLength

   where NextNumberId = @pNextNumberId

end
```

sp_UpdatePOAmounts {sp-dbo-sp-updatepoamounts}

> Update existing record in UpdateAmounts

Property	Value
Schema	dbo
Created	2002-06-12 15:19:45.450000

Modified	2025-06-26 11:54:37.423000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pPOId	int	INPUT	p PO identifier

Definition

```
CREATE        procedure [dbo].[sp_UpdatePOAmounts] @pPOId int AS



declare@VendorId int,

@TotalItems int,

@tempItemCount int,

@TotalBidCost money,

@TotalGrossCost money,

@TotalItemsCost money,

@tempTotalGrossCost money,

@TotalCalcAmount money,

@TotalDiscountAmount money,

@DiscountRate decimal(9,5)



  -- Initialize Variables

  select @TotalGrossCost = 0,

         @TotalItems = 0,

 @TotalCalcAmount = 0,

 @TotalDiscountAmount = 0



  -- Get Amount of PO

  select @TotalBidCost = sum(isnull(PODetailItems.Quantity,0) * round(isnull(PODetailIt...

         @tempItemCount = count(PODetailItems.DetailId)

    from PODetailItems
```

```
    join Detail on Detail.DetailId = PODetailItems.DetailId

    join Requisitions on Requisitions.RequisitionId = Detail.RequisitionId

... (truncated)
```

sp_UpdatePricePlan {sp-dbo-sp-updatepriceplan}

> Update existing record in UpdatePlan

Property	Value
Schema	dbo
Created	2001-11-26 13:44:31.953000
Modified	2009-03-25 06:55:28.397000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pPricePlanId	int	INPUT	p Price Plan identifier

Definition

```
CREATE                   procedure sp_UpdatePricePlan @pPricePlanId int AS



declare @PricePlanId int



select @PricePlanId = @pPricePlanId



if @PricePlanId = 0

begin

  declare PPCursor cursor read_only forward_only for

    select PricePlanId

      from PricePlans

     where Active = 1



  open PPCursor



  fetch next from PPCursor into @PricePlanId



  while @@fetch_status = 0

  begin

    exec dbo.sp_UpdatePricePlan @PricePlanId


    fetch next from PPCursor into @PricePlanId

  end
```

```
    close PPCursor

  ... (truncated)
```

sp_UpdateReq {sp-dbo-sp-updatereq}

> Update existing record in UpdateReq

Property	Value
Schema	dbo
Created	2001-08-24 14:40:45.673000
Modified	2012-07-30 13:56:22.440000
Parameters	4

Parameters

#	Parameter	Type	Direction	Description
1	@pRequisitionId	int	INPUT	p Requisition identifier
2	@pBudgetAccountI	int	INPUT	p Budget Account identifier
3	@pBudgetId	int	INPUT	p Budget identifier
4	@pUserId	int	INPUT	p User identifier

Definition

```
CREATE         PROCEDURE [dbo].[sp_UpdateReq] @pRequisitionId int, @pBudgetAccountId in...



declare @oldBudgetAccountId int,

@oldTotalRequisitionCost money,

@oldBudgetId int,

@oldUserAccountId int,

@oldAmountAvailable money,

@oldUseAllocations int,

@newBudgetAccountId int,

@newTotalRequisitionCost money,

@newBudgetId int,

@newUserAccountId int,

@newAmountAvailable money,

@newUseAllocations int,

@oldRequisitionId int,

@newRequisitionId int,

@oldUserId int,

@newUserId int,

@oldAccountId int,

@newAccountId int,
```

```
@oldTotalItemsCost money,

@newTotalItemsCost money,

@newTotalBidCost money,
```

```
@newTotalGrossCost money,

@oldShippingCost money,

... (truncated)
```

sp_UpdateReqDetail {sp-dbo-sp-updatereqdetail}

> Update existing record in UpdateReq

Property	Value
Schema	dbo
Created	2004-01-28 12:56:31.543000
Modified	2025-07-01 08:44:49.613000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pReqId	int	INPUT	p Req identifier

Definition

```
CREATE      procedure [dbo].[sp_UpdateReqDetail] @pReqId int AS



declare @ReqId int,

@CategoryId int,

@DistrictId int,

@TodaysDate datetime



update Requisitions

   set BidHeaderId = BidHeaderId

 where RequisitionId = @pReqId



 return



select @TodaysDate = getdate()



print 'Building Requisition List'



select Requisitions.RequisitionId, Requisitions.CategoryId, School.DistrictId

  into #ReqList

  from Detail

  join Requisitions on Requisitions.RequisitionId = Detail.RequisitionId

  join School on School.SchoolId = Requisitions.SchoolId

  join Budgets on Budgets.BudgetId = Requisitions.BudgetId
```

```
                and Budgets.StartDate <= dateadd(year,1,getdate())

                and Budgets.EndDate >= dateadd(year,1,getdate())

  ... (truncated)
```

sp_UpdateReqDetailItem {sp-dbo-sp-updatereqdetailitem}

> Update existing record in UpdateReq

Property	Value
Schema	dbo
Created	2002-03-11 15:26:20.357000
Modified	2009-03-25 06:55:28.380000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pItemId	int	INPUT	p Item identifier

Definition

```
CREATE    procedure sp_UpdateReqDetailItem @pItemId int AS



declare @ReqId int



select Requisitions.RequisitionId

  into #ReqList

  from Detail

  join Requisitions on Requisitions.RequisitionId = Detail.RequisitionId

  join School on School.SchoolId = Requisitions.SchoolId

  join NewFF on NewFF.ItemId = Detail.ItemId

            and NewFF.DistrictId = School.DistrictId

  left outer join StatusTable on StatusTable.StatusId = Requisitions.StatusId

 where isnull(StatusTable.StatusCode,'') != 'O'

   and Detail.ItemId = @pItemId

 group by Requisitions.RequisitionId



Update Detail

   set UnitId = NewFF.UnitId,

       UnitCode = NewFF.Code,

       BidPrice = NewFF.BidPrice,

       CatalogPrice = NewFF.CatalogPrice,

       GrossPrice = NewFF.GrossPrice,

       DiscountRate = NewFF.DiscountRate,
```

```
        CatalogPage = NewFF.Page,

        PriceId = NewFF.PriceId,

  ... (truncated)
```

sp_UpdateReqDetailList {sp-dbo-sp-updatereqdetaillist}

> Update existing record in UpdateReq

Property	Value
Schema	dbo
Created	2004-05-05 16:33:26.200000
Modified	2009-03-25 06:55:28.473000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pRSId	int	INPUT	p RS identifier

Definition

```
CREATE   procedure dbo.sp_UpdateReqDetailList @pRSId int AS



    Update Detail

       set Reproc = 1

      from Detail

      join Requisitions on Requisitions.RequisitionId = Detail.RequisitionId

      join ReportSessionLinks on ReportSessionLinks.IntId = Requisitions.RequisitionId

                              and ReportSessionLinks.RSId = @pRSId
```

sp_UpdateReqDetailPricePlan {sp-dbo-sp-updatereqdetailpriceplan}

> Update existing record in UpdateReqPlan

Property	Value
Schema	dbo
Created	2002-05-29 14:49:00.810000
Modified	2009-03-25 06:55:28.223000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pPricePlanId	int	INPUT	p Price Plan identifier

Definition

```
CREATE    procedure sp_UpdateReqDetailPricePlan @pPricePlanId int AS



declare @ReqId int



select Requisitions.RequisitionId

  into #ReqList

  from Detail

  join Requisitions on Requisitions.RequisitionId = Detail.RequisitionId

  join School on School.SchoolId = Requisitions.SchoolId

  join NewFF on NewFF.ItemId = Detail.ItemId

            and NewFF.DistrictId = School.DistrictId

  left outer join StatusTable on StatusTable.StatusId = Requisitions.StatusId

 where Detail.PricePlanId = @pPricePlanId

   and isnull(StatusTable.StatusCode,'') != 'O'

 group by Requisitions.RequisitionId



Update Detail

   set UnitId = NewFF.UnitId,

       UnitCode = NewFF.Code,

       BidPrice = NewFF.BidPrice,

       CatalogPrice = NewFF.CatalogPrice,

       GrossPrice = NewFF.GrossPrice,

       DiscountRate = NewFF.DiscountRate,
```

```
        CatalogPage = NewFF.Page,

        PriceId = NewFF.PriceId,

... (truncated)
```

sp_UpdateReqHeader {sp-dbo-sp-updatereqheader}

> Update existing record in UpdateReqHeader

Property	Value
Schema	dbo
Created	2001-10-12 10:53:56.250000
Modified	2009-03-25 06:55:28.380000
Parameters	6

Parameters

#	Parameter	Type	Direction	Description
1	@pChangeField	varchar(255)	INPUT	p Change Field parameter
2	@pSessionId	int	INPUT	p Session identifier
3	@pRequisitionId	int	INPUT	p Requisition identifier
4	@pCharField	varchar(255)	INPUT	p Char Field parameter
5	@pChar2Field	varchar(255)	INPUT	p Char2Field parameter
6	@pIntField	int	INPUT	p Int Field parameter

Definition

```
CREATE  procedure sp_UpdateReqHeader @pChangeField varchar(255), @pSessionId int, @pReq...



declare@BudgetAccountId int,

@UserAccountId int,

@BudgetId int,

        @DistrictId int,

@ShippingId int,

@ItemCount int,

@UserId int,

@AccountCode varchar(255),

@CharSessionId varchar(16),

@Attention varchar(255),

        @StartDate varchar(32),

@OrigSchoolId int,

@OrigUserId int,

@OrigBudgetId int,

@OrigBudgetAccountId int,

@OrigUserAccountId int,

@OrigCategoryId int,

@OrigShippingId int,

@OrigAttention varchar(50),

@OrigAccountCode varchar(50),

@OrigBidHeaderId int,
```

```
@NewSchoolId int,

@NewUserId int,

... (truncated)
```

sp_UpdateShippingCode {sp-dbo-sp-updateshippingcode}

> Update existing record in UpdateShippingCode

Property	Value
Schema	dbo
Created	2014-01-31 12:16:25.037000
Modified	2014-01-31 12:16:25.037000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@pShippingId	int	INPUT	p Shipping identifier
2	@pVendorId	int	INPUT	p Vendor identifier
3	@pShippingCode	varchar(50)	INPUT	p Shipping code

Definition

```
create procedure dbo.sp_UpdateShippingCode @pShippingId int, @pVendorId int, @pShipping...

as

declare @currentId int



select @currentId = sv.ShippingVendorId

  from ShipLocations sl

  join Vendors on Vendors.VendorId = @pVendorId

  left outer join ShippingVendor sv on sv.ShippingId = sl.ShippingId

                        and sv.VendorId = Vendors.VendorId

 where sl.ShippingId = @pShippingId



if isnull(@currentId,0) = 0

begin

  insert ShippingVendor (Active, ShippingId, VendorId, ShippingCode)

    values (1, @pShippingId, @pVendorId, ltrim(rtrim(@pShippingCode)))

end

else

begin

  update ShippingVendor

     set ShippingCode = rtrim(ltrim(@pShippingCode))

   where ShippingVendor.ShippingVendorId = @currentId

end
```

sp_UpdateVIC {sp-dbo-sp-updatevic}

> Update existing record in UpdateVIC

Property	Value
Schema	dbo
Created	2010-03-05 11:16:34.783000
Modified	2010-03-05 11:16:34.783000
Parameters	4

Parameters

#	Parameter	Type	Direction	Description
1	@pBidHeaderId	int	INPUT	p Bid Header identifier
2	@pVendorId	int	INPUT	p Vendor identifier
3	@pItemCode	varchar(50)	INPUT	p Item code
4	@pNewVIC	varchar(50)	INPUT	p New VIC parameter

Definition

```
create procedure dbo.sp_UpdateVIC @pBidHeaderId int, @pVendorId int, @pItemCode varchar...



select @pBidHeaderId BidHeaderId, BidResults.ItemId, BidResults.BidResultsId into #Item...

  from BidResults

  join BidImports on BidImports.BidImportId = BidResults.BidImportId

                 and BidImports.VendorId = @pVendorId

  join BidHeaders on BidHeaders.BidHeaderId = BidImports.BidHeaderId

                 and BidHeaders.BidHeaderId = @pBidHeaderId

 where BidResults.ItemCode = @pItemCode



Update BidResults

   set VendorItemCode = @pNewVIC,

       PackedVendorItemCode = dbo.uf_PackCodeCatalog(@pNewVIC, BidImportCatalogList.Cat...

  from BidResults

  join BidImports on BidImports.BidImportId = BidResults.BidImportId

  join #ItemHold ih on ih.BidResultsId = BidResults.BidResultsId

  left outer join BidImportCatalogList on BidImportCatalogList.BidImportId = BidImports...



Update BidItems

   set VendorItemCode = @pNewVIC,

       CrossRefId = (select Top 1 CrossRefId

                     from CrossRefs with (nolock)

                     join Catalog on Catalog.CatalogId = CrossRefs.CatalogId
```

```
                                        and Catalog.Active = 1

                          where CrossRefs.CatalogId = BidImportCatalogList.CatalogId

  ... (truncated)
```

sp_upgraddiagrams {sp-dbo-sp-upgraddiagrams}

> Stored procedure: upgraddiagrams

Property	Value
Schema	dbo
Created	2009-03-26 16:18:10.473000
Modified	2009-03-26 16:18:10.473000
Parameters	0

Definition

```
CREATE PROCEDURE dbo.sp_upgraddiagrams

AS

BEGIN

IF OBJECT_ID(N'dbo.sysdiagrams') IS NOT NULL

return 0;



CREATE TABLE dbo.sysdiagrams

(

name sysname NOT NULL,

principal_id int NOT NULL,-- we may change it to varbinary(85)

diagram_id int PRIMARY KEY IDENTITY,

version int,



definition varbinary(max)

CONSTRAINT UK_principal_name UNIQUE

(

principal_id,

name

)

);
```

```
/* Add this if we need to have some form of extended properties for diagrams */
```

```
/*

IF OBJECT_ID(N'dbo.sysdiagram_properties') IS NULL

... (truncated)
```

sp_ValidateBidImport {sp-dbo-sp-validatebidimport}

> Purchase order procedure for Bid

Property	Value
Schema	dbo
Created	2003-07-15 16:20:30.577000
Modified	2009-03-25 06:55:28.503000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pBidImportId	int	INPUT	p Bid Import identifier

Definition

```
CREATE  procedure dbo.sp_ValidateBidImport @pBidImportId int as



-- Reset Bid Results Status Flag

Update BidResults

   set Status = null

 where BidImportId = @pBidImportId

   and Status is not null



-- Check Header Ids

Update BidResults

   set Status = 'Invalid Bid Header Link'

  from BidResults

  left outer join BidHeaders on BidHeaders.BidHeaderId = BidResults.BidHeaderId

 where BidResults.BidImportId = @pBidImportId

   and BidHeaders.BidHeaderId is null

   and BidResults.Status is null



-- Check Request Item Link

Update BidResults

   set Status = 'Request Item Link Invalid'
```

```
  from BidResults

  join BidHeaders on BidHeaders.BidHeaderId = BidResults.BidHeaderId

  left outer join BidRequestItems on BidRequestItems.BidRequestItemId = BidResults.BidR...
```

```
                                    and BidRequestItems.ItemId = BidResults.ItemId

    where BidResults.BidImportId = @pBidImportId

   ... (truncated)
```

sp_ValidateForPO {sp-dbo-sp-validateforpo}

> Purchase order procedure for For

Property	Value
Schema	dbo
Created	2012-04-13 15:54:14.953000
Modified	2015-03-23 19:14:07.090000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pRSId	int	INPUT	p RS identifier
2	@Response	varchar(MAX)	OUTPUT	Response parameter

Definition

```
CREATE procedure [dbo].[sp_ValidateForPO] @pRSId int, @Response varchar(max) output

as

declare @TestMsg varchar(max),@AlreadyPO varchar(max), @NotApproved varchar(max), @Item...



select @Response = null



-- Check for Already being made into PO

select @AlreadyPO = null

select @AlreadyPO = coalesce(@AlreadyPO + char(13) + char(10),'') + 'Requisition Number...

  from ReportSessionLinks rsl with (nolock)

  join Requisitions on Requisitions.RequisitionId = rsl.IntId

  left outer join PO on PO.RequisitionId = Requisitions.RequisitionId

 where rsl.RSId = @pRSId

   and PO.POId is not null

 group by Requisitions.RequisitionId, isnull(Requisitions.RequisitionNumber,'')

 order by Requisitions.RequisitionId



-- Check for Already being made into Manual PO

select @ManualPO = null

select @ManualPO = coalesce(@ManualPO + char(13) + char(10),'') + 'Requisition Number '...

  from ReportSessionLinks rsl with (nolock)

  join Requisitions on Requisitions.RequisitionId = rsl.IntId

 where rsl.RSId = @pRSId
```

```
    and exists(select Approvals.ApprovalId from Approvals where Approvals.RequisitionId ...

  group by Requisitions.RequisitionId, isnull(Requisitions.RequisitionNumber,'')

 ... (truncated)
```

sp_VendorOverride {sp-dbo-sp-vendoroverride}

> Vendor management procedure for Override

Property	Value
Schema	dbo
Created	2005-01-31 21:26:21.783000
Modified	2009-03-25 06:55:28.333000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@pBidResultsId	int	INPUT	p Bid Results identifier
2	@pSessionId	int	INPUT	p Session identifier
3	@pReason	varchar(4096)	INPUT	p Reason parameter

Definition

```
--sp_AwardBidHeader 1023

--select * from BidRequestItems where BidRequestItemid = 2049100

--sp_VendorOverride 6335194, 48041683, 0, 'Test2'

--select count(*) from BidResultsChangeLog

--select * from Detail where DetailId = 6335194

--select * from BidResults where BidRequestItemId = 2049100

--select * from BidHeaders where BidHeaderId = 1023

--select * from BidHeaderDetail where DetailId = 6335194

--select * from Requisitions where RequisitionId = 190930

--select * from BidItems join Bids on Bids.BidId = BidItems.BidId and Bids.BidHeaderId ...

--delete BidItems where BidItemId = 3679686




CREATE      procedure dbo.sp_VendorOverride @pBidResultsId int, @pSessionId int, @pReas...



declare @Type int,

@BidRequestItemId int,

        @ItemId int,

@BidHeaderId int,

@BidImportId int,

@BRChangeLogId int,

@NewSortKey varchar(255)
```

```
create table #DetailChanges (

DetailId int null,

... (truncated)
```

sp_VendorOverrideLine {sp-dbo-sp-vendoroverrideline}

> Vendor management procedure for OverrideLine

Property	Value
Schema	dbo
Created	2008-03-06 21:26:34.967000
Modified	2014-01-10 17:08:35.853000
Parameters	5

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pBidResultsId	int	INPUT	p Bid Results identifier
3	@pSelected	int	INPUT	p Selected parameter
4	@pVOMId	int	INPUT	p VOM identifier
5	@pReason	varchar(4096)	INPUT	p Reason parameter

Definition

```
--sp_AwardBidHeader 1023

--select * from BidRequestItems where BidRequestItemid = 2049100

--sp_VendorOverride 6335194, 48041683, 0, 'Test2'

--select count(*) from BidResultsChangeLog

--select * from Detail where DetailId = 6335194

--select * from BidResults where BidRequestItemId = 2049100

--select * from BidHeaders where BidHeaderId = 1023

--select * from BidHeaderDetail where DetailId = 6335194

--select * from Requisitions where RequisitionId = 190930

--select * from BidItems join Bids on Bids.BidId = BidItems.BidId and Bids.BidHeaderId ...

--delete BidItems where BidItemId = 3679686



CREATE    procedure [dbo].[sp_VendorOverrideLine] @pSessionId int, @pBidResultsId int, ...



declare @Type int,

@BidRequestItemId int,

        @ItemId int,

@BidHeaderId int,

@BidImportId int,

@BRChangeLogId int,

@BidStatus int,

@BidItemStatus int,

@NewSortKey varchar(255)
```

```
insert DebugMsgs (Msg)

... (truncated)
```

sp_VendorOverrideOld {sp-dbo-sp-vendoroverrideold}

> Vendor management procedure for OverrideOld

Property	Value
Schema	dbo
Created	2008-03-06 18:02:56.060000
Modified	2009-03-25 06:55:28.567000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@pBidResultsId	int	INPUT	p Bid Results identifier
2	@pSessionId	int	INPUT	p Session identifier
3	@pReason	varchar(4096)	INPUT	p Reason parameter

Definition

```
--sp_AwardBidHeader 1023

--select * from BidRequestItems where BidRequestItemid = 2049100

--sp_VendorOverride 6335194, 48041683, 0, 'Test2'

--select count(*) from BidResultsChangeLog

--select * from Detail where DetailId = 6335194

--select * from BidResults where BidRequestItemId = 2049100

--select * from BidHeaders where BidHeaderId = 1023

--select * from BidHeaderDetail where DetailId = 6335194

--select * from Requisitions where RequisitionId = 190930

--select * from BidItems join Bids on Bids.BidId = BidItems.BidId and Bids.BidHeaderId ...

--delete BidItems where BidItemId = 3679686




create procedure dbo.sp_VendorOverrideOld @pBidResultsId int, @pSessionId int, @pReason...



declare @Type int,

@BidRequestItemId int,

        @ItemId int,

@BidHeaderId int,

@BidImportId int,

@BRChangeLogId int,

@NewSortKey varchar(255)
```

```
create table #DetailChanges (

DetailId int null,

... (truncated)
```

sp_VerifyForPO {sp-dbo-sp-verifyforpo}

> Purchase order procedure for For

Property	Value
Schema	dbo
Created	2015-03-23 21:31:50.740000
Modified	2015-03-23 21:31:50.740000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pRSId	int	INPUT	p RS identifier

Definition

```
create procedure [dbo].[sp_VerifyForPO] @pRSId int

as

declare @we table(RequisitionId int, ErrorMsg varchar(255))



-- Check for Already being made into PO

insert @we(RequisitionId, ErrorMsg)

select Requisitions.RequisitionId, 'Already been made into a Purchase Order.'

  from ReportSessionLinks rsl with (nolock)

  join Requisitions on Requisitions.RequisitionId = rsl.IntId

  left outer join PO on PO.RequisitionId = Requisitions.RequisitionId

 where rsl.RSId = @pRSId

   and PO.POId is not null

 group by Requisitions.RequisitionId, isnull(Requisitions.RequisitionNumber,'')

 order by Requisitions.RequisitionId



-- Check for Already being made into Manual PO

insert @we(RequisitionId, ErrorMsg)

select Requisitions.RequisitionId, 'Already been made into a Manual Purchase Order.'

  from ReportSessionLinks rsl with (nolock)

  join Requisitions on Requisitions.RequisitionId = rsl.IntId

 where rsl.RSId = @pRSId

   and exists(select Approvals.ApprovalId from Approvals where Approvals.RequisitionId ...

 group by Requisitions.RequisitionId, isnull(Requisitions.RequisitionNumber,'')
```

```
    order by Requisitions.RequisitionId



  ... (truncated)
```

sp_WarningsForPO {sp-dbo-sp-warningsforpo}

> Purchase order procedure for WarningsFor

Property	Value
Schema	dbo
Created	2013-08-07 10:37:33.010000
Modified	2015-04-07 10:00:23.083000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pRSId	int	INPUT	p RS identifier
2	@Response	varchar(MAX)	OUTPUT	Response parameter

Definition

```
CREATE procedure [dbo].[sp_WarningsForPO] @pRSId int, @Response varchar(max) output

as

declare @OverBudget varchar(max), @SmallPOs varchar(max)



select @Response = null



-- Check for being overbudget

select @OverBudget = null

select @OverBudget = coalesce(@OverBudget + char(13) + char(10),'') + 'Requisition Numb...

  from ReportSessionLinks rsl with (nolock)

  join Requisitions on Requisitions.RequisitionId = rsl.IntId

  join BudgetAccounts on BudgetAccounts.BudgetAccountId = Requisitions.BudgetAccountId

  join UserAccounts on UserAccounts.UserAccountId = Requisitions.UserAccountId

 where rsl.RSId = @pRSId

   and (   (    BudgetAccounts.UseAllocations = 1

            and BudgetAccounts.AmountAvailable < 0)

        or (    UserAccounts.UseAllocations = 1

            and UserAccounts.AllocationAvailable < 0))

 group by Requisitions.RequisitionId, isnull(Requisitions.RequisitionNumber,'')

 order by Requisitions.RequisitionId



--Check for PO's below District Minimum

select @SmallPOs = null
```

```
select @SmallPOs = coalesce(@SmallPOs + char(13) + char(10),'') + 'Requisition Number '...

  from (

... (truncated)
```

usp_BidMatchRefs {sp-dbo-usp-bidmatchrefs}

> Stored procedure: uBidMatchRefs

Property	Value
Schema	dbo
Created	2015-08-21 16:56:29.430000
Modified	2019-08-20 15:00:35.347000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@BidRequestItemId	int	INPUT	Bid Request Item identifier
2	@MatchItemId	int	INPUT	Match Item identifier

Definition

```
CREATE   procedure [dbo].[usp_BidMatchRefs] @BidRequestItemId int, @MatchItemId int

as

declare @CategoryId int,

--@BidRequestItemId int,

@ItemId int,

@BidHeaderId int



-- Set Passed Parameter

--select @BidRequestItemId = 12354566

--exec usp_BidMatchRefs 12354566,0

-- Lookup Category and ItemId

select @CategoryId = BidHeaders.CategoryId, @ItemId = BidRequestItems.ItemId, @BidHeade...

  from BidRequestItems

  join BidHeaders on BidHeaders.BidHeaderId = BidRequestItems.BidHeaderId

 where BidRequestItems.BidRequestItemId = @BidRequestItemId



-- Get List of Possible Vendor/VendorItemCodes to Match

select bvic.ItemId, bvic.VendorId, bvic.VendorItemCode, bvic.BidHeaderId, bvic.BidResul...

  into #IVICList

  from vw_BidVendorItemCodes bvic

 where bvic.ItemId = @ItemId

   and bvic.CategoryId = @CategoryId
```

```
-- Get List of Possible Manufacturer Part Numbers to Match

select bmpl.ItemId, bmpl.VendorId, bmpl.ManufPartNoBid, bmpl.BidHeaderId, bmpl.BidResul...

... (truncated)
```

usp_BidPageNumberUpdate {sp-dbo-usp-bidpagenumberupdate}

> Stored procedure: uBidPageNumberUpdate

Property	Value
Schema	dbo
Created	2019-01-10 11:15:05.640000
Modified	2019-02-05 10:27:20.383000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@BidHeaderId	int	INPUT	Bid Header identifier
2	@VendorId	int	INPUT	Vendor identifier

Definition

```
create   procedure usp_BidPageNumberUpdate @BidHeaderId int, @VendorId int

as

update BidResults

   set PageNo = cast(XR.Page as int)

--select *

  from BidHeaders

  join BidImports on BidImports.BidHeaderId = BidHeaders.BidHeaderId

                 and BidImports.VendorId = @VendorId

  join BidResults on BidResults.BidImportId = BidImports.BidImportId

                 and BidResults.ItemBidType in ('C','A','N','S')

  outer apply (select top 1 CrossRefs.Page

                 from CrossRefs

 join Catalog on Catalog.CatalogId = CrossRefs.CatalogId

             and Catalog.Active = 1

 join BidImportCatalogList on BidImportCatalogList.BidImportId = BidImports.BidImpo...

                         and BidImportCatalogList.CatalogId = Catalog.CatalogId

where CrossRefs.UniqueItemNumber = BidResults.PackedVendorItemCode

  and CrossRefs.Active = 1

  and isnumeric(CrossRefs.Page) = 1

  and isnull(CrossRefs.Page,0) not in (0,9999)

order by Catalog.CatalogYear desc, CrossRefs.GrossPrice desc, CrossRefs.CrossRefId ...

 where BidHeaders.BidHeaderId = @BidHeaderId
```

```
update BidItems

   set PageNo = cast(XR.Page as int),

... (truncated)
```

usp_BidRanking {sp-dbo-usp-bidranking}

> Stored procedure: uBidRanking

Property	Value
Schema	dbo
Created	2015-03-24 12:48:21.477000
Modified	2015-03-24 13:07:04.690000
Parameters	0

Definition

```
--exec usp_BidRanking

-- ============================================

-- Author:Shawn Mason (do I have to claim this?)

-- Create date: 3/23/15

-- Description:bidding ranking return

-- ============================================

CREATE PROCEDURE [dbo].[usp_BidRanking]





AS

BEGIN



SET NOCOUNT ON;



Declare @RankValue int = 0;



With

MSRPItems (BidHeaderId, MfgId, MfgName, MfgProductLineId, MSRPOptInId, OptionName,

  AllFlag, ProductLineName, DiscountRate, VendorId, vendorName

  ,RankValue, TotalAward,RankForWgt

  )

as

(
```

```
SELECT Distinct

   r.BidHeaderId

... (truncated)
```

usp_BidRequestItemMergeDetail_notused {sp-dbo-usp-bidrequestitemmergedetail-notused}

> Bid request processing for uMerge_notused

Property	Value
Schema	dbo
Created	2015-08-07 14:17:05.750000
Modified	2019-08-16 15:17:28.047000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@BidRequestItemId	int	INPUT	Bid Request Item identifier

Definition

```
-- ============================================

-- Author:Shawn Mason

-- Create date: 07/31/2015

-- Description:Detail portion of screen used to possibly identify duplicate items in a...

-- ============================================

CREATE PROCEDURE [dbo].[usp_BidRequestItemMergeDetail]

-- Add the parameters for the stored procedure here

@BidRequestItemId int = 0



AS

BEGIN

-- SET NOCOUNT ON added to prevent extra result sets from

-- interfering with SELECT statements.

SET NOCOUNT ON;



--Declare @BidRequestItemId int =  14321590

Declare @MfgPartNumber varchar(50) = null

Declare @BidHeaderId int = null

Declare @ManufPartNoBid varchar(50) = null
```

```
Select @BidHeaderID = BRI.BidHeaderId

  ,@MfgPartNumber = ManufacturorPartNumber

From BidRequestItems BRI Inner Join
```

```
 CrossRefs CR on CR.ItemId = BRI.ItemId

WHERE BRI.BidRequestItemId = @BidRequestItemId

... (truncated)
```

usp_BidRequestItemMergeDetailDavid {sp-dbo-usp-bidrequestitemmergedetaildavid}

> Bid request processing for uMergeDavid

Property	Value
Schema	dbo
Created	2015-08-21 19:05:43.383000
Modified	2022-08-23 14:57:27.473000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@BidRequestItemId	int	INPUT	Bid Request Item identifier

Definition

```
CREATE   procedure [dbo].[usp_BidRequestItemMergeDetailDavid] @BidRequestItemId int

as

declare @CategoryId int,

--@BidRequestItemId int,

@ItemId int,

@BidHeaderId int



-- Set Passed Parameter

--select @BidRequestItemId = 15999144



-- Lookup Category and ItemId

select @CategoryId = BidHeaders.CategoryId, @ItemId = BidRequestItems.ItemId, @BidHead...

  from BidRequestItems

  join BidHeaders on BidHeaders.BidHeaderId = BidRequestItems.BidHeaderId

 where BidRequestItems.BidRequestItemId = @BidRequestItemId



-- Get List of Possible Vendor/VendorItemCodes to Match

Declare @IVICList Table

(ItemId int

,VendorId int

,VendorItemCode varchar(50)

,BidHeaderId int

,BidResultsId int
```

```
)


... (truncated)
```

usp_BidRequestItemMergeDetailDavidTest_notused {sp-dbo-usp-bidrequestitemmergedetaildavidtest-notuse

> Bid request processing for uMergeDavidTest_notused

Property	Value
Schema	dbo
Created	2015-08-30 12:26:23.237000
Modified	2019-08-16 15:17:34.253000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@BidRequestItemId	int	INPUT	Bid Request Item identifier

Definition

```
CREATE procedure [dbo].[usp_BidRequestItemMergeDetailDavidTest] @BidRequestItemId int

as

declare @CategoryId int,

--@BidRequestItemId int,

@ItemId int,

@BidHeaderId int



-- Set Passed Parameter

--select @BidRequestItemId = 15999144



-- Lookup Category and ItemId

select @CategoryId = BidHeaders.CategoryId, @ItemId = BidRequestItems.ItemId, @BidHead...

  from BidRequestItems

  join BidHeaders on BidHeaders.BidHeaderId = BidRequestItems.BidHeaderId

 where BidRequestItems.BidRequestItemId = @BidRequestItemId



-- Get List of Possible Vendor/VendorItemCodes to Match

Declare @IVICList Table

(ItemId int

,VendorId int

,VendorItemCode varchar(50)

,BidHeaderId int

,BidResultsId int
```

```
)


... (truncated)
```

usp_BidRequestItemMergeDetailTempKevin_notused {sp-dbo-usp-bidrequestitemmergedetailtempkevin-notuse

> Bid request processing for uMergeTempKevin_notused

Property	Value
Schema	dbo
Created	2015-08-20 16:18:11.260000
Modified	2019-08-16 15:17:42.087000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@BidRequestItemId	int	INPUT	Bid Request Item identifier

Definition

```
-- ============================================

-- Author:Kevin

-- Create date: 08/20/2015

-- Description:Detail portion of screen used to possibly identify duplicate items in a...

-- ============================================

CREATE PROCEDURE [dbo].[usp_BidRequestItemMergeDetailTempKevin]

-- Add the parameters for the stored procedure here

@BidRequestItemId int = 0



AS

BEGIN

-- SET NOCOUNT ON added to prevent extra result sets from

-- interfering with SELECT statements.

SET NOCOUNT ON;



--Declare @BidRequestItemId int = 12348577 --14321590

-- comment above line - input paramater



--Select ItemId From BidRequestItems Where BidRequestItemId = @BidRequestItemId -- item...

--Select BH.CategoryId From BidRequestItems BRI Join BidHeaders BH On BH.BidHeaderId = ...



Declare @ItemId int = 0
```

```
Declare @BidHeaderId int = 0

Declare @CategoryId int = 0

... (truncated)
```

usp_BidRequestMergeActions {sp-dbo-usp-bidrequestmergeactions}

> Bid request processing for uMergeActions

Property	Value
Schema	dbo
Created	2015-08-24 16:13:59.090000
Modified	2015-11-24 23:37:35.160000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@BidRequestItemIc	int	INPUT	Bid Request Item Id Source parame
2	@BidRequestItemIc	int	INPUT	Bid Request Item Id Target parame
3	@ExcludeFlag	int	INPUT	Exclude flag

Definition

```
-- ============================================

-- Author:Shawn Mason

-- Create date: 07/31/2015

-- Description:Fulfills required action on BidRequestMerge Screen

-- ============================================

CREATE procedure [dbo].[usp_BidRequestMergeActions]

-- Add the parameters for the stored procedure here

@BidRequestItemIdSource int = 0

,@BidRequestItemIdTarget int = 0

,@ExcludeFlag int = 0    -- 1 indicates to exclude this item source from ever merging




AS

BEGIN

SET NOCOUNT ON;

------------------------

-- Merging into new item

-- Create new item from old item in ITEMS table

Declare @Return int = 0

Declare @ItemIdOld int = 0

Declare @ItemIdNew int = 0

    Declare @CategoryId int = 0
```

```
Select @ItemIdOld = ItemId, @CategoryId = BidHeaders.CategoryId

From BidRequestItems inner join

... (truncated)
```

usp_BidRequestMergeActionsUNDO-wait {sp-dbo-usp-bidrequestmergeactionsundo-wait}

> Bid request processing for uMergeActionsUNDO-wait

Property	Value
Schema	dbo
Created	2015-08-27 13:05:50.727000
Modified	2015-09-01 16:00:40.960000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@BidRequestItemId	int	INPUT	Bid Request Item identifier

Definition

```
-- ============================================

-- Author:Shawn Mason

-- Create date: 08-27-

-- Description:08-27-2015

-- ============================================

CREATE PROCEDURE [dbo].[usp_BidRequestMergeActionsUNDO-wait]

@BidRequestItemId int = 0



AS

BEGIN

SET NOCOUNT ON;

-- Verify Item has been merged previously

Declare @MergedFlag tinyint = 0

Declare @DestinationBidRequestItemId int = 0



Select @MergedFlag = Merged, @DestinationBidRequestItemId=DestinationBidRequestItemId ...

If @MergedFlag = 1 --verifying record was actually merged at one time

BEGIN

Declare @BidRequest int = 0

Declare @RequisitionCount int = 0
```

```
Select @BidRequest = BidRequest, @RequisitionCount = RequisitionCount From [dbo].[Bid...



-- Reduce counts
```

```
Update BidRequestItems

Set BidRequest = BidRequest - @BidRequest

... (truncated)
```

usp_BringAccountsForward {sp-dbo-usp-bringaccountsforward}

> Stored procedure: uBringAccountsForward

Property	Value
Schema	dbo
Created	2018-09-06 12:09:56.677000
Modified	2022-05-04 15:44:34.360000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pDistrictId	int	INPUT	p District identifier

Definition

```
--sp_

--exec usp_BringAccountsForward 27

CREATE   procedure [dbo].[usp_BringAccountsForward] @pDistrictId int as

declare@StartDate datetime,

@EndDate datetime,

@NewBudgetId int,

@OldBudgetId int



-- Build Start Date

select @StartDate = convert(datetime,'07/01/' + convert(char(4),year(getdate()) + case ...



-- Build End Date

select @EndDate = convert(datetime,'06/30/' + convert(char(4),year(@Startdate) + 1) + '...



-- Create New Budgets as Needed

insert Budgets (DistrictId, Active, Name, StartDate, EndDate, VisibleFrom, VisibleUntil...

  select District.DistrictId, 1, convert(char(4),year(@StartDate)) + ' - ' + convert(ch...

    from District

    left outer join Budgets on Budgets.DistrictId = District.DistrictId

                              and Budgets.Name like cast(year(@StartDate) as char(4)) + '%'

                              and Budgets.Active = 1

   where District.DistrictId = @pDistrictId

     and Budgets.BudgetId is null
```

```
select top 1 @NewBudgetId = NewBudget.BudgetId,

... (truncated)
```

usp_ChangeBidHeaderNumber {sp-dbo-usp-changebidheadernumber}

> Bid header management for uChangeNumber

Property	Value
Schema	dbo
Created	2015-12-02 21:11:23.403000
Modified	2015-12-02 21:34:49.667000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@OldBidHeaderId	int	INPUT	Old Bid Header identifier
2	@NewBidHeaderId	int	INPUT	New Bid Header identifier

Definition

```
CREATE procedure [dbo].[usp_ChangeBidHeaderNumber] @OldBidHeaderId int, @NewBidHeaderId...

as

begin



set identity_insert BidHeaders on

insert BidHeaders (Active, AlertLink, AlertMsg, AllowAdditionalManufacturers, AllowAddi...

  select Active, AlertLink, AlertMsg, AllowAdditionalManufacturers, AllowAdditionalProd...

    from BidHeaders

   where BidHeaderId = @OldBidHeaderId

set identity_insert BidHeaders off



Update BidHeaderDetail

   set BidHeaderId = @NewBidHeaderId

 where BidHeaderId = @OldBidHeaderId



Update BidRequestItems

   set BidHeaderId = @NewBidHeaderId

 where BidHeaderId = @OldBidHeaderId



Update BidImports

   set BidHeaderId = @NewBidHeaderId

 where BidHeaderId = @OldBidHeaderId
```

```
Update BidResults

   set BidHeaderId = @NewBidHeaderId

... (truncated)
```

usp_ContinuanceAcceptance {sp-dbo-usp-continuanceacceptance}

> Stored procedure: uContinuanceAcceptance

Property	Value
Schema	dbo
Created	2017-11-01 10:46:44.767000
Modified	2024-02-28 14:28:10.010000
Parameters	4

Parameters

#	Parameter	Type	Direction	Description
1	@pId	uniqueidentifier	INPUT	p identifier
2	@pStatus	varchar(50)	INPUT	p status
3	@pSignedBy	varchar(255)	INPUT	p Signed By parameter
4	@pComments	varchar(4096)	INPUT	p Comments parameter

Definition

```
CREATE procedure [dbo].[usp_ContinuanceAcceptance] @pId uniqueidentifier, @pStatus varc...

as

begin

declare @BudgetId int, @DCRows int



-- Get District Continuance

select @BudgetId = BudgetId

  from DistrictContinuances

 where DistrictContinuances.Id = @pId



select @DCRows = @@rowcount



if @DCRows > 0

begin

-- Update Continuance Status

update DistrictContinuances

   set [Status] = case UPPER(@pStatus) when 'ACCEPT' then 'A' when 'REJECT' then 'R' ...

   Received = getdate(),

   SignedBy = @pSignedBy,

   Comments = @pComments

 where Id = @pId

end
```

```
end
```

usp_CopyRequisition {sp-dbo-usp-copyrequisition}

> Requisition procedure for u

Property	Value
Schema	dbo
Created	2025-03-26 17:45:26.217000
Modified	2025-08-11 11:44:01.123000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@SessionId	int	INPUT	Session identifier
2	@BudgetId	int	INPUT	Budget identifier
3	@RequisitionId	int	INPUT	Requisition identifier

Definition

```
--exec usp_CopyRequisition 1785595599, 1685926, 59353636

--select * from Requisitions where RequisitionId = 59303301

CREATE   procedure [dbo].[usp_CopyRequisition] @SessionId int, @BudgetId int, @Requisit...

as

begin

declare @SessionBudgetId int,

@Status varchar(50),

@Message varchar(4096)

declare @NewReqId int,

@DistrictId int,

@SchoolId int,

@UserId int,

@UserAccountId int,

@BudgetAccountId int,

@AccountCode varchar(50),

@CategoryId int,

@Attention varchar(50),

@TodaysDate datetime,

@AccountCount int,

@DontDeleteNoBids int,
```

```
@NewUserId int,

@NewSchoolId int,

@ShippingId int,
```

```
    @NewAttention varchar(50)


... (truncated)
```

usp_CreateFreightRequest {sp-dbo-usp-createfreightrequest}

> Create new uCreateFreightRequest

Property	Value
Schema	dbo
Created	2022-01-30 23:03:10.497000
Modified	2022-02-16 13:48:39.313000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@RequisitionId	int	INPUT	Requisition identifier

Definition

```
CREATE   procedure [dbo].[usp_CreateFreightRequest] @RequisitionId int

as

begin

/*

-- Create Freight Request(s)

Insert ShippingRequests (VendorId, EMailAddresses, RequisitionId, RequestStatus)

select Vendors.VendorId, String_Agg(vc.Email, ',') Emails, Requisitions.RequisitionId...

  from Requisitions

  join Detail on Detail.RequisitionId = Requisitions.RequisitionId

          and Detail.AdditionalShipping = 1

 and Detail.VendorId != 7691

  join Vendors on Vendors.VendorId = Detail.VendorId

  outer apply (select ShippingRequests.ShippingRequestId

                  from ShippingRequests

where ShippingRequests.RequisitionId = Requisitions.RequisitionId

  and ShippingRequests.VendorId = Vendors.VendorId) sr

  outer apply (select top 100 trim(VendorContacts.Email) Email

                  from VendorContacts

where VendorContacts.VendorId = Vendors.VendorId

  and VendorContacts.Active = 1
```

```
  and VendorContacts.FreightContact = 1

  and coalesce(trim(VendorContacts.Email),'') != ''

group by trim(VendorContacts.Email)
```

```
order by trim(VendorContacts.Email)) vc

 where Requisitions.RequisitionId = @RequisitionId

... (truncated)
```

usp_DetailedIdentityColumnsReport {sp-dbo-usp-detailedidentitycolumnsreport}

> Purchase order procedure for uedIdentityColumns

Property	Value
Schema	dbo
Created	2021-08-05 06:05:36.683000
Modified	2021-08-05 06:21:13.053000
Parameters	0

Definition

```
-- ================================================================

-- Author:      Eli Leiba

-- Create date: 06-2018

-- Description:

--   Produce a Detailed Identity columns report for the whole database

--   That includes the database, schema, table, column, type,

--   Seed, increment and the data type value limit

-- ================================================================

CREATE PROCEDURE dbo.usp_DetailedIdentityColumnsReport

AS

SELECT A.TABLE_CATALOG AS CATALOG,

   A.TABLE_SCHEMA AS "SCHEMA",

   A.TABLE_NAME AS "TABLE",

   B.COLUMN_NAME AS "COLUMN",

   IDENT_SEED (A.TABLE_NAME) AS Seed,

   IDENT_INCR (A.TABLE_NAME) AS Increment,

   IDENT_CURRENT (A.TABLE_NAME) AS Curr_Value,

   B.DATA_TYPE as "Type",

   Type_Limit = CASE lower (B.DATA_TYPE)

      WHEN 'bigint'

         THEN '9,223,372,036,854,775,807'

      WHEN 'int'

         THEN '2,147,483,647'
```

```
        WHEN 'smallint'

           THEN '32,767'

  ... (truncated)
```

usp_EmailBlastProcessOrderDetailChangeNotifications {sp-dbo-usp-emailblastprocessorderdetailchangeno

> Order processing procedure for uChangeNotifications

Property	Value
Schema	dbo
Created	2022-03-28 16:17:18.447000
Modified	2022-04-01 10:36:19.437000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pTemplateRequis	int	INPUT	p Template Requisitioner Email Bla
2	@pTemplateApprov	int	INPUT	p Template Approver Email Blast id

Definition

```
CREATE           procedure [dbo].[usp_EmailBlastProcessOrderDetailChangeNotifications]

@pTemplateRequisitionerEmailBlastId int,

@pTemplateApproverEmailBlastId int

as

declare @NewRequisitionerEmailBlastId int,

        @NewApproverEmailBlastId int



-- Notes:

-- @pTemplateRequisitionerEmailBlastId = The Id of the "Template: Order Detail Change R...

-- @pTemplateApproverEmailBlastId = The Id of the "Template: Order Detail Change Approv...



set nocount on

begin transaction

begin try

    lineno 31  -- set this number based on create sproc script



-- Create copy of "Requisitioner" Template Blast

    insert EmailBlast (BlastName, BlastDescription,

                    BlastHTML, SQLStmt,ReportWhereClause, EmailFrom, EmailCC, EmailBCC,...

                        UseDefaultReadReceiptEmail, ReadReceiptEmail, BlastVar1, BlastVa...

    Select 'Order Detail Change Notification of Requisitioners ' + Convert(varchar, cas...

       BlastHTML, SQLStmt, ReportWhereClause, EmailFrom, EmailCC, EmailBCC, EmailSubje...

   UseDefaultReadReceiptEmail, ReadReceiptEmail, BlastVar1, BlastVar2, VarDataSQL
```

```
from EmailBlast

Where EmailBlastId = @pTemplateRequisitionerEmailBlastId

... (truncated)
```

usp_EmailBlastSetNotificationBlastHTMLApprover {sp-dbo-usp-emailblastsetnotificationblasthtmlapprove

> Email procedure for uSetNotificationHTMLApprover

Property	Value
Schema	dbo
Created	2022-03-31 21:22:24.740000
Modified	2024-03-01 12:48:44.997000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pApproverEmailB	int	INPUT	p Approver Email Blast identifier
2	@pRequistionerEma	int	INPUT	p Requistioner Email Blast identifie

Definition

```
CREATE         procedure [dbo].[usp_EmailBlastSetNotificationBlastHTMLApprover]

@pApproverEmailBlastId int,

@pRequistionerEmailBlastId int

as



set nocount on



Update Notifications

   Set EmailHTMLTable = SSApproverBlast.HTMLTable

From

(

Select N2.EmailBlastId, N2.NotificationId, ReqBlastData.HTMLTable

From Notifications N2

Join

(

Select SS2.ApproverUserId,

'<table border="1" cellpadding="1" cellspacing="1" style="height: 79px"><tbody>' +

'<tr><td>Username</td><td>Attention</td><td>Requisitions</td></tr>' +

STRING_AGG(

  '<tr>' +

  '<td>' + SS2.UserName  + '</td>' +

  '<td>' + SS2.AttnRequisitioner + '</td>' +

  '<td>' + SS2.Reqs + '</td>' +
```

```
    '</tr>'

  , '') WITHIN GROUP (ORDER BY SS2.UserName) +

  ... (truncated)
```

usp_EmailBlastSetNotificationBlastHTMLRequisitioner {sp-dbo-usp-emailblastsetnotificationblasthtmlre

> Requisition procedure for uSetNotificationHTMLer

Property	Value
Schema	dbo
Created	2022-03-31 21:24:29.963000
Modified	2024-02-29 14:56:28.437000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pEmailBlastId	int	INPUT	p Email Blast identifier

Definition

```
CREATE             procedure [dbo].[usp_EmailBlastSetNotificationBlastHTMLRequisitioner]

@pEmailBlastId int

as



set nocount on

/*

Select N.NotificationId, ApprvlUser.UserId ReqUserId,

'<table border="1" cellpadding="1" cellspacing="1" style="height: 79px"><tbody>' +

'<tr><td>Requisition#</td><td>Username</td><td>Attention</td><td></td><td>Vendor</td><t...

STRING_AGG(

  '<tr>' +

  '<td rowspan="2">' + cast(REQ.RequisitionNumber as nvarchar(max)) + '</td>' +

  '<td rowspan="2">' + cast(ReqUser.UserName as varchar) + '</td>' +

  '<td rowspan="2">' + cast(ReqUser.Attention as varchar(50)) + '</td>' +

  '<td>' + 'Original Order:' + '</td>' +

  '<td>' + case when DN.OrigVendorId=7691 then 'No Vendor' else cast(OrigVen.Name as va...

  '<td>' + case when DN.OrigVendorId=7691 then 'N/A' else cast(OrigItem.ItemCode as var...

  '<td>' + isnull(cast(cast(DN.OrigBidPrice as Decimal(18,2)) as varchar),'') + '</td>' +

  '<td>' + case when DN.OrigVendorId=7691 then 'N/A' else cast(OrigItem.Description as ...

  '</tr>' +

  '<tr>' +

  '<td>' + 'Updated Order:' + '</td>' +

  '<td>' + case when DN.NewVendorId=7691 then 'No Vendor' else cast(NewVen.Name as varc...
```

```
    '<td>' + case when DN.NewVendorId=7691 then 'N/A' else cast(DTL.ItemCode as varchar(5...

    '<td>' + isnull(cast(cast(DN.NewBidPrice as Decimal(18,2)) as varchar),'') + '</td>' +

  ... (truncated)
```

usp_EmailBlastVarsOrderDetailChangeApprover_NotUsed {sp-dbo-usp-emailblastvarsorderdetailchangeappro

> Order processing procedure for uVarsChangeApprover_NotUsed

Property	Value
Schema	dbo
Created	2022-03-28 16:21:56.200000
Modified	2022-04-06 13:07:27.063000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pRequistionerEma	int	INPUT	p Requistioner Email Blast identifie
2	@pUserId	int	INPUT	p User identifier

Definition

```
CREATE       procedure [dbo].[usp_EmailBlastVarsOrderDetailChangeApprover_NotUsed]

@pRequistionerEmailBlastId int,

@pUserId int

as

declare @TableHTML varchar(max)



-- Note: This code was tested and works but it is not currently being used.

--       It was being used in the "Variable Data SQL" tab of the blast.  As such, it wo...

--       Instead... the sproc: usp_EmailBlastProcessOrderDetailChangeNotifications exec...

--                  the HTML to be included in the email content and saves it in the no...



set nocount on



Select @TableHTML =

'<table border="1" cellpadding="1" cellspacing="1" style="height: 79px"><tbody>' +

'<tr><td>Username</td><td>Attention</td><td>Requisitions</td></tr>' +

STRING_AGG(

  '<tr>' +

  '<td>' + SS2.UserName  + '</td>' +

  '<td>' + SS2.AttnRequisitioner + '</td>' +

  '<td>' + SS2.Reqs + '</td>' +

  '</tr>'

, '') WITHIN GROUP (ORDER BY SS2.UserName) +
```

```
    '</tbody></table>'

  From

  ... (truncated)
```

usp_EmailBlastVarsOrderDetailChangeRequistioner_NotUsed {sp-dbo-usp-emailblastvarsorderdetailchanger

> Order processing procedure for uVarsChangeRequistioner_NotUsed

Property	Value
Schema	dbo
Created	2022-03-28 16:23:50.637000
Modified	2022-04-06 13:09:18.137000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pEmailBlastId	int	INPUT	p Email Blast identifier
2	@pUserId	int	INPUT	p User identifier

Definition

```
CREATE       procedure [dbo].[usp_EmailBlastVarsOrderDetailChangeRequistioner_NotUsed]

@pEmailBlastId int,

@pUserId int

as

declare @EmailContentHTML varchar(max)



-- Note: This code was tested and works but it is not currently being used.

--       It was being used in the "Variable Data SQL" tab of the blast.  As such, it wo...

--       Instead... the sproc: usp_EmailBlastProcessOrderDetailChangeNotifications exec...

--                  the HTML to be included in the email content and saves it in the no...



set nocount on



Select @EmailContentHTML =

'<table border="1" cellpadding="1" cellspacing="1" style="height: 79px"><tbody>' +

'<tr><td>Requisition#</td><td>Username</td><td>Attention</td><td></td><td>Vendor</td><t...

STRING_AGG(

  '<tr>' +

  '<td rowspan="2">' + cast(REQ.RequisitionNumber as nvarchar(max)) + '</td>' +

  '<td rowspan="2">' + cast(ReqUser.UserName as varchar) + '</td>' +

  '<td rowspan="2">' + cast(ReqUser.Attention as varchar(50)) + '</td>' +

  '<td>' + 'Original Order:' + '</td>' +

  '<td>' + case when DN.OrigVendorId=7691 then 'No Vendor' else cast(OrigVen.Name as va...
```

```
    '<td>' + case when DN.OrigVendorId=7691 then 'N/A' else cast(OrigItem.ItemCode as var...

    '<td>' + isnull(cast(cast(DN.OrigBidPrice as Decimal(18,2)) as varchar),'') + '</td>' +

  ... (truncated)
```

usp_EndPOSend {sp-dbo-usp-endposend}

> Purchase order procedure for uEndSend

Property	Value
Schema	dbo
Created	2019-04-28 12:45:09.220000
Modified	2019-04-28 12:46:45.290000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pPOQueueItemId	int	INPUT	p POQueue Item identifier
2	@pSendStatus	varchar(255)	INPUT	p Send status

Definition

```
create   procedure usp_EndPOSend @pPOQueueItemId int, @pSendStatus varchar(255)

as

declare @POId int



select @POId = POId

  from POQueueItems

 where POQueueItems.POQueueItemId = @pPOQueueItemId



Update POQueueItems

   set SendEnded = getdate(),

       SendStatus = @pSendStatus,

   PayloadId = (select top 1 VendorUploads.PayloadId from VendorUploads where VendorUp...

 where POQueueItemId = @pPOQueueItemId
```

usp_FindEmail {sp-dbo-usp-findemail}

> Email procedure for u

Property	Value
Schema	dbo
Created	2024-01-25 18:21:30.610000
Modified	2024-08-14 23:33:25.320000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description

1	@PassedList	varchar(MAX)	INPUT	Passed list/array

Definition

```
CREATE Procedure dbo.usp_FindEmail @PassedList varchar(max)

AS

  declare @EmailList table(Email varchar(255))

  declare @Results table(Type varchar(50), DV varchar(50), Locator varchar(256),Email v...



  insert @EmailList(Email)

  select trim(value) from string_split(@PassedList,',')



  insert @Results(Type, DV, Locator, Email, Phone, BelongsTo)

  select 'District User', District.Name, right('00000' + cast(Users.CometId as varchar)...

    from @EmailList el

    join Users on trim(Users.Email) = el.Email

              and Users.Active = 1

    join District on District.DistrictId = Users.DistrictId

                and District.Active = 1

    join School on School.SchoolId = Users.SchoolId

               and School.Active = 1

    join CSRep on CSRep.CSRepId = District.CSRepId



  insert @Results(Type, DV, Locator, Email, Phone, BelongsTo)
```

```
    select 'District Contact', District.Name, DistrictContactTypes.Description, DistrictC...

      from @EmailList el

      join DistrictContacts on trim(DistrictContacts.eMail) = el.Email

      join District on District.DistrictId = DistrictContacts.DistrictId

                   and District.Active = 1

  ... (truncated)
```

usp_FindEmail_BK {sp-dbo-usp-findemail-bk}

> Email procedure for u_BK

Property	Value
Schema	dbo
Created	2024-08-14 23:31:34.320000
Modified	2024-08-14 23:31:34.320000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@PassedList	varchar(MAX)	INPUT	Passed list/array

Definition

```
CREATE Procedure dbo.usp_FindEmail_BK @PassedList varchar(max)

as

declare @EmailList table(Email varchar(255))

declare @Results table(Type varchar(50), DV varchar(50), Locator varchar(256),Email var...



insert @EmailList(Email)

select trim(value) from string_split(@PassedList,',')



insert @Results(Type, DV, Locator, Email

, Phone)

select 'District User', District.Name, right('00000' + cast(Users.CometId as varchar),5...

  from @EmailList el

  join Users on trim(Users.Email) = el.Email

            and Users.Active = 1

  join District on District.DistrictId = Users.DistrictId

               and District.Active = 1

  join School on School.SchoolId = Users.SchoolId

             and School.Active = 1



insert @Results(Type, DV, Locator, Email, Phone)

select 'District Contact', District.Name, DistrictContactTypes.Description, DistrictCon...

  from @EmailList el

  join DistrictContacts on trim(DistrictContacts.eMail) = el.Email
```

```
    join District on District.DistrictId = DistrictContacts.DistrictId

                and District.Active = 1

  ... (truncated)
```

usp_GeneratePassword {sp-dbo-usp-generatepassword}

> Password management procedure for uGenerate

Property	Value
Schema	dbo
Created	2023-09-20 16:34:11.640000
Modified	2024-12-01 19:39:15.220000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pUserId	int	INPUT	p User identifier
2	@pLength	int	INPUT	p Length parameter

Definition

```
CREATE     procedure [dbo].[usp_GeneratePassword] @pUserId int, @pLength int

as

begin

set NOCOUNT on

declare @CharSet varchar(128) = 'ABCDEFGHIJKLMNOPQRSTUVWXYZ012345789abcdefghijklmnopqrs...

@NewPass varchar(64) = '',

@Idx int = 1,

@MeetsRequirements tinyint = 0,

@RandChar char(1),

@RandIdx int,

@CometId int



Select @CometId = CometId

  from Users

 where UserId = @pUserId

--print @CometId

--print @pUserId

while @MeetsRequirements = 0

begin

select @NewPass = ''

select @Idx = 1

while @Idx <= @pLength

begin
```

```
Select @RandIdx = cast(RAND() * len(@CharSet) as int) + 1

if @RandIdx > len(@CharSet) or @RandIdx < 1

... (truncated)
```

usp_GeneratePassword_Print {sp-dbo-usp-generatepassword-print}

> Password management procedure for uGenerate_Print

Property	Value
Schema	dbo
Created	2025-01-03 09:17:08.013000
Modified	2025-01-03 09:17:08.013000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pUserId	int	INPUT	p User identifier
2	@pLength	int	INPUT	p Length parameter

Definition

```
create   procedure [dbo].[usp_GeneratePassword_Print] @pUserId int, @pLength int

as

begin

set NOCOUNT on

declare @CharSet varchar(128) = 'ABCDEFGHIJKLMNOPQRSTUVWXYZ012345789abcdefghijklmnopqrs...

@NewPass varchar(64) = '',

@Idx int = 1,

@MeetsRequirements tinyint = 0,

@RandChar char(1),

@RandIdx int,

@CometId int



Select @CometId = CometId

  from Users

 where UserId = @pUserId

--print @CometId

--print @pUserId

while @MeetsRequirements = 0

begin

select @NewPass = ''
```

```
select @Idx = 1

while @Idx <= @pLength

begin
```

```
Select @RandIdx = cast(RAND() * len(@CharSet) as int) + 1

if @RandIdx > len(@CharSet) or @RandIdx < 1

... (truncated)
```

usp_GetBidItemAIData {sp-dbo-usp-getbiditemaidata}

> Retrieve record(s) from uGetAIData

Property	Value
Schema	dbo
Created	2025-07-10 09:25:50.210000
Modified	2025-10-31 13:40:39.663000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@IdList	varchar(MAX)	INPUT	Id list/array

Definition

```
CREATE   procedure [dbo].[usp_GetBidItemAIData] @IdList varchar(max)

as

-- Return Existing Data for AI Process

select BidResults.BidResultsId,

   coalesce(trim(Items.Description),'') BidItemDescription,

       coalesce(trim(BidResults.Alternate),'') ShortDescription,

   coalesce(trim(BidResults.ManufacturerBid),'') Manufacturer,

   coalesce(trim(BidResults.ManufPartNoBid),'') ManufacturerPartNumber,

   coalesce(trim(BidResults.UNSPSC),'') UNSPSC

  from BidResults with (nolock)

  join Items on Items.ItemId = BidResults.ItemId

 where BidResults.BidResultsId in (Select cast(ss.value as int) Id from string_split(@I...
```

usp_GetBidItemsNeedingAIUpdate {sp-dbo-usp-getbiditemsneedingaiupdate}

> Retrieve record(s) from uGetsNeedingAIUpdate

Property	Value
Schema	dbo
Created	2025-07-10 09:22:52.240000
Modified	2025-11-03 22:27:54.570000
Parameters	0

Definition

```
CREATE     procedure [dbo].[usp_GetBidItemsNeedingAIUpdate] as

begin

/* Table Changes

alter table BidResults

add

HashKeyvarbinary(64) null,

ProductNamesnvarchar(4000) null,

TypeAheadsnvarchar(4000) null,

AIShortDescnvarchar(1024) null,

AIFullDescnvarchar(4000) null,

AIUNSPSCvarchar(20) null,

AIDatedatetime null

*/



-- Return the list of Id's to process

select BidResults.BidResultsId BidResultsId, BidResults.[HashKey]

  from BidResults

  join BidImports on BidImports.BidImportId = BidResults.BidImportId

  join BidHeaders on BidHeaders.BidHeaderId = BidImports.BidHeaderId

                 and BidHeaders.EffectiveUntil > getdate()

 where BidResults.ItemBidType in ('A','C','S')

   and BidResults.AIdate is null

   and BidResults.HashKey is not null
```

```
set nocount off

... (truncated)
```

usp_GetImageList {sp-dbo-usp-getimagelist}

> Retrieve record(s) from uGetImage

Property	Value
Schema	dbo
Created	2021-05-03 22:29:23.433000
Modified	2025-03-21 09:02:46.013000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@mod	int	INPUT	mod parameter
2	@rem	int	INPUT	rem parameter

Definition

```
--exec usp_GetImageList 4, 3

CREATE   procedure [dbo].[usp_GetImageList] @mod int = 1, @rem int = 0

as

begin



create table #ImageList (

imageId bigint identity(1,1) not null primary key,

imageURL varchar(512) not null,

seqbigint null)



/*

insert #imageList(imageURL, Seq)

select trim(il.ImageURL), CHECKSUM(HASHBYTES('SHA2_512',trim(il.ImageURL)))

  from ImageLog il

  join Images on Images.ImageURL = ImageLog.ImageURL

 where coalesce(writeStatus,'') != '200'

*/

insert #imageList(imageURL, Seq)

  select trim(ie.ImageURL), CHECKSUM(HASHBYTES('SHA2_512',trim(ie.ImageURL)))

    from ImageErrors ie

   where json_value(error,'$.message') = 'unable to verify the first certificate'

   group by trim(ie.ImageURL), CHECKSUM(HASHBYTES('SHA2_512',trim(ie.ImageURL)))
```

```
/*

... (truncated)
```

usp_GetItemAIData {sp-dbo-usp-getitemaidata}

> Retrieve record(s) from uGetAIData

Property	Value
Schema	dbo
Created	2025-04-27 18:18:06.687000
Modified	2025-05-07 16:46:32.383000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@IdList	varchar(MAX)	INPUT	Id list/array

Definition

```
CREATE   procedure [dbo].[usp_GetItemAIData] @IdList varchar(max)

as

-- Return Existing Data for AI Process

select CrossRefs.CrossRefId,

       coalesce(trim(CrossRefs.ShortDescription),'') ShortDescription,

   coalesce(trim(CrossRefs.FullDescription),'') FullDescription,

   coalesce(trim(CrossRefs.Manufacturor),'') Manufacturer,

   coalesce(trim(CrossRefs.ManufacturorPartNumber),'') ManufacturerPartNumber,

   coalesce(trim(CrossRefs.UNSPSC),'') UNSPSC

  from CrossRefs with (nolock)

 where CrossRefs.CrossRefId in (Select cast(ss.value as int) Id from string_split(@IdLi...
```

usp_GetItemsNeedingAIUpdate {sp-dbo-usp-getitemsneedingaiupdate}

> Retrieve record(s) from uGetsNeedingAIUpdate

Property	Value
Schema	dbo
Created	2025-04-27 18:21:27.427000
Modified	2025-06-30 14:55:37.197000
Parameters	0

Definition

```
CREATE   procedure [dbo].[usp_GetItemsNeedingAIUpdate] as

begin

/* Table Changes

alter table CrossRefs

add

HashKeyvarbinary(64) null,

ProductNamesnvarchar(4000) null,

TypeAheadsnvarchar(4000) null,

AIShortDescnvarchar(1024) null,

AIFullDescnvarchar(4000) null,

AIUNSPSCvarchar(20) null,

AIDatedatetime null

*/



declare @SourceCatalogs table (

CatalogIdint not null primary key,

VendorIdint not null,

DatePosteddatetime)



insert @SourceCatalogs (CatalogId, VendorId, DatePosted)

select Catalog.CatalogId, Catalog.VendorId, Catalog.PostDate

  from Catalog with (nolock)

  join BidsCatalogList on BidsCatalogList.CatalogId = Catalog.CatalogId
```

```
    join Bids on Bids.BidId = BidsCatalogList.BidId

             and Bids.Active = 1

  ... (truncated)
```

usp_GetMSDSSheets {sp-dbo-usp-getmsdssheets}

> Retrieve record(s) from uGetMSDSSheets

Property	Value
Schema	dbo
Created	2017-01-25 06:19:09.853000
Modified	2017-01-25 06:28:50.420000
Parameters	0

Definition

```
CREATE procedure usp_GetMSDSSheets

as

declare @MSDSId int, @Counter int

declare @ItemList varchar(max), @ItemDesc varchar(max)

declare @SDS table(MSDSId int, Counter int, ItemDescription varchar(512), ItemList varc...



declare ic cursor for

select wl.MSDSId, Counter

  from (

select master.dbo.ufn_RegExReplace(ReportProducts.Manufacturer,'(?:.{0,}\(){1,}(?<msds>...

  from NJ_RTK.dbo.Employers

  join NJ_RTK.dbo.Facilities on Facilities.EmployerId = Employers.Id

  join NJ_RTK.dbo.ReportSurveys on ReportSurveys.FacilityId = Facilities.Id

                                and ReportSurveys.Id =

    (select top 1 rs.Id

       from NJ_RTK.dbo.ReportSurveys rs

      where rs.FacilityId = Facilities.Id

      order by rs.RunDate desc)

  join NJ_RTK.dbo.ReportProducts on ReportProducts.ReportSurveyId = ReportSurveys.Id

  and isnumeric(master.dbo.ufn_RegExReplace(ReportProducts.Manufacturer,'(?:.{0,}\(){1,...

 group by master.dbo.ufn_RegExReplace(ReportProducts.Manufacturer,'(?:.{0,}\(){1,}(?<ms...

  ) wl

 order by wl.Counter desc
```

```
open ic

... (truncated)
```

usp_getMyLastYearsReqs {sp-dbo-usp-getmylastyearsreqs}

> Retrieve record(s) from ugetMyLastYearsReqs

Property	Value
Schema	dbo
Created	2025-03-26 17:44:57.500000
Modified	2025-03-26 17:44:57.500000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pUserId	int	INPUT	p User identifier
2	@pBudgetId	int	INPUT	p Budget identifier

Definition

```
--exec usp_getMyLastYearsReqs 207252,1685926

create     procedure [dbo].[usp_getMyLastYearsReqs] @pUserId int, @pBudgetId int

as

declare @PriorBudgetId int,

@CurrentBudgetId int



select @PriorBudgetId = rb.BudgetId, @CurrentBudgetId = cb.BudgetId

  from Budgets cb

  join Budgets rb on rb.DistrictId = cb.DistrictId

                 and Year(rb.StartDate) = Year(cb.StartDate) - 1

 and rb.Active = 1

 where cb.BudgetId = @pBudgetId



select Requisitions.RequisitionId,

   Category.Name CategoryName,

   Requisitions.RequisitionNumber,

   Requisitions.Attention,

   coalesce(Requisitions.AccountCode,'') AccountCode,

   Requisitions.TotalRequisitionCost Amount,

   dbo.uf_RequisitionStatus(Requisitions.RequisitionId) [Status],

   case when coalesce(ap.StatusId,0) in (6,35,45,49) and nr.ReqNumbers is null then 'R...

   '<input type="radio" id="bfrCopy_' + cast(Requisitions.RequisitionId as varchar) + ...

   '<input type="radio" id="bfrSkip_' + cast(Requisitions.RequisitionId as varchar) + ...
```

```
    from Requisitions

    join Category on Category.CategoryId = Requisitions.CategoryId

  ... (truncated)
```

usp_GetNextPONumber {sp-dbo-usp-getnextponumber}

> Retrieve record(s) from uGetNextNumber

Property	Value
Schema	dbo
Created	2019-04-09 14:29:29.543000
Modified	2024-04-12 10:46:12.650000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pDistrictId	int	INPUT	p District identifier
2	@pBudgetId	int	INPUT	p Budget identifier

Definition

```
CREATE   procedure [dbo].[usp_GetNextPONumber] @pDistrictId int, @pBudgetId int

as

begin

declare @NextNumberId int

set Nocount on



-- Find Current Entry

select @NextNumberId = NextNumberId

  from NextNumber

 where DistrictId = @pDistrictId

   and BudgetId = @pBudgetId

   and IDType = 'P'



-- No Current Entry Available

if @@rowcount = 0

begin

    -- User Prior Year as Reference base

insert NextNumber(DistrictId, BudgetId, IDType, Prefix, Suffix, NextNumber, SuppressLZ...

    select top 1 NextNumber.DistrictId, @pBudgetId, 'P', NextNumber.Prefix, NextNumber...

from NextNumber

join Budgets on Budgets.BudgetId = NextNumber.BudgetId

            and Budgets.Active = 1

join Budgets cb on cb.DistrictId = Budgets.DistrictId
```

```
                  and cb.Active = 1

      and cb.BudgetId = @pBudgetId

   ... (truncated)
```

usp_GetPODetail {sp-dbo-usp-getpodetail}

> Retrieve record(s) from uGet

Property	Value
Schema	dbo
Created	2025-06-05 14:22:47.843000
Modified	2025-09-11 16:06:24.730000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@POId	int	INPUT	Purchase order identifier

Definition

```
--exec usp_GetPODetail 717551465



--exec usp_GetPODetail_Test 717443521

--exec usp_GetPODetail_Test 717443510

CREATE     procedure [dbo].[usp_GetPODetail] @POId int

as

begin

/* This procedure gets the Ordered Detail for a PO along with the Stored Status of the ...

declare @POLinesnvarchar(max),

@POStatusnvarchar(1024),

@VendorIdint,

@sslOrderNumber int



declare @POItems table (

POItemIdint identity(1,1) not null primary key,

sslOrderNumberint null,

OrderLineIdint null,

OrderStatusnvarchar(1024) null,

LineStatusnvarchar(1024) null,

OrderedDescriptionnvarchar(2048) null,

ShippedDescriptionnvarchar(2048) null,

OrderedVendorItemCodevarchar(50) null,

ShippedVendorItemCodevarchar(50) null,
```

```
ItemCodevarchar(50) null,

UOMvarchar(50) null,

... (truncated)
```

usp_GetPODetail_Test {sp-dbo-usp-getpodetail-test}

> Retrieve record(s) from uGet_Test

Property	Value
Schema	dbo
Created	2025-06-15 19:24:54.823000
Modified	2025-06-24 15:35:25.850000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@POId	int	INPUT	Purchase order identifier

Definition

```
--exec usp_GetPODetail_Test 717551465



--exec usp_GetPODetail_Test 717443521

--exec usp_GetPODetail_Test 717443510

create     procedure [dbo].[usp_GetPODetail_Test] @POId int

as

begin

/* This procedure gets the Ordered Detail for a PO along with the Stored Status of the ...

declare @POLinesnvarchar(max),

@POStatusnvarchar(1024),

@VendorIdint,

@sslOrderNumber int



declare @POItems table (

POItemIdint identity(1,1) not null primary key,

sslOrderNumberint null,

OrderLineIdint null,

OrderStatusnvarchar(1024) null,

LineStatusnvarchar(1024) null,

OrderedDescriptionnvarchar(2048) null,

ShippedDescriptionnvarchar(2048) null,

OrderedVendorItemCodevarchar(50) null,

ShippedVendorItemCodevarchar(50) null,
```

```
ItemCodevarchar(50) null,

UOMvarchar(50) null,

... (truncated)
```

usp_GetPOs {sp-dbo-usp-getpos}

> Retrieve record(s) from uGets

Property	Value
Schema	dbo
Created	2019-04-28 12:46:44.110000
Modified	2025-10-13 23:47:07.697000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@BudgetId	int	INPUT	Budget identifier

Definition

```
--exec usp_GetPOs 1672666--1672687

CREATE     procedure [dbo].[usp_GetPOs] @BudgetId int

as

/*

"POId": "#variables.rsPOs.POId#",

"BidHeaderId": "#variables.rsPOs.BidHeaderId#",

"CategoryId": "#variables.rsPOs.CategoryId#",

"RequisitionId": "#variables.rsPOs.RequisitionId#",

"SchoolId": "#variables.rsPOs.SchoolId#",

"VendorId": "#variables.rsPOs.VendorId#",

"AccountCode": "#variables.rsPOs.AccountCode#",

"Amount": "#variables.rsPOs.Amount#",

"Attention": "#variables.rsPOs.Attention#",

"CategoryName": "#variables.rsPOs.CategoryName#",

"DateSent": "#variables.rsPOs.DateSent#",

"ItemCount": "#variables.rsPOs.ItemCount#",

"PONumber": "#variables.rsPOs.PONumber#",

"SchoolName": "#variables.rsPOs.SchoolName#"

"Status": "#variables.rsPOs.POStatus#",

"VendorName": "#variables.rsPOs.VendorName#",

"UserNumber": "#variables.rsPOs.UserNumber#",

"Updated": false

*/
```

```
declare @POs table (

POIdint null,

... (truncated)
```

usp_GetPOs_Test {sp-dbo-usp-getpos-test}

> Retrieve record(s) from uGets_Test

Property	Value
Schema	dbo
Created	2022-05-18 01:08:58.337000
Modified	2022-05-18 01:08:58.337000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@BudgetId	int	INPUT	Budget identifier

Definition

```
create     procedure [dbo].[usp_GetPOs_Test] @BudgetId int

as

/*

"POId": "#variables.rsPOs.POId#",

"BidHeaderId": "#variables.rsPOs.BidHeaderId#",

"CategoryId": "#variables.rsPOs.CategoryId#",

"RequisitionId": "#variables.rsPOs.RequisitionId#",

"SchoolId": "#variables.rsPOs.SchoolId#",

"VendorId": "#variables.rsPOs.VendorId#",

"AccountCode": "#variables.rsPOs.AccountCode#",

"Amount": "#variables.rsPOs.Amount#",

"Attention": "#variables.rsPOs.Attention#",

"CategoryName": "#variables.rsPOs.CategoryName#",

"DateSent": "#variables.rsPOs.DateSent#",

"ItemCount": "#variables.rsPOs.ItemCount#",

"PONumber": "#variables.rsPOs.PONumber#",

"SchoolName": "#variables.rsPOs.SchoolName#"

"Status": "#variables.rsPOs.POStatus#",

"VendorName": "#variables.rsPOs.VendorName#",

"UserNumber": "#variables.rsPOs.UserNumber#",

"Updated": false

*/

declare @POs table (
```

```
POIdint null,

BidHeaderId int null,

... (truncated)
```

usp_getSDSDocsAll {sp-dbo-usp-getsdsdocsall}

> Retrieve record(s) from ugetSDSDocsAll

Property	Value
Schema	dbo
Created	2022-09-14 18:34:46.163000
Modified	2022-09-14 18:35:26.530000
Parameters	0

Definition

```
--exec usp_getSDSDocsUser 2687384

--exec usp_getSDSDocsSchool 16689

--exec usp_getSDSDocsDistrict 396

create   procedure [dbo].[usp_getSDSDocsAll]

as

begin

select String_Agg(cast(u.SafetyDataSheetId as varchar(max)),',') IdList

  from SafetyDataSheets u

end
```

usp_getSDSDocsDistrict {sp-dbo-usp-getsdsdocsdistrict}

> Retrieve record(s) from ugetSDSDocsDistrict

Property	Value
Schema	dbo
Created	2022-09-14 16:57:36.250000
Modified	2022-09-14 18:35:48.920000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@DistrictId	int	INPUT	District identifier

Definition

```
--exec usp_getSDSDocsUser 2687384

--exec usp_getSDSDocsSchool 16689

--exec usp_getSDSDocsDistrict 396

CREATE   procedure [dbo].[usp_getSDSDocsDistrict] @DistrictId int

as

begin

declare @urls table(url varchar(512), Id bigint null)



insert @urls(url)

select trim(CrossRefs.MSDSRef)

  from Detail

  join Requisitions on Requisitions.RequisitionId = Detail.RequisitionId

                   and Requisitions.DateEntered > dateadd(year,-5,getdate())

  join Users on Users.UserId = Requisitions.UserId

            and Users.Active = 1

  join School on School.SchoolId = Users.SchoolId

 and School.DistrictId = @DistrictId

             and School.Active = 1

  join Budgets on Budgets.BudgetId = Requisitions.BudgetId

  join CrossRefs on CrossRefs.CrossRefId = Detail.CrossRefId

                and CrossRefs.MSDSRef like 'http%'

 group by trim(CrossRefs.MSDSRef)
```

```
insert @urls(url)

select trim(BidResults.SDS_URL)

... (truncated)
```

usp_getSDSDocsSchool {sp-dbo-usp-getsdsdocsschool}

> Retrieve record(s) from ugetSDSDocsSchool

Property	Value
Schema	dbo
Created	2022-09-14 16:53:18.677000
Modified	2022-09-14 18:36:37.433000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@SchoolId	int	INPUT	School identifier

Definition

```
--exec usp_getSDSDocsUser 2687384

CREATE   procedure [dbo].[usp_getSDSDocsSchool] @SchoolId int

as

begin

declare @urls table(url varchar(512), Id bigint null)



insert @urls(url)

select trim(CrossRefs.MSDSRef)

  from Detail

  join Requisitions on Requisitions.RequisitionId = Detail.RequisitionId

                   and Requisitions.DateEntered > dateadd(year,-5,getdate())

  join Users on Users.UserId = Requisitions.UserId

            and Users.Active = 1

  join School on School.SchoolId = Users.SchoolId

             and School.SchoolId = @SchoolId

  join Budgets on Budgets.BudgetId = Requisitions.BudgetId

  join CrossRefs on CrossRefs.CrossRefId = Detail.CrossRefId

                and CrossRefs.MSDSRef like 'http%'

 group by trim(CrossRefs.MSDSRef)
```

```
insert @urls(url)

select trim(BidResults.SDS_URL)

  from Detail
```

```
    join Requisitions on Requisitions.RequisitionId = Detail.RequisitionId

                    and Requisitions.DateEntered > dateadd(year,-5,getdate())

  ... (truncated)
```

usp_getSDSDocsUser {sp-dbo-usp-getsdsdocsuser}

> Retrieve record(s) from ugetSDSDocs

Property	Value
Schema	dbo
Created	2022-09-14 16:48:46.587000
Modified	2022-09-14 18:36:11.577000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@UserId	int	INPUT	User identifier

Definition

```
--exec usp_getSDSDocsUser 2687384

CREATE   procedure [dbo].[usp_getSDSDocsUser] @UserId int

as

begin

declare @urls table(url varchar(512), Id bigint null)



insert @urls(url)

select trim(CrossRefs.MSDSRef)

  from Detail

  join Requisitions on Requisitions.RequisitionId = Detail.RequisitionId

                   and Requisitions.DateEntered > dateadd(year,-5,getdate())

  join Users on Users.UserId = Requisitions.UserId

            and Users.UserId = @UserId

  join Budgets on Budgets.BudgetId = Requisitions.BudgetId

  join CrossRefs on CrossRefs.CrossRefId = Detail.CrossRefId

                and CrossRefs.MSDSRef like 'http%'

 group by trim(CrossRefs.MSDSRef)



insert @urls(url)

select trim(BidResults.SDS_URL)
```

```
  from Detail

  join Requisitions on Requisitions.RequisitionId = Detail.RequisitionId

                   and Requisitions.DateEntered > dateadd(year,-5,getdate())
```

```
    join Users on Users.UserId = Requisitions.UserId

              and Users.UserId = @UserId

  ... (truncated)
```

usp_getSDSheets {sp-dbo-usp-getsdsheets}

> Retrieve record(s) from ugetSDSheets

Property	Value
Schema	dbo
Created	2022-08-08 07:59:20.680000
Modified	2022-08-08 07:59:48.130000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@districtId	int	INPUT	district identifier
2	@SchoolId	int	INPUT	School identifier
3	@UserId	int	INPUT	User identifier

Definition

```
create   procedure usp_getSDSheets @districtId int, @SchoolId int, @UserId int as

begin

    select coalesce(bi.SafetyDataSheetId, xr.SafetyDataSheetId) SafetyDataSheetId, ItemId

            --,RequisitionNumber

        from Detail

        join Requisitions on Requisitions.RequisitionId = Detail.RequisitionId

        join Budgets on Budgets.BudgetId = Requisitions.BudgetId

                    and Budgets.DistrictId = @districtId

                    and cast(left(Budgets.Name,4) as int) > year(getdate()) - 7

        outer apply (select SafetyDataSheets.SafetyDataSheetId

                    from CrossRefs

                    join SafetyDataSheets on SafetyDataSheets.SDSURL = CrossRefs.MSDSRef

                    where CrossRefs.CrossRefId = Detail.CrossRefId) xr

        outer apply (select SafetyDataSheets.SafetyDataSheetId

                    from BidItems

                    join BidResults on BidResults.BidResultsId = BidItems.BidResultsId

                    join SafetyDataSheets on SafetyDataSheets.SDSURL = BidResults.SDS_URL

                    where BidItems.BidItemId = Detail.BidItemId) bi

    where coalesce(bi.SafetyDataSheetId, xr.SafetyDataSheetId) is not null

      and Requisitions.UserId = case when coalesce(@UserId,0) = 0 then Requisitions.Use...

      and Requisitions.SchoolId = case when coalesce(@SchoolId,0) = 0 then Requisitions...

    group by coalesce(bi.SafetyDataSheetId, xr.SafetyDataSheetId), ItemId

end
```

usp_getSDSItems {sp-dbo-usp-getsdsitems}

> Retrieve record(s) from ugetSDSs

Property	Value
Schema	dbo
Created	2022-08-03 12:32:01.713000
Modified	2022-08-08 07:59:48.233000
Parameters	0

Definition

```
create   procedure usp_getSDSItems as

begin

    select i.ItemId

        ,SDS_URL

        ,id.ItemDescription

        ,coalesce(ItemImage,'') as ItemImage

        ,ItemCode

        ,coalesce(a.Manufacturer,i.BrandName,'') as BrandName

        ,coalesce(a.ManufacturerPartNumber,i.[ManufacturorNumber],'') as [ManufacturorN...

    from Items i

    join vw_ItemDescription id on id.ItemId = i.ItemId

    join (

        select ItemId = cast(ItemId as char(20))

                ,SDS_URL as SDS_URL

                ,[ImageURL] as ItemImage

                ,ManufacturerBid as Manufacturer

                ,ManufPartNoBid as ManufacturerPartNumber

        from dbo.BidResults

--        ${strSDSUrls && `where SDS_URL in (${strSDSUrls})`}

        Union

        select ItemId = cast(ItemId as char(20))

                ,MSDSRef as SDS_URL

                ,[ImageURL] as ItemImage
```

```
                    ,Manufacturor as Manufacturer

                    ,ManufacturorPartNumber as ManufacturerPartNumber

  ... (truncated)
```

usp_GetSDSURLs {sp-dbo-usp-getsdsurls}

> Retrieve record(s) from uGetSDSURLs

Property	Value
Schema	dbo
Created	2021-06-07 12:38:34.817000
Modified	2021-07-23 14:19:40.913000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@IdList	utv_IdsList	INPUT	Id list/array

Definition

```
create     procedure [dbo].[usp_GetSDSURLs] @IdList utv_IdsList readonly

as

begin

declare @PassedIdCount int



select @PassedIdCount = count(*) from @IDList



insert SafetyDataSheets(sdsURL, Seq)

  select trim(CrossRefs.MSDSRef), CHECKSUM(HASHBYTES('SHA2_512',trim(CrossRefs.MSDSRef)))

    from BidHeaders

join BidImports on BidImports.BidHeaderId = BidHeaders.BidHeaderId

               and BidImports.Active = 1

join BidImportCatalogList on BidImportCatalogList.BidImportId = BidImports.BidImportId

join Catalog on Catalog.CatalogId = BidImportCatalogList.CatalogId

            and Catalog.Active = 1

join CrossRefs on CrossRefs.CatalogId = Catalog.CatalogId

              and CrossRefs.Active = 1

  and CrossRefs.MSDSRef like 'http%'

left outer join SafetyDataSheets il on il.SDSURL = trim(CrossRefs.MSDSRef)

   where BidHeaders.EffectiveUntil > getdate()

     and il.SafetyDataSheetId is null

   group by trim(CrossRefs.MSDSRef), CHECKSUM(HASHBYTES('SHA2_512',trim(CrossRefs.MSDS...
```

```
insert SafetyDataSheets(sdsURL, Seq)

  select trim(BidResults.SDS_URL), CHECKSUM(HASHBYTES('SHA2_512',trim(BidResults.SDS_U...

... (truncated)
```

usp_GetVendorPricing {sp-dbo-usp-getvendorpricing}

> Retrieve record(s) from uGetPricing

Property	Value
Schema	dbo
Created	2021-03-31 09:15:55.260000
Modified	2021-03-31 09:15:55.260000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pBidHeaderId	int	INPUT	p Bid Header identifier

Definition

```
--exec usp_SetPricing 9336

--exec [dbo].[usp_SearchItemsByReqHKDS] 50484832,541,0,'9736890',0,0

--exec [dbo].[usp_SearchItemsByReqHKDS] 50484832,3,0,'110806',0,0

create   procedure [dbo].[usp_GetVendorPricing] @pBidHeaderId int

as

begin



 --declare @pBidHeaderId int = 8647



create table #ItemTable (

Idint identity(1,1) not null primary key,

[CrossRefId] [int] NULL,

[CatalogId] [int] NULL,

[BidHeaderId] [int] NULL,

[HeadingId] [int] NULL,

[KeywordId] [int] NULL,

[CategoryId] [int] NULL,

[ItemId] [int] NULL,

[VendorId] [int] null,

[BidItemId] [int] NULL,
```

```
[DistrictId] [int] NULL,

[HeadingKeywordId] [bigint] NULL,

[BidPrice] [money] NULL,
```

```
[CatalogPrice] [money] NULL,

[DiscountRate] [numeric](9, 5) NULL,

... (truncated)
```

usp_ImportUser {sp-dbo-usp-importuser}

> Purchase order procedure for u

Property	Value
Schema	dbo
Created	2022-02-17 17:00:24.037000
Modified	2022-02-26 10:11:50.210000
Parameters	11

Parameters

#	Parameter	Type	Direction	Description
1	@pDistrictId	int	INPUT	p District identifier
2	@pSchoolId	int	INPUT	p School identifier
3	@pUserNumber	int	INPUT	p User number
4	@pAttention	varchar(50)	INPUT	p Attention parameter
5	@pEmail	varchar(255)	INPUT	p email address
6	@pDistrictAccounti	varchar(50)	INPUT	p District Accounting code
7	@pApprovalLevel	int	INPUT	p Approval Level parameter
8	@pApproverNumbe	int	INPUT	p Approver number
9	@pAccountCode	varchar(50)	INPUT	p Account code
10	@pAllocation	money	INPUT	p Allocation parameter
11	@pAllowMSRP	int	INPUT	p Allow MSRP parameter

Definition

```
CREATE   procedure [dbo].[usp_ImportUser]

@pDistrictId int,

@pSchoolId int,

@pUserNumber int,

@pAttention varchar(50),

@pEmail varchar(255),

@pDistrictAccountingCode varchar(50),

@pApprovalLevel int,

@pApproverNumber int,

@pAccountCode varchar(50),

@pAllocation money,

@pAllowMSRP int

as

declare @DistrictId int,

@BudgetId int,

@SchoolId int,

@UserIdint,

@ApproverId int,

@RecCount int
```

```
set nocount on

begin transaction

begin try
```

```
    lineno 37  -- set this number based on create sproc script

-- Check for Valid District

... (truncated)
```

usp_MakeZ$ {sp-dbo-usp-makez$}

> Stored procedure: uMakeZ$

Property	Value
Schema	dbo
Created	2022-12-02 15:36:26.127000
Modified	2023-12-01 08:13:51.520000
Parameters	0

Definition

```
--exec [usp_MakeZ$]

CREATE   procedure [dbo].[usp_MakeZ$] as

declare @BidHeaderId int

--select * from Priceplans where Code like 'Z%'

declare bc cursor for

select BidHeaderId

  from BidHeaders

 where PriceplanId = 7

   and CategoryId = 4

   and dateadd(day,2,getdate()) between EffectiveFrom and EffectiveUntil

union

select BidHeaderId

  from BidHeaders

 where PriceplanId = 25

   and CategoryId != 4

   and dateadd(day,2,getdate()) between EffectiveFrom and EffectiveUntil



open bc



fetch next from bc into @BidHeaderId



while @@FETCH_STATUS = 0

begin
```

```
print 'Copying Bid ' + cast(@BidHeaderId as varchar) + ' to Z$'

exec sp_BidCopyChangePP @BidHeaderId,1280564,1

... (truncated)
```

usp_MakeZC {sp-dbo-usp-makezc}

> Stored procedure: uMakeZC

Property	Value
Schema	dbo
Created	2022-12-02 15:35:16.937000
Modified	2022-12-03 20:51:20.270000
Parameters	0

Definition

```
CREATE   procedure [dbo].[usp_MakeZC] as

declare @BidHeaderId int,

@BidRequestItemId int

--select * from Priceplans where Code like 'Z%'

declare bc cursor for

select BidHeaderId

  from BidHeaders

 where PriceplanId = 1

   and getdate() between EffectiveFrom and EffectiveUntil



open bc



fetch next from bc into @BidHeaderId



while @@FETCH_STATUS = 0

begin

print 'Copying Bid ' + cast(@BidHeaderId as varchar) + ' to ZC'

exec sp_BidCopyChangePP @BidHeaderId,4,1



-- Award New Bid

exec sp_AwardBidHeader @BidHeaderId



-- Wait 2 Minutes
```

```
waitfor delay '00:02:00'



... (truncated)
```

usp_MissingHeaders {sp-dbo-usp-missingheaders}

> Stored procedure: uMissingHeaders

Property	Value
Schema	dbo
Created	2019-09-05 09:35:55.580000
Modified	2019-09-05 09:35:55.580000
Parameters	0

Definition

```
create procedure usp_MissingHeaders as



select CSRep.Name, District.Name, Category.Name, Items.ItemCode, Items.Description, Uni...

  from Items

  join BidRequestItems on BidRequestItems.ItemId = Items.ItemId

  join BidHeaders on BidHeaders.BidHeaderId = BidRequestItems.BidHeaderId

                 and BidHeaders.EffectiveUntil > dateadd(year,-3,getdate())

  join District on District.DistrictId = Items.DistrictId

  join CSRep on CSRep.CSRepId = District.CsRepId

  join Units on Units.UnitId = Items.UnitId

  join Category on Category.CategoryId = Items.CategoryId

  left outer join Headings on Headings.HeadingId = Items.HeadingId

  left outer join Keywords on Keywords.KeywordId = Items.KeywordId

 where Items.DistrictId > 0

   and Items.Active = 1

   and (Headings.HeadingId is null or Headings.Title like 'Misc%')

 group by CSRep.Name, District.Name, Category.Name, Items.ItemCode, Items.Description, ...

 order by CSRep.Name, District.Name, Category.Name, Items.SortSeq
```

usp_mySDS {sp-dbo-usp-mysds}

> Stored procedure: umySDS

Property	Value
Schema	dbo

Created	2019-03-15 16:05:09.473000
Modified	2019-03-15 16:05:09.473000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@DistrictId	int	INPUT	District identifier
2	@ShippingId	int	INPUT	Shipping identifier

Definition

```
create   procedure usp_mySDS @DistrictId int, @ShippingId int

as



  select Detail.ItemId, ShipLocations.Name ShipLocation, Detail.Description

    into #myItems

from Detail

join Requisitions on Requisitions.RequisitionId = Detail.RequisitionId

and Requisitions.DateEntered > dateadd(year,-8,getdate())

join Budgets on Budgets.BudgetId = Requisitions.BudgetId

and Budgets.DistrictId = 204

left outer join ShipLocations on ShipLocations.ShippingId = Requisitions.ShippingId

   group by Detail.ItemId, ShipLocations.Name, Detail.Description





  select coalesce(ss.Description, s.Description, i.Description,'') AlternateDesc, coale...

    from #myItems mi

outer apply (select top 1 ri.AlternateDesc Description, ri.Manufacturer, MSDS.MSDSId, ...

        from RTK_ReportItems rri

        join RTK_Items ri on ri.RTK_ItemsId = rri.RTK_ItemsId

join MSDS on MSDS.MSDSId = ri.MSDSId

        join vw_DMSSDSDocuments on vw_DMSSDSDocuments.MSDSId = MSDS.MSDSId

        where rri.ItemId = mi.ItemId

        and rri.Year >= year(getdate()) - 7
```

```
          order by ri.Manufacturer desc) i

   outer apply (select SDSDocs.Description, SDSDocs.Manufacturer, SDSDocs.MSDSId, SDSDocs...

   ... (truncated)
```

usp_OrderEZVendors {sp-dbo-usp-orderezvendors}

> Order processing procedure for uEZs

Property	Value
Schema	dbo
Created	2019-03-19 13:42:03.770000
Modified	2025-09-18 15:12:44.180000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pRequisitionId	int	INPUT	p Requisition identifier
2	@ShowEDS	int	INPUT	Show EDS parameter

Definition

```
--exec usp_OrderEZVendors 55566873,1

CREATE   procedure [dbo].[usp_OrderEZVendors] @pRequisitionId int, @ShowEDS int

as

declare @BidHeaderId int, @DistrictId int, @CategoryId int

declare @BidsList as dbo.utv_BidsList;  -- table it TYPE'd in Programmability section

declare @VendorList table (VendorId int, CatalogId int, isEDS int, CategoryId int)



select @BidHeaderId = isnull(Requisitions.BidHeaderId,0), @DistrictId = Budgets.Distric...

  from Requisitions with (nolock)

  left outer join Budgets on Budgets.BudgetId = Requisitions.BudgetId

 where RequisitionId = @pRequisitionId



-- Build Base List of Bids for each Requisition

if @BidHeaderId is not null and @BidHeaderId != 0

begin

insert @BidsList (RequisitionId, BidHeaderId)

values (@pRequisitionId, @BidHeaderId)

end



-- Add All other bids needed to list
```

```
while @@rowcount != 0

begin

-- Add Parent PreBids
```

```
insert @BidsList (RequisitionId, BidHeaderId)

select Requisitions.RequisitionId, BidHeaders.BidHeaderId

... (truncated)
```

usp_POPrintExport {sp-dbo-usp-poprintexport}

> Purchase order procedure for uPrint

Property	Value
Schema	dbo
Created	2019-04-29 14:48:09.230000
Modified	2019-04-29 14:48:09.230000
Parameters	4

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pDistrictId	int	INPUT	p District identifier
3	@pBudgetId	int	INPUT	p Budget identifier
4	@pPOPrint	varchar(MAX)	INPUT	p POPrint parameter

Definition

```
create   procedure [dbo].[usp_POPrintExport] @pSessionId int, @pDistrictId int, @pBudge...

as

begin

declare @RequestDate datetime = getdate(),

@RSId int



insert ReportSession(ReportStarted) values(@RequestDate)

select @RSId = Scope_Identity()



insert ReportSessionLinks(RSId, IntId)

      select @RSId, PO.POId

  from SessionTable

  join Budgets on Budgets.BudgetId = @pBudgetId

  join District on District.DistrictId = Budgets.DistrictId

   and District.DistrictId = @pDistrictId

  join Requisitions on Requisitions.BudgetId = Budgets.BudgetId

  join PO on PO.RequisitionId = Requisitions.RequisitionId

  join openjson(@pPOPrint) with (POId int '$."POId"', Seq int '$."Seq"') poi on poi.P...

 where SessionTable.SessionId = @pSessionId

 order by poi.Seq



select @RSId RSId, cast(@@RowCount as varchar) + ' POs were printed/exported successfu...

end
```

usp_POStatusByRep {sp-dbo-usp-postatusbyrep}

> Purchase order procedure for uStatusByRep

Property	Value
Schema	dbo
Created	2021-04-21 15:27:48.283000
Modified	2021-04-21 17:44:45.303000
Parameters	0

Definition

```
create   procedure usp_POStatusByRep as

begin

declare @BaseYear int = year(getdate()) - 1,

@CurrentYear int = year(getdate()),

@NJGrowthFactor float = 0.0678,--0.10686128818636, --0.0678,

@NYGrowthFactor float = 0.1155,--0.06097285239229, --0.1155,

@NJPOFactor float = 1.3083,

@NYPOFactor float = 1.4331




select CSrep.Name RepName, Schedule.StateId, Schedule.Name ScheduleName, case when Requ...

       sum(case when Requisitions.DateEntered between cast('11/01/2016' as datetime) an...

   sum(POCountBase.Counter) PITPOs

  into #WorkList

  from Requisitions

  join Budgets on Budgets.BudgetId = Requisitions.BudgetId

  join District on District.DistrictId = Budgets.DistrictId

               and District.County != 'TEST'

   join CSRep on CSRep.CSRepId = District.CSRepId

  outer apply (select ScheduleTypes.StateId, ScheduleTypes.Name from ScheduleTypes wher...

  outer apply (select count(*) Counter from PO where PO.RequisitionId = Requisitions.Re...

  outer apply (select count(*) Counter from PO where PO.RequisitionId = Requisitions.Re...

 where Requisitions.DateEntered > cast('11/01/' + cast(@BaseYear - 1 as varchar) as dat...
```

```
    and coalesce(Requisitions.OrderType,1) = 1

  group by CSrep.Name, Schedule.StateId, Schedule.Name, case when Requisitions.DateEnter...

 ... (truncated)
```

usp_POStatusByState {sp-dbo-usp-postatusbystate}

> Purchase order procedure for uStatusByState

Property	Value
Schema	dbo
Created	2022-05-05 07:31:34.597000
Modified	2023-05-18 09:57:32.977000
Parameters	0

Definition

```
--exec usp_POStatusByState

CREATE     procedure [dbo].[usp_POStatusByState] as

begin

declare @BaseYear int = year(getdate()) - 1,

@CurrentYear int = year(getdate()),

@NJGrowthFactor float = 0.0678,--0.10686128818636, --0.0678,

@NYGrowthFactor float = 0.1155,--0.06097285239229, --0.1155,

@NJPOFactor float = 1.3083,

@NYPOFactor float = 1.4331



create table #WorkList (

StateIdint null,

ScheduleNamevarchar(50) null,

[Year]int null,

Reqsint null,

POsint null,

PITReqsint null,

PITSubmittedReqs int null,

PITPOsint null)


-- Get Base Year Numbers

insert #WorkList (StateId, ScheduleName, [Year], Reqs, POs, PITReqs, PITSubmittedReqs, ...

select Schedule.StateId, Schedule.Name ScheduleName,
```

```
        @BaseYear [Year], count(*) Reqs, sum(POCount.Counter) POs,

        sum(case

... (truncated)
```

usp_POStatusUpdates {sp-dbo-usp-postatusupdates}

> Purchase order procedure for uStatusUpdates

Property	Value
Schema	dbo
Created	2019-07-17 15:25:13.507000
Modified	2023-06-30 13:58:00.010000
Parameters	4

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pDistrictId	int	INPUT	p District identifier
3	@pBudgetId	int	INPUT	p Budget identifier
4	@pPOStatusUpdate	varchar(MAX)	INPUT	p POStatus Updates parameter

Definition

```
CREATE     procedure [dbo].[usp_POStatusUpdates] @pSessionId int, @pDistrictId int, @pB...

as

begin

declare @POCount int,

@RequestDate datetime = getdate()



insert POStatus(POId, StatusId, UserId)

      select PO.POId, poi.POStatus, SessionTable.UserId

  from SessionTable

  join Budgets on Budgets.BudgetId = @pBudgetId

  join District on District.DistrictId = Budgets.DistrictId

   and District.DistrictId = @pDistrictId

  join Requisitions on Requisitions.BudgetId = Budgets.BudgetId

  join PO on PO.RequisitionId = Requisitions.RequisitionId

  join openjson(@pPOStatusUpdates) with (POId int '$."POId"',

                                          POStatus int '$."POStatus"') poi on poi.POId...

 where SessionTable.SessionId = @pSessionId

 group by PO.POId, poi.POStatus, SessionTable.UserId



select @POCount = @@Rowcount

select cast(@POCount as varchar) + ' PO Statuses where Updated successfully' as Status

end
```

usp_QueuePOsToSend {sp-dbo-usp-queuepostosend}

> Purchase order procedure for usToSend

Property	Value
Schema	dbo
Created	2019-06-10 11:24:30.497000
Modified	2025-06-04 15:27:29.560000
Parameters	6

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pDistrictId	int	INPUT	p District identifier
3	@pBudgetId	int	INPUT	p Budget identifier
4	@pRequestedDeliv	date	INPUT	p Requested Delivery date
5	@pPOComments	varchar(4096)	INPUT	p POComments parameter
6	@pPOSend	varchar(MAX)	INPUT	p POSend parameter

Definition

```
CREATE       procedure [dbo].[usp_QueuePOsToSend] @pSessionId int, @pDistrictId int, @p...

as

begin

declare @POCount int,

@RequestDate datetime = getdate()



--insert DebugMsgs(Msg) values ('SessionId=' + isnull(cast(@pSessionId as varchar),'<n...

--insert DebugMsgs(Msg) values ('POSend=' + isnull(left(@pPOSend,1000),'<null>'))



begin transaction



/* Create Queue Entry for Each Vendor */

insert POQueue(UserId, VendorId, SessionId, RequestDate, EarliestDeliveryDate, Request...

  select SessionTable.UserId, PO.VendorId, Sessiontable.SessionId, @RequestDate, /*dat...

  from SessionTable

  join Budgets on Budgets.BudgetId = @pBudgetId

  join District on District.DistrictId = Budgets.DistrictId

               and District.DistrictId = @pDistrictId

  join Requisitions on Requisitions.BudgetId = Budgets.BudgetId

  join PO on PO.RequisitionId = Requisitions.RequisitionId

  join Vendors on Vendors.VendorId = PO.VendorId

             and Vendors.AllowElectronicPOs = 1

  join openjson(@pPOSend) with (POId int '$."POId"') poi on poi.POId = PO.POId
```

```
    outer apply (select POQueueItems.POQueueItemId

                    from POQueueItems

  ... (truncated)
```

usp_RestoreBidHeaderNumber {sp-dbo-usp-restorebidheadernumber}

> Bid header management for uRestoreNumber

Property	Value
Schema	dbo
Created	2015-12-03 00:16:55.067000
Modified	2015-12-03 00:41:19.630000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@OldBidHeaderId	int	INPUT	Old Bid Header identifier

Definition

```
CREATE procedure [dbo].[usp_RestoreBidHeaderNumber] @OldBidHeaderId int

as

begin



begin Transaction



set identity_insert BidHeaders on

insert BidHeaders (Active, AlertLink, AlertMsg, AllowAdditionalManufacturers, AllowAddi...

  select bhr.Active, bhr.AlertLink, bhr.AlertMsg, bhr.AllowAdditionalManufacturers, bhr...

    from edsrestore.dbo.BidHeaders bhr

    left outer join EDS.dbo.BidHeaders bhc on bhc.BidHeaderId = bhr.BidHeaderId

   where bhr.BidHeaderId = @OldBidHeaderId

     and bhc.BidHeaderId is null

set identity_insert BidHeaders off



set identity_insert BidHeaderDetail on

insert BidHeaderDetail (BidHeaderDetailId, BidHeaderId, BidRequestItemId, DateAdded, De...

  select r.BidHeaderDetailId, r.BidHeaderId, r.BidRequestItemId, r.DateAdded, r.DetailI...

    from edsrestore.dbo.BidHeaderDetail r

    left outer join EDS.dbo.BidHeaderDetail c on c.BidHeaderDetailId = r.BidHeaderDetailId

 where r.BidHeaderId = @OldBidHeaderId

   and c.BidHeaderDetailId is null

set identity_insert BidHeaderDetail off
```

```
set identity_insert BidRequestItems on

... (truncated)
```

usp_SavePositionData {sp-dbo-usp-savepositiondata}

> Save (insert or update) record in uSavePositionData

Property	Value
Schema	dbo
Created	2025-04-21 20:52:26.047000
Modified	2025-04-21 20:52:26.047000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@UserId	int	INPUT	User identifier
2	@PositionData	nvarchar(4000)	INPUT	Position Data parameter

Definition

```
create   procedure [dbo].[usp_SavePositionData] @UserId int, @PositionData nvarchar(4000)

as

Update Users

   set PositionData = @PositionData

  from Users

 where UserId = @UserId
```

usp_SDSDocs {sp-dbo-usp-sdsdocs}

> Stored procedure: uSDSDocs

Property	Value
Schema	dbo
Created	2019-02-21 12:45:25.227000
Modified	2025-07-24 16:03:22.303000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@pItemId	int	INPUT	p Item identifier
2	@pDetailId	int	INPUT	p Detail identifier
3	@pBidHeaderId	int	INPUT	p Bid Header identifier

Definition

```
--exec usp_SDSDocs 13573286,null,12880

CREATE   procedure [dbo].[usp_SDSDocs] @pItemId int, @pDetailId int, @pBidHeaderId int ...

as

begin

declare @ItemId int = null,

@BidItemId int = null,

@CrossRefId int = null



declare @BidList table (

BidHeaderId int)



declare @Docs table (

Iduniqueidentifier null,

ItemIdint not null,

CrossRefIdint null,

MSDSIdint null,

[URL]varchar(1024) not null,

DocIduniqueidentifier null)



if @pItemId is null and @pDetailId is not null

begin

select @ItemId = Detail.ItemId,

@BidItemId = Detail.BidItemId,
```

```
  @CrossRefId = Detail.CrossRefId

    from Detail

  ... (truncated)
```

usp_SearchItems_SearchDataDB {sp-dbo-usp-searchitems-searchdatadb}

> Item management procedure for us_DataDB

Property	Value
Schema	dbo
Created	2019-10-16 07:14:11.507000
Modified	2019-10-16 07:35:16.450000
Parameters	6

Parameters

#	Parameter	Type	Direction	Description
1	@pRequisitionId	int	INPUT	p Requisition identifier
2	@pVendorId	int	INPUT	p Vendor identifier
3	@pHeadingId	bigint	INPUT	p Heading identifier
4	@pFilter	varchar(4096)	INPUT	p Filter parameter
5	@pDistrictId	int	INPUT	p District identifier
6	@pDSHeadingId	bigint	INPUT	p DSHeading identifier

Definition

```
--USE [EDS]

--GO

--/****** Object:  StoredProcedure [dbo].[usp_SearchItemsByReqHKDS]    Script Date: 3/5...

--SET ANSI_NULLS ON

--GO

--SET QUOTED_IDENTIFIER ON

--GO

--USE [EDS]

--GO

--/****** Object:  StoredProcedure [dbo].[usp_SearchItemsByReqHKDS]    Script Date: 1/1...

--SET ANSI_NULLS ON

--GO

--SET QUOTED_IDENTIFIER ON

--GO




--set nocount on

--select * from dbo.usp_SearchItemsByReqHKDS(24803674, 0, -1, '', 400, 78527) order by ...

--exec dbo.usp_SearchItemsByReqHKDS 44174806, 0, -1, '', 51, 0

----exec dbo.usp_SearchItemsByReqHKDS 50845401, 0, 0, '23604-1005', 400, -1

----select * from Requisitions where RequisitionId = 1715646

--declare @pRequisitionId int     = 50845401--44174806--50484832--35--8647--49415157

--declare @pVendorId int    = 0--541 --2198
```

```
--declare @pHeadingId BigInt    = 0

--declare @pFilter varchar(4096)  = 'pencil' --'TISSUE KLEENEX 100/BOX 28224'

... (truncated)
```

usp_SearchItemsByReqHKDS {sp-dbo-usp-searchitemsbyreqhkds}

> Item management procedure for usByReqHKDS

Property	Value
Schema	dbo
Created	2018-08-07 23:53:11.767000
Modified	2022-12-22 15:00:36.410000
Parameters	7

Parameters

#	Parameter	Type	Direction	Description
1	@pRequisitionId	int	INPUT	p Requisition identifier
2	@pVendorId	int	INPUT	p Vendor identifier
3	@pHeadingId	bigint	INPUT	p Heading identifier
4	@pFilter	varchar(4096)	INPUT	p Filter parameter
5	@pDistrictId	int	INPUT	p District identifier
6	@pDSHeadingId	bigint	INPUT	p DSHeading identifier
7	@QueryType	varchar(3)	INPUT	Query type

Definition

```
--USE [EDS]

--GO

--/****** Object:  StoredProcedure [dbo].[usp_SearchItemsByReqHKDS]    Script Date: 7/3...

--SET ANSI_NULLS ON

--GO

--SET QUOTED_IDENTIFIER ON

--GO



--exec dbo.usp_SearchItemsByReqHKDS 58609170, 9, 0, 'blue red colors', 400, 0, 'and'

--exec dbo.usp_SearchItemsByReqHKDS 56371080, 0, -1, 'gloves', 505, 0

----exec dbo.usp_SearchItemsByReqHKDS 50845401, 0, 0, '23604-1005', 400, -1

----select * from Requisitions where RequisitionId = 1715646  ; select * from school wh...

--  select * from [SearchData].[dbo].[PricingConsolidated] where DistrictId = 604 BidHe...

--declare @pRequisitionId int     = 54336163

--declare @pVendorId int    = 0--8919--0--541 --2198

--declare @pHeadingId BigInt    = 0---1

--declare @pFilter varchar(4096)  = 'Copy Paper'  --'TISSUE KLEENEX 100/BOX 28224'

--declare @pDistrictId int    = 400

--declare @pDSHeadingId bigint    = 0-- 0--1521492941208

--declare @QueryType varchar(3)   = 'and'
```

```
--  exec dbo.usp_SearchItemsByReqHKDS 54335122,0,0,N'post-it notes',400,-1

--  exec dbo.usp_SearchItemsByReqHKDS 54335153,0,0,N'mop head',400,-1

--  exec dbo.usp_SearchItemsByReqHKDS 54335152,0,0,N'',400,-1
```

```
CREATE   procedure [dbo].[usp_SearchItemsByReqHKDS]

... (truncated)
```

usp_SearchItemsByReqHKDS_David {sp-dbo-usp-searchitemsbyreqhkds-david}

> Item management procedure for usByReqHKDS_David

Property	Value
Schema	dbo
Created	2020-04-16 11:47:58.260000
Modified	2020-04-16 11:47:58.260000
Parameters	6

Parameters

#	Parameter	Type	Direction	Description
1	@pRequisitionId	int	INPUT	p Requisition identifier
2	@pVendorId	int	INPUT	p Vendor identifier
3	@pHeadingId	bigint	INPUT	p Heading identifier
4	@pFilter	varchar(4096)	INPUT	p Filter parameter
5	@pDistrictId	int	INPUT	p District identifier
6	@pDSHeadingId	bigint	INPUT	p DSHeading identifier

Definition

```
--exec dbo.usp_SearchItemsByReqHKDSTest 54335122, 9, 0, 'blue', 400, 0

--exec dbo.usp_SearchItemsByReqHKDS 44174806, 0, -1, '', 51, 0

----exec dbo.usp_SearchItemsByReqHKDS 50845401, 0, 0, '23604-1005', 400, -1

----select * from Requisitions where RequisitionId = 1715646  ; select * from school wh...

--  select * from [SearchData].[dbo].[PricingConsolidated] where DistrictId = 604 BidHe...

--declare @pRequisitionId int     = 54407344--50484832--35--8647--49415157

--declare @pVendorId int    = 0--8919--0--541 --2198

--declare @pHeadingId BigInt    = 0---1

--declare @pFilter varchar(4096)  = 'floor cleaner'  --'TISSUE KLEENEX 100/BOX 28224'

--declare @pDistrictId int    = 400

--declare @pDSHeadingId bigint    = -1-- 0--1521492941208

--  exec dbo.usp_SearchItemsByReqHKDS 54335122,0,0,N'post-it notes',400,-1

--  exec dbo.usp_SearchItemsByReqHKDS 54335153,0,0,N'mop head',400,-1

--  exec dbo.usp_SearchItemsByReqHKDS 54335152,0,0,N'',400,-1



create   procedure [dbo].[usp_SearchItemsByReqHKDS_David] (@pRequisitionId int, @pVendo...

as

begin



--set nocount on

declare @UseElasticSearch tinyint = 1  -- [1= Use ElasticSEarch for string search]  [0 ...

If trim(@pFilter) = ''   -- if not using ElasticSearch then use old method

set @UseElasticSearch = 0
```

```
... (truncated)
```

usp_SearchItemsByReqHKDSDavid {sp-dbo-usp-searchitemsbyreqhkdsdavid}

> Item management procedure for usByReqHKDSDavid

Property	Value
Schema	dbo
Created	2020-06-09 16:03:49.093000
Modified	2020-06-09 17:20:06.727000
Parameters	6

Parameters

#	Parameter	Type	Direction	Description
1	@pRequisitionId	int	INPUT	p Requisition identifier
2	@pVendorId	int	INPUT	p Vendor identifier
3	@pHeadingId	bigint	INPUT	p Heading identifier
4	@pFilter	varchar(4096)	INPUT	p Filter parameter
5	@pDistrictId	int	INPUT	p District identifier
6	@pDSHeadingId	bigint	INPUT	p DSHeading identifier

Definition

```
--  select cast(794166624256 as bigint) & cast(0x7FFFFFFF as bigint)

--  select (cast(794166624256 as bigint) & cast(0x7FFFFFFF00000000 as bigint)) / cast(...



--select cast(HeadingId as bigint) * 0x100000000,* from searchData.dbo.PricingConsolida...

--exec dbo.usp_SearchItemsByReqHKDSDavid 54437909, 9, 0, 'blue', 400, 0

--exec dbo.usp_SearchItemsByReqHKDS 44174806, 0, -1, '', 51, 0

----exec dbo.usp_SearchItemsByReqHKDS 50845401, 0, 0, '23604-1005', 400, -1

----select * from Requisitions where RequisitionId = 1715646  ; select * from school wh...

--  select * from [SearchData].[dbo].[PricingConsolidated] where DistrictId = 604 BidHe...

--declare @pRequisitionId int     = 54407344--50484832--35--8647--49415157

--declare @pVendorId int    = 0--8919--0--541 --2198

--declare @pHeadingId BigInt    = 0---1

--declare @pFilter varchar(4096)  = 'floor cleaner'  --'TISSUE KLEENEX 100/BOX 28224'

--declare @pDistrictId int    = 400

--declare @pDSHeadingId bigint    = -1-- 0--1521492941208

--  exec dbo.usp_SearchItemsByReqHKDS 54335122,0,0,N'post-it notes',400,-1

--  exec dbo.usp_SearchItemsByReqHKDS 54335153,0,0,N'mop head',400,-1

--  exec dbo.usp_SearchItemsByReqHKDS 54335152,0,0,N'',400,-1



create   procedure [dbo].[usp_SearchItemsByReqHKDSDavid] (@pRequisitionId int, @pVendor...

as

--declare @pRequisitionId int = 54437909, @pVendorId int = 0, @pHeadingId bigint = 0, @...

begin
```

```
--set nocount on

... (truncated)
```

usp_SearchItemsByReqHKDSError {sp-dbo-usp-searchitemsbyreqhkdserror}

> Item management procedure for usByReqHKDSError

Property	Value
Schema	dbo
Created	2020-06-08 12:51:31.027000
Modified	2020-06-08 12:51:31.027000
Parameters	6

Parameters

#	Parameter	Type	Direction	Description
1	@pRequisitionId	int	INPUT	p Requisition identifier
2	@pVendorId	int	INPUT	p Vendor identifier
3	@pHeadingId	bigint	INPUT	p Heading identifier
4	@pFilter	varchar(4096)	INPUT	p Filter parameter
5	@pDistrictId	int	INPUT	p District identifier
6	@pDSHeadingId	bigint	INPUT	p DSHeading identifier

Definition

```
--exec dbo.usp_SearchItemsByReqHKDSTest 54335122, 9, 0, 'blue', 400, 0

--exec dbo.usp_SearchItemsByReqHKDS 44174806, 0, -1, '', 51, 0

--exec dbo.usp_SearchItemsByReqHKDS 54451189,0,78421,'Dry Erase Board',58,-1



----select * from Requisitions where RequisitionId = 1715646  ; select * from school wh...

--  select * from [SearchData].[dbo].[PricingConsolidated] where DistrictId = 604 BidHe...

--declare @pRequisitionId int     = 54451189--50484832--35--8647--49415157

--declare @pVendorId int    = 0--8919--0--541 --2198

--declare @pHeadingId BigInt    = 78421---1

--declare @pFilter varchar(4096)  = 'Dry Erase Board'  --'TISSUE KLEENEX 100/BOX 28224'

--declare @pDistrictId int    = 58

--declare @pDSHeadingId bigint    = -1-- 0--1521492941208

--  exec dbo.usp_SearchItemsByReqHKDS 54335122,0,0,N'post-it notes',400,-1

--  exec dbo.usp_SearchItemsByReqHKDS 54335153,0,0,N'mop head',400,-1

--  exec dbo.usp_SearchItemsByReqHKDS 54335152,0,0,N'',400,-1



create   procedure [dbo].[usp_SearchItemsByReqHKDSError] (@pRequisitionId int, @pVendor...

as

begin


--set nocount on

declare @UseElasticSearch tinyint = 1  -- [1= Use ElasticSEarch for string search]  [0 ...

If trim(@pFilter) = ''   -- if not using ElasticSearch then use old method
```

```
set @UseElasticSearch = 0



... (truncated)
```

usp_SearchItemsByReqHKDSTest {sp-dbo-usp-searchitemsbyreqhkdstest}

> Item management procedure for usByReqHKDSTest

Property	Value
Schema	dbo
Created	2018-12-12 10:51:27.980000
Modified	2019-06-26 14:50:48.210000
Parameters	6

Parameters

#	Parameter	Type	Direction	Description
1	@pRequisitionId	int	INPUT	p Requisition identifier
2	@pVendorId	int	INPUT	p Vendor identifier
3	@pHeadingId	bigint	INPUT	p Heading identifier
4	@pFilter	varchar(4096)	INPUT	p Filter parameter
5	@pDistrictId	int	INPUT	p District identifier
6	@pDSHeadingId	bigint	INPUT	p DSHeading identifier

Definition

```
--USE [EDS]

--GO

--/****** Object:  StoredProcedure [dbo].[usp_SearchItemsByReqHKDS]    Script Date: 3/5...

--SET ANSI_NULLS ON

--GO

--SET QUOTED_IDENTIFIER ON

--GO

--USE [EDS]

--GO

--/****** Object:  StoredProcedure [dbo].[usp_SearchItemsByReqHKDS]    Script Date: 1/1...

--SET ANSI_NULLS ON

--GO

--SET QUOTED_IDENTIFIER ON

--GO




--set nocount on

--select * from dbo.usp_SearchItemsByReqHKDSTest(51628105, 0, -1, '', 11478849, 1209569...

--exec dbo.usp_SearchItemsByReqHKDS 44174806, 0, -1, '', 51, 0

----exec dbo.usp_SearchItemsByReqHKDS 50845401, 0, 0, '23604-1005', 400, -1

----select * from Requisitions where RequisitionId = 1715646

--declare @pRequisitionId int     = 50845401--44174806--50484832--35--8647--49415157

--declare @pVendorId int    = 0--541 --2198
```

```
--declare @pHeadingId BigInt    = 0

--declare @pFilter varchar(4096)  = 'pencil' --'TISSUE KLEENEX 100/BOX 28224'

... (truncated)
```

usp_SearchVendors {sp-dbo-usp-searchvendors}

> Vendor management procedure for us

Property	Value
Schema	dbo
Created	2019-01-28 08:13:15.270000
Modified	2025-09-18 15:12:43.980000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pRequisitionId	int	INPUT	p Requisition identifier

Definition

```
--exec usp_SearchVendors 55566873

CREATE   procedure [dbo].[usp_SearchVendors] @pRequisitionId int

as

declare @BidHeaderId int

declare @BidsList as dbo.utv_BidsList;  -- table it TYPE'd in Programmability section

declare @VendorList table (VendorId int, CategoryId int)



select @BidHeaderId = isnull(Requisitions.BidHeaderId,0)

  from Requisitions with (nolock)

  left outer join Budgets on Budgets.BudgetId = Requisitions.BudgetId

 where RequisitionId = @pRequisitionId



-- Build Base List of Bids for each Requisition

if @BidHeaderId is not null and @BidHeaderId != 0

begin

insert @BidsList (RequisitionId, BidHeaderId)

values (@pRequisitionId, @BidHeaderId)

end



-- Add All other bids needed to list

while @@rowcount != 0

begin

-- Add Parent PreBids
```

```
insert @BidsList (RequisitionId, BidHeaderId)

select Requisitions.RequisitionId, BidHeaders.BidHeaderId

... (truncated)
```

usp_SetBidItemAIData {sp-dbo-usp-setbiditemaidata}

> Bid item processing for uSetAIData

Property	Value
Schema	dbo
Created	2025-07-10 10:02:05.567000
Modified	2025-11-03 15:47:21.440000
Parameters	6

Parameters

#	Parameter	Type	Direction	Description
1	@BidResultsId	int	INPUT	Bid Results identifier
2	@ProductNames	varchar(4000)	INPUT	Product Names parameter
3	@TypeAheads	varchar(4000)	INPUT	Type Aheads parameter
4	@ShortDescription	varchar(4000)	INPUT	Short description
5	@FullDescription	varchar(4000)	INPUT	Full description
6	@UNSPSC	varchar(20)	INPUT	UNSPSC parameter

Definition

```
CREATE   procedure [dbo].[usp_SetBidItemAIData] @BidResultsId int, @ProductNames varcha...

as

begin



-- Update First Item with new Data

 Update BidResults

   set ProductNames = @ProductNames,

       TypeAheads = @TypeAheads,

   AIShortDesc = @ShortDescription,

   AIFullDesc = @FullDescription,

   AIUNSPSC = @UNSPSC,

   AIDate = getdate()

  from BidResults with (rowlock,updlock)

 where BidResults.BidResultsId = @BidResultsId



-- Get List of Items to Update

Select BidResults.BidResultsId into #UpdateList

  from BidResults xr with (rowlock,updlock)

  join BidResults on BidResults.HashKey = xr.HashKey

                 and BidResults.Active = 1

 where xr.BidResultsId = @BidResultsId

   and xr.BidResultsId != BidResults.BidResultsId
```

```
/*

-- Update Everything that has the same HashKey

... (truncated)
```

usp_SetItemAIData {sp-dbo-usp-setitemaidata}

> Item management procedure for uSetAIData

Property	Value
Schema	dbo
Created	2025-04-27 18:21:27.653000
Modified	2025-07-11 15:08:50.277000
Parameters	6

Parameters

#	Parameter	Type	Direction	Description
1	@CrossRefId	int	INPUT	Cross Ref identifier
2	@ProductNames	varchar(4000)	INPUT	Product Names parameter
3	@TypeAheads	varchar(4000)	INPUT	Type Aheads parameter
4	@ShortDescription	varchar(4000)	INPUT	Short description
5	@FullDescription	varchar(4000)	INPUT	Full description
6	@UNSPSC	varchar(20)	INPUT	UNSPSC parameter

Definition

```
CREATE   procedure [dbo].[usp_SetItemAIData] @CrossRefId int, @ProductNames varchar(400...

as

begin

declare @SourceCatalogs table (

CatalogIdint not null primary key,

VendorIdint not null,

DatePosteddatetime)

declare @SavedHashKeyvarbinary(64)



select @SavedHashKey = CrossRefs.HashKey

  from CrossRefs with (nolock)

 where CrossRefs.CrossRefId = @CrossRefId



-- Update First Item with new Data

 Update CrossRefs

   set ProductNames = @ProductNames,

       TypeAheads = @TypeAheads,

   AIShortDesc = @ShortDescription,

   AIFullDesc = @FullDescription,

   AIUNSPSC = @UNSPSC,

   AIDate = getdate()

  from CrossRefs with (rowlock,updlock)

 where CrossRefs.CrossRefId = @CrossRefId
```

```
-- Build table of current Catalogs

... (truncated)
```

usp_SetPricing {sp-dbo-usp-setpricing}

> Stored procedure: uSetPricing

Property	Value
Schema	dbo
Created	2018-08-06 23:59:55.660000
Modified	2025-11-30 16:55:35.343000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pBidHeaderId	int	INPUT	p Bid Header identifier

Definition

```
--alter table SearchData_Test.dbo.PricingConsolidated add TotalQuantity int null

--exec usp_SetPricing 9336

--exec [dbo].[usp_SearchItemsByReqHKDS] 50484832,541,0,'9736890',0,0

--exec [dbo].[usp_SearchItemsByReqHKDS] 50484832,3,0,'110806',0,0

CREATE    procedure [dbo].[usp_SetPricing] @pBidHeaderId int

as

begin



 --declare @pBidHeaderId int = 8647



create table #ItemTable (

Idint identity(1,1) not null primary key,

[CrossRefId] [int] NULL,

[CatalogId] [int] NULL,

[BidHeaderId] [int] NULL,

[HeadingId] [int] NULL,

[KeywordId] [int] NULL,

[CategoryId] [int] NULL,

[ItemId] [int] NULL,

[VendorId] [int] null,
```

```
[BidItemId] [int] NULL,

[DistrictId] [int] NULL,

[HeadingKeywordId] [bigint] NULL,
```

```
[BidPrice] [money] NULL,

[CatalogPrice] [money] NULL,

... (truncated)
```

usp_SetPricing_SearchDataDB {sp-dbo-usp-setpricing-searchdatadb}

> Search procedure for uSetPricing_DataDB

Property	Value
Schema	dbo
Created	2019-10-16 07:17:55.180000
Modified	2019-11-01 12:45:14.770000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pBidHeaderId	int	INPUT	p Bid Header identifier

Definition

```
--exec usp_SetPricing 9336

--exec [dbo].[usp_SearchItemsByReqHKDS] 50484832,541,0,'9736890',0,0

--exec [dbo].[usp_SearchItemsByReqHKDS] 50484832,3,0,'110806',0,0

CREATE    procedure [dbo].[usp_SetPricing_SearchDataDB] @pBidHeaderId int

as

begin



 --declare @pBidHeaderId int = 8004



create table #ItemTable (

Idint identity(1,1) not null primary key,

[CrossRefId] [int] NULL,

[CatalogId] [int] NULL,

[BidHeaderId] [int] NULL,

[HeadingId] [int] NULL,

[KeywordId] [int] NULL,

[CategoryId] [int] NULL,

[ItemId] [int] NULL,

[VendorId] [int] null,

[BidItemId] [int] NULL,
```

```
[DistrictId] [int] NULL,

[HeadingKeywordId] [bigint] NULL,

[BidPrice] [money] NULL,
```

```
[CatalogPrice] [money] NULL,

[DiscountRate] [numeric](9, 5) NULL,

... (truncated)
```

usp_ShowItemURLs {sp-dbo-usp-showitemurls}

> Item management procedure for uShowURLs

Property	Value
Schema	dbo
Created	2019-07-29 15:10:09.020000
Modified	2019-07-29 15:11:17.870000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pItemId	int	INPUT	p Item identifier

Definition

```
create   procedure usp_ShowItemURLs @pItemId int

as

begin

create table #URLs (

Idint identity(1,1) not null primary key,

VendorIdint null,

CatalogIdint null,

UPCvarchar(20) null,

VendorItemCode varchar(50) null,

PackedCodevarchar(50) null,

ImageURLvarchar(300),

Datestampdatetime null

)



insert #URLs(VendorId, CatalogId, UPC, VendorItemCode, PackedCode, ImageURL, Datestamp)

  select Catalog.VendorId, Catalog.CatalogId, null, CrossRefs.VendorItemCode, CrossRefs...

    from CrossRefs

join Catalog on Catalog.CatalogId = CrossRefs.CatalogId

and Catalog.Active = 1

   where CrossRefs.ItemId = @pItemId

     and CrossRefs.ImageURL like 'http%'

 and CrossRefs.Active = 1
```

```
select *

  from #URLs

... (truncated)
```

usp_StartPOSend {sp-dbo-usp-startposend}

> Purchase order procedure for uStartSend

Property	Value
Schema	dbo
Created	2019-04-28 12:45:09.133000
Modified	2023-05-23 10:24:06.520000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pPOQueueId	int	INPUT	p POQueue identifier
2	@pPOId	int	INPUT	p PO identifier

Definition

```
CREATE   procedure [dbo].[usp_StartPOSend] @pPOQueueId int, @pPOId int

as

begin

declare @POQueueItemId int



select @POQueueItemId = POQueueItems.POQueueItemId

  from POQueue with (nolock)

  join POQueueItems on POQueueItems.POQueueId = POQueue.POQueueId

 where POQueue.POQueueId = @pPOQueueId

   and POQueueItems.POId = @pPOId

 order by POQueueItems.POQueueItemId



Update POQueueItems

   set SendStarted = getdate()

 where POQueueItemId = @POQueueItemId





select Vendors.UploadType, Vendors.UploadEmailList, Vendors.Name VendorName, District.N...

  from POQueueItems

  join POQueue on POQueue.POQueueId = POQueueItems.POQueueId

  join Vendors on Vendors.VendorId = POQueue.VendorId

  join PO on PO.POId = POQueueItems.POId

  join Requisitions on Requisitions.RequisitionId = PO.RequisitionId
```

```
    join Category on Category.CategoryId = Requisitions.CategoryId

    join School on School.SchoolId = Requisitions.SchoolId

  ... (truncated)
```

usp_StoreImage {sp-dbo-usp-storeimage}

> Stored procedure: uStoreImage

Property	Value
Schema	dbo
Created	2021-05-03 22:02:21.937000
Modified	2021-05-03 22:02:21.937000
Parameters	15

Parameters

#	Parameter	Type	Direction	Description
1	@imageURL	varchar(512)	INPUT	image URL
2	@imageActualURL	varchar(512)	INPUT	image Actual URL
3	@pHash	char(64)	INPUT	p Hash parameter
4	@imageSize	int	INPUT	image Size parameter
5	@imageFormat	varchar(20)	INPUT	image Format parameter
6	@width	int	INPUT	width parameter
7	@height	int	INPUT	height parameter
8	@imageSpace	varchar(20)	INPUT	image Space parameter
9	@channels	int	INPUT	channels parameter
10	@depth	varchar(20)	INPUT	depth parameter
11	@density	int	INPUT	density parameter
12	@statusCode	int	INPUT	status code
13	@statusText	varchar(512)	INPUT	status text
14	@contentType	varchar(50)	INPUT	content type

15	@headers	varchar(MAX)	INPUT	headers parameter

Definition

```
create   procedure [dbo].[usp_StoreImage] @imageURL varchar(512),

                                                @imageActualURL varchar(512),

 @pHash char(64),

 @imageSize int,

 @imageFormat varchar(20),

 @width int,

 @height int,

 @imageSpace varchar(20),

 @channels int,

 @depth varchar(20),

 @density int,

 @statusCode int,

 @statusText varchar(512),

 @contentType varchar(50),

 @headers varchar(max)

as

begin

declare @imageId bigint,

@imageLogId bigint
```

```
-- Look for having already uploaded Image

select top 1 @imageId = ImageId

  from Images

 where pHash = @pHash

   and (   ImageURL = @imageURL

... (truncated)
```

usp_StoreImageDone {sp-dbo-usp-storeimagedone}

> Stored procedure: uStoreImageDone

Property	Value
Schema	dbo
Created	2021-05-03 22:02:22.350000
Modified	2021-05-03 22:02:22.350000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@imageLogId	bigint	INPUT	image Log identifier
2	@writeStatus	int	INPUT	write status

Definition

```
create   procedure [dbo].[usp_StoreImageDone] @imageLogId bigint, @writeStatus int

as

begin



update ImageLog

   set WriteStatus = @writeStatus,

   WriteDate = getdate()

 where ImageLogId = @ImageLogId

end
```

usp_StoreImageError {sp-dbo-usp-storeimageerror}

> Stored procedure: uStoreImageError

Property	Value
Schema	dbo
Created	2021-05-03 22:02:22.643000
Modified	2021-05-03 22:02:22.643000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@imageURL	varchar(2048)	INPUT	image URL
2	@error	varchar(MAX)	INPUT	error parameter

Definition

```
create   procedure [dbo].[usp_StoreImageError] @imageURL varchar(2048), @error varchar(...

as

begin



insert ImageErrors(ImageURL, error)

  values(@imageURL, @error)

end
```

usp_StoreVendorOrder {sp-dbo-usp-storevendororder}

> Order processing procedure for uStore

Property	Value
Schema	dbo
Created	2025-06-06 19:51:03.117000
Modified	2025-07-25 11:35:56.227000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@VendorId	int	INPUT	Vendor identifier
2	@POId	int	INPUT	Purchase order identifier
3	@VendorData	nvarchar(MAX)	INPUT	Vendor Data parameter

Definition

```
CREATE   procedure [dbo].[usp_StoreVendorOrder] @VendorId int, @POId int, @VendorData n...

as

begin

declare @VendorOrderId int

declare @POLinesnvarchar(max),

@POStatusnvarchar(1024),

@RetMsgnvarchar(max)



select @RetMsg = ''



Insert VendorOrders(VendorId, POId, lastUpdated, VendorData)

values(@VendorId, @POId, getdate(), @VendorData)



Select @VendorOrderId = scope_identity()



-- Check for School Specialty

if @VendorId = 9

begin

-- Get Status JSON Data

Select top 1 @POStatus = json_Value(VendorOrders.VendorData, '$.status'),

@POLines = json_query(VendorOrders.VendorData,'$.lines')

  from VendorOrders

 where VendorOrders.POId = @POId
```

```
    order by VendorOrders.LastUpdated desc



  ... (truncated)
```

usp_TransactionLogMover {sp-dbo-usp-transactionlogmover}

> Move procedure for uTransactionr

Property	Value
Schema	dbo
Created	2025-03-09 16:36:24.617000
Modified	2025-04-06 12:08:31.603000
Parameters	0

Definition

```
--exec usp_TransactionLogMover

CREATE   procedure [dbo].[usp_TransactionLogMover] as

begin

declare @IdsToRemove table (SysId uniqueidentifier not null primary key)



set transaction isolation level read uncommitted

/*

declare @BOD datetime



select @BOD = cast(cast(getdate() as date) as datetime)



insert @IdsToRemove(SysId)

set transaction isolation level read uncommitted

select top 10000 tl.SysId

  from TransactionLogCF tl with (nolock)

  join TransactionLog_HISTORY tlh on tlh.SysId = tl.SysId

 where tl.RequestStart < @BOD

 order by tl.RequestStart



if @@ROWCOUNT > 0

begin

Delete tl

  from TransactionLogCF tl
```

```
    join @IdsToRemove idr on idr.SysId = tl.SysId

  end

  ... (truncated)
```

usp_UpdateBudgets {sp-dbo-usp-updatebudgets}

> Update existing record in uUpdateBudgets

Property	Value
Schema	dbo
Created	2019-09-05 09:27:02.500000
Modified	2019-09-05 09:29:49.367000
Parameters	0

Definition

```
CREATE   procedure [dbo].[usp_UpdateBudgets] as

declare@StartDate datetime,

@EndDate datetime



-- Build Start Date

if month(getdate()) >= 7

begin

  select @StartDate = convert(datetime,'07/01/' + convert(char(4),year(getdate()) + 1))

end

else

begin

  select @StartDate = convert(datetime,'07/01/' + convert(char(4),year(getdate())))

end



-- Build End Date

select @EndDate = convert(datetime,'06/30/' + convert(char(4),year(@Startdate) + 1) + '...



-- Update Existing Rows

Update bc

   set VisibleFrom = dateadd(year,1,bl.VisibleFrom),

       VisibleUntil = dateadd(year,1,bl.VisibleUntil),

   EditFrom = dateadd(year,1,bl.EditFrom),

   EditUntil = dateadd(year,1,bl.EditUntil),
```

```
    EarlyAccess = dateadd(year,1,bl.EarlyAccess),

    AnnualCutoff = dateadd(year,1,bl.AnnualCutoff)

  ... (truncated)
```

usp_UpdatePONextNumber {sp-dbo-usp-updateponextnumber}

> Update existing record in uUpdateNextNumber

Property	Value
Schema	dbo
Created	2019-08-08 19:37:13.187000
Modified	2024-04-11 21:59:10.680000
Parameters	8

Parameters

#	Parameter	Type	Direction	Description
1	@pDistrictId	int	INPUT	p District identifier
2	@pBudgetId	int	INPUT	p Budget identifier
3	@pPrefix	varchar(50)	INPUT	p Prefix parameter
4	@pNextNumber	int	INPUT	p Next number
5	@pSuffix	varchar(50)	INPUT	p Suffix parameter
6	@pSuppressLZ	int	INPUT	p Suppress LZ parameter
7	@pNumberLength	int	INPUT	p Number Length parameter
8	@pActualNumber	tinyint	INPUT	p Actual number

Definition

```
CREATE       procedure [dbo].[usp_UpdatePONextNumber] @pDistrictId int, @pBudgetId int,...

as

begin



if @pPrefix is not null or @pNextNumber is not null or @pSuffix is not null or @pSuppr...

begin

/* Update Next Number Info */

Update NextNumber

   set Prefix = @pPrefix,

   NextNumber = @pNextNumber,

   Suffix = @pSuffix,

   SuppressLZ = @pSuppressLZ,

   NumberLength = @pNumberLength,

   ActualNumber = @pActualNumber

 where IdType = 'P'

   and DistrictId = @pDistrictId

   and BudgetId = @pBudgetId



if @@rowcount = 0

begin
```

```
insert NextNumber(DistrictId, BudgetId, IDType, Prefix, NextNumber, Suffix, Suppress...

  select DistrictId, BudgetId, 'P', @pPrefix, @pNextNumber, @pSuffix, @pSuppressLZ, ...

from Budgets
```

```
    where Budgets.DistrictId = @pDistrictId

  and Budgets.BudgetId = @pBudgetId

 ... (truncated)
```

usp_UpdatePONumbers {sp-dbo-usp-updateponumbers}

> Update existing record in uUpdateNumbers

Property	Value
Schema	dbo
Created	2019-05-01 11:38:14.953000
Modified	2019-05-01 11:38:14.953000
Parameters	8

Parameters

#	Parameter	Type	Direction	Description
1	@pDistrictId	int	INPUT	p District identifier
2	@pBudgetId	int	INPUT	p Budget identifier
3	@pPOUploads	varchar(MAX)	INPUT	p POUploads parameter
4	@pPrefix	varchar(50)	INPUT	p Prefix parameter
5	@pNextNumber	int	INPUT	p Next number
6	@pSuffix	varchar(50)	INPUT	p Suffix parameter
7	@pSuppressLZ	int	INPUT	p Suppress LZ parameter
8	@pNumberLength	int	INPUT	p Number Length parameter

Definition

```
CREATE   procedure [dbo].[usp_UpdatePONumbers] @pDistrictId int, @pBudgetId int, @pPOUp...

as

begin

declare @POCount int



/* Update PO Numbers */

Update PO

   set PONumber = poi.PONumber

  from openjson(@pPOUploads)

  with (POId int '$."POId"',

        PONumber varchar(50) '$."PONumber"') poi

  join PO on PO.POId = poi.POId

  join Requisitions on Requisitions.RequisitionId = PO.RequisitionId

  join Budgets on Budgets.BudgetId = Requisitions.BudgetId

 where Budgets.DistrictId = @pDistrictId

   and Budgets.BudgetId = @pBudgetId



select @POCount = @@rowcount



if @pPrefix is not null or @pNextNumber is not null or @pSuffix is not null or @pSuppr...

begin

/* Update Next Number Info */

Update NextNumber
```

```
    set Prefix = @pPrefix,

    NextNumber = @pNextNumber,

... (truncated)
```

usp_validateRequisitionStatuses {sp-dbo-usp-validaterequisitionstatuses}

> Requisition procedure for uvalidateStatuses

Property	Value
Schema	dbo
Created	2023-09-25 17:22:49.813000
Modified	2023-09-25 17:22:49.813000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@RSID	int	INPUT	RS identifier

Definition

```
create   procedure usp_validateRequisitionStatuses @RSID int

as

begin

declare @Status varchar(50) = '',

@Message varchar(max) = '',

@Errors int,

@ReqList varchar(max) = '',

@Warnings int



select @Errors = count(*), @ReqList = String_Agg(Requisitions.RequisitionNumber, ', ')

  from Requisitions

  join ReportSessionLinks rsl on rsl.IntId = Requisitions.RequisitionId

                              and rsl.RSId = @RSId

  outer apply (Select Approvals.ApprovalId from Approvals where Approvals.RequisitionId...

 where Ap.ApprovalId is not null



if @@ROWCOUNT = 0

begin

Select @Status = 'error', @Message = 'No Requisitions were found.'

end
```

```
if @@ROWCOUNT > 0 and @Errors > 0

begin

Select @Status = 'error', @Message = 'Requisitions ' + @ReqList + ' were Printed for PO.'
```

```
end


... (truncated)
```

usp_VendorStatsCYvsLY {sp-dbo-usp-vendorstatscyvsly}

> Vendor management procedure for uStatsCYvsLY

Property	Value
Schema	dbo
Created	2021-04-12 16:26:29.430000
Modified	2025-05-08 16:15:38.140000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pVendorId	int	INPUT	p Vendor identifier
2	@DistrictLevel	int	INPUT	District Level parameter

Definition

```
--exec usp_VendorStatsCYvsLY 9,1

CREATE   procedure [dbo].[usp_VendorStatsCYvsLY] @pVendorId int, @DistrictLevel int = 0

as

begin

set transaction isolation level read uncommitted



declare @Week1Start0 datetime,

@Week1Start1 datetime,

@WeekNbr int,

@WeekStart0 datetime,

@WeekStart1 datetime,

@VendorId int,

@VendorName varchar(50),

@BudgetYear0 char(4),

@BudgetYear1 char(4),

@StartDate datetime,

@PriorSaturday datetime,

@Rundate datetime,

@LastYearBidDate datetime,

@ThisYearBidDate datetime
```

```
select @Rundate = CAST(cast(month(getdate()) as varchar(2)) + '/' + cast(day(getdate())...

select @PriorSaturday = case when datepart(weekday,@Rundate) <= 7 then dateadd(day,1-(d...
```

```
select @BudgetYear0 = cast(year(getdate())-1 as varchar),

... (truncated)
```

usp_WaitingTasks {sp-dbo-usp-waitingtasks}

> Stored procedure: uWaitingTasks

Property	Value
Schema	dbo
Created	2019-08-14 13:07:26.557000
Modified	2019-08-16 12:13:35.210000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pUserId	int	INPUT	p User identifier

Definition

```
--exec usp_WaitingTasks 194513



create   procedure usp_WaitingTasks @pUserId int

as

begin

create table #Tasks (

TaskId int identity(1,1) not null primary key,

DistrictIdint not null,

BudgetIdint null,

TaskNamevarchar(255) not null,

Priorityint null,

Quantityint null)





create table #UserList (

UserListId int identity(1,1) not null primary key,

TaskIdint not null,

UserIdint not null)



-- Find Districts that have Reqs at Ready to Bid

insert #Tasks (DistrictId, BudgetId, TaskName, Priority, Quantity)

  select District.DistrictId, Budgets.BudgetId, 'Requisitions Ready to Bid', 1, ReqStat...

from District with (nolock)
```

```
join Budgets on Budgets.DistrictId = District.DistrictId

and getdate() between Budgets.VisibleFrom and Budgets.VisibleUntil

... (truncated)
```

x_TestErrorHandling {sp-dbo-x-testerrorhandling}

> Stored procedure: x TestErrorHandling

Property	Value
Schema	dbo
Created	2016-04-27 22:11:28.560000
Modified	2016-04-27 22:37:36.787000
Parameters	0

Definition

```
-- ============================================

-- Author:sm

-- Create date: 4/26/16

-- Description:test error catching

-- ============================================

CREATE PROCEDURE [dbo].[x_TestErrorHandling]

-- Add the parameters for the stored procedure here



AS

BEGIN

Begin Try

RaisError('Forced error for testing',16,1);

End Try

Begin Catch

EXEC [Utility].[Log_ProcedureCall] @objectID = @@PROCID

End Catch

END
```

Schema: EDSIQWebUser

sp_CCAddAddendaItem_EDSIQWebuser

{sp-edsiqwebuser-sp-ccaddaddendaitem-edsiqwebuser}

> Item management procedure for CCAddAddenda_EDSIQWebuser

Property	Value
Schema	EDSIQWebUser
Created	2002-12-12 14:53:59.467000
Modified	2015-11-24 23:37:39.233000
Parameters	13

Parameters

#	Parameter	Type	Direction	Description
1	@pHeadingId	int	INPUT	p Heading identifier
2	@pKeywordId	int	INPUT	p Keyword identifier
3	@pDescription	varchar(1024)	INPUT	p description
4	@pUnitId	int	INPUT	p Unit identifier
5	@pBrandName	varchar(255)	INPUT	p Brand name
6	@pManufacturorNu	varchar(50)	INPUT	p Manufacturor number
7	@pVendorId	int	INPUT	p Vendor identifier
8	@pVendorPartNum	varchar(50)	INPUT	p Vendor Part number
9	@pItemsPerUnit	varchar(50)	INPUT	p Items Per Unit parameter
10	@pListPrice	money	INPUT	p List price
11	@pExtraDetail	varchar(1024)	INPUT	p Extra Detail parameter
12	@pRequisitionId	int	INPUT	p Requisition identifier
13	@pQuantity	int	INPUT	p quantity

Definition

```
CREATE procedure [EDSIQWebUser].[sp_CCAddAddendaItem_EDSIQWebuser] @pHeadingId int, @pK...

                                        @pUnitId int, @pBrandName varchar(255), @pManufac...

                                        @pVendorPartNumber varchar(50), @pItemsPerUnit va...

                                        @pRequisitionId int, @pQuantity int

as

declare @NextNumber varchar(50),

@DistrictCode varchar(16),

@DistrictId int,

@CategoryId int,

@ItemId int,

@UnitCode varchar(16),

@PricePlanId int,

@CatalogId int



  select @DistrictCode = District.DistrictCode,

         @DistrictId = District.DistrictId,

         @CategoryId = Requisitions.CategoryId,

         @CatalogId = Catalog.CatalogId

    from dbo.Requisitions

    join dbo.Users on Users.UserId = Requisitions.UserId

    join dbo.District on District.DistrictId = Users.DistrictId

    left outer join Catalog on Catalog.CategoryId = Requisitions.CategoryId

                            and Catalog.Active = 1
```

```
                                and Catalog.Name = 'EDS'

      where Requisitions.RequisitionId = @pRequisitionId

   ... (truncated)
```

sp_CCAddAddendaMaint {sp-edsiqwebuser-sp-ccaddaddendamaint}

> Stored procedure: CCAddAddendaMaint

Property	Value
Schema	EDSIQWebUser
Created	2003-05-16 12:59:52.123000
Modified	2015-11-24 23:37:42.797000
Parameters	13

Parameters

#	Parameter	Type	Direction	Description
1	@pHeadingId	int	INPUT	p Heading identifier
2	@pKeywordId	int	INPUT	p Keyword identifier
3	@pDescription	varchar(1024)	INPUT	p description
4	@pUnitId	int	INPUT	p Unit identifier
5	@pBrandName	varchar(255)	INPUT	p Brand name
6	@pManufacturorNu	varchar(50)	INPUT	p Manufacturor number
7	@pVendorId	int	INPUT	p Vendor identifier
8	@pVendorPartNuml	varchar(50)	INPUT	p Vendor Part number
9	@pItemsPerUnit	varchar(50)	INPUT	p Items Per Unit parameter
10	@pListPrice	money	INPUT	p List price
11	@pExtraDetail	varchar(1024)	INPUT	p Extra Detail parameter
12	@pDistrictId	int	INPUT	p District identifier
13	@pCategoryId	int	INPUT	p Category identifier

Definition

```
CREATE procedure [EDSIQWebUser].[sp_CCAddAddendaMaint] @pHeadingId int, @pKeywordId int...

                                        @pUnitId int, @pBrandName varchar(255), @pManufac...

                                        @pVendorPartNumber varchar(50), @pItemsPerUnit va...

                                        @pDistrictId int, @pCategoryId int

as

declare @NextNumber varchar(50),

@DistrictCode varchar(16),

@DistrictId int,

@CategoryId int,

@ItemId int,

@UnitCode varchar(16),

@PricePlanId int,

@CatalogId int



  select @DistrictCode = District.DistrictCode,

         @DistrictId = District.DistrictId

    from dbo.District

   where District.DistrictId = @pDistrictId



  if isnull(@DistrictCode,'') = ''

  begin

    select @DistrictCode = ''
```

```
    end


    select @CategoryId = Category.CategoryId,

  ... (truncated)
```

sp_CCUpdateAddendaItem_EDSIQWEBUSER {sp-edsiqwebuser-sp-ccupdateaddendaitem-edsiqwebuser}

> Item management procedure for CCUpdateAddenda_EDSIQWEBUSER

Property	Value
Schema	EDSIQWebUser
Created	2002-12-12 14:54:09.420000
Modified	2013-02-04 00:18:57.917000
Parameters	14

Parameters

#	Parameter	Type	Direction	Description
1	@pHeadingId	int	INPUT	p Heading identifier
2	@pKeywordId	int	INPUT	p Keyword identifier
3	@pDescription	varchar(1024)	INPUT	p description
4	@pUnitId	int	INPUT	p Unit identifier
5	@pBrandName	varchar(255)	INPUT	p Brand name
6	@pManufacturorNu	varchar(50)	INPUT	p Manufacturor number
7	@pVendorId	int	INPUT	p Vendor identifier
8	@pVendorPartNum	varchar(50)	INPUT	p Vendor Part number
9	@pItemsPerUnit	varchar(50)	INPUT	p Items Per Unit parameter
10	@pListPrice	money	INPUT	p List price
11	@pExtraDetail	varchar(1024)	INPUT	p Extra Detail parameter

12	@pRequisitionId	int	INPUT	p Requisition identifier
13	@pQuantity	int	INPUT	p quantity
14	@pDetailId	int	INPUT	p Detail identifier

Definition

```
CREATE      procedure EDSIQWebUser.sp_CCUpdateAddendaItem @pHeadingId int, @pKeywordId ...

                                        @pUnitId int, @pBrandName varchar(255), @pManufac...

                                        @pVendorPartNumber varchar(50), @pItemsPerUnit va...

                                        @pRequisitionId int, @pQuantity int, @pDetailId int

as

declare @ItemId int,

@BidItemId int,

@UnitCode varchar(16),

@PricePlanId int



  -- Get Detail Record Info

  select @ItemId = ItemId,

         @BidItemId = BidItemId

    from Detail with (nolock)

   where DetailId = @pDetailId



  -- Get Unit Code Description

  select @UnitCode = Code

    from Units with (nolock)

   where UnitId = @pUnitId



  if @@rowcount = 0

  begin
```

```
      select @UnitCode = ''

    end

  ... (truncated)
```

sp_CCUpdateAddendaMaint {sp-edsiqwebuser-sp-ccupdateaddendamaint}

> Stored procedure: CCUpdateAddendaMaint

Property	Value
Schema	EDSIQWebUser
Created	2003-05-16 13:01:59.263000
Modified	2015-11-24 23:37:29.050000
Parameters	12

Parameters

#	Parameter	Type	Direction	Description
1	@pHeadingId	int	INPUT	p Heading identifier
2	@pKeywordId	int	INPUT	p Keyword identifier
3	@pDescription	varchar(1024)	INPUT	p description
4	@pUnitId	int	INPUT	p Unit identifier
5	@pBrandName	varchar(255)	INPUT	p Brand name
6	@pManufacturorNu	varchar(50)	INPUT	p Manufacturor number
7	@pVendorId	int	INPUT	p Vendor identifier
8	@pVendorPartNum	varchar(50)	INPUT	p Vendor Part number
9	@pItemsPerUnit	varchar(50)	INPUT	p Items Per Unit parameter
10	@pListPrice	money	INPUT	p List price
11	@pExtraDetail	varchar(1024)	INPUT	p Extra Detail parameter
12	@pItemId	int	INPUT	p Item identifier

Definition

```
CREATE procedure [EDSIQWebUser].[sp_CCUpdateAddendaMaint] @pHeadingId int, @pKeywordId ...

                                        @pUnitId int, @pBrandName varchar(255), @pManufac...

                                        @pVendorPartNumber varchar(50), @pItemsPerUnit va...

                                        @pItemId int

as

declare @ItemId int,

@BidItemId int,

@UnitCode varchar(16),

@PricePlanId int



  -- Get Detail Record Info

  select @ItemId = ItemId

    from Items

   where ItemId = @pItemId



  -- Update Item

  Update Items

     set HeadingId = @pHeadingId,

         KeywordId = @pKeywordId,

         [Description] = @pDescription,

         UnitId = @pUnitId,

         BrandName = @pBrandName,
```

```
            ManufacturorNumber = @pManufacturorNumber,

            VendorId = @pVendorId,

            VendorPartNumber = @pVendorPartNumber,

   ... (truncated)
```

sp_CombineReqs {sp-edsiqwebuser-sp-combinereqs}

> Stored procedure: CombineReqs

Property	Value
Schema	EDSIQWebUser
Created	2003-01-08 20:30:11.700000
Modified	2009-03-25 06:55:28.363000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@pRSId	int	INPUT	p RS identifier
2	@pDelete	tinyint	INPUT	p Delete parameter
3	@rRequisitionId	int	OUTPUT	r Requisition identifier

Definition

```
CREATE        procedure EDSIQWebUser.sp_CombineReqs @pRSId int, @pDelete tinyint, @rReq...



-- Declare Local Variables

declare@RequisitionId int,

@DistrictId int,

@CategoryId int,

@SchoolId int,

@UserId int,

@BudgetId int,

@AccountId int,

@BudgetAccountId int,

@UserAccountId int,

@AccountCode varchar(30),

@Total money,

@TodaysDate datetime,

@Qty int,

@ItemId int,

@DetailId int,

@DelReqId int,

@rStatus int,

@SourceId int,

@StatusId int
```

```
-- Verify Session

select @TodaysDate = getdate()

... (truncated)
```

sp_CombineReqsNoDelete {sp-edsiqwebuser-sp-combinereqsnodelete}

> Stored procedure: CombineReqsNoDelete

Property	Value
Schema	EDSIQWebUser
Created	2003-06-03 12:45:57.357000
Modified	2009-03-25 06:55:28.457000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pRSId	int	INPUT	p RS identifier
2	@rRequisitionId	int	OUTPUT	r Requisition identifier

Definition

```
create procedure sp_CombineReqsNoDelete @pRSId int, @rRequisitionId int output as



-- Declare Local Variables

declare@RequisitionId int,

@DistrictId int,

@CategoryId int,

@SchoolId int,

@UserId int,

@BudgetId int,

@AccountId int,

@BudgetAccountId int,

@UserAccountId int,

@AccountCode varchar(30),

@Total money,

@TodaysDate datetime,

@Qty int,

@ItemId int,

@DetailId int,

@DelReqId int,

@rStatus int,

@SourceId int,

@StatusId int
```

```
-- Verify Session

select @TodaysDate = getdate()

... (truncated)
```

sp_ConvertReadyBatches {sp-edsiqwebuser-sp-convertreadybatches}

> Batch processing procedure for ConvertReadyes

Property	Value
Schema	EDSIQWebUser
Created	2003-02-11 19:54:47.873000
Modified	2009-03-25 06:55:28.600000
Parameters	0

Definition

```
CREATE  procedure sp_ConvertReadyBatches as


declare @BatchId int


declare CVCur cursor read_only for

select Batches.BatchId

  from Batches

  join BatchDetail on BatchDetail.BatchId = Batches.BatchId

 where Batches.ErrorCount = 0

   and Batches.Converted is null

   and Batches.BatchDate >= convert(datetime,'11/01/2002')

   and BatchDetail.OrigBookAmount is not null

 group by Batches.BatchId


open CVCur


fetch next from CVCur into @BatchId


while @@fetch_status = 0

begin

  print 'Converting Batch ' + convert(varchar(16),@BatchId)


  exec sp_BatchConvert 20638, @BatchId
```

```
    fetch next from CVCur into @BatchId

  ... (truncated)
```

sp_CopyReq {sp-edsiqwebuser-sp-copyreq}

> Copy procedure for Req

Property	Value
Schema	EDSIQWebUser
Created	2002-11-25 14:06:52.077000
Modified	2014-10-07 17:53:24.480000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pRequisitionId	int	INPUT	p Requisition identifier

Definition

```
CREATE procedure [EDSIQWebUser].[sp_CopyReq] @pRequisitionId int as



declare @NewReqId int,

@BudgetId int,

@DistrictId int,

@SchoolId int,

@UserId int,

@UserAccountId int,

@BudgetAccountId int,

@AccountCode varchar(50),

@CategoryId int,

@Attention varchar(50),

@TodaysDate datetime,

@AccountCount int,

@DontDeleteNoBids int,

@NewUserId int



set transaction isolation level read uncommitted

--begin transaction


-- Get Current Date

select @TodaysDate = getdate()
```

```
-- Get District Id

select @DistrictId = School.DistrictId,

... (truncated)
```

sp_CopyReqs {sp-edsiqwebuser-sp-copyreqs}

> Copy procedure for Reqs

Property	Value
Schema	EDSIQWebUser
Created	2003-06-30 12:55:48.217000
Modified	2009-03-25 06:55:28.427000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pReqList	varchar(255)	INPUT	p Req list/array

Definition

```
CREATE          procedure EDSIQWebUser.sp_CopyReqs @pReqList varchar(255) as



exec dbo.sp_CopyReqsBulk @pReqList

return



declare @ReqId int,

@ReqCount int,

@ReqList int



set transaction isolation level read uncommitted

select @ReqList = convert(int,@pReqList)

select @ReqCount = count(*) from ReportSessionLinks where RSId = @ReqList

insert DebugMsgs (Msg) values ('ReqList=' + convert(varchar(16),@ReqList) + ',' + @pReq...



declare ReqListCur cursor read_only for

/*select IntId from ReportSessionLinks where RSId = @ReqList*/

select IntId

  from ReportSessionLinks

  join Requisitions on Requisitions.RequisitionId = ReportSessionLinks.IntId

  join Users on Users.UserId = Requisitions.UserId

            and Users.Active = 1

 where RSId = @ReqList
```

```
open ReqListCur



... (truncated)
```

sp_CoverView {sp-edsiqwebuser-sp-coverview}

> Stored procedure: CoverView

Property	Value
Schema	EDSIQWebUser
Created	2003-01-09 15:10:55.607000
Modified	2009-03-25 06:55:28.473000
Parameters	0

Definition

```
CREATE  Procedure EDSIQWebUser.sp_CoverView AS



drop table CoverView



select *

  into CoverView

  from CoverViewSrc



select *

  from CoverView

 order by DistrictId, SchoolId, UserId
```

sp_DeleteDistrictBudgetPOs {sp-edsiqwebuser-sp-deletedistrictbudgetpos}

> Delete record from DeleteDistrictBudgets

Property	Value
Schema	EDSIQWebUser
Created	2002-08-14 11:59:37.500000
Modified	2009-03-25 06:55:28.677000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pDistrictId	int	INPUT	p District identifier
2	@pBudgetId	int	INPUT	p Budget identifier

Definition

```
create procedure sp_DeleteDistrictBudgetPOs @pDistrictId int, @pBudgetId int AS



declare @POIdint



declare POCur cursor fast_forward read_only for

select POId

  from PO

  join Requisitions on Requisitions.RequisitionId = PO.RequisitionId

  join School on School.SchoolId = Requisitions.SchoolId

             and School.DistrictId = @pDistrictId

 where Requisitions.BudgetId = @pBudgetId

 group by POId



open POCur



fetch next from POCur into @POId



while @@fetch_status = 0

begin

  exec sp_DeletePO @POId


  fetch next from POCur into @POId
```

```
end



close POCur

... (truncated)
```

sp_DeleteEmptyReqs {sp-edsiqwebuser-sp-deleteemptyreqs}

> Delete record from DeleteEmptyReqs

Property	Value
Schema	EDSIQWebUser
Created	2003-01-09 16:38:54.450000
Modified	2014-01-06 16:40:17.927000
Parameters	0

Definition

```
--select * from District where DistrictId = 263




CREATE     Procedure [EDSIQWebUser].[sp_DeleteEmptyReqs] AS



declare @RequisitionId int,

@rStatus int



insert DebugMsgs(Msg) values ('Deleting Empty Requisitions')



declare DelReqCur cursor fast_forward read_only for

select Requisitions.RequisitionId

  from Requisitions

  join Budgets on Budgets.BudgetId = Requisitions.BudgetId

              and Budgets.DistrictId != 263 -- Belleville

  left outer join Detail on Detail.RequisitionId = Requisitions.RequisitionId

  left outer join Approvals on Approvals.RequisitionId = Requisitions.RequisitionId

  left outer join ApprovalsHistory on ApprovalsHistory.RequisitionId = Requisitions.Req...

 where Detail.detailId is null

   and Approvals.ApprovalId is null

   and ApprovalsHistory.ApprovalId is null



open DelReqCur
```

```
fetch next from DelReqCur into @RequisitionId

... (truncated)
```

sp_DeletePOList {sp-edsiqwebuser-sp-deletepolist}

> Delete record from Delete

Property	Value
Schema	EDSIQWebUser
Created	2003-05-02 09:50:18.560000
Modified	2009-03-25 06:55:28.380000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pRSId	int	INPUT	p RS identifier

Definition

```
create procedure sp_DeletePOList @pRSId int AS



declare @POId int



declare dpocur cursor fast_forward read_only for

select PO.POId

  from PO

  join ReportSessionLinks on ReportSessionLinks.IntId = PO.POId

 where ReportSessionLinks.RSId = @pRSId



open dpocur



fetch next from dpocur into @POId



while @@fetch_status = 0

begin

  exec sp_DeletePO @POId



  fetch next from dpocur into @POId

end
```

```
close dpocur

deallocate dpocur
```

sp_DeleteRequisitionWithItems {sp-edsiqwebuser-sp-deleterequisitionwithitems}

> Delete record from DeleteWiths

Property	Value
Schema	EDSIQWebUser
Created	2003-03-13 11:26:51.937000
Modified	2009-03-25 06:55:28.753000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@pSessionId	int	INPUT	p Session identifier
2	@pRequisitionId	int	INPUT	p Requisition identifier
3	@rStatus	int	OUTPUT	r status

Definition

```
create procedure sp_DeleteRequisitionWithItems @pSessionId int, @pRequisitionId int, @r...



declare @ReqNumber varchar(255)



select Requisitions.RequisitionId

  from Requisitions

  left outer join PO on PO.RequisitionId = Requisitions.RequisitionId

 where Requisitions.RequisitionId = @pRequisitionId

   and PO.POId is null



if @@rowcount = 0

begin

  RETURN

end



exec sp_UpdateReq @pRequisitionId, null, null, null



delete Detail

 where RequisitionId = @pRequisitionId


delete Requisitions

 where RequisitionId = @pRequisitionId
```

```
select @rStatus = 0
```

sp_MultiBatchLoad {sp-edsiqwebuser-sp-multibatchload}

> Batch processing procedure for MultiLoad

Property	Value
Schema	EDSIQWebUser
Created	2002-09-23 10:28:01.700000
Modified	2015-11-24 23:37:34.047000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pCategory	char(1)	INPUT	p Category parameter
2	@pSourceFile	varchar(255)	INPUT	p Source File parameter

Definition

```
CREATE procedure [EDSIQWebUser].[sp_MultiBatchLoad] @pCategory char(1), @pSourceFile va...



declare @SQLStmt varchar(1024),

@BatchId int,

@Records int,

        @DistrictCode char(2)



print '**********************' + @pSourceFile + '**********************'



-- Create Temp Table

create table #ImportBatch (

DataRowvarchar(512),

RowIdint identity(1,1)

)



-- Build Load Ascii File into TempDB statement

select @SQLStmt = 'BULK INSERT #ImportBatch FROM ''' + @pSourceFile + ''' WITH (FORMATF...



execute(@SQLStmt)
```

```
declare BatchCur cursor fast_forward read_only for

  select substring(DataRow,1,2)

    from #ImportBatch
```

```
    group by substring(DataRow,1,2)



... (truncated)
```

sp_NightlyGarbageCollection {sp-edsiqwebuser-sp-nightlygarbagecollection}

> Stored procedure: NightlyGarbageCollection

Property	Value
Schema	EDSIQWebUser
Created	2002-11-22 06:50:37.590000
Modified	2009-03-25 06:55:28.690000
Parameters	0

Definition

```
create procedure sp_NightlyGarbageCollection AS



-- Delete Empty User Accounts

delete UserAccounts

  from UserAccounts

  left outer join (

    select Users.UserId

      from Users

      left outer join UserAccounts on UserAccounts.UserId = Users.UserId

     where Users.Active = 0

       and Users.CometId is null

       ) ss on ss.UserId = UserAccounts.UserId

  left outer join Requisitions on Requisitions.UserAccountId = UserAccounts.UserAccountId

 where Requisitions.RequisitionId is null

   and UserAccounts.Active = 0



-- Delete Empty Users

Delete Users

  from Users

  left outer join UserAccounts on UserAccounts.UserId = Users.UserId

  left outer join Requisitions on Requisitions.UserAccountId = UserAccounts.UserAccount...

 where Users.Active = 0

   and Users.CometId is null
```

sp_OrderBookCopy {sp-edsiqwebuser-sp-orderbookcopy}

> Order processing procedure for Book

Property	Value
Schema	EDSIQWebUser
Created	2002-12-19 16:06:48.450000
Modified	2015-11-24 23:37:41.007000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pOrderBookId	int	INPUT	p Order Book identifier

Definition

```
CREATE procedure [EDSIQWebUser].[sp_OrderBookCopy] @pOrderBookId int as



declare @OrderBookId int



insert dbo.OrderBooks (PricePlanDescription, Category, CategoryId, PricePlanId, AwardId...

  select 'Copy of ' + PricePlanDescription, Category, CategoryId, PricePlanId, AwardId,...

    from dbo.OrderBooks

   where OrderBookId = @pOrderBookId



select @OrderBookId = Scope_Identity() --DCH 11/24/2015 @@IDENTITY



insert dbo.OrderBookDetail (OrderBookId, Active, ItemId, BidItemId, Weight)

  select @OrderBookId, Active, ItemId, BidItemId, Weight

    from dbo.OrderBookDetail

   where OrderBookId = @pOrderBookId
```

sp_SavingsLetter {sp-edsiqwebuser-sp-savingsletter}

> Stored procedure: SavingsLetter

Property	Value
Schema	EDSIQWebUser
Created	2003-06-30 12:55:56.327000
Modified	2009-03-25 06:55:28.473000
Parameters	1

Parameters

#	Parameter	Type	Direction	Description
1	@pRSId	int	INPUT	p RS identifier

Definition

```
CREATE procedure EDSIQWebUser.sp_SavingsLetter (@pRSId int) as



declare @DistrictId int,

@CategoryId int,

@CategoryName varchar(50)



create table #CatTable (

DistrictIdint null,

CategoryIdint null,

DistrictNamevarchar(512) null,

CategoryNamevarchar(50) null,

UniqueItemsint null,

TotalItemsint null,

TotalBidCostmoney null,

TotalCatalogCost money null,

TotalStateContractCost money null,

StateContractDiscount decimal(9,5) null,

OverallDiscount decimal(9,5) null,

TotalSavingsmoney null,

CategoriesIncluded varchar(512) null,
```

```
CategoriesExcluded varchar(512) null,

AccountRepvarchar(50) null,

IncludedSavings money null,
```

```
IncludedDiscount decimal(9,5) null)


... (truncated)
```

sp_Sys3000ToWinCap {sp-edsiqwebuser-sp-sys3000towincap}

> Stored procedure: Sys3000ToWinCap

Property	Value
Schema	EDSIQWebUser
Created	2002-07-31 10:58:03.607000
Modified	2002-07-31 10:58:03.607000
Parameters	2

Parameters

#	Parameter	Type	Direction	Description
1	@pSourceFile	varchar(255)	INPUT	p Source File parameter
2	@pBidId	varchar(255)	INPUT	p Bid identifier

Definition

```
CREATE  procedure sp_Sys3000ToWinCap @pSourceFile varchar(255), @pBidId varchar(255)

AS



declare @InsertCmd varchar(255)



create table #NewFormat (

Type varchar(255) null,

RequestTypevarchar(255) null,

PONumbervarchar(255) null,

Vendorvarchar(255) null,

ItemDescription varchar(255) null,

Quantityvarchar(255) null,

UnitCostvarchar(255) null,

UnitMeasurevarchar(255) null,

Fundvarchar(255) null,

BudgetAccountvarchar(255) null,

PODescriptionvarchar(255) null,

OtherRefvarchar(255) null,

BlanketOrdervarchar(255) null,

BidIdvarchar(255) null,
```

```
Categoryvarchar(255) null,

ItemIdvarchar(255) null,

IssueDatevarchar(255) null,
```

```
Requestorvarchar(255) null,

POTable1varchar(255) null,

... (truncated)
```

Schema: utility

Log_ProcedureCall {sp-utility-log-procedurecall}

> Logging procedure for ProcedureCall

Property	Value
Schema	utility
Created	2016-04-27 23:15:10.387000
Modified	2016-04-27 23:15:10.387000
Parameters	3

Parameters

#	Parameter	Type	Direction	Description
1	@ObjectID	int	INPUT	Object identifier
2	@DatabaseID	int	INPUT	Database identifier
3	@AdditionalInfo	nvarchar(MAX)	INPUT	Additional Info parameter

Definition

```
CREATE PROCEDURE [utility].[Log_ProcedureCall]

 @ObjectID       INT,

 @DatabaseID     INT = NULL,

 @AdditionalInfo NVARCHAR(MAX) = NULL

AS

BEGIN

 SET NOCOUNT ON;



 DECLARE

  @ProcedureName NVARCHAR(400);



 SELECT

  @DatabaseID = COALESCE(@DatabaseID, DB_ID()),

  @ProcedureName = COALESCE

  (

   QUOTENAME(DB_NAME(@DatabaseID)) + '.'

   + QUOTENAME(OBJECT_SCHEMA_NAME(@ObjectID, @DatabaseID))

   + '.' + QUOTENAME(OBJECT_NAME(@ObjectID, @DatabaseID)),

   ERROR_PROCEDURE()

  );
```

```
 INSERT Utility.dbo.ProcedureLog

 (
```

```
    DatabaseID,

    ObjectID,

  ... (truncated)
```