EVIUM CHARGING

32A
Level 2
Charging Stations

FEATURES

- **Modern Compact Design:**
  EVSE from factor smaller than a standard sheet of letter-size paper.
- **Robust Construction, certified for outdoor use:**
  Tamper-resistant features; NEMA 4 certified for outdoor and indoor use.
- **Simple Operation:**
  EVSE models simply plug-in to EV and charge.
- **Network Options:**
  iEVSE and iEVSE Plus are OCPP 1.6 networked enabled charging stations to support access control, payment capability, remote management and control, demand response. Network connection via Wi-Fi; iEVSE Plus models also include 4G-LTE celular, RFID card reader and Local Load Management capability.
- **Cable Management**
  Standard Connector and Cable Holster included, optional cable management solutions available.

EVIUM CHARGING

(EVSE, IEVSE, IEVSE PLUS)

PRODUCT DESCRIPTION AND SPECIFICATIONS

OPTIONAL

Part Number	**EVOCHARGE EVSE**: EVC3AA0A2E1A1 (18 ft. charge cable) or EVC3AA0B2E1A1 (25 ft. charge cable) **EVOCHARGE iEVSE**: EVC3AB0A2E1A1 (18 ft. charge cable) or EVC3AB0B2E1A1 (25 ft. charge cable) **EVOCHARGE iEVSE Plus**: EVC3AC0B1E1A1 (25 ft. charge cable) **EV Cable Management System (optional)**: EVOREEL and retractor
Connector/EVSE Level	SAE J1772; AC Level 2
Max Output Rating	32A; 7.68 kW Maximum Output - For use with dedicated 40A (or greater) supply circuit.
Alternate Adjustable Output Settings	24A; 5.76 kW Maximum Output - For use with 30A circuit rating 16A; 3.84 kW Maximum Output - For use with 20A circuit rating.
Electrical Circuit/ Input Power Requirements	208-240VAC, 50/60 Hz., Single Phase, circuit requirement: Dedicated; Branch breaker: Double pole; Circuit Conductors: Line 1, Line 2, Earth ground.
Input Power Connection	**EVSE & iEVSE**: Plug-in, NEMA 6-50 plug (removable for harwire connection)); iEVSE Plus: Hardwire
Operational Ratings	NEMA 4, indoor/outdoor rated; Temp: -22°F to 122°F (-30°C to 50°C); Humidity: 95% RH
Mounting	Wall or pedestal installation
Dimensions	**EVSE**: 11 x 7.5 x 3.2 inches (28 x 19 x 8.1 cm)
Weight	**EVSE 18 ft.**: 14 lbs, **EVSE 25 ft.**: 16 lbs.
Display & Indicators	LED charge status indicators (power/ready, charging, fault)
Cable Management Type	Connector/Cable Holster (standard); EvoReel & Retractor Cable Management (optional)
Standards & Compliance	Charging Station: UL/cUL listed; SAE J1772, UL 355, CSA; EVOREEL: ETL/cETL

*Visit eviumcharging.com for more information or to download an installation manual