EVIUM CHARGING

40A EVSE
Level 2
Charging Stations

FEATURES

- **Modern Compact Design:**
  EVSE from factor smaller than a standard sheet of letter-size paper.
- **Robust Construction, certified for outdoor use:**
  Tamper-resistant features; NEMA 4 certified for outdoor and indoor use.
- **Smart Charging:**
  Connect via WiFi to manage charging stations. Evium app available for iEVSE Home Stations.
- **Cable Management:**
  Standard Connector and Cable Holster included, optional cable management solutions available.

EVIUM CHARGING

(IEVSE, IEVSE HOME)

PRODUCT DESCRIPTION AND SPECIFICATIONS

OPTIONAL

Part Number	**EVOCHARGE iEVSE 40**: EVC4012000 **EVOCHARGE iEVSE Home 40**: EVC4012001
Connector/EVSE Level	SAE J1772; AC Level 2
Max Output Rating	40A; 9.6 kW Maximum Output - For use with dedicated 50A (or greater) supply circuit.
Alternate Adjustable Output Settings	32A; 7.7 kW Maximum Output - For use with 40A circuit rating; 24A 5.76 kW Maximum Output - For use with 30A circuit rating; 16A 3.84 kW Maximum Output - For use with 20A circuit rating.
Electrical Circuit/ Input Power Requirements	208-240VAC, 50/60 Hz., Single Phase, circuit requirement: Dedicated; Branch breaker: Double pole; Circuit Conductors: Line 1, Line 2, Earth ground, 120VAC maximum from ground.
Input Power Connection	**iEVSE & iEVSE Home**: Plug-in, NEMA 6-50 plug (removable for harwire connection)
Operational Ratings	NEMA 4, indoor/outdoor rated; Temp: -22°F to 122°F (-30°C to 50°C); Humidity: 95% RH
Mounting	Wall or pedestal installation
Dimensions	**EVSE**: 11 x 7.5 x 3.2 inches (28 x 19 x 8.1 cm)
Weight	**EVSE 25 ft.**: 16 lbs.
Display & Indicators	LED charge status indicators (power/ready, charging, fault)
Cable Management Type	Connector/Cable Holster (standard); Retractor Cable Management (optional)
Standards & Compliance	Charging Station: UL/cUL listed; SAE J1772, UL 2594

*Visit eviumcharging.com for more information or to download an installation manual