EVIUM CHARGING

EVIUM
DC FAST CHARGER
60kW Series

FEATURES

- Powerful Compact All-in-One Charger
- Simple Air-Cooled Power Modules
- Easy to Maintain
- Parallel Charging Feature
- Available in 500VDC and 1000VDC
- OCPP 1.6J
- Credit Card Reader
- Cord Management

EVIUM CHARGING

DC FAST CHARGER SPECIFICATIONS

Intertek

Product Number	TP3-60-480	TP5-60-480
Input	480VAC (3P+N+PE) || 60Hz	
Output Voltage	150 - 500 VDC	150 - 1000 VDC
Output Current	0 to 150A	
FLA || Breaker Rating	80A || 100A	
Cyclic Charge Mode	CCS1 - 150A || CHAdeMO - 125A	
Parallel Charge Mode (Optionl)	30kW per Port	
Efficiency	>94% at nominal output power	
Connectors	CCS1 CCS1 and CCS1 CCS1 and CHAdeMO	
Power Factor	>0.98	
Display	10" touch screen	
Access Control	RFID: ISO/IEC 14443A/B | Credit Card Reader (Optional)	
Metering	DC kWh meter per each connector	
Operating temperature	-30°C to 55°C (-22°F to 131°F)	
Altitude	6,500' (2,000m)	
Working || Storage Humidity	≤ 95% RH || ≤ 99% RH (Non-condensing)	
Dimensions (L x D x H)	29" x 19" x 72"	
Protective Class	NEMA 3S (IP54), IK10	
Cooling System	Air Cooling fans	
Weight	530 lbs (240 kg)	
Compliance	UL and CE certified	
Charging Cable	16ft (5m), Cable Retractor Included	
Communication || Protocol	Ethernet, 4G/WiFi || OCPP 1.6J	
Electrical Safety: GFCI	RCD 20 mA Type A	
DC Charge System	Mode 4 - IEC-61851, ISO-15118, DIN 70121 Mode 4 - CHAdeMO 0.9, 1.0	
Electrical Safety: Surge Protection	20 kA	
Electrical Safety General	Over Voltage, Under Voltage, Over Current, Missing Ground	
Electrical Safety: Output Short	Output power disabled when output is short circuited	
Electrical Safety Temperature	Temperature Sensors @ Charge Coupler and Power Electronics	
Emergency Stop	Emergency stop buttom disables output power	
Regulatory Compliance	UL - 2202 || EMC: EN 61000-6-1:2007, EN 61000-6-3:2007 /A1:2011/AC:2012	

(323) 702 - 2400 www.eviumcharging.com david@eviumcharging.com