EVIUM CHARGING

AC

12kW 50a

50Amps | J1772 Dual Connector

(323) 702 - 2400
www.eviumcharging.com
david@eviumcharging.com

EVIUM CHARGING

AC CHARGER SPECIFICATIONS

12kW Model

Intertek

Rated Power	2 x 12kw
Product #	EV2W - 50 - 220 - J2
Input / Output voltage	208VAC - 240VAC, 60 / 50 Hz
Breaker	2 x 63A
Connectors	Dual
Output Current	Max 50A per Connector
Weight	~40 lbs. (charger) | ~16 lbs. (cable)
Working Temperature	-30°C to 55°C
Relative Humidity	5% to 95% Non-Condensing
Altitude	≤ 3000m
IP Rating	NEMA 3R
Connector Standard	SAE J1772 (16' Standard / 24' Optional)
RFID system	ISO/IEC 14443 A/B
Communication Protocol	OCPP 1.6J
Internet	Ethernet (Standard), 4G (Optional)
Meter Accuracy	1%
User interface	5'' Touch Screen
Installation Type	Wall Mount
Material	Galvanized steel
Dimensions	12'' x 17'' x 7'' (L x H x D)
Compliance standard	EN 61851 - 1:2011, EN 61000 - 6 - 1:2007, EN 61000 - 6 - 3:2007/A1:2011/AC:2012
Certification	CE, ETL
Safety	Over Current, Short Circuit , Surge Protection, Leakage Current Protection
Additional Information	Pedestal - Optional / Mounting Bracket & Holster are standard accessories