EVIUM CHARGING

# AC

## 19.2kW 80a

80Amps | J1772 Connector

(323) 702 - 2400 www.eviumcharging.com david@eviumcharging.com

EVIUM CHARGING

# AC CHARGER SPECIFICATIONS

19kW Model

Intertek

| | |
|---|---|
| Rated Power | 19.2kW |
| Product # | TP2W-80-220-J1 |
| Input / Output voltage | 208VAC - 240VAC, 60 / 50 Hz<br>80A continuous load with 100A branch circuit |
| Breaker | 100A |
| Connectors | Single |
| Output Current | 80A |
| Weight | ~35 lbs. (charger) \| ~8 lbs. (cable) |
| Working Temperature | -30°C to 55°C |
| Relative Humidity | 5% to 95% Non-Condensing |
| Altitude | ≤ 3000m |
| IP Rating | IP54 |
| Connector Standard | SAE J1772 (16' Standard / 24' Optional) |
| RFID system | ISO/IEC 14443 A/B |
| Communication Protocol | OCPP 1.6J |
| Internet | Ethernet (Standard), 4G (Optional) |
| Meter Accuracy | 1% |
| User interface | 5'' Touch Screen |
| Installation Type | Wall Mount |
| Material | Galvanized steel |
| Dimensions | 12'' x 17'' x 7'' (L x H x D) |
| Compliance standard | EN 61851 - 1:2011, EN 61000 - 6 - 1:2007, EN 61000 - 6 - 3:2007/A1:2011/AC:2012 |
| Certification | CE, (UL) |
| Safety | Over Current, Short Circuit , Surge Protection, Leakage Current Protection |
| Additional Information | Pedestal - Optional / Mounting Bracket & Holster are standard accessories |