EVIUM CHARGING

Evium

DCFC

30kW 100a

FEATURES

- Up to 100A with 1000VDC
- 4G / Wi-Fi / Ethernet connectivity
- 7" Touch screen display
- OCPP 1.6J
- CCS1 Connecto
- Wall Mount / Pedestal (Optional) Installation
- Easy Installation (Indoor / Outdoor)
- Cord Management (Optional)

(323) 702 - 2400 www.eviumcharging.com david@eviumcharging.com

EVIUM CHARGING

DC FAST CHARGER SPECIFICATIONS

30kW

Intertek

Product Number	TP5-30-480-1
Model Number	TP-EVPD-30kW
Input Voltage	480VAC (3P+N+PE), 60Hz
Output Voltage	150 to 1000VDC
Output Current	Up to 100A
FLA || Breaker Rating	40A || 50A
Connector (s)	CCS1
Efficiency	≥94% at nominal output power
Power Factor	>0.98
Operating temperature	22°F to 131°F (-30°C to 55°C)
Working || Storage Humidity	≤ 95% RH || ≤ 99% RH (Non-condensing)
Altitude	< 6600ft (2000m)
Display	7'' touch screen
RFID System	ISO || IEC 14443A/B
Dimensions (L x D x H)	21'' x 12'' x 27''
Protective Class	NEMA 3S, IK 10
Cooling System	Air cooled
Weight	176 lbs (80kg)
Charging Protocol	Mode 4, IEC-61851, ISO-15118, DIN SPEC 7012
Length of Charging Cable	16ft (5m)
Communication || Protocol	Ethernet / 4G Wi-Fi || OCPP 1.6J
Electrical Safety: GFCI	RCD 20 mA Type A
Electrical Safety: Surge Protection	20 kA
Electrical Safety General	Over Voltage, Under Voltage, Over Current, Missing Ground
Electrical Safety: Output Short	Output power disabled when output is short circuited
Electrical Safety Temperature	Temperature Sensors @ Charge Coupler and Power Electronics
Emergency Stop	Emergency Stop Button Disables Output Power
Regulatory Compliance	UL-2202 || CSA C22.2#107.1:2016 || EMC: EN 61000-6-1:2007, EN 61000-6-3:2007/A1:2011/AC:2012