

Discretisation of 2D domains, bounded by NURBS curves

Author: Andrej Kolar-Požun
Mentor: Marjetka Knez

29. november 2023

NURBS

- ▶ NURBS - Non Uniform Rational B-Splines.

NURBS

- ▶ NURBS - Non Uniform Rational B-Splines.
- ▶ B-Splines $N_{k,p}(\xi)$ basis for polynomial splines with prescribed smoothness.

NURBS

- ▶ NURBS - Non Uniform Rational B-Splines.
- ▶ B-Splines $N_{k,p}(\xi)$ basis for polynomial splines with prescribed smoothness.
- ▶ B-Splines + Control points \rightarrow B-Spline Curve (special case - Bézier curve).

NURBS

- ▶ NURBS - Non Uniform Rational B-Splines.
- ▶ B-Splines $N_{k,p}(\xi)$ basis for polynomial splines with prescribed smoothness.
- ▶ B-Splines + Control points \rightarrow B-Spline Curve (special case - Bézier curve).
- ▶
$$C(\xi) = \frac{\sum_{k=1}^n \mathbf{P}_k w_k N_{k,p}(\xi)}{\sum_{k=1}^n w_k N_{k,p}(\xi)}.$$

NURBS

- ▶ NURBS - Non Uniform Rational B-Splines.
- ▶ B-Splines $N_{k,p}(\xi)$ basis for polynomial splines with prescribed smoothness.
- ▶ B-Splines + Control points \rightarrow B-Spline Curve (special case - Bézier curve).
- ▶
$$C(\xi) = \frac{\sum_{k=1}^n \mathbf{P}_k w_k N_{k,p}(\xi)}{\sum_{k=1}^n w_k N_{k,p}(\xi)}.$$
- ▶ Multipatch NURBS are also common.

Problem description

- ▶ $\partial\Omega = C(I)$ - simple and closed curve.

Problem description

- ▶ $\partial\Omega = C(I)$ - simple and closed curve.
- ▶ Goal - discretise Ω . Obtain $X \subset \Omega$.

Problem description

- ▶ $\partial\Omega = C(I)$ - simple and closed curve.
- ▶ Goal - discretise Ω . Obtain $X \subset \Omega$.
- ▶ Motivation - Meshless methods and Monte Carlo.

Problem description

- ▶ $\partial\Omega = C(I)$ - simple and closed curve.
- ▶ Goal - discretise Ω . Obtain $X \subset \Omega$.
- ▶ Motivation - Meshless methods and Monte Carlo.
- ▶ Requirement 1: Algorithm takes N or h as input.

Problem description

- ▶ $\partial\Omega = C(I)$ - simple and closed curve.
- ▶ Goal - discretise Ω . Obtain $X \subset \Omega$.
- ▶ Motivation - Meshless methods and Monte Carlo.
- ▶ Requirement 1: Algorithm takes N or h as input.
- ▶ Requirement 2: Quasiuniformness, quasirandomness.

- ▶ inRS¹ algorithm for calculating indicator function of Ω .

¹Sommariva, Vianello inRS: Implementing the indicator function of NURBS-shaped planar domains.

- ▶ inRS¹ algorithm for calculating indicator function of Ω .
- ▶
$$C(\xi) = \frac{\sum_{k=1}^n \mathbf{P}_k w_k N_{k,p}(\xi)}{\sum_{k=1}^n w_k N_{k,p}(\xi)}.$$

¹Sommariva, Vianello inRS: Implementing the indicator function of NURBS-shaped planar domains.

- ▶ inRS¹ algorithm for calculating indicator function of Ω .
- ▶ $C(\xi) = \frac{\sum_{k=1}^n \mathbf{P}_k w_k N_{k,p}(\xi)}{\sum_{k=1}^n w_k N_{k,p}(\xi)}.$
- ▶ Main idea - try reduce to the polygon case.

¹Sommariva, Vianello inRS: Implementing the indicator function of NURBS-shaped planar domains.

- ▶ inRS¹ algorithm for calculating indicator function of Ω .
- ▶
$$C(\xi) = \frac{\sum_{k=1}^n \mathbf{P}_k w_k N_{k,p}(\xi)}{\sum_{k=1}^n w_k N_{k,p}(\xi)}.$$
- ▶ Main idea - try reduce to the polygon case.
- ▶ Divide I into I_k such that C restricted to it is a pair of rational functions.

¹Sommariva, Vianello inRS: Implementing the indicator function of NURBS-shaped planar domains.

- ▶ inRS¹ algorithm for calculating indicator function of Ω .
- ▶
$$C(\xi) = \frac{\sum_{k=1}^n \mathbf{P}_k w_k N_{k,p}(\xi)}{\sum_{k=1}^n w_k N_{k,p}(\xi)}.$$
- ▶ Main idea - try reduce to the polygon case.
- ▶ Divide I into I_k such that C restricted to it is a pair of rational functions.
- ▶ For each I_k , calculate the roots of the derivatives of the appropriate rational function.




¹Sommariva, Vianello inRS: Implementing the indicator function of NURBS-shaped planar domains.

- ▶ inRS¹ algorithm for calculating indicator function of Ω .
- ▶
$$C(\xi) = \frac{\sum_{k=1}^n \mathbf{P}_k w_k N_{k,p}(\xi)}{\sum_{k=1}^n w_k N_{k,p}(\xi)}.$$
- ▶ Main idea - try reduce to the polygon case.
- ▶ Divide I into I_k such that C restricted to it is a pair of rational functions.
- ▶ For each I_k , calculate the roots of the derivatives of the appropriate rational function.
- ▶ For each $I_{k,j}$ find $a_{k,j} = \min_{I_{k,j}} \alpha_k(\xi)$




¹Sommariva, Vianello inRS: Implementing the indicator function of NURBS-shaped planar domains.

- ▶ inRS¹ algorithm for calculating indicator function of Ω .
- ▶
$$C(\xi) = \frac{\sum_{k=1}^n \mathbf{P}_k w_k N_{k,p}(\xi)}{\sum_{k=1}^n w_k N_{k,p}(\xi)}.$$
- ▶ Main idea - try reduce to the polygon case.
- ▶ Divide I into I_k such that C restricted to it is a pair of rational functions.
- ▶ For each I_k , calculate the roots of the derivatives of the appropriate rational function.
- ▶ For each $I_{k,j}$ find $a_{k,j} = \min_{I_{k,j}} \alpha_k(\xi)$
- ▶ Cover $\partial\Omega$ by monotone boxes $\mathcal{B}_{k,j} = [a_{k,j}, b_{k,j}] \times [c_{k,j}, d_{k,j}]$.




¹Sommariva, Vianello inRS: Implementing the indicator function of NURBS-shaped planar domains.






- If (x_0, y_0) outside global bounding box \rightarrow also outside Ω .



- ▶ If (x_0, y_0) outside global bounding box \rightarrow also outside Ω .
- ▶ If (x_0, y_0) outside monotone boxes - polygon case.






- ▶ If (x_0, y_0) outside global bounding box \rightarrow also outside Ω .
- ▶ If (x_0, y_0) outside monotone boxes - polygon case.
- ▶ If inside one of the monotone boxes - polynomial solve.












- ▶ degenerate cases and multipatch.

- ▶ degenerate cases and multipatch.



► Halton nodes + rejection sampling






DIVG

- ▶ DIVG² - Dimension Independent Variable Density node Generation.


²Slak, Kosec: On generation of node distributions for meshless PDE discretizations

- DIVG² - Dimension Independent Variable Density node Generation.




²Slak, Kosec: On generation of node distributions for meshless PDE discretizations

- ▶ DIVG² - Dimension Independent Variable Density node Generation.
- ▶ q - queue of active points, initially filled with seed points. Algorithm runs as long as it's non-empty.




DIVG

- ▶ DIVG² - Dimension Independent Variable Density node Generation.
- ▶ q - queue of active points, initially filled with seed points. Algorithm runs as long as it's non-empty.
- ▶ At each step, pop q to get a point x_0 , use it to generate new candidates.




²Slak, Kosec: On generation of node distributions for meshless PDE discretizations


- ▶ DIVG² - Dimension Independent Variable Density node Generation.
- ▶ q - queue of active points, initially filled with seed points. Algorithm runs as long as it's non-empty.
- ▶ At each step, pop q to get a point x_0 , use it to generate new candidates.
- ▶ Candidate is accepted if it's inside the domain and if it is far enough from already accepted points.




- ▶ DIVG² - Dimension Independent Variable Density node Generation.
- ▶ q - queue of active points, initially filled with seed points. Algorithm runs as long as it's non-empty.
- ▶ At each step, pop q to get a point x_0 , use it to generate new candidates.
- ▶ Candidate is accepted if it's inside the domain and if it is far enough from already accepted points.
- ▶ Algorithm is efficient with the help of a kd-tree.




seed nodes




iteration 124



final distribution




candidate generation





- ▶ sDIVG³ idea - use DIVG in the parameter space.

³Duh, Kosec, Slak: Fast variable density node generation on parametric surfaces with application to mesh-free methods

- sDIVG³ idea - use DIVG in the parameter space.




³Duh, Kosec, Slak: Fast variable density node generation on parametric surfaces with application to mesh-free methods



► NURBS-DIVG⁴

⁴Duh, Shankar, Kosec: Discretization of non-uniform rational B-spline (NURBS) models for meshless isogeometric analysis


- ▶ NURBS-DIVG⁴
- ▶ Multipatch - Discretise each patch separately with sDIVG.





⁴Duh, Shankar, Kosec: Discretization of non-uniform rational B-spline (NURBS) models for meshless isogeometric analysis

- ▶ Interior check - $(\mathbf{p} - \mathbf{x}) \cdot \mathbf{n} > 0$


- Interior check - $(\mathbf{p} - \mathbf{x}) \cdot \mathbf{n} > 0$




- ▶ Interior check - $(\mathbf{p} - \mathbf{x}) \cdot \mathbf{n} > 0$
- ▶ Improve accuracy with supersampling.






Utah teapot



Tiger








Comparison

NURBS describing the duck shape



Domain filled by inRS



Domain filled via oversampling

