

The `checklistings` package*

Timothy Bourke and Marc Pouzet

April 30, 2015

1 Introduction

User manuals and papers about programming languages usually contain many code samples, often with accompanying compiler messages, giving the types or values of declarations, or errors explaining why certain declarations are invalid. Packages like `fancyvrb`¹ and `listings`² are ideal for displaying code—this package extends them slightly to facilitate passing this same code through a compiler and displaying the results. While it does not focus on a specific programming language, it is intended to work well with ML-like languages.

As an example, the text at left below is generated by the \LaTeX code at right:

```
Code samples are included verbatim
and the results of compilation can be
included automatically:
```

```
let inc x = x + 1
let y = inc 3

val inc : int -> int
val y : int
```

```
1 Code samples are included
2 verbatim and the results of
3 compilation can be included
4 automatically:
5 \begin{chklisting}[withresult]
6 let inc x = x + 1
7 let y = inc 3
8 \end{chklisting}
```

A first pass through `latex` generates both an `.chk1` file, with parameters for the compiler, and an `.ml` file containing the source code (i.e., the two lines in the example above). Running the `checklistings.sh` script processes these files to produce a `.tex` file with the results of compilation. A second pass through `latex` updates the compiler message.

It is possible to continue examples and to label them (to be continued at some later point):

*This document corresponds to `checklistings` ?, dated ?.

¹<http://www.ctan.org/pkg/fancyvrb>

²<http://www.ctan.org/pkg/listings>

```

1 These definitions follow on from the previous ones:
2 \begin{chklisting}[continue,withresult,label=early]
3 let z = y + inc y
4 \end{chklisting}

```

These definitions follow on from the previous ones:

```

let z = y + inc y
val z : int

```

Examples need not necessarily succeed:

```

1 This code does not compile:
2 \begin{chklisting}[continue, fail, withresult,skipone]
3 let u = 3
4 let w = u + "four"
5 \end{chklisting}

```

This code does not compile:

```

let w = u + "four"

```

File "chklisting.ml", line 3, characters 12-18:

```

Error: This expression has type string but an expression was expected of type
      int

```

Note that the line number is not correct. This is because the `continue` option added a line to include the previous definitions and the `skipone` option hid the `let u = 3` line.

2 Use

Using the package involves three elements:

1. The declaration `\usepackage{checklistings}`.
Section 2.1 describes the options for configuring package behaviour.
2. The environment `chklisting`.
This environment is used like any other verbatim environment. Section 2.2 describes options that may be given to control its behaviour.
3. The script `checklistings.sh`.
Running this script passes the contents of each `chklisting` environment through a compiler or interpreter and copies the resulting output into a file.

2.1 Package options

`\checklistings` Package options are either given as optional arguments to `\usepackage` or via one

or more calls to `\checklistings`. The advantage of the latter is that macros are not expanded (for a detailed explanation see the documentation for `kvoptions`,³ Section 4.1, *Package kvoptions-patch*). Options are passed as a comma separated list of $\langle key \rangle = \langle value \rangle$ pairs and single $\langle key \rangle$ s.

There are three classes of options: options controlling the default behaviour of `chklisting`, options for configuring the `checklistings.sh` script, and options controlling the display of code and results.

2.1.1 Behavioural options

These options control the default behaviour of the `chklisting` environment.

option	description	default
<code>withresult</code>	Automatically show compilation results.	<code>false</code>
<code>skipone</code>	Do not display the first line of code (see the description under the <code>chklisting</code> environment).	<code>false</code>
<code>skiptwo</code>	Do not display the first two lines of code (see the description under the <code>chklisting</code> environment).	<code>false</code>
<code>ignoreerrors</code>	Globally disable the display of error messages (within a red box) when compilation fails or succeeds unexpectedly.	<code>false</code>

2.1.2 Configuring compilation

These options are used for naming and placing the files generated by `chklisting` environments. They are passed to the `checklistings.sh` script and thus control its behaviour.

option	description	default
<code>prefix</code>	Prefix for naming source files. It must not contain underscores (<code>_</code>).	<code>chklisting</code>
<code>ext</code>	Extension of source files.	<code>.ml</code>
<code>subdir</code>	If defined, source files are created in the given subdirectory, which must already exist. A final slash (<code>/</code>) should not be given. The name must not contain underscores (<code>_</code>).	<code>.</code>
<code>prompt</code>	The prompt displayed by “ <code>chklistingcmd</code> ”.	<code>#</code>
<code>compiler</code>	Path of the compiler to execute.	<code>ocamlc</code>
<code>compilerflags</code>	Flags passed to the compiler. These are not revealed by “ <code>chklistingcmd</code> ”.	
<code>lastflags</code>	Flags passed to the compiler before the main source file, i.e., the last one given.	<code>-i</code>
<code>includecmd</code>	The source language command for importing the definitions of another file.	<code>open</code>

³<http://www.ctan.org/pkg/kvoptions>

html The path of a program that renders source code as html. This value can be useful when using HeVeA to produce web pages from L^AT_EX documents. In any case, it is optional.

Each **chklisting** environment is assigned a number n , from zero, and its contents are written to the file: $\langle subdir \rangle / \langle prefix \rangle \langle n \rangle . \langle ext \rangle$, where $\langle n \rangle$ is zero-padded to four characters. For example, by default, the fourth environment is written to the file **chklisting0003.ml** in the current directory.

Source lines are added for each dependency, and those files are compiled using the $\langle compiler \rangle$, $\langle compilerflags \rangle$, and $\langle lastflags \rangle$ options. For example, if the fourth environment depends on the first and the second, a line is added:

$\langle includecmd \rangle$ **Withopen0000** $\langle includecmd \rangle$ **Withopen0001**,

where **Withopen** is the prefix used for such augmented files, and the compiler is invoked with:

$\langle compiler \rangle$ $\langle compilerflags \rangle$ **Withopen0000** **Withopen0001**
 $\langle lastflags \rangle$ **Withopen0003**

2.1.3 Controlling the display

This package exploits the display options given by the **fancyvrb** package.

option	description	default
codestyle	fancyvrb options for code	
msgstyle	fancyvrb options for compiler messages	formatcom =\em
errstyle	fancyvrb options for error messages	formatcom =\em
codelst	listings options for source code, passed with \lstset . When this option is not empty, fancyvrb=true is included automatically.	
msglst	As for codelst , but applied to compiler messages.	
errlst	As for codelst , but applied to error messages.	

Other options are passed directly through to the **fancyvrb** package and applied to all **chklisting** code blocks (but not to messages or errors). For example, **frame=single**. These options must typically be set using **\checklistings**, since they will usually contain commands that should not be expanded immediately (like **\em** or **\bf**).

2.2 The **chklisting** environment

chklisting As an optional argument, this environment takes a comma separated list of $\langle key \rangle = \langle value \rangle$ and single $\langle key \rangle$ s.

option	description
fail	This code is expected to fail; an error is reported if it succeeds.
continue	This code is continued from the previous chklisting environment; all of the definitions available there are imported.
label	Label this code for later inclusion.
include	All of the definitions available after the environment with the given label are imported.
withresult	The result of compiling the code is displayed (see also \chklistingmsg and \chklistingerr). This is normally either the types of declared values or the results of evaluation. For environments marked fail , it will be an error message.
withoutresult	The result of compiling code is not displayed automatically. This is the default behaviour, but it can be overridden by the package options.
hide	Do not display the code itself. It is still compiled and displayed (if withresult) is active, and its definitions are still available for continuation (continue) or labelling (label) and later inclusion (include).
skipone	Do not display the first line of the code. This line is still sent to the compiler and may thus be used to open other modules, or to pass execution options (via comments).
skiptwo	As pre the previous option, but two lines are skipped.
skipnone	Do not skip any lines; this option overrides any package-level skip setting.
ignoreerrors	Do not display an error message within the document when compilation fails or succeeds unexpectedly.
showerrors	Display an error message within the document when compilation fails or succeeds unexpectedly. This is the default behaviour unless the ignoreerrors package option was set.

The results of compiling the code in a **runenvironment** are made available in the following macros until the next **runenvironment** which will redefine them.

\chklistingcmd	\chklistingcmd contains an idealised version of the command line used to compile the code sample. It includes the prompt , the basename of compiler , and lastflags , but not compilerflags or the list of included files. Furthermore, the subdir and serial number are removed from the filename of the code sample, which becomes simply <i><prefix>.<ext></i> .
\chklistingmsg	\chklistingmsg{<label>} : inserts the verbatim text emitted by the compiler, provided compilation succeeded, for the chklisting environment labelled <i><label></i> . When <i><label></i> is left empty, the message for the last environment is inserted. It should not be used after environments marked fail .
\chklistingerr	\chklistingerr{<label>} : inserts the verbatim text emitted by the compiler, provided compilation failed, for the chklisting environment labelled <i><label></i> .

When $\langle label \rangle$ is left empty, the message for the last environment is inserted. It should only be used after environments marked `fail`.

2.3 The `checklistings.sh` script

Processing a document that uses the `checklistings` package produces a `.chk1` file containing compiler options and a list of source files to together with their interdependencies. The `checklistings.sh` script processes `.chk1` files by executing the specified compiler (or interpreter) against each listed source file $\langle subdir \rangle / \langle prefix \rangle \langle n \rangle . \langle ext \rangle$ and copying the results—the command-line used, whether it succeeded or failed, the messages on `stdout`, and the messages on `stderr`—into a corresponding file, $\langle subdir \rangle / \langle prefix \rangle \langle n \rangle . \text{tex}$, for inclusion in the original document.

The `checklistings.sh` script is written for the Bourne shell (`sh`). It takes a list of `.chk1` files as arguments (with or without the extensions), but if none are given it processes all such files in the current working directory.

The compilation options specified within a \LaTeX source file, see Section 2.1.2, can be manually overridden by processing a `.chk1` file, before any others, containing a ‘`lock`’ directive, for example: `lock compiler=/usr/local/bin/ocamlc`. This feature is useful when working with others to develop the compiler being documented.

3 Remarks

3.1 Known limitations

The package and script have some known limitations.

- Line numbers in error messages may not correspond correctly with the line numbers of sample files, due to either the `skip*` options, or because of lines added to import code.
- The system has been designed to work with ML-style compilers. It has not been tested with other compilers and interpreters. Please contact tim@tbrk.org if you would like to support other systems. Patches are most welcome, but the intent is to keep this package relatively simple rather than to try to do everything.
- Multiple languages in a single document are not supported.
- Care must be taken when using `checklistings` with the overlays of the Beamer package. In particular, `chklisting` environment commands are to be avoided within commands that completely omit material from slides, like `only`, `alt`, or `temporal`, or with ‘closed’ overlay specifications, like 2 or 1–3. As these commands do not execute the material, the environment sequence numbers do not increase monotonically, and the compilation results may not be properly synchronized with the verbatim text. Commands that only

hide material, or that introduce it successively, like `uncover` or `visible`, or ‘open’ overlay specifications, like 2–, should function as expected.

4 Implementation

All internal macros have names of the form `\CHKL@⟨name⟩`.

`\chklisting` Generate the sequence of source code identifiers used in per-environment filenames and to manage dependencies. If `beamer` is being used, reset the counter on each overlay to avoid generating multiple output files for the same program.

```
1 \newcounter{chklisting}
2 \ifdefined\resetcounteronoverlays
3 \resetcounteronoverlays{chklisting}
4 \fi
```

`\ifCHKL@fileexists` An internal boolean variable for remembering whether an input `.tex` file, corresponding to the compilation of source code, was found.

```
5 \newif\ifCHKL@fileexists
```

4.1 Package Options

The package options are processed using the `kvoptions` package.⁴

`\CHKL@pkg@verbopts` This list accumulates package-level options for the `verbatim` environments.

```
6 \def\CHKL@pkg@verbopts{}
```

Declare the package options and their default values:

```
7 \DeclareBoolOption{withresult}
8 \DeclareComplementaryOption{withoutresult}{withresult}
9 \DeclareBoolOption[true]{showerrors}
10 \DeclareComplementaryOption{ignoreerrors}{showerrors}
11 \DeclareVoidOption{skipone}
12   {\edef\CHKL@pkg@verbopts{\CHKL@pkg@verbopts,firstline=2}}
13 \DeclareVoidOption{skiptwo}
14   {\edef\CHKL@pkg@verbopts{\CHKL@pkg@verbopts,firstline=3}}
15 \DeclareDefaultOption
16   {\edef\CHKL@pkg@verbopts{\CHKL@pkg@verbopts,\CurrentOption}}
17 \DeclareStringOption[] {codestyle}
18 \DeclareStringOption[formatcom=\em]{msgstyle}
19 \DeclareStringOption[formatcom=\em]{errstyle}
20 \DeclareStringOption{codelst}
21 \DeclareStringOption{msglst}
22 \DeclareStringOption{errlst}
23 \DeclareStringOption{emptyoption}
24 \DeclareStringOption[.]{subdir}
25 \DeclareStringOption[chklisting]{prefix}
```

⁴<http://www.ctan.org/pkg/kvoptions>

```

26 \DeclareStringOption[.ml]{ext}
27 \DeclareStringOption[\#]{prompt}
28 \DeclareStringOption[ocamlc]{compiler}
29 \DeclareStringOption{compilerflags}
30 \DeclareStringOption[-i]{lastflags}
31 \DeclareStringOption[open]{includecmd}
32 \DeclareStringOption[] {html}
33 \ProcessKeyvalOptions*

```

`\checklistings` This macro offers another way of setting package options with the advantage that values are not expanded.

```

34 \def\checklistings{\kvsetkeys{CHKL}}

```

4.2 Logging Files to Process

Several definitions and commands are used to create and write to the `.chk1` file.

`\CHKL@samplefile` The file generated when a L^AT_EX document that uses the `checklistings` package is processed.

```

35 \newwrite\CHKL@samplefile
36 \openout\CHKL@samplefile=\jobname.chk1
37 \AtEndDocument{\closeout\CHKL@samplefile}

```

Package options are logged to the file.

```

38 \write\CHKL@samplefile{subdir=\CHKL@subdir/}
39 \write\CHKL@samplefile{prefix=\CHKL@prefix}
40 \write\CHKL@samplefile{ext=\CHKL@ext}
41 \write\CHKL@samplefile{compiler=\CHKL@compiler}
42 \write\CHKL@samplefile{compilerflags=\CHKL@compilerflags}
43 \write\CHKL@samplefile{lastflags=\CHKL@lastflags}
44 \write\CHKL@samplefile{includecmd=\CHKL@includecmd}
45 \write\CHKL@samplefile{htmlfilter=\CHKL@html}

```

`\CHKL@logsample` An entry is logged for each `chklisting` environment. It contains the sequence number for the example, followed by a colon, an ordered list of other sample files to import, and the page and line numbers (to include in error messages).

```

46 \DeclareRobustCommand{\CHKL@logsample}[2]{%
47   \edef\CHKL@tolog{#1:#2 [page=\noexpand\thepage] [line=\the\inputlineno]}%
48   \expandafter\write\expandafter\CHKL@samplefile\expandafter{\CHKL@tolog}%
49 }

```

4.3 Insertion of Compilation Results

Several macros are defined for use by the `checklistings.sh` script (and any similar program). These macros are called from within the `.tex` file generated for each `chklisting` environment.

<code>\ifchklisting</code>	A successful compilation is signalled by <code>\chklistingtrue</code> , and a failed compilation by <code>\chklistingfalse</code> . 50 <code>\newif\ifchklisting</code>
<code>\setchklistingcmd</code>	The command used to compile a sample is recorded by <code>\setchklistingcmd</code> which (re)defines the internal <code>\CHKL@prompt</code> value. 51 <code>\DeclareRobustCommand{\setchklistingcmd}[1]{%</code> 52 <code>\global\def\chklistingcmd{\emph{\CHKL@prompt{#1}}}</code>
<code>ChkListingMsg</code>	Normal compiler messages (written on <code>stdout</code>) should be communicated between <code>\begin{ChkListingMsg}</code> and <code>\end{ChkListingMsg}</code> . This verbatim text is saved using the <code>SaveVerbatim</code> feature of <code>fancyvrb</code> . 53 <code>\def\ChkListingMsg{\FV@Environment}{ChkListingMsg}</code> 54 <code>\def\FVB@ChkListingMsg{\FVB@SaveVerbatim{ChkListingMsg}}</code> 55 <code>\let\FVE@ChkListingMsg\FVE@SaveVerbatim</code> 56 <code>\DefineVerbatimEnvironment{ChkListingMsg}{ChkListingMsg}{}</code>
<code>ChkListingErr</code>	Compiler error messages (usually written on <code>stderr</code>) should be communicated between <code>\begin{ChkListingErr}</code> and <code>\end{ChkListingErr}</code> . This verbatim text is saved using the <code>SaveVerbatim</code> feature of <code>fancyvrb</code> . 57 <code>\def\ChkListingErr{\FV@Environment}{ChkListingErr}</code> 58 <code>\def\FVB@ChkListingErr{\FVB@SaveVerbatim{ChkListingErr}}</code> 59 <code>\let\FVE@ChkListingErr\FVE@SaveVerbatim</code> 60 <code>\DefineVerbatimEnvironment{ChkListingErr}{ChkListingErr}{}</code>
<code>\chklistingfile</code>	This is the filename used by <code>checklistings.sh</code> to refer to the file containing sample code when <code>\setchklistingcmd</code> is called. 61 <code>\DeclareRobustCommand{\chklistingfile}{\CHKL@prefix\CHKL@ext}</code>

4.4 Main Environment

Several auxiliary definitions are needed to track per-environment configuration options.

<code>\ifCHKL@shouldfail</code>	This boolean variable records whether sample code is expected to fail. 62 <code>\newif\ifCHKL@shouldfail</code>
<code>\ifCHKL@showcode</code>	This boolean variable records whether the compilation result should be shown. 63 <code>\newif\ifCHKL@showcode</code>

The `keyval` package⁵ is used to parse environment options. The following macros setup parameters used by the `chklisting` environment.

<code>\CHKL@continue</code> <code>\CHKL@precontinue</code>	These two macros hold lists of source code identifiers: <code>\CHKL@precontinue</code> tracks the dependencies of the previous <code>chklisting</code> environment, and <code>\CHKL@continue</code>
---	---

⁵<http://www.ctan.org/pkg/kvoptions>

tracks those of the current one. The `continue` option appends the previous dependencies onto the list of current ones. The dependencies used at each labelled environment are remembered in `\RBRB@deps<label>`. The `include` option causes them to be added to the list of current dependencies

```

64 \edef\CHKL@precontinue{}
65 \define@key{CHKL@envkeys}{continue}[]{\edef\CHKL@continue{\CHKL@precontinue}}
66 \define@key{CHKL@envkeys}{include}{%
67   \edef\CHKL@continue{\CHKL@continue\space\ifundefined{CHKL@deps@#1}%
68     {#1}{\csname CHKL@deps@#1\endcsname}}}%

69 \define@key{CHKL@envkeys}{fail}[]{\CHKL@shouldfailtrue}
70 \define@key{CHKL@envkeys}{label}{\edef\CHKL@label{#1}}
71 \define@key{CHKL@envkeys}{skipnone}[]{\edef\CHKL@verbopts{\CHKL@verbopts,firstline=1}}
72 \define@key{CHKL@envkeys}{skipone}[]{\edef\CHKL@verbopts{\CHKL@verbopts,firstline=2}}
73 \define@key{CHKL@envkeys}{skiptwo}[]{\edef\CHKL@verbopts{\CHKL@verbopts,firstline=3}}
74 \define@key{CHKL@envkeys}{hide}[]{\CHKL@showcodefalse}
75 \define@key{CHKL@envkeys}{withresult}[]{\CHKL@withresulttrue}
76 \define@key{CHKL@envkeys}{withoutresult}[]{\CHKL@withresultfalse}
77 \define@key{CHKL@envkeys}{showerrors}[]{\CHKL@showerrorstrue}
78 \define@key{CHKL@envkeys}{ignoreerrors}[]{\CHKL@showerrorsfalse}

```

`\chklistingmsg` This macro takes a single argument `<label>`. It first configures the `listings` and `fancyvrb` packages with the current display options. It then checks the `fancyvrb` saved text namespace (`'FV@SV@...'`) for an entry named `'...CHKL@MSG@<label>'`. If found, the associated verbatim text is inserted via the `\UseVerbatim` feature of `fancyvrb`, otherwise an error message is inserted. In the latter case, we prefer not to fail outright, because the user may not yet have had the chance to run the compiler on the extracted code, in which case the log will already contain warnings from `chklisting`. By convention, the `chklisting` environment creates an entry for the empty label (`'FV@SV@CHKL@MSG@'`) when compilation succeeds.

```

79 \DeclareRobustCommand{\chklistingmsg}[1]{
80   \bgroup%
81   \ifx\CHKL@msglst\CHKL@emptyoption\else
82     \expandafter\lstset\expandafter{\CHKL@msglst,fancyvrb=true}\fi%
83   \@ifundefined{FV@SV@CHKL@MSG@#1}
84     {\def\@tempa{#1}
85       \ifx\@tempa\empty
86         \CHKL@none
87       \else
88         $\angle$No message found for the label '#1'!\angle$
89       \fi}
90     {\expandafter\UseVerbatim\expandafter[\CHKL@msgstyle]{CHKL@MSG@#1}}%
91   \egroup}

```

`\chklistingerr` This macro is essentially the same as the previous one—only that the substring `'ERR'` is used instead of `'MSG'`.

```

92 \DeclareRobustCommand{\chklistingerr}[1]{
93   \bgroup%

```

```

94 \ifx\CHKL@errlst\CHKL@emptyoption\else
95   \expandafter\lstset\expandafter{\CHKL@errlst,fancyvrb=true}\fi%
96 \@ifundefined{FV@SV@CHKL@ERR@#1}
97   {\def\@tempa{#1}
98     \ifx\@tempa\empty
99       \CHKL@none
100    \else
101      $\langle$No message found for the label ‘#1’!$\rangle$
102    \fi}
103   {\expandafter\UseVerbatim\expandafter[\CHKL@errstyle]{CHKL@ERR@#1}}%
104 \egroup}

```

chklisting This is the main environment for including source code. This macro works in two parts:

1. It uses the listings package to write the code to a file,
2. It either loads the corresponding .tex file or logs an error message.

The listings package allows the definition of custom verbatim environments. This one has a single argument (a list of keyval options).

```

105 \lstnewenvironment{chklisting}[1] []
106   {%

```

Set default parameter values before invoking \setkeys:

```

107   \CHKL@shouldfailfalse%
108   \CHKL@showcodetrue%
109   \let\CHKL@label\@undefined%
110   \edef\CHKL@continue{}%
111   \let\CHKL@verbopts\CHKL@pkg@verbopts%
112   \def\@currentlabel{\thechklisting}%
113   \setkeys{CHKL@envkeys}{#1}%

```

Log an entry to the .chk1 file:

```

114   \CHKL@logsample{\arabic{chklisting}}{\CHKL@continue\ifCHKL@shouldfail\space[fail]\fi}%

```

Update \CHKL@precontinue for the next source code block, and, if a label was defined, add an \CHKL@deps@<label> entry.

```

115   \global\edef\CHKL@precontinue{\CHKL@continue\space\arabic{chklisting}}%
116   \@ifundefined{CHKL@label}{\fi}%
117   \global\expandafter\edef\csname CHKL@deps@\CHKL@label\endcsname{\CHKL@precontinue}}%

```

A file will be created in the \CHKL@subdir subdirectory, with the name \CHKL@prefix followed by the value of the chklisting counter, padded out with zeroes to four digits, and the extension \RBRB@ext.

```

118   \edef\CHKL@num{%
119     \ifnum\value{chklisting}<1000 0\fi
120     \ifnum\value{chklisting}<100 0\fi
121     \ifnum\value{chklisting}<10 0\fi
122     \arabic{chklisting}}%
123   \stepcounter{chklisting}%
124   \def\CHKL@file{\CHKL@subdir/\CHKL@prefix\CHKL@num}%

```

Clear the definitions used to return information about the compilation run, and close the environment by opening a file, using the `listings` package, into which to write the ensuing contents.

```

125 \global\let\chklistingcmd\@undefined%
126 \global\let\FV@SV@ChkListingMsg\@undefined%
127 \global\let\FV@SV@ChkListingErr\@undefined%
128 \chklistingtrue%
129 \setbox\@tempboxa\hbox\bgroup%
130 \lst@BeginWriteFile{\CHKL@file\CHKL@ext}%
131 }

```

Start closing the environment by closing the previously opened file and group.

```

132 {%
133 \lst@EndWriteFile%
134 \egroup%

```

If `hide` is not active, apply `\CHKL@verbopts` and reload the newly created file.

```

135 \ifCHKL@showcode%
136 \bgroup%
137 \ifx\CHKL@codelst\CHKL@emptyoption\else%
138 \expandafter\lstset\expandafter{\CHKL@codelst,fancyvrb=true}%
139 \fi%
140 \expandafter\fvset\expandafter{\CHKL@verbopts}%
141 \expandafter\VerbatimInput\expandafter[\CHKL@codestyle]{\CHKL@file\CHKL@ext}%
142 \egroup%
143 \fi%

```

Check whether a corresponding `.tex` file was created:

```

144 \global\edef\CHKL@none{${\langle$}Cannot load \CHKL@file.tex!${\rangle$}}%
145 \InputIfFileExists{\CHKL@file.tex}{\CHKL@fileexiststrue}{\CHKL@fileexistsfalse}%

```

If the `.tex` file was loaded successfully, create ‘unlabelled’ saved verbatim environments for the message and error texts. These are exploited, respectively, by the `\chklistingmsg` and `\chklistingerr` macros.

```

146 \ifCHKL@fileexists%
147 \ifundefined{FV@SV@ChkListingMsg}%
148 {}{\global\let\FV@SV@CHKL@MSG@=\FV@SV@ChkListingMsg}%
149 \ifundefined{FV@SV@ChkListingErr}%
150 {}{\global\let\FV@SV@CHKL@ERR@=\FV@SV@ChkListingErr}%

```

Then, if compilation failed and the `fail` option was not active, or if compilation succeeded and the `fail` option is active, log a warning message and, if errors are not being ignored, include details in the document. Otherwise, if `withresult` was given, expand either `\chklistingerr` or `\chklistingmsg`.

```

151 \ifCHKL@shouldfail%
152 \ifchklisting%
153 \PackageWarning{checklistings}%
154 {Compilation of \CHKL@file\CHKL@ext\space should have failed}%
155 \ifCHKL@showerrors%

```

```

156             \UseVerbatim[frame=single,
157                 label=Unexpected success,
158                 rulecolor=\color{red}]{ChkListingMsg}%
159         \fi%
160     \else%
161         \ifCHKL@withresult%
162             {\setlength{\partopsep}{0em}\chklistingerr{}}%
163         \fi%
164     \fi%
165 \else%
166     \ifchklisting%
167         \ifCHKL@withresult%
168             {\setlength{\partopsep}{0em}\chklistingmsg{}}%
169         \fi%
170     \else%
171         \PackageWarning{checklistings}%
172             {Compilation of \CHKL@file\CHKL@ext\space should not have failed}%
173         \ifCHKL@showerrors%
174             \UseVerbatim[frame=single,
175                 label=Unexpected failure,
176                 rulecolor=\color{red}]{ChkListingErr}%
177             \fi%
178         \fi%
179     \fi%
180 \else%

```

If the .tex file was not loaded successfully, clear the \chklistingcmd macros, and the ‘unlabelled’ saved verbatim environments for the message and error results.

```

181     \PackageWarning{checklistings}{Cannot load \CHKL@file.tex}%
182     \global\let\chklistingcmd\CHKL@none%
183     \global\let\FV@SV@CHKL@MSG@\@undefined%
184     \global\let\FV@SV@CHKL@ERR@\@undefined%
185 \fi%
186 % If this environment is labelled, create persistent references to the saved
187 % verbatim environments for the message and error results.
188 % These are exploited, respectively, by the |\chklistingmsg| and
189 % |\chklistingerr| macros when their \meta{label} argument is not empty.
190 %
191 \ifundefined{CHKL@label}{\fi%
192     \global\expandafter\let%
193     \csname FV@SV@CHKL@MSG@\CHKL@label\endcsname=\FV@SV@CHKL@MSG@%
194     \global\expandafter\let%
195     \csname FV@SV@CHKL@ERR@\CHKL@label\endcsname=\FV@SV@CHKL@ERR@%
196 }%
197 }%

```

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

C		
\checklistings ... 2 , 34	\CHKL@shouldfailfalse	\FV@SV@CHKL@MSG@ ...
\CHKL@codelst . 137 , 138 107 148 , 183 , 193
\CHKL@codestyle ... 141	\CHKL@shouldfailtrue 69	\FV@SV@ChkListingErr
\CHKL@compiler 41	\CHKL@showcodefalse 74 127 , 150
\CHKL@compilerflags 42	\CHKL@showcodetrue . 108	\FV@SV@ChkListingMsg
\CHKL@continue	\CHKL@showerrorsfalse 126 , 148
. 64 , 110 , 114 , 115 78	\FVB@ChkListingErr . 58
\CHKL@emptyoption .	\CHKL@showerrorstrue 77	\FVB@ChkListingMsg . 54
..... 81 , 94 , 137	\CHKL@subdir ... 38 , 124	\FVB@SaveVerbatim 54 , 58
\CHKL@errlst 94 , 95	\CHKL@tolog 47 , 48	\FVE@ChkListingErr . 59
\CHKL@errstyle 103	\CHKL@verbopts	\FVE@ChkListingMsg . 55
\CHKL@ext ... 40 , 61 ,	71 , 72 , 73 , 111 , 140	\FVE@SaveVerbatim 55 , 59
130 , 141 , 154 , 172	\CHKL@withresultfalse	
\CHKL@file ... 124 , 76	I
130 , 141 , 144 ,	\CHKL@withresulttrue 75	\ifCHKL@fileexists .
145 , 154 , 172 , 181	\chklisting 1 5 , 146
\CHKL@fileexistsfalse	chklisting (environ-	\ifCHKL@shouldfail .
..... 145	ment) 4 , 105 62 , 114 , 151
\CHKL@fileexiststrue	\chklistingcmd	\ifCHKL@showcode 63 , 135
..... 145	... 5 , 52 , 125 , 182	\ifCHKL@showerrors .
\CHKL@html 45	\ChkListingErr 57 155 , 173
\CHKL@includedcmd .. 44	ChkListingErr (envi-	\ifCHKL@withresult .
\CHKL@label 70 ,	ronment) 57 161 , 167
109 , 117 , 193 , 195	\chklistingerr	\ifchklisting 50 , 152 , 166
\CHKL@lastflags ... 43	... 5 , 92 , 162 , 189	
\CHKL@logsample 46 , 114	\chklistingfile ... 61	L
\CHKL@msglst 81 , 82	\ChkListingMsg 53	\lst@BeginWriteFile 130
\CHKL@msgstyle 90	ChkListingMsg (envi-	\lst@EndWriteFile . 133
\CHKL@none .. 86 , 99 , 144 , 182	ronment) 53	\lstnewenvironment . 105
\CHKL@num 118 , 124	\chklistingmsg	
\CHKL@pkg@verbopts 5 , 79 , 168 , 188	S
. 6 , 12 , 14 , 16 , 111	\chklistingtrue ... 128	\setchklistingcmd . 51
\CHKL@precontinue .	E	
..... 64 , 115 , 117	environments:	T
\CHKL@prefix 39 , 61 , 124	chklisting ... 4 , 105	\thechklisting 112
\CHKL@prompt 52	ChkListingErr .. 57	
\CHKL@samplefile 35 ,	ChkListingMsg .. 53	U
38 , 39 , 40 , 41 ,	F	\UseVerbatim 90 , 103 , 156 , 174
42 , 43 , 44 , 45 , 48	\FV@Environment . 53 , 57	
	\FV@SV@CHKL@ERR@ ...	V
 150 , 184 , 195	\VerbatimInput 141