

## Sheet 2

### Topic: Linear Algebra

#### Exercise 1: Linear Algebra

- a) Consider the matrices

$$A = \begin{pmatrix} 0.25 & 0.1 \\ 0.2 & 0.5 \end{pmatrix}, B = \begin{pmatrix} 0.25 & -0.3 \\ -0.3 & 0.5 \end{pmatrix}$$

Are they symmetric positive definite?

- b) For

$$C = \begin{pmatrix} -3 & 0 \\ 0 & 1 \end{pmatrix}$$

Find the largest value for  $\mu \in \mathcal{R}$  for which  $C + \mu I$  is not symmetric positive definite.

- c) Write a program in Python that determines whether a matrix is orthogonal.  
d) Use this program to investigate whether

$$D = \frac{1}{3} \begin{pmatrix} 2 & 2 & -1 \\ 2 & -1 & 2 \\ -1 & 2 & 2 \end{pmatrix}$$

is orthogonal.

#### Exercise 2: 2D Transformations as Affine Matrices

Transformations between coordinate frames play an important role in robotics. As background for exercises 2 and 3 on this sheet, please refer to the linear algebra slides on affine transformations and transformation combination.

The 2D pose of a robot w.r.t. a global coordinate frame is commonly written as  $\mathbf{x} = (x, y, \theta)^T$  where  $(x, y)$  denotes its position in the xy-plane and  $\theta$  its orientation. The homogeneous transformation matrix that represents a pose  $\mathbf{x} = (x, y, \theta)^T$  w.r.t. to the origin  $(0, 0, 0)^T$  of the global coordinate system is given by

$$\mathbf{T} = \begin{pmatrix} \mathbf{R}(\theta) & \mathbf{t} \\ 0 & 1 \end{pmatrix}, \quad \mathbf{R}(\theta) = \begin{pmatrix} \cos \theta & -\sin \theta \\ \sin \theta & \cos \theta \end{pmatrix}, \quad \mathbf{t} = \begin{pmatrix} x \\ y \end{pmatrix}$$

- a) While being at pose  $\mathbf{x}_1 = (x_1, y_1, \theta_1)^T$ , the robot senses a landmark  $l$  at position  $(l_x, l_y)$  w.r.t. to its local frame. Use the matrix  $\mathbf{T}$  to calculate the coordinates of  $l$  w.r.t. the global frame.  
b) Now imagine that you are given the landmark's coordinates w.r.t. the global frame. How can you calculate the coordinates that will be sensed in its local frame?  
c) The robot moves to a new pose  $\mathbf{x}_2 = (x_2, y_2, \theta_2)^T$  w.r.t. the global frame. Find the transformation matrix  $T_{12}$  that represents the new pose w.r.t. to  $\mathbf{x}_1$ . Hint: Write  $T_{12}$  as a product of homogeneous transformation matrices.

- d) The robot is at position  $\mathbf{x}_2$ . Where is the landmark  $\mathbf{l} = (l_x, l_y)$  w.r.t. the robot's local frame now?

### Exercise 3: Sensing

A robot is located at  $x = 1.0\text{m}$ ,  $y = 0.5\text{m}$ ,  $\theta = \frac{\pi}{4}$ . Its laser range finder is mounted on the robot at  $x = 0.2\text{m}$ ,  $y = 0.0\text{m}$ ,  $\theta = \pi$  (w.r.t. the robot's frame of reference).

The distance measurements of one laser scan can be found in the file **laserscan.dat**.

The first distance measurement is taken in the angle  $\alpha = -\frac{\pi}{2}$  (in the frame of reference of the laser range finder), the last distance measurement has  $\alpha = \frac{\pi}{2}$  (i.e., the field of view of the sensor is  $\pi$ ), and all neighboring measurements are in equal angular distance (all angles in radians)

Note: You can load the data file and calculate the corresponding angles in Python using

```
import math
import numpy as np
scan = np.loadtxt('laserscan.dat')
angle = np.linspace(-math.pi/2, math.pi/2,
np.shape(scan)[0], endpoint='true')
```

- a) Use Python to plot all laser end-points in the frame of reference of the laser range finder.

Note: You can use myplotlib.pyplot package for plotting

```
import myplotlib.pyplot as plt
```

- b) Use homogeneous transformation matrices in Python to compute and plot the center of the robot, the center of the laser range finder, and all laser end-points in world coordinates

Note: You can equally scale the x and y-axis of a plot using

```
plt.gca().set_aspect('equal', adjustable='box')
```