

Parallel Runtime Interface for Fortran (PRIF) Specification, Revision 0.7

PRIF Committee

prif-spec@googlegroups.com - go.lbl.gov/prif-pubs







Lawrence Berkeley National Laboratory Technical Report (LBNL-2001721)
[doi:10.25344/S46S3W](https://doi.org/10.25344/S46S3W)

December 17, 2025

Abstract

This document specifies an interface to support the multi-image parallelism features of Fortran, named the Parallel Runtime Interface for Fortran (PRIF). PRIF is a solution in which a runtime library is primarily responsible for implementing coarray allocation, deallocation and accesses, image synchronization, atomic operations, events, teams and collective subroutines. The Fortran compiler is responsible for transforming the invocation of Fortran-level multi-image parallelism features into procedure calls to the necessary PRIF subroutines. The interface is designed for portability across shared- and distributed-memory machines, different operating systems, and multiple architectures. Implementations of this interface are intended as an augmentation for the compiler's own runtime library. With an implementation-agnostic interface, alternative parallel runtime libraries may be developed that support the same interface. One benefit of this approach is the ability to vary the communication substrate. A central aim of this document is to define a parallel runtime interface in standard Fortran syntax, which enables us to leverage Fortran to succinctly express various properties of the procedure interfaces, including argument attributes.

PRIF Committee This specification is maintained by the [PRIF Committee](#).
Committee members at the time of publication include:

[Dan Bonachea](#) , [Katherine Rasmussen](#) , [Damian Rouson](#)  – *Lawrence Berkeley National Laboratory, USA*
[Brad Richardson](#)  – *National Aeronautics and Space Administration, USA*
[Jean-Didier Pailleux](#) , [Etienne Renault](#)  – *SiPearl, R&D, France*

Feedback and questions should be directed to the mailing list: prif-spec@googlegroups.com
or to the GitHub issue tracker: go.lbl.gov/prif-pubs

Contents

| | |
|--|-----------|
| Title Page | i |
| Contents | ii |
| 1 Change Log | 1 |
| Revision 0.2 (Dec 2023) | 1 |
| Revision 0.3 (May 2024) | 1 |
| Revision 0.4 (Jul 2024) | 2 |
| Revision 0.5 (Dec 2024) | 2 |
| Revision 0.6 (Sep 2025) | 3 |
| Revision 0.7 (Dec 2025) | 3 |
| 2 Problem Description | 4 |
| 3 Interface Description | 4 |
| 3.1 Parallel Runtime Interface for Fortran (PRIF) | 5 |
| 3.2 Delegation of tasks between the Fortran compiler and the PRIF implementation | 5 |
| 3.3 Design Decisions and Impact | 6 |
| 3.4 How to read the PRIF specification | 7 |
| 4 PRIF Types and Named Constants | 7 |
| 4.1 Fortran Intrinsic Derived Types | 7 |
| 4.1.1 <code>prif_team_type</code> | 7 |
| 4.1.2 <code>prif_event_type</code> | 7 |
| 4.1.3 <code>prif_lock_type</code> | 7 |
| 4.1.4 <code>prif_notify_type</code> | 8 |
| 4.2 PRIF-Specific Types | 8 |
| 4.2.1 <code>prif_coarray_handle</code> | 8 |
| 4.2.2 <code>prif_critical_type</code> | 8 |
| 4.3 Named Constants in <code>ISO_FORTRAN_ENV</code> | 9 |
| 4.3.1 <code>PRIF_ATOMIC_INT_KIND</code> | 9 |
| 4.3.2 <code>PRIF_ATOMIC_LOGICAL_KIND</code> | 9 |
| 4.3.3 <code>PRIF_CURRENT_TEAM</code> | 9 |
| 4.3.4 <code>PRIF_INITIAL_TEAM</code> | 9 |
| 4.3.5 <code>PRIF_PARENT_TEAM</code> | 9 |
| 4.3.6 <code>PRIF_STAT_FAILED_IMAGE</code> | 9 |
| 4.3.7 <code>PRIF_STAT_LOCKED</code> | 9 |
| 4.3.8 <code>PRIF_STAT_LOCKED_OTHER_IMAGE</code> | 9 |
| 4.3.9 <code>PRIF_STAT_STOPPED_IMAGE</code> | 9 |
| 4.3.10 <code>PRIF_STAT_UNLOCKED</code> | 9 |
| 4.3.11 <code>PRIF_STAT_UNLOCKED_FAILED_IMAGE</code> | 9 |
| 4.4 PRIF-Specific Named Constants | 10 |
| 4.4.1 <code>PRIF_STAT_OUT_OF_MEMORY</code> | 10 |
| 4.4.2 <code>PRIF_STAT_ALREADY_INIT</code> | 10 |
| 4.4.3 <code>PRIF_VERSION_MAJOR</code> | 10 |
| 4.4.4 <code>PRIF_VERSION_MINOR</code> | 10 |
| 5 PRIF Procedures | 10 |
| 5.1 Common Arguments | 11 |
| 5.1.1 Integer and Pointer Arguments | 11 |
| 5.1.2 <code>stat</code> and <code>errmsg</code> Arguments | 11 |
| 5.2 Program Startup and Shutdown | 12 |
| 5.2.1 <code>prif_init</code> | 12 |
| 5.2.2 <code>prif_stop</code> | 12 |
| 5.2.3 <code>prif_error_stop</code> | 12 |
| 5.2.4 <code>prif_register_stop_callback</code> | 13 |
| 5.2.5 <code>prif_fail_image</code> | 13 |

| | | |
|--------|---|----|
| 5.3 | Image Queries | 14 |
| 5.3.1 | Common Arguments in Image Queries | 14 |
| 5.3.2 | <code>prif_num_images</code> | 14 |
| 5.3.3 | <code>prif_this_image</code> | 14 |
| 5.3.4 | <code>prif_failed_images</code> | 15 |
| 5.3.5 | <code>prif_stopped_images</code> | 15 |
| 5.3.6 | <code>prif_image_status</code> | 15 |
| 5.4 | Storage Management | 15 |
| 5.4.1 | <code>prif_allocate_coarray</code> | 15 |
| 5.4.2 | <code>prif_allocate</code> | 17 |
| 5.4.3 | <code>prif_deallocate_coarray</code> | 17 |
| 5.4.4 | <code>prif_deallocate_coarrays</code> | 17 |
| 5.4.5 | <code>prif_deallocate</code> | 18 |
| 5.4.6 | <code>prif_alias_create</code> | 18 |
| 5.4.7 | <code>prif_alias_destroy</code> | 18 |
| 5.4.8 | <code>MOVE_ALLOC</code> | 19 |
| 5.5 | Coarray Queries | 19 |
| 5.5.1 | Common Arguments in Coarray Queries | 19 |
| 5.5.2 | <code>prif_image_index</code> | 19 |
| 5.5.3 | <code>prif_initial_team_index</code> | 20 |
| 5.5.4 | <code>prif_lcobound</code> | 21 |
| 5.5.5 | <code>prif_ucobound</code> | 21 |
| 5.5.6 | <code>prif_coshape</code> | 21 |
| 5.5.7 | <code>prif_local_data_pointer</code> | 22 |
| 5.5.8 | <code>prif_size_bytes</code> | 22 |
| 5.5.9 | <code>prif_set_context_data</code> | 22 |
| 5.5.10 | <code>prif_get_context_data</code> | 22 |
| 5.6 | Contiguous Coarray Access | 23 |
| 5.6.1 | Common Arguments in Contiguous Coarray Access | 23 |
| 5.6.2 | <code>prif_get</code> | 23 |
| 5.6.3 | <code>prif_get_indirect</code> | 24 |
| 5.6.4 | <code>prif_put</code> | 24 |
| 5.6.5 | <code>prif_put_indirect</code> | 24 |
| 5.6.6 | <code>prif_put_with_notify</code> | 25 |
| 5.6.7 | <code>prif_put_with_notify_indirect</code> | 25 |
| 5.6.8 | <code>prif_put_indirect_with_notify</code> | 25 |
| 5.6.9 | <code>prif_put_indirect_with_notify_indirect</code> | 26 |
| 5.7 | Strided Coarray Access | 26 |
| 5.7.1 | Common Arguments in Strided Coarray Access | 26 |
| 5.7.2 | <code>prif_get_strided</code> | 27 |
| 5.7.3 | <code>prif_get_strided_indirect</code> | 27 |
| 5.7.4 | <code>prif_put_strided</code> | 28 |
| 5.7.5 | <code>prif_put_strided_indirect</code> | 28 |
| 5.7.6 | <code>prif_put_strided_with_notify</code> | 29 |
| 5.7.7 | <code>prif_put_strided_with_notify_indirect</code> | 29 |
| 5.7.8 | <code>prif_put_strided_indirect_with_notify</code> | 30 |
| 5.7.9 | <code>prif_put_strided_indirect_with_notify_indirect</code> | 30 |
| 5.8 | SYNC Statements | 31 |
| 5.8.1 | <code>prif_sync_memory</code> | 31 |
| 5.8.2 | <code>prif_sync_all</code> | 31 |
| 5.8.3 | <code>prif_sync_team</code> | 31 |
| 5.8.4 | <code>prif_sync_images</code> | 31 |
| 5.9 | Locks | 32 |
| 5.9.1 | Common Arguments in Locks | 32 |
| 5.9.2 | <code>prif_lock</code> | 32 |
| 5.9.3 | <code>prif_lock_indirect</code> | 32 |
| 5.9.4 | <code>prif_unlock</code> | 33 |
| 5.9.5 | <code>prif_unlock_indirect</code> | 33 |
| 5.10 | Critical | 33 |

| | | |
|-----------|--|-----------|
| 5.10.1 | Common Arguments in Critical | 33 |
| 5.10.2 | <code>prif_critical</code> | 33 |
| 5.10.3 | <code>prif_end_critical</code> | 33 |
| 5.11 | Events and Notifications | 34 |
| 5.11.1 | Common Arguments in Events and Notifications | 34 |
| 5.11.2 | <code>prif_event_post</code> | 34 |
| 5.11.3 | <code>prif_event_post_indirect</code> | 34 |
| 5.11.4 | <code>prif_event_wait</code> | 35 |
| 5.11.5 | <code>prif_event_query</code> | 35 |
| 5.11.6 | <code>prif_notify_wait</code> | 35 |
| 5.12 | Teams | 36 |
| 5.12.1 | <code>prif_form_team</code> | 36 |
| 5.12.2 | <code>prif_get_team</code> | 36 |
| 5.12.3 | <code>prif_team_number</code> | 36 |
| 5.12.4 | <code>prif_change_team</code> | 36 |
| 5.12.5 | <code>prif_end_team</code> | 37 |
| 5.13 | Collective Subroutines | 37 |
| 5.13.1 | Common Arguments in Collective Subroutines | 37 |
| 5.13.2 | <code>prif_co_broadcast</code> | 37 |
| 5.13.3 | <code>prif_co_max</code> | 37 |
| 5.13.4 | <code>prif_co_max_character</code> | 38 |
| 5.13.5 | <code>prif_co_min</code> | 38 |
| 5.13.6 | <code>prif_co_min_character</code> | 38 |
| 5.13.7 | <code>prif_co_sum</code> | 39 |
| 5.13.8 | <code>prif_co_reduce</code> | 39 |
| 5.14 | Atomic Memory Operations | 42 |
| 5.14.1 | Common Arguments in Atomic Memory Operations | 42 |
| 5.14.2 | Non-Fetching Atomic Operations | 42 |
| 5.14.3 | Fetching Atomic Operations | 44 |
| 5.14.4 | Atomic Access | 45 |
| 5.14.5 | Atomic Compare-and-Swap | 46 |
| 6 | Glossary | 47 |
| 7 | Future Work | 48 |
| 8 | Acknowledgments | 48 |
| 9 | Copyright | 48 |
| 10 | Legal Disclaimer | 48 |

1 Change Log

Revision 0.2 (Dec 2023)

- Fill out interfaces to all PRIF provided procedures
- Write descriptions, discussions and overviews of various features, arguments, etc.

Revision 0.3 (May 2024)

- `prif_(de)allocate` are renamed to `prif_(de)allocate_coarray`
- `prif_(de)allocate_non_symmetric` are renamed to `prif_(de)allocate`
- `prif_local_data_size` renamed to `prif_size_bytes` and add a client note about the procedure
- Update interface to `prif_base_pointer` by replacing three arguments, `coindices`, `team`, and `team_number`, with one argument `image_num`. Update the semantics of `prif_base_pointer`, as it is no longer responsible for resolving the coindices and team information into a number that represents the image on the initial team before producing the address. That is now expected to occur before the `prif_base_pointer` call and passed into the `image_num` argument.
- Add target attribute on `coarray_handles` argument to `prif_deallocate_coarray`
- Add pointer attribute on `handle` argument to `coarray_cleanup` callback for `prif_allocate_coarray`
- Add target attribute on `value` argument to `prif_put` and `prif_get`
- Add new PRIF-specific constant `PRIF_STAT_OUT_OF_MEMORY`
- Clarify that remote pointers passed to various procedures must reference storage allocated using `prif_allocate_coarray` or `prif_allocate`
- Clarify description of the `allocated_memory` argument for the procedures `prif_allocate_coarray` and `prif_allocate`
- Clarify descriptions of `event_var_ptr`, `lock_var_ptr`, and `notify_ptr`
- Clarify descriptions for `prif_stop`, `prif_put`, `prif_get`, intrinsic derived types, sections about `MOVE_ALLOC` and coarray accesses
- Replace the phrase “local completion” with the phrase “source completion”, and add the new phrase to the glossary
- Clarify that `prif_stop` should be used to initiate normal termination
- Describe the `operation` argument to `prif_co_reduce`
- Rename and clarify the cobounds arguments to `prif_alias_create`
- Clarify the descriptions of `source_image/result_image` arguments to collective calls
- Clarify completion semantics for atomic operations
- Rename `coindices` argument names to `cosubscripts` to more closely correspond with the terms used in the Fortran standard
- Rename `local_buffer` and `local_buffer_stride` argument names to `current_image_buffer` and `current_image_buffer_stride`
- Update `coindexed-object` references to *coindexed-named-object* to match the term change in the most recent Fortran 2023 standard
- Convert several explanatory sections to “Notes”
- Add implementation note about PRIF being defined in Fortran
- Add section “How to read the PRIF specification”
- Add section “Glossary”
- Improve description of the `final_func` argument to `prif_allocate_coarray` and move some of previous description to a client note.

Revision 0.4 (Jul 2024)

- Changes to Coarray Access (puts and gets):
 - Refactor to provide separate procedure interfaces for the various combinations of: direct vs indirect target location, puts with or without a *notify-variable*, direct vs indirect *notify-variable* location, and strided vs contiguous data access.
 - Add discussion of direct and indirect location accesses to the Design Decisions and Impact section
 - Rename `_raw_` procedures to `_indirect_`
 - Replace `cosubscripts`, `team`, and `team_number` arguments with `image_num`
 - Replace `first_element_addr` arguments with `offset`
 - Replace `type(*)` value arguments with `size` and `current_image_buffer`
 - Rename `remote_ptr_stride` arguments to `remote_stride`
 - Rename `current_image_buffer_stride` arguments to `current_image_stride`
 - Rename `size` arguments to `size_in_bytes`
- Other changes to PRIF procedure interfaces:
 - Establish a new uniform argument ordering across all non-collective communication procedures
 - Remove `prif_base_pointer`. Direct access procedures should be used instead.
 - Add direct versions of `prif_event_post`, `prif_lock`, and `prif_unlock` and rename previous versions to `..._indirect`
 - Convert `prif_num_images` into three different procedures with no optional arguments, in order to more closely align with the Fortran standard. Do the same with `prif_image_index`.
 - Correct the kind for atomic procedures from `atomic_int_kind` to `PRIF_ATOMIC_INT_KIND` and from `atomic_logical_kind` to `PRIF_ATOMIC_LOGICAL_KIND`
 - Remove target attribute from `coarray_handles` argument in `prif_deallocate_coarray`
 - Rename `element_length` argument in `prif_allocate_coarray` to `element_size`
 - Rename `image_index` argument in `prif_this_image_no_coarray` to `this_image`
 - Remove generic interfaces throughout
- Miscellaneous new features:
 - Allow multiple calls to `prif_init` from each process, and add `PRIF_STAT_ALREADY_INIT` constant
 - Add new PRIF-specific constants `PRIF_VERSION_MAJOR` and `PRIF_VERSION_MINOR`
- Narrative and editorial improvements:
 - Add/improve Common Arguments subsections and add links to them below procedure interfaces
 - Elide argument lists for all procedures and add prose explaining how the PRIF specification presents the procedure interfaces
 - Add client notes to subsections introducing PRIF Types, and permute subsection order
 - Add guidance to clients regarding coarray dummy arguments
 - Remove grammar non-terminals, including `coindexed-named-object`
 - Add several terms to the glossary
 - Numerous minor wording changes throughout

Revision 0.5 (Dec 2024)

- Convert all instances of `c_intmax_t` to `c_int64_t`
- Replace `lbounds`, `ubounds`, `element_size` arguments in `prif_allocate_coarray` with `size_in_bytes`
- Specify definition of `prif_coarray_handle` to be a derived type with one member that is a pointer
- Add `prif_register_stop_callback`
- Remove `contiguous` attribute from argument `a` in collective subroutines
- Update argument list to `prif_co_reduce` to use `operation_wrapper` and add `cdata` argument
- Add `prif_co_max_character` and `prif_co_min_character`
- Constrain argument type for argument `a` to `prif_co_max`, `prif_co_min`, and `prif_co_sum`
- Add client note indicating that `prif_co_reduce` may be used to support other collective calls where `a` is not an interoperable type
- Clarify the semantics of derived types passed to `prif_co_broadcast`
- Add `prif_local_data_pointer`
- Prohibit overlap between source and destination memory regions in coarray access
- Numerous minor editorial changes throughout

Revision 0.6 (Sep 2025)

- Add `prif_initial_team_index` family of calls, to support image selectors within non-initial teams
- Add `data_pointer_offset` argument to `prif_alias_create`, update `prif_local_data_pointer` accordingly
- Clarify that aliased coarray descriptors should not be passed to `prif_size_bytes`
- Correct integer kind for `team_number` argument to `prif_image_index_with_team_number`
- Adjust prose to clarify that PRIF focuses on multi-image parallel features
- Numerous minor editorial changes throughout

Revision 0.7 (Dec 2025)

- `prif_deallocate_coarray` is renamed to `prif_deallocate_coarrays`
- Add `prif_deallocate_coarray` to deallocate a single coarray
- Specify a required definition for `prif_team_type`
- Specify additional constraints on the representation of `prif_event_type`, `prif_lock_type`, `prif_notify_type` and `prif_critical_type`

2 Problem Description

In order to be fully [Fortran 2023](#) compliant, a Fortran compiler needs support for what is commonly referred to as Coarray Fortran, which includes features related to multi-image parallelism. These features include the following statements, subroutines, functions, types, and kind type parameters:

- **Statements:**
 - *Synchronization:* SYNC ALL, SYNC IMAGES, SYNC MEMORY, SYNC TEAM
 - *Events:* EVENT POST, EVENT WAIT
 - *Notify:* NOTIFY WAIT
 - *Error termination:* ERROR STOP
 - *Locks:* LOCK, UNLOCK
 - *Failed images:* FAIL IMAGE
 - *Teams:* FORM TEAM, CHANGE TEAM
 - *Critical sections:* CRITICAL, END CRITICAL
- **Intrinsic functions:**
 - *Image Queries:* NUM_IMAGES, THIS_IMAGE, FAILED_IMAGES, STOPPED_IMAGES, IMAGE_STATUS
 - *Coarray Queries:* LCOBOUND, UCOBOUND, COSHAPE, IMAGE_INDEX
 - *Teams:* TEAM_NUMBER, GET_TEAM
- **Intrinsic subroutines:**
 - *Collective subroutines:* CO_SUM, CO_MAX, CO_MIN, CO_REDUCE, CO_BROADCAST
 - *Atomic subroutines:* ATOMIC_ADD, ATOMIC_AND, ATOMIC_CAS, ATOMIC_DEFINE, ATOMIC_FETCH_ADD, ATOMIC_FETCH_AND, ATOMIC_FETCH_OR, ATOMIC_FETCH_XOR, ATOMIC_OR, ATOMIC_REF, ATOMIC_XOR
 - *Other subroutines:* EVENT_QUERY
- **Types, kind type parameters, and values:**
 - *Intrinsic derived types:* EVENT_TYPE, TEAM_TYPE, LOCK_TYPE, NOTIFY_TYPE
 - *Atomic kind type parameters:* ATOMIC_INT_KIND, ATOMIC_LOGICAL_KIND
 - *Values:* STAT_FAILED_IMAGE, STAT_LOCKED, STAT_LOCKED_OTHER_IMAGE, STAT_STOPPED_IMAGE, STAT_UNLOCKED, STAT_UNLOCKED_FAILED_IMAGE

In addition to supporting the above features, compliant Fortran compilers also need to handle multi-image execution concepts such as image control. The image control concept affects the behaviors of some statements that were introduced in Fortran expressly for supporting multi-image parallel programming, but image control also affects the behavior of some statements that pre-existed parallelism in standard Fortran:

- **Image control statements:**
 - *Pre-existing statements:* ALLOCATE, DEALLOCATE, STOP, END, MOVE_ALLOC on coarray
 - *New statements:* SYNC ALL, SYNC IMAGES, SYNC MEMORY, SYNC TEAM, CHANGE TEAM, END TEAM, CRITICAL, END CRITICAL, EVENT POST, EVENT WAIT, FORM TEAM, LOCK, UNLOCK, NOTIFY WAIT

One example consequence of these statements being categorized as image control statements is the need to restrict movement of surrounding code by optimizing compilers.

Note that PRIF deliberately omits single-image parallel features (e.g. `do concurrent`) which are orthogonal to multi-image parallelism and out-of-scope for this specification.

3 Interface Description

This specification defines a library interface to support the features listed above, named the Parallel Runtime Interface for Fortran (PRIF). By defining an implementation-agnostic interface, we envision facilitating the development of alternative parallel runtime libraries that support the same interface. One benefit of this approach is the ability to vary the communication substrate. A central aim of this document is to specify a parallel runtime interface in standard Fortran syntax, which enables us to leverage Fortran to succinctly express various properties of the procedure interfaces, including argument attributes. See [Bonachea, Rasmussen, Richardson and Rouson \(2024\)](#) for additional details.

3.1 Parallel Runtime Interface for Fortran (PRIF)

The Parallel Runtime Interface for Fortran is a library interface in which the PRIF implementation is responsible for coarray allocation, deallocation and accesses, image synchronization, atomic operations, events, teams, and collective subroutines. In this interface, the compiler is responsible for transforming the invocation of Fortran-level multi-image parallelism features to add procedure calls to the necessary PRIF subroutines. Below is a table showing the delegation of tasks between the compiler and the PRIF implementation. The interface is designed for portability across shared- and distributed-memory machines, different operating systems, and multiple architectures.

Implementations of PRIF are intended as an augmentation for the compiler’s own runtime library. While the interface can support multiple implementations, we envision needing to build the PRIF implementation as part of installing the compiler. The procedures and types provided for direct invocation as part of the PRIF implementation shall be defined in a Fortran module with the name `prif`.

3.2 Delegation of tasks between the Fortran compiler and the PRIF implementation

The following table outlines which tasks are the responsibility of the Fortran compiler and which tasks are the responsibility of the PRIF implementation. A ‘X’ in the “Fortran compiler” column indicates that the compiler has the primary responsibility for that task, while a ‘X’ in the “PRIF implementation” column indicates that the compiler invokes the PRIF implementation to perform the task and the PRIF implementation has primary responsibility for the task’s implementation. See the [Procedure descriptions](#) for the list of PRIF implementation procedures that the compiler invokes.

| Tasks | Fortran compiler | PRIF implementation |
|---|------------------|---------------------|
| Allocate/initialize coarrays with <code>save</code> attribute prior to <code>main</code> | X | |
| Track corank of coarrays | X | |
| Track local coarrays for implicit deallocation when exiting a scope | X | |
| Initialize a coarray with <code>SOURCE=</code> as part of <code>ALLOCATE</code> | X | |
| Provide <code>prif_critical_type</code> coarrays for <code>CRITICAL</code> | X | |
| Track variable allocation status, including resulting from use of <code>MOVE_ALLOC</code> | X | |
| Provide final subroutine for each derived type appearing in a coarray that is finalizable or has allocatable components | X | |
| Intrinsics related to multi-image parallelism, e.g. <code>NUM_IMAGES</code> , <code>COSHAPE</code> | | X |
| Allocate and deallocate a coarray | | X |
| Reference a coindexed object | | X |
| Team statements/constructs: <code>FORM TEAM</code> , <code>CHANGE TEAM</code> , <code>END TEAM</code> | | X |
| Team stack abstraction | | X |
| Track coarrays for implicit deallocation at <code>END TEAM</code> | | X |
| Atomic subroutines, e.g. <code>ATOMIC_FETCH_ADD</code> | | X |
| Collective subroutines, e.g. <code>CO_BROADCAST</code> , <code>CO_SUM</code> | | X |
| Synchronization statements, e.g. <code>SYNC ALL</code> , <code>SYNC TEAM</code> | | X |
| Events: <code>EVENT POST</code> , <code>EVENT WAIT</code> | | X |
| Locks: <code>LOCK</code> , <code>UNLOCK</code> | | X |
| <code>CRITICAL</code> construct | | X |
| <code>NOTIFY WAIT</code> statement | | X |

NOTE: Caffeine - LBNL’s Implementation of the Parallel Runtime Interface for Fortran

Implementations for much of the Parallel Runtime Interface for Fortran exist in [Caffeine](#), a parallel runtime library supporting coarray Fortran compilers. Caffeine continues to be developed in order to fully implement PRIF. Caffeine targets the [GASNet-EX](#) exascale networking middleware, however PRIF is deliberately agnostic to details of the communication substrate. As such it should be possible to develop PRIF implementations targeting other substrates including the Message Passing Interface (MPI). See [Rouson and Bonachea \(2022\)](#) for additional details.

3.3 Design Decisions and Impact

As stated earlier, PRIF specifies a set of **Fortran** types, values, and procedure interfaces, all provided by the PRIF implementation in the `prif` Fortran module. This means that a compiler typically needs to transform Fortran code making use of the multi-image parallelism features as though it had been written to use PRIF directly. Conceptually this could happen as a source-to-source transformation, but in practice it's expected to happen in later phases of processing. It is worth further noting that whilst each implementation of PRIF defines the contents of the PRIF types and the values of the named constants, because PRIF is a Fortran module, a compiler should have access to their definitions during code compilation in the same way as other Fortran modules. One notable consequence of the current design is that different PRIF implementations will likely not be ABI compatible.

The PRIF design delegates the responsibility of defining the coarray descriptor, a metadata abstraction which tracks multi-image properties of each coarray, to the PRIF implementation. The PRIF implementation provides the compiler with a pointer-like handle (`prif_coarray_handle`) that references the coarray descriptor. The compiler is then responsible for storing and passing the handle back to the implementation for operations involving a given coarray. For Fortran procedures with coarray dummy arguments, the compiler should ensure that the coarray handle corresponding to the actual argument is made available for use in coarray operations within the procedure. This could be achieved by passing the handle as an extra argument, or by including the handle in a compiler-managed variable descriptor.

Many of the PRIF procedures providing communication involving coindexed data have direct and indirect variants. The direct variants accept a coarray handle as an argument and can operate on data stored within the coarray, i.e. memory locations allocated using `prif_allocate_coarray`. The indirect variants accept a pointer instead, and are used for operating on data which is not necessarily stored directly within a coarray, i.e. the memory location was either allocated using `prif_allocate`, or is being accessed through a pointer component in a different coarray. Note that for `put` operations, the target location of the coindexed assignment and the notify variable to be modified upon completion can independently be direct or indirect. The pointer to an indirect location is typically obtained using `prif_get*` to retrieve pointer information from the representation of an allocatable or pointer component of some derived type stored within a coarray.

The distinction between direct and indirect access is necessitated by the fact that coarrays are permitted to be of derived types with allocatable or pointer components. Unlike the coarray data, the target memory referenced by these components is generally allocated non-collectively, and those allocations can occur before or after the collective allocation of the coarray. Nevertheless, Fortran requires this target memory to be accessible to remote images. Consider the following program as an example:

```
program coarray_with_allocatable_component
  type :: my_type
    integer, allocatable :: component
  end type
  type(my_type) :: coarray[*]
  if (this_image() == 1) then
    allocate(coarray%component, source = 42)
  endif
  sync all
  print *, coarray[1]%component
end program
```

It is also valid for a pointer component in one coarray to reference data stored in another coarray. Consider the following program as an example:

```
program coarray_with_pointer_component
  type :: my_pointer
    integer, pointer :: val
  end type
  integer, target :: i[*]
  type(my_pointer) :: j[*]
  i = this_image()
  j%val => i
  sync all
  print *, j[1]%val
end program
```

3.4 How to read the PRIF specification

The PRIF types and procedures generally align with corresponding types and procedures from the Fortran standard. In many cases, the correspondence is clear from the identifiers. For example, the PRIF procedure `prif_num_images` corresponds to the intrinsic function `NUM_IMAGES` that is defined in the Fortran standard. In other cases, the correspondence may be less clear and is stated explicitly.

In order to avoid redundancy, some details are omitted from this document, because the corresponding descriptions in the Fortran standard contain the detailed specification of concepts and behavior required by the language. For example, this document references the term `coarray` multiple times, but does not define it since it is part of the language and the Fortran standard defines it. As such, in order to fully understand the PRIF specification, it is critical to read and reference the [Fortran 2023](#) standard alongside it. Additionally, the descriptions in the PRIF specification use similar language to the language used in the Fortran standard, for example terms like “shall”. Where PRIF uses terms not defined in the standard, their definitions may be found in the [Glossary](#).

4 PRIF Types and Named Constants

The types and named constants described in this section shall be defined in the `prif` module and have the `public` attribute, unless otherwise specified.

4.1 Fortran Intrinsic Derived Types

These types are defined by the PRIF implementation. The compiler should use these PRIF-provided implementation definitions for the corresponding types in the compiler’s implementation of the `ISO_FORTRAN_ENV` module. This enables the internal structure of each given type to be tailored as needed for a given PRIF implementation.

Each type specified in this section is defined by the PRIF implementation as a derived type with only private components. Each is an extensible type with no type parameters. Each nonallocatable component is fully default-initialized.

4.1.1 `prif_team_type`

- `prif_team_type` provides the implementation for `TEAM_TYPE` in `ISO_FORTRAN_ENV`
- The `prif_team_type` derived type shall be defined exactly as shown in the code snippet below. The `prif_team_descriptor` derived type shall be a private derived type with private components that are implementation-dependent.

```
type, public :: prif_team_type
  private
  type(prif_team_descriptor), pointer :: info => null()
end type
```

- The `prif_team_type` type shall only have intrinsic assignment.

4.1.2 `prif_event_type`

- `prif_event_type` provides the implementation for `EVENT_TYPE` in `ISO_FORTRAN_ENV`
- `prif_event_type` shall have a storage size no greater than 64 bytes (512 bits), and each nonallocatable component of the representation shall be default-initialized to all zero bits. It shall not require alignment greater than the maximum alignment requirement of any intrinsic type or pointer component.

4.1.3 `prif_lock_type`

- `prif_lock_type` provides the implementation for `LOCK_TYPE` in `ISO_FORTRAN_ENV`
- `prif_lock_type` shall have a storage size no greater than 64 bytes (512 bits), and each nonallocatable component of the representation shall be default-initialized to all zero bits. It shall not require alignment greater than the maximum alignment requirement of any intrinsic type or pointer component.

4.1.4 `prif_notify_type`

- `prif_notify_type` provides the implementation for `NOTIFY_TYPE` in `ISO_FORTRAN_ENV`
- `prif_notify_type` shall have a storage size no greater than 64 bytes (512 bits), and each nonallocatable component of the representation shall be default-initialized to all zero bits. It shall not require alignment greater than the maximum alignment requirement of any intrinsic type or pointer component.

CLIENT NOTE:

The components comprising the definitions of `prif_team_descriptor`, `prif_event_type`, `prif_lock_type` and `prif_notify_type` are deliberately unspecified by PRIF, and to ensure portability the compiler should not hard-code reliance on those details. However note that at compile-time the detailed representation corresponding to a given PRIF implementation is visible to the compiler in the interface declarations of the `prif` module.

4.2 PRIF-Specific Types

These derived types are defined by the PRIF implementation in the `prif` module. They don't correspond directly to types mandated by the Fortran specification, but rather are helper types used in PRIF to provide the multi-image Fortran features.

Each type specified in this section is defined by the PRIF implementation as a derived type with only private components and with no type parameters.

4.2.1 `prif_coarray_handle`

- `prif_coarray_handle` is a derived type provided by the PRIF implementation. It represents a reference to a coarray descriptor (also referred to as a “handle” for the coarray descriptor) and is passed back and forth across PRIF for coarray operations.
- The `prif_coarray_handle` derived type shall be defined exactly as shown in the code snippet below. The `prif_coarray_descriptor` derived type shall be a private derived type with private components that are implementation-dependent.

```
type, public :: prif_coarray_handle
  private
  type(prif_coarray_descriptor), pointer :: info
end type
```

- The `prif_coarray_handle` type shall only have intrinsic assignment.
- `prif_coarray_handle` values contain a pointer that is specific to a particular image. As such, handle values are not meaningful to other images and should not be directly passed between images.

4.2.2 `prif_critical_type`

- `prif_critical_type` is a derived type provided by the PRIF implementation that is used for implementing critical blocks.
- `prif_critical_type` shall have a storage size no greater than 64 bytes (512 bits), and each nonallocatable component of the representation shall be default-initialized to all zero bits. It shall not require alignment greater than the maximum alignment requirement of any intrinsic type or pointer component.

CLIENT NOTE:

The components comprising the `prif_coarray_descriptor` and `prif_critical_type` types are deliberately unspecified by PRIF, and to ensure portability the compiler should not hard-code reliance on those details. However note that at compile-time the detailed representation corresponding to a given PRIF implementation is visible to the compiler in the interface declarations of the `prif` module.

4.3 Named Constants in ISO_FORTRAN_ENV

These named constants are defined by the PRIF implementation, and it is suggested that the compiler deploy a rename to use the PRIF implementation definitions for these values in the compiler's implementation of the `ISO_FORTRAN_ENV` module.

4.3.1 PRIF_ATOMIC_INT_KIND

This shall be set to an implementation-defined value from the compiler-provided `INTEGER_KINDS` array.

4.3.2 PRIF_ATOMIC_LOGICAL_KIND

This shall be set to an implementation-defined value from the compiler-provided `LOGICAL_KINDS` array.

4.3.3 PRIF_CURRENT_TEAM

This shall be a value of type `integer(c_int)` that is defined by the implementation. It shall be distinct from the values `PRIF_INITIAL_TEAM` and `PRIF_PARENT_TEAM`

4.3.4 PRIF_INITIAL_TEAM

This shall be a value of type `integer(c_int)` that is defined by the implementation. It shall be distinct from the values `PRIF_CURRENT_TEAM` and `PRIF_PARENT_TEAM`

4.3.5 PRIF_PARENT_TEAM

This shall be a value of type `integer(c_int)` that is defined by the implementation. It shall be distinct from the values `PRIF_CURRENT_TEAM` and `PRIF_INITIAL_TEAM`

4.3.6 PRIF_STAT_FAILED_IMAGE

This shall be a value of type `integer(c_int)` that is defined by the implementation to be negative if the implementation cannot detect failed images and positive otherwise. It shall be distinct from all other stat named constants defined by this specification.

4.3.7 PRIF_STAT_LOCKED

This shall be a value of type `integer(c_int)` that is defined by the implementation. It shall be distinct from all other stat named constants defined by this specification.

4.3.8 PRIF_STAT_LOCKED_OTHER_IMAGE

This shall be a value of type `integer(c_int)` that is defined by the implementation. It shall be distinct from all other stat named constants defined by this specification.

4.3.9 PRIF_STAT_STOPPED_IMAGE

This shall be a positive value of type `integer(c_int)` that is defined by the implementation. It shall be distinct from all other stat named constants defined by this specification.

4.3.10 PRIF_STAT_UNLOCKED

This shall be a value of type `integer(c_int)` that is defined by the implementation. It shall be distinct from all other stat named constants defined by this specification.

4.3.11 PRIF_STAT_UNLOCKED_FAILED_IMAGE

This shall be a value of type `integer(c_int)` that is defined by the implementation. It shall be distinct from all other stat named constants defined by this specification.

4.4 PRIF-Specific Named Constants

These named constants have no directly corresponding constants specified in the Fortran standard.

4.4.1 PRIF_STAT_OUT_OF_MEMORY

This shall be a value of type `integer(c_int)` that is defined by the implementation. It shall be distinct from all other stat named constants defined by this specification. It shall indicate a low-memory error condition and may be produced by `prif_allocate_coarray` or `prif_allocate`.

4.4.2 PRIF_STAT_ALREADY_INIT

This shall be a value of type `integer(c_int)` that is defined by the implementation. It shall be distinct from all other stat named constants defined by this specification. It shall indicate that `prif_init` has previously been called.

4.4.3 PRIF_VERSION_MAJOR

This shall be a named constant of type `integer(c_int)` that is defined by the implementation and represents the major revision number of the PRIF specification (i.e. this document) that the implementation supports.

4.4.4 PRIF_VERSION_MINOR

This shall be a named constant of type `integer(c_int)` that is defined by the implementation and represents the minor revision number of the PRIF specification (i.e. this document) that the implementation supports.

5 PRIF Procedures

PRIF provides implementations of multi-image Fortran features, as specified in [Fortran 2023](#). For any given `prif_*` procedure that corresponds to a Fortran procedure or statement of similar name, the constraints and semantics associated with each argument to the `prif_*` procedure match those of the analogous argument to the multi-image Fortran feature, except where this document explicitly specifies otherwise. Similarly, the constraints and semantics of the PRIF procedure itself match those of the analogous multi-image Fortran feature, except where this document explicitly specifies otherwise. In particular, any image synchronization requirements specified for a multi-image Fortran feature are performed by the corresponding PRIF procedure, unless otherwise specified.

This section specifies PRIF subroutine declarations, formatted as in this example:

```
subroutine prif_stop(...)
  logical(c_bool), intent(in) :: quiet
  integer(c_int), intent(in), optional :: stop_code_int
  character(len=*), intent(in), optional :: stop_code_char
end subroutine
```

Unless otherwise noted, each such subroutine declaration appearing in this document specifies a public `module` `subroutine` interface declaration that shall be provided by a compliant PRIF implementation in the `prif` Fortran module, along with an implementation. As shown in the first line of the declaration above, the *dummy-arg-list* is elided using `...` as a presentational short-hand. Subroutine dummy arguments are specified in-order on subsequent lines, and compliant module subroutines shall accept dummy arguments using those same names and ordering.

Where `optional` dummy arguments would be allowed to appear in the corresponding multi-image Fortran feature, `optional` dummy arguments are used for the equivalent PRIF procedure. For most cases where a multi-image feature provides different overloads with different lists of valid arguments, distinct corresponding procedure variants are specified in PRIF.

IMPLEMENTATION NOTE:

PRIF is defined as a set of Fortran procedures, types and named constants, and as such an implementation of PRIF cannot be expressed solely in C/C++. However C/C++ can be used to implement internal portions of PRIF procedures via calls to `BIND(C)` procedures.

CLIENT NOTE:

PRIF procedures, types and named constants are defined as Fortran entities, *without* the `BIND(C)` attribute (except where otherwise noted), and thus clients should use them as such.

5.1 Common Arguments

There are multiple Common Arguments sections throughout this specification that outline details of the arguments that are common for the following sections of procedure interfaces.

5.1.1 Integer and Pointer Arguments

There are several categories of arguments where the PRIF implementation needs pointers and/or integers. These fall broadly into the following categories:

1. `integer(c_intptr_t)`: Anything containing a pointer representation where the compiler might be expected to perform pointer arithmetic
2. `type(c_ptr)` and `type(c_funptr)`: Anything containing a pointer to an object/function where the compiler is expected only to pass it (back) to the PRIF implementation
3. `integer(c_size_t)`: Anything containing an object size, in units of bytes or elements, e.g. `size_in_bytes`, `offset`, `shape`, etc.
4. `integer(c_ptrdiff_t)`: strides between elements for non-contiguous coarray accesses
5. `integer(c_int)`: Integer arguments corresponding to image index and stat arguments. It is expected that the most common integer arguments appearing in Fortran code are of default integer kind, it is expected that this will correspond with that kind, and there is no reason to expect these arguments to have values that would not be representable in this kind.
6. `integer(c_int64_t)`: Cobounds, indices, cosubscripts, and any other argument to an intrinsic procedure that accepts or produces an arbitrary integer.

The compiler is responsible for generating values and temporary variables as necessary to pass arguments of the correct type/size, and perform conversions when needed.

5.1.2 stat and errmsg Arguments

- **stat** : This argument is `intent(out)` and represents the presence and type of any error that occurs. A value of zero indicates no error occurred. It is of type `integer(c_int)`, to minimize the frequency that integer conversions are needed. If the user program provides a different kind of integer as the argument, it is the compiler's responsibility to use an intermediate variable as the argument to the PRIF procedure and provide conversion to the actual argument.
- **errmsg or errmsg_alloc** : There are two optional `intent(inout)` arguments for this, one which is allocatable and one which is not. It is the compiler's responsibility to ensure the appropriate optional argument is passed, and at most one shall be provided in any given call. If no error occurs, the definition status of the actual argument is unchanged.

5.2 Program Startup and Shutdown

For any program that uses multi-image Fortran features, the compiler shall insert calls to `prif_init` and `prif_stop`. These procedures initialize and terminate the multi-image parallel runtime. `prif_init` shall be called prior to any other calls to the PRIF implementation and shall be called at least once per process. Any second or subsequent call to `prif_init` by a given process is guaranteed to return immediately with no effect on system state, with `PRIF_STAT_ALREADY_INIT` assigned to the variable specified in the `stat` argument. `prif_stop` shall be called to initiate normal termination if the program reaches normal termination at the end of the main program.

5.2.1 `prif_init`

Description: This procedure initializes the multi-image parallel environment.

```
subroutine prif_init(...)
  integer(c_int), intent(out) :: stat
end subroutine
```

Further argument descriptions:

- **stat:** a zero value indicates success, the named constant `PRIF_STAT_ALREADY_INIT` indicates previous initialization and any other non-zero value indicates an error occurred during initialization

5.2.2 `prif_stop`

Description: This procedure synchronizes all executing images, cleans up the multi-image parallel runtime environment, and terminates the program. Calls to this procedure do not return. This procedure supports both normal termination at the end of a program, as well as any `STOP` statements from the user source code.

```
subroutine prif_stop(...)
  logical(c_bool), intent(in) :: quiet
  integer(c_int), intent(in), optional :: stop_code_int
  character(len=*), intent(in), optional :: stop_code_char
end subroutine
```

Further argument descriptions: At most one of the arguments `stop_code_int` or `stop_code_char` shall be supplied.

- **quiet:** if this argument has the value `.true.`, no output of signaling exceptions or stop code will be produced. If a `STOP` statement does not contain this optional part, the compiler should provide the value `.false.`
- **stop_code_int:** is used as the process exit code if it is provided. Otherwise, the process exit code is 0.
- **stop_code_char:** is written to the unit identified by the named constant `OUTPUT_UNIT` from the intrinsic module `ISO_FORTRAN_ENV` if provided.

5.2.3 `prif_error_stop`

Description: This procedure terminates all executing images. Calls to this procedure do not return.

```
subroutine prif_error_stop(...)
  logical(c_bool), intent(in) :: quiet
  integer(c_int), intent(in), optional :: stop_code_int
  character(len=*), intent(in), optional :: stop_code_char
end subroutine
```

Further argument descriptions: At most one of the arguments `stop_code_int` or `stop_code_char` shall be supplied.

- **quiet:** if this argument has the value `.true.`, no output of signaling exceptions or stop code will be produced. If an `ERROR STOP` statement does not contain this optional part, the compiler should provide the value `.false.`
- **stop_code_int:** is used as the process exit code if it is provided. Otherwise, the process exit code is a non-zero value.
- **stop_code_char:** is written to the unit identified by the named constant `ERROR_UNIT` from the intrinsic module `ISO_FORTRAN_ENV` if provided.

5.2.4 prif_register_stop_callback

Description: Register a procedure to be invoked when either `prif_stop` or `prif_error_stop` are invoked, before program termination. This procedure may be called multiple times to register multiple different callbacks that will all be invoked during the invocation of `prif_stop` or `prif_error_stop`, in the reverse order in which they were registered by the calling image. The registered procedure is permitted to invoke other `prif` procedures, so long as it does not cause subsequent invocation of either `prif_stop` or `prif_error_stop`. If an image invokes `prif_error_stop`, only that image will invoke the registered callback procedures. For a `prif_stop` invocation, the callback procedures will be invoked after all of the images have synchronized.

```
subroutine prif_register_stop_callback(...)
  procedure(prif_stop_callback_interface), pointer, intent(in) :: callback
end subroutine
```

Further argument descriptions:

- **callback:** shall be a pointer to a procedure with the following interface, where the `is_error_stop` argument indicates whether `prif_stop` or `prif_error_stop` was invoked, and the remaining arguments are the same as the arguments to the `prif_stop` or `prif_error_stop` procedure that led to this callback invocation. The abstract interface below shall be publicly defined in the `prif` module.

```
abstract interface
  subroutine prif_stop_callback_interface(...)
    logical(c_bool), intent(in) :: is_error_stop, quiet
    integer(c_int), intent(in), optional :: stop_code_int
    character(len=*), intent(in), optional :: stop_code_char
  end subroutine
end interface
```

5.2.5 prif_fail_image

Description: causes the executing image to cease participating in program execution without initiating termination. Calls to this procedure do not return.

```
subroutine prif_fail_image()
end subroutine
```

5.3 Image Queries

5.3.1 Common Arguments in Image Queries

- **team**: a value of type `prif_team_type` that identifies a current or ancestor team containing the calling image. When the **team** argument has the `optional` attribute and is absent, the team specified is the current team.

5.3.2 `prif_num_images`

Description: Query the number of images in the specified or current team.

```
subroutine prif_num_images(...)
  integer(c_int), intent(out) :: num_images
end subroutine

subroutine prif_num_images_with_team(...)
  type(prif_team_type), intent(in) :: team
  integer(c_int), intent(out) :: num_images
end subroutine

subroutine prif_num_images_with_team_number(...)
  integer(c_int64_t), intent(in) :: team_number
  integer(c_int), intent(out) :: num_images
end subroutine
```

[Argument descriptions](#)

Further argument descriptions:

- **team_number**: identifies the initial team or a sibling team of the current team

5.3.3 `prif_this_image`

Description: Query the image index, or cosubscripts with respect to an indicated coarray, of the calling image, with respect to a given team or the current team.

```
subroutine prif_this_image_no_coarray(...)
  type(prif_team_type), intent(in), optional :: team
  integer(c_int), intent(out) :: this_image
end subroutine

subroutine prif_this_image_with_coarray(...)
  type(prif_coarray_handle), intent(in) :: coarray_handle
  type(prif_team_type), intent(in), optional :: team
  integer(c_int64_t), intent(out) :: cosubscripts(:)
end subroutine

subroutine prif_this_image_with_dim(...)
  type(prif_coarray_handle), intent(in) :: coarray_handle
  integer(c_int), intent(in) :: dim
  type(prif_team_type), intent(in), optional :: team
  integer(c_int64_t), intent(out) :: cosubscript
end subroutine
```

[Argument descriptions](#)

Further argument descriptions:

- **coarray_handle**: handle for a descriptor of an established coarray
- **cosubscripts**: the cosubscripts that would identify the calling image in the specified team when used as cosubscripts for the specified coarray
- **dim**: identify which of the elements from **cosubscripts** should be produced as the **cosubscript** value
- **cosubscript**: the element identified by **dim** of the array **cosubscripts** that would have been produced without the **dim** argument present

5.3.4 prif_failed_images

Description: Query the image indices of any images known to have failed. It is the compiler's responsibility to convert to a different kind if the `kind` argument to `FAILED_IMAGES` appears.

```
subroutine prif_failed_images(...)
  type(prif_team_type), intent(in), optional :: team
  integer(c_int), allocatable, intent(out) :: failed_images(:)
end subroutine
```

[Argument descriptions](#)

5.3.5 prif_stopped_images

Description: Query the image indices of any images known to have initiated normal termination. It is the compiler's responsibility to convert to a different kind if the `kind` argument to `STOPPED_IMAGES` appears.

```
subroutine prif_stopped_images(...)
  type(prif_team_type), intent(in), optional :: team
  integer(c_int), allocatable, intent(out) :: stopped_images(:)
end subroutine
```

[Argument descriptions](#)

5.3.6 prif_image_status

Description: Query the image execution state of an image

```
subroutine prif_image_status(...)
  integer(c_int), intent(in) :: image
  type(prif_team_type), intent(in), optional :: team
  integer(c_int), intent(out) :: image_status
end subroutine
```

[Argument descriptions](#)

Further argument descriptions:

- **image:** the image index of the image in the given or current team for which to produce the execution status
- **image_status:** defined to the value `PRIF_STAT_FAILED_IMAGE` if the identified image is known to have failed, `PRIF_STAT_STOPPED_IMAGE` if the identified image is known to have initiated normal termination, otherwise zero.

5.4 Storage Management

5.4.1 prif_allocate_coarray

Description: This procedure allocates a coarray and provides a handle referencing a corresponding coarray descriptor. This call is collective over the current team. Calls to `prif_allocate_coarray` are inserted by the compiler when there is an explicit coarray allocation or at the beginning of a program to allocate space for coarrays with the `save` attribute (explicit or implicit). The PRIF implementation stores the coshape information in order to internally track it during the lifetime of the coarray.

```

subroutine prif_allocate_coarray(...)
  integer(c_int64_t), intent(in) :: lcobounds(:), ucobounds(:)
  integer(c_size_t), intent(in) :: size_in_bytes
  type(c_funptr), intent(in) :: final_func
  type(prif_coarray_handle), intent(out) :: coarray_handle
  type(c_ptr), intent(out) :: allocated_memory
  integer(c_int), intent(out), optional :: stat
  character(len=*), intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine

```

Further argument descriptions:

- **lcobounds** and **ucobounds**: Shall be the lower and upper bounds of the codimensions of the coarray being allocated. Shall be rank-one arrays with the same dimensions as each other. The specified cobounds shall be sufficient to have a unique index for every image in the current team. I.e. `product(ucobounds - lcobounds + 1) >= num_images()`.
- **size_in_bytes**: The size, in bytes, of the calling image's portion of the coarray element data. This argument shall have the same value on all images in corresponding calls.
- **final_func**: Shall be the C address of a procedure that is interoperable, or `C_NULL_FUNPTR`. If not null, this procedure will be invoked by the PRIF implementation once by each image at deallocation of this coarray, before the storage is released. If provided, the procedure's interface shall be equivalent to the following Fortran interface:

```

subroutine coarray_cleanup(handle, stat, errmsg) bind(C)
  type(prif_coarray_handle), pointer, intent(in) :: handle
  integer(c_int), intent(out) :: stat
  character(len=:), intent(out), allocatable :: errmsg
end subroutine

```

or to the following equivalent C prototype:

```

void coarray_cleanup(
    CFI_cdesc_t* handle, int* stat, CFI_cdesc_t* errmsg)

```

- **coarray_handle**: A handle referencing the calling image's coarray descriptor of the allocated coarray. The descriptor and handle are created by the PRIF implementation, and the compiler uses the handle for subsequent operations involving the associated coarray and for deallocation of the associated coarray.
- **allocated_memory**: A pointer to the block of allocated but uninitialized memory that provides the storage for the calling image's coarray element data. The compiler is responsible for associating the Fortran-level coarray object with this storage, and initializing the storage if necessary. The produced pointer value may differ across corresponding calls from images in the team.

CLIENT NOTE:

final_func is used by the compiler to support various clean-up operations at coarray deallocation, whether it happens explicitly (i.e. via `prif_deallocate_coarray(s)`) or implicitly (e.g. via `prif_end_team`). First, **final_func** may be used to support the user-defined final subroutine for derived types. Second, it may be necessary for the compiler to generate such a subroutine to clean up allocatable components, typically with calls to `prif_deallocate`. Third, it may also be necessary to modify the allocation status of an allocatable coarray variable, especially in the case that it was allocated through a dummy argument.

The coarray handle can be interrogated by the procedure callback using PRIF queries to determine the memory address and size of the data in order to orchestrate calling any necessary final subroutines or deallocation of any allocatable components, or the context data to orchestrate modifying the allocation status of a local variable portion of the coarray. The **pointer** attribute for the **handle** argument is required because `prif_coarray_handle` is not C interoperable.

5.4.2 prif_allocate

Description: This procedure is used to non-collectively allocate remotely accessible storage, such as needed for an allocatable component of a coarray.

```
subroutine prif_allocate(...)
  integer(c_size_t), intent(in) :: size_in_bytes
  type(c_ptr), intent(out) :: allocated_memory
  integer(c_int), intent(out), optional :: stat
  character(len=*), intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine
```

Further argument descriptions:

- **size_in_bytes:** The size, in bytes, of the object to be allocated.
- **allocated_memory:** A pointer to the block of allocated but uninitialized memory that provides the requested storage. The compiler is responsible for associating the Fortran object with this storage, and initializing the storage if necessary.

5.4.3 prif_deallocate_coarray

Description: This procedure releases memory previously allocated for the coarray associated with the handle in `coarray_handle`. This means that any local objects associated with this memory become invalid. The compiler shall insert calls to this procedure when exiting a local scope where implicit deallocation of a coarray is mandated by the standard and when a coarray is explicitly deallocated through a `DEALLOCATE` statement. This call is collective over the current team, and the provided handle must denote corresponding coarray descriptors that were allocated by the current team using `prif_allocate_coarray` and not yet deallocated. The implementation starts with a synchronization over the current team, and then the final subroutine for the coarray (if any) is called. A synchronization also occurs before control is returned from this procedure, after all deallocation has been completed.

```
subroutine prif_deallocate_coarray(...)
  type(prif_coarray_handle), intent(in) :: coarray_handle
  integer(c_int), intent(out), optional :: stat
  character(len=*), intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine
```

Further argument descriptions:

- **coarray_handle:** Is the handle of the coarray that shall be deallocated.

5.4.4 prif_deallocate_coarrays

Description: This procedure has behavior analogous to `prif_deallocate_coarray`, except that it operates on an array of handles. The provided array of handles must have the same size on each image and denote corresponding coarray descriptors (in the same order on every image). All coarrays referenced by the handles in `coarray_handles` are deallocated collectively over the current team. As with `prif_deallocate_coarray`, the call starts and ends with a synchronization over the current team, but need not include additional synchronization (e.g. between deallocation of individual coarrays).

```
subroutine prif_deallocate_coarrays(...)
  type(prif_coarray_handle), intent(in) :: coarray_handles(:)
  integer(c_int), intent(out), optional :: stat
  character(len=*), intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine
```

Further argument descriptions:

- **coarray_handles:** Is an array of all of the handles for the coarrays that shall be deallocated.

5.4.5 prif_deallocate

Description: This non-collective procedure releases memory previously allocated by a call to `prif_allocate` and not yet deallocated.

```
subroutine prif_deallocate(...)
  type(c_ptr), intent(in) :: mem
  integer(c_int), intent(out), optional :: stat
  character(len=*), intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine
```

Further argument descriptions:

- **mem:** Pointer to the block of memory to be released.

CLIENT NOTE:

Calls to `prif_allocate_coarray` and `prif_deallocate_coarray(s)` are collective operations, while calls to `prif_allocate` and `prif_deallocate` are not. Note that a call to `MOVE_ALLOC` with coarray arguments is also a collective operation, as described in the section below.

CLIENT NOTE:

The compiler is responsible to generate code that collectively runs `prif_allocate_coarray` once for each coarray with the `save` attribute (explicit or implicit) and initialize them where applicable.

5.4.6 prif_alias_create

Description: Create a new coarray descriptor aliased to an existing coarray, with possibly altered corank, cobounds and/or element data offset. This may be needed as part of `CHANGE TEAM` after [prif_change_team](#), or to pass to a coarray dummy argument (especially in the case that the cobounds are different). This call does not alter data in the coarray.

```
subroutine prif_alias_create(...)
  type(prif_coarray_handle), intent(in) :: source_handle
  integer(c_int64_t), intent(in) :: alias_lcobounds(:)
  integer(c_int64_t), intent(in) :: alias_ucobounds(:)
  integer(c_size_t), intent(in) :: data_pointer_offset
  type(prif_coarray_handle), intent(out) :: alias_handle
end subroutine
```

Further argument descriptions:

- **source_handle:** a handle to an existing coarray descriptor (which may itself be an alias) for which a new alias descriptor is to be created. The original descriptor is not modified.
- **alias_lcobounds** and **alias_ucobounds:** the cobounds to be used for the new alias. Both arguments must have the same size, but it need not match the corank associated with **source_handle**
- **data_pointer_offset:** specifies an offset in bytes from the beginning of the element data referenced by **source_handle** descriptor where the element data for the **alias_handle** descriptor should begin. Passing zero implies that **source_handle** and **alias_handle** alias the exact same element data.
- **alias_handle:** a handle to a new coarray descriptor that aliases the data in an existing coarray

5.4.7 prif_alias_destroy

Description: Delete an alias descriptor for a coarray. Does not deallocate or alter the original coarray.

```
subroutine prif_alias_destroy(...)
  type(prif_coarray_handle), intent(in) :: alias_handle
end subroutine
```

Further argument descriptions:

- **alias_handle:** handle to the alias descriptor to be destroyed

5.4.8 MOVE_ALLOC

MOVE_ALLOC is not provided by PRIF because it depends on unspecified details of the compiler's allocatable representation. It is the compiler's responsibility to implement MOVE_ALLOC using PRIF-provided operations. For example, according to the Fortran standard, MOVE_ALLOC with coarray arguments is an image control statement that requires synchronization, so the compiler should likely insert call(s) to `prif_sync_all` as part of the implementation.

CLIENT NOTE:

The use of `prif_set_context_data` and `prif_get_context_data` can allow for an efficient implementation of MOVE_ALLOC that maintains tracking of allocation status.

5.5 Coarray Queries

5.5.1 Common Arguments in Coarray Queries

- **coarray_handle**: a handle for a descriptor of an established coarray to be accessed by this operation

5.5.2 prif_image_index

Description: This procedure queries the index of the image, on the identified team or the current team if no team is provided, identified by the cosubscripts provided in the `sub` argument applied to the indicated coarray descriptor.

```
subroutine prif_image_index(...)
  type(prif_coarray_handle), intent(in) :: coarray_handle
  integer(c_int64_t), intent(in) :: sub(:)
  integer(c_int), intent(out) :: image_index
end subroutine

subroutine prif_image_index_with_team(...)
  type(prif_coarray_handle), intent(in) :: coarray_handle
  integer(c_int64_t), intent(in) :: sub(:)
  type(prif_team_type), intent(in) :: team
  integer(c_int), intent(out) :: image_index
end subroutine

subroutine prif_image_index_with_team_number(...)
  type(prif_coarray_handle), intent(in) :: coarray_handle
  integer(c_int64_t), intent(in) :: sub(:)
  integer(c_int64_t), intent(in) :: team_number
  integer(c_int), intent(out) :: image_index
end subroutine
```

[Argument descriptions](#)

Further argument descriptions:

- **team** and **team_number**: Identifies the selected team, otherwise the selected team is the current team. `sub` is interpreted relative to the selected team, and the resulting image index is relative to the selected team.
- **sub**: A list of integers that identify a specific image in the selected team when interpreted as cosubscripts for the specified coarray descriptor.
- **image_index**: When the cosubscripts in `sub` fall within the cobounds of the coarray descriptor and the corresponding image index is not greater than the number of images in the selected team, `image_index` is defined to the index of the corresponding image, relative to the selected team. Otherwise, `image_index` is defined to zero.

CLIENT NOTE:

`prif_image_index` can be used to implement IMAGE_INDEX.

5.5.3 prif_initial_team_index

Description: This procedure is analogous to `prif_image_index`, with the following differences:

1. The resulting value identifies the corresponding image using its image index relative to the initial team, regardless of the selected team.
2. If the cosubscripts in `sub` fall outside the cobounds of the coarray descriptor, or would specify an image index greater than the number of images in the selected team, then behavior is undefined.
3. The optional `stat` output indicates selection of a known failed image.

```

subroutine prif_initial_team_index(...)
  type(prif_coarray_handle), intent(in) :: coarray_handle
  integer(c_int64_t), intent(in) :: sub(:)
  integer(c_int), intent(out) :: initial_team_index
  integer(c_int), intent(out), optional :: stat
end subroutine

subroutine prif_initial_team_index_with_team(...)
  type(prif_coarray_handle), intent(in) :: coarray_handle
  integer(c_int64_t), intent(in) :: sub(:)
  type(prif_team_type), intent(in) :: team
  integer(c_int), intent(out) :: initial_team_index
  integer(c_int), intent(out), optional :: stat
end subroutine

subroutine prif_initial_team_index_with_team_number(...)
  type(prif_coarray_handle), intent(in) :: coarray_handle
  integer(c_int64_t), intent(in) :: sub(:)
  integer(c_int64_t), intent(in) :: team_number
  integer(c_int), intent(out) :: initial_team_index
  integer(c_int), intent(out), optional :: stat
end subroutine

```

Argument descriptions

Further argument descriptions:

- **team** and **team_number**: Identifies the selected team, otherwise the selected team is the current team.
- **sub**: A list of integers that identify a specific image in the selected team when interpreted as cosubscripts for the specified coarray descriptor. The cosubscripts shall fall within the cobounds of the coarray descriptor, and shall specify an image index not greater than the number of images in the selected team.
- **initial_team_index**: defined to the index of the corresponding image, relative to the initial team.
- **stat**: defined to `PRIF_STAT_FAILED_IMAGE` if the image identified by the cosubscripts is known to have failed, otherwise defined to zero.

CLIENT NOTE:

`prif_initial_team_index` can be used to implement image selectors in coindexed accesses. It produces an image number relative to the initial team, which is required by many PRIF communication operations.

5.5.4 prif_lcobound

Description: This procedure queries the lower cobound(s) associated with a coarray descriptor. It is the compiler's responsibility to convert to a different kind if the **kind** argument to LCOBOUND appears.

```
subroutine prif_lcobound_no_dim(...)
  type(prif_coarray_handle), intent(in) :: coarray_handle
  integer(c_int64_t), intent(out) :: lcobounds(:)
end subroutine

subroutine prif_lcobound_with_dim(...)
  type(prif_coarray_handle), intent(in) :: coarray_handle
  integer(c_int), intent(in) :: dim
  integer(c_int64_t), intent(out):: lcobound
end subroutine
```

Argument descriptions

Further argument descriptions:

- **lcobounds:** an array of the size of the corank of the coarray descriptor, defined to the lower cobounds of the indicated coarray descriptor
- **dim:** which codimension of the coarray descriptor to report the lower cobound of
- **lcobound:** the lower cobound of the given dimension

5.5.5 prif_ucobound

Description: This procedure queries the upper cobound(s) associated with a coarray descriptor. It is the compiler's responsibility to convert to a different kind if the **kind** argument to UCBOUND appears.

```
subroutine prif_ucobound_no_dim(...)
  type(prif_coarray_handle), intent(in) :: coarray_handle
  integer(c_int64_t), intent(out) :: ucobounds(:)
end subroutine

subroutine prif_ucobound_with_dim(...)
  type(prif_coarray_handle), intent(in) :: coarray_handle
  integer(c_int), intent(in) :: dim
  integer(c_int64_t), intent(out):: ucobound
end subroutine
```

Argument descriptions

Further argument descriptions:

- **ucobounds:** an array of the size of the corank of the coarray descriptor, defined to the upper cobounds of the indicated coarray descriptor
- **dim:** which codimension of the coarray descriptor to report the upper cobound of
- **ucobound:** the upper cobound of the given dimension

5.5.6 prif_coshape

Description: This procedure queries the sizes of codimensions of a coarray descriptor. It is the compiler's responsibility to convert to a different kind if the **kind** argument to COSHAPE appears.

```
subroutine prif_coshape(...)
  type(prif_coarray_handle), intent(in) :: coarray_handle
  integer(c_size_t), intent(out) :: sizes(:)
end subroutine
```

Argument descriptions

Further argument descriptions:

- **sizes:** an array whose size matches the corank of the indicated coarray descriptor, defined to the difference between the upper and lower cobounds + 1

5.5.7 prif_local_data_pointer

Description: This procedure queries a `c_ptr` referencing the block of storage containing the calling image's element data in the coarray descriptor associated with the given handle. In the case of a `prif_coarray_handle` constructed by a call to `prif_allocate_coarray`, the `local_data` argument is defined to the same value as the `allocated_memory` argument provided during allocation of that coarray. In the case of a `prif_coarray_handle` constructed by a call to `prif_alias_create`, the `local_data` argument is defined to a value that reflects the sum of any offsets applied using the `data_pointer_offset` argument to `prif_alias_create`.

```
subroutine prif_local_data_pointer(...)
  type(prif_coarray_handle), intent(in) :: coarray_handle
  type(c_ptr), intent(out) :: local_data
end subroutine
```

Argument descriptions

5.5.8 prif_size_bytes

Description: This procedure queries the size of the coarray element data associated with each image. This is equal to the `size_in_bytes` argument provided to the `prif_allocate_coarray` invocation that constructed the descriptor referenced by `coarray_handle`. If the `coarray_handle` descriptor was constructed by `prif_alias_create`, the result is unspecified.

```
subroutine prif_size_bytes(...)
  type(prif_coarray_handle), intent(in) :: coarray_handle
  integer(c_size_t), intent(out) :: data_size
end subroutine
```

Argument descriptions

CLIENT NOTE:

`prif_size_bytes` can be used to calculate the number of elements in an array coarray given only the handle and element size

5.5.9 prif_set_context_data

Description: This procedure stores a `c_ptr` associated with a coarray for future retrieval. A typical usage would be to store a reference to the actual variable whose allocation status must be changed in the case that the coarray is deallocated.

```
subroutine prif_set_context_data(...)
  type(prif_coarray_handle), intent(in) :: coarray_handle
  type(c_ptr), intent(in) :: context_data
end subroutine
```

Argument descriptions

CLIENT NOTE:

Each coarray includes some “context data” on a per-image basis, which the compiler may use to support proper implementation of coarray arguments, especially with respect to `MOVE_ALLOC` operations on allocatable coarrays. This data is accessed using the procedures `prif_get_context_data` and `prif_set_context_data`. PRIF does not interpret the contents of this context data in any way, and it is only accessible on the current image. The context data is a property of the allocated coarray object, and is thus shared between all handles and aliased descriptors that refer to the same coarray allocation (i.e. those created from a call to `prif_alias_create`).

5.5.10 prif_get_context_data

Description: This procedure queries the `c_ptr` provided in the most recent call to `prif_set_context_data` with the same coarray (possibly via an aliased coarray descriptor).

```
subroutine prif_get_context_data(...)
  type(prif_coarray_handle), intent(in) :: coarray_handle
  type(c_ptr), intent(out) :: context_data
end subroutine
```

Argument descriptions

5.6 Contiguous Coarray Access

The memory consistency semantics of coarray accesses follow those defined by the Image Execution Control section of the Fortran standard. In particular, coarray accesses maintain serial dependencies for the issuing image. Any data access ordering between images is defined only with respect to ordered segments. Note that for put operations, “source completion” means that the provided source locations are no longer needed (e.g. their memory can be freed once the procedure has returned).

5.6.1 Common Arguments in Contiguous Coarray Access

- **image_num**
 - an argument identifying the image to be communicated with
 - is permitted to identify the calling image
 - this image index is always relative to the initial team, regardless of the current team
- **coarray_handle**: handle for a descriptor of an established coarray to be accessed by this operation. **offset** and **size_in_bytes** must specify a range of storage entirely contained within the element data of the indicated coarray.
- **offset**: indicates an offset in bytes from the beginning of the elements in a remote coarray (indicated by **coarray_handle**) on a selected image (indicated by **image_num**)
- **remote_ptr**: pointer to where on the identified image the data begins. The referenced storage must have been allocated using **prif_allocate** or **prif_allocate_coarray**.
- **current_image_buffer**: pointer to contiguous memory on the calling image that either contains the source data to be copied (puts) or is the destination memory for the data to be retrieved (gets).
- **size_in_bytes**: how much data is to be transferred in bytes
- **notify_ptr**: pointer on the identified image to the notify variable that should be updated after completion of the put operation. The referenced variable shall be of type **prif_notify_type**, and the storage must have been allocated using **prif_allocate** or **prif_allocate_coarray**.
- **notify_coarray_handle, notify_offset**: a coarray handle and byte offset that identifies the location of a **prif_notify_type** variable to be updated after completion of the put operation. That variable must be entirely contained within the element data of the coarray indicated by **notify_coarray_handle**

5.6.2 prif_get

Description: This procedure fetches data in a coarray from a specified image, when the data to be copied are contiguous in linear memory on both sides. The compiler can use this to implement reads from a coindexed object. It need not call PRIF when a coarray reference is not a coindexed object. This procedure blocks until the requested data has been successfully assigned to the **current_image_buffer** argument. If **image_num** indicates the calling image and there is any overlap between the source and destination memory regions, then behavior is undefined. This procedure corresponds to a coindexed object reference that reads contiguous coarray data.

```
subroutine prif_get(...)
  integer(c_int), intent(in) :: image_num
  type(prif_coarray_handle), intent(in) :: coarray_handle
  integer(c_size_t), intent(in) :: offset
  type(c_ptr), intent(in) :: current_image_buffer
  integer(c_size_t), intent(in) :: size_in_bytes
  integer(c_int), intent(out), optional :: stat
  character(len=*), intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine
```

5.6.3 prif_get_indirect

Description: This procedure implements the semantics of [prif_get](#) but fetches `size_in_bytes` number of contiguous bytes from the given image, starting at `remote_ptr` on the given image, copying into `current_image_buffer`.

```
subroutine prif_get_indirect(...)
  integer(c_int), intent(in) :: image_num
  integer(c_intptr_t), intent(in) :: remote_ptr
  type(c_ptr), intent(in) :: current_image_buffer
  integer(c_size_t), intent(in) :: size_in_bytes
  integer(c_int), intent(out), optional :: stat
  character(len=*), intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine
```

Argument descriptions

5.6.4 prif_put

Description: This procedure assigns to the element data of a coarray, when the data to be assigned are contiguous in linear memory on both sides. The compiler can use this to implement intrinsic assignment to a coindexed object. It need not call PRIF when a coarray reference is not a coindexed object. This procedure blocks on source completion. If `image_num` indicates the calling image and there is any overlap between the source and destination memory regions, then behavior is undefined. This procedure corresponds to a contiguous coindexed object reference on the left hand side of an intrinsic assignment statement.

```
subroutine prif_put(...)
  integer(c_int), intent(in) :: image_num
  type(prif_coarray_handle), intent(in) :: coarray_handle
  integer(c_size_t), intent(in) :: offset
  type(c_ptr), intent(in) :: current_image_buffer
  integer(c_size_t), intent(in) :: size_in_bytes
  integer(c_int), intent(out), optional :: stat
  character(len=*), intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine
```

Argument descriptions

5.6.5 prif_put_indirect

Description: This procedure implements the semantics of [prif_put](#) but assigns to `size_in_bytes` number of contiguous bytes on the given image, starting at `remote_ptr` on the given image, copying from `current_image_buffer`.

```
subroutine prif_put_indirect(...)
  integer(c_int), intent(in) :: image_num
  integer(c_intptr_t), intent(in) :: remote_ptr
  type(c_ptr), intent(in) :: current_image_buffer
  integer(c_size_t), intent(in) :: size_in_bytes
  integer(c_int), intent(out), optional :: stat
  character(len=*), intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine
```

Argument descriptions

5.6.6 prif_put_with_notify

Description: This procedure implements the semantics of `prif_put` with the addition of support for the semantics of the `NOTIFY=` specifier through a coarray handle and an offset

```
subroutine prif_put_with_notify(...)
  integer(c_int), intent(in) :: image_num
  type(prif_coarray_handle), intent(in) :: coarray_handle
  integer(c_size_t), intent(in) :: offset
  type(c_ptr), intent(in) :: current_image_buffer
  integer(c_size_t), intent(in) :: size_in_bytes
  type(prif_coarray_handle), intent(in) :: notify_coarray_handle
  integer(c_size_t), intent(in) :: notify_offset
  integer(c_int), intent(out), optional :: stat
  character(len=*), intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine
```

Argument descriptions

5.6.7 prif_put_with_notify_indirect

Description: This procedure implements the semantics of `prif_put` with the addition of support for the semantics of the `NOTIFY=` specifier through a pointer

```
subroutine prif_put_with_notify_indirect(...)
  integer(c_int), intent(in) :: image_num
  type(prif_coarray_handle), intent(in) :: coarray_handle
  integer(c_size_t), intent(in) :: offset
  type(c_ptr), intent(in) :: current_image_buffer
  integer(c_size_t), intent(in) :: size_in_bytes
  integer(c_intptr_t), intent(in) :: notify_ptr
  integer(c_int), intent(out), optional :: stat
  character(len=*), intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine
```

Argument descriptions

5.6.8 prif_put_indirect_with_notify

Description: This procedure implements the semantics of `prif_put` but assigns to `size_in_bytes` number of contiguous bytes on the given image, starting at `remote_ptr` on the given image, copying from `current_image_buffer` and with support for the `NOTIFY=` specifier through a coarray handle and offset

```
subroutine prif_put_indirect_with_notify(...)
  integer(c_int), intent(in) :: image_num
  integer(c_intptr_t), intent(in) :: remote_ptr
  type(c_ptr), intent(in) :: current_image_buffer
  integer(c_size_t), intent(in) :: size_in_bytes
  type(prif_coarray_handle), intent(in) :: notify_coarray_handle
  integer(c_size_t), intent(in) :: notify_offset
  integer(c_int), intent(out), optional :: stat
  character(len=*), intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine
```

Argument descriptions

5.6.9 prif_put_indirect_with_notify_indirect

Description: This procedure implements the semantics of `prif_put` but assigns to `size_in_bytes` number of contiguous bytes on the given image, starting at `remote_ptr` on the given image, copying from `current_image_buffer` and with support for the `NOTIFY=` specifier through a pointer

```
subroutine prif_put_indirect_with_notify_indirect(...)
  integer(c_int), intent(in) :: image_num
  integer(c_intptr_t), intent(in) :: remote_ptr
  type(c_ptr), intent(in) :: current_image_buffer
  integer(c_size_t), intent(in) :: size_in_bytes
  integer(c_intptr_t), intent(in) :: notify_ptr
  integer(c_int), intent(out), optional :: stat
  character(len=*), intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine
```

Argument descriptions

5.7 Strided Coarray Access

5.7.1 Common Arguments in Strided Coarray Access

- **image_num**
 - an argument identifying the image to be communicated with
 - is permitted to identify the calling image
 - this image index is always relative to the initial team, regardless of the current team
- **coarray_handle**: handle for a descriptor of an established coarray to be accessed by this operation. The combination of arguments must specify a set of storage locations entirely contained within the element data of the indicated coarray.
- **offset**: indicates an offset in bytes from the beginning of the elements in a remote coarray (indicated by `coarray_handle`) on a selected image (indicated by `image_num`)
- **remote_ptr**: pointer to where on the identified image the data begins. The referenced storage must have been allocated using `prif_allocate` or `prif_allocate_coarray`.
- **remote_stride**: The stride (in units of bytes) between elements in each dimension on the specified image. Each component of stride may independently be positive or negative, but (together with `extent`) must specify a region of distinct (non-overlapping) locations. For the procedures that provide the `remote_ptr` argument, the striding starts at the `remote_ptr`. For the procedures that provide the `coarray_handle` and `offset` arguments, the striding starts at the location that resides at `offset` bytes past the beginning of the remote elements indicated by `coarray_handle`.
- **current_image_buffer**: pointer to memory on the calling image that either contains the source data to be copied (puts) or is the destination memory for the data to be retrieved (gets).
- **current_image_stride**: The stride (in units of bytes) between elements in each dimension in the calling image buffer. Each component of stride may independently be positive or negative, but (together with `extent`) must specify a region of distinct (non-overlapping) locations. The striding starts at the `current_image_buffer`.
- **element_size**: The size, in bytes, of each block of contiguous element data to be copied
- **extent**: How many elements in each dimension should be transferred. `remote_stride`, `current_image_stride` and `extent` must all have equal size.
- **notify_coarray_handle, notify_offset**: a coarray handle and byte offset that identifies the location of a `prif_notify_type` variable to be updated after completion of the put operation. That variable must be entirely contained within the element data of the coarray indicated by `notify_coarray_handle`
- **notify_ptr**: pointer on the identified image to the notify variable that should be updated after completion of the put operation. The referenced variable shall be of type `prif_notify_type`, and the storage must have been allocated using `prif_allocate` or `prif_allocate_coarray`.

5.7.2 prif_get_strided

Description: Copy data from the given image and indicated coarray, writing into `current_image_buffer`, progressing through `current_image_buffer` in `current_image_stride` increments and through remote memory in `remote_stride` increments, transferring `extent` number of elements in each dimension. This procedure blocks until the requested data has been successfully assigned to the destination locations on the calling image. If `image_num` indicates the calling image and any memory location is specified as both a source and destination location, then behavior is undefined.

```
subroutine prif_get_strided(...)
  integer(c_int), intent(in) :: image_num
  type(prif_coarray_handle), intent(in) :: coarray_handle
  integer(c_size_t), intent(in) :: offset
  integer(c_ptrdiff_t), intent(in) :: remote_stride(:)
  type(c_ptr), intent(in) :: current_image_buffer
  integer(c_ptrdiff_t), intent(in) :: current_image_stride(:)
  integer(c_size_t), intent(in) :: element_size
  integer(c_size_t), intent(in) :: extent(:)
  integer(c_int), intent(out), optional :: stat
  character(len=*), intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine
```

Argument descriptions

5.7.3 prif_get_strided_indirect

Description: This procedure implements the semantics of `prif_get_strided` but starting at `remote_ptr` on the given image.

```
subroutine prif_get_strided_indirect(...)
  integer(c_int), intent(in) :: image_num
  integer(c_intptr_t), intent(in) :: remote_ptr
  integer(c_ptrdiff_t), intent(in) :: remote_stride(:)
  type(c_ptr), intent(in) :: current_image_buffer
  integer(c_ptrdiff_t), intent(in) :: current_image_stride(:)
  integer(c_size_t), intent(in) :: element_size
  integer(c_size_t), intent(in) :: extent(:)
  integer(c_int), intent(out), optional :: stat
  character(len=*), intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine
```

Argument descriptions

5.7.4 prif_put_strided

Description: Assign data to memory on the given image, starting at the location indicated by `coarray_handle` and `offset`, copying from `current_image_buffer`, progressing through `current_image_buffer` in `current_image_stride` increments and through remote memory in `remote_stride` increments, transferring `extent` number of elements in each dimension. This procedure blocks on source completion. If `image_num` indicates the calling image and any memory location is specified as both a source and destination location, then behavior is undefined.

```
subroutine prif_put_strided(...)
  integer(c_int), intent(in) :: image_num
  type(prif_coarray_handle), intent(in) :: coarray_handle
  integer(c_size_t), intent(in) :: offset
  integer(c_ptrdiff_t), intent(in) :: remote_stride(:)
  type(c_ptr), intent(in) :: current_image_buffer
  integer(c_ptrdiff_t), intent(in) :: current_image_stride(:)
  integer(c_size_t), intent(in) :: element_size
  integer(c_size_t), intent(in) :: extent(:)
  integer(c_int), intent(out), optional :: stat
  character(len=*), intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine
```

Argument descriptions

5.7.5 prif_put_strided_indirect

Description: This procedure implements the semantics of `prif_put_strided` but starting at `remote_ptr` on the given image.

```
subroutine prif_put_strided_indirect(...)
  integer(c_int), intent(in) :: image_num
  integer(c_intptr_t), intent(in) :: remote_ptr
  integer(c_ptrdiff_t), intent(in) :: remote_stride(:)
  type(c_ptr), intent(in) :: current_image_buffer
  integer(c_ptrdiff_t), intent(in) :: current_image_stride(:)
  integer(c_size_t), intent(in) :: element_size
  integer(c_size_t), intent(in) :: extent(:)
  integer(c_int), intent(out), optional :: stat
  character(len=*), intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine
```

Argument descriptions

5.7.6 prif_put_strided_with_notify

Description: This procedure implements the semantics of `prif_put_strided` with support for the `NOTIFY=` specifier through a coarray handle and an offset.

```
subroutine prif_put_strided_with_notify(...)
  integer(c_int), intent(in) :: image_num
  type(prif_coarray_handle), intent(in) :: coarray_handle
  integer(c_size_t), intent(in) :: offset
  integer(c_ptrdiff_t), intent(in) :: remote_stride(:)
  type(c_ptr), intent(in) :: current_image_buffer
  integer(c_ptrdiff_t), intent(in) :: current_image_stride(:)
  integer(c_size_t), intent(in) :: element_size
  integer(c_size_t), intent(in) :: extent(:)
  type(prif_coarray_handle), intent(in) :: notify_coarray_handle
  integer(c_size_t), intent(in) :: notify_offset
  integer(c_int), intent(out), optional :: stat
  character(len=*), intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine
```

Argument descriptions

5.7.7 prif_put_strided_with_notify_indirect

Description: This procedure implements the semantics of `prif_put_strided` with support for the `NOTIFY=` specifier through a pointer.

```
subroutine prif_put_strided_with_notify_indirect(...)
  integer(c_int), intent(in) :: image_num
  type(prif_coarray_handle), intent(in) :: coarray_handle
  integer(c_size_t), intent(in) :: offset
  integer(c_ptrdiff_t), intent(in) :: remote_stride(:)
  type(c_ptr), intent(in) :: current_image_buffer
  integer(c_ptrdiff_t), intent(in) :: current_image_stride(:)
  integer(c_size_t), intent(in) :: element_size
  integer(c_size_t), intent(in) :: extent(:)
  integer(c_intptr_t), intent(in) :: notify_ptr
  integer(c_int), intent(out), optional :: stat
  character(len=*), intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine
```

Argument descriptions

5.7.8 prif_put_strided_indirect_with_notify

Description: This procedure implements the semantics of [prif_put_strided](#) but starting at `remote_ptr` on the given image and with support for the `NOTIFY=` specifier through a coarray handle and an offset.

```
subroutine prif_put_strided_indirect_with_notify(...)
  integer(c_int), intent(in) :: image_num
  integer(c_intptr_t), intent(in) :: remote_ptr
  integer(c_ptrdiff_t), intent(in) :: remote_stride(:)
  type(c_ptr), intent(in) :: current_image_buffer
  integer(c_ptrdiff_t), intent(in) :: current_image_stride(:)
  integer(c_size_t), intent(in) :: element_size
  integer(c_size_t), intent(in) :: extent(:)
  type(prif_coarray_handle), intent(in) :: notify_coarray_handle
  integer(c_size_t), intent(in) :: notify_offset
  integer(c_int), intent(out), optional :: stat
  character(len=*), intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine
```

[Argument descriptions](#)

5.7.9 prif_put_strided_indirect_with_notify_indirect

Description: This procedure implements the semantics of [prif_put_strided](#) but starting at `remote_ptr` on the given image and with support for the `NOTIFY=` specifier through a pointer.

```
subroutine prif_put_strided_indirect_with_notify_indirect(...)
  integer(c_int), intent(in) :: image_num
  integer(c_intptr_t), intent(in) :: remote_ptr
  integer(c_ptrdiff_t), intent(in) :: remote_stride(:)
  type(c_ptr), intent(in) :: current_image_buffer
  integer(c_ptrdiff_t), intent(in) :: current_image_stride(:)
  integer(c_size_t), intent(in) :: element_size
  integer(c_size_t), intent(in) :: extent(:)
  integer(c_intptr_t), intent(in) :: notify_ptr
  integer(c_int), intent(out), optional :: stat
  character(len=*), intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine
```

[Argument descriptions](#)

5.8 SYNC Statements

5.8.1 prif_sync_memory

Description: Ends one Fortran segment and begins another, waiting on any pending communication operations with other images.

```
subroutine prif_sync_memory(...)
  integer(c_int), intent(out), optional :: stat
  character(len=*), intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine
```

5.8.2 prif_sync_all

Description: Performs a collective synchronization of all images in the current team.

```
subroutine prif_sync_all(...)
  integer(c_int), intent(out), optional :: stat
  character(len=*), intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine
```

5.8.3 prif_sync_team

Description: Performs a collective synchronization with the images of the identified team.

```
subroutine prif_sync_team(...)
  type(prif_team_type), intent(in) :: team
  integer(c_int), intent(out), optional :: stat
  character(len=*), intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine
```

Further argument descriptions:

- **team:** Identifies the team to synchronize.

5.8.4 prif_sync_images

Description: Performs a collective synchronization with the listed images.

```
subroutine prif_sync_images(...)
  integer(c_int), intent(in), optional :: image_set(:)
  integer(c_int), intent(out), optional :: stat
  character(len=*), intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine
```

Further argument descriptions:

- **image_set:** The image indices of the images in the current team with which to synchronize. Image indices are relative to the current team. Given a scalar argument to SYNC IMAGES, the compiler should pass its value in an array of size 1. Given an asterisk (*) argument to SYNC IMAGES, the compiler should omit the **image_set** argument.

5.9 Locks

5.9.1 Common Arguments in Locks

- **image_num**
 - an argument identifying the image to be communicated with
 - is permitted to identify the calling image
 - this image index is always relative to the initial team, regardless of the current team
- **coarray_handle**: handle for a descriptor of an established coarray to be accessed by this operation. Together with **offset** must identify the location of a **prif_lock_type** variable entirely contained within the element data of the indicated coarray.
- **offset**: indicates an offset in bytes from the beginning of the elements in a remote coarray (indicated by **coarray_handle**) on a selected image (indicated by **image_num**)
- **lock_var_ptr**: a pointer to the base address of the lock variable to be locked or unlocked on the identified image. The referenced variable shall be of type **prif_lock_type**, and the referenced storage must have been allocated using **prif_allocate** or **prif_allocate_coarray**.
- **acquired_lock**: when present, the argument is defined to **.true.** if the lock has become locked by the calling image, otherwise is defined to **.false.**

5.9.2 prif_lock

Description: Waits until the identified lock variable is unlocked and then locks it if the **acquired_lock** argument is not present. Otherwise it sets the **acquired_lock** argument to **.false.** if the identified lock variable was already locked by another image, or locks the identified lock variable and sets the **acquired_lock** argument to **.true.** If the identified lock variable was already locked by the calling image, then an error condition occurs.

```
subroutine prif_lock(...)
  integer(c_int), intent(in) :: image_num
  type(prif_coarray_handle), intent(in) :: coarray_handle
  integer(c_size_t), intent(in) :: offset
  logical(c_bool), intent(out), optional :: acquired_lock
  integer(c_int), intent(out), optional :: stat
  character(len=*), intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine
```

[Argument descriptions](#)

5.9.3 prif_lock_indirect

Description: This procedure implements the semantics of **prif_lock**, but with the lock variable identified by **lock_var_ptr**.

```
subroutine prif_lock_indirect(...)
  integer(c_int), intent(in) :: image_num
  integer(c_intptr_t), intent(in) :: lock_var_ptr
  logical(c_bool), intent(out), optional :: acquired_lock
  integer(c_int), intent(out), optional :: stat
  character(len=*), intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine
```

[Argument descriptions](#)

5.9.4 prif_unlock

Description: Unlocks the identified lock variable. If the identified lock variable was not locked by the calling image, then an error condition occurs.

```
subroutine prif_unlock(...)
  integer(c_int), intent(in) :: image_num
  type(prif_coarray_handle), intent(in) :: coarray_handle
  integer(c_size_t), intent(in) :: offset
  integer(c_int), intent(out), optional :: stat
  character(len=*), intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine
```

Argument descriptions

5.9.5 prif_unlock_indirect

Description: This procedure implements the semantics of `prif_unlock`, but with the lock variable identified by `lock_var_ptr`.

```
subroutine prif_unlock_indirect(...)
  integer(c_int), intent(in) :: image_num
  integer(c_intptr_t), intent(in) :: lock_var_ptr
  integer(c_int), intent(out), optional :: stat
  character(len=*), intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine
```

Argument descriptions

5.10 Critical

The compiler shall define a coarray, and establish (allocate) it in the initial team, that shall only be used to begin and end critical blocks. An efficient compiler may allocate one such coarray for each critical block. The coarray shall be a scalar coarray of type `prif_critical_type`.

5.10.1 Common Arguments in Critical

- **critical_coarray:** the handle for the `prif_critical_type` coarray associated with the selected critical construct

5.10.2 prif_critical

Description: This procedure waits until any other image which has executed this procedure with a corresponding coarray has subsequently executed `prif_end_critical` with the same coarray an identical number of times.

```
subroutine prif_critical(...)
  type(prif_coarray_handle), intent(in) :: critical_coarray
  integer(c_int), intent(out), optional :: stat
  character(len=*), intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine
```

Argument descriptions

5.10.3 prif_end_critical

Description: Completes execution of the critical construct associated with the provided coarray handle.

```
subroutine prif_end_critical(...)
  type(prif_coarray_handle), intent(in) :: critical_coarray
end subroutine
```

Argument descriptions

5.11 Events and Notifications

5.11.1 Common Arguments in Events and Notifications

- **image_num**
 - an argument identifying the image to be communicated with
 - is permitted to identify the calling image
 - this image index is always relative to the initial team, regardless of the current team

5.11.2 prif_event_post

Description: Atomically increment the count of the event variable by one.

```
subroutine prif_event_post(...)
  integer(c_int), intent(in) :: image_num
  type(prif_coarray_handle), intent(in) :: coarray_handle
  integer(c_size_t), intent(in) :: offset
  integer(c_int), intent(out), optional :: stat
  character(len=*), intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine
```

Argument descriptions

Further argument descriptions:

- **coarray_handle**: handle for a descriptor of an established coarray to be accessed by this operation. Together with **offset** must identify the location of a **prif_event_type** variable entirely contained within the element data of the indicated coarray.
- **offset**: indicates an offset in bytes from the beginning of the elements in a remote coarray (indicated by **coarray_handle**) on a selected image (indicated by **image_num**)

5.11.3 prif_event_post_indirect

Description: Atomically increment the count of the event variable by one.

```
subroutine prif_event_post_indirect(...)
  integer(c_int), intent(in) :: image_num
  integer(c_intptr_t), intent(in) :: event_var_ptr
  integer(c_int), intent(out), optional :: stat
  character(len=*), intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine
```

Argument descriptions

Further argument descriptions:

- **event_var_ptr**: a pointer to the base address of the event variable to be incremented on the identified image. The referenced variable shall be of type **prif_event_type**, and the referenced storage must have been allocated using **prif_allocate** or **prif_allocate_coarray**.

5.11.4 prif_event_wait

Description: Wait until the count of the provided event variable on the calling image is greater than or equal to `until_count`, and then atomically decrement the count by that value.

```

subroutine prif_event_wait(...)
  type(c_ptr), intent(in) :: event_var_ptr
  integer(c_int64_t), intent(in), optional :: until_count
  integer(c_int), intent(out), optional :: stat
  character(len=*), intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine

```

Further argument descriptions:

- **event_var_ptr:** a pointer to the event variable on the calling image to be waited on. The referenced variable shall be of type `prif_event_type`, and the referenced storage must have been allocated using `prif_allocate_coarray` or `prif_allocate`.
- **until_count:** the count of the given event variable to be waited for. Treated as the value 1 if not provided.

5.11.5 prif_event_query

Description: Query the count of an event variable on the calling image.

```

subroutine prif_event_query(...)
  type(c_ptr), intent(in) :: event_var_ptr
  integer(c_int64_t), intent(out) :: count
  integer(c_int), intent(out), optional :: stat
end subroutine

```

Further argument descriptions:

- **event_var_ptr:** a pointer to the event variable on the calling image to be queried. The referenced variable shall be of type `prif_event_type`, and the referenced storage must have been allocated using `prif_allocate_coarray` or `prif_allocate`.
- **count:** the current count of the given event variable.

5.11.6 prif_notify_wait

Description: Wait on notification of an incoming put operation

```

subroutine prif_notify_wait(...)
  type(c_ptr), intent(in) :: notify_var_ptr
  integer(c_int64_t), intent(in), optional :: until_count
  integer(c_int), intent(out), optional :: stat
  character(len=*), intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine

```

Further argument descriptions:

- **notify_var_ptr:** a pointer to the notify variable on the calling image to be waited on. The referenced variable shall be of type `prif_notify_type`, and the referenced storage must have been allocated using `prif_allocate_coarray` or `prif_allocate`.
- **until_count:** the count of the given notify variable to be waited for. Treated as the value 1 if not provided.

5.12 Teams

Team creation forms a hierarchical abstraction, where any given team may create zero or more child teams. The initial team is created by the `prif_init` procedure. Each subsequently created team's parent is the then-current team. Team membership is thus strictly hierarchical, and there is a unique path from any given team, along the ancestry tree delineated by team creation, back to the initial team.

5.12.1 `prif_form_team`

Description: Create teams. Each image receives a team value denoting the newly created team containing all images in the current team which specify the same value for `team_number`.

```
subroutine prif_form_team(...)
  integer(c_int64_t), intent(in) :: team_number
  type(prif_team_type), intent(out) :: team
  integer(c_int), intent(in), optional :: new_index
  integer(c_int), intent(out), optional :: stat
  character(len=*), intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine
```

Further argument descriptions:

- `new_index`: the index that the calling image will have in its new team

5.12.2 `prif_get_team`

Description: Query the team value for the current or an ancestor team. It is defined to the current team if `level` is not present or has the value `PRIF_CURRENT_TEAM`, the parent team if `level` is present with the value `PRIF_PARENT_TEAM`, or the initial team if `level` is present with the value `PRIF_INITIAL_TEAM`

```
subroutine prif_get_team(...)
  integer(c_int), intent(in), optional :: level
  type(prif_team_type), intent(out) :: team
end subroutine
```

Further argument descriptions:

- `level`: identify which team value to be queried

5.12.3 `prif_team_number`

Description: This procedure queries the `team_number` that was specified in the call to `prif_form_team` for the selected team, or -1 if the team is the initial team. If `team` is not present, the current team is selected.

```
subroutine prif_team_number(...)
  type(prif_team_type), intent(in), optional :: team
  integer(c_int64_t), intent(out) :: team_number
end subroutine
```

5.12.4 `prif_change_team`

Description: changes the current team to the specified team. For any associate names specified in the `CHANGE TEAM` statement the compiler should follow a call to this procedure with calls to `prif_alias_create` to create an aliased coarray descriptor, and associate any non-coindexed references to the associate name within the `CHANGE TEAM` construct with the selector.

```
subroutine prif_change_team(...)
  type(prif_team_type), intent(in) :: team
  integer(c_int), intent(out), optional :: stat
  character(len=*), intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine
```

5.12.5 prif_end_team

Description: Changes the current team to the parent team. During the execution of `prif_end_team`, the PRIF implementation deallocates any coarrays that became allocated during the change team construct. Prior to invoking `prif_end_team`, the compiler is responsible for invoking `prif_alias_destroy` to delete any aliased coarray descriptors created as part of the `CHANGE TEAM` construct.

```
subroutine prif_end_team(...)
  integer(c_int), intent(out), optional :: stat
  character(len=*), intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine
```

5.13 Collective Subroutines

5.13.1 Common Arguments in Collective Subroutines

- `source_image` or `result_image`
 - Identifies the image in the current team that is the root of the collective operation.
 - If `result_image` is omitted, then all participating images receive the resulting value.

5.13.2 prif_co_broadcast

Description: Broadcast value to images

```
subroutine prif_co_broadcast(...)
  type(*), intent(inout), target :: a(..)
  integer(c_int), intent(in) :: source_image
  integer(c_int), optional, intent(out) :: stat
  character(len=*), intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine
```

[Argument descriptions](#)

Further argument descriptions:

- `a`
 - shall have the same shape, type, and type parameter values, in corresponding references.
 - shall not be polymorphic
 - the value of the `a` argument on the `source_image` is assigned to the `a` argument on all other images via byte-level copy (as if a `TRANSFER` was applied to the source variable)
 - If `a` contains any allocatable or pointer sub-objects, such members are given indeterminate value and allocation status on images other than `source_image`. The caller is responsible for reallocating and populating allocatable subobjects on receiving images.

5.13.3 prif_co_max

Description: Compute maximum value across images.

```
subroutine prif_co_max(...)
  type(*), intent(inout), target :: a(..)
  integer(c_int), intent(in), optional :: result_image
  integer(c_int), intent(out), optional :: stat
  character(len=*), intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine
```

[Argument descriptions](#)

Further argument descriptions:

- `a`
 - shall be of type integer with an interoperable kind or of type real with an interoperable kind

5.13.4 prif_co_max_character

Description: Compute maximum value across images.

```
subroutine prif_co_max_character(...)
  character(len=*,kind=c_char), intent(inout), target :: a(..)
  integer(c_int), intent(in), optional :: result_image
  integer(c_int), intent(out), optional :: stat
  character(len=*, intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine
```

Argument descriptions

Further argument descriptions:

- **a**
 - shall be of type character with kind `c_char`

5.13.5 prif_co_min

Description: Compute minimum value across images.

```
subroutine prif_co_min(...)
  type(*), intent(inout), target :: a(..)
  integer(c_int), intent(in), optional :: result_image
  integer(c_int), intent(out), optional :: stat
  character(len=*, intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine
```

Argument descriptions

Further argument descriptions:

- **a**
 - shall be of type integer with an interoperable kind or of type real with an interoperable kind

5.13.6 prif_co_min_character

Description: Compute minimum value across images.

```
subroutine prif_co_min_character(...)
  character(len=*,kind=c_char), intent(inout), target :: a(..)
  integer(c_int), intent(in), optional :: result_image
  integer(c_int), intent(out), optional :: stat
  character(len=*, intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine
```

Argument descriptions

Further argument descriptions:

- **a**
 - shall be of type character with kind `c_char`

5.13.7 prif_co_sum

Description: Compute sum across images

```
subroutine prif_co_sum(...)
  type(*), intent(inout), target :: a(..)
  integer(c_int), intent(in), optional :: result_image
  integer(c_int), intent(out), optional :: stat
  character(len=*), intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine
```

Argument descriptions

Further argument descriptions:

- **a**
 - shall have any numeric type with an interoperable kind

5.13.8 prif_co_reduce

Description: Generalized reduction across images.

CLIENT NOTE:

In addition to supporting CO_REDUCE, `prif_co_reduce` may be invoked to support any user code CO_MIN, CO_MAX, CO_SUM call where the `a` argument is not an interoperable type.

```
subroutine prif_co_reduce(...)
  type(*), intent(inout), target :: a(..)
  procedure(prif_operation_wrapper_interface), pointer, intent(in) :: &
    operation_wrapper
  type(c_ptr), intent(in), value :: cdata
  integer(c_int), intent(in), optional :: result_image
  integer(c_int), intent(out), optional :: stat
  character(len=*), intent(inout), optional :: errmsg
  character(len=:), intent(inout), allocatable, optional :: errmsg_alloc
end subroutine
```

Argument descriptions

Further argument descriptions:

- **a**
 - shall have the same shape, type, and type parameter values, in corresponding references
 - shall not be of a type with an ultimate component that is allocatable or a pointer
 - shall not be polymorphic
- **operation_wrapper:** pointer to a client-provided thread-safe reduction subroutine. This may for example reference a compiler-generated subroutine wrapper around a user-provided OPERATION argument to CO_REDUCE. Calls to the wrapper may not invoke any PRIF subroutines that incur communication. The operation is assumed to be mathematically associative and commutative, otherwise the resulting values computed may be indeterminate and/or (in the case `result_image` is omitted) may vary across images. The operation may use the `cddata` argument to receive information (such as the operation or data type) not provided by the other arguments. Shall apply the desired operation element-wise to each of the `count` pairs of operands, storing the result in the location from which the second (right-hand) operand is retrieved. `arg1` or `arg2_and_out` are permitted to alias elements of `a`.

operation_wrapper shall have the following interface, which is publicly defined in the prif module:

```
abstract interface
  subroutine prif_operation_wrapper_interface(...) bind(C)
    type(c_ptr), intent(in), value :: arg1
    type(c_ptr), intent(in), value :: arg2_and_out
    integer(c_size_t), intent(in), value :: count
    type(c_ptr), intent(in), value :: cdata
  end subroutine
end interface
```

operation_wrapper argument descriptions:

- **arg1**: Pointer to a contiguous array of left operands. These may be caller-provided input values or intermediate results. The reduction operation is not permitted to write to this memory.
- **arg2_and_out**: Pointer to a contiguous array of right operands and result. These may be caller-provided input values or intermediate results. The reduction operation must write the result(s) to this memory, as described below.
- **count**: Number of elements in **arg1** and **arg2_and_out** arrays. Shall be a non-negative value, which need *not* be equal to `product(shape(a))`; specifically, this wrapper might be invoked to reduce elements corresponding to less or more than one pair of image contributions to the reduction operation. If **count** is equal to zero, the `operation_wrapper` shall have no side effects.
- **cdata**: Client/user data that is the value that the calling image provided when it invoked the corresponding `prif_co_reduce`. It is intended to assist in implementing more than a single data type and/or operation with a common reduction subroutine, or to pass in any dynamic information needed by the reduction (e.g. runtime type parameters).

Example: As an example, consider a call to `CO_REDUCE` with non-interoperable arguments such as the following:

```
type(my_type(len1=*, len2=*)), intent(in) :: a(:)
...
call CO_REDUCE(a, user_func)
...
```

Where `my_type` has a definition like the following:

```
type :: my_type(len1, len2)
  integer, len :: len1, len2
  integer :: ints(len1)
  real :: reals(len2)
end type
```

The `CO_REDUCE` call could be transformed into something like the following:

```
call prif_co_reduce(a, wrapper, c_null_ptr)
contains
  subroutine wrapper(arg1, arg2_and_out, count, cdata) bind(C)
    type(c_ptr), intent(in), value :: arg1          !! "Left" operands
    type(c_ptr), intent(in), value :: arg2_and_out  !! "Right" operands and result
    integer(c_size_t), intent(in), value :: count    !! Operand count
    type(c_ptr), intent(in), value :: cdata         !! Client data, unused here

    type(my_type(len1=a%len1, len2=a%len2)), pointer :: &
      lhs(:)=>null(), rhs_and_result(:)=>null()
    integer(c_size_t) :: i

    if (count == 0) return
    call c_f_pointer(arg1, lhs, [count])
    call c_f_pointer(arg2_and_out, rhs_and_result, [count])
    do i=1, count
      rhs_and_result(i) = user_func(lhs(i), rhs_and_result(i))
    end do
  end subroutine
```

An alternative transformation for this CO_REDUCE call that uses `cdata` to avoid introduction of a subprogram by instead passing a pointer to a generated derived type:

```
type reduction_context_data
  type(c_funptr) :: user_op
  integer :: len1, len2
end type
```

with a call like the following:

```
type(reduction_context_data), target :: cdata
cdata = reduction_context_data(c_funloc(user_func), a%len1, a%len2)
call prif_co_reduce(a, operation_wrapper, c_loc(cdata))
```

where the `operation_wrapper` is defined as follows:

```
subroutine operation_wrapper(arg1, arg2_and_out, count, cdata) bind(C)
  type(c_ptr), intent(in), value :: arg1          !! "Left" operands
  type(c_ptr), intent(in), value :: arg2_and_out  !! "Right" operands and result
  integer(c_size_t), intent(in), value :: count   !! Operand count
  type(c_ptr), intent(in), value :: cdata        !! Client data

  type(reduction_context_data), pointer :: stuff=>null()

  if (count == 0) return
  call c_f_pointer(cdata, stuff)
  block
    abstract interface
      pure function user_op(lhs, rhs) result(res)
        import stuff
        type(my_type(len1=stuff%len1, len2=stuff%len2)), intent(in) :: &
          lhs, rhs
        type(my_type(len1=stuff%len1, len2=stuff%len2)) :: res
      end function
    end interface

    procedure(user_op), pointer :: op_ptr
    type(my_type(len1=stuff%len1, len2=stuff%len2)), pointer :: &
      lhs(:)=>null(), rhs_and_result(:)=>null()

    call c_f_procpointer(stuff%user_op, op_ptr)
    call c_f_pointer(arg1, lhs, [count])
    call c_f_pointer(arg2_and_out, rhs_and_result, [count])

    block
      integer(c_size_t) :: i

      do i=1, count
        rhs_and_result(i) = op_ptr(lhs(i), rhs_and_result(i))
      end do
    end block
  end block
end subroutine
```

5.14 Atomic Memory Operations

All atomic operations are fully blocking operations, meaning they do not return to the caller until after all semantics involving the atomic variable are fully committed with respect to all images.

5.14.1 Common Arguments in Atomic Memory Operations

- **image_num**
 - an argument identifying the image to be communicated with
 - is permitted to identify the calling image
 - this image index is always relative to the initial team, regardless of the current team
- **coarray_handle**: handle for a descriptor of an established coarray to be accessed by this operation. In combination with **offset**, must reference storage entirely contained within the element data of the indicated coarray.
- **offset**: indicates an offset in bytes from the beginning of the elements in a remote coarray (indicated by **coarray_handle**) on a selected image (indicated by **image_num**)
- **atom_remote_ptr**: Is the location of the atomic variable on the identified image to be operated on. The referenced storage must have been allocated using **prif_allocate** or **prif_allocate_coarray**.
- **value**: value to perform the operation with (non-fetching and fetching operations) or value to which the variable shall be set, or retrieved from the variable (atomic access procedures)
- **old**: is set to the initial value of the atomic variable

5.14.2 Non-Fetching Atomic Operations

Description: Each of the following procedures atomically performs the specified operation on a coindexed object.

5.14.2.1 prif_atomic_add, Addition

```

subroutine prif_atomic_add(...)
  integer(c_int), intent(in) :: image_num
  type(prif_coarray_handle), intent(in) :: coarray_handle
  integer(c_size_t), intent(in) :: offset
  integer(PRIF_ATOMIC_INT_KIND), intent(in) :: value
  integer(c_int), intent(out), optional :: stat
end subroutine

subroutine prif_atomic_add_indirect(...)
  integer(c_int), intent(in) :: image_num
  integer(c_intptr_t), intent(in) :: atom_remote_ptr
  integer(PRIF_ATOMIC_INT_KIND), intent(in) :: value
  integer(c_int), intent(out), optional :: stat
end subroutine

```

[Argument descriptions](#)

5.14.2.2 prif_atomic_and, Bitwise And

```

subroutine prif_atomic_and(...)
  integer(c_int), intent(in) :: image_num
  type(prif_coarray_handle), intent(in) :: coarray_handle
  integer(c_size_t), intent(in) :: offset
  integer(PRIF_ATOMIC_INT_KIND), intent(in) :: value
  integer(c_int), intent(out), optional :: stat
end subroutine

subroutine prif_atomic_and_indirect(...)
  integer(c_int), intent(in) :: image_num
  integer(c_intptr_t), intent(in) :: atom_remote_ptr
  integer(PRIF_ATOMIC_INT_KIND), intent(in) :: value
  integer(c_int), intent(out), optional :: stat
end subroutine

```

[Argument descriptions](#)

5.14.2.3 prif_atomic_or, Bitwise Or

```

subroutine prif_atomic_or(...)
  integer(c_int), intent(in) :: image_num
  type(prif_coarray_handle), intent(in) :: coarray_handle
  integer(c_size_t), intent(in) :: offset
  integer(PRIF_ATOMIC_INT_KIND), intent(in) :: value
  integer(c_int), intent(out), optional :: stat
end subroutine

subroutine prif_atomic_or_indirect(...)
  integer(c_int), intent(in) :: image_num
  integer(c_intptr_t), intent(in) :: atom_remote_ptr
  integer(PRIF_ATOMIC_INT_KIND), intent(in) :: value
  integer(c_int), intent(out), optional :: stat
end subroutine

```

[Argument descriptions](#)

5.14.2.4 prif_atomic_xor, Bitwise Xor

```

subroutine prif_atomic_xor(...)
  integer(c_int), intent(in) :: image_num
  type(prif_coarray_handle), intent(in) :: coarray_handle
  integer(c_size_t), intent(in) :: offset
  integer(PRIF_ATOMIC_INT_KIND), intent(in) :: value
  integer(c_int), intent(out), optional :: stat
end subroutine

subroutine prif_atomic_xor_indirect(...)
  integer(c_int), intent(in) :: image_num
  integer(c_intptr_t), intent(in) :: atom_remote_ptr
  integer(PRIF_ATOMIC_INT_KIND), intent(in) :: value
  integer(c_int), intent(out), optional :: stat
end subroutine

```

[Argument descriptions](#)

5.14.3 Fetching Atomic Operations

Description: Each of the following procedures atomically performs the specified operation on a coindexed object, and retrieves the original value.

5.14.3.1 prif_atomic_fetch_add, Addition

```

subroutine prif_atomic_fetch_add(...)
  integer(c_int), intent(in) :: image_num
  type(prif_coarray_handle), intent(in) :: coarray_handle
  integer(c_size_t), intent(in) :: offset
  integer(PRIF_ATOMIC_INT_KIND), intent(in) :: value
  integer(PRIF_ATOMIC_INT_KIND), intent(out) :: old
  integer(c_int), intent(out), optional :: stat
end subroutine

subroutine prif_atomic_fetch_add_indirect(...)
  integer(c_int), intent(in) :: image_num
  integer(c_intptr_t), intent(in) :: atom_remote_ptr
  integer(PRIF_ATOMIC_INT_KIND), intent(in) :: value
  integer(PRIF_ATOMIC_INT_KIND), intent(out) :: old
  integer(c_int), intent(out), optional :: stat
end subroutine

```

[Argument descriptions](#)

5.14.3.2 prif_atomic_fetch_and, Bitwise And

```

subroutine prif_atomic_fetch_and(...)
  integer(c_int), intent(in) :: image_num
  type(prif_coarray_handle), intent(in) :: coarray_handle
  integer(c_size_t), intent(in) :: offset
  integer(PRIF_ATOMIC_INT_KIND), intent(in) :: value
  integer(PRIF_ATOMIC_INT_KIND), intent(out) :: old
  integer(c_int), intent(out), optional :: stat
end subroutine

subroutine prif_atomic_fetch_and_indirect(...)
  integer(c_int), intent(in) :: image_num
  integer(c_intptr_t), intent(in) :: atom_remote_ptr
  integer(PRIF_ATOMIC_INT_KIND), intent(in) :: value
  integer(PRIF_ATOMIC_INT_KIND), intent(out) :: old
  integer(c_int), intent(out), optional :: stat
end subroutine

```

[Argument descriptions](#)

5.14.3.3 prif_atomic_fetch_or, Bitwise Or

```

subroutine prif_atomic_fetch_or(...)
  integer(c_int), intent(in) :: image_num
  type(prif_coarray_handle), intent(in) :: coarray_handle
  integer(c_size_t), intent(in) :: offset
  integer(PRIF_ATOMIC_INT_KIND), intent(in) :: value
  integer(PRIF_ATOMIC_INT_KIND), intent(out) :: old
  integer(c_int), intent(out), optional :: stat
end subroutine

```

```

subroutine prif_atomic_fetch_or_indirect(...)
  integer(c_int), intent(in) :: image_num
  integer(c_intptr_t), intent(in) :: atom_remote_ptr
  integer(PRIF_ATOMIC_INT_KIND), intent(in) :: value
  integer(PRIF_ATOMIC_INT_KIND), intent(out) :: old
  integer(c_int), intent(out), optional :: stat
end subroutine

```

Argument descriptions

5.14.3.4 prif_atomic_fetch_xor, Bitwise Xor

```

subroutine prif_atomic_fetch_xor(...)
  integer(c_int), intent(in) :: image_num
  type(prif_coarray_handle), intent(in) :: coarray_handle
  integer(c_size_t), intent(in) :: offset
  integer(PRIF_ATOMIC_INT_KIND), intent(in) :: value
  integer(PRIF_ATOMIC_INT_KIND), intent(out) :: old
  integer(c_int), intent(out), optional :: stat
end subroutine

subroutine prif_atomic_fetch_xor_indirect(...)
  integer(c_int), intent(in) :: image_num
  integer(c_intptr_t), intent(in) :: atom_remote_ptr
  integer(PRIF_ATOMIC_INT_KIND), intent(in) :: value
  integer(PRIF_ATOMIC_INT_KIND), intent(out) :: old
  integer(c_int), intent(out), optional :: stat
end subroutine

```

Argument descriptions

5.14.4 Atomic Access

Description: The following procedures atomically set or retrieve the value of a coindexed object.

5.14.4.1 prif_atomic_define, set variable's value

```

subroutine prif_atomic_define_int(...)
  integer(c_int), intent(in) :: image_num
  type(prif_coarray_handle), intent(in) :: coarray_handle
  integer(c_size_t), intent(in) :: offset
  integer(PRIF_ATOMIC_INT_KIND), intent(in) :: value
  integer(c_int), intent(out), optional :: stat
end subroutine

subroutine prif_atomic_define_logical(...)
  integer(c_int), intent(in) :: image_num
  type(prif_coarray_handle), intent(in) :: coarray_handle
  integer(c_size_t), intent(in) :: offset
  logical(PRIF_ATOMIC_LOGICAL_KIND), intent(in) :: value
  integer(c_int), intent(out), optional :: stat
end subroutine

subroutine prif_atomic_define_int_indirect(...)
  integer(c_int), intent(in) :: image_num
  integer(c_intptr_t), intent(in) :: atom_remote_ptr
  integer(PRIF_ATOMIC_INT_KIND), intent(in) :: value
  integer(c_int), intent(out), optional :: stat
end subroutine

```

```

subroutine prif_atomic_define_logical_indirect(...)
  integer(c_int), intent(in) :: image_num
  integer(c_intptr_t), intent(in) :: atom_remote_ptr
  logical(PRIF_ATOMIC_LOGICAL_KIND), intent(in) :: value
  integer(c_int), intent(out), optional :: stat
end subroutine

```

[Argument descriptions](#)

5.14.4.2 prif_atomic_ref, retrieve variable's value

```

subroutine prif_atomic_ref_int(...)
  integer(c_int), intent(in) :: image_num
  type(prif_coarray_handle), intent(in) :: coarray_handle
  integer(c_size_t), intent(in) :: offset
  integer(PRIF_ATOMIC_INT_KIND), intent(out) :: value
  integer(c_int), intent(out), optional :: stat
end subroutine

subroutine prif_atomic_ref_logical(...)
  integer(c_int), intent(in) :: image_num
  type(prif_coarray_handle), intent(in) :: coarray_handle
  integer(c_size_t), intent(in) :: offset
  logical(PRIF_ATOMIC_LOGICAL_KIND), intent(out) :: value
  integer(c_int), intent(out), optional :: stat
end subroutine

subroutine prif_atomic_ref_int_indirect(...)
  integer(c_int), intent(in) :: image_num
  integer(c_intptr_t), intent(in) :: atom_remote_ptr
  integer(PRIF_ATOMIC_INT_KIND), intent(out) :: value
  integer(c_int), intent(out), optional :: stat
end subroutine

subroutine prif_atomic_ref_logical_indirect(...)
  integer(c_int), intent(in) :: image_num
  integer(c_intptr_t), intent(in) :: atom_remote_ptr
  logical(PRIF_ATOMIC_LOGICAL_KIND), intent(out) :: value
  integer(c_int), intent(out), optional :: stat
end subroutine

```

[Argument descriptions](#)

5.14.5 Atomic Compare-and-Swap

Description: Performs an atomic compare-and-swap operation. If the value of the atomic variable is equal to the value of the `compare` argument, set it to the value of the `new` argument. The old argument is set to the initial value of the atomic variable.

```

subroutine prif_atomic_cas_int(...)
  integer(c_int), intent(in) :: image_num
  type(prif_coarray_handle), intent(in) :: coarray_handle
  integer(c_size_t), intent(in) :: offset
  integer(PRIF_ATOMIC_INT_KIND), intent(out) :: old
  integer(PRIF_ATOMIC_INT_KIND), intent(in) :: compare
  integer(PRIF_ATOMIC_INT_KIND), intent(in) :: new
  integer(c_int), intent(out), optional :: stat
end subroutine

```

```

subroutine prif_atomic_cas_logical(...)
  integer(c_int), intent(in) :: image_num
  type(prif_coarray_handle), intent(in) :: coarray_handle
  integer(c_size_t), intent(in) :: offset
  logical(PRIF_ATOMIC_LOGICAL_KIND), intent(out) :: old
  logical(PRIF_ATOMIC_LOGICAL_KIND), intent(in) :: compare
  logical(PRIF_ATOMIC_LOGICAL_KIND), intent(in) :: new
  integer(c_int), intent(out), optional :: stat
end subroutine

subroutine prif_atomic_cas_int_indirect(...)
  integer(c_int), intent(in) :: image_num
  integer(c_intptr_t), intent(in) :: atom_remote_ptr
  integer(PRIF_ATOMIC_INT_KIND), intent(out) :: old
  integer(PRIF_ATOMIC_INT_KIND), intent(in) :: compare
  integer(PRIF_ATOMIC_INT_KIND), intent(in) :: new
  integer(c_int), intent(out), optional :: stat
end subroutine

subroutine prif_atomic_cas_logical_indirect(...)
  integer(c_int), intent(in) :: image_num
  integer(c_intptr_t), intent(in) :: atom_remote_ptr
  logical(PRIF_ATOMIC_LOGICAL_KIND), intent(out) :: old
  logical(PRIF_ATOMIC_LOGICAL_KIND), intent(in) :: compare
  logical(PRIF_ATOMIC_LOGICAL_KIND), intent(in) :: new
  integer(c_int), intent(out), optional :: stat
end subroutine

```

Argument descriptions

Further argument descriptions:

- **compare:** the value with which to compare the atomic variable
- **new:** the value to assign into the atomic variable, if it is initially equal to the **compare** argument

6 Glossary

- **Client Note:** a note that is relevant information for compiler developers who are clients of PRIF
- **Implementation Note:** a note that is relevant information for runtime library developers who are implementing PRIF
- **Source Completion:** The source-side resources provided to a communication operation by this image are no longer in use by the PRIF implementation, and the client is now permitted to modify or reclaim them.
- **coindexed object:** A coindexed object is a named coarray variable followed by an image selector (an expression including square brackets).
- **direct location:** A memory location that was allocated using `prif_allocate_coarray`, and can be accessed by remote images using the coarray handle produced by that allocation.
- **indirect location:** A memory location that was not allocated by the same call to `prif_allocate_coarray` that allocated a given coarray, but which is accessible by remote images through that coarray as an allocatable or pointer component. This memory must have been allocated by either `prif_allocate` or `prif_allocate_coarray`. See [Design Decisions](#) for additional information.

7 Future Work

At present all communication operations are semantically blocking on at least source completion. We acknowledge that this prohibits certain types of static optimization, namely the explicit overlap of communication with computation. In the future we intend to develop split-phased/asynchronous versions of various communication operations to enable more opportunities for static optimization of communication.

At present PRIF does not expose a capability for an image to directly access memory on another image. We acknowledge that in some cases an image may be co-located with the image whose coarray data it needs to access, but we don't currently expose this capability to PRIF clients. In the future we intend to expose shared-memory bypass for coarray access to PRIF clients.

8 Acknowledgments

This work was supported in part by the U.S. Department of Energy, Office of Science, Office of Advanced Scientific Computing Research (ASCR), Next Generation Scientific Software Technologies (NGSST) program under Contract No. DE-AC02-05CH11231.

This work was supported in part by the Exascale Computing Project (17-SC-20-SC), a collaborative effort of the U.S. Department of Energy Office of Science and the National Nuclear Security Administration.

This research used resources of the National Energy Research Scientific Computing Center (NERSC), a U.S. Department of Energy Office of Science User Facility located at Lawrence Berkeley National Laboratory, operated under Contract No. DE-AC02-05CH11231

The authors would like to thank Jeff Hammond of NVIDIA for providing helpful comments and suggestions regarding an earlier revision of this specification.

9 Copyright

This work is licensed under [CC BY-ND](#)

This manuscript includes authors at Lawrence Berkeley National Laboratory under Contract No. DE-AC02-05CH11231 with the U.S. Department of Energy. The U.S. Government retains, and the publisher, by accepting the article for publication, acknowledges, that the U.S. Government retains a non-exclusive, paid-up, irrevocable, world-wide license to publish or reproduce the published form of this manuscript, or allow others to do so, for U.S. Government purposes.

10 Legal Disclaimer

This document was prepared as an account of work sponsored by the United States Government. While this document is believed to contain correct information, neither the United States Government nor any agency thereof, nor the Regents of the University of California, nor any of their employees, makes any warranty, express or implied, or assumes any legal responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by its trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof, or the Regents of the University of California. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof or the Regents of the University of California.