

Due 3/15/22 at 11:59pm

- Homework 3 consists of both written and coding questions.
- We prefer that you typeset your answers using \LaTeX or other word processing software. If you haven't yet learned \LaTeX , one of the crown jewels of computer science, now is a good time! Neatly handwritten and scanned solutions will also be accepted for the written questions.
- In all of the questions, **show your work**, not just the final answer.

Deliverables:

1. Submit a PDF of your homework **,with an appendix listing all your code**, to the Gradescope assignment entitled "HW2 Write-Up". **Please start each question on a new page**. If there are graphs, include those graphs in the correct sections. **Do not** put them in an appendix. We need each solution to be self-contained on pages of its own.
 - In your write-up, please state with whom you worked on the homework. This should be on its own page and should be the first page that you submit.
 - In your write-up, please copy the following statement and sign your signature next to it. (Mac Preview and FoxIt PDF Reader, among others, have tools to let you sign a PDF file.) We want to make it *extra* clear so that no one inadvertently cheats. *"I certify that all solutions are entirely in my own words and that I have not looked at another student's solutions. I have given credit to all external sources I consulted."*
 - **Replicate all your code in an appendix**. Begin code for each coding question in a fresh page. Do not put code from multiple questions in the same page. When you upload this PDF on Gradescope, *make sure* that you assign the relevant pages of your code from appendix to correct questions.

1 Administrivia (2 points)

1. Please fill out the Check-In Survey if you haven't already. Please write down the 10 digit alphanumeric code you get after completing the survey.

2. Declare and sign the following statement:

"I certify that all solutions in this document are entirely my own and that I have not looked at anyone else's solution. I have given credit to all external sources I consulted."

Signature: _____

While discussions are encouraged, *everything* in your solution must be your (and only your) creation. Furthermore, all external material (i.e., anything outside lectures and assigned readings, including figures and pictures) should be cited properly. We wish to remind you that consequences of academic misconduct are particularly severe

Solution:

N/A

2 Kernels (16 points)

For a function $k(x_i, x_j)$ to be a valid kernel, it suffices to show either of the following conditions is true:

1. k has an inner product representation: $\exists \Phi : \mathbb{R}^d \rightarrow \mathcal{H}$, where \mathcal{H} is some (possibly infinite-dimensional) inner product space such that $\forall x_i, x_j \in \mathbb{R}^d$, $k(x_i, x_j) = \langle \Phi(x_i), \Phi(x_j) \rangle$.
2. For every sample $x_1, x_2, \dots, x_n \in \mathbb{R}^d$, the kernel matrix

$$K = \begin{bmatrix} k(x_1, x_1) & \cdots & k(x_1, x_n) \\ \vdots & k(x_i, x_j) & \vdots \\ k(x_n, x_1) & \cdots & k(x_n, x_n) \end{bmatrix}$$

is positive semidefinite.

Starting with part (c), you can use either condition (1) or (2) in your proofs.

- (a) (2 points) Show that the first condition implies the second one, i.e. if $\forall x_i, x_j \in \mathbb{R}^d$, $k(x_i, x_j) = \langle \Phi(x_i), \Phi(x_j) \rangle$ then the kernel matrix K is PSD.

Solution: $\forall a \in \mathbb{R}^n$, $a^T K a = \sum_{i,j} a_i a_j k(x_i, x_j) = \sum_j a_j \langle \sum_i a_i \Phi(x_i), \Phi(x_j) \rangle = \langle \sum_i a_i \Phi(x_i), \sum_j a_j \Phi(x_j) \rangle \geq 0$

- (b) (2 points) Show that if the second condition holds, then for any finite set of vectors, $\mathcal{X} = \{\mathbf{x}_1, \mathbf{x}_2, \dots, \mathbf{x}_n\}$, in \mathbb{R}^d there exists a feature map $\Phi_{\mathcal{X}}$ that maps the finite set \mathcal{X} to \mathbb{R}^n such that, for all \mathbf{x}_i and \mathbf{x}_j in \mathcal{X} , we have $k(\mathbf{x}_i, \mathbf{x}_j) = \langle \Phi_{\mathcal{X}}(\mathbf{x}_i), \Phi_{\mathcal{X}}(\mathbf{x}_j) \rangle$.

Solution: The kernel matrix of the data is a symmetric matrix: $\mathbf{K}_{ij} = k(\mathbf{x}_i, \mathbf{x}_j)$. This matrix admits an diagonalization

$$\mathbf{K} = \mathbf{U} \mathbf{\Lambda} \mathbf{U}^T,$$

where \mathbf{U} is an orthogonal matrix with columns denoted by \mathbf{u}_i and $\mathbf{\Lambda} = \text{diag}(\lambda_1, \lambda_2, \dots, \lambda_n)$ a diagonal matrix. The entries of $\mathbf{\Lambda}$ are non-negative because the kernel matrix is positive semi-definite. Therefore, we can define $\Phi_{\mathcal{X}}(\mathbf{x}_i) = (\mathbf{U} \mathbf{\Lambda}^{1/2})_i^T$, the i -th column of $(\mathbf{U} \mathbf{\Lambda}^{1/2})^T$. Then, by construction, we have $k(\mathbf{x}_i, \mathbf{x}_j) = \langle \Phi_{\mathcal{X}}(\mathbf{x}_i), \Phi_{\mathcal{X}}(\mathbf{x}_j) \rangle$.

- (c) (2 points) Given a positive semidefinite matrix \mathbf{A} , show that $k(x_i, x_j) = x_i^T \mathbf{A} x_j$ is a valid kernel.

Solution: We can show k admits a valid inner product representation:

$$k(x_i, x_j) = x_i^T \mathbf{A} x_j = x_i^T \mathbf{P} \mathbf{D}^{1/2} \mathbf{D}^{1/2} \mathbf{P}^T x_j = \langle \mathbf{D}^{1/2} \mathbf{P}^T x_i, \mathbf{D}^{1/2} \mathbf{P}^T x_j \rangle = \langle \Phi(x_i), \Phi(x_j) \rangle$$

where $\Phi(x) = \mathbf{D}^{1/2} \mathbf{P}^T x$

- (d) (2 points) Give a counterexample that shows why $k(x_i, x_j) = x_i^T (\text{rev}(x_j))$ (where $\text{rev}(x)$ reverses the order of the components in x) is *not* a valid kernel.

Solution: A counterexample: We have that $k((-1, 1), (-1, 1)) = -2$, but this is invalid since if k is a valid kernel then $\forall x$, $k(x, x) = \langle \Phi(x), \Phi(x) \rangle \geq 0$.

(e) (4 points) Show that when $k: \mathbb{R}^d \times \mathbb{R}^d \rightarrow \mathbb{R}$ is a valid kernel, for all vectors $\mathbf{x}_1, \mathbf{x}_2 \in \mathbb{R}^d$ we have

$$|k(\mathbf{x}_1, \mathbf{x}_2)| \leq \sqrt{k(\mathbf{x}_1, \mathbf{x}_1)k(\mathbf{x}_2, \mathbf{x}_2)}.$$

Show how the classical Cauchy-Schwarz inequality is a special case.

Solution: The kernel matrix of two points must be positive semi-definite:

$$\begin{bmatrix} k(\mathbf{x}_1, \mathbf{x}_1) & k(\mathbf{x}_1, \mathbf{x}_2) \\ k(\mathbf{x}_2, \mathbf{x}_1) & k(\mathbf{x}_2, \mathbf{x}_2) \end{bmatrix} \geq 0.$$

Therefore the determinant of this matrix must be non-negative. Since $k(\mathbf{x}_1, \mathbf{x}_2) = k(\mathbf{x}_2, \mathbf{x}_1)$, we get that

$$k(\mathbf{x}_1, \mathbf{x}_1)k(\mathbf{x}_2, \mathbf{x}_2) - k(\mathbf{x}_1, \mathbf{x}_2)^2 \geq 0.$$

Now the conclusion follows by simple algebraic manipulations.

We can recover the classic Cauchy-Schwarz inequality ($\langle \mathbf{x}_1, \mathbf{x}_2 \rangle \leq \|\mathbf{x}_1\|_2 \|\mathbf{x}_2\|_2$) by choosing k to be the linear kernel: $k(\mathbf{x}_1, \mathbf{x}_2) = \langle \mathbf{x}_1, \mathbf{x}_2 \rangle$.

(f) (4 points) Suppose k_1 and k_2 are valid kernels with feature maps $\Phi_1: \mathbb{R}^d \rightarrow \mathbb{R}^p$ and $\Phi_2: \mathbb{R}^d \rightarrow \mathbb{R}^q$ respectively, for some finite positive integers p and q . Construct a feature map for the product of the two kernels in terms of Φ_1 and Φ_2 , i.e. construct Φ_3 such that for all $\mathbf{x}_1, \mathbf{x}_2 \in \mathbb{R}^d$ we have

$$k(\mathbf{x}_1, \mathbf{x}_2) = k_1(\mathbf{x}_1, \mathbf{x}_2)k_2(\mathbf{x}_1, \mathbf{x}_2) = \langle \Phi_3(\mathbf{x}_1), \Phi_3(\mathbf{x}_2) \rangle.$$

Hint: Recall that the inner product between two matrices $A, B \in \mathbb{R}^{p \times q}$ is defined to be

$$\langle A, B \rangle = \text{tr}(A^\top B) = \sum_{i=1}^p \sum_{j=1}^q A_{ij} B_{ij}.$$

Solution:

We have

$$\begin{aligned} k_1(\mathbf{x}_1, \mathbf{x}_2)k_2(\mathbf{x}_1, \mathbf{x}_2) &= \langle \Phi_1(\mathbf{x}_1), \Phi_1(\mathbf{x}_2) \rangle \langle \Phi_2(\mathbf{x}_1), \Phi_2(\mathbf{x}_2) \rangle \\ &= \text{tr}(\Phi_1(\mathbf{x}_1)^\top \Phi_1(\mathbf{x}_2) \Phi_2(\mathbf{x}_2)^\top \Phi_2(\mathbf{x}_1)) \\ &= \text{tr}(\Phi_2(\mathbf{x}_1) \Phi_1(\mathbf{x}_1)^\top \Phi_1(\mathbf{x}_2) \Phi_2(\mathbf{x}_2)^\top). \end{aligned}$$

Therefore we can construct a feature map Φ_3 which maps \mathbf{x} into $\mathbb{R}^{p \times q}$. More precisely, we define

$$\Phi_3(\mathbf{x}) = \Phi_1(\mathbf{x}) \Phi_2(\mathbf{x})^\top.$$

Hence the product of two kernels is a valid kernel.

3 Kernel Ridge Regression: Theory (10 points)

- (a) (2 points) As we already know, the following procedure gives us the solution to ridge regression in feature space:

$$\arg \min_{\mathbf{w}} \|\Phi \mathbf{w} - \mathbf{y}\|_2^2 + \lambda \|\mathbf{w}\|_2^2 \quad (1)$$

Recall that the solution to ridge regression is given by

$$\hat{\mathbf{w}} = (\Phi^\top \Phi + \lambda I_d)^{-1} \Phi^\top \mathbf{y}$$

Show that we can rewrite $\hat{\mathbf{w}}$ as

$$\hat{\mathbf{w}} = \Phi^\top (\Phi \Phi^\top + \lambda I_n)^{-1} \mathbf{y}$$

You may have previously seen this in lecture.

Solution:

$$\begin{aligned} (\Phi^\top \Phi + \lambda I_d)^{-1} \Phi^\top &= (\Phi^\top \Phi + \lambda I_d)^{-1} \Phi^\top (\Phi \Phi^\top + \lambda I_n) (\Phi \Phi^\top + \lambda I_n)^{-1} \\ &= (\Phi^\top \Phi + \lambda I_d)^{-1} (\Phi^\top \Phi \Phi^\top + \lambda \Phi^\top) (\Phi \Phi^\top + \lambda I_n)^{-1} \\ &= (\Phi^\top \Phi + \lambda I_d)^{-1} (\Phi^\top \Phi + \lambda I_d) \Phi^\top (\Phi \Phi^\top + \lambda I_n)^{-1} \\ &= \Phi^\top (\Phi \Phi^\top + \lambda I_n)^{-1} \\ \implies \hat{\mathbf{w}} &= (\Phi^\top \Phi + \lambda I_d)^{-1} \Phi^\top \mathbf{y} \\ &= \Phi^\top (\Phi \Phi^\top + \lambda I_n)^{-1} \mathbf{y} \end{aligned}$$

- (b) (2 points) The prediction for a test point \mathbf{x} is given by $\phi(\mathbf{x})^\top \hat{\mathbf{w}}$, where $\hat{\mathbf{w}}$ is the solution to (1). In this part we will show how $\phi(\mathbf{x})^\top \hat{\mathbf{w}}$ can be computed using only the kernel $k(\mathbf{x}_i, \mathbf{x}_j) = \phi(\mathbf{x}_i)^\top \phi(\mathbf{x}_j)$. Denote the following object:

$$\mathbf{k}(\mathbf{x}) := [k(\mathbf{x}, \mathbf{x}_1), k(\mathbf{x}, \mathbf{x}_2), \dots, k(\mathbf{x}, \mathbf{x}_n)]^\top$$

Using the result from part (a), show that

$$\phi(\mathbf{x})^\top \hat{\mathbf{w}} = \mathbf{k}(\mathbf{x})^\top (\mathbf{K} + \lambda I)^{-1} \mathbf{y}.$$

In other words, if we define $\hat{\alpha} := (\mathbf{K} + \lambda I)^{-1} \mathbf{y}$, then

$$\phi(\mathbf{x})^\top \hat{\mathbf{w}} = \sum_{i=1}^n \alpha_i k(\mathbf{x}, \mathbf{x}_i)$$

— our prediction is a linear combination of kernel functions at different data points.

Note: To be clear, $\phi(\mathbf{x})$ is not the same as Φ . Φ is the featurized X matrix, while $\phi(\mathbf{x})$ is the featurization of a single data point \mathbf{x} . Specifically, Φ is a $R^{n \times d}$ matrix where row i of Φ is $\phi(\mathbf{x}_i)$.

Solution: From above we know that

$$\hat{\mathbf{w}} = \Phi^\top (\Phi \Phi^\top + \lambda I)^{-1} y.$$

Now we recognize that $(\Phi \Phi^\top)_{ij} = \phi(\mathbf{x}_i)^\top \phi(\mathbf{x}_j)$, and thus, $\Phi \Phi^\top = \mathbf{K}$. Thus,

$$\begin{aligned} \phi(\mathbf{x})^\top \hat{\mathbf{w}} &= \phi(\mathbf{x})^\top \Phi^\top (\mathbf{K} + \lambda I)^{-1} y. \\ &= \mathbf{k}(\mathbf{x})^\top (\mathbf{K} + \lambda I)^{-1} y \\ &= \sum_{i=1}^n \alpha_i k(\mathbf{x}, \mathbf{x}_i). \end{aligned}$$

- (c) (6 points) We will now consider kernel functions that do not directly correspond to a finite-dimensional featurization of the input points. For simplicity, we will stick to a scalar underlying raw input x . (The same style of argument can help you understand the vector case as well.) Consider the radial basis function (RBF) kernel function

$$k(x, z) = \exp\left(-\frac{\|x - z\|^2}{2\sigma^2}\right),$$

for some fixed hyperparameter σ . It turns out that this kernel does not correspond to any finite-dimensional featurization $\phi(x)$. However, there exists a series $\phi_d(x)$ of d -dimensional features, such that $\phi_d(x)^\top \phi_d(z)$ converges as $d \rightarrow \infty$ to $k(x, z)$. Using Taylor expansions, find $\phi_d(x)$.

(Hint: focus your attention on the Taylor expansion of $e^{\frac{xz}{\sigma^2}}$.)

Solution: We can rewrite $k(x, z)$ as

$$k(x, z) = e^{-x^2/(2\sigma^2)} e^{-z^2/(2\sigma^2)} e^{xz/\sigma^2}.$$

Now observe that, by the Taylor expansion,

$$e^{xz/\sigma^2} = 1 + \frac{xz}{\sigma^2} + \frac{(xz)^2}{\sigma^4 \cdot 2!} + \frac{(xz)^3}{\sigma^6 \cdot 3!} + \dots$$

We can rewrite this as the inner product of

$$\begin{bmatrix} 1 & \frac{x}{\sigma} & \frac{x^2}{\sigma^2 \sqrt{2!}} & \frac{x^3}{\sigma^3 \sqrt{3!}} & \dots \end{bmatrix}^T,$$

and

$$\begin{bmatrix} 1 & \frac{z}{\sigma} & \frac{z^2}{\sigma^2 \sqrt{2!}} & \frac{z^3}{\sigma^3 \sqrt{3!}} & \dots \end{bmatrix}^T.$$

Truncating to just d terms and substituting back into our expression for $k(x, z)$, we see that

$$k(x, z) \approx \phi_d(x)^\top \phi_d(z),$$

where

$$\phi_d(x) = e^{-x^2/(2\sigma^2)} \begin{bmatrix} 1 & \frac{x}{\sigma} & \frac{x^2}{\sigma^2 \sqrt{2!}} & \dots & \frac{x^{d-1}}{\sigma^{d-1} \sqrt{(d-1)!}} \end{bmatrix}^T,$$

with equality achieved in the limit as $d \rightarrow \infty$.

4 Kernel Ridge Regression: Practice (18 points)

In the following problem, you will implement Polynomial Ridge Regression and its kernel variant Kernel Ridge Regression, and compare them with each other. You will be dealing with a 2D regression problem, i.e., $\mathbf{x}_i \in \mathbb{R}^2$. We give you three datasets, `circle.npz` (small dataset), `heart.npz` (medium dataset), and `asymmetric.npz` (large dataset). In this problem, the labels are actually discrete $y_i \in \{-1, +1\}$, so in practice you should probably use a different model such as kernel SVMs, kernel logistic regression, or neural networks. The use of ridge regression here is for your practice and ease of coding.

You are only allowed to use `numpy.*`, `numpy.linalg.*`, and `matplotlib` in the following questions. Make sure to include plots and results in your writeups.

- (a) (2 points) Use `matplotlib` to visualize all the datasets and attach the plots to your report. Label the points with different y values with different colors and/or shapes.

Solution:

See Figure 1.

- (b) (6 points) Implement polynomial ridge regression (non-kernelized version) to fit the datasets `circle.npz`, `asymmetric.npz`, and `heart.npz`. The data is already shuffled. Use the first 80% data as the training dataset and the last 20% data as the validation dataset. Report both the average training squared loss and the average validation squared loss for polynomial order $p \in \{2, 4, 6, 8, 10, 12\}$. Use the regularization term $\lambda = 0.001$ for all p . Visualize your result and attach the heatmap plots for the learned predictions over the entire 2D domain for $p \in \{2, 4, 6, 8, 10, 12\}$ in your report. Code for generating polynomial features and heatmap plots is included for your convenience.

Solution:

Dataset `circle`

<code>p = 2</code>	<code>train_error =</code>	<code>0.995537</code>	<code>validation_error =</code>	<code>1.001056</code>
<code>p = 4</code>	<code>train_error =</code>	<code>0.943011</code>	<code>validation_error =</code>	<code>0.997914</code>
<code>p = 6</code>	<code>train_error =</code>	<code>0.547155</code>	<code>validation_error =</code>	<code>0.585688</code>
<code>p = 8</code>	<code>train_error =</code>	<code>0.230190</code>	<code>validation_error =</code>	<code>0.249990</code>
<code>p = 10</code>	<code>train_error =</code>	<code>0.174273</code>	<code>validation_error =</code>	<code>0.192998</code>
<code>p = 12</code>	<code>train_error =</code>	<code>0.156723</code>	<code>validation_error =</code>	<code>0.175335</code>

Dataset `heart`

<code>p = 2</code>	<code>train_error =</code>	<code>0.236718</code>	<code>validation_error =</code>	<code>0.189837</code>
<code>p = 4</code>	<code>train_error =</code>	<code>0.012169</code>	<code>validation_error =</code>	<code>0.009123</code>
<code>p = 6</code>	<code>train_error =</code>	<code>0.002630</code>	<code>validation_error =</code>	<code>0.001858</code>
<code>p = 8</code>	<code>train_error =</code>	<code>0.002354</code>	<code>validation_error =</code>	<code>0.001640</code>
<code>p = 10</code>	<code>train_error =</code>	<code>0.002193</code>	<code>validation_error =</code>	<code>0.001500</code>
<code>p = 12</code>	<code>train_error =</code>	<code>0.002090</code>	<code>validation_error =</code>	<code>0.001414</code>




Figure 1: Dataset visualization




Figure 2: Heat map of circle.npz

Dataset asymmetric

p = 2	train_error =	0.998260	validation_error =	1.000176
p = 4	train_error =	0.828692	validation_error =	0.822369
p = 6	train_error =	0.264040	validation_error =	0.242398
p = 8	train_error =	0.179853	validation_error =	0.158347
p = 10	train_error =	0.157977	validation_error =	0.136623
p = 12	train_error =	0.151736	validation_error =	0.130519

See Figure 2, 3, and 4. The error can be found in next part.

```
#!/usr/bin/env python3
import matplotlib.pyplot as plt
import numpy as np
from matplotlib import cm
```





Figure 3: Heat map of heart.npz



(a) $p = 2$

Figure 4: Heat map of asymmetric.npz

```

def lstsq(A, b, lambda_=0):
    return np.linalg.solve(A.T @ A + lambda_ * np.eye(A.shape[1]), A.T @ b)

def heatmap(f, fname=False, clip=5):
    # example: heatmap(lambda x, y: x * x + y * y)
    # clip: clip the function range to [-clip, clip] to generate a clean plot
    # set it to zero to disable this function

    xx0 = xx1 = np.linspace(np.min(X), np.max(X), 72)
    x0, x1 = np.meshgrid(xx0, xx1)
    x0, x1 = x0.ravel(), x1.ravel()
    z0 = f(x0, x1)

    if clip:
        z0[z0 > clip] = clip
        z0[z0 < -clip] = -clip

    plt.hexbin(x0, x1, C=z0, gridsize=50, cmap=cm.jet, bins=None)
    plt.colorbar()
    cs = plt.contour(
        xx0, xx1, z0.reshape(xx0.size, xx1.size), [-2, -1, -0.5, 0, 0.5, 1, 2], cmap=cm.jet)
    plt.clabel(cs, inline=1, fontsize=10)

    pos = y[:] == +1.0
    neg = y[:] == -1.0
    plt.scatter(X[pos, 0], X[pos, 1], c='red', marker='+')
    plt.scatter(X[neg, 0], X[neg, 1], c='blue', marker='v')
    if fname:
        plt.savefig(fname)
    plt.show()

def assemble_feature(x, D):
    """Create a vector of polynomial features up to order D from x"""
    from scipy.special import binom
    xs = []
    for d0 in range(D + 1):
        for d1 in range(D - d0 + 1):
            xs.append((x[:, 0]**d0) * (x[:, 1]**d1))
    poly_x = np.column_stack(xs)
    return poly_x

def main():
    for ds in ['circle', 'heart', 'asymmetric']:
        data = np.load(f'{ds}.npz')

        SPLIT = 0.8
        X = data["x"]
        y = data["y"]
        X /= np.max(X) # normalize the data

        n_train = int(X.shape[0] * SPLIT)
        X_train = X[:n_train, :]
        X_valid = X[n_train:, :]
        y_train = y[:n_train]
        y_valid = y[n_train:]

        LAMBDA = 0.001
        isubplot = 0
        fig = plt.figure(figsize=[12,10])
        for D in range(1, 17):
            ### start poly_nonkernel ###
            Xd_train = assemble_feature(X_train, D)
            Xd_valid = assemble_feature(X_valid, D)
            w = lstsq(Xd_train, y_train, LAMBDA)

```

```

error_train = np.average(np.square(y_train - Xd_train @ w))
error_valid = np.average(np.square(y_valid - Xd_valid @ w))
cond = np.linalg.cond(Xd_valid.T @ Xd_valid + np.eye(Xd_valid.shape[1]))
### end poly_nonkernel ###
if D in [2, 4, 6, 8, 10, 12]:
    isubplot += 1
    plt.subplot(3,2,isubplot)
    heatmap(lambda x, y: assemble_feature(np.vstack([x, y]).T, D) @ w)
    plt.title("D = %d" % D)
    print("p = {:2d}    train_error = {:10.6f}    validation_error = {:10.6f}    cond = {:14.6f}".
          format(D, error_train, error_valid, cond))
fig.savefig(f"./result/{ds}_non_kernel.png")

if __name__ == "__main__":
    main()

```

- (c) (8 points) Implement kernel ridge regression to fit the datasets `circle.npz`, `heart.npz`, and optionally (due to the computational requirements), `asymmetric.npz`. Use the polynomial kernel $K(\mathbf{x}_i, \mathbf{x}_j) = (1 + \mathbf{x}_i^T \mathbf{x}_j)^p$. Use the first 80% data as the training dataset and the last 20% data as the validation dataset. Report both the average training squared loss and the average validation squared loss for polynomial order $p \in \{1, \dots, 16\}$. Use the regularization term $\lambda = 0.001$ for all p . For `circle.npz`, also report the average training squared loss and validation squared loss for polynomial order $p \in \{1, \dots, 24\}$ when you use only the first 15% data as the training dataset and the rest 85% data as the validation dataset. Based on the error, comment on when you want to use a high-order polynomial in linear/ridge regression. Lastly, comment on which of polynomial versus kernel ridge regression runs faster, and why.

Solution:

You can see that when you training data is not enough, i.e., in the case when you only use 15% of the training data, you can easily overfit your training data if you use a high-order polynomial. When you have enough training data, i.e., in the case you are using the 80% of the training data, the overfitting is more unlikely. Therefore, you want to use a high-order polynomial only when you have enough training data to avoid the overfitting problem. For this problem, polynomial ridge regression runs faster than kernel ridge regression, because the number of data points is greater than the number of dimensions with the polynomial basis. The average error here is

```

##### 80% Training Data #####
##### circle.npz #####
p = 1  train_error = 0.997088  validation_error = 0.997579  cond = 3.885463
p = 2  train_error = 0.995537  validation_error = 1.001056  cond = 40.439621
p = 3  train_error = 0.992699  validation_error = 1.019356  cond = 230.817918
p = 4  train_error = 0.943011  validation_error = 0.997941  cond = 437.187915
p = 5  train_error = 0.935539  validation_error = 1.029308  cond = 804.009794
p = 6  train_error = 0.511241  validation_error = 0.547531  cond = 1307.933645
p = 7  train_error = 0.507592  validation_error = 0.549927  cond = 2159.011214
p = 8  train_error = 0.086389  validation_error = 0.101056  cond = 3630.740079
p = 9  train_error = 0.081809  validation_error = 0.097989  cond = 6230.776776
p = 10  train_error = 0.043086  validation_error = 0.054167  cond = 10920.048093
p = 11  train_error = 0.013966  validation_error = 0.018290  cond = 19529.648519
p = 12  train_error = 0.008685  validation_error = 0.011348  cond = 35549.340362
p = 13  train_error = 0.006517  validation_error = 0.008556  cond = 65983.294010
p = 14  train_error = 0.003665  validation_error = 0.004821  cond = 123976.972506
p = 15  train_error = 0.001912  validation_error = 0.002475  cond = 234627.222155
p = 16  train_error = 0.001400  validation_error = 0.001797  cond = 446625.921685
##### heart.npz #####
p = 1  train_error = 0.962643  validation_error = 0.959952  cond = 6.646302
p = 2  train_error = 0.236718  validation_error = 0.189837  cond = 26.941658
p = 3  train_error = 0.115481  validation_error = 0.090813  cond = 217.010014
p = 4  train_error = 0.012163  validation_error = 0.009089  cond = 348.834425
p = 5  train_error = 0.003759  validation_error = 0.002975  cond = 638.648596
p = 6  train_error = 0.002294  validation_error = 0.001613  cond = 1262.823064

```

```

p = 7   train_error = 0.001441 validation_error = 0.001056 cond = 2554.245128
p = 8   train_error = 0.000665 validation_error = 0.000428 cond = 5222.932534
p = 9   train_error = 0.000305 validation_error = 0.000202 cond = 10754.752173
p = 10  train_error = 0.000189 validation_error = 0.000138 cond = 22259.613418
p = 11  train_error = 0.000139 validation_error = 0.000114 cond = 46259.310324
p = 12  train_error = 0.000111 validation_error = 0.000097 cond = 96458.107873
p = 13  train_error = 0.000093 validation_error = 0.000084 cond = 201706.212544
p = 14  train_error = 0.000081 validation_error = 0.000075 cond = 422842.117216
p = 15  train_error = 0.000072 validation_error = 0.000068 cond = 888359.857996
p = 16  train_error = 0.000064 validation_error = 0.000062 cond = 1870033.835947
##### asymmetric.npz #####
p = 1   train_error = 0.999989 validation_error = 1.000194 cond = 4.303603
p = 2   train_error = 0.998260 validation_error = 1.000176 cond = 82.880736
p = 3   train_error = 0.991565 validation_error = 0.991388 cond = 559.928514
p = 4   train_error = 0.828692 validation_error = 0.822373 cond = 4924.555570
p = 5   train_error = 0.758986 validation_error = 0.748816 cond = 15783.658385
p = 6   train_error = 0.263368 validation_error = 0.241398 cond = 36482.622481
p = 7   train_error = 0.218690 validation_error = 0.195606 cond = 73065.066532
p = 8   train_error = 0.140721 validation_error = 0.120891 cond = 148442.373823
p = 9   train_error = 0.120781 validation_error = 0.102239 cond = 303228.309085
p = 10  train_error = 0.109520 validation_error = 0.092603 cond = 623400.268355
p = 11  train_error = 0.095645 validation_error = 0.081190 cond = 1289425.566871
p = 12  train_error = 0.083126 validation_error = 0.070826 cond = 2682742.562813
p = 13  train_error = 0.069519 validation_error = 0.059635 cond = 5613779.945180
p = 14  train_error = 0.052339 validation_error = 0.044942 cond = 11813079.998338
p = 15  train_error = 0.037785 validation_error = 0.032575 cond = 24993651.532068
p = 16  train_error = 0.029511 validation_error = 0.025690 cond = 53158174.199813
##### Just using 15% Training Data #####
##### circle.npz #####
p = 1   train_error = 0.977122 validation_error = 1.017212 cond = 154347.326799
p = 2   train_error = 0.965179 validation_error = 1.040716 cond = 188799.151210
p = 3   train_error = 0.935814 validation_error = 1.083452 cond = 260636.616808
p = 4   train_error = 0.828087 validation_error = 1.220925 cond = 388234.123476
p = 5   train_error = 0.808276 validation_error = 1.294004 cond = 605958.721676
p = 6   train_error = 0.465600 validation_error = 0.731820 cond = 974938.119166
p = 7   train_error = 0.418462 validation_error = 0.701896 cond = 1604147.948302
p = 8   train_error = 0.094915 validation_error = 0.326256 cond = 2690114.807338
p = 9   train_error = 0.064552 validation_error = 0.979804 cond = 4592713.085243
p = 10  train_error = 0.054649 validation_error = 2.273410 cond = 7981356.922646
p = 11  train_error = 0.036871 validation_error = 3.763307 cond = 14136597.558594
p = 12  train_error = 0.019774 validation_error = 1.865602 cond = 26239673.362870
p = 13  train_error = 0.009580 validation_error = 0.104549 cond = 49619782.252457
p = 14  train_error = 0.005777 validation_error = 0.372263 cond = 94594909.390382
p = 15  train_error = 0.004199 validation_error = 0.544182 cond = 181457265.287672
p = 16  train_error = 0.002995 validation_error = 0.436762 cond = 349803221.168144
p = 17  train_error = 0.001924 validation_error = 0.705161 cond = 677043148.807441
p = 18  train_error = 0.001210 validation_error = 1.518994 cond = 1314776445.035100
p = 19  train_error = 0.000851 validation_error = 3.576013 cond = 2560349372.861672
p = 20  train_error = 0.000678 validation_error = 7.938049 cond = 4997765669.676615
p = 21  train_error = 0.000571 validation_error = 16.370187 cond = 9775415811.240183
p = 22  train_error = 0.000483 validation_error = 32.763564 cond = 19153899435.104542
p = 23  train_error = 0.000405 validation_error = 62.110989 cond = 37587428504.160706
p = 24  train_error = 0.000344 validation_error = 103.845313 cond = 73859595026.545380

```

```

#!/usr/bin/env python3

import matplotlib.pyplot as plt
import numpy as np
# import scipy.special
from matplotlib import cm

# data = np.load('circle.npz')
data = np.load('heart.npz')
# data = np.load('asymmetric.npz')

SPLIT = 0.80
X = data["x"]
y = data["y"]
X /= np.max(X) # normalize the data

n_train = int(X.shape[0] * SPLIT)
X_train = X[:n_train, :]
X_valid = X[n_train:, :]
y_train = y[:n_train]
y_valid = y[n_train:]

LAMBDA = 0.001

def poly_kernel(X, XT, D):
    return np.power(X @ XT + 1, D)

```

```

def rbf_kernel(X, XT, sigma):
    XXT = -2 * X @ XT
    XXT += np.sum(X * X, axis=1, keepdims=True)
    XXT += np.sum(XT * XT, axis=0, keepdims=True)
    return np.exp(-XXT / (2 * sigma * sigma))

def heatmap(f, fname=False, clip=5):
    # example: heatmap(lambda x, y: x * x + y * y)
    # clip: clip the function range to [-clip, clip] to generate a clean plot
    # set it to zero to disable this function

    xx0 = xx1 = np.linspace(np.min(X), np.max(X), 72)
    x0, x1 = np.meshgrid(xx0, xx1)
    x0, x1 = x0.ravel(), x1.ravel()
    z0 = f(x0, x1)

    if clip:
        z0[z0 > clip] = clip
        z0[z0 < -clip] = -clip

    plt.hexbin(x0, x1, C=z0, gridsize=50, cmap=cm.jet, bins=None)
    plt.colorbar()
    cs = plt.contour(
        xx0, xx1, z0.reshape(xx0.size, xx1.size), [-2, -1, -0.5, 0, 0.5, 1, 2], cmap=cm.jet)
    plt.clabel(cs, inline=1, fontsize=10)

    pos = y[:] == +1.0
    neg = y[:] == -1.0
    plt.scatter(X[pos, 0], X[pos, 1], c='red', marker='+')
    plt.scatter(X[neg, 0], X[neg, 1], c='blue', marker='v')
    if fname:
        plt.savefig(fname)
    plt.show()

def main():
    for D in range(1, 16):
        # polynomial kernel
        K = poly_kernel(X_train, X_train.T, D) + LAMBDA * np.eye(X_train.shape[0])
        coeff = np.linalg.solve(K, y_train)
        error_train = np.average(np.square(y_train - poly_kernel(X_train, X_train.T, D) @ coeff))
        error_valid = np.average(np.square(y_valid - poly_kernel(X_valid, X_train.T, D) @ coeff))
        print("p = {2d} train_error = {7.6f} validation_error = {7.6f} cond = {14.6f}".
              format(D, error_train, error_valid, np.linalg.cond(K)))
        # heatmap(lambda x, y: poly_kernel(np.column_stack([x, y]), X_train.T, D) @ coeff)
        # if D in [2, 4, 6, 8, 10, 12]:
        #     fname = "result/poly%02d.pdf" % D
        #     heatmap(lambda x, y: poly_kernel(np.column_stack([x, y]), X_train.T, D) @ coeff, fname)

    for sigma in [10, 3, 1, 0.3, 0.1, 0.03]:
        K = rbf_kernel(X_train, X_train.T, sigma) + LAMBDA * np.eye(X_train.shape[0])
        coeff = np.linalg.solve(K, y_train)
        error_train = np.average(
            np.square(y_train - rbf_kernel(X_train, X_train.T, sigma) @ coeff))
        error_valid = np.average(
            np.square(y_valid - rbf_kernel(X_valid, X_train.T, sigma) @ coeff))
        print("sigma = {6.3f} train_error = {7.6f} validation_error = {7.6f} cond = {14.6f}".
              format(sigma, error_train, error_valid, np.linalg.cond(K)))
        heatmap(
            lambda x, y: rbf_kernel(np.column_stack([x, y]), X_train.T, sigma) @ coeff,
            fname="heart_RBF0_%4f.pdf" % sigma)

if __name__ == "__main__":
    main()

```


- (d) (2 points) A popular kernel function that is widely used in various kernelized learning algorithms is called the radial basis function kernel (RBF kernel). It is defined as

$$K(\mathbf{x}, \mathbf{x}') = \exp\left(-\frac{\|\mathbf{x} - \mathbf{x}'\|_2^2}{2\sigma^2}\right). \quad (2)$$

Implement the RBF kernel function for kernel ridge regression to fit the dataset `heart.npz`. Use the regularization term $\lambda = 0.001$. Report the average squared loss, visualize your result and attach the heatmap plots for the fitted functions over the 2D domain for $\sigma \in \{10, 3, 1, 0.3, 0.1, 0.03\}$ in your report. You may want to vectorize your kernel functions to speed up your implementation.

Solution:

The average fitting error is

```
sigma = 10.000 train_error = 0.279653 validation_error = 0.224638 cond = 800690.695468
sigma = 3.000 train_error = 0.119629 validation_error = 0.082379 cond = 778537.061196
sigma = 1.000 train_error = 0.005872 validation_error = 0.004201 cond = 648473.876828
sigma = 0.300 train_error = 0.000053 validation_error = 0.000050 cond = 469873.484420
sigma = 0.100 train_error = 0.000000 validation_error = 0.000000 cond = 442247.855472
sigma = 0.030 train_error = 0.000000 validation_error = 0.000078 cond = 291224.335632
```

The heat map can be found in Figure 5 for $\sigma \in \{10, 3, 1, 0.3, 0.1, 0.03\}$. As we see, the larger σ , the more data the kernel averages over and the more blurry the image of the heatmap gets. The previous code from kernel regression includes the implementation of RBF kernel.




Figure 5: Heatmap of `heart.npz`