## F# Cheat Sheet (Author: Tyler P. Berkshire)

Key Features
Strongly typed with algebraic-style types
Easy concurrency
Extensive multi-paradigm features
Integrated with .NET
Metaprogramming

Core syntax		
let	Bind value to a name	
let rec	Recursive definition	
//, (**)	Inline and multi-line comments	
indentation	Separates code blocks	
whitespace	Separates parameters	

Control Flow	
for $x$ in $\{\ \}$ do	Standard for loop
while $\times$ do	Standard while loop
$\begin{array}{ccc} match  \times  with \\      \end{array}$	Pattern matching against a discriminated union
when	Guards help with complicated pattern matching
>	Pipes emulate UNIX pipes. Output of the left becomes input of the right
<	Reverse pipe
>>	Function composition returns a function instead of immediately evaluating
< <	Reverse function composition
currying	Functions can be curried and partially applied

Algebraic <sup>-</sup>	Гуреѕ
fun()	Function
unit	A function with one range value
type	Keyword to declare custom types
(x,y)	Tuples can be heterogeneous
{x:int, y:float}	Records are labelled tuples
I of int   B of bool	Discriminated unions
<'a>>	Single quote denotes generic type
Option	The option type is either Some or None
[]	Lists are immutable and homogeneous
seq{}	Sequences use <i>yield</i> and <i>yield!</i> to create infinite data types

Metaprogra	amming
quotations	Compiled into objects representing the program
<0 0>	Quotation with type information
<@@	Quotation without type information
Expr<'T>	Resulting type of a quotation
%	Splice a typed expression into a quotation
%%	Splice a non-typed expression into a quotation
Patterns	Active pattern module used to analyze expression objects
ExprShape	Module to traverse expression trees with fewer active patterns

Asynchronous Workflows		
async {}	Expressions in the curly braces become async	
let!	Wait for the async task to return, similar to await	
Async.Start	Start a task asynchronously	
Async.RunSynchronously	Block until all async events are completed	
Async.Parallel	Run the tasks in parallel	
CancellationTokenSource	Workflows can be cancelled by invoking the cancel token	

Actor Model	
MailBoxProcessor	Built in agent class
inbox.Receive()	Read a message
agent.Post	Post a message

Useful Libraries	
FSharp.Data	Providers forworking with structured data files formats (CSV, HTML, JSON, etc.)
FsUnit	Builds upon the .NET testing framework
FSharp.Charting	Compositional library for creating charts

Copyright © 2019by Tyler Berkshire.