

PENETRATION TESTING REPORT

MEDIROZA GENERAL HOSPITAL

Web Application Security Assessment

PREPARED BY: BERNARD MUSILI

CYBERSECURITY MENTOR: WAQAS KARIM, CCIE

ORGANISATION: NETWORKWALKS

BATCH: B082 | WEEK 4 CAPSTONE PROJECT

TARGET: [HTTPS://MEDIROZAHOSPITAL.COM](https://medirozahospital.com)

ASSESSMENT TYPE:

BLACK-BOX WEB APPLICATION PENETRATION TEST

CLASSIFICATION:

CONFIDENTIAL

NETWORKWALKS ACADEMY

1. Executive Summary

A black-box penetration test was conducted against the web infrastructure of **Mediroza General Hospital** as part of the Networkwalks B082 Week 4 Capstone Project. The assessment was conducted within the authorised educational testing environment described by the project, with the objective of identifying security weaknesses, demonstrating their potential impact, and providing practical remediation recommendations.

The assessment identified multiple vulnerabilities ranging from **Medium to Critical severity**. The most significant vulnerability was a **SQL injection flaw in the patient portal login functionality**, which allowed authentication to be bypassed without possessing valid credentials.

Following the authentication bypass, confidential patient laboratory reports were accessible through the patient portal. The PDF documents were protected with passwords, but the passwords were weak enough to be recovered using *password-cracking techniques and wordlists supplied as part of the assessment environment*.

Further analysis of one decrypted PDF using ExifTool revealed sensitive metadata. In particular, the document contained an internal comment referencing an old database-backup directory:

DB backup moved to /old before site migration, do not delete

The /old/ location was subsequently found to have directory listing enabled. This exposed an SQL database backup file containing sensitive organisational information, including employee salary information and shareholder information.

The assessment therefore demonstrated a complete attack chain in which one vulnerability facilitated discovery of another:

Web reconnaissance → authentication weaknesses → SQL injection → authentication bypass → confidential PDF access → weak PDF passwords → metadata disclosure → forgotten backup directory → database backup exposure.

Overall Risk Rating: **CRITICAL**

Immediate remediation of the Critical and High-risk findings is recommended.

2. Assessment Scope and Methodology

2.1 Scope

The assessment was limited to the authorised target:

Target: <https://medirozahospital.com>

Testing focused on the web application and publicly accessible resources associated with the target.

The following activities were outside the intended scope:

- Social engineering
- Denial-of-service attacks
- Destructive testing
- Testing systems outside the authorised target
- Unauthorised access to third-party systems

2.2 Methodology

The assessment followed a structured black-box penetration-testing methodology consisting of:

Phase 1 — Reconnaissance

Information about the target was gathered using publicly accessible resources and controlled web requests.

Activities included:

- Web-server reconnaissance
- HTTP response analysis
- Directory and resource discovery
- Examination of robots.txt
- Identification of application paths
- Analysis of exposed resources

Phase 2 — Vulnerability Identification

The identified web application functionality was tested for weaknesses including:

- Username enumeration
- Authentication weaknesses
- SQL injection
- Improper access control
- Exposed files
- Weak document protection
- Information disclosure
- Directory listing

Phase 3 — Controlled Exploitation

Where vulnerabilities were identified, controlled exploitation was performed to demonstrate their impact without intentionally damaging the target.

Phase 4 — Evidence Collection and Reporting

Evidence was collected through:

- HTTP responses
- Browser observations
- Downloaded test files
- Password-cracking results
- PDF metadata
- Database-backup contents
- Screenshots

The findings were then assessed according to their potential confidentiality, integrity and availability impact.

3. Tools Used

The following tools and resources were used during the assessment:

- **Nmap** — network and service reconnaissance
- **curl** — HTTP request and response analysis
- **Browser Developer Tools** — inspection of web application behaviour
- **Gobuster / directory discovery tools** — discovery of accessible web resources
- **Networkwalks Hash Calculator** — extraction of PDF password hashes
- **Networkwalks Password Cracker** — controlled PDF password recovery
- **qpdf** — decryption of password-protected PDF files after authorised password recovery
- **ExifTool** — extraction and analysis of PDF metadata
- **wget** — retrieval of the exposed database backup
- **ChatGPT** — conversion of raw SQL records into readable analytical tables

4. Findings Summary

No	Vulnerability	Location	Severity
1	Username enumeration	patient/login.php	Medium
2	SQL injection authentication bypass	patient/login.php	Critical
3	Confidential PDF reports accessible after authentication bypass	patient/reports/	High
4	Weak PDF passwords recoverable using wordlists	patient_report_*.pdf	High
5	Sensitive metadata disclosed in patient PDF	patient_report_3.pdf	Medium
6	Forgotten backup directory with directory listing enabled	/old/	Critical
7	Confidential database backup exposed in plain text	/old/mediroza_db_backup_2019.sql	Critical

5. Detailed Findings

5.1 Finding 1 — Username Enumeration

Severity: Medium

Location: patient/login.php

Description

The patient portal login functionality disclosed whether a username existed through different error messages.

A non-existent username produced a response similar to:

Username not found

A valid username with an incorrect password produced:

Incorrect password

This behaviour allows an attacker to distinguish valid accounts from invalid accounts and build a list of potentially valid usernames.

Testing Performed

A test account name was entered with an incorrect password:

Username: bob

Password: test123

The application returned:

Username not found

A second test using:

Username: admin

Password: test123

returned:

Incorrect password

The difference confirmed that admin was recognised as an existing account.

Impact

An attacker can enumerate valid usernames and subsequently use them in password attacks or other authentication attacks.

Recommendation

The application should return a single generic error message for every failed login attempt, for example:

Invalid credentials. Please try again.

The application should not disclose whether the username or password was incorrect.

5.2 Finding 2 — SQL Injection Authentication Bypass

Severity: Critical

Location: patient/login.php

Description

The patient login form was vulnerable to SQL injection. User input was incorporated into a database query without adequate parameterisation.

A single quotation mark supplied in the username field generated a database syntax error, indicating that user input was being interpreted as part of the SQL statement.

Testing Performed

A controlled test using a quotation mark caused a database error.

The observed behaviour indicated that the application was constructing SQL statements using user-controlled input.

A subsequent controlled SQL injection test demonstrated that the authentication query could be altered so that the password verification was bypassed.

Impact

The vulnerability allowed authentication to be bypassed without knowledge of the legitimate user's password.

This represents a **Critical** security issue because successful exploitation provided access to functionality intended for authenticated users.

Recommendation

The application should use:

- Parameterised SQL queries
- Prepared statements
- Server-side input validation
- Proper error handling
- Generic error messages

Database errors should never be returned directly to users.

For PHP applications using PDO, a prepared statement should be used instead of concatenating user input into SQL queries.

5.3 Finding 3 — Confidential Patient Reports Accessible After Authentication Bypass

Severity: High

Location: patient/reports/

Description

After the authentication-control weakness was demonstrated, the patient portal exposed multiple downloadable laboratory reports.

The reports included:

patient_report_1.pdf

patient_report_2.pdf

patient_report_3.pdf

These files represented confidential medical documentation and should have been protected by appropriate authentication and authorisation controls.

Impact

An attacker exploiting the login vulnerability could reach confidential patient documents without having legitimate credentials.

The combination of the authentication bypass and inadequate document access control creates a serious confidentiality risk.

Recommendation

Patient reports should:

- Be stored outside the public web root where practical.
- Be served through authenticated server-side functionality.
- Verify that the requesting user is authorised to access the specific document.
- Use unpredictable file identifiers.
- Prevent direct unauthorised access to document URLs.
- Log access to sensitive medical records

5.4 Finding 4 — Weak PDF Passwords

Severity: High

Location: patient_report_*.pdf

Description

The three patient PDF documents were password protected, but the passwords were weak and recoverable using wordlist-based password cracking.

Results

The controlled assessment recovered passwords for all three reports:

patient_report_1.pdf → **123456**

patient_report_2.pdf → **password**

patient_report_3.pdf → **!@#\$%^&**

The first two passwords were recovered using the supplied default wordlist. The third required a larger password wordlist.

Impact

Weak document passwords provide little protection against an attacker who obtains the encrypted files.

An attacker who can download the files can perform offline password attacks without interacting with the hospital's web application.

Recommendation

The organisation should:

- Use strong, randomly generated document passwords.
- Avoid common passwords and predictable patterns.
- Use unique passwords for sensitive documents.
- Prefer server-side access control over relying solely on PDF passwords.
- Apply modern encryption mechanisms supported by the document-generation system.
- Establish a formal policy for protecting exported medical documents.

5.5 Finding 5 — Sensitive Metadata in Patient PDF

Severity: Medium

Location: patient_report_3.pdf

Description

PDF metadata can contain information that is not immediately visible when the document is opened normally.

After recovering the password for Report 3, the PDF was decrypted using qpdf:

```
qpdf --password='! @$%^&' --decrypt patient_report_3.pdf report3_open.pdf
```

ExifTool was then used to examine the metadata:

```
exiftool report3_open.pdf
```

The following significant metadata was identified:

Author : j. malik

Comments: DB backup moved to /old before site migration, do not delete

Creator : Mediroza CMS 1.4.2

Producer : Mediroza Lab Reporting Module

Impact

The Comments field disclosed an internal operational detail and provided a direct reconnaissance clue to an old database-backup location.

This demonstrates how metadata can unintentionally disclose information about:

- Internal personnel
- Software systems
- Infrastructure
- File-management practices
- Backup locations

Recommendation

Metadata should be sanitised before sensitive documents are distributed.

The document-generation process should automatically remove unnecessary metadata and internal comments.

For example, during controlled document sanitisation:

exiftool -all= filename.pdf

should be used only on an appropriate copy and after confirming that removing metadata will not affect required document functionality.

5.6 Finding 6 — Forgotten Backup Directory with Directory Listing Enabled

Severity: Critical

Location: /old/

Description

The /old/ directory was accessible through the web server and directory listing was enabled.

When a directory does not contain an appropriate index resource and directory listing is enabled, the web server can display its contents to visitors.

The exposed directory contained:

mediroza_db_backup_2019.sql

Testing Performed

The directory was accessed through:

<https://medirozahospital.com/old/>

The directory listing exposed the backup file.

The file was retrieved during the authorised assessment using:

wget https://medirozahospital.com/old/mediroza_db_backup_2019.sql

Impact

A database backup stored in a publicly accessible web directory represents a **Critical** confidentiality failure.

An unauthenticated attacker may be able to retrieve historical organisational information without compromising the database server itself.

Recommendation

The organisation should:

1. Remove the exposed backup immediately.
2. Store backups outside the public web root.
3. Disable directory listing.
4. Review the entire web server for other forgotten backup files.
5. Prevent backup files from being uploaded to publicly accessible directories.
6. Implement access controls around backup repositories.
7. Monitor the web server for requests to backup extensions such as .sql, .bak, .zip, .tar, and similar files.

For Apache environments, directory indexing should be disabled through the appropriate server configuration.

5.7 Finding 7 — Confidential Database Backup Exposed

Severity: Critical

Location: /old/mediroza_db_backup_2019.sql

Description

The exposed SQL backup contained database structures and records associated with the hospital's internal systems.

The backup identified:

Database: mediroza_hr

Host: localhost

CMS: Mediroza CMS 1.4.2

Backup date: 2019-08-27 02:14:03

The backup contained, among other structures:

- **staff**
- **shareholders**

The staff table contained employee information including names, job titles, departments and salary information.

The shareholder table contained ownership information including shareholder names, ownership percentages and share classes.

Impact

Exposure of the database backup creates a major confidentiality risk.

The backup could reveal:

- Organisational structure
- Employee information
- Salary information
- Ownership structure
- Internal system information
- Historical database configuration

The backup was accessible through the web server without appropriate protection.

Recommendation

The organisation should:

- Remove the exposed database backup.
- Store backups outside the web root.
- Encrypt backups at rest.
- Restrict backup access using strong authentication and authorisation.
- Apply least-privilege principles.
- Establish backup-retention policies.
- Regularly scan web directories for accidentally exposed backup files.
- Monitor access logs for suspicious downloads.
- Rotate potentially exposed credentials and secrets if any are present in historical backups.
- Treat historical backups as sensitive information even when they are no longer actively used.

6. Correlation of Findings

One of the most important aspects of the assessment was the relationship between individual vulnerabilities.

The findings were not isolated. They formed a connected attack chain.

Stage 1 — Reconnaissance

Web reconnaissance identified application resources, including the patient area and the /old/ location.

Stage 2 — Authentication Weakness

Username enumeration allowed valid account names to be distinguished from invalid ones.

Stage 3 — SQL Injection

The login functionality accepted SQL injection, allowing authentication controls to be bypassed.

Stage 4 — Patient Data Exposure

The authenticated area exposed three patient laboratory reports.

Stage 5 — Weak Document Protection

The PDFs were protected with weak passwords that could be recovered using wordlists.

Stage 6 — Metadata Disclosure

ExifTool revealed:

Author: j.malik

Comments: DB backup moved to /old before site migration, do not delete

Stage 7 — Backup Exposure

The /old/ directory had directory listing enabled and exposed:

mediroza_db_backup_2019.sql

Stage 8 — Organisational Data Exposure

The database backup contained sensitive staff and shareholder information.

This demonstrates how a relatively small information disclosure in a PDF could provide a useful lead for discovering a much more serious backup exposure.

7. Metadata and Staff Correlation

The PDF metadata contained:

Author: j.malik

The database staff table contained a corresponding employee:

Jameel Malik

Job Title: IT Systems Administrator

Department: IT

This creates a strong correlation between the metadata identifier and an employee record in the exposed database.

The assessment should, however, distinguish **correlation from definitive attribution**. The metadata provides evidence that j.malik was associated with the document metadata, while the staff database identifies the corresponding employee. It does not independently establish every action performed by that individual. This correlation nevertheless demonstrates the risk of leaving identifiable internal information in publicly accessible document metadata.

8. Risk Assessment

Finding	Severity	Primary Impact
Username enumeration	Medium	Account discovery
SQL injection	Critical	Authentication bypass
Patient report exposure	High	Medical information disclosure
Weak PDF passwords	High	Offline document compromise
PDF metadata disclosure	Medium	Internal information leakage
Public backup directory	Critical	Unauthorised file discovery
Exposed database backup	Critical	Staff and corporate information disclosure

Overall Assessment

Overall Risk: CRITICAL

The combination of authentication bypass and exposed sensitive files means that an attacker with limited technical resources could potentially progress from the public-facing web application to confidential organizational information.

9. Recommendations and Remediation

9.1 Fix Username Enumeration

The login system should return the same generic message for all authentication failures.

Recommended message:

Invalid credentials. Please try again.

The application should not reveal whether the username exists.

9.2 Remediate SQL Injection

All database queries involving user input should use parameterised queries or prepared statements.

Example PHP PDO approach:

```
$stmt = $pdo->prepare(
    "SELECT * FROM users WHERE username = ? AND password = ?"
);

$stmt->execute([$username, $password]);
```

Passwords should additionally be securely hashed using a modern password-hashing function such as `password_hash()` rather than stored or compared as plaintext.

Database errors should be logged securely on the server rather than displayed to users.

9.3 Strengthen Patient Report Access Control

Patient reports should not be directly accessible simply because an attacker knows or discovers their filenames.

Implement:

- Authentication
- Authorisation
- Per-user access checks
- Server-side document delivery
- Access logging
- Unpredictable document identifiers
- Secure storage outside the public web root

9.4 Improve PDF Protection

Sensitive PDF documents should use strong, unique protection mechanisms.

Where possible, access control should be implemented at the application/server level rather than relying entirely on PDF passwords.

If PDF passwords are required, they should be:

- Long
- Random
- Unique
- Unpredictable

- Not based on common passwords or symbols

9.5 Remove Sensitive PDF Metadata

The organisation should establish a document-sanitisation process before distributing sensitive documents.

Internal comments, usernames, software information and unnecessary creation details should be removed.

For controlled metadata removal:

```
exiftool -all= filename.pdf
```

A sanitised copy should be created and verified before the original evidence/document is altered or deleted.

9.6 Remove Public Backup Files

The exposed SQL backup should be removed from the public web directory immediately.

Database backups should be stored:

- Outside the web root
- On restricted storage
- With encryption at rest
- Behind authentication
- With appropriate access logging

Historical backups should be included in periodic security reviews.

9.7 Disable Directory Listing

Directory listing should be disabled across the web application.

The server configuration should prevent users from browsing directories where an index page is absent.

The organisation should also conduct a review for other publicly accessible directories such as:

/backup/

/backups/

/old/

/tmp/

/test/

/dev/

/staging/

and other locations containing historical or temporary files.

9.8 Implement Secure Backup Management

A formal backup-security policy should define:

- Where backups are stored
- Who can access them
- How they are encrypted
- How long they are retained
- How old backups are securely deleted
- How backup access is monitored
- How backups are tested for restoration

9.9. Conclusion

The penetration test identified a serious chain of security weaknesses within the Mediroza General Hospital web application.

The most significant vulnerability was the SQL injection flaw in the patient login system, which allowed authentication controls to be bypassed. Once access was obtained, confidential patient reports could be downloaded. Weak PDF passwords allowed the documents to be decrypted using wordlist-based password recovery.

Further investigation of Report 3 revealed sensitive PDF metadata containing an internal comment pointing to an old database-backup directory. The /old/ directory was publicly accessible with directory listing enabled, exposing a historical SQL database backup.

The backup contained sensitive staff and shareholder information, demonstrating that the combination of vulnerabilities could result in significant confidentiality loss. The assessment therefore demonstrates a **Critical overall security risk**. The highest-priority remediation actions are:

1. **Fix the SQL injection vulnerability immediately.**
2. **Remove the publicly accessible database backup.**
3. **Disable directory listing.**
4. **Move backups outside the public web root.**
5. **Strengthen patient-document access controls.**
6. **Replace weak PDF passwords with strong protection mechanisms.**
7. **Remove sensitive metadata from externally distributed documents.**
8. **Fix username enumeration and improve authentication error handling.**

The vulnerabilities identified are well-known and have established remediation approaches. Addressing the Critical and High findings should be prioritised before the application is used to process or expose real patient information.


NB


This penetration-testing assessment was conducted as part of the **Networkwalks B082 Week 4 Capstone Project** in a controlled educational environment.

The testing demonstrated how multiple weaknesses can be chained together to move from publicly accessible web resources to confidential organisational information.

All testing was performed within the authorised scope of the exercise. The identified vulnerabilities and sensitive information should be handled confidentially and used solely for the purposes of security assessment, remediation and education.

Evidence Register





```

NAME
    exiftool - Read and write meta information in files

RUNNING IN WINDOWS
    Drag and drop files or folders onto the exiftool executable to display
    meta information, or rename to "exiftool.exe" and run from the command
    line to access all exiftool features.

    This stand-alone Windows version allows simple command-line options to
    be added to the name of the executable (in brackets and separated by
    spaces at the end of the name), providing a mechanism to use options
    when launched via the mouse. For example, changing the executable name
    to "exiftool(-a -u -gl -w txt).exe" gives a drag-and-drop utility which
    generates sidecar ".txt" files with detailed meta information. As
    shipped, the -k option is added to cause exiftool to pause before
    terminating (keeping the command window open). Options may also be added
    to the "Target" property of a Windows shortcut to the executable.

SYNOPSIS
    Reading
        exiftool [*OPTIONS*] [-*TAG*...] [--*TAG*...] *FILE*...

    Writing
        exiftool [*OPTIONS*] -*TAG*[+<=<=*VALUE*]... *FILE*...

    Copying
        exiftool [*OPTIONS*] -tagsFromFile *SRCFILE* [-[*DSTTAG*<]*SRCTAG*...]
        *FILE*...

-- More --

```


```
Windows PowerShell
Copyright (C) Microsoft Corporation. All rights reserved.

Install the latest PowerShell for new features and improvements! https://aka.ms/PSWindows

PS C:\Users\berna> qpdf --version
qpdf version 12.4.1
Run qpdf --copyright to see copyright and license information.
PS C:\Users\berna> cd "$HOME\Downloads"
PS C:\Users\berna\Downloads> qpdf --password='!@#%*&' --decrypt patient_report_3.pdf report3_open.pdf
PS C:\Users\berna\Downloads> dir


Directory: C:\Users\berna\Downloads


Mode                LastWriteTime         Length Name
----                -
d-----          8/28/2026 11:03 PM             01. JTR_John CLI Win x64
d-----          8/28/2026 11:23 PM             02. JTR_Johnny GUI Win x64
d-----          8/20/2026 12:14 PM             8-jpeg-search
d-----          8/21/2026  5:00 PM          Comae-Toolkit-v20230117
d-----          9/11/2026 12:17 PM          exiftool-13.59.64
d-----          8/28/2026 10:20 PM          john-1.9.0-jumbo-1-win64
d-----          8/12/2026 10:21 PM          kali-linux-2026.2-virtualbox-amd64
d-----          5/1/2026  4:39 PM          metasploitable-linux-2.0.0
d-----          8/19/2026  4:58 PM              z. Extra Reference Files-20260819T135622Z-1-001
-a-----          8/28/2026 11:02 PM    68796870 01. JTR_John CLI Win x64.zip
-a-----          8/28/2026 11:06 PM    20750757 02. JTR_Johnny GUI Win x64.zip
-a-----          8/20/2026 12:12 PM    1101117 12-carve-ext2.zip
-a-----          5/18/2026  9:15 PM    102332 1735252_Pre Tech Studies_Grade 9_Term-II.pdf
-a-----          4/27/2026  6:41 PM    328744 177519711069cf5bb607b60377783952.pdf
-a-----          8/18/2026  2:02 PM    1279817 202513339305003_DENNISMUSILI.pdf
-a-----          5/5/2026  6:33 PM    1005187 5-5-2026_6-32-56_A004314693X_ITR.zip
-a-----          8/20/2026 12:11 PM    1944066 8-jpeg-search.zip
```



```
Windows PowerShell
C:\Users\berna\Downloads\exiftool-13.59_64\exiftool-13.59_64\exiftool_files\lib\Unicode\GCString.pm
C:\Users\berna\Downloads\exiftool-13.59_64\exiftool-13.59_64\exiftool_files\lib\Unicode\LineBreak.pm
C:\Users\berna\Downloads\exiftool-13.59_64\exiftool-13.59_64\exiftool_files\lib\Unicode\LineBreak\Constants.pm
C:\Users\berna\Downloads\exiftool-13.59_64\exiftool-13.59_64\exiftool_files\lib\warnings\register.pm
C:\Users\berna\Downloads\exiftool-13.59_64\exiftool-13.59_64\exiftool_files\lib\Win32\API.pm
C:\Users\berna\Downloads\exiftool-13.59_64\exiftool-13.59_64\exiftool_files\lib\Win32\FindFile.pm
C:\Users\berna\Downloads\exiftool-13.59_64\exiftool-13.59_64\exiftool_files\lib\Win32\API\Struct.pm
C:\Users\berna\Downloads\exiftool-13.59_64\exiftool-13.59_64\exiftool_files\lib\Win32\API\Type.pm
C:\Users\berna\Downloads\exiftool-13.59_64\exiftool-13.59_64\exiftool_files\lib\Win32API\File.pm
C:\Users\berna\Downloads\exiftool-13.59_64\exiftool-13.59_64\exiftool_files\lib\Win32API\File\cFile.pc

PS C:\Users\berna\Downloads> & ".\exiftool-13.59_64\exiftool.exe" report3_open.pdf
ExifTool Version Number      : 13.59
File Name                    : report3_open.pdf
Directory                   : .
File Size                    : 2.9 kB
File Modification Date/Time  : 2026:09:11 13:23:07+03:00
File Access Date/Time       : 2026:09:11 13:23:08+03:00
File Creation Date/Time     : 2026:09:11 13:20:22+03:00
File Permissions             : -rw-rw-rw-
File Type                   : PDF
File Type Extension         : pdf
MIME Type                   : application/pdf
PDF Version                 : 1.4
Linearized                  : No
Author                     : j.malik
Comments                    : DB backup moved to /old before site migration
Creator                    : Mediroza CMS 1.4.2
Keywords                    : pathology, patient report
Producer                   : Mediroza Lab Reporting Module
Subject                     : Full Blood Count
Title                      : Pathology Report - E. Thompson
Page Count                  : 1
PS C:\Users\berna\Downloads>
```





The screenshot shows a Kali Linux terminal window with the following content:

```

kali-linux-2026.2-virtualbox-amd64 [Running] - Oracle VM VirtualBox
File Machine View Input Devices Help

root@kali: ~
Session Actions Edit View Help

(root@kali)~# sudo apt update
Get:1 http://kali.download/kali kali-rolling InRelease [34.0 kB]
Get:2 http://kali.download/kali kali-rolling/main amd64 Packages [21.5 MB]
Get:3 http://kali.download/kali kali-rolling/main amd64 Contents (deb) [53.5 MB]
Get:4 http://kali.download/kali kali-rolling/contrib amd64 Packages [113 kB]
Get:5 http://kali.download/kali kali-rolling/contrib amd64 Contents (deb) [261 kB]
Get:6 http://kali.download/kali kali-rolling/non-free amd64 Packages [183 kB]
Get:7 http://kali.download/kali kali-rolling/non-free amd64 Contents (deb) [915 kB]
Get:8 http://kali.download/kali kali-rolling/non-free-firmware amd64 Packages [16.0 kB]
Get:9 http://kali.download/kali kali-rolling/non-free-firmware amd64 Contents (deb) [40.6 kB]
Fetched 76.5 MB in 1min 56s (657 kB/s)
1240 packages can be upgraded. Run 'apt list --upgradable' to see them.

(root@kali)~# sudo apt install exiftool -y
Note, selecting 'libimage-exiftool-perl' instead of 'exiftool'
libimage-exiftool-perl is already the newest version (13.55+dfsg-1).
libimage-exiftool-perl set to manually installed.
Summary:
  Upgrading: 0, Installing: 0, Removing: 0, Not Upgrading: 1240

(root@kali)~# exiftool -ver
13.55

(root@kali)~# curl -I https://medirozahospital.com
HTTP/2 200
content-type: text/html
last-modified: Fri, 04 Sep 2026 02:03:12 GMT
accept-ranges: bytes
content-length: 5445

```