From documents to an approved handoff

Secure workflow automation for a dedicated notary office

The workflow

Receive documents. Extract structured values. Resolve uncertainty. Approve a frozen export. Confirm its receipt.

The demonstration

One office, synthetic property-purchase documents and an independent reference HTTP destination.

Property purchase intake

Prove a complete, reviewable workflow before expanding integrations.

Inputs and output

Read PDFs, scans and saved email; review extracted values. Staff can add further parties and properties. Enriched cases use canonical JSON; legacy exports remain available for cases without additional details.

Scope boundary

A dedicated-office prototype has PostgreSQL concurrency, HTTP, scanner and restore evidence. Vendor acceptance, client hosting and office measurements remain.

Seven visible stages

Every consequential decision stays visible to the office.

Receive > Classify > Extract

Keep incoming evidence with the case. Identify the workflow and propose values with their source locations.

Validate > Review > Export > Audit

Flag conflict and missing information. Require human approval. Record the export and a separate verified receipt.

A disagreement the office must resolve

Synthetic purchase documents intentionally disagree on the land-register sheet.

Agreed case data

Buyer: Anna Schmidt
Seller: Peter Müller
Purchase price: EUR 850,000
Questionnaire and register: München Blatt 812

A meaningful exception

The draft contract states Blatt 872. The conflict blocks approval until a reviewer chooses or corrects the value. The price also needs explicit confirmation.

Review first. Freeze the decision.

Confidence supports review; it does not authorize a destination write.

The clerk

Compare sources, correct values and confirm required policy fields. Source selections update case data. Reusable labels and mappings are edited separately by an administrator.

The approver

Approve only after all blockers are resolved. The snapshot freezes values, mappings and approval identity. Stale edits cannot undo that approval.

A signed receipt proves the handoff

Actual HTTP transport to an independent reference destination; vendor acceptance remains separate.

Create the approved export

Generate a checksummed payload from the frozen approval. Export a file or send authenticated JSON. Repeated requests reuse the same approval-bound idempotency key.

Confirm the destination

The HTTP receiver commits the payload before returning a signed receipt. Wrong keys or receipts keep delivery pending. A lost-response retry retrieves the original receipt without a duplicate import.

Controls that can be demonstrated

Show the controls and their practical limits.

Confidentiality and approval

Per-office encryption covers source files, source text, structured case values, revisions and audit metadata. Production refuses development secrets. Review and approval share a locking protocol.

Traceability and retention

Audit events have a signed hash chain. Separately held checkpoints detect an older database replay. Encrypted backups restore sources, private fields, approvals and export evidence.

A dedicated pilot boundary

Prepare separate database, storage and keys for each office.

Presentation environment

The launcher creates one office, a separate database, vault and keys. Local OCR reads scans; original-source review remains mandatory. A remote scanner/email client uses only the intake API.

Deployment package

Concurrency and complete encrypted restore passed on local PostgreSQL. A dedicated HTTPS stack is supplied. Its container build, client hosting, TLS and operational recovery still need validation.

Measure results without mixing demo data

Demonstration history is clearly labelled and excluded from live-pilot measurements.

Four analytics tabs

Filter by intake receipt period, workflow, source and demo/live cohort. Inspect extraction and review, workload and median/P90 timing, delivery and audit. Charts have exact-value tables, case links and aggregate CSV export.

Compare the right measures

First-extraction coverage differs from human-completed fields. Elapsed approval time includes waiting; staff handling time and re-keying errors need separate office measurements. Synthetic checks do not establish customer accuracy or savings.

A seven-minute walkthrough

Use /presentation/ as your presenter guide.

Minutes 1–4

Open the unprocessed intake. Process the documents. Show the Blatt 812 / 872 conflict. Resolve the source choice and confirm the price as the clerk.

Minutes 5–7

Sign in as the notary. Approve, create the HTTP export and send it. Show its verified receipt and audit trail. Optionally demonstrate scanned intake and mandatory source review.

Prepare the ProNotar32 connection

The case and mapping foundation is implemented; vendor import still needs validation.

Implemented foundation

Encrypted additional parties and properties, office references, immutable mapping revisions and a canonical JSON adapter. Approval freezes the complete case and mapping; an API serves approved case data.

Next: validate ProNotar32

Obtain the office's version, import schema, accepted sample files and test environment. Implement and verify the vendor adapter. ProNotar delivery is blocked; native plugins, scoped credentials and queued sends remain planned.

Select one destination. Validate one workflow.

A controlled, demonstrable foundation for the first office pilot.

What you can present today

Reviewed case details, frozen mappings, canonical exports and signed HTTP handoff. All 152 tests passed on PostgreSQL 17; the new case-details workflow passed desktop/mobile browser checks. Vendor acceptance remains separate.

What the client supplies next

A supported destination interface and test environment, sanitized examples, an accepted deployment boundary and agreed success criteria.