

ONESIMUS IMPACT FOUNDATION

OIF Platform Administrator Manual

Complete Administration, Operations, Access,
Finance, and Governance Handbook

Onesimus Impact Foundation

17 August 2026

- 1 About this handbook
 - 1.1 Purpose
 - 1.2 Intended readers
 - 1.3 Document control
 - 1.4 Terminology
- 2 Administrator mandate
 - 2.1 Core objectives
 - 2.2 Administrative principles
 - 2.3 Authority boundaries
- 3 Administrator access and navigation
 - 3.1 Main locations
 - 3.2 Recommended administrator browser practices
- 4 Initial system setup
 - 4.1 Pre-launch sequence
 - 4.2 Organization profile setup
 - 4.3 First staff accounts
 - 4.4 Initial content setup
 - 4.5 Initial finance setup
- 5 Operating cadence
 - 5.1 Daily checks
 - 5.2 Weekly checks
 - 5.3 Monthly checks
 - 5.4 Quarterly checks
 - 5.5 Annual or fiscal-period checks
- 6 User and access administration runbook
 - 6.1 Creating or accepting an account
 - 6.2 Changing a role
 - 6.3 Deactivation and offboarding
 - 6.4 Access incident
- 7 Public website and CMS runbook
 - 7.1 Standard content change
 - 7.2 Media standards
 - 7.3 Policy publishing
 - 7.4 Emergency public correction
- 8 Event administration runbook
 - 8.1 Creating an event
 - 8.2 Managing registration
 - 8.3 Post-event closure
- 9 Application and mentorship runbook
 - 9.1 Reviewing applications
 - 9.2 Managing mentorship
- 10 Enquiry and partnership runbook
 - 10.1 Contact messages
 - 10.2 Partnership enquiries
- 11 Donation and Paystack runbook
 - 11.1 Before enabling online giving
 - 11.2 Pending donation procedure
 - 11.3 Successful donation procedure
 - 11.4 Failed donation procedure
 - 11.5 Refunds and reversals
- 12 Messaging runbook
 - 12.1 Provider readiness
 - 12.2 Campaign preparation checklist
 - 12.3 After sending
 - 12.4 High-volume caution
- 13 Finance and accounting runbook
 - 13.1 Expense procedure
 - 13.2 Cash account procedure
 - 13.3 Cash movement procedure
 - 13.4 Journal procedure
 - 13.5 Fiscal period procedure
 - 13.6 Budget procedure
 - 13.7 Bank reconciliation procedure
 - 13.8 Accounting health review
- 14 Reports, audit, and exports
 - 14.1 Report use
 - 14.2 Audit review
 - 14.3 Export handling
- 15 Security administration
 - 15.1 Application security controls
 - 15.2 Credential handling
 - 15.3 Data minimization
 - 15.4 Security incident checklist
- 16 Backup, recovery, and continuity
 - 16.1 Backup scope
 - 16.2 Backup controls
 - 16.3 Recovery order
- 17 Release and deployment runbook
 - 17.1 Before deployment
 - 17.2 Standard commands
 - 17.3 After deployment
 - 17.4 Rollback principle
- 18 Administrator troubleshooting matrix
- 19 Administrator checklists
 - 19.1 New member approval checklist
 - 19.2 New event checklist
 - 19.3 Campaign checklist
 - 19.4 Donation reconciliation checklist
 - 19.5 Fiscal-period close checklist
 - 19.6 Staff offboarding checklist
 - 19.7 Production readiness checklist
- 20 Escalation and change control
- 21 Module reference
- 22 OIF Platform Module and Operations Manual
 - 22.1 1. Purpose and audience
 - 22.2 2. Platform at a glance
 - 22.3 3. Common concepts
 - 22.4 4. Accounts module
 - 22.5 5. Pages and public CMS module
 - 22.6 6. Events module
 - 22.7 7. Applications and mentorship module
 - 22.8 8. Enquiries and newsletter module
 - 22.9 9. Donations module
 - 22.10 10. Messaging module

- 22.11 11. Dashboard and reporting module
- 22.12 12. Finance and accounting module
- 22.13 13. Notifications
- 22.14 14. Configuration and integrations
- 22.15 15. Media and file handling
- 22.16 16. Maintenance and deployment
- 22.17 17. Troubleshooting guide
- 22.18 18. Data stewardship
- 22.19 1. Purpose
- 22.20 2. How role-based access works
- 22.21 3. Capability glossary
- 22.22 4. Role capability matrix
- 22.23 5. Shared access for every authenticated role
- 22.24 6. Super Administrator
- 22.25 7. Global Lead
- 22.26 8. Executive Director
- 22.27 9. Director / Staff
- 22.28 10. Director of Programmes
- 22.29 11. Director of Operations & Volunteer Engagement
- 22.30 12. Director of Communications, Media & Digital
- 22.31 13. Director of Partnerships & Resource Mobilisation
- 22.32 14. Finance / Donations Manager
- 22.33 15. Content Editor
- 22.34 16. Event Manager
- 22.35 17. Mentor
- 22.36 18. Volunteer
- 22.37 19. Applicant
- 22.38 20. Donor
- 22.39 21. Member
- 22.40 22. Choosing the correct role
- 22.41 23. Account onboarding procedure
- 22.42 24. Role-change procedure
- 22.43 25. Offboarding and temporary suspension
- 22.44 26. Periodic access review
- 22.45 27. Practical boundaries and known implementation details

1 About this handbook

1.1 Purpose

This handbook is the complete operating reference for administrators of the Onesimus Impact Foundation (OIF) platform. It explains how to administer the organization’s website, accounts, programmes, events, engagement, donations, communications, finance, reporting, integrations, security, and technical operations.

The handbook combines three layers of guidance:

1. **Administrator runbooks** — what an administrator should do and in what order.
2. **Module reference** — how every functional area works, including record lifecycles and troubleshooting.
3. **Role reference** — what every role can access and how access should be assigned and reviewed.

The final two references are incorporated in full into the PDF edition. The maintained source files are `MODULES_MANUAL.md` and `ROLES_MANUAL.md`.

1.2 Intended readers

This handbook is written primarily for:

- Super Administrators;
- Executive Directors and authorized directors;
- system owners and deployment operators;
- finance, content, event, communications, and member administrators;
- auditors and governance reviewers.

Not every administrator should perform every procedure. The role and capability rules in this handbook always apply.

1.3 Document control

Item	Value
Document	OIF Platform Administrator Manual
Edition	1.1
Effective date	17 August 2026
System	Onesimus Impact Foundation Django Platform
Classification	Internal operating documentation
Review trigger	Role, workflow, integration, security, or deployment change
Recommended review	At least every six months

1.3.1 Changes in edition 1.1

- New member sign-ups now require staff approval before they can sign in (an account-activation gate, not a role change) — see “User and access administration runbook” and `MODULES_MANUAL.md` section 4.3.
- Two new site-wide CMS sections, Page Photos and Page Copy, put every remaining public-site hero photo and headline/paragraph writeup under administrator control — see “Public website and CMS runbook” and `MODULES_MANUAL.md` section 5.8.
- Privacy, Terms, and Donation policies are now seeded automatically so their public pages and footer links never 404 on a fresh deployment.
- The public event detail page adds a live countdown, a registration status indicator, and a seat-fill meter; programme detail pages show a full photo gallery instead of a single image; the Contact page adds a location map.

1.4 Terminology

Term	Meaning
Administrator	A person granted one or more operational capabilities
Super Administrator	The platform role with every defined capability
Django Admin	The technical <code>/admin/</code> interface, distinct from the OIF dashboard
Dashboard	The role-aware workspace at <code>/dashboard/</code>

Term	Meaning
CMS	The Site Content management functions in the dashboard
Capability	A named permission checked by protected views
Public user	A visitor who is not signed in
Member	Both a standard platform role and, in general prose, an account holder
Production	The live organization environment and data
Demo mode	A deliberate simulation mode that can mark donations successful without Paystack

2 Administrator mandate

2.1 Core objectives

An administrator is responsible for keeping the platform:

- accurate;
- available;
- secure;
- appropriately permissioned;
- operationally useful;
- financially controlled;
- auditable;
- compliant with OIF policy and applicable obligations.

Administration is not merely data entry. Every administrative action may affect public information, participant experience, communications, financial records, or access to personal data.

2.2 Administrative principles

2.2.1 Least privilege

Grant the narrowest role that supports a person's authorized work. Do not use Super Administrator as a convenience role.

2.2.2 Separation of duties

Where staffing permits, separate preparation, approval, payment, reconciliation, and review. The application does not enforce a different person for every finance transition, so OIF's operating policy must supply this control.

2.2.3 Evidence before status

Do not mark a donation successful, expense paid, application approved, event attended, or reconciliation complete without appropriate evidence.

2.2.4 Preserve history

Deactivate accounts instead of deleting them. Reverse posted journals instead of altering history. Close or hide records when that preserves operational context better than deletion.

2.2.5 Verify public changes

After a CMS or event change, inspect the public page and its links. A successful save confirms database storage, not visual or editorial correctness.

2.2.6 Protect personal and financial data

Use platform data only for authorized OIF purposes. Keep exports, attachments, credentials, and delivery reports secure.

2.3 Authority boundaries

A platform capability allows a technical action; it does not replace organizational authorization. For example:

- `manage_donations` permits a status change but does not itself prove funds were received;
- `send_messages` permits a campaign but does not establish lawful consent or approve its wording;
- `manage_content` permits publication but does not replace editorial or legal approval;
- `manage_users` permits role changes but does not authorize unapproved access.

3 Administrator access and navigation

3.1 Main locations

Area	Path	Purpose
Public site	/	Public-facing website
Dashboard	/dashboard/	Personal and administrative workspace
Account profile	/accounts/profile/	Personal profile and avatar
Login	/accounts/login/	Authentication
Password reset	/accounts/password-reset/	Self-service password recovery
Django Admin	/admin/	Technical model administration
Sitemap	/sitemap.xml	Search-engine sitemap
Robots file	/robots.txt	Crawler instructions

Dashboard navigation adapts to capabilities. Overview, Events, Donations, Applications, Mentorship, and Profile contain personal information for every authenticated user. Staff functions appear when the role grants the necessary capability.

3.2 Recommended administrator browser practices

- Use a supported, updated browser.
- Do not save platform passwords on shared computers.
- Sign out when leaving an unattended device.
- Avoid simultaneous edits to the same record.
- Do not use browser Back to repeat payment, campaign-send, or state-changing submissions.
- Treat CSV exports and downloaded financial attachments as confidential.
- Use a separate browser profile for production administration where practical.

4 Initial system setup

4.1 Pre-launch sequence

Complete these tasks before the platform is used in production:

1. Configure a strong production secret key.
2. disable debug mode;
3. configure allowed hosts and trusted CSRF origins;
4. configure the production database;
5. configure persistent media storage and backups;
6. configure SMTP and test delivery;
7. configure Paystack and ensure demo mode is off;
8. configure messaging providers only if they will be used;
9. run database migrations and collect static files;
10. create the first Super Administrator;
11. set organization branding and contact details;
12. replace placeholder phone numbers, policies, and sample assets;
13. create or verify programmes and resources;
14. review public pages and responsive presentation;
15. test signup, login, password reset, and profile updates;
16. test event registration and email confirmation;
17. test Paystack with the appropriate test environment;
18. open accounting and review the default chart/fund;
19. assign staff roles;
20. run the production checks and complete the launch checklist.

4.2 Organization profile setup

Open **Site CMS** and configure:

- official organization name and short name;
- tagline, founded year, and location;
- monitored contact email and phone;
- public website URL;
- footer description;
- social URLs;
- full logo, compact mark, and favicon;
- heading and body fonts.

Confirm the result on the public header/footer, browser tab, and dashboard.

4.3 First staff accounts

For each staff member:

1. use an individual account rather than a shared account;
2. confirm the person's name and email;
3. select the role using the role-selection table in this handbook;
4. leave Django staff status disabled unless `/admin/` is required;
5. require the user to set and keep their own password;
6. verify active status;
7. ask the user to confirm their expected dashboard access;
8. document authorization according to OIF policy.

4.4 Initial content setup

Review every public content family:

- programmes;
- resources;

- speakers;
- leadership;
- statistics;
- testimonials;
- gallery;
- policies;
- events;
- page imagery (Site CMS → Page Photos) — replace placeholder hero photos with real OIF photography where available;
- page copy (Site CMS → Page Copy) — replace default headlines/writeups with organization-approved wording where the default text should not go live as-is.

Use active/published controls deliberately. Remove demonstration content from production and verify every download and external URL.

4.5 Initial finance setup

1. Open **Statements & Ledger** to create default ledger accounts and the General Fund.
2. Review account names, types, and posting controls.
3. Create any additional funds with accurate restrictions.
4. create a non-overlapping fiscal period;
5. create and link operational cash/bank/payment-gateway accounts;
6. record verified opening balances and dates;
7. establish the expense evidence and approval procedure;
8. establish Paystack clearing and bank reconciliation procedures;
9. create budgets if used;
10. export and retain an approved opening configuration report.

5 Operating cadence

5.1 Daily checks

An administrator or designated operational owner should review:

- failed logins or infrastructure alerts supplied by the hosting environment;
- new contact messages;
- new partnership enquiries;
- new and pending applications;
- members awaiting approval;
- upcoming event registration counts and capacity;
- Pending or Failed donations;
- receipt-delivery exceptions;
- failed or partially sent campaigns;
- accounting exceptions arising from newly confirmed donations or expenses;
- backup/monitoring alerts.

The exact list should be divided among roles. A Super Administrator need not personally process every queue.

5.2 Weekly checks

- Review inactive or stale operational queues.
- Reconcile Paystack and relevant cash/bank accounts.
- Ensure recent events have accurate attendance.
- Update mentorship progress.
- review public event and programme information;
- inspect campaign delivery rates and recurring failures;
- inspect accounting health;
- review audit entries for sensitive changes;
- confirm scheduled backups completed.

5.3 Monthly checks

- Reconcile all material cash and bank accounts.
- Review donation, expense, cash, and ledger totals.
- produce management reports for the month;
- review budget variance;
- review membership and engagement trends;
- inspect unsuccessful notifications;
- review active staff accounts and broad roles;
- confirm policy and contact information remains current;
- test a restore or follow the approved backup verification process.

5.4 Quarterly checks

- Perform a formal access review.
- Review Super Administrators and Django staff accounts.
- rotate credentials according to provider/security policy;
- review integration configuration and unused providers;
- review data retention and unnecessary exports;
- inspect audit and finance exceptions;
- review disaster-recovery readiness;
- update this handbook for implemented workflow changes.

5.5 Annual or fiscal-period checks

- Confirm the period contains all expected source transactions.
- resolve unbalanced drafts and unposted source records;

- complete bank reconciliations;
- produce and approve final statements;
- close the fiscal period only after review;
- create the next non-overlapping period;
- establish and approve the new budget;
- archive approved exports and evidence;
- review policies, branding, leadership, and programme information.

6 User and access administration runbook

6.1 Creating or accepting an account

Public users can self-register and become Members. A self-registered account is created inactive and cannot sign in until approved — Django itself refuses to authenticate an inactive account, so this is a real gate, not a courtesy notice. Approve a pending member from Members (a “Members awaiting approval” work-queue item and a “Pending approval” filter make them easy to find):

1. confirm the account appears legitimate;
2. open the record;
3. on the Admin tab, check **Active account (approved to sign in)**;
4. save — the member receives a sign-in email automatically.

When an account is created or accepted internally instead (staff, or a Member outside the public flow):

- verify identity using the organization’s approved process;
- avoid duplicate accounts by checking username and email;
- confirm email and phone spelling;
- assign a role only with authorization;
- activate the account;
- use password reset for secure password creation;
- never email a password.

6.2 Changing a role

Only a user with `manage_users` can edit role and Django staff fields in the dashboard. Under the implemented mapping, this is the Super Administrator.

Before a role change:

1. obtain authorization;
2. compare current and proposed capabilities;
3. review whether finance, message delivery, member, or audit data will become visible;
4. apply the change;
5. verify navigation and one representative protected screen;
6. confirm an audit entry exists;
7. tell the user what responsibilities changed.

Approving a Mentor or Volunteer application can automatically promote a Member or Applicant. Review these decisions with the same care as a manual role change.

6.3 Deactivation and offboarding

1. Set the account inactive.
2. remove Django staff/superuser access if present;
3. reassign operational work;
4. rotate any provider credentials known to the person;
5. preserve the account for historical attribution;
6. recover or securely delete local exports according to OIF policy;
7. record completion of the offboarding process.

Do not delete a person merely to remove access.

6.4 Access incident

If an account may be compromised:

1. deactivate it immediately if authorized;
2. preserve logs and relevant audit information;
3. reset credentials;
4. terminate or invalidate hosting sessions where supported;
5. inspect role, integration, content, message, donation, and accounting changes;
6. rotate exposed secrets;

7. notify the responsible OIF owner;
8. follow the incident-response and legal notification procedure;
9. restore access only after verification.

7 Public website and CMS runbook

For a hero photo or headline that is not tied to a specific programme, speaker, leader, testimonial, gallery item, or event, use **Site CMS → Page Photos** or **Site CMS → Page Copy** instead of searching for a content record that does not exist — these two sections cover every remaining public page image and writeup (MODULES_MANUAL.md section 5.8).

7.1 Standard content change

1. Identify the owning content record.
2. confirm approved wording and asset rights;
3. edit the record in the relevant Content Library area;
4. set order and active/published flags;
5. save;
6. open the public page in a new tab;
7. check desktop and mobile layout;
8. check links, files, images, dates, and contact details;
9. correct or unpublish promptly if verification fails.

7.2 Media standards

- Use descriptive, appropriate images.
- Obtain permission or licensing before publication.
- Resize/compress images before upload.
- Avoid placing confidential data in filenames or embedded imagery.
- Supply captions/attribution according to OIF policy.
- Do not use the CMS as the only archive of original media.

7.3 Policy publishing

Policy text should be approved by the responsible governance/legal owner. Clear the placeholder flag only when final text is in place. Record the approval outside the CMS if the application has no separate approval workflow.

7.4 Emergency public correction

For materially wrong or unsafe public information:

1. unpublish or deactivate the affected record;
2. preserve the previous wording where required for evidence;
3. notify the content owner;
4. publish approved corrected information;
5. verify caches/public rendering;
6. record the incident and resolution.

8 Event administration runbook

8.1 Creating an event

1. Select the event type and related programme.
2. enter an accurate title, theme, summary, and description;
3. specify audience, outcomes, agenda, speakers, and preparation;
4. provide accessibility information;
5. upload a flyer;
6. enter start date/time and location;
7. include venue address and/or online URL;
8. set capacity, using zero only for unlimited;
9. add registration and contact notes;
10. decide whether the event is published and registration is open;
11. save and verify the public page;
12. test registration and calendar download.

The system assumes a two-hour duration in generated calendar entries because only the start time is stored.

8.2 Managing registration

- Monitor capacity and active registrations.
- Close registration before capacity is exceeded or logistics require it.
- Treat accessibility and dietary information as sensitive.
- Update attendee status accurately.
- Use event-recipient messaging only for relevant communications.
- Avoid exporting attendee data unless necessary.

8.3 Post-event closure

1. Mark attendance accurately.
2. close registration;
3. retain or unpublish the page according to event/publication policy;
4. review attendance and cancellation metrics;
5. resolve event-related enquiries;
6. update related gallery/impact content if approved;
7. retain necessary participant records according to policy.

9 Application and mentorship runbook

9.1 Reviewing applications

1. Review applicant identity, type, interest, and motivation.
2. follow the approved selection process outside the software where needed;
3. choose Approve or Reject;
4. understand that Mentor and Volunteer approval can change the account role;
5. verify the decision email result if delivery monitoring is available;
6. create mentorship enrollment separately for an approved mentee;
7. preserve fair and confidential handling.

Do not use application notes or decisions for purposes unrelated to the application.

9.2 Managing mentorship

1. Select the correct mentee.
2. assign an approved mentor or leave unassigned temporarily;
3. select the programme and cohort;
4. confirm total sessions;
5. update sessions completed;
6. progress through Phase 1, Phase 2, and Completed;
7. correct assignment or totals promptly;
8. ensure mentors see only their assigned mentees.

10 Enquiry and partnership runbook

10.1 Contact messages

- New means unprocessed.
- Read means acknowledged/reviewed.
- Resolved means the required response or action is complete.
- Reopen to New when further handling is required.

Assign internal responsibility outside the platform if more than one team is involved. The `handled_by` field records the last administrator who changed the status, not a full case-management history.

10.2 Partnership enquiries

Use:

- **New** when received;
- **In review** during qualification;
- **Engaged** during active discussion;
- **Closed** when concluded or no longer active.

Only `manage_partners` changes these statuses. Keep substantive partnership documents in the approved organizational repository, not in free-text messages alone.

11 Donation and Paystack runbook

11.1 Before enabling online giving

1. Confirm the Paystack account and settlement details.
2. use keys for the correct live/test environment;
3. configure the callback and webhook URLs;
4. configure the webhook secret;
5. ensure demo mode is disabled in production;
6. perform a controlled test;
7. confirm receipt email and accounting journal behavior;
8. restrict integration settings to authorized administrators.

11.2 Pending donation procedure

1. Open the donation record.
2. verify the reference is present;
3. run Paystack Verify;
4. compare provider reference, amount, currency, and metadata;
5. use bulk reconciliation for multiple pending references;
6. investigate provider errors;
7. mark success manually only with independent settlement evidence.

11.3 Successful donation procedure

Confirm:

- status is Successful;
- donor details are appropriate;
- receipt was sent or the absence is explained;
- source journal exists;
- Paystack clearing/bank process accounts for settlement and fees;
- campaign/fund treatment is correct.

The campaign text on a donation does not automatically assign a restricted accounting fund.

11.4 Failed donation procedure

- Confirm the provider result.
- Do not treat failure as income.
- allow the donor to retry using a new transaction;
- avoid exposing provider internals to the donor;
- investigate repeated failures or configuration problems.

11.5 Refunds and reversals

The current application does not provide a complete Paystack refund workflow. Handle refunds through the authorized provider/finance process, retain evidence, and record the necessary accounting entries or reversals. Do not simply relabel a previously successful donation and assume the ledger has been corrected.

12 Messaging runbook

12.1 Provider readiness

Before sending:

- verify Email is enabled and SMTP works;
- verify the selected SMS provider and sender ID;
- verify WhatsApp token and phone-number ID;
- confirm provider balance/quota;
- never place credentials in message content.

12.2 Campaign preparation checklist

1. Define the business purpose and owner.
2. select Email, SMS, WhatsApp, or all channels;
3. select the smallest correct audience;
4. use Marketing opt-ins for promotional member messaging;
5. choose an event audience only for that event;
6. review custom recipients carefully;
7. enter subject and body;
8. validate `{name}`, `{first_name}`, `{email}`, `{phone}`, and `{org_name}`;
9. proofread dates, links, phone numbers, and calls to action;
10. test with a small/custom audience when risk is high;
11. obtain content approval;
12. send once and wait for completion.

12.3 After sending

- Inspect Sent, Failed, and Skipped deliveries.
- calculate whether failures indicate data quality or provider problems;
- correct source contact data through the authorized workflow;
- do not resend the entire campaign casually;
- retain campaign evidence according to communications policy;
- respond to opt-out requests and update consent/subscription status.

12.4 High-volume caution

Delivery is synchronous. A large multi-channel audience can hold the web request open. Do not refresh or click Send repeatedly. For materially larger operations, schedule a technical enhancement using a background job queue.

13 Finance and accounting runbook

13.1 Expense procedure

1. Create a Draft expense.
2. record title, category, payee, description, amount, currency, date, method, reference, and receipt;
3. verify evidence and budget authority;
4. approve under OIF policy;
5. mark Paid only after payment;
6. confirm the automated source journal;
7. link or record the corresponding cash movement as required;
8. use Void for cancelled records and review any existing journal.

Approved expenses credit Accounts Payable; Paid expenses credit Cash in the automated source journal. Because source posting is idempotent, changing an already posted Approved expense to Paid does not automatically replace its original journal. Finance must review and enter the appropriate settlement entry.

13.2 Cash account procedure

- Create accounts with the correct type and currency.
- Record verified opening balance and date.
- mask and protect account information.
- link the appropriate asset ledger account;
- use Active, Inactive, and Closed deliberately;
- do not delete an account that has movements;
- update statement balance through reconciliation.

13.3 Cash movement procedure

- Draft movements do not affect balances.
- Posted Money in increases the source account.
- Posted Money out reduces the source account.
- Posted Transfer reduces the source and increases the destination.
- Transfers require different accounts in the same currency.
- Use Void for invalidated movements and confirm reporting effects.
- Attach appropriate evidence.

13.4 Journal procedure

1. Choose entry date, description, reference, period, and fund.
2. add posting-account lines;
3. put each amount on exactly one side;
4. confirm total debits equal credits above zero;
5. save Draft for review or Post;
6. verify the generated journal number;
7. use Reverse for correction after posting.

Never change accounting meaning by directly editing or deleting a posted entry.

13.5 Fiscal period procedure

Before closing:

- all expected transactions are recorded;
- draft journals are posted or removed;
- reconciliations are complete;
- accounting exceptions are resolved;
- reports have been reviewed and retained;
- governance approval has been obtained.

Closing blocks posting into the period. Reopening should be exceptional, authorized, and followed by renewed close review.

13.6 Budget procedure

1. Select fiscal period and optional fund.
2. add each income/expense account once;
3. enter non-negative amounts;
4. review totals and assumptions;
5. approve;
6. lock when final;
7. review variance regularly;
8. return to Draft only through an authorized revision process.

13.7 Bank reconciliation procedure

1. Select the cash/bank account and statement date.
2. enter statement and book balance;
3. enter outstanding deposits and payments;
4. enter documented adjustments;
5. review the calculated adjusted statement balance;
6. investigate until difference is exactly zero;
7. obtain independent review where possible;
8. approve reconciliation;
9. retain the statement and reconciliation evidence.

13.8 Accounting health review

Investigate:

- unbalanced draft journals;
- absence of an open fiscal period;
- draft/unapproved reconciliations;
- successful donations without source journals;
- approved/paid expenses without source journals;
- unexpected clearing balances;
- cash-to-ledger differences;
- trial-balance inequality.

14 Reports, audit, and exports

14.1 Report use

Select the appropriate date range and report area. Check whether totals are:

- personal or organization-wide;
- status-filtered;
- cash-based or journal-based;
- limited by fund;
- based on creation date, transaction date, or event date.

Report access varies by capability. A successful CSV export is audit logged.

14.2 Audit review

Review actor, time, action, target, and detail. Focus on:

- role changes;
- member activation;
- event publication and registration changes;
- donation status and reconciliation;
- accounting posting, reversal, period, budget, and reconciliation actions;
- campaign sends;
- integration changes;
- CMS changes and deletes;
- exports.

Audit logs are not a substitute for hosting, provider, database, and security logs.

14.3 Export handling

- Export only what is necessary.
- Store files in an approved encrypted location.
- Do not email sensitive exports casually.
- restrict access to the same or narrower audience as the platform view;
- delete working copies when no longer needed;
- retain official reports according to OIF policy.

15 Security administration

15.1 Application security controls

When debug is disabled, the settings enable:

- HTTPS redirect by default;
- secure session and CSRF cookies;
- HSTS;
- content-type sniffing protection;
- proxy HTTPS awareness;
- frame denial;
- trusted-origin configuration.

These controls depend on correct deployment and proxy settings.

15.2 Credential handling

- Keep `.env` outside source control.
- Use separate test and production credentials.
- restrict CMS integration configuration;
- rotate exposed or departed-user credentials;
- avoid credential reuse;
- never include secrets in logs, audit detail, support tickets, or manuals.

15.3 Data minimization

Collect only needed participant information. Accessibility, dietary, contact, application, mentorship, donation, and financial data require particular care. Do not retain exports merely because storage is available.

15.4 Security incident checklist

1. Identify and contain.
2. preserve evidence;
3. disable affected access;
4. rotate credentials;
5. assess records and integrations affected;
6. restore trusted configuration/data;
7. notify internal owners and external parties as required;
8. document the incident;
9. implement corrective action;
10. review access and monitoring.

16 Backup, recovery, and continuity

16.1 Backup scope

Back up:

- the production database;
- uploaded media;
- environment and deployment configuration through a secure process;
- approved financial exports and reconciliation evidence;
- any external provider configuration required for recovery.

Static source files can be rebuilt from the repository; user media and the database cannot.

16.2 Backup controls

- Encrypt backups.
- restrict backup access;
- keep more than one recovery point;
- store at least one copy separately from the live host;
- monitor completion;
- test restoration;
- document retention and deletion.

16.3 Recovery order

1. Establish a clean, supported runtime.
2. restore application source at the intended version;
3. restore environment configuration and secrets;
4. restore the database;
5. restore media;
6. run migrations appropriate to the source version;
7. collect static files;
8. run checks;
9. test authentication, public pages, uploads, email, Paystack, and dashboard;
10. reconcile transactions that occurred around the outage.

17 Release and deployment runbook

17.1 Before deployment

```
Back up database and media
Review the change and migration plan
Run Django checks
Check for missing migrations
Run the full test suite
Confirm production configuration
Plan rollback/recovery
```

17.2 Standard commands

```
python manage.py check --deploy
python manage.py makemigrations --check --dry-run
python manage.py test
python manage.py migrate
python manage.py collectstatic --noinput
```

17.3 After deployment

Smoke-test:

- homepage and core public pages;
- static images/styles and uploaded media;
- login, logout, and password reset;
- dashboard role access;
- one non-destructive CMS view;
- event detail and registration;
- email delivery;
- Paystack configuration/status without creating an unintended live charge;
- reports and accounting;
- error logs.

17.4 Rollback principle

Code rollback does not automatically reverse a database migration. Use a planned, tested recovery procedure. Never use destructive version-control or database commands against production without an explicit target, backup, and authorization.

18 Administrator troubleshooting matrix

Symptom	First checks	Escalate when
User cannot sign in	Active status, username, password reset, allowed host/cookies	Multiple users affected or security incident suspected
New member cannot sign in	This is expected until approved — check Members → Pending approval, then activate	Member appears already active but still cannot sign in
Function missing	Role, capability, personal vs organization scope	Mapping does not match approved policy
Public record missing	Published/active flag, date, slug, related record	Database or template error
Upload fails	File size/type, media path, storage permission	Storage unavailable or data at risk
Email missing	Address, backend, SMTP, spam/provider log	Repeated or organization-wide failure
Event registration rejected	Published/open state, capacity, duplicate record, form fields	Valid users consistently fail
Donation Pending	Paystack enabled, reference, verify, webhook	Provider mismatch or settlement dispute
Donation incorrectly Successful	Evidence, demo mode, provider record, source journal	Refund/reversal or security issue
Campaign failures	Channel enabled, credential, quota, destination	Broad failure, duplication, or provider incident
Cash balance wrong	Opening balance, Posted movements, transfers, date filters	Evidence and calculated balance cannot reconcile
Journal will not post	Balance, posting account, open period, source uniqueness	Correction requires policy/accounting judgment
Reconciliation will not approve	Difference calculation and evidence	Difference cannot be resolved
Dashboard error	Logs, database, recent release, affected role/path	500 error, data loss risk, or broad outage

19 Administrator checklists

19.1 New member approval checklist

- ☐ Account appears legitimate (name, email, no obvious spam pattern)
- ☐ No duplicate account already exists for this person
- ☐ Reviewed under Members → Pending approval
- ☐ Active account box checked and saved
- ☐ Membership-accepted email delivery not showing as failed

19.2 New event checklist

- ☐ Approved title and programme
- ☐ Accurate date/time and time zone
- ☐ Venue and/or online link
- ☐ Capacity
- ☐ Accessibility and contact information
- ☐ Flyer and content rights
- ☐ Public page verified
- ☐ Registration tested
- ☐ Calendar file tested
- ☐ Communications owner identified

19.3 Campaign checklist

- ☐ Authorized purpose
- ☐ Correct audience and consent basis
- ☐ Correct channel
- ☐ Proofread subject/body
- ☐ Placeholders tested
- ☐ Links and dates tested
- ☐ Provider ready
- ☐ Approval obtained
- ☐ Send initiated once
- ☐ Delivery report reviewed

19.4 Donation reconciliation checklist

- ☐ Provider reference matches
- ☐ Amount matches
- ☐ Currency matches
- ☐ Metadata/record matches
- ☐ Settlement evidence exists
- ☐ Receipt status reviewed
- ☐ Source journal exists
- ☐ Clearing/bank treatment reviewed
- ☐ Exceptions documented

19.5 Fiscal-period close checklist

- ☐ All transactions recorded
- ☐ Draft journals resolved
- ☐ Source-journal exceptions resolved
- ☐ Bank/cash reconciliations complete
- ☐ Trial balance balances
- ☐ Budget variance reviewed
- ☐ Statements approved
- ☐ Backup completed

- ☐ Close authorized
- ☐ Next period created

19.6 Staff offboarding checklist

- ☐ Account deactivated
- ☐ Staff/superuser access removed
- ☐ Responsibilities reassigned
- ☐ Provider secrets rotated where necessary
- ☐ Local/exported data recovered or deleted
- ☐ Historical attribution preserved
- ☐ Offboarding recorded

19.7 Production readiness checklist

- ☐ Debug disabled
- ☐ Strong secret key
- ☐ Hosts and CSRF origins correct
- ☐ HTTPS/security headers verified
- ☐ Production database configured
- ☐ SMTP tested
- ☐ Paystack configured
- ☐ Demo mode disabled
- ☐ Messaging providers tested or disabled
- ☐ Persistent media and backups configured
- ☐ Policies and contact details finalized
- ☐ Demo content removed
- ☐ Checks, migrations, tests, and static collection complete
- ☐ Administrator and role access reviewed
- ☐ Recovery procedure documented and tested

20 Escalation and change control

Escalate to the responsible OIF owner when:

- authorization is missing or disputed;
- a role would expose materially broader data;
- a payment, refund, settlement, or accounting treatment is uncertain;
- legal/privacy wording or consent is uncertain;
- an incident may require notification;
- data could be lost or overwritten;
- a migration or deployment cannot be safely reversed;
- a provider credential may be compromised;
- an operation requires direct database modification.

Direct database edits should be exceptional, backed up, reviewed, recorded, and performed by a qualified maintainer. Changes to capabilities, accounting automation, payment verification, or communications should include tests and an update to this handbook.

21 Module reference

The following section is incorporated from the maintained OIF Platform Module and Operations Manual.

22 OIF Platform Module and Operations Manual

22.1 1. Purpose and audience

This manual explains how the Onesimus Impact Foundation (OIF) platform is organized, what each module does, how the modules exchange information, and how an operator should use the principal workflows.

It is intended for:

- OIF administrators and directors;
- programme, events, communications, partnerships, and finance teams;
- content editors and member-support personnel;
- developers, maintainers, auditors, and deployment operators.

For access rights and instructions for each user role, see [ROLES_MANUAL.md](#).

22.2 2. Platform at a glance

The platform is a server-rendered Django application with one shared database. It combines five business modules:

Module	Main responsibility	Primary users
accounts	Identity, login, profiles, roles, and capabilities	Everyone
pages	Public website and content-managed information	Visitors and content team
engagement	Events, applications, mentorship, enquiries, and newsletter	Visitors, members, programme teams
donations	Giving, Paystack verification, receipts, and donor history	Donors and finance team
dashboard	Operations, reporting, messaging, finance, CMS, and audit	Authenticated users and staff

Shared project services live in [oif_site](#). HTML is in [templates](#), styling is in [static/css/site.css](#), and development uploads are stored in [media](#).

The public website starts at [/](#). The authenticated workspace starts at [/dashboard/](#). Django's technical administration interface is at [/admin/](#) and should normally be used only by a Super Administrator.

22.3 3. Common concepts

22.3.1 3.1 Authentication

Visitors can browse published public content, submit contact and partnership forms, subscribe to the newsletter, register for an event as a guest, and make a donation.

An account is required to:

- maintain a personal profile;
- see personal registrations, applications, mentorship, and donations;
- cancel a member event registration;
- submit an application;
- use any staff capability.

Public signup always creates a [Member](#). Staff roles must be assigned internally. Password-reset email is available from the login screen.

22.3.2 3.2 Authorization

The platform authorizes actions through named capabilities rather than by scattering role-name checks through the code. A role supplies a set of capabilities; views then require the relevant capability.

This creates three practical levels:

1. **Personal access** — authenticated users see their own activity.
2. **Organization read access** — capabilities such as [view_donations](#), [view_message_reports](#), or [view_org_analytics](#) expose organization-wide information.
3. **Operational write access** — capabilities such as [manage_events](#), [manage_donations](#), or [manage_content](#) allow changes.

A missing navigation link is not the security boundary. The server checks capabilities again when a protected URL is requested.

22.3.3 3.3 Status-driven records

Many records follow an explicit lifecycle:

- registration: Registered → Attended or Cancelled;
- application: Pending review → Approved or Not selected;
- donation: Pending → Successful or Failed;
- contact message: New → Read → Resolved;
- partner enquiry: New → In review → Engaged → Closed;
- expense: Draft → Approved → Paid, or Void;
- journal: Draft → Posted → Reversed;
- budget: Draft → Approved → Locked;
- bank reconciliation: Draft → Reconciled;
- campaign: Draft → Processing → Sent, Partially sent, or Failed.

Operators should change status through the dashboard actions instead of editing database records directly. Dashboard actions apply validation, notifications, accounting automation, and audit logging.

22.3.4 3.4 Audit trail

Significant administrative changes create an **AuditLog** entry containing the actor, action, target, detail, and timestamp. Examples include event changes, application decisions, donation reconciliation, member role changes, content changes, campaign sends, integration changes, accounting actions, and exports.

Audit logging is deliberately best-effort: failure to write an audit entry does not break the user's primary operation. Infrastructure monitoring and database backups therefore remain necessary.

22.4 4. Accounts module

22.4.1 4.1 Responsibilities

The accounts module owns:

- the custom **User** model;
- usernames and passwords;
- personal and staff roles;
- role-to-capability mapping;
- signup, login, logout, profile editing, and password reset;
- member avatars, professional information, and public-profile preference.

22.4.2 4.2 User information

A user can hold a name, username, email, phone number, professional title, location, avatar, biography, role, marketing preference, public-profile flag, and Django active/staff flags.

The normal user profile permits changes to:

- first and last name;
- email and phone;
- title and location;
- avatar and biography;
- public-profile preference.

It does not permit a user to change their own role, active status, or staff status.

22.4.3 4.3 Signup and account administration

New public signups:

1. provide a name, username, email, optional phone, and password;
2. must use an email not already assigned to an account;
3. receive the **Member** role;
4. are created **inactive**, pending staff approval, and are not signed in.

Django's authentication backend refuses to authenticate an inactive account, so a new signup cannot sign in — to the dashboard or anywhere else — until a member administrator approves them. This is enforced by the framework itself, not by a separate check in the view layer.

At signup, the platform sends two best-effort notifications: a confirmation to the new member that their account is pending review, and an internal notification to the OIF inbox flagging the account for approval. The login screen shows a specific "pending approval" message (rather than a generic inactive-account error) if someone tries to sign in before approval.

A user with `manage_members` approves a pending account from **Members**:

1. open the pending member's record (a "Members awaiting approval" work-queue entry appears on Overview, and the Members page shows a "Pending approval" total and a `status=pending` filter to list them);
2. review the account for legitimacy before approving;
3. open the Admin tab and check **Active account (approved to sign in)**;
4. save.

Only a user with `manage_users` sees the role and Django staff fields. When an Applicant becomes a Member, or an inactive account is activated, the platform sends a membership-accepted email containing the sign-in link — this is the first email that includes one, since the initial pending-approval email deliberately does not.

Staff-created accounts (added directly through the Members admin form rather than public self-signup) are not subject to this gate — the administrator creating the record controls `is_active` directly at creation time.

22.4.4 4.4 Passwords and staff safety

- Passwords are never sent in account notification emails.
- Use the password-reset flow rather than asking users to disclose passwords.
- Grant Django `is_staff` only when access to `/admin/` is genuinely required.
- A platform role and Django staff status are separate controls.
- Deactivating a user blocks authentication without deleting their history.

22.5 5. Pages and public CMS module

22.5.1 5.1 Public pages

The public site provides:

- Home;
- About;
- Leadership;
- Speakers;
- Programs and programme detail;
- Event detail;
- Impact;
- Get Involved;
- Donate;
- Gallery;
- Contact;
- Privacy, Terms, and Donation policies;
- sitemap and `robots.txt`;
- custom 404 and 500 pages.

Only published or active records are intended to appear publicly.

22.5.2 5.2 Site branding

`SiteBranding` is a singleton organization profile used by public and dashboard templates. It controls:

- organization and short names;
- tagline, founded year, and location;
- contact email, phone, and website;
- footer summary;
- full logo, compact logo, and favicon;
- Instagram, LinkedIn, X, YouTube, and Facebook links;
- heading and body Google fonts.

Because branding is global, verify changes on both the public site and dashboard. Uploaded logo variants should be optimized for the web and remain legible on light and dark backgrounds.

22.5.3 5.3 Programs and resources

Programs represent the supported OIF wings:

- The Forge;
- The Hadassah Project;
- Humanitarian Wing;
- Virtual Conferences;
- Mentorship Programme.

Each programme has a tagline, headline, description, image, accent, display order, and active flag. The wing is unique, so a second record for the same wing cannot be created.

Resources belong to a programme. A resource may link to an uploaded file or an external URL. Operators should supply at least one usable destination and test the public link after saving.

A programme's detail page shows every published Gallery image associated with that programme (not only the first one) in a photo gallery with the same click-to-expand lightbox used on the main Gallery page, and shows a photo on each "explore more" related-programme card. Both fall back to a muted placeholder until real photos are uploaded through Programs or Gallery.

22.5.4 5.4 Speakers and leadership

Speakers have a name, role, photograph, featured flag, and display order. Leadership records have a name, position, title, credentials, biography, photograph, and display order.

The available leadership positions are Global Lead, Executive Director, Director, and Company Secretary. Leadership CMS records are public content; they do not automatically create user accounts or grant matching roles.

22.5.5 5.5 Impact content and gallery

Site statistics are short label/value/suffix records used for public metrics. Testimonials include source, attribution, quotation, photo, publication flag, and display order. Sources are Conference, Mentorship, and Humanitarian Outreach.

Gallery images can be associated with a programme and have a caption, publication flag, and order. The public gallery includes a lightbox. Programme association also enables relevant images to appear on event pages.

22.5.6 5.6 Policies

The CMS manages Privacy Policy, Terms of Use, and Donation Policy records. All three are seeded automatically by migration with placeholder text, so `/policy/privacy/`, `/policy/terms/`, and `/policy/donation/` — and the footer links to them — always resolve, even on a freshly migrated database with no other content added. `is_placeholder` identifies unfinished legal text. Before production launch:

- replace placeholder copy with approved text;
- clear the placeholder flag;
- verify headings, links, and contact details;
- have the final policy reviewed by the appropriate adviser.

22.5.7 5.7 Content operating procedure

For a normal content update:

1. open the relevant Content Library screen;
2. create or edit the record;
3. upload an appropriately sized asset if needed;
4. set display order and publication/active flags;
5. save and inspect the public page at desktop and mobile widths;
6. check that links and files open;
7. use the audit trail when confirmation of the change is required.

Deletion is permanent at the application level. Avoid deleting records that should simply be hidden; use active or published flags when available.

22.5.8 5.8 Page imagery and page copy

Beyond the record-based content families above (programmes, speakers, gallery, and so on), two singleton CMS sections give administrators direct control over every hero photo and every headline/paragraph "writeup" on the public site that is not already sourced from a program, speaker, leader, testimonial, gallery, or event record.

Page imagery (Site CMS → Page Photos) manages the hero, portrait, and side-panel photo used on every major public page: Home, About, Programs (three hero photos), Impact, Leadership, Speakers, Gallery, Donate, Contact, Get Involved (three portraits), and the side photo on the Give, Apply, Login/password-reset, and Create-account pages — 19 image slots in total.

Page copy (Site CMS → Page Copy) manages the hero and section eyebrow/headline/paragraph writeup on the same set of pages, plus the site-wide footer call-to-action — 85 text fields, grouped by page in the dashboard editing form so the section stays usable at that scale.

Both sections behave the same way:

- every field is optional;
- until a field is filled in, the public page falls back to its original built-in default — the public site cannot go blank or break while these are empty;
- the Site CMS overview shows how many of each are customized versus using the default, so an administrator can see coverage at a glance;
- changes take effect immediately on save, with no publish/approval step.

This is the mechanism to use for rebranding a headline, swapping a stock hero photo for real OIF photography, or adjusting marketing copy without a code change or deployment.

22.6 6. Events module

22.6.1 6.1 Event content

An event can be a Conference, Mentorship Cohort, Humanitarian Outreach, or Workshop/Gathering. It may contain:

- title and automatically generated unique slug;
- associated programme and theme;
- summary and full description;
- intended audience, outcomes, agenda, and speaker list;
- preparation and accessibility information;
- flyer;
- start date/time;
- location, venue address, and online URL;
- virtual/in-person indicator;
- capacity, where zero means unlimited;
- registration note and contact email;
- publication and registration-open controls.

Published controls public visibility. Registration-open controls whether the registration form accepts submissions. These flags are independent.

22.6.2 6.2 Public event experience

A published event page displays logistics, programme context, related media, registration information, related events, social sharing, Google Calendar, and an Apple/standard `.ics` download. Calendar entries use a two-hour event duration because the data model currently stores only a start time.

For an upcoming event, the page also shows a live countdown to the start time, a registration status badge (“Registration open”, “Filling fast”, “Event full”, or “Registration closed” — computed from capacity, active registration count, and the registration-open flag), and a seat-fill progress meter next to the capacity figure and again directly above the registration form. These are computed from existing event and registration data; no extra administrator input is required beyond capacity and registration-open state being accurate.

22.6.3 6.3 Registration

Both members and guests can register. Guests must provide a name and email. Members use account identity and may provide organization, role/title, attendance preference, accessibility needs, dietary needs, and a question.

The platform prevents duplicate member/event and guest-email/event records. Submitting again updates the existing details. Re-registering a cancelled record restores it to Registered. Capacity counts registered and attended records, excluding cancellations.

The registration confirmation email includes the event date, location, attendance mode, event URL, and calendar URL.

22.6.4 6.4 Event administration

Users with `manage_events` can:

- create and edit events;
- publish/unpublish;
- open/close registration;
- inspect upcoming and archived events;
- see capacity, fill rate, attendance rate, role mix, and registration timeline;
- change a registration to Registered, Attended, or Cancelled;
- initiate an event-recipient campaign if they also have `send_messages`.

Before opening registration, verify capacity, contact email, venue/online link, accessibility text, and public visibility. After an event, mark attendance so reporting reflects actual participation. The registration data model also contains check-in time and administrative notes, but the current event dashboard action edits status only.

22.7 7. Applications and mentorship module

22.7.1 7.1 Applications

Authenticated users can apply as:

- Mentor;
- Volunteer;
- Mentee;
- Speaker.

An application records the type, area of interest, motivation, status, reviewer, and review time. Submission sends a confirmation to the applicant and an internal notification.

A reviewer with `manage_applications` may approve or reject. The applicant is notified when the decision changes. Approval automatically promotes a Member or Applicant to Mentor for a mentor application, or Volunteer for a volunteer application. Mentee and Speaker approval do not automatically change roles.

22.7.2 7.2 Mentorship

An enrollment connects a mentee to an optional mentor and programme. It records the cohort, current phase, completed sessions, and total sessions.

Phases are:

- Phase 1 — Recorded Sessions;
- Phase 2 — Live Sessions;
- Completed.

Progress is calculated as completed sessions divided by total sessions. The default plan is 12 sessions.

Users with `manage_mentorship` can create and update all enrollments. Mentors with `view_mentees` see enrollments assigned to them. A member sees their own enrollment. Assignment viewers can see their own mentorship assignment on the overview.

Recommended process:

1. review and approve the relevant application;
2. create the enrollment;
3. choose the mentee, mentor, programme, and cohort;
4. update session counts regularly;
5. advance the phase only when its requirements are complete;
6. set Completed at the end of the programme.

22.8 8. Enquiries and newsletter module

22.8.1 8.1 Contact messages

The public contact form creates a message with New status and sends best-effort notifications to the internal inbox and the sender. A hidden honeypot field rejects basic automated spam.

Users with `manage_contact` can move messages between New, Read, and Resolved. The last operator is stored as `handled_by`.

The Contact page also shows an embedded location map built from the organization's location text (no separate map configuration is required), a response-time expectation next to the send button, and a dedicated hero photo — all editable through Page Copy and Page Photos (5.8) without a code change.

22.8.2 8.2 Partnership enquiries

The Get Involved flow accepts Partner, Sponsor, and Institutional Donor enquiries. The partnerships lifecycle is:

New → In review → Engaged → Closed.

The Enquiries page may be visible to contact managers, but changing partnership status specifically requires `manage_partners`.

22.8.3 8.3 Newsletter

Newsletter signup is public. Email is unique. Submitting an existing address reactivates the subscription and updates the name. Active subscribers can be selected as a Messaging audience.

Consent must be respected. General member campaigns should use the Marketing opt-ins audience when the communication is promotional rather than necessary for service delivery.

22.9 9. Donations module

22.9.1 9.1 Donation information

A donation records:

- optional linked user;
- donor name and email;
- amount and currency;
- Mobile Money, Card, or Bank Transfer channel;
- Pending, Successful, or Failed status;
- generated transaction reference;
- campaign, donor note, and recurring intention;
- whether a receipt was sent.

The recurring flag records intent; it does not create an automated Paystack subscription.

22.9.2 9.2 Online payment flow

The normal Paystack flow is:

1. the donor submits the form;
2. the application creates a Pending donation with an `0IF-...` reference;
3. Paystack returns an authorization URL;
4. the donor completes payment;
5. the callback verifies the transaction;
6. reference, amount, currency, and optional metadata donation ID must match;
7. the donation becomes Successful;
8. a receipt is attempted once;
9. an idempotent accounting journal is attempted.

The signed webhook performs the same reconciliation when the browser does not return to the callback. Webhooks accept only a valid HMAC signature and `charge.success` events.

22.9.3 9.3 Demo and failure behavior

When Paystack is unavailable:

- if demo mode is explicitly enabled, the donation is recorded as Successful;
- if demo mode is disabled, online giving fails closed and the donation becomes Failed.

Demo mode must be disabled in production. Bank transfers require an operational offline verification process; selecting the Bank channel alone is not evidence that funds arrived.

22.9.4 9.4 Privacy and access

A donation status page is visible only when:

- its reference is remembered in the donor's current session;
- it belongs to the authenticated user; or
- the user has organization-wide donation access.

Finance readers can inspect organization-wide donations. Donation managers can verify with Paystack, change status, and reconcile up to 100 pending referenced donations per bulk run.

Manual success should be used only after independent evidence of settlement. Changing a Successful donation back to another state does not automatically reverse its accounting journal.

22.10 10. Messaging module

22.10.1 10.1 Channels and providers

Campaigns support Email, SMS, WhatsApp, or all three. Integrations include:

- Django email backend;
- Arkesel SMS;
- Hubtel SMS;
- WhatsApp Cloud API.

Provider secrets are stored in singleton integration settings when CMS configuration is selected. Secret fields preserve the current value when an empty edit form is submitted.

22.10.2 10.2 Audiences

Available audiences are:

- all active members/accounts;
- users with marketing consent;
- users in a selected role;
- non-cancelled registrants for a selected event, including guests;
- active newsletter subscribers;
- custom recipients, one email or phone per line.

Supported message placeholders are `{name}`, `{first_name}`, `{email}`, `{phone}`, and `{org_name}`. An invalid or unknown placeholder causes the original text to be used, so preview content carefully.

22.10.3 10.3 Campaign lifecycle and delivery

A sender can create a reusable template or campaign, save it as Draft, send it immediately, or resend it from the detail page. Each channel/recipient pair creates a delivery record:

- Sent: provider accepted the message;
- Failed: provider/backend raised an error;
- Skipped: the recipient lacked an address for that channel.

Campaign status becomes Sent, Partially sent, or Failed based on results. Delivery reporting records provider name, reference, error, and send time.

Campaign delivery runs synchronously in the web request. For a large audience:

- split campaigns into manageable groups;
- avoid repeated clicks while the request is running;
- inspect delivery results before retrying;
- understand that resending creates another set of deliveries and can duplicate messages to successful recipients.

Only integration administrators should change credentials. Campaign senders should report configuration failures rather than attempting to obtain secrets.

22.11 11. Dashboard and reporting module

22.11.1 11.1 Overview

Every authenticated user has an Overview. It includes personal registration, giving, and application counts, upcoming published events, and role-dependent widgets.

Organization analytics, work queues, mentee counts, mentorship assignments, and finance summaries appear only when the user's capabilities permit them.

22.11.2 11.2 Reports

The Reports area builds sections independently according to access:

- executive;
- finance;
- events;
- people;
- content;
- engagement.

Reports accept a date range and support CSV export. If the start date is after the end date, the application swaps them. Default reporting covers the previous 365 days.

CSV export is an operational data extract. Store it securely, share it only with authorized recipients, and delete unnecessary copies.

22.11.3 11.3 Analytics

ECharts renders donation trends and channels, member growth, registrations by programme, application status, event attendance, member engagement, campaign results, and finance charts.

The `/dashboard/api/analytics/` endpoint is authenticated and filters panels by capability. Every user receives personal giving history; organization panels require organization analytics access.

22.12 12. Finance and accounting module

22.12.1 12.1 Operational finance

The Finance & Accounting workspace contains donations, expenses, cash accounts, and cash movements.

Expense categories include programmes, events, mentorship, outreach, operations, media, technology, administration, and other. Approved and Paid expenses are recognized as posted operational expenditure. Supporting receipts can be uploaded.

Cash accounts represent cash on hand, bank accounts, mobile-money wallets, payment gateways, savings/reserves, or other accounts. They include opening and statement balances, reconciliation date, active state, and controls for accepting donations or paying expenses.

Cash movements are Money in, Money out, or Transfer. Only Posted movements affect calculated cash balances. Transfers require a different destination account in the same currency.

22.12.2 12.2 Double-entry ledger

The Statements & Ledger area contains:

- ledger accounts;
- funds;
- fiscal periods;
- journals and journal lines;

- budgets and budget lines;
- bank reconciliations;
- financial statements and accounting health checks.

Default accounts are created when accounting is first opened:

Code	Account
1000	Cash and bank
1100	Paystack clearing
1200	Accounts receivable
2000	Accounts payable
3000	Unrestricted net assets
3100	Restricted net assets
4000	Donation income
4100	Grant and partnership income
5000-5400	Programme, event, operations, administration, and charge expenses

A General Fund is also created.

22.12.3 12.3 Funds and fiscal periods

Funds may be unrestricted, temporarily restricted, or permanently restricted. Record donor and restriction details when applicable.

Fiscal periods cannot overlap. A journal cannot be posted into a Closed period. Closing a period therefore acts as a posting lock; reopen only under an authorized correction procedure.

22.12.4 12.4 Journals

A journal is valid for posting when:

- it is Draft;
- it has at least one line;
- total debits equal total credits and are greater than zero;
- each line uses either debit or credit, not both;
- amounts are non-negative;
- accounts permit direct posting;
- the fiscal period is open.

Posted journals are corrected through reversal. Reversal creates and posts a new entry with debit/credit sides exchanged, then marks the original Reversed. Do not delete or directly edit posted journals.

Successful donations automatically debit Paystack clearing and credit Donation income. Approved expenses debit the mapped expense account and credit Cash, or Accounts payable if not Paid. Source uniqueness prevents a second automated journal for the same donation or expense.

22.12.5 12.5 Budgets

A budget belongs to a fiscal period and optional fund. Each account may appear only once in a budget. Amounts cannot be negative. The workflow is Draft → Approved → Locked, with an available return-to-Draft action for authorized correction.

Variance reporting compares income and expense actuals with budget lines.

22.12.6 12.6 Bank reconciliation

A reconciliation compares:

$\text{book balance with statement balance} + \text{outstanding deposits} - \text{outstanding payments} + \text{adjustments}$.

Approval is blocked unless the difference is exactly 0.00. Approval updates the cash account's statement balance and last-reconciled date.

22.12.7 12.7 Statements and controls

The platform calculates:

- trial balance;
- income and expenditure;
- assets, liabilities, and net assets;
- surplus/deficit;
- budget versus actual;

- operating margin and current ratio in management reporting;
- accounting exceptions such as unbalanced drafts, unreconciled accounts, and successful donations or posted expenses without source journals.

The finance team should review accounting health after reconciliation and before closing a reporting period.

22.13 13. Notifications

Transactional email is used for:

- account registration and membership acceptance;
- event registration;
- application receipt and decisions;
- contact and partnership receipt;
- donation receipts;
- password resets.

These emails are best-effort. A mail failure does not roll back the triggering web operation. The console backend prints email locally; production requires a working SMTP backend. Operators should monitor mail delivery independently.

22.14 14. Configuration and integrations

Application configuration is read from environment variables. Integration administrators can optionally manage messaging and Paystack values through the dashboard.

Paystack uses either:

- environment values; or
- CMS configuration when `paystack_use_cms_configuration` is enabled.

Required production controls include:

- `DJANGO_DEBUG=False`;
- a strong `DJANGO_SECRET_KEY`;
- correct allowed hosts and CSRF origins;
- production database credentials;
- SMTP credentials;
- Paystack live/test credentials appropriate to the environment;
- `PAYSTACK_DEMO_MODE=False`;
- persistent media storage and backups.

Never place production credentials in source control, screenshots, audit details, campaign text, or support messages.

22.15 15. Media and file handling

Uploads include branding, avatars, events, programmes, resources, speakers, leadership, testimonials, gallery images, expenses, and cash-movement attachments.

The configured request/upload memory limit is 5 MB; larger uploads may stream to a temporary file, but operators should still optimize media. Uploaded files are not a substitute for a document archive. Production deployments require:

- persistent media storage;
- access restrictions appropriate to financial attachments;
- malware/content checking as operational policy;
- backups and restore testing;
- retention and deletion procedures.

22.16 16. Maintenance and deployment

Supported deployment paths include PythonAnywhere and a Docker/Gunicorn image. The application supports MySQL, database URLs, and SQLite fallback.

Normal release checks are:

```
python manage.py check --deploy
python manage.py makemigrations --check --dry-run
python manage.py test
python manage.py migrate
python manage.py collectstatic --noinput
```

The repository also provides `python manage.py seed_demo` for disposable local sample data. Never run it against production.

Before a release:

1. back up the database and media;
2. review configuration and demo-mode flags;
3. run checks and tests;
4. apply migrations;
5. collect static files;
6. perform public, login, dashboard, email, and payment smoke tests;
7. review error logs after deployment.

22.17 17. Troubleshooting guide

22.17.1 A newly registered member cannot sign in

This is expected: new self-signups are created inactive pending approval, and Django refuses to authenticate an inactive account. Confirm the account exists under Members, filter by “Pending approval”, open the record, and check **Active account (approved to sign in)** on the Admin tab. The member receives a membership-accepted email with the sign-in link once approved. This does not apply to accounts created directly by an administrator through the Members form, which are active immediately unless the administrator leaves the Active account box unchecked.

22.17.2 A user cannot see a dashboard function

1. Confirm they are logged in and active.
2. Check their assigned role.
3. Check whether that role has the required capability in the role manual.
4. Distinguish `manage_members` from `manage_users`.
5. Do not solve the issue by granting Super Administrator unless full access is intended.

22.17.3 An event is missing publicly

Check `is_published`, start date, programme state, and the URL slug. If registration is missing but the page is visible, check `registration_open` and capacity.

22.17.4 A Paystack donation remains Pending

1. Confirm Paystack is enabled and credentials are for the correct environment.
2. Open the donation and run Verify.
3. Check reference, amount, currency, and metadata matching.
4. Run bulk reconciliation if several callbacks were missed.
5. Inspect webhook URL and signature-secret configuration.
6. Never mark Successful merely to clear the queue without settlement evidence.

22.17.5 A receipt or notification was not received

Check the stored recipient address, email backend, SMTP credentials, provider logs, spam filtering, and application logs. Remember that notification failure does not undo the underlying registration, application, or donation.

22.17.6 A campaign has failures

Inspect individual delivery errors. Check channel enablement, provider credentials, phone formatting, missing addresses, sender ID, and provider quota. Retry deliberately because resend can duplicate prior successes.

22.17.7 Accounting will not post

Check that the journal balances above zero, lines use valid posting accounts, the period is open, and no source journal already exists. For reconciliation, the difference must be exactly zero.

22.17.8 Cash and ledger balances differ

Cash movements and general-ledger journals are related operational systems but are not automatically identical in every workflow. Confirm movement status, opening balances, transfer destinations, source journals, clearing entries, and the selected reporting period/fund.

22.18 18. Data stewardship

The platform stores personal, engagement, communications, and financial data. Operators must:

- grant least-privilege roles;
- use organization-wide exports only for authorized purposes;
- avoid copying sensitive data into unsecured files;

- respect marketing consent;
- keep payment credentials and financial attachments confidential;
- deactivate accounts when access is no longer required;
- preserve audit and accounting history;
- follow OIF retention, privacy, incident-response, and backup policies. # OIF Platform Roles and Access Manual

22.19 1. Purpose

This manual describes every OIF platform role, its implemented access, normal responsibilities, boundaries, and recommended assignment criteria.

It is the companion to `MODULES_MANUAL.md`, which explains the platform's functional modules and workflows.

22.20 2. How role-based access works

Each account has one role. The role grants named capabilities. Protected views check capabilities, not the role label. A Django superuser bypasses the normal role mapping and receives every capability.

All authenticated roles receive two baseline capabilities:

- `register_events`;
- `give_donations`.

They can also use the personal dashboard, profile, personal events, applications, mentorship information relevant to them, personal donation history, and personal analytics where implemented.

Role assignment should follow least privilege: give a user the narrowest role that supports their current work.

22.21 3. Capability glossary

Capability	What it permits
<code>view_org_analytics</code>	Organization summary and broad executive/event/people/content/engagement reporting
<code>manage_users</code>	Change platform roles and Django staff status; full user administration authority
<code>manage_members</code>	Search, inspect, activate, and update member operational profiles
<code>manage_events</code>	Create/edit events and administer registrations/attendance
<code>manage_donations</code>	Verify/reconcile donations and manage finance/accounting records
<code>view_donations</code>	Read organization-wide donations, finance, ledger, and statements
<code>manage_applications</code>	Review and decide applications
<code>manage_mentorship</code>	Create and update mentorship enrollments
<code>view_mentees</code>	See mentorships assigned to the current mentor
<code>view_assignments</code>	See personal assignments/mentorship context
<code>manage_content</code>	Manage programmes, resources, speakers, leadership, branding, stats, testimonials, gallery, and policies
<code>manage_media</code>	Media-management authority in the role model; current CMS routes principally require <code>manage_content</code>
<code>manage_speakers</code>	Speaker-management authority in the role model; current speaker routes principally require <code>manage_content</code>
<code>manage_testimonials</code>	Testimonial-management authority in the role model; current CMS routes principally require <code>manage_content</code>
<code>manage_contact</code>	Read and process contact enquiries and view the Enquiries workspace
<code>manage_partners</code>	Change partnership enquiry status
<code>view_partners</code>	Partnership/reporting visibility without status-changing authority
<code>approve_content</code>	Content-approval authority represented in the role model; current CMS does not implement a separate approval state
<code>configure_integrations</code>	Edit SMS, WhatsApp, email enablement, and Paystack CMS configuration
<code>send_messages</code>	Create templates/campaigns and initiate delivery

Capability	What it permits
view_message_reports	View campaigns and per-recipient delivery reporting
view_audit	View the administrative audit trail

The three media/speaker/testimonial capabilities and `approve_content` express policy intent, but current content URLs are gated by `manage_content`. They should not be interpreted as standalone access to those screens until route guards are separated.

22.22 4. Role capability matrix

✓ means the role receives the capability. Baseline event registration and giving are omitted because every role receives them.

Role	Analytics	Members	Events	Donations	Applications	Mentorship	Content	Enquiries/Partners	Me
Super Administrator	Full	Users + members	Manage	Manage + view	Manage	Manage + view	Full	Full	Sei rep
Global Lead	View	—	—	View	—	—	Approve policy only	View partners	Rej
Executive Director	View	Manage	Manage	View	Manage	Manage + view	Manage + approve	Contact + partner view	Sei rep
Director / Staff	View	Manage	Manage	View	Manage	Manage + view	Manage + approve	Contact + partner view	Sei rep
Director of Programmes	View	—	Manage	—	—	Manage + view	Manage/media	—	Sei rep
Director of Operations & Volunteer Engagement	View	Manage	—	—	Manage	Assignment + mentee view	—	Contact	—
Director of Communications, Media & Digital	—	—	—	—	—	—	Manage/media/speakers/testimonials	—	Sei rep
Director of Partnerships & Resource Mobilisation	View	—	—	View	—	—	—	Contact + manage/view partners	Sei rep
Finance / Donations Manager	—	—	—	Manage + view	—	—	—	—	—
Content Editor	—	—	—	—	—	—	Manage/media/speakers/testimonials	—	Sei rep
Event Manager	—	—	Manage	—	—	—	—	—	Sei rep
Mentor	—	—	—	—	—	Assigned mentees + assignments	—	—	—
Volunteer	—	—	—	—	—	Personal assignments	—	—	—
Applicant	—	—	—	—	Personal only	Personal only	—	—	—
Donor	—	—	—	Personal only	Personal only	Personal only	—	—	—
Member	—	—	—	Personal only	Personal only	Personal only	—	—	—

22.23 5. Shared access for every authenticated role

Every authenticated user can normally:

- open Overview;
- edit their profile and avatar;
- see upcoming published events;
- register for events and manage their own registration;
- cancel their own registration;

- submit Mentor, Volunteer, Mentee, or Speaker applications;
- see their own application statuses;
- see mentorship information in which they are the mentee;
- make donations;
- see donations linked to their account;
- see personal giving analytics;
- log out and use password reset.

The Events, Donations, Applications, and Mentorship navigation items are therefore visible even to public-facing roles. Their contents adapt to the current user.

22.24 6. Super Administrator

22.24.1 Intended user

The trusted technical/business owner responsible for the whole platform. Assignment should be rare and reviewed regularly.

22.24.2 Access

The role receives every capability, including:

- role and Django staff administration;
- member, event, donation, application, mentorship, content, enquiry, partner, messaging, integration, and accounting management;
- all organization reporting;
- audit trail;
- Django Admin.

22.24.3 Normal responsibilities

- create and deactivate staff access;
- assign and review roles;
- maintain production integrations and security configuration;
- resolve cross-module incidents;
- review audit and accounting exceptions;
- supervise backups, releases, and access reviews;
- intervene where a narrower role cannot complete an authorized task.

22.24.4 Boundaries and cautions

- Do not use this role for routine content or event work.
- Do not share the account.
- Use a unique strong password and organizationally approved MFA where the hosting/authentication environment supports it.
- Integration credentials and role changes are especially sensitive.
- A Django superuser has the same effective capability breadth even if its role field shows another label.

22.25 7. Global Lead

22.25.1 Intended user

Senior governance leadership requiring organization-wide oversight without routine operational editing.

22.25.2 Access

- organization analytics and executive reports;
- organization-wide donation and finance read access;
- partnership reporting visibility;
- messaging performance reports;
- audit trail;
- content-approval capability in the policy model.

22.25.3 Normal responsibilities

- monitor impact, membership, events, giving, and application trends;
- review financial statements and management reports;
- oversee partnerships and communications performance;
- review the audit trail and escalate anomalies;
- provide governance approval outside the system where required.

22.25.4 Boundaries

This role cannot currently edit events, donations, members, campaigns, content, or integrations. `approve_content` does not currently expose a separate approve/reject action in the CMS.

22.26 8. Executive Director

22.26.1 Intended user

The senior operational leader coordinating programmes, people, content, engagement, and reporting.

22.26.2 Access

- organization analytics and reports;
- member management, excluding role/staff changes;
- event and registration management;
- application decisions;
- mentorship management and assigned-mentee visibility;
- organization donation/finance read access;
- content management and policy approval capability;
- contact enquiry processing and partnership visibility;
- campaign sending and messaging reports;
- audit trail.

22.26.3 Normal responsibilities

- supervise cross-functional operational queues;
- manage events and programme delivery;
- review applications and mentorship activity;
- maintain member operational records;
- review finance without altering finance records;
- approve or oversee public content;
- coordinate organization communications;
- monitor audit history.

22.26.4 Boundaries

The Executive Director cannot change user roles, manage accounting/donation status, change partner status, or configure provider credentials.

22.27 9. Director / Staff

22.27.1 Intended user

A broad legacy/general operations role for trusted staff whose work spans several modules.

22.27.2 Access

Very similar to Executive Director:

- analytics and reports;
- members, events, applications, and mentorship;
- donation/finance read access;
- content and contact management;
- partner visibility;
- campaign sending and reporting.

22.27.3 Differences from Executive Director

- no audit-trail access;
- otherwise current capability coverage is broadly operational.

22.27.4 Assignment guidance

Prefer a functional director role when duties are narrow. Use Director / Staff only when broad cross-functional access is genuinely necessary.

22.28 10. Director of Programmes

22.28.1 Intended user

The person responsible for programme design, programme events, mentorship, and programme communications.

22.28.2 Access

- organization analytics;
- event management;
- mentorship management and assigned-mentee visibility;
- content and media management;
- campaign sending and reporting.

22.28.3 Normal responsibilities

- maintain programme information and resources;
- plan and publish programme events;
- monitor registration and attendance;
- create and update mentorship cohorts;
- track mentee progress;
- communicate with programme and event audiences;
- review programme-related analytics.

22.28.4 Boundaries

No member administration, application review, donation/finance access, enquiry/partner processing, integration configuration, or audit trail.

22.29 11. Director of Operations & Volunteer Engagement

22.29.1 Intended user

The operations leader responsible for members, volunteer intake, assignments, and contact follow-up.

22.29.2 Access

- organization analytics;
- member management, excluding role/staff changes;
- application review;
- personal assignment and mentee visibility;
- contact enquiry processing.

22.29.3 Normal responsibilities

- maintain member operational profiles and active status;
- review volunteer and other applications;
- coordinate volunteer/member engagement;
- process general contact enquiries;
- monitor people and engagement reports;
- view assignments relevant to their account.

22.29.4 Boundaries

No event management, organization-wide donations, mentorship administration, content management, partnership status changes, messaging, integrations, or audit trail. Although application approval may automatically promote a Member to Mentor or Volunteer, this role cannot otherwise select arbitrary roles.

22.30 12. Director of Communications, Media & Digital

22.30.1 Intended user

The communications owner for the public site, media library, and outbound campaigns.

22.30.2 Access

- full current content CMS access;
- media, speaker, and testimonial policy capabilities;
- campaign templates and sending;

- campaign and delivery reports.

22.30.3 Normal responsibilities

- maintain brand, public copy, programmes, resources, speakers, leadership, metrics, testimonials, gallery, and policies;
- optimize and publish media;
- create reusable message templates;
- segment appropriate audiences;
- send and monitor email/SMS/WhatsApp campaigns;
- respect consent and correct failed recipient data through proper processes.

22.30.4 Boundaries

No organization analytics, events, members, finance, applications, mentorship, enquiries, integrations, or audit trail. Provider credential changes must be escalated to a Super Administrator.

22.31 13. Director of Partnerships & Resource Mobilisation

22.31.1 Intended user

The leader responsible for partners, sponsors, institutional donors, resource mobilisation, and related communications.

22.31.2 Access

- organization analytics;
- donation/finance read access;
- contact enquiry processing;
- partnership read and status management;
- campaign sending and reporting.

22.31.3 Normal responsibilities

- progress enquiries from New to In review, Engaged, and Closed;
- maintain timely follow-up ownership;
- monitor giving and resource-mobilisation reporting;
- communicate with appropriate member, newsletter, or custom audiences;
- coordinate with Finance on settlement and with Communications on public copy.

22.31.4 Boundaries

Cannot verify donations, alter accounting records, manage members/events/ applications/content, configure integrations, or view the audit trail.

22.32 14. Finance / Donations Manager

22.32.1 Intended user

The finance operator responsible for donations, expenses, cash control, ledger, budgets, reconciliations, and financial exports.

22.32.2 Access

- organization-wide donation records;
- Paystack verification and reconciliation;
- expense, cash account, and cash movement management;
- ledger accounts, funds, fiscal periods, journals, budgets, and bank reconciliations;
- finance reports, statements, accounting health, and CSV export.

22.32.3 Normal responsibilities

- reconcile Pending donations against Paystack;
- verify settlement before manual success;
- maintain receipt and reference evidence;
- record and approve/pay expenses according to OIF policy;
- maintain cash accounts and posted movements;
- ensure journals balance and periods are correct;
- use reversals for posted-entry corrections;
- prepare budgets and reconciliations;
- review unposted-source and reconciliation exceptions;
- close periods under approved procedure.

22.32.4 Boundaries and segregation

- No member, event, application, content, messaging, integration, or audit administration.
- The application currently allows one finance manager to prepare and approve several finance records. OIF policy should require independent evidence and, where staffing allows, a separate reviewer even when the software does not enforce two distinct people.
- Never use demo mode or manual success in production to conceal settlement failure.
- Successful donations reverted to another status and posted expenses reverted to Draft/Void require accounting review; the source journal is not automatically reversed.

22.33 15. Content Editor

22.33.1 Intended user

A staff member performing routine website and campaign-content maintenance.

22.33.2 Access

- the same current CMS routes as the Communications Director;
- media, speaker, and testimonial policy capabilities;
- message template/campaign creation and sending;
- messaging reports.

22.33.3 Normal responsibilities

- update approved public content and assets;
- maintain publication flags and display order;
- check public rendering and links;
- prepare and send authorized communications;
- review delivery results.

22.33.4 Boundaries

No broader analytics or operations access. This role can send campaigns, so it must be limited to trusted editors with audience and consent training. `approve_content` is not granted; use the organization's review procedure before publication.

22.34 16. Event Manager

22.34.1 Intended user

An operator responsible for event setup, registration, attendance, and event-specific communications.

22.34.2 Access

- create/edit/publish events;
- open and close registration;
- manage attendee registration status;
- view event reports;
- create and send campaigns;
- view campaign delivery reports.

22.34.3 Normal responsibilities

- confirm event logistics and capacity;
- publish accurate detail and accessibility information;
- monitor registrations and fill rate;
- keep attendee contact data confidential;
- record attendance after the event;
- message event registrants using the Event audience.

Check-in time and administrative-note fields exist on registration records, but the current event dashboard action changes registration status only.

22.34.4 Boundaries

No general member management, organization analytics, finance, applications, mentorship, CMS library, enquiries, integrations, or audit trail. Editing an event is not the same as managing programme CMS content.

22.35 17. Mentor

22.35.1 Intended user

An approved mentor assigned to one or more mentorship enrollments.

22.35.2 Access

- personal dashboard functions;
- assigned mentee list and phase summary;
- personal assignment/mentorship context.

22.35.3 Normal responsibilities

- use assigned mentee information only for programme delivery;
- monitor the mentorship view;
- report progress or assignment corrections to a mentorship manager;
- maintain appropriate confidentiality and safeguarding practices.

22.35.4 Boundaries

Mentors cannot create/edit enrollment records themselves, browse all members, or access staff operations. Mentorship managers update session counts and phases in the current implementation.

22.36 18. Volunteer

22.36.1 Intended user

An approved volunteer participating in OIF activities.

22.36.2 Access

- personal dashboard functions;
- personal assignment/mentorship context.

22.36.3 Normal responsibilities

- keep profile and contact details current;
- register for relevant events;
- monitor personal applications and assignments;
- follow operational instructions supplied by staff.

22.36.4 Boundaries

No staff management, reporting, or organization-wide data access.

22.37 19. Applicant

22.37.1 Intended user

A prospective participant whose account is awaiting membership or another decision. Public signup creates a Member role directly (not Applicant), so Applicant is normally assigned through an internal intake process or migrated data. Note that a Member created by public signup is separately gated by account activation (section 21) even though its role is already Member — role and active status are independent controls.

22.37.2 Access

- personal profile;
- personal event, application, mentorship, and donation functions;
- baseline registration and giving.

22.37.3 Transition

When an administrator changes Applicant to Member, the system sends a membership-accepted email. Application approval may also promote an Applicant to Mentor or Volunteer when the application type matches.

22.37.4 Boundaries

No organization-wide or staff access.

22.38 20. Donor

22.38.1 Intended user

A public account primarily associated with giving.

22.38.2 Access

- personal profile;
- giving flow and personal donation history;
- personal events, applications, and mentorship information;
- personal giving analytics.

22.38.3 Boundaries

The Donor role does not expose other donors or organization-wide fundraising. Donation records may also be linked by email in member administration, but organization-wide access still requires a staff capability.

22.39 21. Member

22.39.1 Intended user

The standard account created by public signup and the default community role.

22.39.2 Account activation

A Member created through public signup is created **inactive** and cannot sign in until a user with `manage_members` approves the account (Members → open the record → Admin tab → Active account). This is a gate on authentication, not on role — the account already holds the Member role while pending. See MODULES_MANUAL.md section 4.3 for the full workflow. A Member created directly by an administrator through the Members form is active immediately unless the administrator leaves the box unchecked.

22.39.3 Access

- all shared personal functions;
- event registration and cancellation;
- applications;
- personal mentorship;
- giving and donation history;
- profile and public-profile preference.

22.39.4 Progression

A Member may apply as Mentor or Volunteer. Approval automatically changes the role when appropriate. A Mentee or Speaker application is approved without an automatic role change.

22.39.5 Boundaries

No organization-wide data or staff operations.

22.40 22. Choosing the correct role

Use the following decision guide:

Need	Recommended role
Full platform, roles, credentials, and audit	Super Administrator
Governance oversight without editing	Global Lead
Broad senior operations and audit	Executive Director
Broad operations without audit	Director / Staff
Programmes, programme events, mentorship, content	Director of Programmes
Members, applications, volunteers, contact queue	Director of Operations & Volunteer Engagement
Public content, media, and campaigns	Director of Communications, Media & Digital
Partnerships, fundraising visibility, outreach campaigns	Director of Partnerships & Resource Mobilisation
Donations, finance, accounting, reconciliation	Finance / Donations Manager

Need	Recommended role
Routine CMS and campaign work	Content Editor
Events, attendees, and event campaigns	Event Manager
Assigned mentees	Mentor
Personal volunteer assignments	Volunteer
Standard community access	Member
Giving-focused public account	Donor
Pre-membership/prospective account	Applicant

When one person performs multiple functions, choose the narrowest existing role that covers the authorized duties. Do not automatically select Super Administrator. If no role fits, review the capability mapping with a developer and governance owner rather than informally sharing accounts.

22.41 23. Account onboarding procedure

For a staff account:

1. confirm authorization from the appropriate OIF owner;
2. create or identify the individual's account;
3. select the least-privilege role;
4. leave Django `is_staff` off unless `/admin/` is required;
5. verify the email address and active status;
6. have the user set their own password through the secure flow;
7. ask the user to sign in and confirm the expected navigation;
8. provide the relevant sections of this manual;
9. record the approval under OIF's access-control procedure.

Never send a password by email or messaging campaign.

22.41.1 Public self-signup members

A member who registers through the public sign-up form does not go through this procedure directly — their account is created automatically with the Member role, inactive. Approving them is simpler:

1. confirm the account and requester appear legitimate;
2. open the record from Members (filter by "Pending approval");
3. check Active account on the Admin tab and save;
4. no role selection is needed — public signups are always Member.

Use the staff-account procedure above only when creating an account directly (any other role, or a Member account outside the public signup flow).

22.42 24. Role-change procedure

Only `manage_users` can expose role and Django staff fields in the member form. In the current mapping, that means the Super Administrator.

Before changing a role:

1. confirm the request and business owner;
2. compare old and new capabilities;
3. check whether the user has active responsibilities or sensitive exports;
4. apply the role change;
5. verify navigation and a representative protected action;
6. review the audit entry;
7. notify the user of changed responsibilities without sending credentials.

Application approval is a controlled exception: approving a Mentor or Volunteer application can promote a Member or Applicant automatically.

22.43 25. Offboarding and temporary suspension

When access should stop:

1. set `is_active` to false instead of deleting the account;
2. revoke Django staff/superuser access where applicable;
3. rotate any shared external provider credentials the person knew;

4. reassign mentorships, enquiries, events, or operational ownership;
5. preserve the account so audits, journals, reviews, and other historical records retain attribution;
6. follow OIF policy for retained exports and local copies.

For a temporary leave, deactivate and later reactivate. Reactivation may send a membership-accepted email.

22.44 26. Periodic access review

At least quarterly, or according to OIF policy:

- list active accounts by role;
- confirm each staff user's current duties and manager;
- review all Super Administrators and Django staff users;
- remove obsolete broad roles;
- check dormant or departed users;
- review integration access;
- inspect audit entries for role changes and sensitive actions;
- confirm that finance, communications, and member-data access remains justified.

22.45 27. Practical boundaries and known implementation details

- `manage_members` is not `manage_users`; only the latter changes role/staff fields.
- `view_donations` exposes finance and ledger screens, not merely donation totals.
- `manage_donations` includes broad accounting mutation rights.
- `send_messages` can contact large audiences and must be treated as a high-impact permission.
- `view_message_reports` exposes recipient-level delivery information.
- `manage_contact` is required to open Enquiries; `view_partners` alone mainly contributes reporting visibility.
- CMS routes currently use `manage_content` even though narrower media, speakers, and testimonials capabilities exist.
- `approve_content` does not currently enforce a content approval workflow.
- `view_assignments` currently has limited UI expression; it contributes personal assignment/mentorship context rather than a general assignment management module.
- Django `is_staff` controls admin-site eligibility separately from platform capabilities.
- Django superuser status overrides the normal capability mapping.

These details should be rechecked whenever the role mapping, route decorators, or dashboard navigation changes.