Sub Station Router

File: SubStationRouter.odt

1
1
1
1
2
2
2
2
2
3
3
4
4
5
5
5
5
5

Intro

Goal

Create a OpenWRT Sub Station.

The Router is a WLAN Client and contains a WireGuard Server.

On the Switch Network Outputs can be a SubProject

Hardware

TP-Link TL-WDR4300 Ver. 1.7

TP-Link TL-WDR3600 Ver. 1.5

Software

OpenWRT 22.03.5

File: SubStationRouter.odt 6. Sep 2023 21:22

Basic Setup

LuCi

System->System:

Hostname: WDR3600 WDR4300

Timezone:Europe/Berlin

System->Administration

ChangePassword (Without no ssh) (b...k)

Network->Wireless:

Delete all SSID Masters

Add 5Ghz Client

Advanced Setting:DE

Network->Interfaces

->lan

Change Ipv4 Address

Save & Apply (Requires re-connect)

ipconfig /renew

Wireguard

Add Software

Befor Running scripts the Wireguard Software must be installed

System->Software

->Filter: wireguard / Update Lists

Install: luci-app-wireguard

Automatic add installed:

wireguard-tools

kmod-wireguard

luci-i18n-wireguard-en

luci-proto-wireguard

Install: qrencode

Automatic add installed:

libqrencode

Reboot Device

File: SubStationRouter.odt 6. Sep 2023 21:22

Create script from Template:

https://openwrt.org/docs/guide-user/services/vpn/wireguard/automated

Change Defines in Head of script (separate for each device)

```
export interface="192.168.36"
     export interface="192.168.43" # overlapping with lan subnet
     export DDNS="abcd1234abcd1234.myfritz.net"
     export peer IP="51"
     export WG ${LAN} server port="36996"
     export WG_${LAN}_server_port="43996"
     export WG_${LAN}_server_IP="${interface}.2" # from 1 to 2; d'ont overlap router
     export user_1="jisoo"
     export user_2="jennie"
     export user_3="rose"
     export user 4="lisa"
     export user 1="karina"
     export user_2="giselle"
     export user_3="winter"
     export user_4="ningning"
Copy Script into root account
     scp auto_wq_XX_username-id.sh root@192.168.43.1:~
ssh into router
     ssh root@192.168.43.1
Execute in router
     chmod +x auto_wg_XX_username-id.sh
     ./auto_wg_XX_username-id.sh
after script run
Readback Client scripts
     scp -r root@192.168.XX.1:/etc/wireguard/** readbackXX/
     pause ****** XXXXXXXXXXX *********
```

Post Processing

Modify the Peer config rfiles after extraction

[Interface]

Address = X.X.X.X/24 # get Subnet 255.255.255.0 DNS = 192.168.36.1 # change from 2 to 1 for router dns

[Peer]

everything goes through the tunnel
AllowedIPs = 0.0.0.0/0, ::/0
only the connected subnet is behind the tunnel
AllowedIPs = 192.168.XX.0/24

??? is this true ????

Outside Router Setup

Wireguard Port forwarding (Weiterleitung)

Setup differences per device

Device	Hostname	Lan Subnet	Port Wireguard	Clients	XXXXXXX
WDR3600	WDR3600	192.168.36.1/24	36996	Jisoo Jennie Rose Lisa	
WDR4300	WDR4300	192.168.43.1/24	43996	Karina Giselle Winter Ningning	
Fritz 7490			58989	IU	

File: SubStationRouter.odt 6. Sep 2023 21:22

Links

main

https://openwrt.org/docs/guide-user/services/vpn/start

https://openwrt.org/docs/guide-user/services/vpn/wireguard/start

https://openwrt.org/docs/guide-user/services/vpn/wireguard/automated

grcode generation from config file

https://www.wireguardconfig.com/qrcode

other

https://github.com/nyr

https://wiki.securepoint.de/UTM/VPN/%C3%9Cbersicht

https://www.youtube.com/watch?v=FnvP7dOmy9w&t=181s

 $\frac{https://www.apfeltalk.de/community/threads/os-x-ssh-remote-loesungen-unter-osx-dazu-vnc-kvm.35714/$

https://openwrt.org/docs/guide-user/services/vpn/openvpn/client-luci

very other

 $\underline{https://sekurak.pl/more-information-about-tp-link-backdoor/}$

https://sekurak.pl/tp-link-httptftp-backdoor/