

Jumbo Introduction

AUTHOR: BERND HEUFELDER

26. April 2019



Inhaltsverzeichnis

1	Introduction	1
1.1	Keywords	1
1.2	Machine principle	1
2	Maschinenübersicht	1
2.1	Achsenübersicht	1
3	Differences to Standard 8k8	1
4	Sequences	1
4.1	Overview	1
4.2	UltimET	1

1 Introduction

1.1 Keywords

MMF Moving Metrology Frame

1.2 Machine principle

The main purpose of the Jumbo 8k8 is the repetition accuracy. To achieve this, the gantry system is water cooled to keep the system on room temperature. Also higher accelerations and speeds can be achieved with an active water cooling. There are two different movement parameter sets, one with air cooling and one with water cooling.

2 Maschinenübersicht

2.1 Achsenübersicht

3 Differences to Standard 8k8

Emergency stop switch: Usually the emergency stop is connected with the DIN1 of every AccurET-Controller. In a sequence this digital input is monitored to react on an emergency stop. This is applicable for the controllers inside the machine, but most of the controllers are in an nearby rack. On the Jumbo 8k8, the external rack handles the emergency stop separately.

4 Sequences

After booting the controller, the function `autostart()` will automatically be executed. This is applicable for AccurET controllers as well as the UltimET's.

4.1 Overview

- UltimET
 - Thread 1: mainRoutine
 - Thread 2: errorHandling
 - Thread 3: ??

4.2 UltimET

The `autostart()` function starts the `mainRoutine()` on Thread 1 and the `errorRoutine()` on Thread 2. The `initerrorHandling()` calls the `func112()` and executes it in thread 2 because *K142:2=112.

mainRoutine()