

KeyHolders Endpoint – Response Schema

```
{ // response envelope
  "rc": <integer>, // e.g. 200
  "rm": "<string>", // response message
  "src": "<string>", // source identifier

  // ■■ result ■■
  "result": {
    "count": <integer>, // total matching records
    "limit": <integer>, // page size
    "offset": <integer>, // pagination offset

    // ■■ list items ■■
    "list": [ // array of keyholder objects
      { // keyholder entry
        // ■■ identity ■■
        "userId": "<string>",
        "userName": "<string>", // optional
        "firstName": "<string>",
        "lastName": "<string>",
        "employeeId": "<string>", // optional
        "email": "<string>", // optional

        // ■■ contact ■■
        "cellNo": "<string>", // optional
        "workNo": "<string>", // optional

        // ■■ status & access ■■
        "isActive": <boolean>,
        "lastLogin": "<string>", // optional
        "groupId": <integer>,
        "hasKeys": <boolean>,
        "isOwner": <boolean>,
        "autoApprovable": <boolean>,
        "objHolderActive": <boolean>,
        "unsafeApCount": <integer>,
        "accessObjects": [ ... ], // list
        "userAppRoles": [ ... ], // list

        // ■■ domains ■■
        "domains": [ // array, may be empty
          {
            "domainId": <integer>,
            "name": "<string>",
            "parentId": "<string>", // optional
            "inLockDown": <boolean>
          } // ... more domains
        ],

        // ■■ tags ■■
        "tags": [ // array, may be empty
          {
            "tagId": <integer>,
            "name": "<string>",
            "description": "<string>",
            "colour": <integer>
          } // ... more tags
        ]
      } // ... more entries
    ]
  }
}
```

"key"	"string"	<integer>	<boolean>	[...]	// optional	// comment
field name	string type	integer type	boolean type	array type	optional field	annotation