



Candidate Report: training9NDQTC-UCH


[Check out Codility training tasks](#)

Test Name:

Summary Timeline

Tasks summary

Task	Time spent	Score
PassingCars C	26 min	90%



Tasks Details

Easy	1. PassingCars	Task Score	Correctness	Performance
	Count the number of passing cars on the road.			
		90%	100%	80%

Task description

A non-empty array A consisting of N integers is given. The consecutive elements of array A represent consecutive cars on a road.

Array A contains only 0s and/or 1s:



- 0 represents a car traveling east,
- 1 represents a car traveling west.

The goal is to count passing cars. We say that a pair of cars (P, Q), where $0 \leq P < Q < N$, is passing when P is traveling to the east and Q is traveling to the west.

For example, consider array A such that:

```
A[0] = 0
A[1] = 1
A[2] = 0
```

Solution

Programming language used:	C	
Total time used:	26 minutes	
Effective time used:	26 minutes	
Notes:	<i>not defined yet</i>	

Task timeline



A[3] = 1
A[4] = 1

We have five pairs of passing cars: (0, 1), (0, 3), (0, 4), (2, 3), (2, 4).

Write a function:

```
int solution(int A[], int N);
```

that, given a non-empty array A of N integers, returns the number of pairs of passing cars.

The function should return -1 if the number of pairs of passing cars exceeds 1,000,000,000.

For example, given:

A[0] = 0
A[1] = 1
A[2] = 0
A[3] = 1
A[4] = 1

the function should return 5, as explained above.

Write an **efficient** algorithm for the following assumptions:

- N is an integer within the range [1..100,000];
- each element of array A is an integer that can have one of the following values: 0, 1.

Copyright 2009–2020 by Codility Limited. All Rights Reserved. Unauthorized copying, publication or disclosure prohibited.

Code: 10:11:21 UTC, c, final,
score: 90

[show code in pop-up](#)

```
1 // you can write to stdout for debugging purposes, e
2 // printf("this is a debug message\n");
3 int *prefix_sums(int *A, int N){
4     int *P = (int *)malloc((N+1)*sizeof(int));
5     P[0] = 0;
6     for (int i = 1; i<(N+1); i++){
7         P[i] = P[i-1] + A[i-1];
8         //printf("%d ", P[i]);
9     }
10    return P;
11 }
12
13 int solution(int A[], int N) {
14     // write your code in C99 (gcc 6.2.0)
15     int ret = 0;
16     int *P = prefix_sums(A,N);
17
18     for (int i = 0; i<N; i++){
19         if (!A[i]) {
20             ret += P[N]-P[i];
21             //printf("[%d i%d]", P[N], i);
22         }
23     }
24
25     free(P);
26     return ret<=1000000000? ret:-1;
27 }
```

Analysis summary

The following issues have been detected: wrong answers.

Analysis ?

Detected time complexity: **O(N)**

expand all	Example tests
▶ example example test	✓ OK
expand all	Correctness tests
▶ single single element	✓ OK
▶ double two elements	✓ OK
▶ simple simple test	✓ OK
▶ small_random random, length = 100	✓ OK

▶	small_random2	✓ OK
	random, length = 1000	
expand all		Performance tests
▶	medium_random	✓ OK
	random, length = ~10,000	
▶	large_random	✓ OK
	random, length = ~100,000	
▼	large_big_answer	✗ WRONG ANSWER
	0..01..1, length = ~100,000	got -1794967296 expected -1
1. 0.004 s WRONG ANSWER, got -1794967296 expected -1		
2. 0.001 s OK		
▶	large_alternate	✓ OK
	0101..01, length = ~100,000	
▶	large_extreme	✓ OK
	large test with all 1s/0s, length = ~100,000	

The PDF version of this report that may be downloaded on top of this site may contain sensitive data including personal information. For security purposes, we recommend you remove it from your system once reviewed.