



Candidate Report: trainingK6GP9H-QUJ

[Check out Codility training tasks](#)

Test Name:

Summary Timeline

Tasks summary

Task	Time spent	Score
PassingCars Python	29 min	100%

Total score

100%

Tasks Details

Easy	1. PassingCars Count the number of passing cars on the road.	Task Score	Correctness	Performance
		100%	100%	100%

Task description

A non-empty array A consisting of N integers is given. The consecutive elements of array A represent consecutive cars on a road.

Array A contains only 0s and/or 1s:

- 0 represents a car traveling east,
- 1 represents a car traveling west.

The goal is to count passing cars. We say that a pair of cars (P, Q), where $0 \leq P < Q < N$, is passing when P is traveling to the east and Q is traveling to the west.

For example, consider array A such that:

```
A[0] = 0
A[1] = 1
A[2] = 0
```

Solution

Programming language used:	Python	
Total time used:	29 minutes	?
Effective time used:	29 minutes	?
Notes:	not defined yet	

Task timeline



A[3] = 1

A[4] = 1

We have five pairs of passing cars: (0, 1), (0, 3), (0, 4), (2, 3), (2, 4).

Write a function:

```
def solution(A)
```

that, given a non-empty array A of N integers, returns the number of pairs of passing cars.

The function should return -1 if the number of pairs of passing cars exceeds 1,000,000,000.

For example, given:

A[0] = 0

A[1] = 1

A[2] = 0

A[3] = 1

A[4] = 1

the function should return 5, as explained above.

Write an **efficient** algorithm for the following assumptions:

- N is an integer within the range [1..100,000];
- each element of array A is an integer that can have one of the following values: 0, 1.

Copyright 2009–2020 by Codility Limited. All Rights Reserved. Unauthorized copying, publication or disclosure prohibited.

Code: 03:07:43 UTC, py, final,
score: 100

[show code in pop-up](#)

```
1 # you can write to stdout for debugging purposes, e.
2 # print("this is a debug message")
3
4 def prefix_sums(A):
5     P = [0]
6     for i in range(len(A)):
7         P += [P[i] + A[i]]
8     return P
9
10 def solution(A):
11     # write your code in Python 3.6
12     ret = 0
13     PreSum = prefix_sums(A)
14     TotalSum = PreSum[len(A)]
15     for i in range(len(A)):
16         if 0 == A[i]:
17             ret += TotalSum - PreSum[i]
18         if ret > 1000000000:
19             return -1
20     return ret
```

Analysis summary

The solution obtained perfect score.

Analysis ?

Detected time complexity: **O(N)**

collapse all		Example tests
▼	example example test	✓ OK
1. 0.036 s OK		
collapse all		Correctness tests
▼	single single element	✓ OK
1. 0.036 s OK		
2. 0.036 s OK		
▼	double two elements	✓ OK
1. 0.036 s OK		
2. 0.036 s OK		
3. 0.036 s OK		

4.	0.044 s	OK	
▼	simple	✓ OK	
	simple test		
1.	0.036 s	OK	
▼	small_random	✓ OK	
	random, length = 100		
1.	0.036 s	OK	
▼	small_random2	✓ OK	
	random, length = 1000		
1.	0.036 s	OK	
collapse all		Performance tests	
▼	medium_random	✓ OK	
	random, length = ~10,000		
1.	0.048 s	OK	
▼	large_random	✓ OK	
	random, length = ~100,000		
1.	0.148 s	OK	
▼	large_big_answer	✓ OK	
	0..01..1, length = ~100,000		
1.	0.156 s	OK	
2.	0.120 s	OK	
▼	large_alterate	✓ OK	
	0101..01, length = ~100,000		
1.	0.156 s	OK	
2.	0.144 s	OK	
▼	large_extreme	✓ OK	
	large test with all 1s/0s, length = ~100,000		
1.	0.168 s	OK	
2.	0.156 s	OK	
3.	0.164 s	OK	

The PDF version of this report that may be downloaded on top of this site may contain sensitive data including personal information. For security purposes, we recommend you remove it from your system once reviewed.