

# Combining Datasets: merge and join

One important feature offered by Pandas is its **high-performance, in-memory join and merge operations**,

which you may be familiar with **if you have ever worked with databases**.

**The main interface** for this is the `pd.merge` function,

and **we'll see a few examples** of how this can work in practice.

For convenience, **we will again define the** `display` function from the previous chapter after the usual imports:

```
In [ ]: import pandas as pd
import numpy as np

class display(object):
```

```

"""Display HTML representation of multiple objects"""
template = """<div style="float: left; padding: 10px;">
<p style='font-family:"Courier New", Courier, monospace'>
</div>"""

def __init__(self, *args):
    self.args = args

def _repr_html_(self):
    return '\n'.join(self.template.format(a, eval(a)._repr_html_())
                      for a in self.args)

def __repr__(self):
    return '\n\n'.join(a + '\n' + repr(eval(a))
                       for a in self.args)

```

## Relational Algebra

The behavior implemented in `pd.merge` is **a subset of what is known as relational algebra**,

which is a **formal set of rules for manipulating relational data** that forms the conceptual foundation of operations available in most databases.

The **strength of the relational algebra approach** is that it **proposes several fundamental operations,**

which become the **building blocks of more complicated operations on any dataset.**

With this lexicon of fundamental operations implemented efficiently in a database or other program, a **wide range of fairly complicated composite operations can be performed.**

**Pandas implements several of these fundamental building blocks** in the `pd.merge` function and the related `join` method of `Series` and `DataFrame` objects.

As you will see, these **let you efficiently link data from different sources.**

# Categories of Joins

The `pd.merge` function **implements a number of types of joins**: *one-to-one*, *many-to-one*, and *many-to-many*.

All **three types of joins** are accessed via an identical call to the `pd.merge` interface;

the **type of join performed depends on the form of the input data**.

We'll start with **some simple examples of the three types of merges**, and discuss detailed options a bit later.

## One-to-One Joins

Perhaps the **simplest type of merge is the one-to-one join**, which is in many ways similar to the column-wise concatenation.

**As a concrete example,** consider the following two `DataFrame` objects, which contain information on several employees in a company:

```
In [ ]: df1 = pd.DataFrame({'employee': ['Bob', 'Jake', 'Lisa', 'Sue'],
                             'group': ['Accounting', 'Engineering',
                                       'Engineering', 'HR']})
df2 = pd.DataFrame({'employee': ['Lisa', 'Bob', 'Jake', 'Sue'],
                     'hire_date': [2004, 2008, 2012, 2014]})
display('df1', 'df2')
```

Out[ ]: df1 df2

	employee	group		employee	hire_date
0	Bob	Accounting	0	Lisa	2004
1	Jake	Engineering	1	Bob	2008
2	Lisa	Engineering	2	Jake	2012
3	Sue	HR	3	Sue	2014

**To combine this information into a single DataFrame**, we can use the `pd.merge` function:

```
In [ ]: df3 = pd.merge(df1, df2)
df3
```

```
Out[ ]:
```

	<b>employee</b>	<b>group</b>	<b>hire_date</b>
<b>0</b>	Bob	Accounting	2008
<b>1</b>	Jake	Engineering	2012
<b>2</b>	Lisa	Engineering	2004
<b>3</b>	Sue	HR	2014

The `pd.merge` function **recognizes** that each `DataFrame` has an `employee` column,

and **automatically joins using this column as a key.**

The result of the merge is a new `DataFrame` that **combines the information from the two inputs.**

Notice that **the order of entries in each column is not necessarily maintained**: in this case,

the order of the `employee` column differs between `df1` and `df2`, and the `pd.merge` **function correctly accounts for this**.

Additionally, keep in mind that the **merge in general discards the index**, except in the special case of merges by index (see the `left_index` and `right_index` keywords, discussed momentarily).

## Many-to-One Joins

**Many-to-one joins** are joins in which one of the two key columns contains duplicate entries.

For the many-to-one case, the resulting `DataFrame` will **preserve those duplicate entries as appropriate**.



Consider the **following example** of a many-to-one join:

```
In [ ]: df4 = pd.DataFrame({'group': ['Accounting', 'Engineering', 'H'],  
                           'supervisor': ['Carly', 'Guido', 'Steve']})  
display('df3', 'df4', 'pd.merge(df3, df4)')
```

Out[ ]: df3

	employee	group	hire_date
0	Bob	Accounting	2008
1	Jake	Engineering	2012
2	Lisa	Engineering	2004
3	Sue	HR	2014

df4

	group	supervisor
0	Accounting	Carly
1	Engineering	Guido
2	HR	Steve

```
pd.merge(df3, df4)
```

	employee	group	hire_date	supervisor
0	Bob	Accounting	2008	Carly
1	Jake	Engineering	2012	Guido
2	Lisa	Engineering	2004	Guido
3	Sue	HR	2014	Steve

The resulting DataFrame has **an additional column** with the "supervisor" information,

where the **information is repeated in one or more locations** as required by the inputs.

# Many-to-Many Joins

**Many-to-many joins may be a bit confusing conceptually,** but are nevertheless well defined.

If the **key column in both the left and right arrays contains duplicates,**

then the **result is a many-to-many merge.**

This will be perhaps **most clear with a concrete example.**

Consider the following, where we have a `DataFrame` showing **one or more skills associated with a particular group.**

**By performing a many-to-many join,** we can recover the skills associated with any individual person:

```
In [ ]: df5 = pd.DataFrame({'group': ['Accounting', 'Accounting',  
                                     'Engineering', 'Engineering',  
                                     'skills': ['math', 'spreadsheets', 'softw  
                                                'spreadsheets', 'organization'  
display('df1', 'df5', "pd.merge(df1, df5)")
```

Out[ ]: df1

	employee	group
0	Bob	Accounting
1	Jake	Engineering
2	Lisa	Engineering
3	Sue	HR

df5

	group	skills
0	Accounting	math
1	Accounting	spreadsheets
2	Engineering	software
3	Engineering	math
4	HR	spreadsheets
5	HR	organization

```
pd.merge(df1, df5)
```

	employee	group	skills
0	Bob	Accounting	math

	employee	group	skills
1	Bob	Accounting	spreadsheets
2	Jake	Engineering	software
3	Jake	Engineering	math
4	Lisa	Engineering	software
5	Lisa	Engineering	math
6	Sue	HR	spreadsheets
7	Sue	HR	organization

These three types of joins **can be used with other Pandas tools** to implement a wide array of functionality.

But in practice, **datasets are rarely as clean** as the one we're working with here.

In the following section we'll consider some of the options provided by `pd.merge` that **enable you to tune how the join operations work.**

## Specification of the Merge Key

We've already seen **the default behavior** of `pd.merge` :

**it looks for one or more matching column** names between the two inputs, and uses this as the key.

However, **often the column names will not match so nicely,**

and `pd.merge` provides **a variety of options for handling this.**



# The on Keyword

Most simply, **you can explicitly specify the name of the key column** using the `on` keyword,

which takes a column name or a list of column names:

```
In [ ]: display('df1', 'df2', "pd.merge(df1, df2, on='employee')")
```

Out[ ]:      df1                      df2

df1			df2		
	employee	group		employee	hire_date
0	Bob	Accounting	0	Lisa	2004
1	Jake	Engineering	1	Bob	2008
2	Lisa	Engineering	2	Jake	2012
3	Sue	HR	3	Sue	2014

```
pd.merge(df1, df2, on='employee')
```

	employee	group	hire_date
0	Bob	Accounting	2008
1	Jake	Engineering	2012
2	Lisa	Engineering	2004

	employee	group	hire_date
3	Sue	HR	2014

**This option works only if both the left and right** DataFrame s have the specified column name.

## The left\_on and right\_on Keywords

At times you may **wish to merge two datasets with different column names;**

**for example,** we may have a dataset in which the employee name is labeled as "name" rather than "employee".

In this case, **we can use** the left\_on and right\_on keywords to specify the two column names:

```
In [ ]: df3 = pd.DataFrame({'name': ['Bob', 'Jake', 'Lisa', 'Sue'],  
                           'salary': [70000, 80000, 120000, 90000]})  
display('df1', 'df3', 'pd.merge(df1, df3, left_on="employee",
```

Out[ ]: df1 df3

df1			df3		
	employee	group		name	salary
0	Bob	Accounting	0	Bob	70000
1	Jake	Engineering	1	Jake	80000
2	Lisa	Engineering	2	Lisa	120000
3	Sue	HR	3	Sue	90000

```
pd.merge(df1, df3, left_on="employee",
right_on="name")
```

	employee	group	name	salary
0	Bob	Accounting	Bob	70000
1	Jake	Engineering	Jake	80000
2	Lisa	Engineering	Lisa	120000

	employee	group	name	salary
3	Sue	HR	Sue	90000

**The result has a redundant column that we can drop** if desired —for example, by using the `DataFrame.drop()` method:

```
In [ ]: pd.merge(df1, df3, left_on="employee", right_on="name").drop()
```

Out[ ]:

	employee	group	salary
0	Bob	Accounting	70000
1	Jake	Engineering	80000
2	Lisa	Engineering	120000
3	Sue	HR	90000

# The left\_index and right\_index Keywords

Sometimes, rather than merging on a column, you would **instead like to merge on an index**.

**For example**, your data might look like this:

```
In [ ]: df1a = df1.set_index('employee')  
df2a = df2.set_index('employee')  
display('df1a', 'df2a')
```

Out[ ]: df1a df2a

group		hire_date	
employee		employee	
Bob	Accounting	Lisa	2004
Jake	Engineering	Bob	2008
Lisa	Engineering	Jake	2012
Sue	HR	Sue	2014

You can **use the index as the key for merging by specifying** the `left_index` and/or `right_index` flags in `pd.merge()` :

```
In [ ]: display('df1a', 'df2a',  
               "pd.merge(df1a, df2a, left_index=True, right_index=Tr
```



Out[ ]: df1a df2a

group		hire_date	
employee		employee	
Bob	Accounting	Lisa	2004
Jake	Engineering	Bob	2008
Lisa	Engineering	Jake	2012
Sue	HR	Sue	2014

```
pd.merge(df1a, df2a, left_index=True,
right_index=True)
```

group		hire_date
employee		
Bob	Accounting	2008

		group	hire_date
employee			
Jake	Engineering		2012
Lisa	Engineering		2004
Sue	HR		2014

For convenience, Pandas includes the `DataFrame.join()` method, which **performs an index-based merge without extra keywords**:

```
In [ ]: df1a.join(df2a)
```

Out[ ]:

group hire_date		
employee		
Bob	Accounting	2008
Jake	Engineering	2012
Lisa	Engineering	2004
Sue	HR	2014

If you'd like to **mix indices and columns**,

**you can combine** `left_index` with `right_on` or `left_on` with `right_index` to get the desired behavior:

```
In [ ]: display('df1a', 'df3', "pd.merge(df1a, df3, left_index=True,
```

Out[ ]: df1a df3

group		name	salary
employee			
		0	Bob 70000
Bob	Accounting	1	Jake 80000
Jake	Engineering	2	Lisa 120000
Lisa	Engineering	3	Sue 90000
Sue	HR		

```
pd.merge(df1a, df3, left_index=True,
right_on='name')
```

	group	name	salary
0	Accounting	Bob	70000
1	Engineering	Jake	80000

	<b>group</b>	<b>name</b>	<b>salary</b>
<b>2</b>	Engineering	Lisa	120000
<b>3</b>	HR	Sue	90000

All of these options also work with **multiple indices and/or multiple columns**;

## Specifying Set Arithmetic for Joins

In all the preceding examples we have **glossed over one important consideration in performing a join**:

**the type of set arithmetic** used in the join.

This comes up **when a value appears in one key column but not the other**.

Consider this **example**:

```
In [ ]: df6 = pd.DataFrame({'name': ['Peter', 'Paul', 'Mary'],  
                           'food': ['fish', 'beans', 'bread']},  
                           columns=['name', 'food'])  
df7 = pd.DataFrame({'name': ['Mary', 'Joseph'],  
                   'drink': ['wine', 'beer']},  
                   columns=['name', 'drink'])  
display('df6', 'df7', 'pd.merge(df6, df7)')
```

Out[ ]:

df6

	<b>name</b>	<b>food</b>
<b>0</b>	Peter	fish
<b>1</b>	Paul	beans
<b>2</b>	Mary	bread

df7

	<b>name</b>	<b>drink</b>
<b>0</b>	Mary	wine
<b>1</b>	Joseph	beer

```
pd.merge(df6, df7)
```

	<b>name</b>	<b>food</b>	<b>drink</b>
<b>0</b>	Mary	bread	wine

Here we have merged two datasets that have only a single "name" entry in common: Mary.

**By default**, the result contains the *intersection* of the two sets of inputs;

this is what is known as an *inner join*.

**We can specify this explicitly** using the `how` keyword, which defaults to `"inner"` :

```
In [ ]: pd.merge(df6, df7, how='inner')
```

```
Out[ ]:   name  food  drink
0  Mary  bread  wine
```

**Other options** for the `how` keyword are `'outer'`, `'left'`, and `'right'` .

An *outer join* **returns a join over the union of the input columns**, and fills in all missing values with NAs:



```
In [ ]: display('df6', 'df7', "pd.merge(df6, df7, how='outer')")
```

Out[ ]: df6

	<b>name</b>	<b>food</b>
<b>0</b>	Peter	fish
<b>1</b>	Paul	beans
<b>2</b>	Mary	bread

df7

	<b>name</b>	<b>drink</b>
<b>0</b>	Mary	wine
<b>1</b>	Joseph	beer

```
pd.merge(df6, df7, how='outer')
```

	<b>name</b>	<b>food</b>	<b>drink</b>
<b>0</b>	Peter	fish	NaN
<b>1</b>	Paul	beans	NaN
<b>2</b>	Mary	bread	wine
<b>3</b>	Joseph	NaN	beer

The *left join* and *right join* return **joins over the left entries and right entries**, respectively.

**For example:**

```
In [ ]: display('df6', 'df7', "pd.merge(df6, df7, how='left')")
```

Out[ ]: df6

	<b>name</b>	<b>food</b>
<b>0</b>	Peter	fish
<b>1</b>	Paul	beans
<b>2</b>	Mary	bread

df7

	<b>name</b>	<b>drink</b>
<b>0</b>	Mary	wine
<b>1</b>	Joseph	beer

```
pd.merge(df6, df7, how='left')
```

	<b>name</b>	<b>food</b>	<b>drink</b>
<b>0</b>	Peter	fish	NaN
<b>1</b>	Paul	beans	NaN
<b>2</b>	Mary	bread	wine

The output **rows now correspond to the entries in the left input.**

Using `how='right'` works in a similar manner.

All of these options can be **applied straightforwardly to any of the preceding join types.**

## Overlapping Column Names: The suffixes Keyword

Last, you may end up in a case where your two input DataFrame s **have conflicting column names.**

Consider this **example**:

```
In [ ]: df8 = pd.DataFrame({'name': ['Bob', 'Jake', 'Lisa', 'Sue'],  
                             'rank': [1, 2, 3, 4]})  
df9 = pd.DataFrame({'name': ['Bob', 'Jake', 'Lisa', 'Sue'],  
                     'rank': [3, 1, 4, 2]})  
display('df8', 'df9', 'pd.merge(df8, df9, on="name")')
```

```
Out[ ]: df8          df9
```

	name	rank		name	rank
0	Bob	1	0	Bob	3
1	Jake	2	1	Jake	1
2	Lisa	3	2	Lisa	4
3	Sue	4	3	Sue	2

```
pd.merge(df8, df9, on="name")
```

	name	rank_x	rank_y
0	Bob	1	3
1	Jake	2	1
2	Lisa	3	4

	name	rank_x	rank_y
3	Sue	4	2

Because the output would have **two conflicting column names**, the `merge` function **automatically appends the suffixes** `_x` and `_y` to make the output columns unique.

If these defaults are inappropriate, it is **possible to specify a custom suffix** using the `suffixes` keyword:

```
In [ ]: pd.merge(df8, df9, on="name", suffixes=["_L", "_R"])
```



Out[ ]:

	name	rank_L	rank_R
0	Bob	1	3
1	Jake	2	1
2	Lisa	3	4
3	Sue	4	2

These suffixes **work in any of the possible join patterns**, and also **work if there are multiple overlapping columns**.

## Example: US States Data

Merge and join operations come up most often when **combining data from different sources**.

Here we will consider an **example** of some data about US states and their populations.

```
In [ ]: # Following are commands to download the data
# repo = "https://raw.githubusercontent.com/jakevdp/data-USst
# !cd data && curl -O {repo}/state-population.csv
# !cd data && curl -O {repo}/state-areas.csv
# !cd data && curl -O {repo}/state-abbrevs.csv
```

Let's take a look at the three datasets, using the Pandas  
`read_csv` function:

```
In [ ]: pop = pd.read_csv('data/state-population.csv')
areas = pd.read_csv('data/state-areas.csv')
abbrevs = pd.read_csv('data/state-abbrevs.csv')

display('pop.head()', 'areas.head()', 'abbrevs.head()')
```

```
Out[ ]: pop.head()
```

	state/region	ages	year	population
0	AL	under18	2012	1117489.0
1	AL	total	2012	4817528.0
2	AL	under18	2010	1130966.0
3	AL	total	2010	4785570.0
4	AL	under18	2011	1125763.0

```
areas.head()
```

	state	area (sq. mi)
0	Alabama	52423
1	Alaska	656425

```
abbrevs.head()
```

	state	abbreviation
0	Alabama	AL
1	Alaska	AK

	state	area (sq. mi)		state	abbreviation
2	Arizona	114006	2	Arizona	AZ
3	Arkansas	53182	3	Arkansas	AR
4	California	163707	4	California	CA

Given this information, say we want to **compute a relatively straightforward result**:

rank US states and territories by their 2010 population density.

We clearly have the data here to find this result, but **we'll have to combine the datasets to do so**.

We'll **start with a many-to-one merge** that will give us the full state names within the population `DataFrame` .

We want to **merge based** on the `state/region` column of `pop` and the `abbreviation` column of `abbrevs` .

We'll use `how='outer'` to **make sure no data is thrown away due to mismatched labels:**

```
In [ ]: merged = pd.merge(pop, abbrevs, how='outer',  
                           left_on='state/region', right_on='abbreviat  
merged = merged.drop('abbreviation', axis=1) # drop duplicate  
merged.head()
```

```
Out[ ]:
```

	state/region	ages	year	population	state
0	AL	under18	2012	1117489.0	Alabama
1	AL	total	2012	4817528.0	Alabama
2	AL	under18	2010	1130966.0	Alabama
3	AL	total	2010	4785570.0	Alabama
4	AL	under18	2011	1125763.0	Alabama

Let's **double-check whether there were any mismatches here**, which we can do by looking for rows with nulls:

```
In [ ]: merged.isnull().any()
```

```
Out[ ]: state/region    False  
ages                 False  
year                 False  
population            True  
state                 True  
dtype: bool
```

Some of the `population` values are null;

let's figure out which these are!

```
In [ ]: merged[merged['population'].isnull()].head()
```

Out[ ]:

	state/region	ages	year	population	state
2448	PR	under18	1990	NaN	NaN
2449	PR	total	1990	NaN	NaN
2450	PR	total	1991	NaN	NaN
2451	PR	under18	1991	NaN	NaN
2452	PR	total	1993	NaN	NaN

It appears that **all the null population values are from Puerto Rico prior to the year 2000;**

this is likely due to this **data not being available in the original source.**

More importantly, we see that some of the new `state` **entries are also null**,

which means that **there was no corresponding entry** in the `abbrevs` key!

Let's figure out which regions lack this match:

```
In [ ]: merged.loc[merged['state'].isnull(), 'state/region'].unique()
```

```
Out[ ]: array(['PR', 'USA'], dtype=object)
```

We can quickly infer the issue:

our population data includes entries for Puerto Rico (PR) and the United States as a whole (USA), **while these entries do not appear in the state abbreviation key.**

**We can fix these** quickly by filling in appropriate entries:



```
In [ ]: merged.loc[merged['state/region'] == 'PR', 'state'] = 'Puerto Rico'
merged.loc[merged['state/region'] == 'USA', 'state'] = 'United States'
merged.isnull().any()
```

```
Out[ ]: state/region    False
ages                 False
year                 False
population            True
state                 False
dtype: bool
```

**No more nulls** in the `state` column: we're all set!

**Now we can merge the result** with the area data using a similar procedure.

Examining our results, we will want to join on the `state` column in both:

```
In [ ]: final = pd.merge(merged, areas, on='state', how='left')
final.head()
```

Out[ ]:

	state/region	ages	year	population	state	area (sq. mi)
0	AL	under18	2012	1117489.0	Alabama	52423.0
1	AL	total	2012	4817528.0	Alabama	52423.0
2	AL	under18	2010	1130966.0	Alabama	52423.0
3	AL	total	2010	4785570.0	Alabama	52423.0
4	AL	under18	2011	1125763.0	Alabama	52423.0

Again, let's check for nulls to see **if there were any mismatches**:

In [ ]: `final.isnull().any()`

```
Out[ ]: state/region      False
        ages             False
        year             False
        population       True
        state            False
        area (sq. mi)    True
        dtype: bool
```

There are nulls in the `area` column;

we can take a look to see which regions were ignored here:

```
In [ ]: final['state'][final['area (sq. mi)'].isnull()].unique()
```

```
Out[ ]: array(['United States'], dtype=object)
```

We see that our `areas` `DataFrame` **does not contain the area of the United States as a whole.**

We could **insert the appropriate value** (using the sum of all state areas, for instance),

but in this case **we'll just drop the null values**

because the **population density of the entire United States is not relevant** to our current discussion:

```
In [ ]: final.dropna(inplace=True)
        final.head()
```

Out[ ]:

	state/region	ages	year	population	state	area (sq. mi)
0	AL	under18	2012	1117489.0	Alabama	52423.0
1	AL	total	2012	4817528.0	Alabama	52423.0
2	AL	under18	2010	1130966.0	Alabama	52423.0
3	AL	total	2010	4785570.0	Alabama	52423.0
4	AL	under18	2011	1125763.0	Alabama	52423.0

Now we have all the data we need.

To answer the question of interest, let's first **select the portion of the data corresponding** with the year 2010, and the total population.

We'll use the `query` function to do this quickly:

```
In [ ]: data2010 = final.query("year == 2010 & ages == 'total'")
data2010.head()
```

```
Out[ ]:
```

	state/region	ages	year	population	state	area (sq. mi)
<b>3</b>	AL	total	2010	4785570.0	Alabama	52423.0
<b>91</b>	AK	total	2010	713868.0	Alaska	656425.0
<b>101</b>	AZ	total	2010	6408790.0	Arizona	114006.0
<b>189</b>	AR	total	2010	2922280.0	Arkansas	53182.0
<b>197</b>	CA	total	2010	37333601.0	California	163707.0

Now let's **compute the population density** and display it in order.

**We'll start by re-indexing** our data on the state, and then compute the result:

```
In [ ]: data2010.set_index('state', inplace=True)
density = data2010['population'] / data2010['area (sq. mi)']
```

```
In [ ]: density.sort_values(ascending=False, inplace=True)
density.head()
```

```
Out[ ]: state
District of Columbia    8898.897059
Puerto Rico            1058.665149
New Jersey              1009.253268
Rhode Island            681.339159
Connecticut             645.600649
dtype: float64
```

The result is a ranking of US states, plus Washington, DC, and Puerto Rico, in order of their 2010 population density, in residents per square mile.

We can see that by far the densest region in this dataset is Washington, DC (i.e., the District of Columbia); among states, the densest is New Jersey.

We can also check the end of the list:

```
In [ ]: density.tail()
```

```
Out[ ]: state
        South Dakota    10.583512
        North Dakota     9.537565
        Montana          6.736171
        Wyoming           5.768079
        Alaska            1.087509
        dtype: float64
```

We see that the least dense state, by far, is Alaska, averaging slightly over one resident per square mile.

This type of data merging is a **common task when trying to answer questions using real-world data sources.**