

Introduction

Bert van der Veen


Department of Mathematical Sciences, NTNU

Welcome! 😄



What I hope you take away

1. The gllvm R-package is great!
2. Performing ordination well is hard work
3. Model-based ordination methods do many things better (data properties, diagnostics)
4. One framework for all ordination tools



Detailed outline today

- ▶ Generalised linear model (GLM) recap
- ▶ Practical: `glm` and `mvabund::manyglm`
- ▶ Generalised linear mixed model (GLMM) recap
- ▶ Practical: `glmmTMB`
- ▶ Recap classical ordination methods and concepts

15 minute break 15:45-16:00
 45 minute break 17:45-18:30

Some resources on classical ordination

- ▶ David Zeneley's website
- ▶ Michael Palmer's website
- ▶ Numerical ecology
- ▶ Numerical ecology with R
- ▶ Data analysis in Community and Landscape ecology
- ▶ Analysis of ecological communities

Resources on model-based ordination

- ▶ Some of my other workshop repositories
- ▶ gllvm vignette website
- ▶ Oxford libraries article
- ▶ Warton 2022
- ▶ Fahrmeir and Tutz 2001
- ▶ Ovaskainen and Abrego
- ▶ Bartholomew et al. 2011
- ▶ Skrandal and Rabe-Hesketh 2004

Some recommended reading

- ▶ Halvorsen (2012)
- ▶ Wang et al. (2012)
- ▶ Warton et al. (2012)
- ▶ Clark et al. (2014)
- ▶ Warton et al. (2015)
- ▶ Warton et al. (2015)
- ▶ Hui et al. (2015)
- ▶ Pollock et al. (2015)
- ▶ ter Braak and Smilauer (2015)
- ▶ Hui et al. (2017)
- ▶ Niku et al. (2017)
- ▶ Ovaskainen et al. (2017)
- ▶ Roberts (2017)
- ▶ Warton et al. (2017)
- ▶ Niku et al. (2019)
- ▶ Niku et al. (2019)
- ▶ Roberts (2019)
- ▶ Paul (2020)
- ▶ Zurell et al. (2020)
- ▶ van der Veen et al. (2021)
- ▶ Blanchet et al. (2022)
- ▶ van der Veen (2022)
- ▶ van der Veen et al. (2023)

Motivation

Plant Ecol (2015) 216:669–682
DOI 10.1007/s11258-014-0366-3

Model-based thinking for community ecology

**David I. Warton · Scott D. Foster ·
Glenn De'ath · Jakub Stoklosa · Piers K. Dunstan**

Figure 1: Warton et al. 2015

Figure 3: JSMD of spider data

Use of ordination

- ▶ One of the most used methods of multivariate analysis
 - ▶ but definitely not the only one
- ▶ Arranges species and samples in a low-dimensional space
 - ▶ or any column and row quantity really
- ▶ Summarizes data
- ▶ Find underlying structures (gradients/LVs)

A brief history of ordination

- ▶ Thoughts from community ecology perspective
- ▶ A long history

And me:



A brief history of ordination

Milestones in Ordination: a timeline

- 1901 - Pearson develops PCA as a regression technique
- 1927 - Spearman applies factor analysis to psychology
- 1930 - Ramensky uses an informal ordination technique and the term "Ordnung" in ecology
- 1933 - Hotelling develops PCA for understanding the correlation matrix
- 1950 - Curtis and McIntosh employ the "continuum index" approach
- 1952 - Williams uses Correspondence Analysis
- 1954 - Goodall uses the term "ordination" for PCA
- 1957 - Bray-Curtis (Polar) ordination
- 1964 - Kruskal develops NMDS
- 1970's - Whittaker develops theoretical foundations of gradient analysis
- 1973 - Hill revives Correspondence Analysis
- 1976 - Canonical Correlation introduced to ecology
- 1977 - Fasham, Prentice use NMDS
- 1979 - DCA introduced by Hill and Gauch
- 1982 - Gauch's "Multivariate Analysis in Community Ecology"
- 1986 - CCA introduced by ter Braak
- 1986 - Fuzzy set ordination introduced by Roberts
- 1988 - ter Braak and Prentice's "Theory of Gradient Analysis"

This page was created and is maintained by [Michael Palmer](#).



[To the ordination web page](#)

Historical Perspective

- 1901 - Pearson develops PCA as a regression technique.
- 1927 - Spearman applies factor analysis to psychology.
- 1930 - Ramensky uses an informal ordination technique and introduces the term 'ordnung' into ecology.
- 1954 - D.W. Goodall introduces PCA into ecology and proposes the term 'ordination'.
- 1970 - R.H. Whittaker develops theoretical foundations of gradient analysis, especially unimodal species responses and turnover along environmental gradients.
- 1971 - K.R. Gabriel develops biplot graphical display.
- 1973 - M.O. Hill re-invents correspondence analysis and introduces CA (as 'reciprocal averaging') into ecology.
- 1986 - Cajo ter Braak invents canonical correspondence analysis (CCA) and released CANOCO software.
- 1988 - Cajo ter Braak and Colin Prentice's "A theory of gradient analysis" (Advances in Ecological Research 18; 271-317) that unifies indirect and direct gradient analysis and highlights the importance of underlying species response models.
- 1998, 2002 - Cajo ter Braak and Petr Šmilauer CANOCO 4 & 4.5 software and manual.

- ▶ Inspired by Michael Palmer's and John Birk's
- ▶ But in need of a little update

In the beginning, there were PCA and FA







Whittaker 1956: Unimodal responses






FIG. 4. Transect of the moisture gradient, 3500-4500 ft. Top—curves for tree classes; a, mesic; b, submesic; c, subxeric; d, xeric. Note expansion of mesic stands, compared with Figs. 2 and 3. Middle—curves for tree species; a, *Tilia heterophylla*; b, *Halesia monticola* (both the preceding are bimodal, with populations on each side of the mode of Tsuga); c, *Tsuga canadensis*; d, *Quercus alba*; e, *Pinus pungens*. Bottom—curves for undergrowth coverages: a, herbs; b, shrubs.







► The unimodal model continued

Unimodal model (2)

Ecology (1974) **55**: pp. 1382–1390

ORDINATION OF VEGETATION SAMPLES BY GAUSSIAN SPECIES DISTRIBUTIONS¹

HUGH G. GAUCH, JR.

Ecology and Systematics, Cornell University, Ithaca, New York 14850

GENE B. CHASE²

Education, Cornell University, Ithaca, New York 14850

AND

ROBERT H. WHITTAKER


Ecology and Systematics, Cornell University, Ithaca, New York 14850

BIOMETRICS 41, 859–873
December 1985

Correspondence Analysis of Incidence and Abundance Data: Properties in Terms of a Unimodal Response Model

Cajo J. F. ter Braak





TNO Institute of Mathematics, Information Processing and Statistics,
P. O. Box 100, 6700 AC Wageningen, The Netherlands




- ▶ The unimodal model
- ▶ Development of CCA

- ▶ Skewed might be more realistic
- ▶ NMDS is “robust”
- ▶ Moving away from process-based

Results Minchin dataset




A theory of gradient analysis




{ "Ter Braak and Prentice (1988) developed a theoretical unification of ordination techniques, hence placing gradient analysis on a firm theoretical foundation" (Michael Palmer) }

I was born

vegan



Updating the ordination timeline



Ditching the machine learning developments

Eigenanalysis-based methods

Timeline model-based ordination

The 3 schools of ordination

- 1) "Simple-method"
- 2) "Algorithm-based" (also called "distance-based")
- 3) "Model-based"

- 2) "Algorithm-based" (also called "distance-based")

- ### 3) "Model-based"

The 3 schools of ordination

- 1) "Simple-method"
- 2) "Algorithm-based"
- 3) "Model-based"

Principal Component Analysis
(Detrended) Correspondence
Analysis

Non-metric multidimensional
scaling

UMAP

t-SNE

Row-column interaction models

Graphical models (copula)

Generalized Linear Latent

Variable Models

Joint Species Distribution Modeling (2)

- ▶ A niche process generates data
- ▶ Distributions are driven by 1) environment and 2) interactions
- ▶ Statistically, interaction = correlation of species
- ▶ So we model that:

$$g\{\mathbb{E}(y_{ij}|\epsilon_i)\} = \beta_{0j} + \mathbf{x}_i^\top \beta_j + \epsilon_{ij}, \quad \epsilon_i \sim \mathcal{N}(0, \Sigma) \quad (1)$$

Can be fit using standard mixed-effects modeling software:

```
glmer(abundance~species+x:species+(0+species|sites))
```

Problem: Number of parameters grows quadratically

“Fun” ecological inference








Figure 5: Warton et al. 2015 Alpine plants

Enter: Generalized Linear Latent Variable Models



- ▶ GLLVM for short
- ▶ Adds “factor analytic” structure to Σ
- ▶ $\epsilon_{ij} = \mathbf{u}_i^\top \boldsymbol{\theta}_j$
 - ▶ i.e. $\boldsymbol{\epsilon}_i \sim \mathcal{N}(0, \boldsymbol{\Theta} \boldsymbol{\Theta}^\top)$
- ▶ Faster and fewer parameters:
 - ▶ Number of parameter doesn't grow so fast

$$\Sigma = \begin{bmatrix} \theta_{11} & 0 & 0 \\ \theta_{12} & \theta_{22} & 0 \\ \vdots & \ddots & \vdots \\ \theta_{1j} & \dots & \theta_{dj} \end{bmatrix} \begin{bmatrix} \theta_{11} & \theta_{12} & \dots & \theta_{1j} \\ 0 & \theta_{22} & \ddots & \vdots \\ 0 & 0 & \dots & \theta_{dj} \end{bmatrix} \quad (2)$$

Recall: Results Minchin dataset



Results Minchin dataset: gllvm



Model-based ordination

- ▶ More flexible & statistically appropriate
- ▶ Now straightforward available
- ▶ Very much in active development
- ▶ Has a steep learning curve & computational difficulties

Allows us to do all kinds of fun things

- ▶ Residual diagnostics
- ▶ Species-specific effects from constrained ordination
- ▶ Random-effects
- ▶ Flexible models
- ▶ Etc.

Towards the end

- ▶ I think model-based ordination is the way
- ▶ Developments are very active and we need researchers to push the frontier
 - ▶ ask new questions
 - ▶ show that existing methods are insufficient
 - ▶ apply new advances
 - ▶ update the course material
- ▶ Computation is again an active topic.
- ▶ Learning curve can be/is steep
 - ▶ ordination should now be taught differently. The model-based angle

Ordination is **so much more** than “a descriptive method”
It is a framework for complex (reduced rank) multivariate
statistical modeling

